



(51) International Patent Classification:
H01L 21/02 (2006.01)

(21) International Application Number:
PCT/US2010/037922

(22) International Filing Date:
9 June 2010 (09.06.2010)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
61/185,829 10 June 2009 (10.06.2009) US
61/303,460 11 February 2010 (11.02.2010) US

(71) Applicant (for all designated States except US): **VIS-TADELTEK, LLC** [US/US]; 5605 Vista Del Mar, Yorba Linda, CA 92887 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **VU, Kim, Ngoc** [US/US]; 5605 Vista Del Mar, Yorba Linda, CA 92887 (US).

(74) Agent: **SKRIVANEK, Robert, A., Jr.**; Lando & Anastasi LLP, One Main Street, Eleventh Floor, Cambridge, MA 02142 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,

HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))
- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))

Published:

- with international search report (Art. 21(3))
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))

[Continued on next page]

(54) Title: **EXTREME FLOW RATE AND/OR HIGH TEMPERATURE FLUID DELIVERY SUBSTRATES**




FIG. 1J

(57) Abstract: A flow substrate including a body having a first surface and a second opposing surface, a plurality of pairs of ports defined in the first surface of the body, a plurality of fluid pathways extending between each respective pair of ports and in fluid communication with each port of the respective pair of ports, and at least one cap. Each fluid pathway is formed in the second surface of the body. The at least one cap has a first surface constructed to seal at least one fluid pathway, and a second opposing surface. At least one of the body and the at least one cap includes a weld formation formed in at least one of the second surface of the body and the second surface of the at least one cap constructed to surround the at least one fluid pathway and facilitate welding of the at least one cap to the body along the weld formation.



(88) Date of publication of the international search report:

3 March 2011