

CLAIMS

What is claimed is:

1. A cyclonic coalescer for enhancing separation of a denser phase liquid from a lighter phase liquid within a multiphase stream, the coalescer comprising:
 - a tubular housing;
 - a plurality of coaxial flow chambers extending in the axial direction of the housing;
 - and
 - a swirling element associated with each of the plurality of coaxial flow chambers, the swirling elements are constructed and arranged to impart a tangential velocity of the stream flowing through the associated flow chamber.
2. The coalescer of claim 1, wherein the housing has a first length and the swirl elements extend a second length within the housing.
3. The coalescer of claim 2, wherein the first length is greater than the second length.
4. The coalescer of claim 2, wherein the first length is equal to the second length.
5. The coalescer of claim 1, wherein the swirling element is a vane.
6. The coalescer of claim 5, wherein the vane is fixed at an angle between 40° and 50° with respect to the axial direction of the associated flow chamber.
7. The coalescer of claim 1 further comprising an anti-swirl element associated with each of the plurality of coaxial flow chambers.
8. The coalescer of claim 7, wherein the anti-swirl elements are positioned downstream of the swirling elements.

9. The coalescer of claim 1, wherein the housing has an internal diameter of 16 inches.
10. A system for treating a multiphase fluid stream comprising:
an electrostatic coalescer; and
a cyclonic coalescer comprising:
a tubular housing in fluid communication with the electrostatic coalescer,
a plurality of coaxial flow chambers extending in the axial direction of the housing, and
a swirling element associated with each of the plurality of coaxial flow chambers, the swirling elements are constructed and arranged to impart a tangential velocity of the stream flowing through the associated flow chamber.
11. The system of claim 10, wherein the housing has a first length and the swirl elements extend a second length within the housing.
12. The system of claim 11, wherein the first length is greater than the second length.
13. The system of claim 10, wherein the swirling element is a vane.
14. The system of claim 13, wherein the vane is fixed at an angle between 40° and 50° with respect to the axial direction of the associated flow chamber.
15. The system of claim 10 further comprising an anti-swirl element associated with each of the plurality of coaxial flow chambers.
16. The system of claim 15, wherein the anti-swirl elements are positioned downstream of the swirling elements.

17. The system of claim 10, wherein the cyclonic coalescer is downstream of the electrostatic coalescer.
18. The system of claim 10 further comprising a gravity separation vessel in fluid communication with the cyclonic coalescer.
19. The system of claim 18, wherein the gravity separation vessel is downstream of the cyclonic coalescer.
20. A method for treating a multiphase fluid stream to enhance separation of a denser phase liquid from a lighter phase liquid within the multiphase fluid stream, the method comprising:
- flowing the stream into a plurality of coaxially extending flow chambers;
 - imparting a tangential velocity component on the stream flowing through each flow chamber, the tangential velocity is imparted using a swirl element; and
 - controlling the tangential velocity imparted on the stream to increase an average denser phase droplet size.
21. The method of claim 20, wherein controlling the tangential velocity comprises limiting the total velocity of the flow stream flowing into the flow chambers.
22. The method of claim 21, wherein the total velocity of the flow stream flowing into the flow chambers is less than 3 m/s.
23. The method of claim 20, wherein the swirl element is a vane, wherein controlling the tangential velocity comprises selecting a vane angle with respect to the axial direction of the flow chambers.

24. The method of claim 23, wherein the vane angle is between 40° and 50°.
25. The method of claim 20, wherein the denser phase liquid has a cut diameter of 1000-1350 microns after the tangential velocity has been imparted on the stream.
26. The method of claim 20 further comprising straightening the flow downstream of the swirl element to reduce the tangential velocity component of the stream.
27. The method of claim 20, wherein the tangential velocity imparted on the stream causes an average lighter phase droplet size to increase.
28. A method of producing hydrocarbons from a subsurface reservoir, comprising:
producing hydrocarbons through a wellbore, the produced hydrocarbons exist in a liquid-dominated-by-volume multiphase stream having a denser phase liquid and a lighter phase liquid;
flowing the stream into a plurality of longitudinally extending flow chambers;
imparting a tangential velocity component on the stream flowing through each flow chamber, the tangential velocity is imparted using a swirl element; and
controlling the tangential velocity imparted on the stream to increase an average denser phase droplet size.

CLAIMS

What is claimed is:

1. A cyclonic coalescer for enhancing separation of a denser phase liquid from a lighter phase liquid within a multiphase stream, the coalescer comprising:
a tubular housing;
a plurality of coaxial flow chambers extending in the axial direction of the housing;
and
a swirling element associated with each of the plurality of coaxial flow chambers, the swirling elements are constructed and arranged to impart a tangential velocity of the stream flowing through the associated flow chamber.
2. The coalescer of claim 1, wherein the housing has a first length and the swirl elements extend a second length within the housing.
3. The coalescer of claim 2, wherein the first length is greater than the second length.
4. The coalescer of claim 2, wherein the first length is equal to the second length.
5. The coalescer of any of claims 1 to 4, wherein the swirling element is a vane.
6. The coalescer of claim 5, wherein the vane is fixed at an angle between 40° and 50° with respect to the axial direction of the associated flow chamber.
7. The coalescer of any of claims 1 to 6 further comprising an anti-swirl element associated with each of the plurality of coaxial flow chambers.
8. The coalescer of claim 7, wherein the anti-swirl elements are positioned downstream of the swirling elements.

9. The coalescer of claim 1, wherein the housing has an internal diameter of 16 inches.
10. A system for treating a multiphase fluid stream comprising:
an electrostatic coalescer; and
a cyclonic coalescer as claimed in any of claims 1 to 9.
11. The system of claim 10, wherein the cyclonic coalescer is downstream of the electrostatic coalescer.
12. The system of claim 10 or claim 11 further comprising a gravity separation vessel in fluid communication with the cyclonic coalescer, the gravity separation vessel is downstream of the cyclonic coalescer.
13. A method for treating a multiphase fluid stream to enhance separation of a denser phase liquid from a lighter phase liquid within the multiphase fluid stream, the method comprising:
flowing the stream into a plurality of coaxially extending flow chambers;
imparting a tangential velocity component on the stream flowing through each flow chamber, the tangential velocity is imparted using a swirl element; and
controlling the tangential velocity imparted on the stream to increase an average denser phase droplet size.
14. The method of claim 13, wherein controlling the tangential velocity comprises limiting the total velocity of the flow stream flowing into the flow chambers.
15. The method of claim 13 or claim 14, wherein the total velocity of the flow stream flowing into the flow chambers is less than 3 m/s.

16. The method of any of claims 13 to 15, wherein the swirl element is a vane, wherein controlling the tangential velocity comprises selecting a vane angle with respect to the axial direction of the flow chambers.
17. The method of claim 16, wherein the vane angle is between 40° and 50°.
18. The method of any of claims 13 to 17, wherein the denser phase liquid has a cut diameter of 1000-1350 microns after the tangential velocity has been imparted on the stream.
19. The method of any of claims 13 to 18, wherein the tangential velocity imparted on the stream causes an average lighter phase droplet size to increase.
20. A method of producing hydrocarbons from a subsurface reservoir, comprising:
producing hydrocarbons through a wellbore, the produced hydrocarbons exist in a liquid-dominated-by-volume multiphase stream having a denser phase liquid and a lighter phase liquid;
flowing the stream into a plurality of longitudinally extending flow chambers;
imparting a tangential velocity component on the stream flowing through each flow chamber, the tangential velocity is imparted using a swirl element; and
controlling the tangential velocity imparted on the stream to increase an average denser phase droplet size.