

LOW-PROFILE POWER-GENERATING WIND TURBINE

FIELD OF THE INVENTION

[0001] This invention pertains to wind turbines which have low profiles, which are quiet when operating, and which can be used for generating electrical power. More particularly, the invention pertains to such wind turbines which collect ambient wind air and concentrate and direct that air to and through a radially - bladed rotor at a throat of a turbine air inlet passage.

BACKGROUND OF THE INVENTION

[0002] It is known to generate electrical power by use of wind-powered mechanisms. Known mechanisms for such purposes generally are of two kinds, namely, wind turbines which commonly have rotors resembling aircraft propellers which rotate about horizontal axes, and vertical axis wind turbines which commonly have long vertically extending blades as components of a cylindrical rotor. The rotors of those two kinds of wind turbines are connected to rotatable shafts which are suitably connected to generators which output electrical power. The generators commonly produce DC power which commonly is converted to AC power of a desired frequency, such as by use of inverters.

[0003] Both of those kinds of wind turbines, with possible rare exception, have fixed locations. Also, both of those kinds of wind turbines have considerable height. The generators of horizontal axis wind turbines are enclosed in housings (commonly called "nacelles") located atop towers of sufficient height to provide suitable clearance between the ground and the ends of the rotor blades which extend radially in a common vertical plane from a central hub on the horizontal rotational axis of the rotor. Horizontal axis wind turbines having overall heights well in excess of 120 meters are in use.

[0004] Such horizontal and vertical axis turbines share a common attribute, namely, their rotors are exposed to, and perform in direct response to, ambient wind conditions. For that reason, local winds must have speeds greater than a characteristic minimum speed before the turbines rotate sufficiently rapidly, or with sufficient power (torque), to produce useful generator output.

1 **[0005]** The requirement of such known wind turbines that they have fixed locations is a disadvantageous limitation of them. Also, their considerable-to-large height limits the places where they can be used safely or without objection to their appearance.

5 SUMMARY OF THE INVENTION

10 **[0006]** This invention provides a wind-driven power generation turbine which differs significantly in concept and structural arrangement from the horizontal axis and vertical axis wind turbines reviewed above. Turbines according to this invention can be of small height and can be portable. Their small height enables them to be used on buildings in urban areas, e.g.; when portable, they can be used for such times as are needed in different locations, such as in support of construction activities or in support of military operations, as examples of utility. The present wind turbines are quiet in operation and are easily accessible for maintenance. They can be provided in a wide range of sizes and power generation capabilities.

15 **[0007]** Generally speaking in terms of structure, this invention provides a wind turbine having an ambient air flow inlet passage which extends between inlet and outlet ends. Between those ends, the passage has a selected effective length and configuration. The inlet end has an inlet opening of relatively large area compared to a passage outlet opening at the passage's outlet end. Between its ends, the passage configuration includes a decrease in the passage cross-sectioned area. A rotor is located proximate to the passage outlet opening. The rotor is rotatable about an axis which is substantially aligned with a rear portion of the length of the passage which terminates at the outlet opening. The rotor includes an array of radially extending blades which are spaced regularly about the rotor axis. The blades can interact with air moving through the passage outlet opening to produce rotation of the rotor about its axis.

20 **[0008]** Generally speaking in terms of procedure, this invention provides a method for generating electrical power from wind energy. The method includes providing an electrical generator, a rotor and an air flow passage. The rotor carries an array of blades defined to interact with air moving past them to produce rotation of the rotor. The air flow passage has a relatively large effective inlet opening area and a relatively small outlet opening area. The inlet and outlet openings are spaced along the passage which decreases in cross-sectional area between those openings. The method includes positioning the rotor sufficiently close to the passage outlet opening that air moving through the outlet opening can effectively interact with the rotor blades to produce rotation of the rotor. Another procedural step of the method is coupling the generator to the rotor so that the generator operates to generate electrical

1 energy in response to rotation of the rotor. Another step of the method is orienting the passage so that the inlet opening faces into the direction from which ambient air moves relatively toward the inlet opening.

5 [0009] As air moves relatively toward the passage inlet opening, the air enters into the inlet passage and moves along the passage to the outlet opening and the rotor. The decreasing cross-sectional area of the passage causes the velocity of the air in the passage to increase as it moves along the passage. As a result, the air interacting with the rotor blades is more energetic per unit of volume than the air which enters the passage. The increased
10 velocity of the air interacting with the rotor blades is significant because the power available in moving air (wind) is proportioned to the cube of the air velocity.

DESCRIPTION OF THE DRAWINGS

15 [0010] The design principles, some presently preferred structural arrangements of turbines according to this invention, and the procedural aspects of the invention are depicted in the drawings which accompany and illustrate the description which follows. Those illustrations are comprised by figures as follows:

20 [0011] FIG. 1 is a drawing presenting a simplified schematic depiction of a turbine the invention to illustrate certain principles of the invention;

[0012] FIG. 2 is a drawing which shows a top view of the turbine rotor;

25 [0013] FIG. 3 is a drawing showing a longitudinal cross-sectional elevation view of a turbine of the invention supported on a wheeled foundation;

[0014] FIG. 4 is an elevation view of the inlet (front) end of the turbine shown in Fig. 3 as taken along line 4-4 in Fig. 3;

30 [0015] FIG. 5 is an enlarged fragmentary cross-section view of the stator vanes and rotor blades in a turbine of the invention;

[0016] FIG. 6 is an elevation view, partially in cross-section, which shows how a turbine of the invention can be located on a building having a pitched roof;

35 [0017] FIG. 7 is an exploded perspective view showing how the turbine air inlet passage and a stator vane array can be defined;

1 [0018] FIG. 8 is a drawing showing how a turbine according to the invention, located at a fixed location, can be adjusted in position to face into the direction of an ambient wind; and

5 [0019] FIG. 9 is a fragmentary perspective view of structure which can be an area to movably support a turbine in a suspended state in a case where the foundation for the turbine is located above the turbine.

DESCRIPTION OF THE INVENTION WITH REFERENCE TO THE DRAWINGS

10 [0020] FIG. 1 is presented to illustrate principles of the operation and structure of a wind turbine according to this invention. FIG. 1 shows a low-profile power-generating wind turbine 10 in simplified and somewhat idealized form. The turbine includes a round rotor 11 which carries around its circumference a plurality of regularly spaced radially extending blades 12 of desired length and shape. The rotor is positioned for rotation in a plane which is substantially parallel to an outlet end 15 an inlet air flow passage 13 which has an inlet end 14 spaced in an upstream direction along the inlet passage from the rotor. An optional outlet air flow passage 16 can have an outlet end 17 spaced in a downstream direction from the rotor.

20 [0021] The portion 18 of the inlet passage 13 closely adjacent the rotor on its upstream side preferably is straight, of substantially constant diameter, and aligned with the rotor axis of rotation; that portion of the passage defines a passage throat. Passage 13 between inlets 14 and throat 18 is defined to decrease, preferably substantially smoothly in cross-sectional area proceeding from the inlet to the throat. During times of its operation to generate electrical power, the turbine is oriented so that the opening at inlet end 14 of passage 13 faces into the direction from which air (actual or relative wind) moves toward the turbine. The rearwardly tapering shape of the air inlet passage cooperates with air entering the inlet and moving along the passage to cause that air to increase in velocity as the air moves along the passage. As a result, the air in passage 13 at the upstream side of rotor 11 is more energetic per unit volume of air than is the air just moving into the passage inlet. Therefore, the air entering the spaces 25 between the rotor blades moves faster and can act more forcefully on the rotor blades than can a comparable volume of the air just moving into the passage inlet.

30 [0022] The focused and accelerated nature of the air which acts on the rotor of a wind turbine according to this invention distinguishes such a turbine from wind turbines of the kinds reviewed above in which wind merely blows on the turbine rotor and does not undergo significant velocity increasing and focusing processes before interacting with the turbine rotor.

1 [0023] After passage through rotor 11, air flowing through turbine 10 either exits from
the turbine or enters outlet passage 16 which, if present, extends between rotor 11 and outlet
17. An air outlet passage 16 can increase in cross-sectioned area from the area of throat 86
to the area of the outlet opening of outlet passage which can have substantially the same area
5 as the inlet opening to the turbine. Air outlet passage 16 can enable air in it to expand and
reduce velocity progressively so that the velocity and pressure of air leaving the turbine is
substantially equal to the pressure and velocity of air entering the turbine. However, it has
been found that a turbine according to this invention which does not include an air outlet
passage is effective and may be preferred, especially where low overall height is a desired
10 property of the turbine.

[0024] The foregoing description of inlet air flow passage 13 and of its different portions,
apart from mention of rotor 11, is consistent with the description of a straight venturi tube. It
is within the scope of this invention that passage 13 can be straight along its length.
15 However, to make turbine 10 more compact end-to-end, and for other reasons discussed or
made apparent later herein, it is preferred, when implementing the principles of the invention,
to form passage 13 so that its throat 18 is substantially vertical relative to a substantially
horizontal portion of the passage adjacent inlet end 14. FIG. 1 shows such a passage
configuration, referred to here as a "right turn passage" or RTP. It is envisioned that the bend
20 in an inlet air passage in a turbine of the invention can be greater than a 90° bend.

[0025] If a turbine inlet air flow passage is straight to and through the rotor, the velocity
and mass flow rate of air passing through the rotor normally will be substantially uniform at
25 different locations around the periphery of the rotor where the rotor blades are located. That
is a desirable condition. On the other hand, if there is a bend in the turbine inlet air flow
passage upstream of the rotor, the fact that air has mass can cause the mass distribution of air
at the rotor to be non-uniform; a larger share of the mass of the air at the rotor likely will be
found in that part of the passage throat which corresponds to the outside of the passage bend.
30 To counteract and control such unbalancing of air distribution in a turbine having a right turn
passage as shown in FIG. 1, turbine 10 preferably includes a primary partition or baffle 20
extending in the passage from just forwardly of the rotor blades toward the passage inlet.
Partition 20 preferably is positioned and contoured, in cooperation with the contours of the
passage inlet portion so that substantially equal fractions of the overall quantity of air
35 entering inlet 14 flow to the forward and rear halves of the annular area of the rotor in which
the rotor blades 12 are located; see FIG. 2 and remarks which follow. The positioning and
contouring of the primary partition between its front extent and its rear end adjacent the rotor
preferably is defined so that each half of passage 13 (the half leading to the front of the rotor

1 and the half leading to the rear of the rotor) have substantially equal effects to increase the velocity of the air moving from inlet 14 to the rotor location.

5 [0026] As shown in FIG. 1, primary partition 20 preferably is generally horizontally disposed in passage 13 at its upstream end. The air moving in the passage above partition 20 constitutes an upper air stream which is directed to the forward portion of rotor 11, and the air moving in the passage below partition 20 constitutes a lower air stream which is directed to the rear portion of the rotor. Each of the upper and lower air streams can be, and preferably are, substantially equally subdivided by one or more secondary partitions 21 composed of
10 upper-forward secondary partitions 21' and of lower-rear secondary partitions 21". As with the primary partition 20, the arrangement of the secondary partitions is defined within passage 13 so that the air in each subdivision of the upper and lower air streams moving toward rotor 12 undergoes substantially equal velocity increasing effects. As a result, all the rotor blades 12 encounter substantially the same conditions of air velocity and mass
15 distribution. The number of secondary partitions 21 provided in a turbine 10 can be varied with the size of the turbine; 4 or 5 secondary partitions 21' and 21" can be appropriate in a turbine having a large diameter rotor.

20 [0027] As shown in FIGS. 1 and 5, turbine 13, particularly in the case where it has a right turn inlet air flow passage, can include a set of regularly spaced fixed stator vanes 22 immediately in front of the rotor blades 12. The stator vanes coact with air moving past them so that the direction of movement of air leaving the vanes has a desired direction relative to the shapes of the rotor blades. The effect of the stator vanes is to enable the rotor blades to
25 more efficiently and effectively respond to the forces applied to the rotor blades by the passing air to turn rotor 11 more forcefully in the desired direction of the rotor. The stator vanes preferably extend radially of the turbine axis and can be supported between inner and outer supportive cylindrical shrouds which are fixed relative to a foundation or base for the turbine; see FIG. 7. The inner stator vane shroud support can extend inwardly from that
30 shroud adjacent the rotor; if that shroud support is located below the rotor, as where air moves upwardly through the passage throat 16, that shroud support can provide at least some support for rotation of the rotor relative to it about the turbine axis. Also, it will be apparent that, if desired, the turbine can be a multi-stage turbine in which at least one further group of stator vanes and rotor blades are located downstream adjacent to the first group of vanes and
35 blades encountered by air as it moves through throat 18.

[0028] Rotation of turbine rotor 11 is used to turn the rotor of a generator 24 thereby to produce electrical power which can be used directly from the generator. If the generator is a

1 DC generator and AC power is desired for use, the output of the generator can be applied to an inverter 25. In implementations of this invention which use right turn inlet air flow passages to enable the turbine rotor to turn about a vertical axis, the rotor can be connected to the upper end of a rotatable output shaft 26 which can extend downwardly from the rotor.

5 The lower end of shaft 26 can be connected directly to the generator. More preferably, however, the turbine output shaft is coupled to the generator through a right angle drive 27 which can have an effective gear ratio different from (preferably greater than) 1:1. If the rotor shaft and the generator input shaft are to be aligned, a planetary gear arrangement can be used to couple the two shafts.

10
[0029] In addition to the use of bearings which support rotor shaft 26 for rotation in the turbine, it is desirable also to use thrust bearings to support the rotor shaft. Thrust bearings which are effective in opposite directions are desirable since air moving through the rotor can apply sufficient force on those blades to move the rotor and its shaft in the direction of the air flow.

15
[0030] FIG. 2 is a fragmentary plan view of a rotor 11 useful in a turbine 10 having a right turn inlet air flow passage through the throat of which air moves in an upward direction. Broken line 27 is present in FIG. 2 to denote that rotor blades 12 (only three of which are shown) are present around the entire periphery of the rotor. Forward and rear directions in the turbine are indicated. FIG. 2 shows the locations where the upper end of primary passage partition 20 terminates relative to the rotor to define forward 30 and rear 31 equal-area semicircular arcuate zones through which the rotor blades pass as the rotor turns. FIG. 2 also shows the locations relative to zones 30 and 31 of the upper rear ends of secondary partitions 21' and 21." That is, the air which moves along passage 13 above partition 20 passes through throat 18 to the stator vanes and rotor blades through ducting discharge openings having substantially the same collective shape as zone 30 shown in FIG. 2. Similarly, the air which moves along passage 13 below partition 20 approaches the stator vanes and rotor blades through ducting discharge openings having substantially the same collective shape as zone 31 in FIG. 2. Together, those ducting discharge openings form a circle below the stator vanes. That circle can form the boundary of a substantially circularly cylindrical space inside the turbine around which the inner-front and lower-rear halves of passage inlet portion pass. Rotor shaft 26, generator 24, inverter 25, and related elements of the coupling of the rotor to the generator can be located in that cylindrical space. The floor of that space can be mounted on a foundation for the turbine or can be a part of such a foundation. That space can have its own enclosure 33 (see FIG. 8) separate from the structure defining air flow passage 13.

1 **[0031]** FIG. 2 also shows that rotor 11 can have a central hub 34 to which the upper end of shaft 26 can be secured in alignment with the rotational axis of the rotor.

5 **[0032]** FIG. 3 shows that the foundation on which the turbine can be supported can be a trailer frame 36 (such as a frame similar to a frame for a boat trailer) having an axle and wheels 37. The front end of the trailer is indicated at 38. FIG. 3 also shows that the output of a right angle drive 27 powered by rotor shaft 26 can be coupled to a gearbox 39 by a belt 40.

10 **[0033]** FIGS 3 and 4 show that the effective area of the inlet opening to inlet air flow passage 13 can be enlarged by auxiliary structures movably mounted to the passage structure around the inlet opening. In FIG 4, the fixed structure of the passage defines top 42, bottom 43, and side 44 edges of the opening. Since turbine 10 is shown in FIG. 3 to be carried on a movable vehicle, it can be useful to close the opening to passage 13 when the vehicle is in motion as well as, perhaps, other times when the turbine is not in use. To that end, turbine 10 can be equipped with doors for selective closure of the passage inlet opening. Such doors can be upper and lower doors 45 and 46 which can be hinged to the top and bottom edges, respectively, of the passage inlet opening. Doors 45 and 46 can extend along the full width of the inlet opening. Doors 45 and 46 can be supplemented by movable (hinged) side panels 47 mounted to the side edges 44 of the passage inlet opening; the side panels, when disposed substantially in the plane of the outlet opening, extend along the height of the inlet opening but preferably only partially across the width of the opening. When the inlet opening is to be closed, the doors and side panels can be moved to closed positions substantially in the plane of the outlet opening with the side panels overlapped by the doors.

25 **[0034]** During times when it is desired to operate the turbine, the doors and panels can be opened and moved to defined air capture positions in which they are disposed at angles to the plane of the passage inlet opening. In FIG. 3, doors 45 and 46 are shown to have been moved about 135° from their closed positions, and the side panels can have been moved through similar angles; the doors and side panels are suitably held in their open positions. FIG. 4 shows that the spaces between adjacent edges of the opened doors and side panels can be closed by gusset elements 48. The gussets can be defined by suitably shaped (such as triangular) pieces of canvas, e.g., and can be secured, as by grommets and pins, to the adjacent edges of the doors and side panels. The arrangement of open doors and side panels, and installed gussets, around the fixed boundaries of the passage inlet opening significantly increases the effective area of the passage inlet opening.

30

35

1 [0035] FIGS. 3 and 4 depict the use of doors 45 and 46 which each close one-half the
area bounded by the opening top, bottom and side edges 45-47. If desired, doors
dimensioned at the full height of that opening can be provided; such full-height doors can be
disposed in overlying relation to each other when they are closed.

5 [0036] FIG 5 depicts a workable relation between rotor blades 12 and stator vanes 22.
Preferably, as shown, there is a space between the upper edges of the stator vanes and the
adjacent lower edges of the rotor blades. That space is useful to the desired quiet operation of
a turbine according to the invention.

10 [0037] FIG. 6 shows that a turbine 10' according to this invention which includes a right
turn inlet air flow passage can have its passage inlet 14 located above its outlet so that air
flows downwardly through stator vanes 22 and rotor blades 12. Turbine 10' can have
15 advantages in uses where blowing snow, or other particulate matter moving along or close to
the ground, may be encountered. Further, FIG. 6 shows that turbine 10' can be supported
atop a building 50 having a pitched roof 51 in which the roof surfaces form boundaries of air
inlet and air outlet passages of the turbine.

20 [0038] If a turbine according to this invention is supported on a movable foundation, such
as a trailer as shown in FIG. 3, the turbine can readily be positioned on the ground so that the
inlet 14 of the turbine inlet air flow passage faces directly into an oncoming wind; if the wind
shifts appreciably in direction, the turbine can be repositioned or reoriented as needed.
However, this invention contemplates turbines having such large diameter rotors that
25 reorientation of the turbine foundation is not practical, as well as turbines located atop
buildings where access to the turbine for reorientation of the turbine is not workable or
realistically possible. In the latter situations, the turbines may be self-orienting on their
foundations; an illustration of a self-orienting turbine 10" is found in FIG. 8. The air flow
passage 13 of turbine 10" and the structure in it can be as described above. The inlet air flow
30 passage 13 of that turbine can be supported on a base 55 which, in turn, can be movably
supported, as by rollers 56, on a stationary foundation 57 such as a rooftop or the ground.
The turbine preferably is so mounted on the base that the turbine axis (i.e., the axis of rotation
of the turbine rotor) and the axis of rotation of the base are coincident at 58. As noted above,
the rotor drive shaft and related power generation equipment can be located in a round
35 housing 33 aligned with axis 58 separate from the structure forming air flow passage 13. The
inlet air flow passage structure can be movable around housing 33, and so housing 33 can be
supported on foundation 57 and can extend through a central hole in base 55. In some
instances, air flow passage structures of turbine 10" can be self-orienting since the outlet air

1 flow passage structure, if present can function in a manner akin to the tail of a weathervane;
wind forces acting in the outside of the turbine can turn the turbine about axis 58. In other
instances, such as where the turbine rotor diameter is large, the turbine base 40 can be rotated
by a suitable base drive mechanism 59 (denoted as a yaw drive), such as a motor driven
5 pinion gear engaged with a ring gear carried by the base; see FIG. 8. Operation of the base
drive mechanism can be controlled using information obtained from a wind direction sensor
60 suitably positioned on or associated with the turbine.

10 **[0039]** If a self-orienting turbine is large, it can be useful to provide movable support for
the portion of the airflow passage structure which, if present, is located above the top of the
inlet air flow passage throat. Such support is shown in FIG. 11 where the outlet portion 16 of
the turbine air flow passage structure is located above the passage throat. More specifically,
passage outlet portion 19 can be movably supported, as by a roller 62 connected to the lower
15 exterior of that passage portion, on an annular platform 63 disposed perpendicular to axis 58
and preferably located suitably above foundation 57. Platform 63 can be carried on supports
64 which preferably are located in a circular pattern concentric to axis 58. The diameter of
the pattern of supports 64 is sufficiently large that the turbine can be rotated 360° about axis
58 inside the platform supports.

20 **[0040]** FIG. 7 is an exploded perspective view of structural components useful to define
aspects of an inlet air flow passage of a turbine of this invention. The depicted components
are a bottom passage subassembly 70, on top passage subassembly 71, and a stator
subassembly 72. Subassembly 70 defines a circular structural framework 73 having a height
25 which approximates the distance between a turbine base plane and its rotor plane. In the
upper forward half of the framework 73 is located a semicircular air deflector 74 which forms
surfaces of an upper inlet air flow passage and to which the rear extent of principal air flow
partition 20 can be connected at lower deflector edge 75. A lower semicircular air deflector
76 is carried in the lower half of subassembly 70 at its rear. Deflector 76 can be shaped as
30 one-half of a right circular conic section; it is concave upwardly. Air moving to deflector 76
passes below deflector 74. The upper edge of deflector 76 is shown to be at the mid-height of
framework 73. The forward portion of subassembly 70 can be closed on its sides (as at 77),
its bottom (as at 78), and its top (not shown) to define other aspects of inlet air flow passage
13 rearwardly of its rectangular open inlet end 14.

35 **[0041]** Subassembly 71 is shown to be comprised principally by a circular structural ring
member 79 and by a semicircular cylindrically curved skirt 80 which depends from ring
member 79 a distance equal to the spacing of the upper edge 81 of lower deflector 76. When

1 ring member 79 is properly positioned on and secured to the upper structural ring of subassembly 70, skirt 80 connects to deflector 76 at its edge 81 and closes the upper rear half of framework 73.

5 [0042] Stator assembly 72 includes stator vanes 22 which are carried between inner 83 and outer 84 circularly cylindrical vane supporting shrouds. The stator assembly preferably is annular in shape. The stator assembly is connected to ring member 79 of subassembly 71 as the turbine is assembled.

10 [0043] It was mentioned earlier that a turbine of this invention can be mounted in an inverted position. A form of inverted turbine in which air flows downward through the rotor blades is shown in FIG. 6; in that instance the turbine is not movable about its axis relative to its support structure. It is possible to mount in an inverted position a turbine which is
15 movable about its rotor axis relative to the turbine's supports; FIG 9 depicts one way in which an angularly movable turbine can be supported from above.

[0044] As shown in FIG. 9, a turbine support ring 90 can be supported below a foundation (not shown) by brackets 91 depending from a bracket base 92. Several brackets
20 and bracket base assemblies can be attached to support ring 90 at spaced location around the ring. Each bracket base can be connected to the bottom surface of a suitable foundation. The base of the inverted turbine can be carried by the support ring via plural trolley assemblies 94, one of which is shown in FIG. 9. A trolley assembly 94 can include a frame 95 which can be suitably secured to the turbine base and to which are rotatably mounted upper 96 and
25 lower 97 trolley rollers. The rollers preferably have circumferences contoured to mate closely with the contours of support ring 90. The trolley rollers are located on frame 95 so that the trolley assemblies move along the support ring and not vertically or radially relative to the support ring. Angular motion of the related turbine relative to the support ring axis can be obtained by operation of one or more drive motors connected to one or more of the upper
30 trolley rollers.

[0045] It is envisioned that a right turn passage turbine according to this invention having a rotor diameter on the order of 80 feet can have a height of about 12 feet at its rotor plane.

35 [0046] As noted above, the power available in a wind is proportional to the cube of the wind's velocity, which means that doubling the wind velocity increases the available power by a factor of eight. A small difference in wind velocity can mean a large difference in

1 available energy and in electricity produced, and therefore a large difference in the cost of
electricity produced. It will be seen that the turbines of this invention, characterized by
comparatively small structures which meaningfully increase inlet air velocities, can produce
significant quantities of electricity. The low profiles (small heights) of the present turbines
5 means that the turbines can be used in places where high profile turbines cannot be used or
are not acceptable.

[0047] Turbines of this invention operate in response to energy in air moving relatively
toward the inlet air openings of the turbines. When the turbine is used at a geographically
10 fixed location, such relative air movement is due to a wind moving past that location. It will
be appreciated that such relative air can be caused by movement of the turbine itself, such as
is the case where the turbine is located on a vehicle which is moved for reasons other than the
creation of a relative wind past the turbine. Examples of such vehicles are trains and trucks.
Such vehicles move at moderate to high speeds during significant portions of their useful
15 lives, and so this invention contemplates the use of turbines of the kinds described above on
such vehicles.

[0048] For example, a small version of a turbine of this invention can be mounted atop a
20 driver's cab of a truck or a truck tractor to generate electricity useful in the operation of the
vehicle. Electrical power generated by the turbine can be applied to operate refrigeration
systems aboard the vehicle, as where the vehicle has cargo space for the transport of frozen or
perishable foods. Also, turbine generated electrical energy can be used to charge (or
recharge) batteries on the vehicle to operate vehicle electrical systems when the vehicle is not
25 in motion or is moving at low speed.

[0049] The present invention has been described above with reference to certain
structural arrangements embodying the invention and with reference to certain procedural
aspects of the invention. The preceding description is not intended to be, nor should it be
30 read as, a comprehensive catalog of all forms in which the invention can be embodied or
procedurally implemented. Variations and modifications of the described aspects of the
invention can be practiced without departing from the fair scope of the invention.

1 WHAT IS CLAIMED IS:

5 1. A wind turbine comprising an ambient air inlet flow passage of selected effective length and configuration between an inlet end having an inlet opening of relatively large area and an outlet end having an outlet opening of relatively small area, the inlet passage decreasing in cross-sectional area between its inlet and outlet ends, and a rotor located proximate to the passage outlet opening and rotatable about an axis substantially aligned with a rear portion of the length of the passage which terminates at the outlet opening, the rotor including an array of radially extending blades which are regularly spaced about the rotor axis and which can interact with air moving through the outlet opening to rotate the rotor about its axis.

15 2. A wind turbine according to claim 1 in which forward portion of the length of the inlet flow passage extending from the inlet opening is disposed at a substantial angle relative to the length of the rear portion of the passage.

3. A wind turbine according to claim 2 in which the value of the angle is on the order of 90°.

20 4. A wind turbine according to claim 1 including an array of stator vanes disposed in the flow passage proximately adjacent the rotor blades and operative upon air moving past them to direct that air along desired paths toward the rotor blades.

5. A wind turbine according to claim 4 in which the rotor blades extend from the perimeter of the rotor and form an annular array of blades around the rotor, and the stator vane array is annular and similar in area to the rotor blade array.

25 6. A wind turbine according to claim 1 in which at least a section of the length of the inlet flow passage terminating proximate the outlet opening is defined to cause the mass flow of air moving through the outlet opening to be substantially uniform in the area of the rotor blade array.

30 7. A wind turbine according to claim 6 in which the definition of the inlet flow passage to cause substantially uniform air mass flow includes at least one partition in the air flow passage section.

8. A wind turbine according to claim 7 including a plurality of partitions in the air flow passage section.

35 9. A wind turbine according to claim 2 in which at least a section of the length of the inlet flow passage terminating proximate the outlet opening is defined to cause the mass flow of air moving through the outlet opening to be substantially uniform in the area of the rotor blade array.

10. A wind turbine according to claim 9 in which the rotor blade array is annular and is located along the perimeter of the rotor.

1 11. A wind turbine according to claim 2 including a base carrying the turbine, the base defining a plane substantially normal to the rotor axis, a foundation supporting the base for rotation about an axis substantially parallel to the rotor axis, and a drive coupled between the base and the foundation selectively operable to rotate the base on the foundation.

5 12. A wind turbine according to claim 11 in which the drive includes a relative wind direction sensor.

 13. A wind turbine according to claim 2 including a foundation on which the turbine is supported, and the foundation includes wheels by which the turbine can be moved to and at a selected location of use.

10 14. A wind turbine according to claim 2 in which the inlet opening to the inlet flow passage is closable by at least one door connectible to structure defining the inlet opening, the door being disposable during use of the turbine to effectively increase the effective area of the inlet opening.

15 15. A method for generating electrical power from wind energy, comprising the steps of providing an electrical generator, providing a rotor carrying an array of blades defined to interact with air moving there past to produce rotation of the rotor, providing an air flow passage having a relatively large effective inlet opening area and a relatively small effective outlet opening area, the inlet and outlet openings being spaced along the passage which progressively decreases in cross-sectional area between those openings, positioning the rotor sufficiently proximate the passage outlet opening that air moving through the outlet opening can effectively interact with the rotor blades to produce rotation of the rotor, coupling the generator to the rotor so that the generator operates to generate electrical energy in response to rotation of the rotor, and orienting the passage so that the inlet opening faces into the direction from which ambient air moves relatively toward the inlet opening.

20 16. The method according to claim 15 including the step of controlling the distribution of air flow in the passage to cause the mass flow of air to the rotor blades to be substantially uniform throughout the rotor blade array.

25 17. The method according to claim 15 including providing proximate the passage outlet opening an array of air flow directing stator vanes.

30 18. The method according to claim 15 including sensing the direction of movement of ambient air past the location of the air flow passage and the rotor, and adjusting the orientation of the passage to cause the inlet opening to face toward the sensed direction.

 19. The method according to claim 15 including the step of locating the air flow passage and the rotor on a habitable structure.

35 20. The method according to claim 19 in which the locating step includes locating the passage and the rotor on a building having a sloping roof in such a way that the roof slope can direct toward the passage inlet opening wind moving in a selected direction toward the building.

1 21. The method according to claim 19 in which the locating step comprises supporting the air flow passage and the rotor on an exterior wall of the habitable structure.

 22. The method according to claim 15 including the step of locating the air flow passage, the rotor, and the generator on a vehicle which is movable for reasons other than the
5 generation of electrical power in such a way that the generator can operate in response to relative wind past the vehicle during such movement of the vehicle.

 23. The method according to claim 22 in which the vehicle is a truck tractor.

 24. The method according to claim 22 in which the vehicle is a component of a
train.
10

15

20

25

30

35