

GU02E002WO/ws96277/Dr.L./ee/29.10.1997

Air-cleaning apparatus

DESCRIPTION

- The invention relates to an air-cleaning apparatus, especially an electrostatic air-cleaning apparatus, having a housing, in which an inlet nozzle and an outlet nozzle for an air-current to be cleaned are provided, which is led to an air-cleaning unit being arranged in said housing, wherein said housing of the air-cleaning apparatus is column-like, and wherein said column-like housing comprises an essentially air-tight outer sheath .
- 5
- 10 Such an air-cleaning apparatus comprising an electrostatic separator equipment is known. The air to be cleaned is ionized in a gas ionizer in a high voltage field, so that the floating particles in the air put against a separating surface of a following separator having also a high voltage field. The known electrostatic separator is arranged in a box-like housing having a cylindrical cross section with a noticeable larger diameter than the gas ionizer arranged inside the apparatus.
- 15

This above described electrostatic separator equipment as well as all the other known air-cleaning apparatus are, due to their box-like housings, only capable of cleaning the lower air layers of a room, so that a cleaning of the upper air layers can be accomplished not at all or only very insufficiently.

- 20 The known air-cleaning apparatus are capable of cleaning only a small amount of air per hour. This is caused by the fact that the known air-cleaning apparatus used in living spaces, business premises or restaurants must be built relatively compact, because most of the customers regard it as disturbing, if, for example in their living room, a bulky box stood, which would be necessary with a known air-



cleaning apparatus in order to accommodate the technical components necessary for achieving an adequate cleaning performance.

Due to the positioning of the known air-cleaning apparatus near to the floor, the employable power of a fan sucking in the air is relatively small, as otherwise the persons being in that room would be exposed to an unpleasant draught.

Because of the compact construction of the known air-cleaning apparatus due to the above-mentioned reasons, only very poor sound isolation means can be employed, which is therefore capable only to absorb a small amount of the operating noises of the known air-cleaning apparatus. This once again leads to only a limited performance of the known air-cleaning apparatus.

From DE-OS 35 28 591, there is known a column-like air conditioning device, the housing of which has an essentially air-tight outer sheath and is provided with an inlet and an outlet opening. The air conditioning device consists of a fan having on its pressure side an ion generator and an electric dust separator located on the feed side of the ion generator. The disadvantage of the known air conditioning device is that it only can be set-up in its horizontal direction, so that also with this device the afore-described disadvantages still occur.

From DE-OS 39 21 387, there is known a box-like air-cleaner having air inlet openings in its lateral surface. The air current being sucked in through one of these air inlets openings streams through an electric separating device using a corona discharge.

From JP 60-114361 in Patents Abstracts of Japan, sect. C, vol.9 (1985), no. 260 (C309), there is known an air-cleaning apparatus having air inlet and air outlet openings at both of its lateral surfaces, whereby the air current entering through the inlet opening passes through an electrostatic cleaning device.

- 3 -

Therefore, it is the object of the invention to further develop an air-cleaning apparatus of the afore-mentioned type in order to reach a high cleaning power despite of a compact construction.

5 This object is achieved according to the invention in that said inlet nozzle for said air-current to be cleaned is provided in a first front face of said column-like housing and the outlet nozzle is provided in the other front face of said column-like housing, that said air-cleaning unit provided in said column-like housing is formed tube-like, that an inlet opening of said air-cleaning unit is provided at one of its front faces and is aligned with said inlet nozzle of said column-like housing, and
10 that an outlet opening of said air-cleaning unit is provided at its other front face and is aligned with said outlet nozzle of said column-like housing of said air-cleaning apparatus.

Advantageous embodiments of the invention are given in the dependent claims.

By way of the inventive measures, there is provided in a highly advantageous
15 manner an air-cleaning apparatus, which excels in its exceptional low noise operation and its aesthetic shape. The straight course of flow of the air current, which is achievable in an advantageous way by the inventive construction of the air cleaning apparatus, passing through the air-cleaning apparatus eliminates or reduces the appearance of turbulences in the course of flow. This yields in an ad-
20 vantageous manner that the air noise is minimal while operating the inventive air-cleaning apparatus. Additionally, the straight air guidance achieved by the column-like shape of the inventive air-cleaning apparatus yields the advantage of a very low flow resistance, so that in an advantageous manner a smaller fan power, compared to the known air-cleaning apparatus, is required to reach a cer-
25 tain air-flow. This smaller fan power also contributes to the low noise of the inventive air-cleaning apparatus, whereby the noise level of the inventive air-cleaning apparatus is typically in the range below 30 dBA.

This Sheet Has Been Replaced



- A further advantage of the inventive air-cleaning apparatus is that, by means of the column-like shape of the housing, it is achieved that the inventive air-cleaning apparatus not regarded as a disturbing body in a room, but it is considered as prestigious decoration element. The inventive provision of a closed outer sheath
- 5 allows that the inventive air-cleaning apparatus in an advantageous manner can be provided with various decoration elements, for example a foil decor, a natural wood decor or a powder coating, so that the air-cleaning apparatus can be extremely easy adapted in an advantageous manner to the ambience of the room where it is located.
- 10 The column-like shape of the inventive air-cleaning apparatus has furthermore the advantage that the air-cleaning apparatus can be very easily made longer this without having the effect of being optically disturbing or looking bulky. By the easily possible elongation of the housing it is very easily possible to use a longer air-cleaning unit, through which a higher cleaning degree is achieved in an very ad-
- 15 vantageous manner. Furthermore, the inventive column-like shape of the air-cleaning apparatus allows to use an electrostatic air-cleaning unit which needs a lower high voltage for the ionization of debris than the known air-cleaning apparatus do. This has the advantage that the inventive air-cleaning apparatus sets free clearly less ozone than the known air-cleaning apparatus.
- 20 A further advantageous embodiment of the invention provides that the inventive air-cleaning apparatus is built as a stand-alone apparatus, wherein the inlet nozzle is located at the upper end and the outlet nozzle at the lower end of the inventive air-cleaner apparatus. Such a measure has the advantage that the inventive air-cleaning apparatus allows in an advantageous manner to suck in air even
- 25 from the upper areas of a room.

Furthermore, the afore-described arrangement yields the advantage that the warm air gathering in the upper areas of a room is transported to the lower area, and reascends after passing through the inventive air-cleaning apparatus and

leaving the lower nozzle. The counter-current built up in this way results in a reduction of the sinking velocity of particles being in the air of the room, so that even heavy particles can be gathered easily and reliably.

5 A further advantageous embodiment of the invention provides that the rim surface of the air-cleaning apparatus surrounding the inlet nozzle has a rounded shape. This measure has the advantage that the flow-conditions in the area of the inlet nozzle are improved.

10 A further advantageous embodiment of the invention provides that the inlet opening of the air-cleaning unit of the inventive air-cleaning apparatus is arranged spaced apart from the inlet nozzle of the housing inside the column-like housing of the air-cleaning apparatus. Such a measure has the advantage that a current-leading element positioned in the free space between the inlet nozzle of the column-like housing and the inlet opening is not visible from the outside and therefore does not affect the advantageous aesthetic impression of the inventive
15 air-cleaning apparatus.

A further advantageous embodiment of the invention provides that a light element is positioned in the space between the inlet nozzle of the column-like housing and the inlet opening. This has the advantage that the inventive air-cleaning apparatus can be used, beside its cleaning function, as a room lighting, too.

20 Exemplary embodiments of the invention are shown in the drawings and will be described in detail below. The drawings show:

Figure 1 a first embodiment of an air-cleaning apparatus,

25 Figure 2 a second embodiment of an air-cleaning apparatus,

Figure 3 a third embodiment of an air-cleaner apparatus,

and

Figure 4 a part of the housing of the air-cleaner apparatus.

The first embodiment of an air-cleaning apparatus 1 shown in Figure 1 comprises
5 a column-like housing 2 with a circular, oval or polygonal cross-section, having
an essentially air-tight outer sheath 2a.

The housing 2 can be mounted on a foot, especially by putting it on the foot, or it
can have holding elements for attaching the housing 2 of the air-cleaning appa-
tus 1 to a wall and/or on the ceiling of a room, especially of a living room.

10 In a first front face 2' of the column-like housing 2 there is an inlet nozzle 3,
through which an air current L to be cleaned is sucked in from the environment of
the air-cleaning apparatus 1. Viewed in the flow direction of the air current L
sucked in, the inlet nozzle 3 is followed by an electrostatic air-cleaning unit 10,
which is preferably spaced apart from the inlet nozzle 3, and which is built
15 column-like or tube-like. An inlet opening 11 is arranged in a first front face 10'
of the electrostatic air-cleaning unit 10 and is aligned with the inlet nozzle 3 of the
column-like housing 2 of the air-cleaning apparatus 1. For this reason, the air cur-
rent L sucked in through the inlet nozzle 3 does not exhibit turbulence and it
therefore can enter the electrostatic air-cleaning unit 10, the exact construction of
20 which is of no interest for the following description, almost without any noise.

After the air current L has passed the electrostatic air-cleaning unit 10, the thus
cleaned air current leaves the air-cleaning unit 10 through an outlet opening 12
provided in a second front face 10" of the air-cleaning unit 10. The outlet opening
12 of the column-like air-cleaning unit 10 is in an advantageous manner aligned

with an outlet nozzle 4 of the column-like housing 2 of the air-cleaning apparatus 1. For this reason, there is an essentially straight flow of the air current in this region, too. In a space 5 between the outlet opening 12 of the column-like air-cleaning unit 10 and the outlet nozzle 4 of the column-like housing 2 there is a fan unit 6 having a radial or an axial blower for effecting the above-mentioned flow of the air current L to be cleaned.

The air-cleaning apparatus 1 described above excels in a very low noise level, as the air current L passing through the air-cleaning column 1 is, due to its essentially straight guidance, well-designed seen from an aerodynamic point of view and almost without any turbulence. For this reason, the air-cleaning apparatus 1 produces very little air noise. As the air-cleaning apparatus 1 has a very low flow resistance, a fan unit 6 having a smaller power consumption than the ones required in conventional air-cleaning apparatus in order to suck in the same amount of air is sufficient in an advantageous way. In a reduction to practice of the described embodiment, being 1.4 metres long and having a radius of 8.5 cm, a noise level has been measured which was below 30 dBA.

The column-like construction of the air-cleaning apparatus 1 has the advantage that in an especially advantageous manner noise reduction elements 15, 16 can be provided especially easy in the apparatus 1, bringing forth a further reduction of the noise level created by the operation of the described air-cleaning apparatus 1. The first noise reduction element 15, being provided in a space 5' between the inlet nozzle 3 of the housing 2 and the inlet opening 11 of the air-cleaning unit 10, effects in an advantageous manner a dampening of the flow noise of the air current L being sucked into the air-cleaning column as well as of the operating noise of the electrostatic air-cleaning unit 10. In a corresponding way, the second noise reduction element 16, being provided in the lower space 5 of the column-like housing 2 between the fan unit 6 and the outlet nozzle 4, dampens the flow noise of the cleaned air current R leaving the air-cleaning apparatus 1 as well as of the operating noise of the fan unit 6 and the electrostatic cleaning unit 10.

A further enhancement of the advantageous properties of the described air-cleaning apparatus 1 is achieved by rounding the rim surface 9 of the housing 2 surrounding the inlet nozzle 3. This measure effects in an advantageous manner not only that an optimized flow of the air current L entering in the air nozzle 3 is achieved. Furthermore, this construction effects that in the environment of the air-cleaning apparatus 1 air is not only sucked in from the region above the inlet nozzle 3, but also from an environment reaching several tens of centimetres below the inlet nozzle 3.

In the space 5' being situated below the inlet nozzle 3 preferably a guide element 20 for the air current is arranged, which in an advantageous way enhances the flow velocity of the air current L in this region, thereby preventing the deposition of debris on the inner surface of the housing 2 in front of the air-cleaning unit 10. It is especially advantageous if the current guide element 20 is provided with a lighting element 21. The air-cleaning apparatus 1 thus constructed is capable of performing a dual function, i.e. it can operate as an air cleaner as well as an lighting device. Furthermore, it is possible, as shown by the second embodiment of Figure 2, to provide the air-cleaning apparatus 1 instead of the current guide element 20 only with a lighting element 21' if one is willing not to employ the advantageous properties of the current guide element 20.

In the description given above, it was assumed the inlet nozzle 3 is arranged at the upper end of the column and the outlet nozzle 4 is arranged at the lower end thereof. In principle, it is possible to reverse the arrangement of the two nozzles 3 and 4, but the described arrangement has the advantage that, due to the guiding of the air current L to be cleaned from top to bottom, mainly the warm air being located in the upper region of the room is sucked in and is led through the column-like air-cleaning apparatus 1 down to the lower region of the room, from which it starts to ascend again. The air current produced thereby reduces in an advantageous way the sinking velocity of particles being present in the air, especially of

heavier particles. Due to this, the heavier particles can be better sucked in and cleaned therefore more efficiently.

In respect to the construction of the first embodiment of the air-cleaning apparatus shown in Figure 1, it must be stated that in the region of the inlet nozzle 3
5 mechanical filter means (not shown) can be provided. Furthermore, it is possible to provide the inlet opening 12 of the air-cleaning unit 10 with a protective mesh 17. A corresponding protective mesh 19 can optionally be arranged in the region of the outlet nozzle 4, too.

The column-like construction of the housing 2 of the air-cleaning apparatus 1 has
10 furthermore the advantage that by this measure it is easily possible to arrange all the equipment which is necessary for the operation of the air-cleaning apparatus (not shown in Figure 1) in the housing 2 itself, without being visible from the outside. For this reason the aesthetic impression of the air-cleaning apparatus 1 is not disturbed. For example, a receiving element of a remote control unit allowing
15 the air-cleaning apparatus to be conveniently controlled can be integrated in the housing 2.

The air-cleaning apparatus 1' depicted in Figure 3 has in principle the same of construction as the embodiments of Figures 1 and 2. For this reason, identical or similar parts are designated with the same reference numerals. The main difference
20 between these two air-cleaning apparatus 1, 1' is given by the fact that in the region of the outlet nozzle 4 of the air-cleaning apparatus 1' a filter unit 30 is arranged. Preferably this filter unit 30 is constructed as a carbon filter and/or as an ozone filter. Furthermore, the filter unit 30 can have an element for the release of a deodorizing substance.

25 It must be stated that the described embodiments of the air-cleaning apparatus 1, 1' only have a single air-cleaning unit 10, which is not absolutely necessary. Rather, it is possible to arrange two or more air-cleaning units 10 in the housing

2, which are then preferably arranged parallel to each other. It is also possible to arrange the air-cleaning unit 10 spiral-like in the housing 2 in order to have a longer air path in the electrostatic air-cleaning unit 10 resulting in a higher degree of purification. It does not require any further mentioning that in the housing 2 two
5 or more spiral-like air-cleaning units 10 can be arranged.

In Figure 4 a segment 40 is shown, which is suited in an especially advantageous manner for the construction of the housing 2 of the described air-cleaning apparatus 1, 1'. The segment-like construction of the housing 2 has the advantage that it facilitates an easy pre-mounting of the air-cleaning unit 10 as well as the further
10 equipment co-operating with the air-cleaning unit 10, i.e. before the housing 2 is put around such pre-fabricated components. Each of the at least two segments 40 of the housing 2 has on its two longitudinal edges connecting elements 41a, 41b for putting together the two segments 40 to form the housing 2. It is of advantage that the first connecting element 41a is formed like a hook-like protrusion 42
15 and that the adjacent connecting element 41b of the following segment is an element 43 formed complementary to the hook-form of the first connecting element 41a and engaging the hook-like protrusion.

This Sheet Has Been Replaced



- 11 -

Claims

1. An air-cleaning apparatus, especially an electrostatic air-cleaning apparatus, having a housing, in which an inlet nozzle (3) and an outlet nozzle (4) are provided for an air-current (L) to be cleaned, which is led to an air-cleaning unit (10) being arranged in said housing, wherein said housing (2) of said air-cleaning apparatus (1; 1') has a column-like shape, and wherein said column-like housing (2) comprises an essentially air-tight outer sheath (2a), characterized in that said inlet nozzle (3) for said air-currents (L) to be cleaned is provided in a first front face (2') of said column-like housing (2) and the outlet nozzle (4) is provided in the other front face (2'') of said column-like housing (2), that said air-cleaning unit (10) provided in said column-like housing (2) is formed tube-like, that an inlet opening (11) of said air-cleaning unit (10) is provided at one of its front faces (10') and is aligned with said inlet nozzle (3) of said column-like housing (2), and that an outlet opening (12) of said air-cleaning unit (10) is provided at its other front face (10'') and is aligned with said outlet nozzle (4) of said column-like housing (2) of said air-cleaning apparatus (1; 1').
2. The air-cleaning apparatus according to claim 1, characterized in that said inlet nozzle (3) is provided in the upper one (2') of said two front faces (2'; 2'') of said column-like housing (2) of said air-cleaning apparatus (1; 1').
3. The air-cleaning apparatus according to one of claims 1 or 2, characterized in that a rim face (9) of said column-like housing (2) surrounding said inlet nozzle (3) has a rounded shape.





4. The air-cleaning apparatus according to one of claims 1-3, characterized in that said inlet opening (11) of said air-cleaning unit (10) is spaced apart, in the flow direction of said air current (L), from said inlet nozzle (3).
5. The air-cleaning apparatus according to one of claims 1 to 4, characterized in that a current guide element (20) is provided in front of said inlet opening (11) of said air-cleaning unit (10).
6. The air-cleaning apparatus according to one of claims 1 to 5, characterized in that a lighting element (21) is provided in a space (5') of said housing (2) between said inlet nozzle (3) and said inlet opening (11).
- 10 7. The air-cleaning apparatus according to one of claims 1 to 6, characterized in that a noise reduction element (15) is mounted at least between said inlet nozzle (3) of said housing (2) and said inlet opening (11) of said air-cleaning unit (10).
- 15 8. The air-cleaning apparatus according to one of claims 1 to 7, characterized in that a noise reduction element (16) is mounted at least between said outlet nozzle (4) of said housing (2) and said outlet opening (12) of said air-cleaning unit (10).
- 20 9. The air-cleaning apparatus according to one of claims 1 to 8, characterized in that a fan-unit (6) is provided in front of said outlet nozzle (4) of said column-like housing (2).
10. The air-cleaning apparatus according to one of the proceeding claims, characterized in that said outlet opening (12) of said air-cleaning unit (10) is





spaced apart, in the flow direction, from said outlet nozzle (4) of said column-like housing (2) of said air-cleaning apparatus (1; 1').

- 5 11. The air-cleaning apparatus according to one of claims 1 to 10, characterized in that a filter unit (30) is provided in said housing (2) of said air-cleaning apparatus (1').
12. The air-cleaning apparatus according to claim 11, characterized in that said filter unit (30) is a carbon filter and/or an ozone filter.
- 10 13. The air-cleaning apparatus according to one of the proceeding claims, characterized in that an element for the release of a deodorising substance is provided in said housing (2) of said air-cleaning unit (1).
14. The air-cleaning apparatus according to claims 1 to 13, characterized in that said air-cleaning unit (10) is an electrostatic air-cleaning unit.
- 15 15. The air-cleaning apparatus according to one of the proceeding claims, characterized in that said column-like housing (2) of said air-cleaning apparatus (1; 1') has a circular, oval or polygonal cross section.
16. The air-cleaning apparatus according to one of the proceeding claims, characterized in that said column-like housing (2) of said air-cleaning apparatus (1; 1') is mountable on a foot.
- 20 17. The air-cleaning apparatus according to claims 1 to 16, characterized in that holding elements are provided on said housing (2) of said air-cleaning



This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

- 14 -

apparatus (1), by which said housing (2) of said air-cleaning apparatus (1; 1') can be fixed on a wall and/or a ceiling, especially of a living room.

18. The air-cleaning apparatus according to one of the proceeding claims, characterized in that at least two of said air-cleaning units (10) are provided in said housing (2).
- 5



* C L M S *