

Fragmentation sleeve for an ammunition body**BACKGROUND OF THE INVENTION****1. Field of the Invention**

The invention relates to a fragmentation sleeve according to the preamble of claim 1.

2. Description of the Related Art

A fragmentation type weapon is known from US 3,263,612 THRONER with two groups of discrete cubic slugs made of steel and where one group of slugs comprises a plurality of uniformly sized slugs differing in size from the slugs in the other group, the slugs being assembled in a cementitious matrix of plastic material thereby providing an outer hollow cylindrical shell for the explosive charge which is entirely encased by that shell.

The larger fragments of the one group have a weight of 140 gran (corresponding to 8.4 grams) and the smaller fragments of the second group have a weight of 30 gran (corresponding to 1.8 grams), i.e. THRONER discloses discrete cubical fragments in different large/weight.

From US 7,004,075 RONN ET AL. An ammunition unit is known comprising a plurality of exchangeable warhead modules to be fixed on the casing of the ammunition body by means of securing devices or retention parts. The modules have the shape of curved, relatively narrow segments arranged longitudinally on the generally cylindrical ammunition body. One module may contain uniformly large spherical pellets and another module may contain uniformly small spherical pellets.

BRIEF SUMMARY OF THE INVENTION

It is an object of the invention to provide a fragmentation sleeve for an ammunition body allowing a high degree of flexibility in the geometrical configuration of an ammunition body due to the different configuration of the sleeve allowing the rapid adaptation of the distribution, concentration and/or direction of fragments.

The invention solves the posed problem with a fragmentation sleeve comprising the features of claim 1.

The advantages of the fragmentation sleeve according to the invention are the following:

- optimal adaptability to the actual need of a certain type of ammunition based on standard ammunition which can be adapted to the battlefield requirements quickly and reliably due to its modularity;
- the flexibility of the geometrical configuration of the sleeve allows the use of an ammunition body with such sleeve in already existing systems;
- possibility of manufacturing of weight-optimized systems being of particular relevance for systems for guided missiles.

Further advantageous embodiments of the invention can be commented as follows:

In a special embodiment the fragmentation sleeve has the shape of a hollow cylinder.

In another embodiment the fragmentation sleeve has the shape of double hollow cone, a single hollow spherical zone or a multiple hollow spherical zone.

In a further embodiment the fragmentation sleeve is provided with a place holding annular element having an outside surface matching the inner surface of the sleeve and an internal surface, which is circular cylindrical for contacting a generally circular cylindrically shaped ammunition body.

In a special embodiment of the present invention the fragments consist of steel and have a mean weight in the range of 0.10 to 0.17 grams. This embodiment allows that advantage of good-controlled filling degree due to the matter that the fragments have similar weights, which in combination with the form of the sleeve, allows the advantage of the high degree of flexibility of the configuration of the region of effect. By using of materials with a higher density lies the mean weight in a higher range. The mean weight and the size of the fragments can also vary depending on the task of the fragmentation sleeve (e.g. air-to-air-missile).

In a further embodiment the polymeric matrix of the fragmentation sleeve is based on an epoxy resin, polyester and/or polyurethane.

In a further embodiment the polymeric matrix is fiber reinforced, preferably with glass fiber and/or carbon fiber.

In another embodiment the plurality of fragments of the fragmentation sleeve comprise at least two different types of fragments.

In a further embodiment one type of fragments has essentially spherical shape and the other type of fragments has a non-spherical, preferably cuboid, parallelepipedic or tetrahedral shape.

In a further embodiment at least two different types of fragments comprise different materials.

In a further embodiment the at least two different type of fragments are arranged in a single plane of the internal surface S_i of the sleeve.

In another embodiment the at least two different type of fragments are arranged over each other.

In a further embodiment the plurality of fragments comprise a metal, metallic alloy or metal carbide, preferably steel, tungsten, tungsten carbide or aluminum.

In another embodiment the $V_F:V_M$ ratio between the total volume V_F of the fragments and the total volume V_M of the polymeric matrix is in the range of 0.5 and 0.9, preferably in the range of 0.6 and 0.75.

In a special embodiment of an assembly of at least one fragmentation sleeve and a generally circular cylindrically shaped ammunition body having a central axis X , the length L measured parallel to the central axis X and diameter D , the diameter D is at no place larger than D_i and preferably equal to D_i .

In a further embodiment of the assembly the height H of the annular sleeve is smaller than the length L of the ammunition body and preferably is less than 20 % of L .

In a further embodiment the assembly comprises N sleeves positioned longitudinally relative to the central axis X , whereby $N \geq 2$.

In a further embodiment the assembly comprises N sleeves positioned at least partially on each other relative to the central axis X , whereby $N \geq 2$.

In a further embodiment the ammunition body comprises a hollow charge which is comprised in a casing with the outer surface.

In a further embodiment the ammunition body is chosen from the group of non-barrel based ammunition, and in particular is a bomb, rocket or missile.

In a special embodiment of the manufacture of the assembly of at least one fragmentation sleeve and the shaped ammunition body the sleeve is slid over the body and positioned on an outer surface of the body.

In a further embodiment of the manufacture the sleeve is selected from a plurality $P \geq 2$ of sleeves, whereby at least one sleeve of the plurality P comprises fragments comprising a first material M_1 and at least one further sleeve of the plurality P comprises fragments comprising a second material M_2 , whereby M_1 and M_2 are different materials. This embodiment allows high variability by manufacturing in relation of election of materials (steel, tungsten, molybdenum or other heavy metals as well as light metals or also plastic materials).

In a special embodiment the kit comprising a generally circular cylindrically shaped ammunition body and a plurality $P \geq 2$ of fragmentation sleeves, whereby at least one sleeve of the plurality P comprises fragments comprising a first material M_1 and at least one further sleeve of the plurality P comprises fragments comprising a second material M_2 , whereby M_1 and M_2 are different materials.

Definitions:

"Fragments": The term "fragments" means in the present specification any pre-shaped fragmentations or splinters made of various hard or hardenable materials.

A BRIEF DESCRIPTION OF THE DRAWINGS

Several embodiments of the invention will be described in the following by way of example and with reference to the accompanying drawings in which:

Fig. 1 illustrates schematically a perspective view of an embodiment of the fragmentation sleeve according to the invention mounted on a conventional hollow charge war head;

Fig. 2 illustrates schematically a view of a partial cross-section of the fragmentation sleeve of Fig. 1.

Fig. 3 – 6 illustrate various geometrical shapes of fragmentation sleeves in cross-section according to the invention.

DETAILED DESCRIPTION OF THE INVENTION

Fig. 1 illustrates an essentially circular cylindrically shaped ammunition body 2 comprising a hollow charge 6. The hollow charge 6 is comprised in a casing 7 having an outer surface 3. A fragmentation sleeve 1 is positioned on the outer surface 3 of the body 2. The sleeve 1 is annular and has a shape of a double hollow cone. The sleeve has an outer diameter D_a and an inner diameter being at no place smaller than D_i which is essentially equal to the diameter D of the ammunition body 2.

Fig. 2 illustrates schematically the cross-section of the ammunition body 2 having an outer surface 3. An annular fragmentation sleeve 1 having the shape of a double hollow cone is positioned on the outer surface 3 of the body 2. The sleeve 1 comprises a plurality of fragments 4 being embedded in a polymeric matrix 5. As shown in fig. 2 the

fragmentation sleeve 1 further comprises a place holding element 12. The place holding element 12 has an essentially annular shape and comprises an outside surface 13 matching the inner surface of the fragmentation sleeve 1 and an internal surface 14 being circular cylindrical and matching the outer surface 3 of the circular cylindrical ammunition body 2.

Fig. 3 illustrates schematically a special embodiment of the present invention according to which the fragmentation sleeve 1 has a shape of a hollow cylinder 8. According to this embodiment the sleeve has a constant inner diameter D_i and a constant outer diameter D_a . The inner surface of the cylindrical sleeve 8 matches the outside surface of the ammunition body 2. According to this embodiment the sleeve 1 does not comprise any place holding element.

Fig. 4 illustrates schematically a further special embodiment of the present invention according to which the fragmentation sleeve 1 has a shape of a double hollow cone 9. According to this embodiment the sleeve has an outer diameter varying over its external surface and an inner diameter varying over its internal surface. The inner diameter of the fragmentation sleeve is at no place smaller than D_i , whereby D_i is equal to the diameter D of the circular cylindrically shaped ammunition body 2. The embodiment of the sleeve 1 according to fig. 4 comprises a place holding element 12 having an outside surface 13 and an internal surface 14. The outside surface 13 of the place holding element 12 matches the internal surface of the sleeve. The internal surface 14 of the place holding element is circular cylindrical and matches the outer surface of the body 2.

Fig. 5 illustrates schematically another embodiment of the present invention according to which the fragmentation sleeve 1 has a shape of a single hollow spherical zone 10. According to this embodiment the sleeve 1 has an outer diameter varying over its external surface and an inner diameter varying over its internal surface. The inner diameter is at no place smaller than D_i , which is equal to the diameter of D of the circular cylindrically shaped ammunition body 2. The embodiment of the sleeve 1 according to fig. 5 comprises a place holding element 12 having an outside surface 13 and an internal surface 14. The outside surface 13 of the place holding element 12

matches the internal surface of the sleeve. The internal surface 14 of the place holding element 12 is circular cylindrical and matches the outer surface of the body 2.

Fig. 6 illustrates schematically a further embodiment of the present invention according to which the fragmentation sleeve 1 has a shape of a double hollow spherical zone 11. According to this embodiment the sleeve 1 has an outer diameter varying over its external surface and an inner diameter varying over its internal surface. The inner diameter of the fragmentation sleeve is at no place smaller than D_i , whereby D_i is equal to the diameter of D of the circular cylindrically shaped ammunition body 2. The embodiment of the sleeve 1 according to fig. 6 comprises a place holding element 12 having an outside surface 13 and an internal surface 14. The outside surface 13 of the place holding element 12 matches the internal surface of the sleeve. The internal surface 14 of the place holding element 12 is circular cylindrical and matches the outer surface of the body 2.

Although the invention has been described in conjunction with specific embodiments thereof, it is evident that many alternatives, modifications and variations will be apparent to those skilled in the art. Accordingly, it is intended to embrace all such alternatives, modifications and variations that fall within the scope of the appended claims.

It is appreciated that certain features of the invention, which are, for clarity, described in the context of separate embodiments, may also be provided in combination in a single embodiment. Conversely, various features of the invention, which are, for brevity, described in the context of a single embodiment, may also be provided separately or in any suitable subcombination or as suitable in any other described embodiment of the invention. Certain features described in the context of various embodiments are not to be considered essential features of those embodiments, unless the embodiment is inoperative without those elements.

COPY

3232/PCT (11.11.2016)

CLAIMS

(amended according to Art. 19 PCT)

1. Fragmentation sleeve (1), for a generally circular cylindrically shaped ammunition body (2), the sleeve
 - a) having an annular shape with an inner diameter at no place smaller than D_i , an outer diameter D_a , an internal surface S_i , an external surface S_a , and a height H ; and
 - b) being configured to be slid over and positioned on an outer surface (3) of an ammunition body (2); and
 - c) comprising a plurality of fragments (4) embedded in a polymeric matrix (5),
characterized in that
 - d) the sleeve has the shape of double hollow cone (9), a single hollow spherical zone (10) or a multiple hollow spherical zone (11).
2. Fragmentation sleeve (1) according to claim 1, characterized in that it is provided with a place holding annular element (12) having
 - (i) an outside surface (13) matching the inner surface S_i of the sleeve (1) and
 - (ii) an internal surface (14), which is circular cylindrical for contacting a generally circular cylindrically shaped ammunition body (2).
3. Fragmentation sleeve (1) according to claim 1 or 2, characterized in that the polymeric matrix (5) is based on an epoxy resin, polyester and/or polyurethane.
4. Fragmentation sleeve (1) according to one of the claims 1 to 3, characterized in that the polymeric matrix (5) is fiber reinforced, preferably with glass fiber and/or carbon fiber.
5. Fragmentation sleeve (1) according to one of the claims 1 to 4, characterized in that the plurality of fragments (4) comprise at least two different types of fragments.

6. Fragmentation sleeve (1) according to claim 5, characterized in that one type of fragments has essentially a spherical shape and the other type of fragments has a non-spherical, preferably cuboid, parallelepipedic or tetrahedral shape.
7. Fragmentation sleeve (1) according to claim 5 or 6, characterized in that the at least two different types of fragments comprise different materials.
8. Fragmentation sleeve (1) according to one of the claims 5 to 7, characterized in that the at least two different type of fragments are arranged in a single plane of the internal surface S_i of the sleeve (1).
9. Fragmentation sleeve (1) according to one of the claims 5 to 7, characterized in that the at least two different type of fragments are arranged over each other.
10. Fragmentation sleeve (1) according to one of the claims 1 to 9, characterized in that the plurality of fragments comprise a metal, metallic alloy or metal carbide, preferably steel, tungsten, tungsten carbide or aluminum.
11. Fragmentation sleeve (1) according to one of the claims 1 to 10, characterized in that the ratio $V_F:V_M$ between the total volume V_F of the fragments and the total volume V_M of the polymeric matrix is in the range of 0.5 and 0.9, preferably in the range of 0.6 and 0.75.
12. Assembly of at least one fragmentation sleeve according to one of the claims 1 to 11 and a generally circular cylindrically shaped ammunition body (2) having a central axis X, the length L measured parallel to the central axis X, an outer surface (3) and a diameter D, characterized in that D is at no place larger than D_i and preferably equal to D_i .
13. Assembly according to claim 12, characterized in that the height H of the annular sleeve (1) is smaller than the length L of the body (2), and preferably is less than 20 % of L.

14. Assembly according to claim 12 or 13, characterized in that it comprises N sleeves according to one of the claims 1 to 11 positioned longitudinally relative to the central axis X, whereby $N \geq 2$.

15. Assembly according to one of the claims 12 to 14, characterized in that it comprises N sleeves according to one of the claims 1 to 11 positioned at least partially on each other relative to the central axis X, whereby $N \geq 2$.

16. Assembly according to one of claims 12 to 15, characterized in that the ammunition body (2) comprises a hollow charge (6) which is comprised in a casing (7) with the outer surface (3).

17. Assembly according to one of the claims 12 to 16, characterized in that the ammunition body (2) is chosen from the group of non-barrel based ammunition, and in particular is a bomb, rocket or missile.

18. Manufacture of the assembly according to one of the claims 12 to 17, characterized in that the sleeve (1) according to one of the claims 1 to 11 is slid over the body (2) and positioned on the outer surface (3) of the body (2).

19. Manufacture according to claim 18, characterized in that the sleeve (1) is selected from a plurality $P \geq 2$ of sleeves, and that at least one sleeve of the plurality P comprises fragments (4) comprising a first material M_1 and at least one further sleeve of the plurality P comprises fragments (4) comprising a second material M_2 , whereby M_1 and M_2 are different materials.

20. Kit comprising a generally circular cylindrically shaped ammunition body (2) according to one of the claims 12 to 17 and a plurality $P \geq 2$ of fragmentation sleeves (1) according to one of the claims 1 to 11, whereby at least one sleeve (1) of the plurality P comprises fragments (4) comprising a first material M_1 and at least one further sleeve (1) of the plurality P comprises fragments (4) comprising a second material M_2 , whereby M_1 and M_2 are different materials.

21. Use of the fragmentation sleeve (1) according to one of the claims 1 to 11, as fragmentation device slideable on a standard type of a generally circular cylindrical shaped ammunition body (2) as adaption to the actual need of the battlefield requirements.