


03 NOV 2004

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
8 January 2004 (08.01.2004)

PCT

(10) International Publication Number
WO 2004/002745 A1

(51) International Patent Classification⁷: **B41J 2/05**,
2/045, B81B 7/02, 7/04

(21) International Application Number:
PCT/AU2002/001163

(22) International Filing Date: 29 August 2002 (29.08.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10/183,174 28 June 2002 (28.06.2002) US

(71) Applicant (for all designated States except US): **SILVERBROOK RESEARCH PTY. LTD.** [AU/AU]; 393 Darling Street, Balmain, New South Wales 2041 (AU).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **SILVERBROOK, KIA** [AU/AU]; Silverbrook Research Pty Ltd, 393 Darling Street, Balmain, New South Wales 2041 (AU).

(74) Agent: **SILVERBROOK, KIA**; Silverbrook Research Pty Ltd, 393 Darling Street, Balmain, New South Wales 2041 (AU).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:


— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.



162162

(54) Title: INK JET PRINthead CHIP WITH PREDETERMINED MICRO-ELECTROMECHANICAL SYSTEMS HEIGHT



(57) Abstract: An inkjet printhead chip includes a wafer substrate (12). A CMOS drive circuitry layer is positioned on the wafer substrate. A plurality of nozzle arrangements is positioned on the wafer substrate and the CMOS drive circuitry layer. Each nozzle arrangement includes nozzle chamber walls and a roof wall that define a nozzle chamber and an ink ejection port (35) defined in the roof wall. A micro-electromechanical actuator (14) is connected to the CMOS drive circuitry layer. The actuator has at least one movable member (14) that is positioned to act on ink in the nozzle chamber to eject the ink from the ink ejection port on receipt of a signal from the drive circuitry layer. The movable member is spaced between 2 microns and 15 microns from the CMOS drive circuitry layer.



ACTION

WO 2004/002745 A1