

PRIORITIZATION AND FLOW CONTROL OF A SPREAD SPECTRUM MULTIUSER CHANNEL

BACKGROUND

The invention generally relates to channels used by multiple users in a wireless code division multiple access spread spectrum system. More specifically, the invention relates to a system and method of prioritizing and controlling the flow of data for common and shared channels in a spread spectrum system.

Figure 1 illustrates a simplified wireless spread spectrum code division multiple access (CDMA) communication system 18. A node b 26 within the system 18 communicates with associated user equipment 20-24 (UE). The node b 26 has a single site controller (SC) 30 associated with either a single (shown in Figure 1) or multiple base stations 28. A Group of node bs 26, 32, 34 is connected to a radio network controller (RNC) 36. To transfer communications between RNCs 36-40, an interface between the RNCs (IUR) 42 is utilized. Each RNC 36-40 is connected to a mobile switching center (MSC) 44 which in turn is connected to the core network 46.

To communicate within the system 18, many types of communication channels are used, such as dedicated, shared and common. Dedicated channels transfer data between a node b 26 and a particular UE 20-24. Common and shared channels are used by multiple UEs 20-24 or users. All of these channels carry a variety of data including traffic, control and signaling data.

Since shared and common channels carry data for different users, data is sent using protocol data units (PDUs) or packets. As shown in Figure 2, to regulate the flow of data from differing sources 48-52 into a channel 56, a controller 54 is used.

One common channel used for transmitting data to the UEs 20-24 is the forward access common channel (FACH) 58. As shown in Figure 3, the FACH 58 originates in a RNC 36 and is sent to a node b 28-34 for wireless transmission as a spread spectrum signal to the UEs 20-24. The FACH 58 carries several data types from various sources, such as a common control channel (CCCH), dedicated control and traffic channel (DCCH and DTCH), and a downlink and uplink share channel (DSCH and USCH) control signaling. The FACH 58 also carries control signaling out of band, such as hybrid automatic repeat request (H-ARQ), and similar data transmitted via the IUR 62 from other RNCs 38-40, such as CCCH, DCCH, DTCH and H-ARQ control data.

Various controllers are used by the RNC 36 to control the flow of data. A radio link controller (RLC) 64 handles the CCCH. The dedicated medium access controller (MAC-d) 66 handles the DCCH, the DTCH and some out of band H-ARQ signaling. The shared medium access controller (MAC-sh) 68 handles the DSCH, USCH control signaling and out of band H-ARQ control signaling. Controlling the FACH 58 is the common medium access controller (MAC-c) 60.

Due to the multiple sources of data 48-52 that can be transmitted over a common or shared channel, the channel controllers 54 queue the data prior to transmission. If a large backlog develops in the queue, data in the queue develops

a latency. A large latency of certain data such as control data will result in the failure of a channel. To alleviate this problem, the prior art either flushed the queue to reduce congestion or rerouted the data. Flushing the queue results in the loss of data and requires retransmission which is undesirable. Rerouting data already queued creates a duplication of data within the system and does not resolve the existing congestion.

WO 96/08935 discloses a prioritization scheme for a GSM system. Different types of packets are given a priority for transmission over a common channel. The data packets are sent over the common channel based on their priority.

U.S. Patent No. 5,802,310 discloses a system for data queue control in a communications network. Data is transferred to a queue for a channel. The queue is disabled when the amount of queued data is greater than the first limit and the queue is enabled when the amount of queued data is less than a second threshold. According, it is desirable to reduce the latency of data for shared and common channels without the problems associated with the prior art.

SUMMARY

Packet data from a plurality of sources is received at a controller associated with the multiuser channel. Each packet of the packet data is prioritized based on in part the reroutability of a class of data types. Each packet is scheduled for transmission over the multiuser channel based on in part the prioritization. A backlog of packet data queued is tracked for transfer over the multiuser channel.

Based on in part the tracked queue, the flow of data from each data source is limited.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a simplified illustration of a wireless spread spectrum communication system.

Figure 2 is an illustration of data flowing into a common or shared channel.

Figure 3 is an illustration of data flowing into a FACH channel within a RNC.

Figure 4 is an illustration of a prioritization scheme.

Figure 5 is a prioritization scheme for use with a FACH channel.

Figure 6 depicts a reservation mechanism used with a common or shared channel.

Figure 7 depicts data source windows used with a common or shared channel.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Data prioritization 70 is used to reduce data latency in a multiuser channel controller 54 as illustrated in Figure 4. For a particular common or shared channel, certain data must be transmitted on that channel and is shown in the figure as "mandatory" 88. Other data is preferably sent on the particular channel but may be rerouted to another channel, such as a dedicated channel. This data is referred to as "best effort" 90. Since "mandatory" data 88 is not reroutable, it takes priority over "best effort" data 90.

15

The type of the data within a packet, such as control 96, signaling 98 and traffic data 100, is also used for prioritization. To accomplish prioritization of the data type, control 96 and signaling 98 data packets are separated from traffic data packets 100. One approach to separating the packets is to group similar data type packets together prior to reception at the controller 54. Alternately, packets sent by each channel prior to reception by the controller 54 are provided with a flag or identifier indicating the packets' data type.

Since a prolonged delay in the transfer of control 96 or signaling 98 data results in a frozen channel, control 96 and signaling 98 data are given a higher priority than traffic data 100. Additionally, data associated with multiple users, common or shared 92, has a higher priority than data for a single user, dedicated 94. The data prioritization scheme is typically stored in the software of the multiuser channel's controller.

During periods of high congestion, data is rerouted to other channels based on its priority 70. For instance, best effort dedicated traffic data is rerouted and mandatory common control data is not. By rerouting data prior to queuing, retransmissions will not be required. Accordingly, the amount of queued data is reduced resulting in lower data latency. Additionally, since the rerouted data is never queued, the duplication of data as experienced in the prior art is eliminated.

A prioritization scheme 72 for use with a FACH 58 is shown in Figure 5. Since the DSCH, H-ARQ of the MAC-sh have mandatory shared control data, they have the highest priority, highest. Although the H-ARQ of the MAC-d has mandatory control data, being dedicated it is assigned a slightly lower priority, high.

The CCCH and DCCH are used for signaling and have the next level of priority, medium. The lowest level of priority is assigned to the DTCH because it has best effort dedicated traffic data.

To facilitate this prioritization scheme 72 for the FACH 58, modifications to the RNC 36 are required. As shown in Figure 3, the prior art MAC-d 66 controls the DCCH, DTCH and MAC-d's H-ARQ. As shown in Figure 5, each of these sources has a different priority. Since this data is multiplexed prior to prioritization at the MAC-d 66, the multiplexer of the MAC-d 66 is moved to the MAC-c 60 to allow prioritization at the MAC-c 60. Alternatively, the MAC-d 66 may send the priority and class (mandatory or best effort), such as by a flag or identifier, of each packet of the multiplexed data for prioritization at the MAC-c 60. The data controlled by the RLC 64 and the MAC-sh 68 have equal priority and accordingly, neither requires modification. Using the stored priority list, the data from the various sources is scheduled for transmission and rerouted during periods of high congestion.

Another technique for reducing the latency of data which may be combined with prioritization is to control the flow of data between the various controllers. As shown in Figure 6, a scheduling mechanism 74 is used to regulate the data entering the common or shared channel 56. The scheduling mechanism 74 tracks the backlog of data in the controller's queue. If the mechanism 74 recognizes congestion and that the data will not be transmitted in a certain period of time, access to the channel 56 limits the flow of data from the individual data sources. The individual sources will recognize the need to reroute data or to not attempt transmission. Using a flow

control mechanism with a FACH, MAC and RLC (Layer 2), the latency of signaling is decreased thus increasing efficiency.

To prevent the monopolization of the common or shared channel 56 by one data source 48-52 variable windows 76-86 may be used as shown in Figure 7. Each data source 48-52 has a window or multiple windows 76-86 of outstanding data in the queue that it is permitted. The size of the window 76 is based on the requirements of the specific source. The window 76 is dynamically adjusted in response to the availability of the queue. As the availability of the channel increases, the size of the windows increases which increases the number of outstanding packets. Conversely, as the availability decreases, the size of the windows decreases which decreases the number of outstanding packets. As a result of the decreased windows, the data sources either reroute or stop sending packets to the windows.

*

*

*

1. A code division multiple access (CDMA) communication device comprising:

a first medium access controller (MAC) entity configured to output a first control channel and a dedicated traffic channel (DTCH), the first MAC entity being a MAC-dedicated (MAC-d) entity and the first control channel being a dedicated control channel (DCCH); and

a second MAC entity configured to generate an access channel, the second MAC entity including:

a channel multiplexer configured to receive data, the data being carried by the first control channel, the DTCH, and a second control channel, the channel multiplexer also being configured to multiplex the received data;

a scheduling mechanism configured to receive the multiplexed data and schedule the multiplexed data for transmission on the access channel according to a priority of the received data; and

a flow control entity configured to limit buffering of a portion of the received data in the second MAC entity, the portion of the received data being associated with the first control channel and the DTCH, wherein the access channel is a forward access channel (FACH).

2. The CDMA communication device of claim 1, wherein the second MAC entity is further configured to limit an amount of the multiplexed data transmitted on the access channel.

3. The CDMA communication device of claim 1, wherein the second MAC entity is further configured to limit a portion of the multiplexed data transmitted on the access channel based on whether the portion of the multiplexed data is associated with the first control channel, the second control channel, or the DTCH.

4. The CDMA communication device of claim 1, wherein a window is associated with each of the first control channel, the second control channel, and the DTCH, the second MAC entity is further configured to limit an amount of the multiplexed data transmitted on the access channel by controlling a size of the window associated with said each of the first control channel, the second control channel, and the DTCH.

5. The CDMA communication device of claim 1, wherein the scheduling mechanism is further configured to schedule the multiplexed data for transmission over a downlink shared channel (DSCH).

6. The CDMA communication device of claim 1, wherein the received data includes an indicator of the priority.

7. The CDMA communication device of claim 1, wherein the communication device is a radio network controller (RNC).

8. The CDMA communication device of claim 1, wherein the scheduling mechanism is configured to supply the access channel to a Node-B, such that the Node-B transmits the access channel to a plurality of user equipments (UEs).

9. A communication method, comprising:
outputting a first control channel and a dedicated traffic channel (DTCH) with a first medium access controller (MAC) entity, the first MAC entity being a MAC-dedicated (MAC-d) entity, and the first control channel being a dedicated control channel (DCCH);

receiving the first control channel, the DTCH, and a second control channel, with a channel multiplexer of a second MAC entity, the first control channel, the second control channel, and the DTCH carrying data, and the second MAC entity being configured to output an access channel;

multiplexing the data with the channel multiplexer;

 scheduling, with a scheduling mechanism of the second MAC entity, the multiplexed data for transmission on the access channel according to a priority of the multiplexed data; and

 limiting buffering of a portion of the received data in the second MAC entity, the portion of the received data being associated with the first control channel and the DTCH, wherein the access channel is a forward access channel (FACH).

10. The communication method of claim 9, further comprising limiting an amount of the multiplexed data transmitted on the access channel.

11. The communication method of claim 9, further comprising limiting a portion of the multiplexed data transmitted on the access channel based on whether the portion of the multiplexed data is associated with the first control channel, the second control channel, or the DTCH.

12. The communication method of claim 9, wherein a window is associated with each of the first control channel, the second control channel, and the DTCH, the method further comprising limiting an amount of the multiplexed data transmitted on the access channel by controlling a size of the window associated with said each of the first control channel, the second control channel, and the DTCH.

13. The communication method of claim 9, further comprising scheduling the multiplexed data for transmission over a downlink shared channel (DSCH).

14. The communication method of claim 9, wherein the data includes an indicator of the priority.

15. The communication method of claim 9, wherein the communication device is a radio network controller (RNC).

16. The communication method of claim 9, further comprising supplying the access channel to a Node-B, such that the Node-B transmits the access channel to a plurality of user equipments (UEs).