

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
20 November 2008 (20.11.2008)


PCT

(10) International Publication Number
WO 2008/138345 A1

- (51) International Patent Classification:
B04B 1/20 (2006.01)
- (21) International Application Number:
PCT/DK2008/050102
- (22) International Filing Date: 8 May 2008 (08.05.2008)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
PA 2007 00697 9 May 2007 (09.05.2007) DK
- (71) Applicant (for all designated States except US): **ALFA LAVAL CORPORATE AB** [SE/SE]; Box 73, S-22100 Lund (SE).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **MADSEN, Bent** [DK/DK]; Snogegårdsvej 29A, DK-2820 Gentofte (DK). **DIRCKS, Klaus** [DK/DK]; Gothersgade 93, DK-1123 Copenhagen K (DK).
- (74) Agents: **JØRGENSEN, Bjørn, Barker et al.**; Rigersgade 11, DK-1316 København K (DK).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: A CENTRIFUGAL SEPARATOR AND A LIQUID PHASE DISCHARGE PORT MEMBER



(57) Abstract: A centrifugal separator (1) comprises a bowl (2) rotating in use around an axis of rotation (5). The axis of rotation extends in a longitudinal direction of said bowl, and a radial direction (5a) extends perpendicular to the longitudinal direction. A base plate (6) is provided at one longitudinal end of the bowl, said base plate having an internal side (7) and an external side (8), an outlet opening (9) being provided in the base plate. A casing (33) is projecting at the outlet opening on the external side of said base plate, said casing comprising a casing side (34), a normal (35) to said casing side extending at an acute angle (β) relative to a circumferential direction of the bowl at said casing and a discharge opening (36) is provided in said casing side. The discharge opening is radially outwardly limited by a weir (45) with an overflow edge (39) and said discharge opening extending radially inwardly to a position above a highest intended level of liquid in the bowl.



Declaration under Rule 4.17:

— *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))*

Published:

— *with international search report*