

METHOD, APPARATUS, AND ELECTRONIC DEVICE FOR RESOURCE ALLOCATION BASED ON BLOCKCHAIN

TECHNICAL FIELD

[0001] Implementations of the present specification relate to the field of blockchain
5 technologies, and in particular, to methods, apparatuses, and electronic devices for
resource allocation based on blockchain.

BACKGROUND

[0002] Blockchain technology, also known as distributed ledger technology, is an
emerging technology in which several computing devices participate in
10 "bookkeeping" and jointly maintain a complete distributed database. Because
blockchain technology is characterized by being decentralized, open and transparent,
enabling each computing device to participate in database recording, and enabling
data synchronization to be performed quickly between the computing devices,
blockchain technology is widely used in many fields.

SUMMARY

[0003] Implementations of the present specification provide methods, apparatuses,
and electronic devices for resource allocation based on blockchain.

[0004] According to a first aspect of the implementations of the present
specification, a method for resource allocation based on a blockchain, where the
20 blockchain stores a mapping relationship between a digital digest of an invoice and a
resource allocation state corresponding to the invoice is provided, the method
including: receiving a target transaction submitted by a client to participate in
resource allocation based on a target invoice; in response to the target transaction,
calculating a digital digest of the target invoice, and querying a resource allocation
25 state stored in the blockchain and corresponding to the digital digest; and if the
detected resource allocation state is an unallocated state, invoking resource allocation
logic declared in a smart contract published in the blockchain, to allocate resources to

the client from a predetermined resource pool based on a predetermined allocation rule, and returning a resource allocation result to the client.

[0005] Optionally, the method further includes: receiving an invoice creation request submitted by the client, the invoice creation request including invoice creation information input by a user; in response to the invoice creation request, invoking invoice creation logic declared in the smart contract published in the blockchain to create an invoice based on the invoice creation information; and, calculating a digital digest of the invoice, and storing a mapping relationship between the digital digest and a resource allocation state of the invoice in the blockchain, an initial resource allocation state of the invoice being an unallocated state.

[0006] Optionally, the calculating a digital digest of the target invoice, and querying a resource allocation state stored in the blockchain and corresponding to the digital digest includes: invoking state query logic declared in the smart contract published in the blockchain to calculate a digital digest of the target invoice, and querying a resource allocation state stored in the blockchain and corresponding to the digital digest.

[0007] Optionally, the method further includes: after target resources are allocated to the client from the predetermined resource pool, further invoking resource allocation state update logic declared in the smart contract published in the blockchain, to change the resource allocation state of the target invoice from the unallocated state to an allocated state.

[0008] Optionally, the blockchain further stores a corresponding relationship between each category of resources in the resource pool and the number of resources; the method further including: after the target resources are allocated to the client from the predetermined resource pool based on the predetermined allocation rule, updating a number of resources stored in the blockchain and corresponding to the target resource.

[0009] Optionally, the digital digest of the invoice includes: a hash value obtained through hash calculation based on invoice content of the invoice or unique information in the invoice content.

[0010] Optionally, the target transaction includes the invoice content of the target invoice or the unique information in the invoice content; and the calculating the digital digest of the target invoice includes: obtaining the invoice content of the target invoice in the target transaction or the unique information in the invoice content; and

performing hash calculation based on the obtained invoice content of the target invoice or the obtained unique information in the invoice content to obtain the hash value.

[0011] Optionally, the blockchain is a consortium blockchain.

5 **[0012]** Optionally, the resource pool includes a prize pool; the resources include virtual prizes; the resource allocation includes extracting virtual prizes for the client from the prize pool; and the resource allocation state includes a lottery state.

[0013] According to a second aspect of the implementations of the present specification, an apparatus for resource allocation based on a blockchain, where the
10 blockchain stores a mapping relationship between a digital digest of an invoice and a resource allocation state corresponding to the invoice is provided, the apparatus including: a receiving unit, configured to receive a target transaction submitted by a client to participate in resource allocation based on a target invoice; a query unit, configured to: in response to the target transaction, calculate a digital digest of the
15 target invoice, and query a resource allocation state stored in the blockchain and corresponding to the digital digest; and an allocation unit, configured to: if the detected resource allocation state is an unallocated state, invoke resource allocation logic declared in a smart contract published in the blockchain, to allocate resources to the client from a predetermined resource pool based on a predetermined allocation
20 rule, and return a resource allocation result to the client.

[0014] Optionally, the apparatus further includes: an invoice creation request receiving unit, configured to receive an invoice creation request submitted by the client, the invoice creation request including invoice creation information input by a user; and an invoice creation response unit, configured to: in response to the invoice
25 creation request, invoke invoice creation logic declared in the smart contract published in the blockchain to create an invoice based on the invoice creation information; calculate digital digest of the invoice, and store a mapping relationship between the digital digest and a resource allocation state of the invoice in the blockchain, an initial resource allocation state of the invoice being an unallocated
30 state.

[0015] Optionally, the query unit is specifically configured to: in response to the target transaction, invoke state query logic declared in the smart contract published in the blockchain to calculate a digital digest of the target invoice, and query a resource allocation state stored in the blockchain and corresponding to the digital digest.

[0016] Optionally, the apparatus further includes: a state update subunit, configured to: after target resources are allocated to the client from the predetermined resource pool, further invoke resource allocation state update logic declared in the smart contract published in the blockchain, to change the resource allocation state of the target invoice from the unallocated state to an allocated state.

[0017] Optionally, the blockchain further stores a corresponding relationship between each category of resources in the resource pool and the number of resources; the apparatus further including: a number update subunit, configured to: after the target resources are allocated to the client from the predetermined resource pool based on the predetermined allocation rule, update a number of resources stored in the blockchain and corresponding to the target resource.

[0018] Optionally, the digital digest of the invoice includes: a hash value obtained through hash calculation based on invoice content of the invoice or unique information in the invoice content.

[0019] Optionally, the target transaction includes the invoice content of the target invoice or the unique information in the invoice content; and the calculating the digital digest of the target invoice includes: obtaining the invoice content of the target invoice in the target transaction or the unique information in the invoice content; and performing hash calculation based on the obtained invoice content of the target invoice or the obtained unique information in the invoice content to obtain the hash value.

[0020] Optionally, the blockchain is a consortium blockchain.

[0021] Optionally, the resource pool includes a prize pool; the resources include virtual prizes; the resource allocation includes extracting virtual prizes for the client from the prize pool; and the resource allocation state includes a lottery state.

[0022] According to a third aspect of the implementations of the present application, an electronic device is provided, including: a processor; and a memory configured to store processor-executable instructions; where the processor is configured to perform any one of the above methods for resource allocation based on a blockchain.

[0023] Some implementations of the present specification provide a resource allocation solution based on a blockchain, which enables digital digest and a resource allocation state of an invoice to be stored in the blockchain in advance. Data stored in the blockchain cannot be tampered with and the digital digest is unique (that is, one

digital digest corresponds to one piece of original data); and therefore, whether a target invoice is true can be determined based on the digital digest stored in the blockchain. Specifically, a user only needs to upload the target invoice by using the client, and if it can be detected that the resource allocation state corresponding to the digital digest of the target invoice is stored in the blockchain, it can be determined that the target invoice is true. When the resource allocation state is an unallocated state, resource allocation logic declared in a smart contract published in the blockchain can be invoked to allocate resources to the client from a predetermined resource pool based on a predetermined allocation rule.

BRIEF DESCRIPTION OF DRAWINGS

- [0024] FIG. 1 is a flowchart illustrating a method for resource allocation based on a blockchain according to some implementations of the present specification;
- [0025] FIG. 2 is a schematic diagram illustrating an invoice lottery service according to some implementations of the present specification;
- [0026] FIG. 3 is a schematic diagram illustrating an invoice lottery process according to some implementations of the present specification;
- [0027] FIG. 4 is a diagram illustrating a hardware structure of an apparatus for resource allocation based on a blockchain according to some implementations of the present specification; and
- [0028] FIG. 5 is a schematic block diagram illustrating an apparatus for resource allocation based on a blockchain according to some implementations of the present specification.

DESCRIPTION OF IMPLEMENTATIONS

[0029] Exemplary implementations are described in detail herein, and examples thereof are shown in the accompanying drawings. When the following description refers to the accompanying drawings, unless otherwise indicated, the same numbers in different accompanying drawings refer to the same or similar elements. The following exemplary implementations do not represent all implementations consistent with the present specification. In contrast, they are merely examples of apparatuses and

methods consistent with some aspects of the present specification as described in detail in the appended claims.

[0030] Terms used in the present specification are for the purpose of describing specific implementations only and are not intended to limit the present specification.

5 As used in the present specification and the appended claims, the singular forms "a (an)", "the", and "this" are also intended to include the plural forms, unless the context clearly indicates other meaning. It should also be understood that the term "and/or" as used herein refers to and includes any or all possible combinations of one or more associated listed items.

10 **[0031]** It should be understood that although the terms such as "first", "second", and "third" can be used to describe various types of information in the present specification, the information should not be limited to these terms. These terms are only used to differentiate information of a same type. For example, without departing from the scope of the present specification, the first information can also be called
15 second information, and similarly, the second information can also be called first information. Depending on the context, the word "if" as used herein can be explained as "when" or "in response to determining".

[0032] An invoice can refer to a business voucher issued and collected by all units or individuals in purchasing and selling products, providing or receiving services and
20 engaging in other business activities. Invoices are usually the original basis of accounting, and are also an important basis for law enforcement inspection by audit institutions and tax authorities. For a company, invoices are mainly the basis for the company to perform accounting, and are also the expense vouchers for paying taxes. For employees, invoices can be mainly used for reimbursement.

25 **[0033]** A series of operations can be performed on invoices, such as reimbursement, tax offset, tax refund, and lottery. Taking the lottery service as an example, the tax authorities provide an incentive mechanism of invoice lottery to encourage users to request invoices. Specifically, after requesting an invoice, a user can go to the tax bureau to fill in invoice data and draw a lottery. However, users in general do not
30 know this mechanism, and even if they know the mechanism, they will not go to the tax bureau for drawing a lottery due to the lack of professional knowledge, which affects the enthusiasm of users to request invoices, and then makes it possible for merchants to evade taxes. In view of this, a solution that enables users to query invoices and draw a lottery at any time is needed.

[0034] The present specification provides a resource allocation solution based on blockchain, which enables digital digest and a resource allocation state of an invoice to be stored in the blockchain in advance. Data stored in a blockchain cannot be tampered with and the digital digest is unique (that is, one digital digest corresponds to one piece of original data); and therefore, whether a target invoice is true can be determined based on the digital digest stored in the blockchain. Specifically, a user only needs to upload the target invoice by using a client device, and if it can be detected that the resource allocation state corresponding to the digital digest of the target invoice is stored in the blockchain, it can be determined that the target invoice is true. When the resource allocation state is an unallocated state, resource allocation logic declared in a smart contract published in the blockchain can be invoked to allocate resources to the client.

[0035] FIG. 1 is a flowchart illustrating a method for resource allocation based on a blockchain according to some implementations of the present specification. The blockchain stores a corresponding relationship between a digital digest of an invoice and a resource allocation state corresponding to the invoice; and the digital digest can be calculated based on invoice content of the invoice or unique information in the invoice content. The method includes the following steps.

[0036] Step 110: Receive a target transaction submitted by a client to participate in resource allocation based on a target invoice.

[0037] Step 120: In response to the target transaction, calculate a digital digest of the target invoice, and query a resource allocation state stored in the blockchain and corresponding to the digital digest.

[0038] Step 130: If the detected resource allocation state is an unallocated state, invoke resource allocation logic declared in a smart contract published in the blockchain, to allocate resources to the client from a predetermined resource pool based on a predetermined allocation rule, and return a resource allocation result to the client.

[0039] The blockchain described in the present specification can specifically include a private blockchain, a shared blockchain, a consortium blockchain, and the like, which is not particularly limited in the present specification.

[0040] For example, in a scenario, the above blockchain can be a consortium blockchain composed of headquarters, branches, agencies, and the like as consortium members. An operator of the consortium blockchain can rely on the consortium

blockchain to deploy corresponding services. The above headquarters, branches and agencies as consortium members can each serve as service nodes of the above service. Each service node can publish, in the form of a transaction in the consortium blockchain, the digital digest of the above invoice generated or received by the service node, and store the transaction in a distributed database in the consortium blockchain after the transaction undergoes consensus processing by consensus nodes in the consortium blockchain, so as to complete "upload to the blockchain" for deposit of the transaction information.

[0041] It should be noted that the transaction described in the present specification refers to a piece of data created by a client of the blockchain and needing to be finally published to the distributed database of the blockchain.

[0042] Transactions in the blockchain are usually divided into narrow transactions and broad transactions. The narrow transaction refers to a value transfer published by a user to the blockchain. For example, in a conventional bitcoin blockchain network, a transaction can be a transfer initiated by a user in the blockchain. The broad transaction refers to a piece of service data with a service intention published by a user to the blockchain. For example, the operator can build a consortium blockchain based on actual service requirements, and deploy, based on the consortium blockchain, some other online services unrelated to value transfer (such as a deposit service, authenticity verification service, resource allocation, and invoice lottery). In this consortium blockchain, the transaction can be a service message or service request with a service intention published by the user in the consortium blockchain.

[0043] The above client can include any type of upper-layer application that uses bottom-layer service data stored in the blockchain as data support to implement specific service functions.

[0044] In the blockchain technology, nodes in the blockchain usually need to rely on a corresponding smart contract to operate blocks. For example, operations such as storage, modification, and deletion in the blockchain need to rely on the smart contract. The smart contract can be a computer protocol that can be deployed in the blockchain to disseminate, verify, or perform a contract in an informatization manner. Corresponding operations can be implemented by declaring service logic in the smart contract. The smart contract allows trusted transactions to be conducted without a third party. These transactions are traceable and irreversible. The smart contract can ensure better security than a conventional contract method and reduce other

transaction costs related to the contract. Generally, smart contracts can be deployed locally in blockchain nodes. When a node needs to perform a certain action, the node can invoke the corresponding smart contract and run the smart contract to execute service logic declared in the smart contract, so as to obtain an execution result.

5 **[0045]** The digital digest described in the present specification can refer to a hash value obtained after hash calculation based on original data.

[0046] The hash value is obtained through hash calculation based on invoice content of the invoice or unique information in the invoice content.

[0047] The invoice content can include unique information. For example, the
10 invoice content can include invoice number and invoice code; the invoice number and the invoice code are usually unique information; and accordingly, the digital digest of the invoice can be recorded as hash (invoice number + invoice code). Certainly, the invoice content can further include non-unique information, such as invoice date and amount excluding tax; and accordingly, the digital digest of the invoice can be
15 recorded as hash (invoice number + invoice code + invoice date + amount excluding tax).

[0048] Accordingly, the target transaction can include the invoice content of the target invoice or the unique information in the invoice content; and the calculating the digital digest of the target invoice includes: obtaining the invoice content of the target
20 invoice in the target transaction or the unique information in the invoice content; and performing hash calculation based on the obtained invoice content of the target invoice or the obtained unique information in the invoice content to obtain the hash value.

[0049] As mentioned above, the invoice is uploaded to the blockchain in advance
25 in the present specification. In some implementations, the method further includes: receiving an invoice creation request submitted by the client, the invoice creation request including invoice creation information input by a user; in response to the invoice creation request, invoking invoice creation logic declared in the smart contract published in the blockchain to create an invoice based on the invoice creation
30 information; and, calculating a digital digest of the invoice, and storing a mapping relationship between the digital digest and a resource allocation state of the invoice in the blockchain, an initial resource allocation state of the invoice being an unallocated state.

[0050] It should be noted that the above calculation of the digital digest of the target invoice and the calculation of the digital digest of the invoice during creation of the invoice are performed by using the same hash algorithm.

[0051] The following is an example of uploading an invoice to a blockchain.

5 **[0052]** In the implementations, when a user needs to create an invoice in the blockchain, the user can initiate an invoice creation transaction by using a client, that is, initiate an invoice creation request by using the client. Specifically, the user can input invoice creation information (such as invoice title and amount) of a to-be-created target invoice by using an invoice creation page provided by the client.

10 After the user inputs the invoice creation information, the client can generate a corresponding invoice creation request based on the invoice creation information input by the user, and send the invoice creation request to a node device in the blockchain.

[0053] After receiving the invoice creation request, the node device in the
15 blockchain can respond to the invoice creation request, and invoke invoice creation logic declared in the smart contract published in the blockchain to create an invoice based on the invoice creation information in the invoice creation request; and after the invoice is created, the node device can further calculate a digital digest of the created invoice, and store a mapping relationship between the digital digest and an initial
20 resource allocation state in the blockchain.

[0054] The initial resource allocation state of the created invoice can be an unallocated state.

[0055] In some implementations, the node device responding to the invoice creation request can further first determine whether an invoice creation quota of an
25 invoice issuer corresponding to the invoice creation request is sufficient.

[0056] For example, a taxpayer identification number of an invoice issuer can be obtained from the invoice creation information input by the user in the invoice creation request, the corresponding invoice issuer can be determined based on the taxpayer identification number, and the invoice issuer is the invoice issuer
30 corresponding to the invoice creation request. Subsequently, whether the invoice creation quota of the invoice issuer is sufficient can be first determined.

[0057] In an implementation, the node device can invoke quota check logic declared in the smart contract deployed in the blockchain to determine whether the invoice creation quota of the invoice issuer is sufficient.

[0058] The quota check logic can specifically be program code (such as some program methods or functions that can be invoked) declared in the smart contract and related to execution logic for checking the invoice creation quota of the invoice issuer.

[0059] Alternatively, the node device can invoke a trusted service of a third party and send the invoice creation request to the trusted service of the third party. The trusted service of the third party can be program code deployed on a trusted service device of the third party and related to execution logic for checking the invoice creation quota of the invoice issuer. For example, the trusted service device of the third party can be a device in an intranet of the tax bureau, which can improve data security.

[0060] The trusted service of the third party can determine whether the invoice creation quota of the invoice issuer is sufficient, and return a determined result to the node device. The node device can determine, based on the determined result returned by the trusted service of the third party, whether the invoice creation quota of the invoice issuer is sufficient.

[0061] Specifically, after it is determined that the invoice creation quota of the invoice issuer is sufficient, the trusted service of the third party can return a determined result that the invoice creation quota of the invoice issuer is sufficient to the node device. After receiving the determined result, the node device can determine that the invoice creation quota of the invoice issuer is sufficient. Or, the trusted service of the third party can return, after determining that the invoice creation quota of the invoice issuer is insufficient, the determined result that the invoice creation quota of the invoice issuer is insufficient to the node device. After receiving the determined result, the node device can determine that the invoice creation quota of the invoice issuer is insufficient.

[0062] If it is determined that the invoice creation quota of the invoice issuer is sufficient, the invoice creation logic declared in the smart contract deployed in the blockchain can be invoked to create an invoice based on the invoice creation information input by the user in the invoice creation request; and the corresponding relationship between the digital digest of the created invoice and the resource allocation state is stored.

[0063] The invoice creation logic can specifically be program code declared in the smart contract and related to execution logic for creating the invoice.

[0064] In another implementation, the invoice can be provided by an institution that originally generated the invoice. For example, invoice data can be directly or indirectly uploaded to the blockchain by the State Taxation Administration of the People's Republic of China. Specifically, after an invoice issuing device issues an invoice, the invoice is also recorded in a tax system of a tax bureau, and the tax system of the tax bureau can synchronously upload the invoice to the blockchain for deposit. The process of upload to the blockchain for deposit is the same as that of the previous implementation. Details are omitted herein for simplicity.

[0065] The following describes the resource allocation process of an invoice in the present specification.

[0066] After receiving the invoice, a user can use the invoice as a target invoice, and submit, by a client, a target transaction for participating in resource allocation based on the target invoice, to call a smart contract deployed in the blockchain and used for resource allocation, so as to allocate virtual resources to the client.

[0067] In some implementations, similar to the previous invoice creation, the user can input, to a client, invoice content of the target invoice or unique information in the invoice content (hereinafter, the invoice content or the unique information in the invoice content is simply referred to as invoice data), and the input invoice data is included in the target transaction sent by the client and is sent to a node device in the blockchain, to trigger the node device in the blockchain to invoke the deployed smart contract, so as to allocate virtual resources to the client. Therefore, the node device in the blockchain can directly receive the invoice data.

[0068] In another implementation, the user can take a picture of the issued target invoice, obtain an invoice image of the target invoice, and recognize the obtained invoice image on the client or on a third-party recognition system, to recognize the invoice data; and the invoice data obtained by image recognition is included in the target transaction sent by the client and sent to the node device in the blockchain, to trigger the node device in the blockchain to invoke the deployed smart contract, so as to allocate virtual resources to the client.

[0069] Image recognition of the obtained invoice image data can be performed specifically by a smart contract deployed in the blockchain, or performed by invoking a trusted service of a third party.

[0070] In some implementations, invoice data in the invoice image is recognized by using an image recognition algorithm. In the implementations, the smart contract

includes contract logic for image recognition, which can recognize the invoice data in the invoice image at a node locally.

[0071] In some implementations, the method further includes the following operations.

5 **[0072]** The node device can also send, by invoking the trusted service of a third party (such as a third-party image recognition mechanism), an invoice image in a target transaction to the trusted service of the third party, the trusted service of the third party performs image recognition on the invoice image based on an included image recognition algorithm to obtain the above invoice data, and the node device can
10 obtain the invoice data returned by the third-party image recognition mechanism. In the implementations, the image recognition can be completed by the third-party image recognition mechanism, thereby lowering the requirement for node performance (not all nodes can have computing resources required for image recognition).

[0073] In some implementations, after obtaining the invoice data in the target
15 transaction, the node device can invoke state query logic declared in the smart contract published in the blockchain to calculate a digital digest of the target invoice, and query a resource allocation state stored in the blockchain and corresponding to the digital digest.

[0074] If the blockchain stores the resource allocation state corresponding to the
20 digital digest and the resource allocation state is an unallocated state, resource allocation logic declared in a smart contract published in the blockchain is invoked, to allocate resources to the client from a predetermined resource pool based on a predetermined allocation rule, and a resource allocation result is returned to the client.

[0075] If the blockchain stores the resource allocation state corresponding to the
25 digital digest but the resource allocation state is an allocated state, or if the resource allocation state corresponding to the digital digest cannot be detected, subsequent steps are not performed, and a resource allocation failure notification can be returned to the client.

[0076] Further, after target resources are allocated to the client from the
30 predetermined resource pool, service execution state update logic declared in the smart contract published in the blockchain is further invoked, to change the resource allocation state of the target invoice from the unallocated state to an allocated state.

[0077] In some implementations, the resource pool can include a plurality of types of virtual resources; and accordingly, the blockchain can further store a corresponding

relationship between each category of virtual resources in the resource pool and the number of resources.

5 **[0078]** In this case, after the target resources are allocated to the client from the predetermined resource pool based on the predetermined allocation rule, the smart contract can further update a number of resources stored in the blockchain and corresponding to the target resource.

[0079] The following description based on specific resource allocation scenarios.

10 **[0080]** In a scenario, the resource pool includes a prize pool; the virtual resources include virtual prizes; the resource allocation includes extracting virtual prizes for the client from the prize pool based on a certain lottery rule; and the resource allocation state includes a lottery state.

[0081] In this scenario, the user can construct a target transaction by using a client based on invoice content of the issued invoice or unique information in the invoice content, so as to invoke the smart contract deployed in the blockchain to draw a
15 lottery.

[0082] The following description based on the schematic diagram of an invoice lottery service shown in FIG. 2 and the schematic diagram of an invoice lottery process shown in FIG. 3. As shown in FIG. 2, after invoice A, invoice B, and invoice C are uploaded to the blockchain, a mapping relationship between invoice A hash and a lottery state, a mapping relationship between invoice B hash and a lottery state, and
20 a mapping relationship between invoice C hash and a lottery state can be recorded in the blockchain.

[0083] As shown in FIG. 3, after receiving the invoice, the user can submit, to the blockchain by a client, a target transaction for drawing a lottery based on the invoice,
25 to invoke a smart contract deployed in the blockchain for lottery, so as to draw a lottery for the invoice.

[0084] Accordingly, after obtaining the invoice data in the target transaction, the node device in the blockchain can invoke lottery state query logic declared in the smart contract to calculate the digital digest corresponding to the invoice data, and
30 query invoice stored in the blockchain and corresponding to the digital digest, as well as the lottery state of the invoice.

[0085] If the invoice corresponding to the digital digest exists in the blockchain, and the lottery state of the invoice is that no lottery has been drawn, the node device

can further invoke the lottery logic declared in the smart contract to draw a lottery for the invoice, and then return the lottery result to the client.

[0086] Further, the node device can invoke state update logic in the smart contract to update the lottery state corresponding to the digital digest to that the lottery has
5 been drawn.

[0087] In addition to the lottery having been drawn, the updated lottery state can include whether a prize has been won, for example, the lottery has been drawn (no prize is won), and the lottery has been drawn (first prize).

[0088] If an invoice corresponding to the digital digest exists in the blockchain but
10 the lottery state of the invoice is that the lottery has been drawn, it means that the to-be-identified invoice has been drawn although it has been deposited in the blockchain. Based on the principle that one invoice can only allow the lottery to be drawn once, repeated lottery drawing is avoided, and lottery logic is not allowed to be executed, so the result that the lottery has been drawn for the invoice can be returned
15 to the client.

[0089] As shown in FIG. 2, the inventory of prizes is also recorded in the blockchain; and accordingly, a node also needs to operate prize winning inventory records for lottery results, specifically:

[0090] If the lottery result is that a prize has been won, the inventory of prizes with
20 the winning name stored in the blockchain is reduced by 1 based on the winning name.

[0091] It should be noted that in the present specification, a function of modifying the inventory in the blockchain by an administrator is also provided.

[0092] The present specification provides a resource allocation solution based on a
25 blockchain, which enables a digital digest and a resource allocation state of an invoice to be stored in the blockchain in advance. Data stored in the blockchain cannot be tampered with and the digital digest is unique (that is, one digital digest corresponds to one piece of original data); and therefore, whether a target invoice is true can be determined based on the digital digest stored in the blockchain. Specifically, a user
30 only needs to upload the target invoice by using the client, and if it can be detected that the resource allocation state corresponding to the digital digest of the target invoice is stored in the blockchain, it can be determined that the target invoice is true. When the resource allocation state is an unallocated state, resource allocation logic declared in a smart contract published in the blockchain can be invoked to allocate

resources to the client from a predetermined resource pool based on a predetermined allocation rule. In addition, because data can be globally synchronized in the blockchain, data related to lottery, such as lottery results and prize inventory, can be synchronized between all nodes in the blockchain, so that the data is open and transparent.

[0093] Corresponding to the above implementations of the method for resource allocation based on a blockchain, the present specification further provides implementations of the apparatus for resource allocation based on a blockchain. The apparatus implementations can be implemented by using software, hardware, or a combination thereof. Taking software implementation as an example, a logical apparatus is implemented by reading, using a processor of a device where the apparatus is located, corresponding computer service program instructions in a non-volatile memory into a memory for running. On the hardware level, FIG. 4 is a diagram illustrating a hardware structure of a device where an apparatus for resource allocation based on a blockchain is located according to the present specification. In addition to a processor, a network interface, a memory, and a non-volatile memory shown in FIG. 4, the device where the apparatus according to the implementations is located can generally further include other hardware depending on the actual resource allocation function based on a blockchain. Details are omitted for simplicity.

[0094] FIG. 5 is a diagram illustrating modules in an apparatus for resource allocation based on a blockchain according to some implementations of the present specification. The apparatus corresponds to the implementation shown in FIG. 1, and the blockchain stores a corresponding relationship between a digital digest of an invoice and a resource allocation state corresponding to the invoice. The apparatus includes: a receiving unit 210, configured to receive a target transaction submitted by a client to participate in resource allocation based on a target invoice; a query unit 220, configured to: in response to the target transaction, calculate a digital digest of the target invoice, and query a resource allocation state stored in the blockchain and corresponding to the digital digest; and an allocation unit 230, configured to: if the detected resource allocation state is an unallocated state, invoke resource allocation logic declared in a smart contract published in the blockchain, to allocate resources to the client from a predetermined resource pool based on a predetermined allocation rule, and return a resource allocation result to the client.

[0095] Optionally, the apparatus further includes: an invoice creation request receiving unit, configured to receive an invoice creation request submitted by the client, the invoice creation request including invoice creation information input by a user; and an invoice creation response unit, configured to: in response to the invoice creation request, invoke invoice creation logic declared in the smart contract published in the blockchain to create an invoice based on the invoice creation information; calculate a digital digest of the invoice, and store a mapping relationship between the digital digest and a resource allocation state of the invoice in the blockchain, an initial resource allocation state of the invoice being an unallocated state.

[0096] Optionally, the query unit 220 is specifically configured to: in response to the target transaction, invoke state query logic declared in the smart contract published in the blockchain to calculate a digital digest of the target invoice, and query a resource allocation state stored in the blockchain and corresponding to the digital digest.

[0097] Optionally, the apparatus further includes: a state update subunit, configured to: after target resources are allocated to the client from the predetermined resource pool, further invoke resource allocation state update logic declared in the smart contract published in the blockchain, to change the resource allocation state of the target invoice from the unallocated state to an allocated state.

[0098] Optionally, the blockchain further stores a corresponding relationship between each category of resources in the resource pool and the number of resources; the apparatus further including: a number update subunit, configured to: after the target resources are allocated to the client from the predetermined resource pool based on the predetermined allocation rule, update a number of resources stored in the blockchain and corresponding to the target resource.

[0099] Optionally, the digital digest of the invoice includes: a hash value obtained through hash calculation based on invoice content of the invoice or unique information in the invoice content.

[0100] Optionally, the target transaction includes the invoice content of the target invoice or the unique information in the invoice content; and the calculating the digital digest of the target invoice includes: obtaining the invoice content of the target invoice in the target transaction or the unique information in the invoice content; and performing hash calculation based on the obtained invoice content of the target

invoice or the obtained unique information in the invoice content to obtain the hash value.

[0101] Optionally, the blockchain is a consortium blockchain.

5 **[0102]** Optionally, the resource pool includes a prize pool; the resources include virtual prizes; the resource allocation includes extracting virtual prizes for the client from the prize pool; and the resource allocation state includes a lottery state.

10 **[0103]** The systems, apparatuses, modules or units illustrated in the above implementations can be implemented by computer chips or entities, or by products with certain functions. A typical implementation device is a computer. The computer can be a personal computer, a laptop computer, a cellular phone, a camera phone, a smartphone, a personal digital assistant, a media player, a navigation device, an email sending and receiving device, a game console, a tablet computer, a wearable device, or a combination thereof.

15 **[0104]** The implementation process of functions of each unit in the above apparatus is detailed in the implementation process of the corresponding steps in the above method. Details are omitted herein for simplicity.

20 **[0105]** Because the apparatus implementations basically correspond to the method implementations, for related parts, references can be made to a partial description of the method implementation. The apparatus implementations described above are merely illustrative, where units described as separate components can or cannot be physically separated. Components displayed as units can or cannot be physical units, that is, the components can be located in one place, or can be distributed to multiple network units. Some or all of the modules can be selected based on actual needs to achieve the object of the solution of the present specification. A person of ordinary skill in the art can understand and implement the implementations without making innovative efforts.

25 **[0106]** FIG. 5 shows internal functional modules and the schematic structure of an apparatus for resource allocation based on a blockchain, which can be substantially implemented by an electronic device. The electronic device includes: a processor; and 30 a memory configured to store processor-executable instructions; where the processor is configured to perform the above methods for resource allocation based on a blockchain.

[0107] The method includes: receiving a target transaction submitted by a client to participate in resource allocation based on a target invoice; in response to the target

transaction, calculating a digital digest of the target invoice, and querying a resource allocation state stored in the blockchain and corresponding to the digital digest, the blockchain storing a mapping relationship between the digital digest of an invoice and the resource allocation state corresponding to the invoice; and if the detected resource allocation state is an unallocated state, invoking resource allocation logic declared in a smart contract published in the blockchain, to allocate resources to the client from a predetermined resource pool based on a predetermined allocation rule, and returning a resource allocation result to the client.

[0108] Optionally, the method further includes: receiving an invoice creation request submitted by the client, the invoice creation request including invoice creation information input by a user; in response to the invoice creation request, invoking invoice creation logic declared in the smart contract published in the blockchain to create an invoice based on the invoice creation information; and, calculating a digital digest of the invoice, and storing a mapping relationship between the digital digest and a resource allocation state of the invoice in the blockchain, an initial resource allocation state of the invoice being an unallocated state.

[0109] Optionally, the calculating a digital digest of the target invoice, and querying a resource allocation state stored in the blockchain and corresponding to the digital digest includes: invoking state query logic declared in the smart contract published in the blockchain to calculate a digital digest of the target invoice, and querying a resource allocation state stored in the blockchain and corresponding to the digital digest.

[0110] Optionally, the method further includes: after target resources are allocated to the client from the predetermined resource pool, further invoking resource allocation state update logic declared in the smart contract published in the blockchain, to change the resource allocation state of the target invoice from the unallocated state to an allocated state.

[0111] Optionally, the blockchain further stores a corresponding relationship between each category of resources in the resource pool and the number of resources; the method further including: after the target resources are allocated to the client from the predetermined resource pool based on the predetermined allocation rule, updating a number of resources stored in the blockchain and corresponding to the target resource.

[0112] Optionally, the digital digest of the invoice includes: a hash value obtained through hash calculation based on invoice content of the invoice or unique information in the invoice content.

[0113] Optionally, the target transaction includes the invoice content of the target invoice or the unique information in the invoice content; and the calculating the digital digest of the target invoice includes: obtaining the invoice content of the target invoice in the target transaction or the unique information in the invoice content; and performing hash calculation based on the obtained invoice content of the target invoice or the obtained unique information in the invoice content to obtain the hash value.

[0114] Optionally, the blockchain is a consortium blockchain.

[0115] Optionally, the resource pool includes a prize pool; the resources include virtual prizes; the resource allocation includes extracting virtual prizes for the client from the prize pool; and the resource allocation state includes a lottery state.

[0116] In the above implementations of the electronic device, it should be understood that the processor can be a central processing unit (CPU), or can be another general-purpose processor, a digital signal processor (DSP), an application specific integrated circuit (ASIC), or the like. The general-purpose processor can be a microprocessor or any conventional processor, or the like, and the above memory can be a read-only memory (ROM), a random access memory (RAM), a flash memory, a hard disk or a solid-state disk. The steps of the method according to the implementations of the present specification can be directly performed by a hardware processor or performed by a combination of hardware and software modules in a processor.

[0117] Each implementation in the present specification is described in a progressive way. For the same or similar parts between the implementations, references can be made to each other. Each implementation focuses on differences from other implementations. Particularly, because the electronic device implementation is similar to the method implementations, the description is relatively simple. For related parts, references can be made to partial description of the method implementations.

[0118] A person skilled in the art will easily figure out other implementation solutions of the present specification after considering the present specification and practicing the application disclosed herein. The present specification is intended to

cover any modification, use or adaptive change of the present specification, and these modifications, uses or adaptive changes follow the general principles of the present specification and include common knowledge or conventional technical means in the technical field not disclosed in the present specification. The present specification and
5 implementations are regarded as exemplary only, with the true scope and spirit of the present specification being indicated by the following claims.

[0119] It should be understood that the present specification is not limited to the precise structure already described above and shown in the accompanying drawings, and various modifications and changes can be performed without departing from its
10 scope. The scope of the present specification is limited only by the appended claims.

CLAIMS

What is claimed is:

1. A computer-implemented method for resource allocation based on a blockchain, wherein
5 the blockchain stores a mapping relationship between a digital digest of an invoice and a resource allocation state corresponding to the invoice, the method comprising:
 - receiving (110) a target transaction submitted by a client to participate in resource allocation based on a target invoice, wherein a user of the client takes a picture of the target invoice, obtains an invoice image of the target invoice, wherein invoice data is recognized
10 by image recognition of the client from the obtained invoice image, and wherein the invoice data obtained by the image recognition is included in the target transaction;
 - in response to the target transaction, calculating (120) a digital digest of the target invoice, and querying a resource allocation state stored in the blockchain and corresponding to the digital digest; and
 - 15 in response to the detected resource allocation state is an unallocated state, invoking (130) resource allocation logic declared in a smart contract published in the blockchain, to allocate resources to the client from a predetermined resource pool based on a predetermined allocation rule, and returning a resource allocation result to the client, the computer-implemented method further including:
 - 20 receiving an invoice creation request submitted by the client, the invoice creation request including invoice creation information input by the user;
 - in response to the invoice creation request, invoking invoice creation logic declared in the smart contract published in the blockchain to create an invoice based on the invoice creation information; and
 - 25 calculating a digital digest of the invoice, and storing a mapping relationship between the digital digest and a resource allocation state of the invoice in the blockchain, an initial resource allocation state of the invoice being an unallocated state,
 - wherein the digital digest of the invoice includes:
 - 30 a hash value obtained through hash calculation based on non-unique and unique information in an invoice content of the invoice.

2. The computer-implemented method according to claim 1, wherein the calculating the digital digest of the target invoice, and the querying the resource allocation state stored in the blockchain and corresponding to the digital digest includes:
- invoking state query logic declared in the smart contract published in the blockchain to calculate the digital digest of the target invoice, and querying the resource allocation state stored in the blockchain and corresponding to the digital digest.
3. The computer-implemented method according to claim 1, further including:
- after target resources are allocated to the client from the predetermined resource pool, further invoking resource allocation state update logic declared in the smart contract published in the blockchain to change the resource allocation state of the target invoice from the unallocated state to an allocated state.
4. The computer-implemented method according to claim 3, wherein the blockchain further stores a corresponding relationship between each category of resources in the resource pool and a number of resources, the method further comprising:
- after the target resources are allocated to the client from the predetermined resource pool based on the predetermined allocation rule, updating a number of resources stored in the blockchain and corresponding to the target resource.
5. The computer-implemented method according to claim 4, wherein the target transaction includes the non-unique and unique information in the invoice content;
- the calculating the digital digest of the target invoice includes:
- obtaining the non-unique and unique information in the invoice content of the target invoice in the target transaction; and
- performing the hash calculation, based on the obtained non-unique and unique information in the invoice content of the target invoice, to obtain the hash value.
6. The computer-implemented method according to claim 1, wherein the blockchain is a consortium blockchain.
7. The computer-implemented method according to claim 1, wherein the resource pool includes a prize pool; the resources include virtual prizes; the resource allocation includes

extracting the virtual prizes for the client from the prize pool; and the resource allocation state includes a lottery state.

8. An apparatus for resource allocation based on a blockchain, wherein the blockchain
5 stores a mapping relationship between a digital digest of an invoice and a resource allocation state corresponding to the invoice, the apparatus comprising a plurality of modules for performing the computer-implemented method of any of claims 1 to 7.
9. An electronic device, comprising:
10 a processor; and
a memory configured to store processor-executable instructions,
wherein the processor is configured, by executing the processor-executable instructions, to perform the computer-implemented method according to any one of claims 1 to 7.