

FLUID LENSES, LENS BLANKS, AND METHODS OF MANUFACTURING THE SAME

BACKGROUND

Field

[0001] Embodiments of the present invention relate to lens blanks for fluid lenses and methods of manufacturing fluid lenses.

Background Art

[0002] Basic fluid lenses have been known since about 1958, as described in U.S. Pat. No. 2,836,101 to Swart, incorporated herein by reference in its entirety. More recent examples may be found in "Dynamically Reconfigurable Fluid Core Fluid Cladding Lens in a Microfluidic Channel" by Tang et al., Lab Chip, 2008, vol. 8, p. 395, and in WIPO publication WO2008/063442, each of which is incorporated herein by reference in their entirety. These applications of fluid lenses are directed towards photonics, digital phone and camera technology, and microelectronics.

[0003] Fluid lenses have also been proposed for ophthalmic applications (see, e.g., U.S. Patent No. 7,085,065 to Silver, which is incorporated herein by reference in its entirety). Power adjustment in fluid lenses has been accomplished for example by injecting fluid into a lens cavity, by electrowetting, application of ultrasonic impulse, and by utilizing swelling forces in a cross-linked polymer upon introduction of a swelling agent, such as water.

BRIEF SUMMARY

[0004] In some embodiments, a lens blank for a fluid lens includes a rigid lens and a semi-flexible inflatable membrane attached to the rigid lens. The lens blank is divided into a cavity zone and a bonded zone. The cavity zone extends radially outward from a central area of the lens blank and a cavity is formed between the membrane and the rigid lens within the cavity zone. The bonded zone extends radially outward from the cavity zone and the membrane is bonded and fluidly sealed to the rigid lens throughout the bonded zone. The bonded zone is dimensioned to be trimmed to accommodate a plurality of frame shapes and sizes.

[0005] In some embodiments, a method of manufacturing a fluid lens assembly includes bonding a portion of the membrane to the rigid lens so that the bonded area of the membrane is fluidly sealed to the rigid lens. The bonded area is dimensioned such that the lens blank may be trimmed to form a trimmed lens having a bonded loop area with a width and height corresponding to any common spectacle lens size. The method further includes trimming the lens blank to form a trimmed lens having a bonded loop area with a width and height corresponding to a common spectacle lens size.

[0006] In some embodiments, frame-independent designs for common spectacle lens sizes and shapes may be realized. Such frame-independent designs may in some cases enable the use of a reduced number of stock-keeping units (SKUs) of components for the fluid lens. For example, in some embodiments, a single SKU for each component may be used for both left-eye lenses and right-eye lenses.

[0007] In some embodiments, an array of fluid lenses includes a plurality of fluid lenses, each having a rigid lens and a semi-flexible inflatable membrane attached to the rigid lens. The fluid lens is divided into at least two zones, the zones including a cavity zone extending radially outward from a central area of the fluid lens, forming a cavity between the membrane and the rigid lens in the cavity zone, and a bonded zone extending radially outward from the cavity zone. The membrane is bonded and fluidly sealed to the rigid lens throughout the bonded zone. One or more of the plurality of lens blanks are fluidly connected to one or more of the other fluid lenses within the array.

[0008] Certain embodiments, features, and advantages of the present invention, as well as the structure and operation of various embodiments of the present invention, are described in detail herein with reference to the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS/FIGURES

[0009] The accompanying drawings, which are incorporated herein and form a part of the specification, illustrate embodiments of the present invention and, together with the description, further serve to explain principles of embodiments of the invention and enable a person skilled in the pertinent art to make and use the embodiments of the invention.

[0010] FIG. 1 illustrates a front view of a lens blank according to an embodiment.

[0011] FIG. 2 illustrates a front view of a spectacle lens according to an embodiment.

[0012] FIG. 3 illustrates a front view of a lens blank according to an embodiment.

- [0013] FIG. 4 illustrates a front view of a lens blank according to an embodiment.
- [0014] FIG. 5 illustrates a cross-sectional view of a portion of a lens blank according to an embodiment.
- [0015] FIG. 6 illustrates a front view of a lens blank according to an embodiment.
- [0016] FIG. 7 illustrates a front view of a lens blank according to an embodiment.
- [0017] FIG. 8 illustrates a front view of a lens blank according to an embodiment.
- [0018] FIG. 9 illustrates a front view of a lens blank according to an embodiment.
- [0019] FIG. 10 shows a flow chart for a method of manufacturing a fluid lens assembly according to an embodiment.
- [0020] FIG. 11 shows a flow chart for a method of manufacturing a fluid lens assembly according to an embodiment.
- [0021] FIG. 12 shows a flow chart for a method of manufacturing a fluid lens assembly according to an embodiment.
- [0022] FIG. 13 illustrates a front view of the spectacle lens of FIG. 2 with added dimension labels.
- [0023] FIG. 14 illustrates a front view of the lens blank of FIG. 4 with added dimension labels.
- [0024] FIG. 15 illustrates a front view of an array of lens blanks according to an embodiment.
- [0025] FIG. 16 illustrates a front view of an array of fluid lenses according to an embodiment.
- [0026] The present invention will be described with reference to the accompanying drawings.

DETAILED DESCRIPTION

- [0027] While specific configurations and arrangements are discussed, it should be understood that this is done for illustrative purposes only. A person skilled in the pertinent art will recognize that other configurations and arrangements may be used without departing from the spirit and scope of the present invention. It will be apparent to a person skilled in the pertinent art that this invention may also be employed in a variety of other applications.
- [0028] It is noted that references in the specification to "one embodiment," "an embodiment," "an example embodiment," etc., indicate that the embodiment described may

include a particular feature, structure, or characteristic, but every embodiment may not necessarily include the particular feature, structure, or characteristic. Moreover, such phrases may not refer to the same embodiment. Further, when a particular feature, structure or characteristic is described in connection with an embodiment, it would be within the knowledge of one skilled in the art to effect such feature, structure or characteristic in connection with other embodiments whether or not explicitly described.

[0029] FIG. 1 illustrates a front view of a lens blank 100. Lens blank 100 includes a rigid lens 102 and a semi-flexible inflatable membrane 104 attached to rigid lens 102. Lens blank 100 may be used as a fluid lens when supplied with an intervening fluid. For example, the term "fluid lens" may describe the optical lens formed by a fluid layer and surfaces containing the fluid, such as rigid lens 102 and membrane 104. In some embodiments, such a fluid lens may rely upon hydrostatic pressure of the fluid to cause a change in curvature of membrane 104, which may thereby alter the optical power of the fluid lens.

[0030] Rigid lens 102 may be made of glass, plastic, or other suitable material. Other suitable materials include, for example and without limitation, Diethylglycol bisallyl carbonate (DEG-BAC), poly(methyl methacrylate) (PMMA), and a proprietary polyurea complex, trade name TRIVEX (PPG). The lenses may be made of an impact resistant polymer and may have a scratch resistant coating or an anti-reflective coating.

[0031] In some embodiments, rigid lens 102 may be in the form of a single vision lens comprising a base curve and a fixed optical power. Rigid lens 102 may have a positive, negative, or zero fixed optical power as desired. In some embodiments, the fixed optical power of rigid lens 102 is in the range from about -1D to about +1D. In some embodiments, the curvature of a front surface of rigid lens 102 may be the same as a curvature of a back surface of rigid lens 102, which may result in a substantially zero optical power. In some embodiments, rigid lens 102 may be convex, concave, spherical, and/or aspheric in shape. In some embodiments, rigid lens 102 may include a compensation to its front or back surface to provide a desired optical power at a predetermined level of inflation. The compensation of rigid lens 102 can, for example, be designed based on factors such as the geometry of membrane 104, the desired level of inflation, or any combination thereof or other suitable factors. Rigid lens 102 may have a diameter ranging from about 55 mm to about 95 mm. In some embodiments, the diameter of rigid lens 102 may range from about 60 mm to about 90 mm.

[0032] Membrane 104 may be made of a semi-flexible, transparent, water impermeable material, such as, for example and without limitation, clear and elastic polyolefins, polyhalocarbons, polycycloaliphatics, polyethers, polyesters, polyimides and polyurethanes, for example, polyvinylidene difluoride or dichloride films. Other polymers suitable for use as membrane materials include, for example and without limitation, polysulfones, polyurethanes, polythiourethanes, polyethylene terephthalate, polymers of cycloolefins and aliphatic or alicyclic polyethers. Membrane 104 may be made of a biocompatible impermeable material, such as a cyclo-aliphatic hydrocarbon. In some embodiments, the thickness of membrane 104 may range from about 10 microns to 2.0 mm. The fluid used in the fluid lens may be a colorless fluid, for example air or distilled water. In some embodiments, the fluid is tinted, depending on the application. One example of fluid that may be used is manufactured by Dow Corning of Midland, MI, under the name "diffusion pump oil," which is also generally referred to as "silicone oil." In some embodiments, the fluid may be an aliphatic polysiloxane having a refractive index matching the lens material. In some embodiments, the fluid comprises at least one photochromic additive.

[0033] Lens blank 100 is divided into a cavity zone 106 and a bonded zone 108. In certain embodiments, cavity zone 106 extends radially outward from central area 110 of lens blank 100. Central area 110 is shown in FIG. 1 as being in the exact center of lens blank 100. In some embodiments, central area 110 may be offset from the exact center of lens blank 100 in a desired location. Within cavity zone 106, a cavity is formed between membrane 104 and rigid lens 102. The cavity is configured to be at least partially filled with fluid. As the cavity is filled with fluid, the optical power of the fluid lens is determined by the combination of surface topography of the optical surfaces and their spacings and refractive indices of the optical components of the fluid lens, represented by the two surfaces of the rigid lens, the two surfaces of the fluid and the two surfaces of the membrane. As the volume of fluid is altered in the cavity, membrane 104 may inflate or deflate. This inflation may serve to alter the optical power of the fluid lens. In some embodiments, there is a direct and proportional relationship between the change in power of a fluid lens and the level of inflation effected.

[0034] In some embodiments, bonded zone 108 extends radially outward from cavity zone 106. In some embodiments, bonded zone 108 extends to a peripheral edge of rigid lens 102. In some embodiments, bonded zone 108 does not extend to a peripheral edge of rigid lens 102. In some embodiments, membrane 104 extends beyond and overhangs rigid lens

102. Throughout bonded zone 108, membrane 104 is bonded and fluidly sealed to rigid lens 102. In some embodiments, membrane 104 is bonded directly to rigid lens 102. In some embodiments, a layer of material, such as a stiffening layer, is sandwiched between membrane 104 and rigid lens 102. In some embodiments, this bond provides a seal between membrane 104 and rigid lens 102 that provides an environmentally robust diffusion barrier to the fluid in the cavity. Membrane 104 may be bonded to rigid lens 102 in various ways. In some embodiments, membrane 104 is bonded to rigid lens 102 via a heat seal. In some embodiments, membrane 104 is bonded to rigid lens 102 via laser welding. In some embodiments, membrane 104 is bonded to rigid lens 102 via adhesive. Other bonding options may also be used without departure from the spirit and scope of the present invention.

[0035] In some embodiments where adhesive is used to bond membrane 104 to rigid lens 102, the adhesive is index-matched to membrane 104, the fluid, and rigid lens 102. For example, in some embodiments, the refractive index of the rigid lens, the membrane, and the fluid are equal at least to three significant figures, such as 0.002 units at one or more wavelengths, such as at 550 nm. In some embodiments, the refractive indexes of each of the various components are in a range from about 1.47 to about 1.78 measured at about 550 nm. In some embodiments, the refractive indexes of each of the various components are in a range from about 1.52 to about 1.70 measured at about 550 nm. In some embodiments, a refractive index of the adhesive and a refractive index of rigid lens 102 do not differ by more than about 0.05 units. In some embodiments, a refractive index of the adhesive and a refractive index of membrane 104 do not differ by more than about 0.05 units. In some embodiments, a refractive index of the adhesive and a refractive index of the fluid do not differ by more than about 0.05 units. In some embodiments, a refractive index of membrane 104, a refractive index of the fluid, a refractive index of rigid lens 102, and a refractive index of the adhesive do not differ by more than about 0.05 units.

[0036] In some embodiments, bonded zone 108 is in the shape of a loop, such as a circular or elliptical ring. In some embodiments, bonded zone 108 may be a desired non-geometric loop shape. Bonded zone 108 is dimensioned so as to have a bonded loop area with a width and height corresponding to any common spectacle lens size. One example of a common spectacle lens shape is shown in dashed line outline 114. Other common spectacle lens shapes may include, for example, circles, ellipses, rectangles with rounded corners, or irregular shapes. In some embodiments where bonded zone 108 is in the shape of a ring, a

width of the ring can range from about 18 mm to about 40 mm. In some embodiments, the width of the ring can vary across the surface of the lens. In some embodiments, common spectacle lens shapes may be accommodated with a bonded zone 108 having a width in a range from about 6 mm to about 24 mm. In some embodiments, common spectacle lens shapes may be accommodated with a bonded zone 108 having a width in a range from about 6 mm to about 18 mm. In some embodiments, the range of "A" dimensions (nasal-temporal dimensions) of common spectacle frames may be accommodated with a bonded zone 108 having a width in a range from about 26 mm to about 48 mm. In some embodiments, the range of "B" dimensions (vertical dimensions) of common spectacle frames may be accommodated with a bonded zone 108 having a width in a range from about 18 mm to about 30 mm. In some embodiments, a range of inter-pupillary distances that may be accommodated is in a range from about 45 mm to about 75 mm.

[0037] An inner peripheral edge 116 of bonded zone 108 may be in the shape of a circle. In some other embodiments, inner peripheral edge 116 is in the shape of an oval, rectangle, or an irregular pattern. In some embodiments, bonded zone 108 is dimensioned to form a loop that may be trimmed to form a smaller bonded loop having any outside loop width from about 25 mm to about 48 mm and any outside loop height from about 18 mm to about 30 mm.

[0038] FIG. 2 illustrates a front view of a spectacles lens 118 in the form of a trimmed lens 120. Trimmed lens 120 is formed via a manufacturing operation that trims lens blank 100 to a typical spectacle shape and size. Lens blank 100 may be trimmed by any suitable cutting and/or machining method, such as, for example, through a glass cutter, saw, drill, scissors, knife, laser, plasma cutter, or water jet cutter. Because trimmed lens 120 is merely trimmed from lens blank 100 within bonded zone 108, trimmed lens 120 will result in a trimmed rigid lens 122 and a trimmed membrane 124 attached to trimmed rigid lens 122. Like lens blank 100, trimmed lens 120 is divided into cavity zone 106 and a trimmed bonded zone 126. Cavity zone 106 is the same size and shape as cavity zone 106 on lens blank 100. Trimmed bonded zone 126 extends to a peripheral edge of trimmed rigid lens 122. Like bonded zone 108 on lens blank 100, throughout trimmed bonded zone 126, trimmed membrane 124 is bonded and fluidly sealed to trimmed rigid lens 122. This configuration allows for a fluid seal between trimmed membrane 124 and trimmed rigid lens 122, thereby preventing fluid from leaking out from cavity zone 106.

[0039] In trimmed lens 120, the optical power of the fluid lens includes a variable portion corresponding to cavity zone 106 and a fixed portion corresponding to trimmed bonded zone 126. In some embodiments, trimmed membrane 124 is transparent and does not provide a substantial optical power. In some embodiments, the optical power of the fixed portion is provided only by trimmed rigid lens 122. In some embodiments, the optical power of the variable portion is provided by a combination of trimmed rigid lens 122 and the cavity. In some embodiments, the optical power of the variable portion ranges from about -1.0D in an uninflated state to about +1.0D in an inflated state. In some embodiments, the optical power of the variable portion ranges from about +0.25D in an uninflated state to about +4.0D in an inflated state. In some embodiments, the optical power of the variable portion ranges from about -12.00D in an uninflated state to about +12.0D in an inflated state.

[0040] FIG. 13 illustrates a front view of an exemplary trimmed lens with added dimension labels "A" and "B". Dimension "A" identifies a trimmed lens width. Suitable values for this dimension include, but are not limited to, values ranging from approximately 30 mm to approximately 60 mm. Dimension "B" identifies a trimmed lens height. Suitable values for this dimension include, but are not limited to, values ranging from approximately 20 mm to approximately 40 mm.

[0041] FIG. 3 illustrates a front view of lens blank 128 according to an embodiment. In this embodiment, membrane 136 does not extend to a peripheral edge of rigid lens 138. This may occur because the membrane may not be precisely the same size or shape of the rigid lens or may not be perfectly aligned with the rigid lens during the manufacturing process of the lens blank. In some embodiments, a membrane of a different size, shape, and/or alignment compared to the rigid lens is desired. This configuration divides lens blank 128 into three zones—cavity zone 130, bonded zone 132, and outer zone 134. In some embodiments, cavity zone 130 and bonded zone 132 are similar to their respective zones in FIG. 1. Outer zone 134 extends radially outward from a peripheral edge of membrane 136 to a peripheral edge of rigid lens 138. In some embodiments, outer zone includes only rigid lens 138. In some embodiments, outer zone 134 has a width along a surface of rigid lens 138 from about 2 mm to about 10 mm. In some embodiments, outer zone 134 has a width along a surface of rigid lens 138 from about 3 mm to about 6 mm.

[0042] FIG. 4 illustrates a front view of lens blank 140 according to an embodiment. Like lens blank 100 of FIG. 1, lens blank 140 is divided into a cavity zone and a bonded zone.

Cavity zone 142 of lens blank 140 is sub-divided into an aspheric sub-zone 144 extending radially outward from central area 146 of cavity zone 142, and a spherical sub-zone 148 extending radially outward from aspheric sub-zone 144 to bonded zone 150. The curvature of rigid lens 152 within aspheric sub-zone 144 is aspheric and the curvature of rigid lens 152 within spherical sub-zone 148 is spherical. Aspheric sub-zone 144 is in the shape of a circle. In other embodiments, aspheric sub-zone 144 is in the shape of an oval, rectangle, or non-geometric shape. In some embodiments, spherical sub-zone 148 may act as a blending zone that utilizes inflation of membrane 154 to provide a continuous blend of curvatures from the edge of aspheric sub-zone 144 to bonded zone 150.

[0043] In some embodiments, the thickness of membrane 154 within aspheric sub-zone 144 may be contoured to offset the asphericity of rigid lens 152 within aspheric sub-zone 144. In some embodiments, the term "contoured" may denote variation in a mechanical dimension, such as thickness, a mechanical property, such as sag, or an optical property, such as astigmatism or power in the x, y plane. In some embodiments, a contoured thickness may modulate the extent of inflation over the overall surface area in order to bring an inner peripheral edge 156 to a fixed periphery of the fluid lens, which may be defined by a desired frame geometry. In some embodiments, the contour offsets the asphericity of rigid lens 152 when membrane 154 is both inflated and uninflated. In some embodiments, the contour offsets the asphericity of rigid lens 152 only when membrane 154 is inflated or uninflated.

[0044] In some embodiments, the area of aspheric sub-zone 144 may range from about 100 mm² to about 600 mm². In some embodiments, the area of aspheric sub-zone 144 may range from about 180 mm² to about 450 mm². In some embodiments, aspheric sub-zone 144 is in the shape of a continuous convex polynomial, such as an ellipse or circle. In some embodiments, aspheric sub-zone 144 may be in the shape of a desired irregular shape. In some embodiments where aspheric sub-zone 144 is in the shape of an ellipse, the ellipse may have an eccentricity in a range from about 0.95 to about 0.50. In some embodiments, the ellipse may have an eccentricity in a range from about 0.95 to about 0.65.

[0045] In some embodiments, a vertical dimension of aspheric sub-zone 144 is determined based on a potential vertical movement of a pupil. For example, the vertical dimension of the aspheric sub-zone can be determined based on the point of regard of the human eye along the principal meridian of the optic following a path of the pupil when gazing directly forward. In some embodiments, this vertical dimension may be approximately

25 mm. In some embodiments, the vertical dimension may be in the range from about 18 mm to about 24 mm.

[0046] In some embodiments, spherical sub-zone 148 is in the shape of a continuous convex polynomial, such as an ellipse or circle. In some embodiments, spherical sub-zone 148 may be in the shape of a desired irregular shape. In some embodiments where spherical sub-zone 148 is in the shape of a circle, the circle may have a radius in a range from about 10 mm to about 30 mm. In some embodiments, the circle may have a radius in a range from about 12 mm to about 24 mm.

[0047] FIG. 14 illustrates a front view of an exemplary lens blank with added dimension labels "C" through "H".

[0048] Dimension "C" identifies a lens blank diameter. Suitable values for this dimension include, but are not limited to, values ranging from approximately 60 mm to approximately 95 mm.

[0049] Dimension "D" identifies a cavity zone height. Suitable values for this dimension include, but are not limited to, values ranging from approximately 10 mm to approximately 30 mm.

[0050] Dimension "E" identifies a cavity zone width. Suitable values for this dimension include, but are not limited to, values ranging from approximately 20 mm to approximately 40 mm.

[0051] Dimension "F" identifies a width between a membrane and an edge of the lens blank. Suitable values for this dimension include, but are not limited to, values ranging from approximately 1 mm to approximately 30 mm.

[0052] Dimension "G" identifies an aspheric sub-zone height. Suitable values for this dimension include, but are not limited to, values ranging from approximately 10 mm to approximately 20 mm.

[0053] Dimension "H" identifies an aspheric sub-zone width. Suitable values for this dimension include, but are not limited to, values ranging from approximately 12 mm to approximately 30 mm.

[0054] FIG. 5 illustrates a cross-sectional view of a fluid lens 158 according to an embodiment. As described in U.S. Appl. No. 13/407,416, which is incorporated herein by reference in its entirety, membrane 160 may be attached to rigid lens 162 and include a thick zone 164, a hinge-like section 166, and a center disk area 168. In some embodiments, center

disk area 168 may be configured to provide for a substantially constant spherical power greater than approximately 2.0 diopters over a substantially full field of view of a user along the horizontal axis. For example, the full field of view of the user may be approximately 50 mm along the horizontal axis centered at an optical center of fluid lens 158.

[0055] In some embodiments, hinge-like section 166 may accommodate a non-planar geometry of an inflated membrane 160 while still remaining attached to rigid lens 162. In some embodiments, hinge-like section 166 may facilitate full inflation of membrane 160 corresponding to a target power range, while minimizing stresses transferred to a thick zone 164 that would cause astigmatism to build. In some embodiments, hinge-like section 166 may allow sag changes to be "absorbed" without causing substantial optical distortion in both the center disk area 168 and thick zone 164 of membrane 160. In some embodiments, the use of a hinge-like section, such as hinge-like section 166, may make it possible to effectively isolate optical properties of membrane 160 within individual sections. A hinge having a high aspect ratio, which may be defined as the ratio of the width to its thickness, may be particularly effective.

[0056] In some embodiments, thick zone 164 has a thickness of approximately 1 mm, and center disk area 168 has a thickness of approximately 0.225 mm. In some embodiments, center disk area 168 has a diameter of approximately 12 mm, and the disk edge has a diameter of approximately 23.2 mm. Hinge-like section 166 may be formed between thick zone 164 and center disk area 168. In some embodiments, fluid lens 158 may provide for an approximately 22 degree gaze angle between the center of center disk area 168 and the disk edge. In some embodiments, fluid lens 158 may be configured for use with a frame in the shape of a rounded rectangle, approximately 55 mm by 25 mm in size. This configuration may provide acceptable optical performance in center disk area 168 while maintaining acceptable properties to the edge of the frame.

[0057] The term "central optical zone" may be used to denote a viewing zone in the fluid lens centered on an optic axis corresponding to the location of a user's eye. In some embodiments, the optic axis is aligned to the center of the pupil of an average or individual wearer. In some embodiments, the optical zone is approximately 15 mm wide (along the x axis) and approximately 12 mm high (along the y axis), which may correspond to a horizontal gaze angle of approximately +/- 15 degrees and a vertical gaze angle of approximately +/- 12 degrees.

[0058] In some embodiments, center disk area 168 in membrane 160 has a degree of eccentricity of approximately 0.9. That is, the horizontal width is approximately 1.11 times bigger than the vertical width. This design pushes the location of the transition zone corresponding to the hinge-like section to greater gaze angles in the horizontal direction, where it places lesser constraints upon visual width and horizontal eye movements. In some embodiments, a vertical cross-section thickness is approximately 0.200 mm, a width is approximately 3.7 mm, and an aspect ratio is approximately 1:18.5. In some embodiments, the horizontal cross-section thickness is approximately 0.2 mm, with a corresponding width of approximately 1.45 mm, and an aspect ratio of approximately 1:7.

[0059] Hinge width, among other design parameters, may be adjusted as desired. For example, in some embodiments, a combination of a wider hinge along the Y-axis and a thinner hinge along the horizontal axis may serve to reduce astigmatism induced by inflation. In some embodiments, the width may be in the range from about 0.1 mm to about 2.5 mm. In some embodiment, the thickness of hinge-like section 166 ranges from about 0.01 mm to about 0.25 mm. In some embodiments, the thickness of the hinge section ranges from about 0.07 mm to about 0.20 mm. For gaze angles that may be used for near vision (e.g., from about 0 to about 15 degrees), this configuration may provide for target image quality (e.g., having a blur circle at the retina of approximately 10 microns, corresponding to approximately 0.5D of astigmatism, or an approximately spherical equivalent 0.25D of image blur).

[0060] Some embodiments described herein show a relatively stable level of spherical power and astigmatism along the horizontal axis, with a relatively shorter range of spherical power and astigmatism along the vertical axis. As one example, the lens may be configured such that the spherical power varies less than approximately 0.25 diopters over approximately 10 mm (+/- approximately 5 mm) from the optical center. In some embodiments the lens is configured such that the spherical power varies less than approximately 0.25 diopters over approximately 20 mm (+/- approximately 10 mm) from the optical center. In some embodiments, the spherical power and/or astigmatism along the vertical axis may have an equal or greater range compared to the horizontal axis. One measure of optical performance may be the magnitude of induced astigmatism along the horizontal axis. In some embodiments, induced astigmatism may be less than approximately 0.5 diopters over at least approximately 10 mm along the horizontal axis (+/- approximately 5 mm) from the optical

center, and in some embodiments, over approximately 20 mm (+/- approximately 10 mm) from the optical center.

[0061] FIGs. 6-8 illustrate alternative embodiments of lens blanks. FIG. 6 illustrates a front view of lens blank 170 according to an embodiment, wherein aspheric sub-zone 172 is in the shape of an oval and spherical sub-zone 174 is in the shape of a circle. FIG. 7 illustrates a front view of lens blank 176 according to an embodiment wherein both aspheric sub-zone 178 and spherical sub-zone 180 is in the shape of an oval. FIG. 8 illustrates a front view of lens blank 182 according to an embodiment wherein both an inner peripheral edge 184 and an outer peripheral edge 186 of bonded zone 188 are rectangular with rounded corners.

[0062] FIG. 9 illustrates a front view of lens blank 190 according to an embodiment. Lens blank 190 includes a channel 192 formed within rigid lens 194. In some embodiments, channel 192 may allow access to a cavity to exchange fluid between the cavity and a reservoir containing excess fluid in order to alter a hydrostatic pressure of the fluid inside the cavity. In some embodiments, channel 192 is configured to allow fluid to enter or exit the cavity to inflate or uninflate membrane 198. In some embodiments, channel 192 is connected to a reservoir via a connecting tube. In some embodiments, the fluid lens, channel, connecting tube, and reservoir together form a sealed unit.

[0063] In some embodiments, the reservoir may be compressed to push fluid out into the fluid lens via the connecting tube and/or channel. In some embodiments, the reservoir is compressed via a plunger impinging against a diaphragm to increase pressure within the reservoir. In some embodiments, the reservoir is compressed via a caliper. Other suitable configurations may be used. One or more suitable configurations are disclosed, for example, in U.S. Patent No. 8,087,778 to Gupta, which is incorporated by reference herein in its entirety.

[0064] The reservoir may be incorporated into a temple piece, into a spectacles frame, or other desired location. The reservoir may be made of a flexible, transparent, water impermeable material. For example and without limitation, the reservoir may be made of Polyvinylidene Difluoride, such as Heat-shrink VITON(R), supplied by DuPont Performance Elastomers LLC of Wilmington, DE, DERAY- KYF 190 manufactured by DSG-CANUSA of Meckenheim, Germany (flexible), RW-175 manufactured by Tyco Electronics Corp. of Berwyn, PA (formerly Raychem Corp.) (semi-rigid), or other suitable material. Additional

embodiments of reservoirs are described in U.S. Publication No. 2011-0102735, which is incorporated herein by reference in its entirety.

[0065] Alternatively, or in addition, lens blank 190 may include a tube 200 disposed between membrane 198 and rigid lens 194. Tube 200 may be substantially rigid or substantially flexible as desired. In some embodiments, tube 200 is made of the same materials as the reservoir. In some embodiments, tube 200 is made of one or more materials, such as TYGON (polyvinyl chloride), PVDF (Polyvinylidene fluoride), and natural rubber. For example, PVDF may be suitable based on its durability, permeability, and resistance to crimping. Tube 200 may be transparent, translucent, or opaque. In some embodiments, tube 200 has substantially the same refractive index as one or more of rigid lens 194, membrane 198, and the fluid. Like channel 192, tube 200 may be configured to allow fluid to enter or exit the cavity to inflate or uninflate membrane 198. In an embodiment, tube 200 is inserted into channel 192.

[0066] FIG. 10 shows a flow chart 202 for a method of manufacturing a fluid lens assembly according to an embodiment. Reference is made to the fluid lens parts illustrated in FIGs. 1 and 2 for example only. That is, this method may be used to manufacture any suitable fluid lens described herein or otherwise.

[0067] In step 204, a portion of a membrane 104 is bonded to a rigid lens 102 so that the bonded area of membrane 104 is fluidly sealed to rigid lens 102. Any suitable bonding process may be used to bond the membrane to the rigid lens. For example, as described herein, in some embodiments, membrane 104 is bonded to rigid lens 102 via a heat seal. In some embodiments, membrane 104 is bonded to rigid lens 102 via laser welding. In some embodiments, membrane 104 is bonded to rigid lens 102 via adhesive. The bonded area is dimensioned such that a lens blank 100 may be trimmed to form a trimmed lens 120 having a bonded loop area with a width and height corresponding to any common spectacle lens size.

[0068] Step 206 includes trimming lens blank 100 to form a trimmed lens 120 having a bonded loop area with a width and height corresponding to a given spectacle lens size. As described herein, lens blank 100 may be trimmed to a given spectacle shape and size via any suitable cutting and/or machining method, such as, for example, through a glass cutter, saw, drill, scissors, knife, laser, plasma cutter, or water jet cutter.

[0069] FIG. 11 shows a flow chart 208 for a method of manufacturing a fluid lens assembly, according to an embodiment. Reference is made to the fluid lens parts illustrated in

FIG. 9 for example only. That is, this method may be applied to manufacture any suitable fluid lens described herein or otherwise. Step 210 includes forming a channel 192 within a rigid lens 194. Channel 192 may be formed via any suitable machining method, such as, for example, through a glass cutter, saw, drill, scissors, knife, laser, plasma cutter, or water jet cutter. Channel 192 is configured to allow fluid to enter or exit a cavity to inflate or uninflate a membrane 198. In some embodiments, steps 204 and 206 of flow chart 208 will remain substantially the same as described herein for flow chart 202 in FIG. 10.

[0070] FIG. 12 shows a flow chart 212 for a method of manufacturing a fluid lens assembly, according to an embodiment. Reference is made to the fluid lens parts illustrated in FIG. 9 for example only. That is, this method may be applied to manufacture any suitable fluid lens described herein or otherwise. Step 214 includes placing tube 200 between membrane 198 and rigid lens 194 before membrane 198 is fluidly sealed and bonded to rigid lens 194. This may be accomplished, for example, by laying tube 200 across rigid lens 194 before membrane 198 is bonded to rigid lens 194. Tube 200 is configured to allow fluid to enter or exit the cavity to inflate or uninflate the membrane. In some embodiments, steps 204 and 206 of flow chart 212 will remain substantially the same as described herein for flow chart 202 in FIG. 10.

[0071] FIG. 15 illustrates a front view of an array 216 including a plurality of lens blanks 218 (which can also be referred to as "lenslets") according to an embodiment. Each of lens blanks 218 may be any suitable lens blank described herein. In some embodiments, lens blanks 218 are modified from one or more of the lens blanks described herein to achieve a desired array shape or configuration. Array 216 includes eight rows and ten columns of lens blanks 218 arranged in a rectangular shape. In some embodiments, array 216 includes a greater or lesser number of rows and/or columns. In some embodiments, array 216 is a desired non-rectangular shape. Array 216 may be formed from a single flat rigid lens 220, such as, for example, one or more of the rigid lenses described herein. In some embodiments, array 216 includes multiple pieces of rigid lens materials. In some embodiments, rigid lens 220 includes one or more curved pieces of rigid material. In some embodiments, one or more of the plurality of lens blanks 218 provide different optical properties from one or more of the other lens blanks 218 within array 216. For example, one or more of the plurality of lens blanks 218 may include different materials, thicknesses, curvatures, or other properties.

[0072] Array 216 includes vertical channels 222 and horizontal channels 224 formed in rigid lens 220. The channels may, for example, be a suitable depth and width to facilitate separating array 216 into separate lens blanks 218 or into a smaller array of a plurality of lens blanks 218. The separating process may include any suitable cutting and/or machining method described herein, such as, for example, through a glass cutter, saw, drill, scissors, knife, laser, plasma cutter, or water jet cutter. In some embodiments, the channels are diagonal or curved. The channels may be in the form of one or more desired shapes. For example, the channels may be in the shape of one or more of a rectangle, triangle, circle, ellipse, or non-geometric shape. In some embodiments, array 216 does not include channels. In some embodiments, array 216 includes cutting lines on or below a surface of array 216 to facilitate separating array 216 or for other desired uses.

[0073] FIG. 16 illustrates a front view of an array 226 of fluid lenses 228 according to an embodiment. Fluid lenses 228 or a desired plurality of fluid lenses 228 may be sliced apart and used, for example within ophthalmic or microfluidic devices. Each fluid lens 228 includes a cavity zone 230 and bonded zone 232 similar to other suitable fluid lenses described herein. Cavity zone 230 may be in the shape of a circle. In some embodiments, one or more of cavity zones 230 are in other suitable shapes, such as, for example, an ellipse. In some embodiments, cavity zone 230 is formed with a surface relief (e.g., a depression) for each fluid lens 228. Rigid plate 236 may be composed or manufactured similarly to any suitable rigid lenses described herein. In some embodiments, rigid plate 236 is injection molded or cast-molded from a liquid prepolymer using appropriate forming tools or inserts. In some embodiments, rigid plate 236 is machined from a flat panel.

[0074] Array 226 further includes channels 234 that fluidly connect one or more fluid lenses 228 with one or more additional fluid lenses 228. In the embodiment, shown in FIG. 16, channels 234 connect each fluid lens 228 to its two adjacent fluid lenses in a horizontal direction. In some embodiments, one or more channels can have a width ranging from about 20 microns to about 1 mm. Channels can be configured to connect adjacent or non-adjacent fluid lenses in one or more horizontal, vertical, diagonal, or other directions as desired. Channels 234 may be formed, for example, by laser scribing. In some embodiments, channels 234 are formed by water jet processing.

[0075] In the embodiment shown in FIG. 16, several fluid lenses 228 include valves 238 within one or more of channels 234. Valves 238 are controllable to fluidly seal one or more

of channels 234 and prevent fluid from entering or exiting a specific fluid lens 228. In some embodiments, every fluid lens 228 includes at least one valve 238. In some embodiments, valves 238 are configured to automatically fluidly seal channel 234 once a desired state within cavity zone 230 or channel 234 is reached. For example, valves 238 may be configured to automatically fluidly seal channel 234 once a desired fluid pressure, volume, temperature, or flow rate within cavity zone 230 or channel 234 is reached or maintained for a predetermined length of time.

[0076] In some embodiments, valves 238 are operatively connected to a flow controller. Flow controllers may be used to control fluid flow for a single fluid lens 228 or between a plurality of adjacent or non-adjacent fluid lenses 228. The flow controllers may be electrically operated. One or more flow controllers may be addressable by one or more logic controllers to adjust fluid flow within each fluid lens 228 separately. In some embodiments, the adjustment of fluid flows within one or more of the fluid lenses 228 can adjust the optical power for one or more fluid lenses 228. In some embodiments, such a configuration may allow multiple optical powers within a lens array formed by a plurality of lenslets 228. In some embodiments, a lens array formed by a plurality of lenslets 228 can be in the form of bifocal eyeglasses having two distinct optical powers.

[0077] In some embodiments, valves are not used to control optical power within a plurality of fluid lenses. Fluid lenses 228 may be configured to allow for different optical powers within array 226 based on differences between the material properties or shapes of the materials or components. For example, array 226 can include fluid lenses 228 having different membrane materials with different inflation characteristics, different rigid lens curvatures, or different channel thicknesses, any of which may affect the optical powers of one or more fluid lenses 228 within array 226.

[0078] As shown in FIG. 16, array 226 includes eight rows and ten columns of fluid lenses 228 arranged in a rectangular shape. In some embodiments, array 226 includes a greater or lesser number of rows and/or columns. For example, array 226 may include several hundred, thousand, or more fluid lenses 228 formed on a single plate. In some embodiments, array 226 includes 900 fluid lenses 228, with each fluid lens 228 having an area from about 1 mm² to about 10 mm².

[0079] While various embodiments of the present invention have been described above, it should be understood that they have been presented by way of example only, and not

limitation. It will be apparent to persons skilled in the relevant art that various changes in form and detail may be made therein without departing from the spirit and scope of the invention. Thus, the breadth and scope of the present invention should not be limited by any of the above-described exemplary embodiments, but should be defined only in accordance with the following claims and their equivalents.

[0080] The choice of materials for each of the pieces in the embodiments of the assemblies described herein may be informed by the requirements of mechanical properties, temperature sensitivity, optical properties, such as dispersion, moldability properties, or any other factor apparent to a person having ordinary skill in the art. For example, the pieces of the various assemblies described may be manufactured through any suitable process, such as metal injection molding (MIM), cast, machining, plastic injection molding, and the like. The assemblies may be any suitable shape, and may be made of plastic, metal, or other suitable material. In some embodiments, lightweight material may be used such as, for example and without limitation, high impact resistant plastics material, aluminum, titanium, or the like. In some embodiments, one or more of the parts may be made entirely or partly of a transparent material.

[0081] Further, the purpose of the foregoing Abstract is to enable the U.S. Patent and Trademark Office and the public generally, and especially the scientists, engineers and practitioners in the art who are not familiar with patent or legal terms or phraseology, to determine quickly from a cursory inspection the nature and essence of the technical disclosure of the application. The Abstract is not intended to be limiting as to the scope of the present invention in any way.

WHAT IS CLAIMED IS:

1. A lens blank for a fluid lens, the lens blank comprising:
 - a rigid lens; and
 - a semi-flexible inflatable membrane attached to the rigid lens,wherein the lens blank is divided into at least two zones, the zones comprising:
 - a cavity zone extending radially outward from a central area of the lens blank, forming a cavity between the membrane and the rigid lens in the cavity zone, and
 - a bonded zone extending radially outward from the cavity zone, wherein the membrane is bonded and fluidly sealed to the rigid lens throughout the bonded zone,wherein the bonded zone is dimensioned to be trimmed to accommodate a plurality of frame shapes and sizes.
2. The lens blank of claim 1, wherein the plurality of frame shapes and sizes includes every frame shape and size ranging in width from about 20 mm to about 60 mm and ranging in height from about 10 mm to about 30 mm.
3. The lens blank of claim 1, wherein the lens blank is divided into at least three zones, the third zone comprising:
 - an outer zone extending radially outward from a peripheral edge of the membrane to a peripheral edge of the rigid lens.
4. The lens blank of claim 1, wherein the membrane is sealed directly to the rigid lens.
5. The lens blank of claim 1,
 - wherein the cavity zone is sub-divided into an aspheric sub-zone extending radially outward from a central area of the cavity zone, and a spherical sub-zone extending radially outward from the aspheric sub-zone to the bonded zone,
 - wherein the curvature of the rigid lens within the aspheric sub-zone is aspheric and the curvature of the rigid lens within the spherical sub-zone is spherical, and
 - wherein the thickness of the membrane within the aspheric sub-zone is contoured such that the contour offsets the asphericity of the rigid lens within the aspheric sub-zone.
6. The lens blank of claim 5, wherein the aspheric sub-zone is in the shape of an oval.

7. The lens blank of claim 1, wherein the inner peripheral edge of the bonded zone is in the shape of an oval.
8. The lens blank of claim 1, wherein the optical power of the cavity zone ranges from about -1.0D in an uninflated state to about +1.0D in an inflated state.
9. The lens blank of claim 1, wherein the optical power of the variable portion ranges from about +0.25D in an uninflated state to about +4.0D in an inflated state.
10. The lens blank of claim 1, wherein a refractive index of the rigid lens and a refractive index of the membrane do not differ by more than 0.01 units.
11. The lens blank of claim 1, wherein the cavity is at least partially filled with fluid comprising at least one photochromic additive.
12. The lens blank of claim 1, wherein the lens blank further comprises:
 - a channel formed within the rigid lens, wherein the channel is configured to allow fluid to enter or exit the cavity to inflate or uninflate the membrane.
13. The lens blank of claim 1, wherein the lens blank further comprises:
 - a tube disposed between the membrane and rigid lens, wherein the tube is configured to allow fluid to enter or exit the cavity to inflate or uninflate the membrane.
14. The lens blank of claim 1, wherein the membrane is bonded to the rigid lens via adhesive.
15. The lens blank of claim 14, wherein a refractive index of the adhesive and a refractive index of the rigid lens do not differ by more than 0.01 units.
16. The lens blank of claim 14, wherein a refractive index of the adhesive and a refractive index of the membrane do not differ by more than 0.01 units.
17. The lens blank of claim 14, wherein a refractive index of the adhesive and a refractive index of fluid disposed within the cavity do not differ by more than 0.01 units.
18. A method of manufacturing a fluid lens assembly from a lens blank including a semi-flexible inflatable membrane and a rigid lens, the method comprising:

bonding a portion of the membrane to the rigid lens so that the bonded area of the membrane is fluidly sealed to the rigid lens, wherein the bonded zone is dimensioned to be trimmed to accommodate a plurality of frame shapes and sizes; and
trimming the lens blank to form a trimmed lens.

19. The method of claim 18, further comprising:
forming a channel within the rigid lens, wherein the channel is configured to allow fluid to enter or exit the cavity to inflate or uninflate the membrane.
20. The method of claim 18, further comprising:
placing a tube between the membrane and rigid lens before the membrane is bonded to the rigid lens, wherein the tube is configured to allow fluid to enter or exit the cavity to inflate or uninflate the membrane.
21. An array of lens blanks, the array comprising:
a plurality of lens blanks according to claim 1.
22. The array of lens blanks of claim 21, wherein the plurality of rigid lenses is formed from a single sheet of material.
23. The array of lens blanks of claim 21, wherein one or more of the plurality of lens blanks have different optical properties with respect to one or more of the other lens blanks within the array.
24. An array of fluid lenses, the array comprising:
a plurality of fluid lenses comprising:
a rigid lens; and
a semi-flexible inflatable membrane attached to the rigid lens,
wherein the fluid lens is divided into at least two zones, the zones comprising:
a cavity zone extending radially outward from a central area of the lens blank, forming a cavity between the membrane and the rigid lens in the cavity zone, and
a bonded zone extending radially outward from the cavity zone, wherein the membrane is bonded and fluidly sealed to the rigid lens throughout the bonded zone,
wherein one or more of the plurality of lens blanks are fluidly connected to one or more of the other fluid lenses within the array.

25. They array of claim 24, wherein the one or more of the plurality of fluid lenses are fluidly connected to one or more of the other lens blanks within the array through a fluid channel formed between the fluid lenses.
26. They array of claim 24, wherein one or more of the fluid lenses comprises a valve controllable to fluidly seal one or more of the fluid channel.