



(51) International Patent Classification:
B29C 47/10 (2006.01)

(21) International Application Number:
PCT/EP2009/053204

(22) International Filing Date:
18 March 2009 (18.03.2009)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
08103227.8 31 March 2008 (31.03.2008) EP

(71) Applicant (for all designated States except US): **INEOS EUROPE LIMITED** [GB/GB]; Hawkslease, Chapel Lane, Lyndhurst Hampshire SO43 7FG (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **PITMAN, Gary Lindsay** [GB/GB]; 8 Windsor Place, Stirling FK8 2HY (GB).

(74) Agent: **KING, Alex**; Compass Patents Llp, 120 Bridge Road, Chertsey Surrey KT16 8LA (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ,

CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:


- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))
- of inventorship (Rule 4.17(iv))

Published:

- with international search report (Art. 21(3))

(54) Title: EXTRUDER AND PROCESS FOR EXTRUDING A POLYMER

Fig. 1



(57) Abstract: The present invention relates to an extruder for a polymer, and a process for extruding a polymer using said extruder. In particular, the present invention provides an extruder comprising: (i) two or more barrel sections (1a, 1b, 1c) arranged sequentially from: (a) an upstream feed barrel section (1a) to which polymer feedstock to be extruded is fed, the upstream feed barrel section containing two or more screws each having a diameter of X; to (b) a downstream barrel section (1c) from which melted polymer is passed to a die and extruded; and (ii) one or more feed ports for feeding polymer feedstock to be extruded into the extruder at its upstream end, characterised in that the total area of the one or more feed ports through which polymer feedstock is introduced is greater than 4*X, and a process for extrusion of polymer comprising feeding a polymer feedstock to the feed port of such an extruder.