

TAP WATER COLLECTING DEVICE

BACKGROUND

1. Technical Field

[0001] The present disclosure relates to a tap water collecting device, and in particular to, a tap water collecting device on which a shower head is located and placed easily and stably without falling off.

2. Description of Related Art

[0002] The earliest way people can bathe can be a bath or a shower. As a shower head is provided, it changes the world, and the people now mostly take a shower when bathing. The structure of the conventional shower head has a hollow grip disposed on an top end of a water outlet, and a terminal end of the grip is connected to a water-tap via a soft tube, such that the water flow is spurted out from the water outlet with a splash or beam shape, and the user can use the shower head to take the shower.

[0003] However, some the water amount of some shower device is not enough due to the too long path from the tube or water heater to the shower head, or most some shower device firstly outputs cold water from the shower head since the time of the water heater for heating the water is too long. Currently, the user lets the cold water flow to a drainage hole, and thus this cause the waste of the water resource. Further, to make sure the water is hot, the user usually use her/his hand or leg skin to sense the temperature of the water as the basis of controlling and adjusting the water temperature. However,

such manner may have a potential danger, especially when the temperature of the output water is too high, the user cannot react in real time, and only after her/his skin is burned and feels hurt, she/he knows how to adjust the water temperature, which easily causes the improperly handled and burned events. Thus, how to design a novel hardware to efficiently collect and reuse the firstly output water of the shower head, to indicate the output water temperature of the shower head to the user, and to achieve the objective of absence of wasting the water resource without burning the user is an issue which the bath product manufacturers and researcher try to solve and overcome.

SUMMARY

[0004] Accordingly, the present disclosure provides an improved tap water collecting device on which a shower head is located and placed easily and stably without falling off. By the hardware design of the surrounding on wall and the opening slot, the shower head can efficiently contact the opening slot and smoothly slide from the expanded oblique sections tapered arc sections, and be located and hanged at the stop straight section, such that the objectives of easily placing and stably fixing without falling off can be achieved. The tap water collecting device collects the cold water firstly output from the shower head, and the laterally disposed temperature display can indicate the temperature, such that the danger that the user tests the water temperature by her/his body can be avoided. Accordingly, the objectives of fixing the shower head to a location and easily collecting the water without

wasting the water resource can be achieved, and the present disclosure can have benefits of recycling economic.

[0005] According to the objective of the present disclosure, a tap water collecting device is illustrated, and the tap water collecting device provides a fixed hanging location to a shower head to collect the water output from the shower head. The tap water collecting device at least comprises a pendant, a temperature display and a tube. The pendant comprises a surrounding, an opening disposed on a top end of the surrounding and a tapered tube portion disposed on a bottom end of the surrounding, and the surrounding comprises an opening slot, a fixing portion and a sleeve hole, wherein the opening slot is disposed at a side of the surrounding, the opening slot comprises two opposite vertical straight sections connected to the opening, two opposite expanded oblique sections disposed corresponding to the opening and respectively connected to terminal ends of the vertical straight sections, two opposite tapered arc sections respectively disposed corresponding to the vertical straight sections and respectively connected to terminal ends of the expanded oblique sections and a stop straight section connected to the tapered arc sections and closing the opening slot, the vertical straight section and the expanded oblique section have a first angle therebetween, the sleeve hole is disposed in an internal end of the fixing portion, and multiple external threads are disposed on a bottom end of the tapered tube portion. The temperature display is fixed and connected to the fixing portion, and the temperature display has a temperature sensing convex, wherein the temperature sensing convex extends to interior of

the surrounding via the sleeve hole. The tube is connected to the bottom end of the tapered tube portion, a sleeve is disposed on a terminal end of the tube, and the terminal end of the tube contacts of the tapered tube portion, wherein multiple internal threads are disposed on an internal end of the sleeve, such that the sleeve is fixed and screwed to the external threads of the tapered tube portion via the internal threads, and the tube is fixed to pendant.

[0006] In an embodiment of the present disclosure, the first angle is 5 degrees through 30 degrees.

[0007] In an embodiment of the present disclosure, the tapered arc section and the stop straight section have a second angle therebetween.

[0008] In an embodiment of the present disclosure, the second angle is 5 degrees through 30 degrees.

[0009] In an embodiment of the present disclosure, the opening slot further has an outer cover layer covering the opening slot.

[0010] In an embodiment of the present disclosure, the fixing portion further comprises an engaging portion and a slot portion disposed in an internal end of the engaging portion.

[0011] In an embodiment of the present disclosure, the temperature display is engaged to the engaging portion via a latch.

[0012] In an embodiment of the present disclosure, the fixing portion further comprises a fixing hole and a first screw screwing through the fixing hole.

[0013] In an embodiment of the present disclosure, the tube has a water collecting device disposed on another terminal end of the tube, and the other terminal end of the tube is disposed corresponding to the sleeve.

[0014] In an embodiment of the present disclosure, the surrounding has a decoration portion disposed on another side of the surrounding, and the other side of the surrounding is disposed corresponding to the opening slot.

[0015] In an embodiment of the present disclosure, the decoration portion is one of a convex wavy decoration portion or a straight convex decoration portion.

[0016] In an embodiment of the present disclosure, the decoration portion has multiple through holes.

[0017] In an embodiment of the present disclosure, the pendant is fixed to a wall by screwing at least second screws through the through holes.

[0018] In an embodiment of the present disclosure, the opening of the pendant is provided to receive a shower head, such that the shower head contacts the expanded oblique sections and the tapered arc sections of the opening slot; wherein a terminal end of the shower head is connected to a grip.

[0019] To sum up, by the hardware design of the surrounding on wall and the opening slot, the shower head can efficiently contact the opening slot and smoothly slide from the expanded oblique sections tapered arc sections, and be located and hanged at the stop straight section, such that the objectives of easily placing and stably fixing without falling off can be achieved. The tap water collecting device collects the cold water firstly output from the shower

head, and the laterally disposed temperature display can indicate the temperature, such that the danger that the user tests the water temperature by her/his body can be avoided. Accordingly, the objectives of fixing the shower head to a location and easily collecting the water without wasting the water resource can be achieved, and the present disclosure can have benefits of recycling economic.

BRIEF DESCRIPTION OF THE DRAWINGS

[0020] The accompanying drawings are included to provide a further understanding of the present disclosure, and are incorporated in and constitute a part of this specification. The drawings illustrate exemplary embodiments of the present disclosure and, together with the description, serve to explain the principles of the present disclosure.

[0021] FIG. 1 is a three dimensional schematic diagram of a tap water collecting device according to an embodiment of the present disclosure.

[0022] FIG. 2 is an explosive diagram of a tap water collecting device according to an embodiment of the present disclosure.

[0023] FIG. 3 is a plan view of a tap water collecting device according to an embodiment of the present disclosure.

[0024] FIG. 4 is a schematic diagram showing an angle of an opening slot of a tap water collecting device according to an embodiment of the present disclosure.

[0025] FIG. 5 is another schematic diagram showing an opening slot of a tap water collecting device according to an embodiment of the present disclosure.

[0026] FIG. 6 is a schematic diagram showing an operation of a temperature display of a tap water collecting device according to an embodiment of the present disclosure.

[0027] FIG. 7 is a first schematic diagram showing installation of shower head of a tap water collecting device according to an embodiment of the present disclosure.

[0028] FIG. 8 is a second schematic diagram showing installation of shower head of a tap water collecting device according to an embodiment of the present disclosure.

[0029] FIG. 9 is an explosive diagram of a tap water collecting device according to another embodiment of the present disclosure.

[0030] FIG. 10 is a three dimensional schematic diagram of a tap water collecting device according to another embodiment of the present disclosure.

DESCRIPTION OF THE EXEMPLARY EMBODIMENTS

[0031] To understand the technical features, content and advantages of the present disclosure and its efficacy, the present disclosure will be described in detail with reference to the accompanying drawings. The drawings are for illustrative and auxiliary purposes only and may not necessarily be the true scale and precise configuration of the present disclosure. Therefore, the scope

of the present disclosure should not be limited to the scale and configuration of the attached drawings.

[0032] Firstly, referring to FIG. 1 through FIG. 6, the drawings show a three dimensional diagram, an explosive diagram and a plan view of a tap water collecting device according to an embodiment of the present disclosure, and a schematic diagram of an angle of an opening slot. The tap water collecting device (1) of the present disclosure provide a fixed hanging location to a shower head (not shown in the drawings), which can collect the output water of the shower head, and the tap water collecting device (1) at least comprises a pendant (11), a temperature display (12) and a tube (13).

[0033] The pendant (11) comprises a surrounding (111), an opening (112) disposed on a top end of the surrounding (111) and a tapered tube portion (113) disposed on a bottom end of the surrounding (111), the surrounding comprises (111) an opening slot (1111), a fixing portion (1112) and a sleeve hole (1113), wherein the opening slot (1111) is disposed at a side of the surrounding (111), the opening slot (1112) comprises two opposite vertical straight sections (11111) connected to the opening (112), two opposite expanded oblique sections (11112) disposed corresponding to the opening (112) and respectively connected to terminal ends of the vertical straight sections (11111), two opposite tapered arc sections (11113) respectively disposed corresponding to the vertical straight sections (11111) and respectively connected to terminal ends of the expanded oblique sections (11112) and a stop straight section (11114) connected to the tapered arc sections (11113) and

closing the opening slot (1111). The vertical straight section (11111) and the expanded oblique section (11112) have a first angle (θ_1) therebetween, and the sleeve hole (1113) is disposed in an internal end of the fixing portion (1112), and multiple external threads (1131) are disposed on a bottom end of the tapered tube portion (113). Further, the first angle (θ_1) is 5 degrees through 30 degrees. Moreover, the tapered arc section (11113) and the stop straight section (11114) have a second angle (θ_2) therebetween, wherein the second angle (θ_2) is 5 degrees through 30 degrees. Further, as shown in FIG. 5, the opening slot (1111) further has an outer cover layer (1115) covering the opening slot (1111). In a preferred embodiment of the present disclosure, the pendant (11) is formed by the surrounding (111), the opening (112) and the tapered tube portion (113), wherein the opening (112) is disposed on the top end of the surrounding (111), and the tapered tube portion (113) is connected to and disposed on the bottom end of the surrounding (111). Further, the surrounding (111) further has the opening slot (1111), the fixing portion (1112) and the sleeve hole (1113), wherein the opening slot (1111) is disposed on the side of the surrounding (111) with a square shape, the fixing portion (1112) is formed on the other side of the surrounding (111), and the sleeve hole (1113) is formed on the internal end of the fixing portion (1112). Moreover, the opening slot (1111) comprises two opposite vertical straight sections (11111) extending downward from the opening (112), two opposite expanded oblique sections (11112) disposed corresponding to the opening (112) and respectively extending from the terminal ends of the vertical straight sections (11111), two opposite tapered arc

sections (11113) respectively extending from the terminal ends of the expanded oblique sections (11112) and a stop straight section (11114) connected to the tapered arc sections (11113), wherein the vertical straight section (11111) and the expanded oblique section (11112) have the first angle (θ_1) being 5 degrees through 30 degrees, therebetween, the first angle (θ_1) is the better guiding angle which the shower head placed in the opening slot (1111), the tapered arc section (11113) and the stop straight section (11114) have the second angle (θ_2) being 5 degrees through 30 degrees, therebetween, and the second angle (θ_2) is the better guiding angle which the shower head placed in the opening slot (1111). That is, when the shower head is to be placed on the pendant (11), the shower head is firstly placed in the opening slot (1111) via the opening (112), then the shower head contacts the opening slot (1111) and smoothly slides and displaces from the expanded oblique sections (11112) and the tapered arc sections (11113) via the first angle (θ_1) and the second angle (θ_2), and thus the shower head is hooked by and located at the stop straight section (11114) to achieve the objectives of easily placing and being stable without falling off. The output water of the shower head can be collected by the tapered tube portion (113), and then smoothly outputs. In addition, as shown in FIG. 5, the opening slot (1111) has the outer cover layer (1115) which covers the opening slot (1111), such that via the protection of the outer cover layer (1115), it prevents the shower head from being scratched during the location procedure which the shower head slides in the opening slot (1111).

[0034] The temperature display (12) is fixed and connected to the fixing portion (1112), and the temperature display (12) has a temperature sensing convex (121), wherein the temperature sensing convex (121) extends to interior of the surrounding (111) via the sleeve hole (1113). Further, the fixing portion (1112) comprises an engaging portion (11121) and a slot portion (11122) disposed in an internal end of the engaging portion (11121). Moreover, the temperature display (12) is engaged to the engaging portion (11121) via a latch (122). Further referring to FIG. 6 simultaneously, which is a schematic diagram showing an operation of the tap water collecting device according to an embodiment of the present disclosure, wherein the temperature display (12) is engaged into the slot portion (11122) of the fixing portion (1112) to connect with the engaging portion (11121). When the temperature display (12) is damaged, the temperature display (12) can be detached and replaced easily. The temperature sensing convex (121) disposed at the terminal end of the temperature display (12) is protruding out from the interior of the surrounding (111) via the sleeve hole (1113), such that when the shower head outputs the hot water, the temperature sensing convex (121) directly contacts the hot water, and the temperature display (12) can display the water temperature of the shower head in real time.

[0035] The tube (13) is connected to the bottom end of the tapered tube portion (113), a sleeve (131) is disposed on a terminal end of the tube (13), the terminal end of the tube (13) contacts of the tapered tube portion (113), wherein multiple internal threads (1311) are disposed on an internal end of the

sleeve (131), such that the sleeve (131) is fixed and screwed to the external threads (1131) of the tapered tube portion (113) via the internal threads (1311), and the tube (13) is fixed to pendant (11). Further, another terminal end of the tube (13) is connected to a water collecting device (not shown in the drawings). In a preferred embodiment of the present disclosure, the tube (13) is connected to the bottom end of the tapered tube portion (113), and the terminal end of the tube (13) which contacts the tapered tube portion (113) has the sleeve (131), wherein the interior of the sleeve (131) has the multiple internal threads (1311), such the sleeve (131) is screwed to the external threads (1131) of the tapered tube portion (113) via the internal threads (1311), the tube (13) is fixed to the pendant (11), and the water collecting device which disposed on the other terminal end of the tube (13) corresponding to the sleeve (131) can collect the output water of the tapered tube portion (113).

[0036] That is, referring to FIG. 7 and FIG. 8 simultaneously, which are first and second schematic diagrams showing installation of shower head of a tap water collecting device according to an embodiment of the present disclosure, the tap water collecting device (1) of the present disclosure provides a fixed hanging location to the shower head (2) and collects the output water of the shower head (2), wherein the tap water collecting device (1) can be adopted by the shower heads (2) different dimensions via the expanded oblique sections (11112) and the tapered arc sections (11113). The shower head (2) can be placed in the opening (112) of the pendant (11), and the shower head (2) can contact the expanded oblique sections (11112) and the tapered arc sections

(11113) of the opening slot (1111). A terminal end of the shower head (2) is connected to a grip (21), and the shower head (2) is fixed to the pendant (11) and guided to smoothly displace via the expanded oblique sections (11112) and the tapered arc sections (11113), such that it can efficiently prevent the shower head (2) from being stuck and unable to fall in the stop straight section (11114). The tap water collecting device (1) is helpful to the shower head (2) placed in the pendant (11) for being successfully guided to displace and stably located. When the shower head (2) is switched to output the hot water, the tap water collecting device (1) can collect the cold water firstly output from the shower head (2), and the tapered tube portion (113) collects the cold water and smoothly outputs the cold water to the water collecting device for storing the cold water.

[0037] In addition, referring to FIG. 9, which is an explosive diagram of a tap water collecting device according to another embodiment of the present disclosure, the fixing portion (1112) can further comprises a fixing hole (11123) and a first screw (not shown in the drawings) being screwed through the fixing hole (11123). The fixing portion (1112) is formed by the fixing hole (11123) and the first screw, the temperature display (12) is fixed to the fixing hole (11123) via the first screw, and the temperature sensing convex (121) is protruding out from the interior of the surrounding (111) via the sleeve hole (1113). When the shower head (2) outputs the hot water, the temperature sensing convex (121) directly contacts the hot water, and the temperature

display (12) can display the water temperature of the shower head (2) in real time.

[0038] Further, the other terminal end of the surrounding (111) corresponding to the opening slot (1111) further has a decoration portion (1114), wherein the decoration portion (1114) is one of a convex wavy decoration portion or a straight convex decoration portion, and the decoration portion (1114) has multiple through holes (11141). Moreover, the pendant (11) can be fixed and screwed to a wall via at least two second screws (11142) which screws through the through holes (11141). Referring to FIG. 1 again, the decoration portion (1114) being the convex wavy decoration portion is disposed on the terminal end of the decoration portion (1114) corresponding to the opening slot (1111), the decoration portion (1114) has three through holes (11141), and the tap water collecting device (1) is fixed and screwed to the wall via the three second screws (11142) which screws through the through holes (11141). Referring to FIG. 10 simultaneously, which is a three dimensional schematic diagram of a tap water collecting device according to another embodiment of the present disclosure, the decoration portion (1114) being the straight convex decoration portion is disposed on the terminal end of the decoration portion (1114) corresponding to the opening slot (1111), the decoration portion (1114) has three through holes (11141), and the tap water collecting device (1) is fixed and screwed to the wall via the three second screws (11142) which screws through the through holes (11141).

[0039] According to the above descriptions, compared to the conventional product and technology, the present disclosure has the advantages as follows.

[0040] By the hardware design of the surrounding on wall and the opening slot, the shower head can efficiently contact the opening slot and smoothly slide from the expanded oblique sections tapered arc sections, and be located and hanged at the stop straight section, such that the objectives of easily placing and stably fixing without falling off can be achieved. The tap water collecting device collects the cold water firstly output from the shower head, and the laterally disposed temperature display can indicate the temperature, such that the danger that the user tests the water temperature by her/his body can be avoided. Accordingly, the objectives of fixing the shower head to a location and easily collecting the water without wasting the water resource can be achieved, and the present disclosure can have benefits of recycling economic.

[0041] To sum up, the tap water collecting device provided by the present disclosure is not anticipated by publications or used in public, which meets patentability of the invention. Examination of the present disclosure is respectfully requested, as well as allowance of the present disclosure.

[0042] The above-mentioned descriptions represent merely the exemplary embodiment of the present disclosure, without any intention to limit the scope of the present disclosure thereto. Various equivalent changes, alternations or modifications based on the claims of present disclosure are all

consequently viewed as being embraced by the scope of the present disclosure.

WHAT IS CLAIMED IS:

1. A tap water collecting device, at least comprising:

a pendant comprising a surrounding, an opening disposed on a top end of the surrounding and a tapered tube portion disposed on a bottom end of the surrounding, the surrounding comprises an opening slot, a fixing portion and a sleeve hole, wherein the opening slot is disposed at a side of the surrounding, the opening slot comprises two opposite vertical straight sections connected to the opening, two opposite expanded oblique sections disposed corresponding to the opening and respectively connected to terminal ends of the vertical straight sections, two opposite tapered arc sections respectively disposed corresponding to the vertical straight sections and respectively connected to terminal ends of the expanded oblique sections and a stop straight section connected to the tapered arc sections and closing the opening slot, the vertical straight section and the expanded oblique section have a first angle therebetween, the sleeve hole is disposed in an internal end of the fixing portion, and multiple external threads are disposed on a bottom end of the tapered tube portion;

a temperature display fixed and connected to the fixing portion, the temperature display has a temperature sensing convex, wherein the temperature sensing convex extends to interior of the surrounding via the sleeve hole; and

a tube connected to the bottom end of the tapered tube portion, a sleeve

is disposed on a terminal end of the tube, the terminal end of the tube contacts of the tapered tube portion, wherein multiple internal threads are disposed on an internal end of the sleeve, such that the sleeve is fixed and screwed to the external threads of the tapered tube portion via the internal threads, and the tube is fixed to pendant.

2. The tap water collecting device according to claim 1, wherein the first angle is 5 degrees through 30 degrees.
3. The tap water collecting device according to claim 1, wherein the tapered arc section and the stop straight section have a second angle therebetween.
4. The tap water collecting device according to claim 3, wherein the second angle is 5 degrees through 30 degrees.
5. The tap water collecting device according to claim 1, wherein the opening slot further has an outer cover layer covering the opening slot.
6. The tap water collecting device according to claim 1, wherein the fixing portion further comprises an engaging portion and a slot portion disposed in an internal end of the engaging portion.
7. The tap water collecting device according to claim 6, wherein the temperature display is engaged to the engaging portion via a latch.
8. The tap water collecting device according to claim 1, wherein the fixing portion further comprises a fixing hole and a first screw screwing through the fixing hole.

9. The tap water collecting device according to claim 1, wherein the tube has a water collecting device disposed on another terminal end of the tube, and the other terminal end of the tube is disposed corresponding to the sleeve.
10. The tap water collecting device according to claim 1, wherein the surrounding has a decoration portion disposed on another side of the surrounding, and the other side of the surrounding is disposed corresponding to the opening slot.
11. The tap water collecting device according to claim 10, wherein the decoration portion is one of a convex wavy decoration portion or a straight convex decoration portion.
12. The tap water collecting device according to claim 10, wherein the decoration portion has multiple through holes.
13. The tap water collecting device according to claim 12, wherein the pendant is fixed to a wall by screwing at least second screws through the through holes.
14. The tap water collecting device according to claim 1, wherein the opening of the pendant is provided to receive a shower head, such that the shower head contacts the expanded oblique sections and the tapered arc sections of the opening slot; wherein a terminal end of the shower head is connected to a grip.