

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
14 October 2004 (14.10.2004)

PCT

(10) International Publication Number
WO 2004/088305 A1

(51) International Patent Classification⁷: **G01N 33/18**,
31/10, 27/413, 27/30

[AU/AU]; 34 Kincaid Drive, Highland Park, QLD 4211 (AU).

(21) International Application Number:
PCT/AU2004/000438

(74) Agent: **MISCHLEWSKI, Darryl**; IP Strategies, P.O. Box 1254, Camberwell, VIC 3124 (AU).

(22) International Filing Date: 5 April 2004 (05.04.2004)

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003901589 4 April 2003 (04.04.2003) AU

(71) Applicant (for all designated States except US): **GRIF-FITH UNIVERSITY** [AU/AU]; Kessels Road, Nathan, QLD 4111 (AU).


(72) Inventor; and

(75) Inventor/Applicant (for US only): **ZHAO, Huijun**

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

[Continued on next page]

(54) Title: PHOTOELECTROCHEMICAL DETERMINATION OF CHEMICAL OXYGEN DEMAND



(57) Abstract: A method for determining chemical oxygen demand of a water sample comprises the steps of (a) applying a constant potential bias to a photoelectrochemical cell, having a photoactive working electrode (e.g. a layer of titanium dioxide nanoparticles coated on an inert conductive substrate) and a counter electrode, and containing a supporting electrolyte solution; (b) illuminating the working electrode with a light source and recording the background photocurrent produced at the working electrode from the supporting electrolyte solution; (c) adding a water sample, to be analysed, to the photoelectrochemical cell; (d) illuminating the working electrode with a light source and recording the total photoelectrocurrent produced with the sample; (e) determining the chemical oxygen demand according to the type (exhaustive or non-exhaustive) of degradation conditions employed. An apparatus for carrying out the method is also claimed.



Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*