PCT WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : G11B 33/04 — A1

(11) International Publication Number: WO 96/14636

(43) International Publication Date: 17 May 1996 (17.05.96)

(21) International Application Number: PCT/GB95/02581

(22) International Filing Date: 3 November 1995 (03.11.95)

(30) Priority Data:
9422190.0 3 November 1994 (03.11.94) GB

(71) Applicant *(for all designated States except US)*: THE DUBOIS PLC [GB/GB]; 3/4 Great Marlborough Street, London W1V 3AR (GB).

(72) Inventors; and
(75) Inventors/Applicants *(for US only)*: PIJANOWSKI, Stefan, Alexander [GB/GB]; 24 Clifton Drive, Oundle, Northants PE8 4EP (GB). FRASER, Anthony, Henry, Joseph [GB/GB]; 4 Wilmington House, Highbury Crescent, London N5 1RU (GB). FARRAR, Peter, Antony [GB/GB]; Glenelg House, Gladstone Road, Rawdon, Leeds LS19 6HZ (GB).

(74) Agent: S.G. UNWIN & CO.; Brookfurlong Farmhouse, Islip, Oxford OX5 2TJ (GB).

(81) Designated States: AL, AM, AT, AT (Utility model), AU, BB, BG, BR, BY, CA, CH, CN, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), TJ, TM, TT, UA, UG, US, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, LS, MW, SD, SZ, UG).

Published
With international search report.
With amended claims and statement.

SG 9701833-7

(54) Title: APPARATUS FOR HOLDING A COMPACT DISK

(57) Abstract

The apparatus comprises: a base portion (12), disk-engaging means (15, 16) extending from the base portion (12) for releasably engaging the central hole of the disk; and resilient ejection means (17) arranged to urge the compact disk out of engagement with the disk-engaging means (15, 16) when the disk-engaging means (15, 16) is released, the disk-engaging means comprising resilient inwardly extending radial arms (15), cantilevered from the base portion (12); the inner ends of the arms (15) being mechanically interconnected (16, 21) so that pressure applied to any one or more of the inner ends of the arms (15) flexes each of the arms (15) towards the base portion (12) to move the inner ends of the arms (15) towards each other sufficiently to release their engagement with the disk. The apparatus may be formed as a one-piece plastics moulding as a tray for insertion in a box or as part of a wall of a video-style library box.

