

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
21 April 2005 (21.04.2005)

PCT

(10) International Publication Number
WO 2005/036035 A2

- (51) International Patent Classification⁷: **F16K**
- (21) International Application Number:
PCT/US2004/033180
- (22) International Filing Date: 8 October 2004 (08.10.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/481,495 9 October 2003 (09.10.2003) US
- (71) Applicant (for all designated States except US): **EMERSON ELECTRIC CO.** [US/US]; 8000 West Florissant, St. Louis, MO 63136 (US).

Stephen [US/US]; 407 West Vine Street, Hatfield, PA 19440 (US).


(74) Agent: **GLEASON, Mark, L.**; Locke, Liddell & Sapp LLP, 600 Travis Street, Suite 3400, Houston, TX 77002 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

[Continued on next page]

(54) Title: VALVE ASSEMBLY



(57) Abstract: A flow control valve includes an inlet and an outlet through which fluid enters and exits the valve. A valve plunger has a guide spring attached thereto, such that the guide spring is situated between the plunger and a valve orifice. The plunger, and thus the guide spring, is movable relative to the orifice to control fluid flow through the valve. The guide spring and the orifice surface adjacent the guide spring define coplanar surfaces that seal against each other when the valve is closed.

WO 2005/036035 A2



SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *without international search report and to be republished upon receipt of that report*