

"HERMETIC COMPRESSOR WITH A HEAT DISSIPATION SYSTEM"

Field of the Invention

The present invention refers to a hermetic compressor of the type used in refrigeration appliances, such as refrigerators and freezers, and which is provided with a heat dissipation system in the interior of the compressor, said system being particularly used to transfer thermal energy from the hot parts of the interior of the compressor to ambients located external and distant from the cylinder block thereof.

Background of the Invention

Hermetic compressors of the type used in refrigeration systems usually comprise, in the interior of a casing, a motor-compressor assembly having a cylinder block within which is defined a cylinder having an end closed by a cylinder head defining, therewithin, a discharge chamber in selective fluid communication with a compression chamber defined inside the cylinder and which is closed by a valve plate provided between the closed end of the cylinder and the cylinder head, said fluid communication being defined through suction and discharge orifices provided in said valve plate and which are selectively and respectively closed by suction and discharge valves generally carried by the valve plate.

During the compression of gas, heat is generated as a result of different processes, such as: the heating of the gas during compression; the losses due to attrition on the bearings, where the power by viscous attrition is transformed into thermal energy and heat; and the losses in the electric motor, which are also transformed in heat.

In its constructive form, the compressor is mounted in a casing connected to the refrigeration system which includes, besides the compressor, a condenser, an

evaporator and an expanding device. This circuit is hermetically sealed, not transferring mass to the external ambient.

One part of the thermal power generated by the compressor is sent with the refrigerant fluid to the discharge line and dissipated in the condenser of the refrigeration system. The other part is transferred to the refrigerant fluid and to the lubricant oil contained in the interior of the casing. On their turn, the refrigerant fluid and the lubricant oil transfer the other part of the heat to the casing, which dissipates said other part of the generated heat to the external ambient.

This system achieves a thermal balance when certain conditions are maintained constant, such as for example the temperature of the external ambient and the operating condition of the compressor, considering as constant the evaporation and condensation pressures and the ventilation characteristics.

In this situation of thermal balance, a temperature profile can be established, which is directly related to the energetic efficiency of the compressor, since, on one hand, the heating of the ambient of the casing causes heating of the lubricant oil, reducing its viscosity and the power that is lost by viscous attrition. The load capacity of the hydrodynamic bearing is dimensioned taking into account this viscosity reduction. On the other hand, there are many negative aspects resulting from the heating within the casing, such as: temperature increase of the refrigerant fluid being drawn; compression power increase resulting from the high temperature of the cylinder; and the need to use special materials in the construction of the compressor to resist the high temperatures.

The usual process of heat transfer from the inside to the outside of the compressor presently occurs as follows: the heat generated in the compression of the refrigerant fluid is transmitted to the cylinder block and to the discharge muffler and then it is transferred, by convection, to the gas in the internal ambient of the compressor and also to the oil falling on said heated surfaces. The gas and the oil will change heat with the internal walls of the casing and the heat will have to trespass the wall of the casing by conduction, to be finally dissipated, by natural or forced convection, from the compressor body to the external ambient. In this process, there is a series of thermal resistances that impair heat exchange and heat dissipation.

There are also known from the art the following heat transfer processes: by forced ventilation occurring between the internal components and the lubricant oil and between the compressor body and the ambient outside its casing; and by cooling the lubricant oil through a cooling pipe, through which the refrigerant fluid of the condenser of a refrigeration system to which the compressor belongs is deviated to a heat exchanger immersed in the oil inside the compressor, removing heat therefrom.

The known prior art presents different alternatives to promote heat transfer, such as: using heat exchangers with Stirling machines, as taught in patent US 6,347,523; providing fins in the cylinder heads and an auxiliary air circulation system; using heat pipes; using a fluid pumping system by means of pumps driven by oscillatory, mechanical and electrical movements, etc.

However, such known solutions present some disadvantages. In the case of the known solutions

which use finned cylinder heads and heat exchange with air, the disadvantage resides in the fact that it is not possible to achieve high heat transfer capacity. In said systems, a saturation limit in relation to the heat transfer capacity is easily achieved. This occurs as a function of the saturation of the efficiency of the fins by increasing the length of and/or decreasing the distance between the fins, or by the impossibility of finding air moving equipments with sufficient capacity to allow reaching the pressure and flowrate levels which are required in determined heat transfer capacities. Moreover, such solutions lead to an increase of vibrations and noise in the refrigeration system and to less reliability due to the large amount of movable parts they have.

In a known solution disclosed in patent US 6,499,977 a scroll compressor carries, in its exterior, a refrigeration system using a heat pipe. In this solution, the heat in the compressor casing is removed by means of a heat pipe system. Heat transfer is improved only from the external surface of the casing to the external ambient, maintaining constant the other thermal resistances. Such compressor has a constructive characteristic in which the cylinder is directly exposed to the external ambient and therefore the high thermal resistance of the gas of the internal ambient does not cause any damages to said compressor. However, for the reciprocating hermetic compressor it is highly desirable to minimize or eliminate such internal thermal resistance of the gas.

Another solution of heat transfer by using heat pipes is disclosed in patent US 6,412,479, in which the heat pipes are provided in the interior of an internal combustion engine to remove heat from the cylinder head. Nevertheless, said solution refers to an

internal combustion engine (and not to a hermetic compressor) in which the objective is to re-use the unburnt gases of the discharge in the supply system.

Other known solutions described in patents US 5,651,258 and US 5,695,004 also present a heat pipe system for removing heat from the interior of the compressor, re-using or not said heat in a refrigeration system to which the compressor is associated. Such solutions however are not directed to the issue of energetic efficiency of a hermetic compressor, since the heat pipes are applied to the system to use said heat and not to remove it from the hot parts of a hermetic compressor.

Objects of the Invention

Thus, it is an object of the present invention to provide a hermetic compressor with a heat dissipating system in the interior of the compressor casing, particularly to remove heat from its cylinder block, reducing the whole thermal resistance therewithin and making its inner temperature more homogeneous, without the problems found in the known solutions, such as higher energy consumption and need of using special material to resist high temperatures.

It is a further object of the present invention to provide a compressor such as cited above, which allows the heat dissipated from the parts thereof to be transferred to the exterior of the compressor casing.

Summary of the Invention

These and other objects are attained by a hermetic compressor with a heat dissipating system, said compressor comprising: a casing within which is defined an oil sump; a cylinder block mounted inside the casing and defining a cylinder, for compression of a refrigerant fluid, having an end closed by a cylinder head in which is defined a discharge chamber,

said heat dissipation system comprising a thermal energy transfer duct having a heat absorbing end mounted to the cylinder block in order to absorb the heat generated by compression of the refrigerant fluid inside the cylinder, and a heat releasing end provided away from the cylinder block in order to conduct and liberate the heat absorbed therefrom to another means at a temperature which is lower than the temperature of the means in which the absorption occurs.

The present solution considers the application of heat exchangers such as heat pipes, which effect heat exchange very efficiently and allow a high amount of heat to be removed from specific regions of the compressor, more particularly from the hot parts associated with the cylinder block, conducting said heat to another means located inside or outside the casing.

Brief Description of the Drawings

The invention will be described with reference to the enclosed drawings given by way of example of a preferred embodiment and in which:

Figure 1 illustrates, schematically and in a cross-sectional view, a refrigeration compressor illustrating a first embodiment of the refrigeration system of the present invention;

Figure 2 illustrates, schematically and in a top plan view, the embodiment shown in figure 1;

Figure 3 illustrates, schematically and in a cross-sectional view, as in figure 1, a second embodiment of the refrigeration system;

Figure 4 illustrates, schematically and in a cross-sectional view, a variant for the second embodiment of the refrigeration system shown in figure 1;

Figure 5 illustrates, schematically, a perspective view of the construction shown in figure 4;

Figure 6 illustrates, schematically, a bottom plan view of the construction of the cylinder head shown in figure 5;

Figure 7 illustrates, schematically, a lateral elevational view of the construction of the cylinder head shown in figure 6;

Figure 8 illustrates, schematically, a vertical sectional view of the construction of the cylinder head shown in figures 6 and 7, taken according to line VIII-VIII of figure 7;

Figure 9 illustrates, schematically, a bottom plan view of another construction of the cylinder head of the present invention;

Figure 10 illustrates, schematically, a lateral elevational view of the construction of the cylinder head shown in figure 9;

Figure 11 illustrates, schematically, a lateral view of a construction of the thermal energy transfer duct of the present invention;

Figures 11a, 11b and 11c illustrate, schematically, cross-sectional views of each portion of the thermal energy transfer duct shown in figure 11;

Figure 12 illustrates, schematically, a lateral view of another construction of the thermal energy transfer duct of the present invention;

Figures 13 and 13a illustrate, schematically, the curves of the performance of the thermal energy transfer duct shown in figure 11; and

Figures 14 and 14a illustrate, schematically, the curves of the performance of the thermal energy transfer duct shown in figure 12.

Detailed Description of the Illustrated Embodiment

The heat dissipation system of the present invention is designed to be applied in a compressor of the type used in refrigeration systems of refrigeration

appliances, said compressor comprising, within a hermetic casing 1, a motor-compressor assembly having a cylinder block 2 in which is defined a cylinder 3 housing, at one end, a piston (not illustrated) which
5 compresses a refrigerant fluid and having an opposite end 4 closed by a cylinder cover or cylinder head 10 within which is defined a suction chamber and a discharge chamber (not illustrated), which maintain a selective fluid communication with a compression
10 chamber (not illustrated) defined inside the cylinder 3 between a piston top portion and a valve plate 5 provided between the opposite end of the cylinder 3 and the cylinder head 10 through suction and discharge orifices (not illustrated) provided in said valve
15 plate 5 and which are selectively and respectively closed by suction and discharge valves (not illustrated).

The gas being drawn by the compressor and coming from a suction line (not illustrated) of the refrigeration
20 system to which the compressor is coupled, reaches the interior of the casing 1 through a suction muffler 6 usually provided within said casing 1 and maintained in fluid communication with the inside of the suction chamber of the compressor.

25 In the interior of the casing 1 there is defined, adjacent to a lower portion 1a thereof, an oil sump 7 which contains the oil for lubricating the motor-compressor assembly parts presenting relative movement to each other, the lubricating oil deposited in said
30 oil sump 7 being pumped to the motor-compressor assembly by a non-illustrated pump. While the appended drawings illustrate a compressor with the cylinder block located over the electric motor, it should be understood that the invention encompasses the hermetic
35 compressors in which the electric motor is provided

over the cylinder block.

According to the present invention, inside the casing 1 there is provided a thermal energy transfer duct 20, which is for example flexible (heat pipe) and made of
5 a material with good thermal conductivity, such as copper, and which has a heat absorbing end 21 mounted to the cylinder block 2 in a region of the latter at a high temperature as a function of the compression of the refrigerant fluid caused by the movement of the
10 piston, so as to absorb the heat generated by compression of said refrigerant fluid inside the cylinder 3, and a heat releasing end 22 spaced away from the cylinder block 2 in order to conduct and liberate the heat absorbed therefrom to another means
15 at a lower temperature than that of the means where absorption occurs.

Figures 1 and 2 illustrate a constructive option of the present invention in which the heat absorbing end 21 of the thermal energy transfer duct 20 is coupled
20 to the cylinder block 2 in a mounting region adjacent to the valve plate 5. In this constructive option, the heat absorbing end 21 of the thermal energy transfer duct 20 is coupled to a projection 4a of the opposite end 4 of the cylinder block 2.

25 In another constructive option, the heat absorbing end 21 of the thermal energy transfer duct 20 is coupled to the cylinder head 10, as illustrated in figures 3-5. In this construction, the cylinder head 10 is provided with at least one housing 11 to receive the
30 heat absorbing end 21 of the thermal energy transfer duct 20, said housing 11 being provided with retaining means to secure the heat absorbing end 21, which means are for example incorporated to the housing 11.

In the construction of the cylinder head 10
35 illustrated in figures 6-8, the cylinder head 10

carries, from a face 12 opposite to a mounting face 13 to be seated against the valve plate 5, a projection 14 defining, internally, a channel 15 which is for example rectilinear and provided along the longitudinal extension of said cylinder head 10, said channel 15 defining the housing 11.

According to the present invention, the channel 15 has a first end 15a which is open and dimensioned to receive the heat absorbing end 21 of the thermal energy transfer duct 20. In the illustrated construction, the channel 15 is further provided with a second end 15b which is open and dimensioned to receive, selectively, the heat absorbing end 21 of a thermal energy transfer duct 20, which may be provided independently of the provision of another thermal energy transfer duct 20 with its heat absorbing end 21 mounted to the first end 15a of the channel 15.

In another non-illustrated constructive option, each of the first and second ends 15a, 15b can receive, simultaneously or not, a heat absorbing end 21 of a respective thermal energy transfer duct 20.

In the illustrated embodiment, the channel 15 has a first end 15a and a second end 15b aligned to each other according to an axis which is inclined in relation to the plane of the face of said cylinder head 10 to be seated against the valve plate 5. The inclination of the axis of the channel 15 is defined so that the first end 15a is more spaced away from said face to be seated to the valve plate 5 in relation to the second end 15b, in order to facilitate the fitting, through any of said first and second ends 15a, 15b of the channel 15, of a heat absorbing end 21 of the thermal energy transfer duct 20, as illustrated in figures 3 and 4, respectively.

In the constructive option for the cylinder head 10

illustrated in figures, 1, 4 and 5, the heat absorbing end 21 of the thermal energy transfer duct 20 is tightly fitted directly into the housing 11.

Figures 9 and 10 illustrate a constructive option for the cylinder head 10 of the present invention, in which said cylinder head 10 presents a pair of parallel channels 15, 15' laterally provided from the face 12 of the cylinder head 10, so that each receives a respective heat absorbing end 21 of a thermal energy transfer duct 20, as already discussed in relation to the cylinder head 10 shown in figures 6-8.

It should be understood that the heat absorbing end 21 of the thermal energy transfer duct 20 might be mounted to the cylinder block 2 directly to any compressor component associated with the cylinder block 2, in order to receive, from the latter, the heat generated by compression of the refrigerant fluid.

According to a constructive option of the present invention illustrated in figures 4 and 5, the heat releasing end 22 of the thermal energy transfer duct 20 liberates heat to a means located within the casing 1 and defined by the oil contained inside the latter, for example by immersing said heat releasing end 22 in the oil sump 7 defined inside the casing 1, so as to liberate heat to said oil sump 7. In this construction, the heat releasing end 22 can be loosely immersed in the oil sump 7 or retained therein by an appropriate retaining means. In a variant of this construction illustrated in figure 4, the present heat dissipation system comprises an additional thermal energy transfer duct 30 having a respective heat absorbing end 31 immersed in the oil of the oil sump 7, and a heat releasing end 32 outside said oil sump 7 to carry at least part of the heat from said oil to a

region spaced away therefrom.

In the illustrated construction, the heat releasing end 32 of the additional thermal energy transfer duct 30 is provided with a duct portion 33 which hermetically trespasses the casing 1 in order to project outwardly therefrom and to liberate heat via the heat releasing end 32 to a means external to said casing 1, generally defined by the external ambient itself.

10 In another constructive option, not illustrated, the heat releasing end 22 of the thermal energy transfer duct 20 liberates heat to a flow of lubricant oil circulating inside the casing 1, for example the oil to be used to lubricate the compressor parts with relative movement to each other.

According to the present invention, the heat removed from the cylinder block can be also directed to the outside of the casing 1 without passing through the oil contained therewithin, as illustrated in figure 3.

20 In this case, said heat releasing end 22 of the thermal energy transfer duct 20 has an end portion 23 trespassing, hermetically, the casing 1, in order to project outwardly therefrom and liberate heat to a means external to said casing 1, as discussed above.

25 Figures 11 and 12 exemplify two constructive forms of a thermal energy transfer duct 20 (or additional thermal energy transfer duct 30) of the present invention, in which each of said ducts has a respective evaporator portion 20a, of heat absorption, a transport portion 20b or adiabatic portion, a condenser portion 20c, and a heat dissipation portion 20d, for example including at least one heat dissipating fin 20e provided along said heat dissipation portion 20d, as illustrated.

35 In the construction illustrated in figure 11, the

condenser portion 20c is associated with a heat dissipating fin 20e disposed along the extension of said condenser portion 20c. In the construction illustrated in figure 12, the thermal energy transfer duct 20 comprises two heat dissipating portions 20d, one of them presenting a heat dissipating fin 20e disposed along the extension of the evaporator portion (heat absorption) 20a of the thermal energy transfer duct 20, and the other of said heat dissipating portions comprising a plurality of heat dissipating fins 20e disposed parallel to each other and transversal to the extension of the condenser portion 20c, said fins being transversally or longitudinally arranged in the thermal energy transfer duct 20 to increase the heat dissipation area of the latter. The provision of the heat dissipating fins 20e, as well as the arrangement and quantity thereof, is a function of the parameters of said thermal energy transfer duct 20, such as area, temperature and ventilation of the place where it is located.

As illustrated in figures 11a, 11b and 11c, in a construction option of the present invention the evaporator portion 20a which forms the thermal energy transfer duct 20 presents a cross section which is different from the cross section of the other portions of said thermal energy transfer duct, which cross section is calculated as a function of the heat absorption parameters desired for that portion. This procedure is also applied to determine the cross section of the other portions of the thermal energy transfer duct.

For the thermal energy transfer duct constructions illustrated in figures 11 and 12, the result of the quantity of heat versus temperature in the transport portion 20b (or adiabatic portion) of the thermal

energy transfer duct 20 and the result of the quantity of heat versus effective unit of length of the thermal energy transfer duct (of the condenser portion 20c) of each construction of thermal energy transfer duct 20 are illustrated in figures 13, 13a, 14, 14a.

The effective length considered in the graphs illustrated in figures 13a and 14a represents the sum of the length of the transport portion 20b (Ladb) and half of the sum of the lengths of the evaporator portion 20a (Levap) and condenser portion 20c (Lcond), i.e.:

$$L_{ef} = L_{adb} + (L_{cond} + L_{evap})/2.$$

For obtaining such results, these thermal energy transfer duct constructions present an external diameter for example of about 6mm and a copper wall thickness of about 0.5mm. As illustrated in figures 13, 13a, 14 and 14a, the represented curves were obtained for external diameters (Dext) of the thermal energy transfer duct of 4mm and 6mm.

With the solution of the present invention, the removal of heat from the hot region of the cylinder block 2 allows reducing the temperatures in the interior of the compressor, increasing the energetic efficiency of the compressor.

While only some ways of carrying out the invention have been illustrated, it should be understood that changes in the form and arrangement of the components of the compressor could be made without departing from the inventive concept defined in the appended claims.

CLAIMS

1. A hermetic compressor with a heat dissipating system, said compressor comprising: a casing (1) within which is defined an oil sump (7); a cylinder block (2) mounted inside the casing (1) and defining a cylinder (3), for compression of a refrigerant fluid, having an end closed by a cylinder head (10) in which is defined a discharge chamber, characterized in that is comprises at least one thermal energy transfer duct (20) having a heat absorbing end (21) mounted to the cylinder block (2) in order to absorb the heat generated by compression of the refrigerant fluid inside the cylinder (3), and a heat releasing end (22) provided away from the cylinder block (2) in order to conduct and liberate the heat absorbed therefrom to another means at a temperature which is lower than the temperature of the means in which absorption occurs.
2. Hermetic compressor, according to claim 1, characterized in that the heat releasing end (22) of the thermal energy transfer duct (20) liberates heat to a means located inside the casing (1) and defined by the oil contained in the interior of the latter.
3. Hermetic compressor, according to claim 2, characterized in that the heat releasing end (22) of the thermal energy transfer duct (20) is immersed in the oil of the oil sump (7) so as to liberate heat to the latter.
4. Hermetic compressor, according to claim 3, characterized in that it comprises an additional thermal energy transfer duct (30) having a respective heat absorbing end (31) immersed in the oil of the oil sump (7), and a heat releasing end (32) provided in a duct portion (33) which trespasses, hermetically, the casing (1) so as to project outwardly therefrom and liberate heat to a means outside the casing (1).

5. Hermetic compressor, according to claim 2, characterized in that the heat releasing end (22) of the thermal energy transfer duct (20) liberates heat to a flow of lubricant oil circulating in the interior of the casing (1).

6. Hermetic compressor, according to claim 3 and in which the cylinder head (10) is mounted against a face of a valve plate (5) provided with suction and discharge orifices which are selectively closed by respective suction and discharge valves, characterized in that the heat absorbing end (21) of the thermal energy transfer duct (20) is coupled to the cylinder block (2) in a mounting region adjacent to the valve plate (5).

7. Hermetic compressor, according to claim 6, characterized in that the heat absorbing end (21) of the thermal energy transfer duct (20) is coupled to the cylinder head (10).

8. Hermetic compressor, according to claim 7, characterized in that the cylinder head (10) is provided with at least one housing (11) to receive a respective heat absorbing end (21) of the thermal energy transfer duct (20).

9. Hermetic compressor, according to claim 8, characterized in that the heat absorbing end (21) of the thermal energy transfer duct (20) is affixed to the respective housing (11) through retaining means carried by the latter.

10. Hermetic compressor, according to claim 9, characterized in that the retaining means are incorporated to the housing (11).

11. Hermetic compressor, according to claim 10, characterized in that the heat absorbing end (21) of the thermal energy transfer duct (20) is tightly fitted into the housing (11).

12. Hermetic compressor, according to claim 11, characterized in that the cylinder head (10) incorporates a projection (14) defining, therewithin, a channel (15) having a first end (15a) which is open
5 and dimensioned to receive the heat absorbing end (21) of the thermal energy transfer duct (20).

13. Hermetic compressor, according to claim 12, characterized in that the channel (15) is provided with a second end (15b) which is open and dimensioned
10 to receive, selectively, the heat absorbing end (21) of the thermal energy transfer duct (20), which may be provided independently of the provision of another thermal energy transfer duct 20 with its heat absorbing end 21 mounted to the first end 15a of the
15 channel 15.

14. Hermetic compressor, according to claim 1, characterized in that the heat releasing end (22) of the thermal energy transfer duct (20) has an end portion trespassing, hermetically, the casing (1) so
20 as to project outwardly therefrom and liberate heat to a means outside the casing (1).