(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
16 May 2002 (16.05.2002)

PCT

(10) International Publication Number
WO 02/39290 A2

(51) International Patent Classification[7]: G06F 13/00

(21) International Application Number: PCT/US01/31816

(22) International Filing Date: 12 October 2001 (12.10.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/708,221 7 November 2000 (07.11.2000) US

(71) Applicant *(for all designated States except US)*: **INTEL CORPORATION** [US/US]; 2200 Mission College Boulevard, Santa Clara, CA 95052 (US).

(72) Inventors; and

(75) Inventors/Applicants *(for US only)*: **VOLK, Andrew** [US/US]; 7380 Sierra Ponds Lane, Granit Bay, CA 95746 (US). **RAJAPPA, Srinvasan** [IN/US]; 1016 Folsom Ranch Drive, #101, Folsom, CA 95630 (US).

(74) Agents: **MALLIE, Michael, J.**; Blakely Sokoloff Taylor & Zafman, 7th Floor, 12400 Wilshire Boulevard, Los Angeles, CA 90025 et al. (US).


(81) Designated States *(national)*: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States *(regional)*: ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— *without international search report and to be republished upon receipt of that report*

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR REDUCING SIMULTANEOUS SWITCHING OUTPUT NOISE USING DYNAMIC BUS INVERSION



(57) Abstract: An embodiment of a computer system implementing dynamic bus inversion includes a first system logic device having a dynamic bus inversion encoder and also includes a second system logic device having a dynamic bus inversion decoder. The first and second system logic devices are coupled via a data bus. The encoder compares a group of data bits currently placed on the data bus with a next group of data bits to be placed on the data bus. If the encoder determines that greater than a predetermined number of bit transitions would occur between the current and next group of data bits, the encoder inverts the next group of data bits before placing the next group of data bits onto the data bus. The encoder also asserts an inversion signal that is received by the decoder. In response to the assertion of the inversion signal, the decoder inverts the previously inverted next group of data bits to restore the original data.

WO 02/39290 A2

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.