



(51) International Patent Classification:
C10L 1/14 (2006.01)

(21) International Application Number:
PCT/GB2011/050206

(22) International Filing Date:
7 February 2011 (07.02.2011)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
1001923.0 5 February 2010 (05.02.2010) GB

(71) Applicant (for all designated States except US): **PALOX LIMITED**; 4 Zinas Kanther Street, Limassol (CY).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **MARTIN, David William** [GB/GB]; 24 Lymington Grove, Netherton, Liverpool, Merseyside L30 6YF (GB). **POSSELT, Dietmar** [DE/DE]; Ziegelhäuser Landstrasse, 7, 69120 Heidelberg (DE). **OETTER, Günter** [DE/DE]; Hans-von-Marees-Strasse, 21, 67227 Frankenthal (DE). **KIEFER, Matthias** [DE/DE]; Richard-Wagner-Strasse, 8, 67061 Ludwigshafen (DE).

(74) Agent: **BUCKLEY, Guy**; Patent Outsourcing Limited, 1 King Street, Bakewell, Derbyshire DE45 1DZ (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: PROTECTION OF LIQUID FUELS

(57) Abstract: A liquid concentrate comprising essentially: (A) 0.1 to 10 wt.% of one or more amphoteric emulsifying agents; (B) 30 to 95 wt.% of one or more nonionic alkoxyated surfactants; (C) 0 to 20 wt.% of one or more glycol-based solubilizers; and (D) 0 to 65 wt.% of one or more organic solvents; wherein component (B) comprises a mixture of C₆-C₁₅ -alkanol ethoxylates with different carbon numbers for the alkanol unit species, the carbon numbers for the two C₆-C₁₅ -alkanol ethoxylates which have the highest share in weight in the mixture being at least 1.5 carbon numbers distant from each other, is useful for reducing or eliminating the formation in a liquid hydrocarbon fuel of ice particles having a weight average particle size greater than 1 µm when said liquid hydrocarbon fuel is cooled to temperatures in the range of from 0 to -50°C.

