WHAT IS CLAIMED IS:

1. A wireless communication method, wherein the method is applicable to a terminal management network element, and the method comprises:

receiving a second request, wherein the second request is used for requesting at least one of following operations for a terminal device: re-authorization, re-authentication, revocation of authorization, or revocation of authentication;

determining a target network element; and

sending the second request to the target network element.

2. The method according to claim 1, wherein the determining the target network element comprises:

determining a session management network element as the target network element.

3. The method according to claim 1, wherein the determining the target network element comprises:

determining a second target manner corresponding to a second operation, wherein the second operation comprises at least one of authorization, authentication, re-authorization or re-authentication, revocation of authorization or revocation of authentication; and

determining the target network element based on the second target manner.

4. The method according to claim 3, wherein the second target manner comprises a first manner and/or a second manner, the first manner refers to that the terminal device sends information for performing the second operation through a registration process, and the second manner refers to that the terminal device sends the information for performing the second operation through a session management process; and the determining the target network element based on the second target manner, comprises:

in a case that the second target manner is the first manner, determining a mobility management network element as the target network element; in a case that the second target manner is the second manner, determining a session management network element as the target network element.

5. The method according to claim 4, wherein the determining the second target manner corresponding to the second operation comprises:

determining the second target manner based on a first mapping relationship, wherein the first mapping relationship comprises a parameter corresponding to the first manner and/or a parameter corresponding to the second manner.

6. The method according to claim 5, wherein the determining the second target manner based on the first mapping relationship comprises:

in a case that a parameter of the terminal device matches the parameter corresponding to the

first manner, determining the first manner as the second target manner; in a case that the parameter of the terminal device matches the parameter corresponding to the second manner, determining the second manner as the second target manner.

7. The method according to claim 5, wherein the parameters belong to at least one of following information:

area information, Public Land Mobile Network (PLMN) information or time information.

8. The method according to claim 5, wherein the first mapping relationship information is preconfigured.

9. The method according to claim 3, wherein the determining the second target manner corresponding to the second operation comprises:

obtaining query information through unified data storage (UDR) or unified data management (UDM), wherein the query information is used for indicating information of a mobility management network element and/or a session management network element serving the terminal device, and/or, the query information is used for indicating whether the mobility management network element and/or the session management network element supports the second operation; and

determining the second target manner based on the query information.

10. A terminal management network element, comprising:

a receiving unit, configured to receive a second request, wherein the second request is used for requesting at least one of following operations for a terminal device: re-authorization, re-authentication, revocation of authorization or revocation of authentication;

a determination unit, configured to determine a target network element; and

a sending unit, configured to send the second request to the target network element.

11. The terminal management network element according to claim 10, wherein the determination unit is further configured to:

determine a session management network element as the target network element.

12. The terminal management network element according to claim 10, wherein the determination unit is further configured to:

determine a second target manner corresponding to a second operation, wherein the second operation comprises at least one of authorization, authentication, re-authorization or re-authentication, revocation of authorization or revocation of authentication; and

determine the target network element based on the second target manner.

13. The terminal management network element according to claim 12, wherein the second target manner comprises a first manner and/or a second manner, the first manner refers to that the terminal device sends information for performing the second operation through a registration

process, and the second manner refers to that the terminal device sends the information for performing the second operation through a session management process; and the determination unit is further configured to:

in a case that the second target manner is the first manner, determine a mobility management network element as the target network element; in a case that the second target manner is the second manner, determine a session management network element as the target network element.

14. The terminal management network element according to claim 13, wherein the determination unit is further configured to:

determine the second target manner based on a first mapping relationship, wherein the first mapping relationship comprises a parameter corresponding to the first manner and/or a parameter corresponding to the second manner.

15. The terminal management network element according to claim 14, wherein the determination unit is further configured to:

in a case that a parameter of the terminal device matches the parameter corresponding to the first manner, determine the first manner as the second target manner; in a case that the parameter of the terminal device matches the parameter corresponding to the second manner, determine the second manner as the second target manner.