(A1)

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

G00002

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
6 June 2002 (06.06.2002)

PCT

(10) International Publication Number
WO 02/44516 A1

(51) International Patent Classification[7]: E21B 33/043, 33/035

(21) International Application Number: PCT/US01/43769

(22) International Filing Date:
14 November 2001 (14.11.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/726,007 29 November 2000 (29.11.2000) US

(71) Applicant: COOPER CAMERON CORPORATION [US/US], 515 Post Oak Boulevard, Suite 1200, Houston, TX 77027 (US)

(72) Inventor: ALLEN, Timothy, J., Route 2, Box 224A, Hempstead, TX 77445 (US).

(74) Agent: HARTMANN, Michael, P., Cooper Cameron Corp., P.O Box 1212, Houston, TX 77251-1212 (US).

(81) Designated States *(national)*: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW

(84) Designated States *(regional)*: ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)


Published:
— *with international search report*

[Continued on next page]

(54) Title: WELLHEAD ASSEMBLY FOR ACCESSING AN ANNULUS IN A WELL AND A METHOD FOR ITS USE

162162

WO 02/44516 A1



(57) Abstract: A wellhead assembly comprises a central bore through the wellhead assembly having an opening in the central bore in the pressure boundary region of the wellhead assembly. The port preferably extends through the high pressure housing into the bore of the wellhead assembly. A first casing string is secured at a first end within the wellhead assembly below the opening of the port in the central bore of the wellhead assembly A second casing string is secured at a first end within the wellhead assembly above the opening of the port in the central bore of the wellhead assembly. A fluid flowpath is thereby formed comprising the port in the wellhead assembly and an annulus between the first and second casing strings In this way, access is provided to an annulus within the well A method for passing a fluid through an annulus in a well is also provided, the well having a wellhead assembly comprising a central bore therethrough, the annulus being formed between a first casing string and a second casing secured within the wellhead assembly and extending into the well.

GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

Published:
— *with international search report*

(88) Date of publication of the international search report:
17 October 2002

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette