(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
7 March 2002 (07.03.2002)

PCT

(10) International Publication Number
WO 02/019398 A3

(51) International Patent Classification[7]: H01L 21/02

(21) International Application Number: PCT/US01/27138

(22) International Filing Date: 31 August 2001 (31.08.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/653,280 31 August 2000 (31.08.2000) US

(71) Applicant: MICRON TECHNOLOGY, INC. [US/US]; 8000 S. Federal Way, Boise, ID 83707-0006 (US).

(72) Inventors: YANG, Sam; 5923 S. Sweet Gum Way, Boise, ID 83716 (US). DRYNAN, John, M.; 7237 W. Colonial Street B-207, Boise, ID 83709 (US).

(74) Agent: MINUTOLI, Gianni; Dickstein Shapiro Morin & Oshinsky LLP, 2101 L Street N.W., Washington, DC 20037-1526 (US).

(81) Designated States *(national)*: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.


(84) Designated States *(regional)*: ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— *with international search report*

(88) Date of publication of the international search report:
15 August 2002

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: PLANARIZATION OF METAL CONTAINER STRUCTURES



(57) Abstract: A conductive material is provided in an opening formed in an insulative material. The process involves first forming a conductive material over at least a portion of the opening and over at least a portion of the insulative material which is outside of the opening. Next, a metal-containing fill material is formed over at least a portion of the conductive material which is inside the opening and which is also over the insulative material outside of the opening. The metal-containing at least partially fills the opening. At least a portion of both the metal-containing material and the conductive material outside of the openinng is then removed. Thereafter, at least a portion of the metal-containing fill material which is inside the opening is then removed.

WO 02/019398 A3