

METHOD FOR PREPARING BLEND PRODUCTSBACKGROUND OF THE INVENTION1. Field Of The Invention

This invention relates to a method for controlling the preparation of blend products from blend stocks boiling at 350°C or less by predicting chemical, performance, perceptual or physical properties of blend stocks, blend products and/or other refinery or chemical processes using a combination of gas chromatography and mass spectrometry.

2. Description Of The Related Art

Refineries and chemical plants typically control blending of various component streams and certain additives through the use of both on-line analyzers and off-line laboratory analyses to provide product quality information. These quality parameters (chemical composition, physical or perceptual or performance properties) are then fed back into linear programs or other blend control software which may be a series of simultaneous equations which predict percentages of refinery streams used to meet certain blend targets. The equations typically are executed more than three times per hour and their output is used to control proportional flow valves to vary the quality of the finished product which can either go to tankage or directly to pipelines and terminals, trucks, or to ship-loading facilities. Multiple on-line analyzers are typically required for blend control.

U.S. Patent 5,223,714 describes a process for controlling the blending of fluids using near-infrared spectroscopy by converting the near-infrared absorbances to signals and mathematically correlating the signal to volume of component.

Gas chromatography has been used to predict physical and performance properties of hydrocarbon mixtures boiling in the gasoline

range. Crawford and Hellmuth, Fuel, 1990, 69, 443-447, describe the use of gas chromatography and principal components regression analysis to predict the octane values for gasolines blended from different refinery streams. Japanese laid-open patent application JP 03-100463 relates to a method of estimating the cetane number for fuel oils by separating an oil sample into its components using gas chromatography, measuring the signal strength of ion intensities at characteristic masses in the mass spectrum, and correlating these ion intensities to cetane number using multiple regression analysis.

It would be desirable to have a single analyzer means for rapidly measuring the chemical, performance, perceptual or physical properties of blend stocks or blend products and using these properties to control the blending process.

SUMMARY OF THE INVENTION

This invention relates to a process for controlling the blending of a plurality of blend stocks each having boiling points less than about 350°C into at least one blend product which comprises:

- (a) selecting at least one physical, perceptual, performance or chemical property of at least one blend stock or blend product;
- (b) selecting reference samples, said reference samples containing characteristic compound types present in at least one blend stock or blend product and which have known values for the property or properties selected in step (a);
- (c) producing a training set by the steps of:
 - (1) injecting each reference sample into a gas chromatograph which is interfaced to a mass spectrometer thereby causing at least a partial separation of the hydrocarbon mixture into constituent chemical components;

- (2) introducing the constituent chemical components of each reference sample into the mass spectrometer, under dynamic flow conditions;
 - (3) obtaining for each reference sample a series of time resolved mass chromatograms;
 - (4) calibrating the mass chromatograms to correct retention times;
 - (5) selecting a series of corrected retention time windows;
 - (6) selecting within each retention time window a series of molecular and/or fragment ions, said ions being representative of characteristic compounds or compound classes expected within the retention time window;
 - (7) recording the total amount of each characteristic compound or compound group selected in step c(6);
 - (8) forming the data from steps c(6) and c(7) into a X-block matrix;
 - (9) forming the property data selected in (a) for reference samples selected in (b) into a Y-block matrix;
 - (10) analyzing the data from steps c(8) and c(9) by multivariate correlation techniques including Partial Least Squares, Principal Component Regression or Ridge Regression to produce a series of coefficients;
- (d) subjecting at least one blend stock or blend product sample to steps c(1) to c(3) in the same manner as the reference sample to produce a series of time resolved mass chromatograms;
- (e) repeating steps c(4) to c(8) for each mass chromatogram from step (d);

- (f) multiplying the matrix from step (e) by the coefficients from step c(10) to produce a predicted value of the property or properties for the at least one blend stock or blend product sample; and
- (g) using the predicted values of the property or properties of the at least one blend stock or blend product sample to control the amount of blend stock in the blend product.

In another embodiment, this invention relates to a process for controlling or monitoring chemical or refinery processes which utilize feed stocks and/or produce products having boiling points less than about 350°C which comprises:

- (a) selecting at least one physical, perceptual, performance or chemical property of at least one feed stock or product;
- (b) selecting reference samples, said reference samples containing characteristic compound types present in the at least one feed stock or product and which have known values of the property or properties selected in step (a);
- (c) producing a training set by the steps of:
 - (1) injecting each reference sample into a gas chromatograph which is interfaced to a mass spectrometer thereby causing at least a partial separation of the hydrocarbon mixture into constituent chemical components;
 - (2) introducing the constituent chemical components of each reference sample into the mass spectrometer, under dynamic flow conditions;
 - (3) obtaining for each reference sample a series of time resolved mass chromatograms;

- (4) calibrating the mass chromatograms to correct retention times;
 - (5) selecting a series of corrected retention time windows;
 - (6) selecting within each retention time window a series of molecular and/or fragment ions, said ions being representative of characteristic compounds or compound classes expected within the retention time window;
 - (7) recording the total amount of each characteristic compound or compound group selected in step c(6);
 - (8) forming the data from steps c(6) and c(7) into a X-block matrix;
 - (9) forming the property data selected in (a) for reference samples selected in (b) into a Y-block matrix;
 - (10) analyzing the data from steps c(8) and c(9) by multivariate correlation techniques including Partial Least Squares, Principal Component Regression, or Ridge Regression to produce a series of coefficients;
- (d) subjecting at least one refinery or chemical process product or feed stock sample to steps c(1) to c(3) in the same manner as the reference sample to produce a series of time resolved mass chromatograms;
- (e) repeating steps c(4) to c(8) for each mass chromatogram from step (d);
- (f) multiplying the matrix from step (e) by the coefficients from step c(10) to produce a predicted value of the property or properties for the refinery or chemical process and sample or samples; and

- (g) using the predicted values of the property or properties of the refinery or chemical sample or samples to control the refinery or chemical process.

The gas chromatography/mass spectrometry (GC/MS) method described above can be used to rapidly predict a wide range of chemical and physical properties of complex mixtures such as blend stocks and blend products. Such properties include octane number, specific chemical constituents, e.g., benzene, H₂O and H₂S, additive concentration, distillation characteristics, oxidative stability and the like. The method can also handle the collinear data generated by the GC/MS analyses.

BRIEF DESCRIPTION OF THE DRAWING

Figure 1 is a schematic flow diagram of the blend process, control valves, GC/MS analytical center and computer control system.

Figure 2 is a graph showing predicted versus measured research octane values for the training set.

Figure 3 is a graph showing predicted versus measured research octane values for the test set.

Figure 4 is a graph showing predicted versus measured motor octane values for the training set.

Figure 5 is a graph showing predicted versus measured motor octane values for the test set.

Figure 6 is a graph showing predicted versus measured D&L values at 158°F (70°C) for the training set.

Figure 7 is a graph showing predicted versus measured D&L values at 302°F (150°C) for the training set.

Figure 8 is a graph showing predicted versus measured T50 for the training set.

Figure 9 is a graph showing predicted versus measured T90 for the training set.

DETAILED DESCRIPTION OF THE INVENTION

The blend products produced by the process of the invention include motor gasoline, aviation gasoline, jet fuel, diesel fuel, heating oil, kerosene, LPG, furnace fuels, solvents, and refinery and/or chemical plant intermediate streams (such as process feed stocks/products). The blend products are produced from various blend stocks which are usually refinery or chemicals streams. Typical blend stocks include reformat, alkylate, isomerates, light cycle oil, catalytic naphthas, raffinates, extracts, virgin distillate streams, gas oils and other refinery or chemical plant intermediate streams or process products; and can include individual components such as additives as well as individual chemicals such as benzene, toluene and xylene.

Figure 1 is a schematic flow diagram of an on-line blend process. In Figure 1, blending stocks are contained in Tanks 10a to 10n where n is the number of blend tanks. Each blend tank is connected to a common gathering line 22 which feeds into a blending or mixing tank 24. The connecting lines 12a to 12n to gathering line 20 are interrupted by control valves 14a to 14n and sampling ports 16a to 16n. Sampling ports 16a to 16n are connected to a sampling manifold 40 through lines 18a to 18n which are interrupted by control valves 20a to 20n. Product line 26 is also connected through sampling port 32 to sampling manifold 40 through line 28 which is interrupted by control valve 30. Sampling manifold 40 is connected to a sample/injection valve 46 by line 42 interrupted by control valve 44. Sampling manifold 40 is also connected to Sump 50 by purge line 52 interrupted by control valve 54. Control valve 46 is also connected to purge line 52 through line 56 interrupted by control valve 58. Sampling manifold 40 and sample/injection 46 are purged by the sample

to be analyzed. During the purge phase, sample is collected in sump 50.

Once the sampling manifold 40 and sample/injection valve 46 are purged of any contaminants, sample to be analyzed is injected through valve 46 into GC/MS analyzer 60 which can be purged to sump 50 through valve 62. The raw data generated by GC/MS analyzer 60 is fed to computer 64 where it is subjected to mathematical treatment. Output from computer 64 is fed as an electronic signal through line 70 to blend control computer 72 which electronically controls valves 14a to 14n thereby controlling product quality exiting blending unit 24.

For at-line operation, sampling manifold 40 is connected to a remote blend stock source 90 through line 94 interrupted by control valve 92. For off-line operation, a remotely collected sample is directly injected into GC/MS analyzer 60 by sample/injection valve 46. Computer output may be read through display panel 80.

The operation of GC/MS analyzer 60 and computer 64 is described in further detail as follows. Blend stocks and blend products are complex hydrocarbon mixtures. The use of GC/MS to analyze such complex mixtures for chemical and physical properties generates a large amount of collinear data. Multiple regression analysis can be used for normal linear data. However, this type of analysis cannot be used for collinear data.

The method according to the invention involves a means for predicting chemical, perceptual, performance and/or physical properties of blend stocks and product blends or refinery or chemical processes by quantitative identification of components using a combination of retention times from a GC analysis coupled with target fragment and/or molecular ions produced by the MS. The MS information is compared against a set of one or more known properties from reference samples which form a training set. By mathematically comparing the experimental data against that of the training set, one may predict the desired property or properties of the blend stock or blend product or refinery or chemical process.

GC/MS utilizes a gas chromatograph interfaced with a mass spectrometer. While a chromatographic method such as supercritical fluid chromatography, liquid chromatography or size exclusion chromatography may be used to separate the mixture into components or mixtures of components, gas chromatography, especially capillary gas chromatography is our preferred means for interfacing with a mass spectrometer. Both GC and MS utilize computer software for instrument control, data acquisition and data reduction. The computer platform should be capable of acquiring at least 2000 mass spectra in about 7 minutes.

The sample mixture to be analyzed is first injected into a GC where the mixture components are separated as a function of retention time, typically on the basis of boiling point. Only partial chromatographic resolution of mixture components is necessary. The GC oven temperature is usually programmed for samples with a wide boiling range. Components may also be identified by a detector such as a flame ionization detector, atomic emission detector, thermal conductivity detector or electron capture detector.

The separated or partially separated components are then introduced into a mass spectrometer under dynamic flow conditions. Since a GC operates under atmospheric pressure and a MS under vacuum conditions (about 10^{-3} kPa), the instrument interface requires a coupling device such as a molecular separator (e.g., jet, membrane, etc.), open split coupler or capillary direct interface to efficiently transfer sample while minimizing carrier gas effects.

Depending on the nature of the sample, the mixture may be introduced directly into a MS using a direct insertion probe without a prior GC separation step. Other thermal separation techniques not involving a GC may be used to introduce the sample into the mass spectrometer.

In the MS, sample molecules are bombarded with high energy electrons thereby creating molecular ions which fragment in a pattern characteristic of the molecular species involved. A continuous series

of mass spectra are obtained over a scan range of 10 or more daltons to at least 450 daltons. The mass spectral data may also be acquired in the selected ion monitoring (SIM) mode. In the selected ion mode, care must be taken to select ions representative of the components of interest and to operate under repeatable conditions. A variety of MS instruments may be used including low resolution, high resolution, MS/MS (hybrid or triple quadrupole, etc.), ion cyclotron resonance and time of flight. Any ionization technique may be used, such as electron ionization, chemical ionization, multiphoton ionization, field desorption, field ionization, etc., provided that the technique provides either molecular or fragment ions which are suitable for use in the analysis procedure.

The results of sample analysis are a series of l mass spectra. The mass spectra are divided into n time intervals where n is an integer from 1 to l . At least one diagnostic ion is chosen from each of m time intervals where m is an integer from 1 to n . The term "diagnostic ion" refers to an ion which is representative of a compound, a chemical class or a performance, perceptual or physical property correlated thereto. Regardless of whether mass spectra are obtained in the scan or selected ion mode, it is important that the mass spectra be obtained under conditions which will yield diagnostic ions of suitable and repeatable intensity and accuracy.

If the mass spectral data are acquired in the scan mode, the mass range covered during the acquisition should be sufficient to provide acquisition of all of the ions which could be used as diagnostic ions during mathematical treatment in each mass spectral scan. If the mass spectral data are acquired in the selected ion monitoring mode, then care must be taken that the ions selected for monitoring are suitable for use in measuring the components of interest.

The sample mass spectral data are then compared to mass spectral data from a series of reference samples with known performance, perceptual, physical and/or chemical properties. In order to compare reference mass spectral data with sample mass spectral data,

it may be desirable to time align the sample data to help ensure the integrity of the comparison. There are commercially available computer programs for such data alignment, for example, Hewlett-Packard GC/MS software G1034C version C.01.05.

The reference mass spectral data, and associated properties data, are arranged in matrix form for mathematical treatment as described below. In the case of chemical composition information, one matrix is formed of reference sample ion intensities at given masses and the other matrix contains known ion intensities for molecular fragment ions of known components. The training set for chemical composition data is thus made up of mass spectral data for different components characteristic of compounds or molecular series expected to be found in the sample mixtures. Similar training sets can be formed for other chemical or perceptual or performance or physical properties of interest. These training sets form one block or matrix of data (Y-block or properties matrix). The actual sample mass spectral data (which may have been time aligned) form the other block (X-block) or matrix of data. These two matrices are subjected to mathematical treatment known as Partial Least Squares (PLS), or Principal Component Regression (PCR), or Ridge Regression (RR) to obtain a mathematically describable relationship between the properties data and mass spectral data, known as a model. Coefficients provided by this model are mathematically combined with the suitably treated mass spectral data from samples with unknown desired properties to:

- a) predict desired properties,
- b) assess the suitability of the model for such predictions,
and
- c) diagnose the stability and general correctness of the
process that yielded the mass spectral data

PLS/PCR/RR are described in the literature, e.g., Wold S., A. Ruhe, H. Wold, and W. J. Dunn, "The Collinearity Problem in Linear Regression. The Partial Least Squares (PLS) Approach to Generalized

Inverses", SIAM J. Sci. Stat. Comput., 1984 5(3), 735-743, or Geladi P., and B. R. Kowalki, "Partial Least Squares Regression: A Tutorial", Anal. Chim. Acta, 1986, 185, 1-17, or Höskuldsson A., "PLS Regression Methods", J. Chemometrics, 1988, 2, 211-228, or in many other articles in journals such as the Journal of Chemometrics or Intelligent Laboratory Systems; Frank, I. and J. Friedman, "A Statistical View Of Some Chemometrics Regression Tools", Technometrics, 1993, Vol. 35, No. 2; Jackson, J. E., "A User's Guide To Principal Components", Wiley-Interscience, New York, 1991; Montgomery, D. C. and E. A. Peck, "Introduction To Linear Regression Analysis", Wiley-Interscience, New York, 1990; and Martens, H., and T. Naes, "Multivariable Calibration", Wiley-Interscience, New York, 1989.

When dealing with a complex mixture, it is necessary to select appropriate masses or groups of masses at specific retention times for a particular compound or classes of compounds. The selection of such masses are the basis for a set of rules which then forms the data for the training set. There are no set procedures for such a selection process. The researcher must select appropriate masses for compounds of interest. For example, motor gasolines typically contain paraffins, cycloparaffins olefins and aromatics. It is known that paraffinic hydrocarbons yield fragment ions at masses 43, 57, 71, 85, ... daltons, and these masses may be used as diagnostic of this class of compounds. Moreover, when coupled with retention time data, it is possible to identify concentrations of specific compounds within this class of compounds. In a similar manner, training sets for other chemical, performance, perceptual or physical properties may be developed by correlating compositional data with other properties of interest, e.g., boiling range, viscosity and the like. The result of a mathematical treatment such as PLS/PCR/RR of the training set is a set of coefficients for the properties of interest.

These coefficients are then multiplied by the data matrix for the sample. The result is a prediction of the desired property or properties which can then be used to control the blend process and product quality; or to control various refinery or chemical process operating units depending on the quality of the feed stocks or

products. Moreover, variances in properties serve to promptly alert operators of upsets/changes in operating conditions which could influence product quality. The method of the invention is further illustrated by the following examples.

EXAMPLE 1

The method for predicting the physical, perceptual, performance or chemical properties of a complex hydrocarbon mixture such as a blend product or blend stock or refinery or chemical process feed, intermediate or final stream is demonstrated in this example using research octane number (RON) as the specific property for purposes of illustration. The method is generally applicable to a range of other performance properties as well as physical, perceptual or chemical properties of such mixtures.

The initial consideration is to establish a set of standard GC/MS operating parameters so that the GC/MS analytical data used for predicting properties are obtained under consistent operating conditions. The GC/MS instrument used in this example is a Hewlett-Packard 5972 Mass Selective Detector interfaced to a Hewlett-Packard 5890 Series II Gas Chromatograph fitted for use with microbore columns also fitted with a Vortex Cooler for rapid column oven cooling and a liquid sampling valve.

The GC/MS operating conditions are summarized in Table 1.

Table 1

GC Conditions	
Column	Phenyl Silicone (such as HP-5) 10m x 0.1 mm, 17 micron film thickness
Temperature Program	
Initial Temperature (°C)	35
Initial Time (minutes)	3
Program Rate (°C/minute)	30
Final Temperature (°C)	230
Final Time (minutes)	1
Injection Valve Temperature (°C)	70
Injection Valve On (minutes)	1.01
Injection Valve Off (minutes)	1.15
Injection Port Temperature (°C)	275
Injection Volume μ L	0.5
Carrier Gas	Helium
Linear Velocity	25.6
Split Ratio	500:1
Column Head Press. kPa	Approx. 260
Interface Temperature (°C)	280
Vortex Cooler	
Delivery Air Pressure (psi)	55
Cooler Off (minutes)	4.00
Cooler On (minutes)	10.48
Mass Spectrometer Conditions	
Mass Spectrometer On (minutes)	1.00
Ionization Mode	Electron Ionization, 70 eV nominal
Mass Range Scanned (daltons)	10-400
Cycle Time (minutes)	0.003

In order to predict properties of an unknown hydrocarbon mixture, it is first necessary to select reference samples having known values of the property or properties of interest. These reference samples are used to form a training set as described below. Six hundred twenty seven (627) samples comprised the training set for RON. These samples were analyzed under on-line conditions over a 12 month period and covered the range 89.3 to 96.9 RON (ASTM D 2885-90). These samples were chosen from over 26,000 samples acquired during testing over a 14 month period as representing the variation in gasoline

blending using 9 different refinery streams and MMT (methycyclopentadienyl manganese tricarbonyl). The 627 samples in the training set were further chosen during periods of stable blending operation at average blend rates of 2230+ barrels/hour.

A data treatment method should be selected prior to obtaining raw GC/MS data. Two types of data treatments which may be used are Chemist's Rules and Hydrocarbon Compound Type Analysis as described, for example, in ASTM D 2789-90 "Test Method for Hydrocarbon Types in Low Olefinic Gasoline by Mass Spectrometry". Chemist's Rules involve two separate sections: (1) a calibration section to correct retention times, i.e., the time between zero and the time when a given peak occurs; and (2) the actual Rules which are based on a selected series of masses corresponding to prominent compounds or molecular series expected for the type of hydrocarbon mixture under investigation. These compounds or compound types are selected on the basis that they have prominent molecular and/or fragment ions unique to that compound or molecular series. A portion of the Chemist's Rules are shown in Table 2. A full set of Chemist's Rules for motor gasoline are shown following Example 6.

TABLE 2
Chemist's Rules for Mogas

Rule ^a	Compound ^b	Masses ^c						Retention Time ^d	
								Start	End
1	C3=	27	41	42				1.560	1.590
2	C3	29	43	44				1.570	1.600
3	iC4	29	43	58				1.605	1.624
4	nC5	29	43	58				1.624	1.680
5	C5=	27	41	55	70			1.684	1.708
6	C5	29	43	57	72			1.705	1.739
7	C5=	27	41	55	70			1.736	1.772
8	C5	29	43	57	72			1.739	1.794
9	C5=	27	41	55	70			1.772	1.794
10	C5/-2	39	53	68				1.775	1.796
11	C5=	27	41	55	70			1.794	1.840
12	C5/-2	39	53	68				1.796	1.839
13	C5/-2	39	53	68				1.839	1.873
14	C5/-4	39	40	65	66			1.856	1.882
15	C6=	27	41	55	56	69	84	1.907	1.934
16	C6	29	43	57	71	86		1.926	1.973
.	.	.	.	.	.	.	.	.	.
.	.	.	.	.	.	.	.	.	.
.	.	.	.	.	.	.	.	.	.
138	C1Benzothio	145	147	148				7.701	7.849
139	2Me/-12	141	142					7.722	7.770
140	1Me/-12	141	142					7.820	7.861
141	C2/-12	141	156					8.283	8.382
142	Phenanthrene	178						9.500	10.000

a) Rule number, integer index

b) Compound or group of compounds rule applies to, for example

C3= refers to olefin or cycloparaffin with 3 carbons

C5/-2 refers to diolefin, dicycloparaffin or cyclo-olefin
with 5 carbons

C5/-4 refers to triolefin, tricycloparaffin, dicyclo-
olefin, cyclodiolefin with a total of 5 carbons

C1Benzothio methyl substituted benzothiophene (C_nH_{2n-10}S)

c) Masses used in Rule [up to n may be specified, where n is an
integer which is equal to the number of masses scanned during the

time interval (d) either in full scan mode or selected ion monitoring mode].

- d) Retention Time for both starting and ending expected retention times based on historical averages in minutes.

A reference retention time is then determined for each mass spectral ion grouping selected for use in the Chemist's Rules for each of the selected compound types or specific molecules identified in Table 2. Such corrections are necessary due to slight shifts in retention times which may result from column degradation, column head pressure fluctuations, changes in column carrier gas linear velocity, or minor fluctuations in the GC column oven temperatures or other causes. The calibration step generates a series of correction factors for the entire GC/MS data file. The results of applying such corrections are shown in Table 3.

TABLE 3

Mass (a)	Reference Time (b)	Type (c)	Limit (d)	Calibration Time (e)	Correction (f)
58	1.652	P	0.100	1.642	-0.010
78	2.556	P		2.549	-0.007
92	3.863	P		3.862	-0.001
106	4.917	P		4.933	0.016
128	7.148	P		7.163	0.015
142	7.746	P		7.770	0.024

- (a) Mass or compound selected for the calibration.
(b) Expected occurrence time, typically based on average of several analyses.
(c) P=Peak or maximum occurrence; F=First occurrence of the material
(d) Range ($\pm$ minutes) for reference compound
(e) Observed retention time for reference material
(f) Correction to be applied between reference materials (column a). Correction for the first material is from initial time to calibration time; correction for the second material is between first and second reference materials; and the last correction is applied to end of data acquisition.

Once the correction coefficients are determined, the actual Rules are then determined. In the case of research octane number prediction, a total of 142 Rules is used based on compound or compound

series identifications. For each Rule, a set of characteristic mass numbers is determined. These characteristic mass numbers can range from 1 to n, where n is an integer representing the entire mass range scanned or the number of selected ions being monitored. In this case, up to seven characteristic mass numbers are illustrated. The ion intensities of the masses for each Rule are summed within the upper and lower retention time limits for that Rule. The results are shown for a sampling of the 142 Rules in Table 4 for this demonstration analysis. Table 4 is shown in its entirety following Example 6.

Table 4

CHEMIST'S RULES FOR MOGAS WITH CORRECTIONS

Total Raw Abundance (TIC) :	125963855	
Chemist Rule :	80972353	(64.282%)
Air Leakage :	7201540	(5.717%)
Avg Scan Rate (Min/Max) :	128	(126/215)
Number of Records :	4857	

[illegible]

.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.
.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.
138	C1Benzothio	145	147	148					7.701	7.849	7.724	0.023	7.873	0.024	255718	0.32%	
139	2MeNaphthalene	141	142						7.722	7.770	7.746	0.024	7.794	0.024	1030117	1.27%	
140	1McNaphthalene	141	142						7.820	7.861	7.844	0.024	7.885	0.024	410403	0.51%	
141	C2 Naphthalene	141	156						8.283	8.382	8.307	0.024	8.406	0.024	39022	0.05%	
142	Phenanthrene	178							9.500	10.00	9.524	0.024	10.024	0.024	0	0.00%	
													Sum =		80972353	100.00 %	

- a) Rule number, integer index
- b) Compound or group of compounds rule applies to, for example
 C3= refers to olefin or cycloparaffin with 3 carbons
 C5/-2 refers to diolefin, dicycloparaffin or cyclo-olefin with 5 carbons
 C5/-4 refers to triolefin, tricycloparaffin, dicyclo-olefin, cyclodiolefin
 with a total of 5 carbons
 C1Benzothiophene methyl substituted benzothiophene (C_n/H_{2n-10S})
- c) Masses used in Rule [up to n may be specified, where n is an integer which is equal to the number of masses scanned during the time interval (d to e) either in full scan mode or selected ion monitoring mode].
- d) start retention time in minutes
- e) end retention time in minutes
- f) corrected start retention time, in minutes
- g) correction = difference between start and cstart (in minutes)
- h) corrected end time, in minutes
- i) correction = difference between end and cend (in minutes)
- j) Abundance, both as total sum and as normalized percentage based on Chemist's Rules.

Total Raw Abundance (TIC): total area observed in the GC/MS analysis.

Chemist Rule: total area found using the Chemist's Rules; based on experience, should be greater than 30% of total raw abundance.

Air Leakage: total ionization due to air (m/z 28, 32, 44, 44) useful diagnostic for instrumentation difficulties.

Average Scan Rate (Min/Max): shows the minimum, average and maximum scan rates during the GC/MS analysis and is a useful diagnostic to identify instrumental problems.

Number of records: is the number of mass spectral scans acquired during the analysis.

The analysis summarized in Table 4 is done for each reference sample. The results from these respective analyses form a training set which is subjected to mathematical treatment. The goal is to develop a model that can be used to predict the unknown properties of future samples using their mass spectral data only. The mathematical treatments are described by multivariate correlation techniques such as Projection to Latent Structures (PLS) or otherwise known as Partial Least Squares (PLS), Principal Component Regression (PCR), and Ridge Regression (RR). These techniques are superior to ordinary multiple linear regression in their ability to treat collinearity amongst variables in the X-block or GC/MS data matrix (and Y-block or properties matrix for PLS), and in their ability to handle the quantity of data generated by the Chemist's Rules. Ordinary Multiple Linear Regression cannot be used to treat collinear variables.

PLS/PCR/RR are numerical analysis techniques for detecting and formulating a mathematical structure (model) within a data set

comprising observations associated with multiple objects. Each object has associated with it observations for multiple variables, the latter being common to all objects. These multiple variables are assigned into two categories, known as X-block and Y-block. Observations associated with all variables in the X-block are realized from a common process (GC/MS data in this case). Observations associated with variables in the Y-block (known properties in this case) are realized from processes that may be different for each variable. The data set used to construct this mathematical model is referred to as the model calibration data set.

The common use of PLS/PCR/RR is to apply the model developed from the calibration data set to X-block observations realized for new objects (not in the calibration dataset) to predict values for the corresponding variables in the Y-block for these new objects, without having to execute the Y-block processes used in the calibration dataset. Using diagnostics that are simultaneously generated by the PLS/PCR/RR model, assessment of whether the new objects can be adequately described by the model, and whether the model is used in an extrapolation mode versus interpolation mode can be performed.

PLS/PCR addresses the collinearity features in the X-block and Y-block, by suitably reducing the dimensionality in both X and Y blocks (for PLS), and X-block only (for PCR) to form the model. Collinearity is a term referring to the existence of relationships between variables within the block itself. In the PLS modeling algorithm a number of independent dimensions in the X- and Y-blocks are identified by forming pseudo-variables known as principal components or latent vectors through different sets of linear combinations of original variables in each block. Each set of such combinations constitutes an independent dimension. It comprises a set of coefficients that each value associated with each variable in the block is to be weighted by to arrive at the new value for this dimension. The values for the new, reduced dimensions in the Y-block are regressed onto their counterparts in the new, reduced dimensions of the X-block to arrive at the most parsimonious dimension size (number of latent vectors) and their associated weights, with the final goal

of one linear equation generated to permit prediction of Y-block variables using X-block variables. The number of dimensions used to construct the model is determined through optimization of a criterion known as PRESS (Prediction Error Sum of Squares), cumulated by a Cross Validation (CV) technique using the training data set, and, following the general model parsimony principle.

For PCR, the number of independent dimensions in the X-block are first selected and identified in a similar fashion as in PLS by forming principal components. Then, for each variable in the Y-block, a model is obtained by performing ordinary multiple linear regression using the Principal Components as "Prediction Variables".

For Ridge Regression, the collinearity problem is dealt with in a different manner than PLS/PCR. Here a diagonal matrix known as the Lambda Matrix is added to the Covariance Matrix of the X-block with the net effect of stabilizing the numerical computation needed to obtain the model coefficients. The selection of Lambda values is through optimization of PRESS criterion using cross validation of the training set.

Thus, the Chemist's Rule data for the various reference samples derived from GC/MS analysis form the X-block variables. PLS/PCR/RR treatment may require preliminary reorganization of the X-block data, such as transposition and removal of redundant data and constants or mathematical transformations. The Y-block variables are the property (or properties) to be predicted, and may also require mathematical transformations such as logarithmic or geometric, as well as reorganization. The data blocks may be represented by:

X-BLOCK MATRIX

[Chemist's Rules (n samples x 142 columns)]

X _{1,1}	X _{1,2}	X _{1,3}	...	X _{1,140}	X _{1,141}	X _{1,142}
X _{2,1}	X _{2,2}	X _{2,3}	...	X _{2,140}	X _{2,141}	X _{2,142}
X _{3,1}	X _{3,2}	X _{3,3}	...	X _{3,140}	X _{3,141}	X _{3,142}
.	.	.	.	.	.	.
.	.	.	.	.	.	.
.	.	.	.	.	.	.
X _{n,1}	X _{n,2}	X _{n,3}	...	X _{n,140}	X _{n,141}	X _{n,142}

Y-BLOCK VECTOR

[Measured Property or Properties (n samples)]

Y ₁
Y ₂
Y ₃
.
.
.
Y _n

The Y-block may be a single observation per set of Chemist's Rules as shown above, or it may be a n x m matrix of observations where there are m different properties to be predicted.

The results of PLS/PCR/RR treatment of the training set data are a series of coefficients. Raw GC/MS data from an unknown sample (or samples) are then treated by the Chemist's Rules first to correct the retention times and then to form the ion summations. Each value for the Chemist's Rule ion summation result is then multiplied by the training set coefficients and summed to generate the prediction of the desired property. This is shown in Figure 2 which is graph of predicted vs. measured RON values for the training set. Figure 3 is a graph showing predicted vs. measured RON values for the test set. Figures 2 and 3 illustrate the quality of the predicted research octane values for both an unknown test set of 500 samples acquired

on-line on a motor gasoline blender referenced to the on-line research octane engine (ASTM D 2885-90). The error in the predicted RON values verses the on-line engine values is due to the sparse number of Premium unleaded gasoline blends in the training set. The predicted vs. measured values for regular unleaded gasoline are mostly within ± 0.5 RON units.

EXAMPLE 2

The procedure of Example 1 was repeated for predicting motor octane number (MON) for motor gasoline. The same 627 member training set was used, with the Y-block values from an on-line MON engine. The same suite of on-line unknown samples were used in the prediction of motor octane number. Figure 4 is a graph of predicted vs. measured MON values for the training set. Figure 5 is a graph of predicted and measured MON values for an unknown training set of 500 samples acquired on-line on a motor gasoline blender referenced to the on-line motor octane engine (ASTM D 2855-90). The error in the predicted MON values verses the on-line engine values at high MON values is due to the sparse number of premium unleaded samples in the training set. This error can be offset by a bias correction (of approximately 1.5 octane units) when used for blending control. The predicted vs. measured values for regular unleaded gasoline are mostly within ± 0.5 MON units.

EXAMPLE 3

The procedure of Example 1 was repeated for predicting distillation + losses (D+L) at 158°F (70°C) for motor gasoline blends. In this example, a training set of 259 members was used with the Y-block data being the laboratory inspection data on once per blend samples. The data ranged from 15.8% to 51.5% with an average value of 36.9%, the samples were analyzed in accordance with ASTM D 86-90. The results for the model training set parity plot are in Figure 6 which is a graph of predicted vs. measured D+L at 158°F.

EXAMPLE 4

The procedure of Example 1 was repeated for predicting distillation + losses (D+L) at 302°F (150°C) for motor gasoline blends. In this example, a training set of 259 members was used with the Y-block data being the laboratory inspection data on once per blend samples. The data ranged from 77.5% to 94.1% with an average value of 85.7%, the samples were analyzed in accordance with ASTM D 86-90. The results for the model training set parity plot are in Figure 7 which is a graph of predicted vs. measured D+L at 302°F.

EXAMPLE 5

The procedure of Example 1 was repeated for predicting distillation temperature at the 50% distilled point (T50) for motor gasoline blends. In this example, a training set of 261 members was used with the Y-block data being the laboratory inspection data (ASTM D 86-90) on once per blend samples. The data ranged from 153.8 to 236.3°F (66.7 to 113.5°C) with an average value of 191.0°F (88.3°C). The results for the training set are shown in Figure 8.

EXAMPLE 6

The procedure of Example 1 was repeated for predicting distillation temperature for 90% distilled point (T90) for motor gasoline blends. In this example, a training set of 261 members was used with the Y-block data being the laboratory inspection data (ASTM D 86-90) on once per blend samples. The data ranged from 263.5 to 349.7°F (128.6 to 176.5°C) with an average value of 319.6°F (159.8°C). The results for the model training set are shown in Figure 9 which is a graph of predicted vs. measured T90 in °F.

Other properties of motor gasoline blends such as upper and lower explosive limits, vapor pressure, flash point, viscosity, heat content, total aromatics (or aromatics by species), reformulated gasoline qualities, etc., could be predicted using the method according to the invention. The subject method can also be applied for

predicting properties of other types of complex hydrocarbon mixtures such as diesel fuel, jet fuel, kerosene, heating oil, reformat, alkylate, specialty solvents, etc.; as well as refinery or chemical process feed stocks, intermediate streams and products.

There are several components of blended gasoline which can be measured directly on-line using instrumentation such as described in this patent. These materials include, but are not limited to, water, hydrogen sulfide, benzene, toluene, the isomeric C2 benzenes through C7 benzenes, substituted and unsubstituted indans, styrenes, naphthalenes and heavier aromatics or partially hydrogenated aromatics, and various hydrocarbon or oxygenated compound types across the entire carbon number range common to gasolines and/or other materials boiling below 350°C.

Complete Chemist's Rules for Mogas

Rule ^a	Compound ^b	Masses ^c							Retention Time ^d	
									Start	End
1	C3=	27	41	42						1.59
2	C3	29	43	44					1.570	1.600
3	iC4	29	43	58					1.605	1.624
4	nC5	29	43	58					1.624	1.680
5	C5=	27	41	55	70				1.684	1.708
6	C5	29	43	57	72				1.705	1.739
7	C5=	27	41	55	70				1.736	1.772
8	C5	29	43	57	72				1.739	1.794
9	C5=	27	41	55	70				1.772	1.794
10	C5/-2	39	53	68					1.775	1.796
11	C5=	27	41	55	70				1.794	1.840
12	C5/-2	39	53	68					1.796	1.839
13	C5/-2	39	53	68					1.839	1.873
14	C5/-4	39	40	65	66				1.856	1.882
15	C6=	27	41	55	56	69	84		1.907	1.934
16	C6	29	43	57	71	86			1.926	1.973
17	C6=	27	41	55	56	69	84		1.934	1.962

18	C5=	27	41	55	70				1.945	1.969
19	C6=	27	41	55	56	69	84		1.962	1.982
20	C6	29	43	57	71	86			1.998	2.032
21	C6=	27	41	55	56	69	84		2.036	2.066
22	C6	29	43	57	71	86			2.076	2.117
23	C6=	27	41	55	56	69	84		2.095	2.137
24	C6=	27	41	55	56	69	84		2.137	2.156
25	C6=	27	41	55	56	69	84		2.156	2.178
26	C6/-2	41	53	67	82				2.159	2.186
27	C6=	27	41	55	56	69	84		2.178	2.203
28	C6/-2	41	53	67	82				2.186	2.204
29	C6=	27	41	55	56	69	84		2.203	2.244
30	C6=	27	41	55	56	69	84		2.244	2.290
31	C7	43	57	71	85	100			2.252	2.276
32	C6=	27	41	55	56	69	84		2.290	2.314
33	C6/-4	39	41	56	79	80			2.357	2.384
34	C6/-4	39	41	56	79	80			2.384	2.415
35	C6/-2	41	53	67	82				2.441	2.477
36	C7=	41	55	69	70	83	98		2.467	2.487
37	C7=	41	55	69	70	83	98		2.519	2.537
38	Benzene	78							2.521	2.590
39	C6=	27	41	55	56	69	84		2.524	2.562
40	C7	43	57	71	85	100			2.554	2.611

41	C7=	41	55	69	70	83	98		2.571	2 610
42	C7	43	57	71	85	100			2 645	2 684
43	C8	39	41	56	83	99	114		2.740	2 870
44	C7=	41	55	69	70	83	98		2.742	2.868
45	C7	43	57	71	85	100			2.771	2.793
46	C7=	41	55	69	70	83	98		2 911	3 141
47	C7	43	57	71	85	100			2.928	2.976
48	C7/-2	39	53	67	81	96			2.978	3 025
49	C7/-2	39	53	67	81	96			3.137	3.167
50	C7=	41	55	69	70	83	98		3.168	3.198
51	C7=	41	55	69	70	83	98		3.246	3.300
52	C8	43	57	71	85	99	114		3.351	3.446
53	C8	43	57	71	85	99	114		3.369	3.422
54	C8=	41	55	69	83	97	112		3.371	3.396
55	C7=	41	55	69	70	83	98		3 409	3 437
56	C8=	41	55	69	83	97	112		3.487	3.509
57	C7/-2	39	53	67	81	96			3.488	3.508
58	C7/-4	41	56	79	93	94			3.530	3.550
59	C8=	41	55	69	83	97	112		3.582	3.605
60	C8	43	55	57	71	99	114		3.585	3.661
61	C7/-4	41	56	79	93	94			3.590	3.710
62	C8	43	57	71	85	99	114		3.610	3.622
63	C8	43	57	70	71	85	99	114	3.661	3.721
64	C7/-2	39	53	67	81	96			3.676	3.727

65	C8	43	57	71	85	99	114		3.734	3.791
66	C8=	41	55	69	83	97	112		3.789	3.817
67	C8	43	57	71	85	99	114		3.805	3.940
68	Toluene	91	92						3.810	3.915
69	C7/-2	39	53	67	81	96			3.874	3.899
70	C8=	41	55	69	83	97	112		3.912	3.990
71	C8=	41	55	69	83	97	112		4.062	4.318
72	C8/-2	39	53	67	81	95	110		4.167	4.181
73	C8	43	57	71	85	99	114		4.191	4.221
74	C8/-2	39	53	67	81	95	110		4.299	4.325
75	C8=	41	55	69	83	97	112		4.491	4.559
76	C9=	41	69	83	97	111	126		4.492	4.588
77	C9	43	71	85	99	113	128		4.492	4.508
78	C9	43	71	85	99	113	128		4.556	4.578
79	C8/-2	39	53	67	81	95	110		4.590	4.605
80	C9=	41	69	83	97	111	126		4.645	4.936
81	Et Benzene	91	105	106					4.804	4.856
82	C9	43	71	85	99	113	128		4.836	4.870
83	m+p-Xylene	91	105	106					4.877	4.956
84	C9	43	71	85	99	113	128		4.906	4.925
85	C9=	41	69	83	97	111	126		4.972	5.084
86	o-Xylene	91	105	106					5.086	5.146
87	C9=	41	69	83	97	111	126		5.113	5.161
88	C9	43	71	85	99	113	128		5.138	5.159

89	C9=	41	69	83	97	111	126		5.211	5.459
90	C3 Benzene	91	92	105	119	120			5.354	5.382
91	C10/-2	109	110	123	137	138			5.400	6.100
92	C10=	69	83	97	111	125	140		5.400	6.210
93	C10	57	71	85	99	113	142		5.400	6.112
94	C3 Benzene	91	92	105	119	120			5.579	5.614
95	C3 Benzene	91	92	105	119	120			5.637	5.732
96	C3 Benzene	91	92	105	119	120			5.777	5.816
97	C3 Benzene	91	92	105	119	120			5.873	5.934
98	C4 Benzene	91	92	105	106	119	134		5.982	6.023
99	C4 Benzene	91	92	105	106	119	134		6.071	6.107
100	C3 Benzene	91	92	105	119	120			6.082	6.123
101	C11=	69	83	97	125	139	154		6.138	6.900
102	C11	71	85	99	113	127	156		6.138	6.754
103	Indane	117	118						6.179	6.217
104	Indene	115	116						6.245	6.286
105	C4 Benzene	91	92	105	106	119	134		6.255	6.402
106	C11/-2	81	95	109	123	137	152		6.400	6.750
107	C4 Benzene	91	92	105	106	119	134		6.434	6.558
108	C11/-4	79	83	107	121	135	150		6.450	6.700
109	C1 Indane	104	117	118	131	145	146		6.0479	6.545
110	C4 Benzene	91	92	105	106	119	134		6.627	6.745
111	C12/-2	81	95	109	123	151	166		6.710	7.430
112	C12=	69	83	97	111	139	168		6.710	7.430

113	C12	71	85	99	113	141	170		6.712	7.330
114	C5 Benzene	91	105	106	119	133	148		6.798	7.048
115	C12/-4	93	107	121	135	149	164		6.800	7.430
116	C2 Indane	104	117	118	131	145	146		6.834	6.846
117	C1 Indane	104	117	118	131	145	146		6.836	6.941
118	C1 Indene	115	129	130					6.903	6.973
119	C13/-2	81	95	109	123	165	180		7.000	7.760
120	C13=	69	83	97	111	153	182		7.000	7.760
121	C2 Indane	104	117	118	131	145	146		7.089	7.207
122	Naphthalene	102	128						7.113	7.182
123	C5 Benzene	91	105	106	119	133	148		7.159	7.198
124	Benzeneothiophene	133	134						7.176	7.210
125	C5 Benzene	91	105	106	119	133	148		7.226	7.251
126	C6 Benzene	91	105	106	119	133	162		7.300	7.320
127	MMT	55	79	134	162	218			7.300	7.820
128	C6 Benzene	91	105	106	119	133	162		7.366	7.500
129	C2 Indane	104	117	118	131	145	146		7.376	7.410
130	C2 Indene	115	129	143	144				7.400	7.604
131	C2 Indane	104	117	118	131	145	146		7.465	7.494
132	C2 Indane	104	117	118	131	145	146		7.547	7.587
133	C3 Indene	115	129	143	157	158			7.600	7.730
134	C5 Benzene	91	105	106	119	133	148		7.631	7.652
135	C13	71	85	99	113	155	184		7.645	7.660

136	C2 Indane	104	117	118	131	145	146		7.652	7.676
137	C3 Indane	117	131	145	159	160			7.664	7.723
138	C1 Benzothio	147	148						7.701	7.849
139	2Me Naphthalene	141	142						7.722	7.770
140	1Me Naphthalene	141	142						7.820	7.861
141	C2 Naphthalene	141	142						8.283	8.382
142	Phenanthrene	178							9.500	10.000

- a) Rule number, integer index
- b) Compound or group of compounds rule applies to, for example
 C3= refers to olefin or cycloparaffin with 3 carbons
 C5/-2 refers to diolefin, dicycloparaffin or cyclo-olefin with 5 carbons
 C5/-4 refers to triolefin, tricycloparaffin, dicyclo-olefin, cyclodiolefin
 with a total of 5 carbons
 C1Benzothio methyl substituted benzothiophene (C_n/H_{2n-10S})
- c) Masses used in Rule [up to n may be specified, where n is an integer which is equal to the number of masses scanned during the time interval (d) either in full scan mode or selected ion monitoring mode].
- d) Retention time for both starting and ending retention times based on historical averages, in minutes

COMPLETE CHEMIST'S RULES FOR MOGAS WITH CORRECTIONS

Total Raw Abundance (TIC) :	125963855	
Chemist Rule :	80972353	(64.282%)
Air Leakage	7201540	(5.717%)
Avg Scan Rate (Min/Max)	128	(126/215)
Number of Records	4857	

Rule ^a	Compound ^b	Masses ^c						Start ^d	End ^e	CStart ^f	Corr ^g	CEnd ^h	Corr ⁱ	Abundance ^j	
1	C3=	27	41	42				1.560	1.590	1.551	-0.009	1.581	-0.009	0	0.00%
2	C3	29	43	44				1.570	1.600	1.561	-0.009	1.591	-0.009	0	0.00%
3	iC4	29	43	58				1.605	1.624	1.596	-0.009	1.614	-0.010	14233	0.02%
4	nC5	29	43	58				1.624	1.680	1.614	-0.010	1.670	-0.010	715655	0.88%
5	C5=	27	41	55	70			1.684	1.708	1.674	-0.010	1.698	-0.010	20805	0.03%
6	C5	29	43	57	72			1.705	1.739	1.695	-0.010	1.730	-0.009	1129596	1.40%
7	C5=	27	41	55	70			1.736	1.772	1.727	-0.009	1.763	-0.009	780267	0.96%
8	C5	29	43	57	72			1.739	1.794	1.730	-0.009	1.785	-0.009	1189151	1.47%
9	C5=	27	41	55	70			1.772	1.794	1.763	-0.009	1.785	-0.009	1097894	1.36%
10	C5/-2	39	53	68				1.775	1.796	1.766	-0.009	1.787	-0.009	194465	0.24%
11	C5=	27	41	55	70			1.794	1.840	1.785	-0.009	1.831	-0.009	1219014	1.51%
12	C5/-2	39	53	68				1.796	1.839	1.787	-0.009	1.830	-0.009	213325	0.26%
13	C5/-2	39	53	68				1.839	1.873	1.830	-0.009	1.864	-0.009	48362	0.06%

14	C5/-4	39	40	65	66				1.856	1.882	1.847	-0.009	1.873	-0.009	35019	0.04%
15	C6=	27	41	55	56	69	84		1.907	1.934	1.898	-0.009	1.925	-0.009	47825	0.06%
16	C6	29	43	57	71	86			1.926	1.973	1.917	-0.009	1.964	-0.009	1586920	1.96%
17	C6=	27	41	55	56	69	84		1.934	1.962	1.925	-0.009	1.953	-0.009	379986	0.47%
18	C5=	27	41	55	70				1.945	1.969	1.936	-0.009	1.960	-0.009	813127	1.00%
19	C6=	27	41	55	56	69	84		1.962	1.982	1.953	-0.009	1.973	-0.009	1160073	1.43%
20	C6	29	43	57	71	86			1.998	2.032	1.989	-0.009	2.023	-0.009	810472	1.00%
21	C6=	27	41	55	56	69	84		2.036	2.066	2.027	-0.009	2.058	-0.008	467971	0.58%
22	C6	29	43	57	71	86			2.076	2.117	2.068	-0.008	2.109	-0.008	1112977	1.38%
23	C6=	27	41	55	56	69	84		2.095	2.137	2.087	-0.008	2.129	-0.008	1269477	1.57%
24	C6=	27	41	55	56	69	84		2.137	2.156	2.129	-0.008	2.148	-0.008	442930	0.55%
25	C6=	27	41	55	56	69	84		2.156	2.178	2.148	-0.008	2.170	-0.008	421028	0.52%
26	C6/-2	41	53	67	82				2.159	2.186	2.151	-0.008	2.178	-0.008	161562	0.20%
27	C6=	27	41	55	56	69	84		2.178	2.203	2.170	-0.008	2.195	-0.008	248065	0.31%
28	C6/-2	41	53	67	82				2.186	2.204	2.178	-0.008	2.196	-0.008	105786	0.13%
29	C6=	27	41	55	56	69	84		2.203	2.244	2.195	-0.008	2.236	-0.008	447307	0.55%
30	C6=	27	41	55	56	69	84		2.244	2.290	2.236	-0.008	2.282	-0.008	1057535	1.31%
31	C7	43	57	71	85	100			2.252	2.276	2.244	-0.008	2.268	-0.008	160388	0.20%
32	C6=	27	41	55	56	69	84		2.290	2.314	2.282	-0.008	2.306	-0.008	484444	0.60%
33	C6/-4	39	41	56	79	80			2.357	2.384	2.349	-0.008	2.377	-0.007	18054	0.02%
34	C6/-4	39	41	56	79	80			2.384	2.415	2.377	-0.007	2.408	-0.007	30534	0.04%
35	C6/-2	41	53	67	82				2.441	2.477	2.434	-0.007	2.470	-0.007	312982	0.39%
36	C7=	41	55	69	70	83	98		2.467	2.487	2.460	-0.007	2.480	-0.007	105390	0.13%

37	C7=	41	55	69	70	83	98		2.519	2.537	2.512	-0.007	2.530	-0.007	48309	0.06%
38	Benzene	78							2.521	2.590	2.514	-0.007	2.583	-0.007	456913	0.56%
39	C6=	27	41	55	56	69	84		2.524	2.562	2.517	-0.007	2.555	-0.007	155038	0.19%
40	C7	43	57	71	85	100			2.554	2.611	2.547	-0.007	2.604	-0.007	1413849	1.75%
41	C7=	41	55	69	70	83	98		2.571	2.610	2.564	-0.007	2.603	-0.007	600947	0.74%
42	C7	43	57	71	85	100			2.645	2.684	2.638	-0.007	2.678	-0.006	1094972	1.35%
43	C8	39	41	56	83	99	114		2.740	2.870	2.734	-0.006	2.865	-0.005	1910679	2.36%
44	C7=	41	55	69	70	83	98		2.742	2.868	2.736	-0.006	2.863	-0.005	1307310	1.62%
45	C7	43	57	71	85	100			2.771	2.793	2.765	-0.006	2.787	-0.006	236375	0.29%
46	C7=	41	55	69	70	83	98		2.911	3.141	2.906	-0.005	3.137	-0.004	1121554	1.39%
47	C7	43	57	71	85	100			2.928	2.976	2.923	-0.005	2.971	-0.005	823658	1.02%
48	C7I-2	39	53	67	81	96			2.978	3.025	2.973	-0.005	3.020	-0.005	203121	0.25%
49	C7I-2	39	53	67	81	96			3.137	3.167	3.133	-0.004	3.163	-0.004	64492	0.08%
50	C7=	41	55	69	70	83	98		3.168	3.198	3.164	-0.004	3.194	-0.004	100858	0.13%
51	C7=	41	55	69	70	83	98		3.246	3.300	3.242	-0.004	3.297	-0.003	624082	0.77%
52	C8	43	57	71	85	99	114		3.351	3.446	3.348	-0.003	3.443	-0.003	700278	0.87%
53	C8	43	57	71	85	99	114		3.369	3.422	3.366	-0.003	3.419	-0.003	672534	0.83%
54	C8=	41	55	69	83	97	112		3.371	3.396	3.368	-0.003	3.393	-0.003	71932	0.09%
55	C7=	41	55	69	70	83	98		3.409	3.437	3.406	-0.003	3.434	-0.003	292860	0.36%
56	C8=	41	55	69	83	97	112		3.487	3.509	3.484	-0.003	3.507	-0.002	77610	0.10%
57	C7I-2	39	53	67	81	96			3.488	3.508	3.485	-0.003	3.506	-0.002	37349	0.05%
58	C7I-4	41	56	79	93	94			3.530	3.550	3.528	-0.002	3.548	-0.002	12506	0.02%
59	C8=	41	55	69	83	97	112		3.582	3.605	3.580	-0.002	3.603	-0.002	106300	0.13%

60	C8	43	55	57	71	99	114		3.585	3.661	3.583	-0.002	3.659	-0.002	947376	1.17%
61	C7/-4	41	56	79	93	94			3.590	3.710	3.588	-0.002	3.708	-0.002	191500	0.24%
62	C8	43	57	71	85	99	114		3.610	3.622	3.608	-0.002	3.620	-0.002	453814	0.56%
63	C8	43	57	70	71	85	99	114	3.661	3.721	3.659	-0.002	3.720	-0.001	780121	0.96%
64	C7/-2	39	53	67	81	96			3.676	3.727	3.674	-0.002	3.726	-0.001	202854	0.25%
65	C8	43	57	71	85	99	114		3.734	3.791	3.733	-0.001	3.790	-0.001	231822	0.29%
66	C8=	41	55	69	83	97	112		3.789	3.817	3.788	-0.001	3.816	-0.001	83481	0.10%
67	C8	43	57	71	85	99	114		3.805	3.940	3.804	-0.001	3.940	0.000	1033435	1.28%
68	Toluene	91	92						3.810	3.915	3.809	-0.001	3.915	0.000	7948033	9.82%
69	C7/-2	39	53	67	81	96			3.874	3.899	3.873	-0.001	3.899	0.000	51218	0.06%
70	C8=	41	55	69	83	97	112		3.912	3.990	3.912	0.000	3.991	0.001	403062	0.50%
71	C8=	41	55	69	83	97	112		4.062	4.318	4.064	0.002	4.324	0.006	932003	1.15%
72	C8/-2	39	53	67	81	95	110		4.167	4.181	4.171	0.004	4.185	0.004	33396	0.04%
73	C8	43	57	71	85	99	114		4.191	4.221	4.195	0.004	4.226	0.005	270706	0.33%
74	C8/-2	39	53	67	81	95	110		4.299	4.325	4.305	0.006	4.331	0.006	92852	0.12%
75	C8=	41	55	69	83	97	112		4.491	4.559	4.500	0.009	4.569	0.010	262214	0.32%
76	C9=	41	69	83	97	111	126		4.492	4.588	4.501	0.009	4.598	0.011	283866	0.35%
77	C9	43	71	85	99	113	128		4.492	4.508	4.501	0.009	4.517	0.009	38948	0.05%
78	C9	43	71	85	99	113	128		4.556	4.578	4.566	0.010	4.588	0.010	48572	0.06%
79	C8/-2	39	53	67	81	95	110		4.590	4.605	4.601	0.011	4.616	0.011	15446	0.02%
80	C9=	41	69	83	97	111	126		4.645	4.936	4.656	0.011	4.952	0.016	401171	0.50%
81	Et Benzene	91	105	106					4.804	4.856	4.818	0.014	4.871	0.015	1755888	2.17%
82	C9	43	71	85	99	113	128		4.836	4.870	4.850	0.014	4.885	0.015	180884	0.22%

83	m+p-Xylene	91	105	106					4.877	4.956	4.892	0.015	4.972	0.016	6618720	8.17%
84	C9	43	71	85	99	113	128		4.906	4.925	4.921	0.015	4.941	0.016	52748	0.07%
85	C9=	41	69	83	97	111	126		4.972	5.084	4.988	0.016	5.100	0.016	183924	0.23%
86	o-Xylene	91	105	106					5.086	5.146	5.102	0.016	5.162	0.016	2736750	3.38%
87	C9=	41	69	83	97	111	126		5.113	5.161	5.129	0.016	5.177	0.016	112279	0.14%
88	C9	43	71	85	99	113	128		5.138	5.159	5.154	0.016	5.175	0.016	78032	0.10%
89	C9=	41	69	83	97	111	126		5.211	5.459	5.226	0.015	5.474	0.015	214003	0.26%
90	C3 Benzene	91	92	105	119	120			5.354	5.382	5.369	0.015	5.397	0.015	92133	0.11%
91	C10/-2	109	110	123	137	138			5.400	6.100	5.415	0.015	6.115	0.015	0	0.00%
92	C10=	69	83	97	111	125	140		5.400	6.210	5.415	0.015	6.225	0.015	379745	0.47%
93	C10	57	71	85	99	113	142		5.400	6.112	5.415	0.015	6.127	0.015	678126	0.84%
94	C3 Benzene	91	92	105	119	120			5.579	5.614	5.594	0.015	5.629	0.015	571333	0.71%
95	C3 Benzene	91	92	105	119	120			5.637	5.732	5.652	0.015	5.747	0.015	4268402	5.27%
96	C3 Benzene	91	92	105	119	120			5.777	5.816	5.792	0.015	5.831	0.015	778193	0.96%
97	C3 Benzene	91	92	105	119	120			5.873	5.934	5.888	0.015	5.949	0.015	3263117	4.03%
98	C4 Benzene	91	92	105	106	119	134		5.982	6.023	5.997	0.015	6.038	0.015	60719	0.08%
99	C4 Benzene	91	92	105	106	119	134		6.071	6.107	6.086	0.015	6.122	0.015	497424	0.61%
100	C3 Benzene	91	92	105	119	120			6.082	6.123	6.097	0.015	6.138	0.015	776999	0.96%
101	C11=	69	83	97	125	139	154		6.138	6.900	6.153	0.015	6.915	0.015	166061	0.21%
102	C11	71	85	99	113	127	156		6.138	6.754	6.153	0.015	6.769	0.015	324662	0.40%
103	Indane	117	118						6.179	6.217	6.194	0.015	6.232	0.015	382862	0.47%
104	Indene	115	116						6.245	6.286	6.260	0.015	6.301	0.015	60477	0.08%
105	C4 Benzene	91	92	105	106	119	134		6.255	6.402	6.270	0.015	6.417	0.015	1817904	2.25%

106	C11/-2	81	95	109	123	137	152		6.400	6.750	6.415	0.015	6.765	0.015	0	0.00%
107	C4 Benzene	91	92	105	106	119	134		6.434	6.558	6.449	0.015	6.573	0.015	1317323	1.63%
108	C11/-4	79	93	107	121	135	150		6.450	6.700	6.465	0.015	6.715	0.015	42140	0.05%
109	Me Indane	104	117	131	132				6.479	6.545	6.494	0.015	6.560	0.015	296319	0.37%
110	C4 Benzene	91	92	105	106	119	134		6.627	6.745	6.642	0.015	6.760	0.015	1013676	1.25%
111	C12/-2	81	95	109	123	151	166		6.710	7.430	6.725	0.015	7.449	0.019	445	0.00%
112	C12=	69	83	97	111	139	168		6.710	7.430	6.725	0.015	7.449	0.019	76201	0.09%
113	C12	71	85	99	113	141	170		6.712	7.330	6.727	0.015	7.347	0.017	181880	.023%
114	C5 Benzene	91	105	106	119	133	148		6.798	7.048	6.813	0.015	7.063	0.015	1158186	1.43%
115	C12/-4	93	107	121	135	149	164		6.800	7.430	6.815	0.015	7.449	0.019	6694	0.01%
116	C2 Indane	104	117	118	131	145	146		6.834	6.846	6.849	0.015	6.861	0.015	65467	0.08%
117	Me Indane	104	117	131	132				6.836	6.941	6.851	0.015	6.956	0.015	725115	0.90%
118	Me Indene	115	129	130					6.903	6.973	6.918	0.015	6.988	0.015	227195	0.28%
119	C13/-2	81	95	109	123	165	180		7.000	7.760	7.015	0.015	7.784	0.024	0	0.00%
120	C13=	69	83	97	111	153	182		7.000	7.760	7.015	0.015	7.784	0.024	82801	0.10%
121	C2 Indane8	104	117	118	131	145	146		7.089	7.207	7.104	0.015	7.222	0.016	430159	0.53%
122	Naphthalene	102	128						7.113	7.182	7.128	0.015	7.197	0.015	680168	0.84%
123	C5 Benzene	91	105	106	119	133	148		7.159	7.198	7.174	0.015	7.213	0.015	214964	0.27%
124	Benzothiophene	133	134						7.176	7.210	7.191	0.015	7.226	0.016	117429	0.15%
125	C5 Benzene	91	105	106	119	133	148		7.226	7.251	7.242	0.016	7.267	0.016	74124	0.09%
126	C6 Benzene	91	105	106	119	133	162		7.300	7.320	7.317	0.017	7.337	0.017	69597	0.09%
127	MMT	55	79	134	162	218			7.300	7.820	7.317	0.017	7.844	0.024	82404	0.10%

128	C6 Benzene	91	105	106	119	133	162		7.366	7.500	7.384	0.018	7.520	0.020	260793	0.32%
129	C2/-8	104	117	118	131	145	146		7.376	7.410	7.394	0.018	7.429	0.019	144073	0.18%
130	C2 Indene	115	129	143	144				7.400	7.604	7.419	0.019	7.626	0.022	185620	0.23%
131	C2 Indane	104	117	118	131	145	146		7.465	7.494	7.485	0.020	7.514	0.020	148372	0.18%
132	C2 Indane	104	117	118	131	145	146		7.547	7.587	7.568	0.021	7.609	0.022	136473	0.17%
133	C3 Indene	115	129	143	157	158			7.600	7.730	7.622	0.022	7.754	0.024	58298	0.07%
134	C5 Benzene	91	105	106	119	133	148		7.631	7.652	7.653	0.022	7.675	0.023	42922	0.05%
135	C13	71	85	99	113	155	184		7.645	7.660	7.668	0.023	7.683	0.023	36141	0.05%
136	C2 Indane/-8	104	117	118	131	145	146		7.652	7.676	7.675	0.023	7.699	0.023	72406	0.09%
137	C3 Indene	117	131	145	159	160			7.664	7.723	7.687	0.023	7.747	0.024	96291	0.12%
138	C1 Benzothio	145	147	148					7.701	7.849	7.724	0.023	7.873	0.024	255718	0.32%
139	2MeNaphthalene	141	142						7.722	7.770	7.746	0.024	7.794	0.024	1030117	1.27%
140	1MeNaphthalene	141	142						7.820	7.861	7.844	0.024	7.885	0.024	410403	0.51%
141	C2 Naphthalene	141	156						8.283	8.382	8.307	0.024	8.406	0.024	39022	0.05%
142	Phenanthrene	178							9.500	10.00	9.524	0.024	10.024	0.024	0	0.00%
															80972353	100.00%

- a) Rule number, integer index
- b) Compound or group of compounds rule applies to, for example
 - C3= refers to olefin or cycloparaffin with 3 carbons
 - C5/-2 refers to diolefin, dicycloparaffin or cyclo-olefin with 5 carbons
 - C5/-4 refers to triolefin, tricycloparaffin, dicyclo-olefin, cyclodiolefin with a total of 5 carbons
 - ClBenzothio methyl substituted benzothiophene ($C_n/H_{2n-10}S$)
- c) Masses used in Rule [up to n may be specified, where n is an integer which is equal to the number of masses scanned during the time interval (d to e) either in full scan mode or selected ion monitoring mode].
- d) start retention time in minutes
- e) end retention time in minutes
- f) corrected start retention time, in minutes
- g) correction = difference between start and cstart (in minutes)
- h) corrected end time, in minutes
- i) correction = difference between end and cend (in minutes)
- j) Abundance, both as total sum and as normalized percentage based on Chemist's Rules.

CLAIMS:

1. (a) A process for controlling the blending of a plurality of blend stocks each having boiling points less than about 350° C into at least one blend product which comprises:
 - (a) selecting at least one physical, perceptual, performance or chemical properties of a least one blend stock or blend product;
 - (b) selecting reference samples, said reference samples containing characteristic compound types present in at least one blend stock or blend product and which may have known values of the property or properties selected in step (a);
 - (c) producing a training set by the steps of:
 - (1) injecting each reference sample into a gas chromatograph which is interfaced to a mass spectrometer thereby causing at least a partial separation of the hydrocarbon mixture into constituent chemical components;
 - (2) introducing the constituent chemical components of each reference sample into the mass spectrometer, under dynamic flow conditions;
 - (3) obtaining for each reference sample a series of time resolved mass chromatograms;
 - (4) calibrating the mass chromatograms to correct retention times;
 - (5) selecting a series of corrected retention time windows;
 - (6) selecting within each retention time window a series of molecular or fragment ions, said ions being representative of characteristic compounds or compound classes expected within the retention time window;



- (7) recording the total amount of each characteristic compound or compound group selected in step c(6);
- (8) forming the data from steps c(6) and c(7) into a X-block matrix;
- (9) forming the property data selected in (a) for reference samples selected in (b) into a Y-block matrix;
- (10) analyzing the data from steps c(8) and c(9) by multivariate correlation techniques including Partial Least Squares, Principal Component Regression, Ridge Regression to produce a series of coefficients;
- (d) subjecting at least one blend stock or blend product sample to steps c(1) to c(3) in the same manner as the reference sample to produce a series of time resolved mass chromatograms;
- (e) repeating steps c(4) to c(8) for each mass chromatogram from step (d);
- (f) multiplying the matrix from step (e) by the coefficients from step c(10) to produce a predicted value of the property or properties for the at least one blend stock or blend product samples; and
- (g) using the predicting values of a selected property or properties of the at least one blend stock or blend product sample to control the amount of blend stock in the blend product.

2. A process for controlling or monitoring chemical or refinery processes which utilize feed stocks and/or produce products having boiling points less than about 350°C which comprises:

- (a) selecting at least one physical, perceptual, performance or chemical property of at least one feed stock, intermediate stream or process product;



- (b) selecting reference samples, said reference samples containing characteristic compound types present in the at least one feed stock, intermediate stream or product and which have known values of the property or properties selected in step (a);
- (c) producing a training set by the steps of:
- (1) injecting each reference sample into a gas chromatograph which is interfaced to a mass spectrometer thereby causing at least a partial separation of the hydrocarbon mixture into constituent chemical components;
 - (2) introducing the constituent chemical components of each reference sample into the mass spectrometer, under dynamic flow conditions;
 - (3) obtaining for each reference sample a series of time resolved mass chromatograms;
 - (4) calibrating the mass chromatograms to correct retention times;
 - (5) selecting a series of corrected retention time windows;
 - (6) selecting within each retention time window a series of molecular and/or fragment ions, said ions being representative of characteristic compounds or compound classes expected within the retention time window;
 - (7) recording the total amount of each characteristic compound or compound group selected in step c(6);
 - (8) forming the data from steps c(6) and c(7) into a X-block matrix;
 - (9) forming the property data selected in (a) for reference samples selected in (b) into a Y-block matrix;



- (10) analyzing the data from steps c(8) and c(9) by multivariate correlation techniques including Partial Least Squares, Principal Component Regression, or Ridge Regression to produce a series of coefficients;
- (d) subjecting at least one refinery of chemical process intermediate, product or feed stock sample to steps c(1) to c(3) in the same manner as the reference sample to produce a series of time resolved mass chromatograms;
- (e) repeating steps c(4) to c(8) for each mass chromatogram from step (d);
- (f) multiplying the matrix from step (e) by the coefficients from step c(10) to produce a predicted value of the property or properties for the refinery or chemical process sample or samples; and
- (g) using the predicted values of the property or properties of the refinery or chemical sample or samples to control the refinery or chemical process.

3. The method of claims 1 or 2 wherein the gas chromatograph is a capillary gas chromatograph and the mass spectrometer is a quadrupole mass spectrometer.

4. The method of claims 1 or 2 wherein the gas chromatograph and mass spectrometer are operated under repeatable conditions.

5. The method of claims 1 or 2 wherein the selection of a series of molecular and/or fragment ions characteristic of compounds or compound classes is accomplished using Chemist's Rules.

6. The method of claims 1 or 2 wherein the selection of a series of molecular and/or fragment ions characteristic of compounds or compound classes is accomplished using Hydrocarbon Type Analysis.



7. The method of claims 1 or 2 wherein data from the gas chromatograph and mass spectrometer are stored in a computer.

8. The method of claims 1 or 2 wherein data from steps (c) to (f) are treated in a computer.

9. The method of claims 1 or 2 wherein other performance, perceptual, chemical or physical properties of the hydrocarbon mixture are selected.

10. The method of claims 1 or 2 wherein the data are collinear.

11. The method of claim 1 wherein the multivariate correlation technique is Partial Least Squares.



* C L M S *