

960704533

IPDS

copy

THIS SHEET HAS BEEN
REPLACED

5 The invention relates to a ROM-RAM disk and a method which makes it possible to read the ROM area and to write to the RAM area at the same time, as well as to read ROM and RAM simultaneously using a scanning unit.

10 A ROM-RAM disk is an optical recording medium which has memory areas which can only be read and memory areas which can both be read and written to. Memories which can only be read are called ROM or read only memory, and memories which can both be read and written to are called RAM or random access memory. A ROM is implemented on optical information media by
15 means of so-called pits which form a spiral data track in the CD. While, in the case of the CD, a light-reflecting aluminium layer has depressions, so-called pits, which represent the data stored on the disk, the MOD has a magnetic layer in which data can be recorded
20 and from which data can be read by means of different magnetization. Information and bits are likewise stored on a spiral data track in domains having a different magnetization direction. In this case, in contrast to an analogue record disc, the data track is read from
25 the inside to the outside at a constant linear velocity, the so-called CLV.

DE-OS 37 32 875 discloses a recording medium which is in the form of a disk and represents a combination of an optical disk and a magneto-optical
30 disk - a so-called ROM-RAM disk. On this recording medium, data are stored both in pits and in domains in a spiral data track. Since the pits and magnetic domains are arranged one above the other, the memory capacity or the memory volume of the ROM-RAM disk is
35 theoretically equal to the sum of the memory volumes.

In order to be able to store and read the information which is stored on an optical information medium in pits or magnetic domains or in a RAM area or a ROM area, a minimum length of memory structures is



required, which length is dependent on the wavelength of the scanning laser beam and the memory principle used. In the case of a laser beam wavelength of 780 nm, which is frequently used for scanning optical information media, the minimum length of a memory structure in the RAM area or in the ROM area is approximately 0.8 μm , in order to implement a maximum memory volume. In order to reproduce information which is stored in the RAM area on a ROM-RAM disk, a minimum length of the recording structure for the RAM information of more than 1.38 μm is required in order to be able to select and read the RAM information from the signal mixture, which consists of ROM information and RAM information. This results in it being necessary to read a ROM area or a RAM area and a ROM-RAM area at a different velocity and in it not being possible simultaneously to read the ROM-RAM area and to read the ROM area and to write to the RAM area at the same time. By increasing the linear velocity CLV, the memory volume of the ROM-RAM disk is necessarily reduced in comparison with the theoretical double memory capacity.

It is therefore the object of the invention to create a ROM-RAM disk and a method which enable simultaneous reading of ROM and RAM and reading of the ROM area and writing to the RAM area at the same time, as well as a memory volume which is as large as possible.

This object is achieved by the invention which is specified in the main claims. Advantageous further developments of the invention are specified in subclaims.

A ROM-RAM disk is used as the basis, which has ROM and RAM memory areas superimposed in a spiral information track. In order to ensure a memory volume which is as large as possible in the case of an information medium of comparable diameter, despite the longer memory structures and increased linear velocity required to separate the information during reading, either the area of a ROM-RAM disk which has both ROM and RAM memory structures is provided only beyond a



diameter beyond which a scanning or writing velocity is reached at a constant rotation speed, which velocity ensures reading and separation of the information stored in ROM and RAM structures, or the entire memory area is provided with a reduced data clock rate for the RAM as well as the ROM-RAM area, which is stored and read using a constant linear velocity.

While the first design provides a recording medium which provides either a ROM area or a RAM area in the inner area and a ROM-RAM memory area only beyond a diameter at which a linear velocity is achieved which is required to separate a ROM signal or RAM signal from a ROM-RAM signal mixture at a constant rotation speed, the second design comprises the available memory surface on the information medium being provided entirely as ROM-RAM and being read and stored using a constant linear velocity with a reduced data clock rate for the RAM. The ROM in the ROM-RAM is unchanged. With respect to the first design, it should be noted that the magneto-optic disk is controlled at a constant angular velocity CAV or a constant rotation speed in conjunction with the reading and storing of data in a normal manner, so that the linear velocity increases with the radius. The RAM memory capacity of the ROM-RAM area of the ROM-RAM disk is therefore identical to the memory capacity of a conventional erasable disk despite not starting until a greater diameter, the memory volume of the ROM-RAM disk being increased by the ROM area, and the simultaneous reading of ROM and RAM as well as reading of the ROM area and writing to the RAM area at the same time being possible. The area which has both RAM and ROM memory structure is provided in the case of the first design beyond a diameter at which the linear velocity is preferably at least 1.8 m/s at a constant rotation speed.

The special feature of the method in conjunction with the first design is, in particular, that, in contrast to the ROM of a CD which is scanned at a constant linear velocity, the ROM-RAM information



medium is scanned at a constant rotation speed or a constant angular velocity, or the information is recorded at a constant angular velocity, a constant rotation speed of the disk in the region of 500 rpm being used for reading and writing information on a ROM-RAM disk.

The method which is provided in conjunction with the second design comprises, in particular, the ROM-RAM disk being read and written to at a constant linear velocity, this being done by the information being stored and read in the RAM area at a data clock rate which is reduced in comparison with the CD. A known linear velocity in the region of 1.2 m/s is used in this case. In this case, it is possible to operate advantageously in a known manner using a constant linear velocity or CLV, since the required lengthening of the memory structures is achieved using the reduced clock rate.

A comparison of the designs shows that the area which can be used for storage or the memory volume of the second design is further increased over that of the first design and consists of the sum of the original ROM memory capacity and the new RAM memory capacity.

The memory capacity of an information medium which simultaneously contains ROM and RAM memory areas in a spiral track is increased, and simultaneous reading of ROM and RAM as well as reading of the ROM area and writing to the RAM area at the same time using one scanning unit are achieved, particularly as a result of the special design of the recording medium and the use of a constant rotation speed, or by using a constant linear velocity with a reduced data rate for the RAM, in an advantageous manner.

The invention is explained in more detail in the following text, with reference to drawings, in which:

Fig. 1 shows a diagram of the linear velocity;

Fig. 2 shows an outline sketch of the memory area distribution of a first ROM/RAM information medium;



Fig. 3 shows an outline sketch of the memory area distribution of a second ROM-RAM information medium.

According to a first design, Fig. 2 shows the memory area distribution of a first ROM-RAM information medium or a first ROM-RAM disk, and Fig. 3 shows the memory area distribution of a second ROM-RAM information medium or a second ROM-RAM disk. The ROM-RAM information media which are illustrated as outline sketches in Figs. 2 and 3 have a centre hole in the inner region for centring the information medium in a playback and/or recording apparatus, adjacent to which there is an area which is provided in accordance with common standardization for clamping-in purposes and is likewise not provided for information storage. Only the area beyond a radius R of approximately 25 mm is thus provided for information storage and information reproduction. The ROM-RAM disk of the first design according to Fig. 2 initially has an area beyond the radius R provided for information storage and information reproduction, and the corresponding diameter, which area contains either exclusively magnetic domains or exclusively pits, that is to say either a ROM or a RAM. Adjacent to this first memory area there is then a second memory area ROM-RAM which has both pits and magnetic domains superimposed in a spiral track, which domains form the actual ROM-RAM memory area. In order to be able to use the elements of known recording and reproduction devices advantageously and nevertheless to be able to implement a comparatively high memory capacity, a memory area distribution having ROM memory in the inner area is preferably selected, so that a rotation speed of approximately 500 rpm can be used. This corresponds to the rotation speed of a CD in the inner area, a linear velocity of approximately 1.2 m/s being implemented. Since this linear velocity is not sufficient for separation of ROM information or RAM information from a ROM-RAM information signal mixture, the ROM-RAM area is provided only beyond a radius R or diameter at which a



linear velocity of more than 1.8 m/s is achieved at a constant rotation speed. This value occurs beyond a radius R of approximately 40 mm, as is clearly illustrated in Fig. 1. Although the recording medium is not completely provided as ROM-RAM in terms of the available memory area, a comparatively greater memory capacity is achieved. This is as a result, in particular, of the length of the memory structure required for scanning signal separation and of a necessary scanning velocity which is higher than in the case of an information medium having exclusively ROM or RAM memory areas.

From Fig. 1 it can be seen that, at a constant rotation speed of 500 rpm, cf. the continuous line in Fig. 1, the velocity V of 1.2 m/s which is required for only-RAM or only-ROM memory areas is achieved at a radius R of 25 mm, and the velocity V of 1.8 m/s which is required for writing and reading of ROM-RAM memory areas is achieved at a radius R of 40 mm.

According to Fig. 3, the second design is represented by a ROM-RAM disk which has both pits and domains superimposed in the entire available memory area on a spiral track, which domains form a ROM-RAM information medium. The ROM-RAM disk is written to at a constant linear velocity of only 1.2 m/s and is also read at only this linear velocity, although this velocity is actually too low for separation of a ROM signal or a RAM signal from a ROM-RAM signal mixture. Nevertheless, simultaneous reading of ROM and RAM and reading of the ROM area and writing to the RAM area at the same time, and an even greater memory volume are achieved, in that the data clock rate of the RAM information is reduced. The reduction in the clock rate leads to longer memory structures, so that the length of the memory structures required to separate a ROM signal or a RAM signal from a ROM-RAM signal mixture is achieved. The memory volume is further increased. This is shown by a simple comparison. In the case of an inner radius R_i of the memory area of 25 mm and an outer radius R_a of the memory area of 75 mm, this



results, in the case of CLV or a constant linear velocity, in an effectively used area A of

$$A = \pi p \cdot R_a^2 - \pi p \cdot R_i^2 = \pi p \cdot 5000 \text{ mm}^2.$$

5 Since it can be assumed that, at a constant clock rate or data rate and using CAV or a constant rotation speed, the inner radius R_i governs the quantity of stored information per track, the memory volume available in each track is only as much as in the first track. Considered from the point of view of
10 memory volume, all tracks are in consequence identical. This results in an effectively used area A of
$$A = 2 \cdot \pi p \cdot R_i (R_a - R_i) = \pi p \cdot 2500 \text{ mm}^2.$$

In consequence, the memory volume in the case of CLV is greater than in the case of CAV, so that a
15 further advantage can be recorded.



Claims



THIS SHEET HAS BEEN REPLACED

1. ROM-RAM disk, which has superimposed ROM and RAM memory areas on a spiral track, characterized in that, corresponding to a first design, an area of a ROM-RAM disk which has both ROM and RAM memory structures is provided only beyond a radius (R) or diameter beyond which a scanning or writing velocity (V) is reached at a constant rotation speed, which velocity ensures reading and separation of the information stored in ROM-RAM structures, or in that, corresponding to a second design, the available memory area is formed entirely by a ROM-RAM memory area, RAM memory structures having a reduced data rate being provided in order to form a length of the memory structures which is required to separate the information stored in ROM-RAM structures.
2. ROM-RAM disk according to Claim 1, characterized in that the inner region, which can be used for information storage, of a ROM-RAM disk which can be written to and read from at a constant rotation speed is a ROM memory area or a RAM memory area up to a diameter at which a sampling rate is reached which is required for reading and separating the information stored in ROM-RAM structures.
3. ROM-RAM disk according to Claim 1 or 2, characterized in that an area which has both a RAM and a ROM memory structure is provided beyond a diameter on the disk at which the scanning rate is at least 1.8 m/s when the rotation speed of the disk is constant.
4. ROM-RAM disk according to Claim 1, characterized in that the RAM memory structures are provided for writing and reading at a linear velocity of 1.2 m/s at a reduced data rate in order to form a length of the memory structures which is necessary to separate the information stored in ROM-RAM structures.
5. Method for the simultaneous reading of a ROM-RAM disk which has a ROM and RAM memory structure and has superimposed ROM and RAM memory areas on a spiral track, and for reading a ROM and for writing to a RAM

This Sheet Has Been Replaced



- at the same time, characterized in that, corresponding to a first design, a ROM-RAM disk has a memory area, which has both ROM and RAM structures, beyond a radius (R) or diameter at which reading or separating of the information stored in the ROM-RAM structures is ensured and the disk is driven at a constant rotation speed in order to read and to write the information, or in that, corresponding to a second design, the available memory area is formed by a ROM-RAM memory area, RAM memory structures having a reduced data rate being provided in order to form the length of the memory structures which is required to separate the information stored in ROM-RAM structures, and the ROM-RAM disk being driven at a constant linear velocity.
- 5
- 10
- 15 6. Method according to Claim 5, characterized in that a rotation speed in the region of 500 rpm is used as the constant rotation speed.
- 20 7. Method according to Claim 5, characterized in that a linear velocity in the region of 1.2 m/s is used as the constant linear velocity.



This Sheet Has Been Replaced



1. ROM-RAM disk having a high memory capacity, and a method for reading and writing to the ROM-RAM disk.

2.

2.1. The object of the invention is to create a ROM-RAM disk and a method which allow simultaneous reading of ROM and RAM and reading of the ROM area and writing to the RAM area at the same time, as well as a memory volume which is as large as possible.

2.2. According to the invention, corresponding to a first design, an area of a ROM-RAM disk which has both ROM and RAM memory structures is provided only beyond a radius (R) or diameter beyond which a scanning or writing velocity (V) is reached at a constant rotation speed, which velocity ensures reading and separation of the information stored in ROM-RAM structures, or, corresponding to a second design, the available memory area is formed entirely by a ROM-RAM memory area, RAM memory structures having a reduced data rate being provided in order to form a length of the memory structures which is required to separate the information stored in ROM-RAM structures.

2.3. The invention can be used especially in conjunction with the production and use of optical recording media.

3. Fig. 1



THIS SHEET HAS BEEN
REPLACED




Fig.1




Fig.2

This Sheet Has Been Replaced






Fig.3



9607045-3

IPO's

copy

REPLACEMENT SHEET

20 MAR 1997

1

ROM-RAM Disk

The invention relates to a ROM-RAM disk and a method which makes it possible to read the ROM area and to write to the RAM area at the same time, as well as to read ROM and RAM simultaneously using a scanning unit.

A ROM-RAM disk is an optical recording medium which has memory areas which can only be read and memory areas which can both be read and written to. Memories which can only be read are called ROM or read only memory, and memories which can both be read and written to are called RAM or random access memory. A ROM is implemented on optical information media by means of so-called pits which form a spiral data track in the CD. While, in the case of the CD, a light-reflecting aluminium layer has depressions, so-called pits, which represent the data stored on the disk, the MOD has a magnetic layer in which data can be recorded and from which data can be read by means of different magnetization. Information and bits are likewise stored on a spiral data track in domains having a different magnetization direction. In this case, in contrast to an analogue record disc, the data track is read from the inside to the outside at a constant linear velocity, the so-called CLV.

DE-OS 37 32 875 discloses a recording medium which is in the form of a disk and represents a combination of an optical disk and a magneto-optical disk - a so-called ROM-RAM disk. On this recording medium, data are stored both in pits and in domains in a spiral data track. Since the pits and magnetic domains are arranged one above the other, the memory capacity or the memory volume of the ROM-RAM disk is theoretically equal to the sum of the memory volumes.

In order to be able to store and read the information which is stored on an optical information medium in pits or magnetic domains or in a RAM area or a ROM area, a minimum length of memory structures is

20 MAR 1997

2

required, which length is dependent on the wavelength of the scanning laser beam and the memory principle used. In the case of a laser beam wavelength of 780 nm, which is frequently used for scanning optical information media, the minimum length of a memory structure in the RAM area or in the ROM area is approximately 0.8 μm , in order to implement a maximum memory volume. In order to reproduce information which is stored in the RAM area on a ROM-RAM disk, a minimum length of the recording structure for the RAM information of more than 1.38 μm is required in order to be able to select and read the RAM information from the signal mixture, which consists of ROM information and RAM information. This results in it being necessary to read a ROM area or a RAM area and a ROM-RAM area at a different velocity and in it not being possible simultaneously to read the ROM-RAM area and to read the ROM area and to write to the RAM area at the same time. By increasing the linear velocity CLV, the memory volume of the ROM-RAM disk is necessarily reduced in comparison with the theoretical double memory capacity.

It is therefore the object of the invention to create a ROM-RAM disk and a method which enable simultaneous reading of ROM and RAM and reading of the ROM area and writing to the RAM area at the same time, as well as a memory volume which is as large as possible.

This object is achieved by the invention which is specified in the main claims. Advantageous further development (sic) of the invention are specified in subclaims.

A ROM-RAM disk is used as the basis, which has ROM and RAM memory areas superimposed in a spiral information track. In order to ensure a memory volume which is as large as possible in the case of an information medium of comparable diameter, despite the longer memory structures and increased linear velocity required to separate the information during reading, either the area of a ROM-RAM disk which has both ROM and RAM memory structures is provided only beyond a

20 MAR 1997

diameter beyond which a scanning or writing velocity is reached at a constant rotation speed, which velocity ensures reading and separation of the information stored in ROM and RAM structures, or the entire memory area is provided with a reduced data clock rate for the RAM as well as the ROM-RAM area, which is stored and read using a constant linear velocity.

While the first design provides a recording medium which provides either a ROM area or a RAM area in the inner area and a ROM-RAM memory area only beyond a diameter at which a linear velocity is achieved which is required to separate a ROM signal or RAM signal from a ROM-RAM signal mixture at a constant rotation speed, the second design comprises the available memory surface on the information medium being provided entirely as ROM-RAM and being read and stored using a constant linear velocity with a reduced data clock rate for the RAM. The ROM in the ROM-RAM is unchanged. With respect to the first design, it should be noted that the magneto-optic disk is controlled at a constant angular velocity CAV or a constant rotation speed in conjunction with the reading and storing of data in a normal manner, so that the linear velocity increases with the radius. The RAM memory capacity of the ROM-RAM area of the ROM-RAM disk is therefore identical to the memory capacity of a conventional erasable disk despite not starting until a greater diameter, the memory volume of the ROM-RAM disk being increased by the ROM area, and the simultaneous reading of ROM and RAM as well as reading of the ROM area and writing to the RAM area at the same time being possible. The area which has both RAM and ROM memory structure is provided in the case of the first design beyond a diameter at which the linear velocity is preferably at least 1.8 m/s at a constant rotation speed.

The special feature of the method in conjunction with the first design is, in particular, that, in contrast to the ROM of a CD which is scanned at a constant linear velocity, the ROM-RAM information

20 MAR 1997

4

medium is scanned at a constant rotation speed or a constant angular velocity, or the information is recorded at a constant angular velocity, a constant rotation speed of the disk in the region of 500 rpm being used for reading and writing information on a ROM-RAM disk.

The method which is provided in conjunction with the second design comprises, in particular, the ROM-RAM disk being read and written to at a constant linear velocity, this being done by the information being stored and read in the RAM area at a data clock rate which is reduced in comparison with the CD. A known linear velocities (sic) in the region of 1.2 m/s is used in this case. In this case, it is possible to operate advantageously in a known manner using a constant linear velocity or CLV, since the required lengthening of the memory structures is achieved using the reduced clock rate.

A comparison of the designs shows that the area which can be used for storage or the memory volume of the second design is further increased over that of the first design and consists of the sum of the original ROM memory capacity and the new RAM memory capacity.

The memory capacity of an information medium which simultaneously contains ROM and RAM memory areas in a spiral track is increased, and simultaneous reading of ROM and RAM as well as reading of the ROM area and writing to the RAM area at the same time using one scanning unit are achieved, particularly as a result of the special design of the recording medium and the use of a constant rotation speed, or by using a constant linear velocity with a reduced data rate for the RAM, in an advantageous manner.

The invention is explained in more detail in the following text, with reference to drawings, in which:

Fig. 1 shows a diagram of the linear velocity;

Fig. 2 shows an outline sketch of the memory area distribution of a first ROM/RAM information medium;

20 MAR 1997

Fig. 3 shows an outline sketch of the memory area distribution of a second ROM-RAM information medium.

According to a first design, Fig. 2 shows the memory area distribution of a first ROM-RAM information medium or a first ROM-RAM disk, and Fig. 3 shows the memory area distribution of a second ROM-RAM information medium or a second ROM-RAM disk. The ROM-RAM information media which are illustrated as outline sketches in Figs. 2 and 3 have a centre hole in the inner region for centring the information medium in a playback and/or recording apparatus, adjacent to which there is an area which is provided in accordance with common standardization for clamping-in purposes and is likewise not provided for information storage. Only the area beyond a radius R of approximately 25 mm is thus provided for information storage and information reproduction. The ROM-RAM disk of the first design according to Fig. 2 initially has an area beyond the radius R provided for information storage and information reproduction, and the corresponding diameter, which area contains either exclusively magnetic domains or exclusively pits, that is to say either a ROM or a RAM. Adjacent to this first memory area there is then a second memory area ROM-RAM which has both pits and magnetic domains superimposed in a spiral track, which domains form the actual ROM-RAM memory area. In order to be able to use the elements of known recording and reproduction devices advantageously and nevertheless to be able to implement a comparatively high memory capacity, a memory area distribution having ROM memory in the inner area is preferably selected, so that a rotation speed of approximately 500 rpm can be used. This corresponds to the rotation speed of a CD in the inner area, a linear velocity of approximately 1.2 m/s being implemented. Since this linear velocity is not sufficient for separation of ROM information or RAM information from a ROM-RAM information signal mixture, the ROM-RAM area is provided only beyond a radius R or diameter at which a

20 MAR 1997

6

linear velocity of more than 1.8 m/s is achieved at a constant rotation speed. This value occurs beyond a radius R of approximately 40 mm, as is clearly illustrated in Fig. 1. Although the recording medium is not completely provided as ROM-RAM in terms of the available memory area, a comparatively greater memory capacity is achieved. This is as a result, in particular, of the length of the memory structure required for scanning signal separation and of a necessary scanning velocity which is higher than in the case of an information medium having exclusively ROM or RAM memory areas.

From Fig. 1 it can be seen that, at a constant rotation speed of 500 rpm, cf. the continuous line in Fig. 1, the velocity V of 1.2 m/s which is required for only-RAM or only-ROM memory areas is achieved at a radius R of 25 mm, and the velocity V of 1.8 m/s which is required for writing and reading of ROM-RAM memory areas is achieved at a radius R of 40 mm.

According to Fig. 3, the second design is represented by a ROM-RAM disk which has both pits and domains superimposed in the entire available memory area on a spiral track, which domains form a ROM-RAM information medium. The ROM-RAM disk is written to at a constant linear velocity of only 1.2 m/s and is also read at only this linear velocity, although this velocity is actually too low for separation of a ROM signal or a RAM signal from a ROM-RAM signal mixture. Nevertheless, simultaneous reading of ROM and RAM and reading of the ROM area and writing to the RAM area at the same time, and an even greater memory volume are achieved, in that the data clock rate of the RAM information is reduced. The reduction in the clock rate leads to longer memory structures, so that the length of the memory structures required to separate a ROM signal or a RAM signal from a ROM-RAM signal mixture is achieved. The memory volume is further increased. This is shown by a simple comparison. In the case of an inner radius R_i of the memory area of 25 mm and an outer radius R_a of the memory area of 75 mm, this

20 MAR 1997

7

results, in the case of CLV or a constant linear velocity, in an effectively used area A of

$$A = \pi p \cdot R_a^2 - \pi p \cdot R_i^2 = \pi p \cdot 5000 \text{ mm}^2.$$

Since it can be assumed that, at a constant clock rate or data rate and using CAV or a constant rotation speed, the inner radius R_i governs the quantity of stored information per track, the memory volume available in each track is only as much as in the first track. Considered from the point of view of memory volume, all tracks are in consequence identical. This results in an effectively used area A of

$$A = 2 \cdot \pi p \cdot R_i (R_a - R_i) = \pi p \cdot 2500 \text{ mm}^2.$$

In consequence, the memory volume in the case of CLV is greater than in the case of CAV, so that a further advantage can be recorded.

THIS SHEET HAS BEEN
REPLACED

REPLACEMENT SHEET

20 MAR 1997

Claims



1. ROM-RAM disk, which has superimposed ROM and RAM memory areas on a spiral track, characterized in that, corresponding to a first design, an area of a ROM-RAM disk which has both ROM and RAM memory structures is provided only beyond a radius (R) or diameter beyond which a scanning or writing velocity (V) is reached at a constant rotation speed, which velocity ensures reading and separation of the information stored in ROM-RAM structures, or in that, corresponding to a second design, the available memory area is formed entirely by a ROM-RAM memory area, RAM memory structures having a reduced data rate being provided in order to form a length of the memory structures which is required to separate the information stored in ROM-RAM structures.
2. ROM-RAM disk according to Claim 1, characterized in that the inner region, which can be used for information storage, of a ROM-RAM disk which can be written to and read from at a constant rotation speed is a ROM memory area or a RAM memory area up to a diameter at which a sampling rate is reached which is required for reading and separating the information stored in ROM-RAM structures.
3. ROM-RAM disk according to Claim 1 or 2, characterized in that an area which has both a RAM and a ROM memory structure is provided beyond a diameter on the disk at which the scanning rate is at least 1.8 m/s when the rotation speed of the disk is constant.
4. ROM-RAM disk according to Claim 1, characterized in that the RAM memory structures are provided for writing and reading at a linear velocity of 1.2 m/s at a reduced data rate in order to form a length of the memory structures which is necessary to separate the information stored in ROM-RAM structures.
5. Method for the simultaneous reading of a ROM-RAM disk which has a ROM and RAM memory structure and has superimposed ROM and RAM memory areas on a spiral track, and for reading a ROM and for writing to a RAM

THIS SHEET HAS BEEN
REPLACED

REPLACEMENT SHEET

20 MAR 1997

9

at the same time, characterized in that, corresponding to a first design, a ROM-RAM disk has a memory area, which has both ROM and RAM structures, beyond a radius (R) or diameter at which reading or separating of the information stored in the ROM-RAM structures is ensured and the disk is driven at a constant rotation speed in order to read and to write the information, or in that, corresponding to a second design, the available memory area is formed by a ROM-RAM memory area, RAM memory structures having a reduced data rate being provided in order to form the length of the memory structures which is required to separate the information stored in ROM-RAM structures, and the ROM-RAM disk being driven at a constant linear velocity.


6. Method according to Claim 5, characterized in that a rotation speed in the region of 500 rpm is used as the constant rotation speed.

7. Method according to Claim 5, characterized in that a linear velocity in the region of 1.2 m/s is used as the constant linear velocity.



This Sheet Has Been Replaced





- 10 -

ROM-RAM Disk.

Abstract

1. ROM-RAM disk having a high memory capacity, and a method for reading and writing to the ROM-RAM disk.

2.

2.1. The object of the invention is to create a ROM-RAM disk and a method which allow simultaneous reading of ROM and RAM and reading of the ROM area and writing to the RAM area at the same time, as well as a memory volume which is as large as possible.

2.2. According to the invention, corresponding to a first design, an area of a ROM-RAM disk which has both ROM and RAM memory structures is provided only beyond a radius (R) or diameter beyond which a scanning or writing velocity (V) is reached at a constant rotation speed, which velocity ensures reading and separation of the information stored in ROM-RAM structures, or, corresponding to a second design, the available memory area is formed entirely by a ROM-RAM memory area, RAM memory structures having a reduced data rate being provided in order to form a length of the memory structures which is required to separate the information stored in ROM-RAM structures.

2.3. The invention can be used especially in conjunction with the production and use of optical recording media.

3. Fig. 1

20 MAR 1997

1




Fig.1




Fig.2




Fig.3



REPLACEMENT SHEET

24 AUG 1998


8

57045-3

IPO's

copy

1. ROM-RAM disk, which has superimposed ROM and RAM memory areas on a spiral track, characterised in that, an area of a ROM-RAM disk which has both ROM and RAM memory structures is provided only beyond a radius (R) or diameter beyond which a scanning or writing velocity (V) is reached at a constant rotation speed, which velocity ensures reading and separation of the information stored in ROM-RAM structures.
2. ROM-RAM disk according to Claim 1, characterized in that the inner region, which can be used for information storage, of a ROM-RAM disk which can be written to and read from at a constant rotation speed is a ROM memory area or a RAM memory area up to a diameter at which a sampling rate is reached which is required for reading and separating the information stored in ROM-RAM structures.
3. ROM-RAM disk according to Claim 1 or 2, characterized in that an area which has both a RAM and a ROM memory structure is provided beyond a diameter on the disk at which the scanning rate is at least 1.8 m/s when the rotation speed of the disk is constant.
4. ROM-RAM disk according to Claim 1, characterized in that the RAM memory structures are provided for writing and reading at a linear velocity of 1.2 m/s at a reduced data rate in order to form a length of the memory structures which is necessary to separate the information stored in ROM-RAM structures.
5. Method for the simultaneous reading of a ROM-RAM disk which has a ROM and RAM memory structure and has superimposed ROM and



RAM memory areas on a spiral track, and for reading a ROM and for writing to a RAM at the same time, characterised in that, a ROM-RAM disk has a memory area, which has both ROM and RAM structures, beyond a radius (R) or diameter at which reading or separating of the information stored in the ROM-RAM structures is ensured and the disk is driven at a constant rotation speed in order to read and to write the information.

6. Method according to Claim 5, characterized in that a rotation speed in the region of 500 rpm is used as the constant rotation speed.
7. Method according to Claim 5, characterized in that a linear velocity in the region of 1.2 m/s is used as the constant linear velocity.