



DEMANDE INTERNATIONALE PUBLIÉE EN VERTU DU TRAITE DE COOPERATION EN MATIÈRE DE BREVETS (PCT)

(51) Classification internationale des brevets ⁶ : F16L 19/08, 19/12, 47/04	A1	(11) Numéro de publication internationale: WO 97/15777
		(43) Date de publication internationale: 1er mai 1997 (01.05.97)

(21) Numéro de la demande internationale: PCT/FR96/0164

(22) Date de dépôt international: 21 octobre 1996 (21.10.96)

(30) Données relatives à la priorité:

95/12702

27 octobre 1995 (27.10.95)

FR

(71) Déposant (pour tous les Etats désignés sauf US): LEGRIS S.A.
[FR/FR]; 74, rue de Paris, F-35000 Rennes (FR).

(72) Inventeur; et

(75) Inventeur/Déposant (US seulement): BOGARD, Olivier
[FR/FR]; 1, rue Lenoir, F-35000 Rennes (FR).4) Mandataires: ROBERT, Jean-Pierre etc.; Cabinet Boettcher,
23, rue La Boétie, F-75008 Paris (FR).(81) Etats désignés: CN, JP, KR, SG, US, brevet européen (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

Publiée

Avec rapport de recherche internationale.

(54) Title: DEVICE FOR CONNECTING A TUBE TO A COUPLING

(54) Titre: DISPOSITIF DE LIAISON D'UN TUBE A UN EMBOUT

(57) Abstract

A device for joining a tube (3) to a cylindrical coupling (1) defined by a front surface (6) and a coupling sleeve (11) of which a first section (12) comprises releasable fastening means (13) engageable with aligned means (5) on the coupling (1), while a second portion (14) axially adjacent to the first (13) comprises means (15) for preventing the removal of the end of the tube (3) inserted into the sleeve (11) and engaging the front surface (6) of the coupling (1). The sleeve (11) is provided with an internal guide ring (19) for guiding the end of the tube (3), the internal diameter (D) of the guide ring is substantially the same as the external diameter of the tube (3), and said ring includes a first portion (20) slidably mounted in the second section (14) of the sleeve (11), and a second portion (21) axially projecting into the first section (12) of the sleeve (11), whereas the coupling (1) is provided with a groove (7) formed in the front surface (6) thereof for receiving and centring the free end of the second projecting portion (21) of the ring (19) when the fastening means (5, 13) are in mutual engagement.

