


METHOD FOR LIMITING THE DEFLECTION OF A LASER BEAM FROM A LASER HEAD DURING TEMPERATURE CHANGES AND A LASER HEAD**Technical field**

The invention relates to a method for limiting the deflection of a laser head during temperature changes and to the actual construction of the laser heads with a resonator firmly connected to the head body used in systems whose operating temperature can change significantly and rapidly. These temperature changes can be caused by external influences when the system with "storage" temperature must suddenly operate in an environment with a significantly different temperature, or by internal influences when the laser head is heated by waste heat during intensive laser operation. The invention falls within the field of laser technology.

Background of the invention

Laser heads of several laser types, e.g. "TEA" (Transversally Excited at Atmospheric pressure), are often designed so that the heat transfer between the head and the environment is significant only through a part of their surface. Such laser heads are namely often designed as blocks that have good thermal contact with the environment through only one of 6 walls of such a block. At least two walls, usually three, are namely equipped with high-voltage bushings, the other two carry elements of the optical resonator of the head, where on one wall there is a semi-transparent mirror and on the opposite wall there is a "totally" reflecting mirror. Thus, four to five walls out of six are logically excluded from significant heat transfer. The sixth wall is connected via a low thermal resistance to a cooler mediating heat exchange with the environment.

Under these circumstances, a thermal gradient develops on the head. The thermal resistance of the sixth wall of the head, which is usually the largest wall in the surface, to the environment is small. The resistance of the remaining walls is large. Since the material of the head has certain, often non-negligible, thermal expansion, it comes to deformation – to the deflection of the laser head. The described process cannot be symmetrical with respect to the resonator axis. Since the simplest and in several respects also the most advantageous design of the head uses resonator elements directly and firmly connected to the head body, it leads to the misplacement of the resonator mirrors, as they cease to be ideally parallel. The consequence of such a condition is a deterioration of the parameters, or even a failure of the laser.



SECTION A - A




Fig. 1

a slight increase in the weight of the head, it is possible to significantly reduce the thermal resistance between the warmest and coldest wall of the head. The result is a reduction in the temperature difference between the walls of the head, which significantly reduces the influence of thermal dynamics on the mechanical stability of the optical resonator and thus leads to more stable laser parameters.

Brief description of the drawings

A method for limiting the deflection of the laser head during temperature changes and a laser head according to the present invention is illustrated in the attached drawings. Fig. 1 shows the actual laser head in a side view and in section A - A. Fig. 2 shows the actual laser head in a top view and in a front view.

Examples of embodiment of the invention

It is to be understood that the individual embodiments of the invention are presented for illustration and not as a limitation of the technical solutions. Those skilled in the art will find out or be able to ascertain by using no more than routine experimentation many equivalents to specific embodiments of the invention. Such equivalents will also fall within the scope of the claims.

It cannot be a problem for those skilled in the art to optimally design the construction and the selection of its elements; therefore these features have not been solved in detail.

Example 1

In this example of a particular embodiment of the invention, a solution of the method for limiting the deflection of the laser head during temperature changes according to the present invention is described. The method is applied to a TEA laser head of a CO₂ laser in the shape of a block made of stainless steel. From Fig. 1 and 2 it is apparent that the front wall 5 and the rear wall 6 carry resonator mirrors 7, while the HV bushing 8 of the main discharge electrodes is located on the upper wall 2. The left and right side walls 1 carry HV bushings 8 of pre-ionizers. The last lower wall 3 is smooth and heat is lead away from the head through it. The thermal gradient that deforms the head, originates between the warmest upper wall 2 and the coldest lower wall 3 and detuns the resonator as a result. This thermal gradient or temperature difference is, however, significantly limited in such a way that between the warmest upper wall 2 and the coldest lower wall 3 of the laser head, metal plate parts 4 with high thermal conductivity and low specific weight are

attached by a thermally conductive joint to the side walls 1 connecting the upper wall 2 and the lower wall 3 of the laser head.

Alternatively, due to weather and / or operating conditions, it is possible that the lower wall 2 of the laser head will be the warmest and the upper wall 3 will be the coldest.

Example 2

In this example of a particular embodiment of the invention, the construction of TEA head of a CO₂ laser in the shape of a block made of stainless steel is described, as shown in Fig. 1 and 2. The laser head TEA of a CO₂ laser basically described in Example 1 is further solved in such a way that four metal plate parts 4 with high thermal conductivity and even with a low specific weight, what aluminum is suitable for, are attached on each side by a thermally conductive joint to the side walls 1 connecting the warmer upper wall 2 and the colder lower wall 3 of the laser head.

Industrial usability

The method for limiting the deflection of the laser head during temperature changes and a laser head is usable in applications of laser technology.