

SECURING DEVICE

This invention relates to a device for securing at least one cable, pipe or other elongate member to a support and/or for securing together two or more cables, pipes or other elongate members, for convenience, hereinafter being included in the term "cable".

In installing single-core electric power cables in cable networks of industrial plant, it is the general practice to arrange three single-core power cables alongside one another with their axes passing through the apices of a triangle, such an arrangement usually being referred to as a trefoil cable group. A trefoil cable group is usually secured to a cable ladder by means of cleats and, at spaced positions between the cleats, the cables of the group are secured together by cable straps or ties. These arrangements have the disadvantage that for different sizes of cables different sizes of cable straps and cleats have to be used.

A cable securing device is also known in which a strap is wrapped around the cables to secure them together, one end of the strap being fixed to a plate having a rotatable split rod, and the free end of the strap being held in the slit in the rod. When the rod is rotated the strap is tensioned around the cables to secure them together. This arrangement has the disadvantage that in use there is nothing to prevent the

rod rotating to loosen the strap.

It is an object of the present invention to provide a device for securing at least one cable to a support and/or for securing together two or more cables which is
5 capable of accommodating a greater range of cable sizes, and which remains secured when in use.

According to the present invention the device comprises a strap which can pass around the cable or cables to be secured at least once, and tensioning means
10 for tensioning the strap around the cable or cables, the tensioning means comprising a plate having upstanding walls at each end between which the strap can pass; a rod in the form of a split pin being rotatably securable in aligned apertures in the upstanding walls of the
15 plate; and locking means for preventing rotation of the split pin when positioned in the apertures, the locking means comprising a key which engages in the eye of the split pin and which can be used to assist in rotating the split pin, and the upstanding walls of the plate have aligned slots, the arrangement being such that
20 after rotation of the split pin the key can be turned over to engage in the aligned slots to prevent further rotation of the split pin.

This arrangement is such that in use one end of the strap is fastened to the plate (for example by welding),
25 and, after the strap has passed one or more times around the cable or cables to be secured and the split pin has

been positioned in the apertures in the upstanding walls of the plate, the free end of the strap is passed through the slit in the rotatable split pin, the split pin is rotated to tension the strap around the cable or cables, and the locking means is then used to prevent
5 further rotation (either tightening or loosening the strap) of the split pin.

The plate is preferably made of stainless steel.

When the device is used for securing two or more
10 cables it is preferable that the strap is passed around the cables at least twice in order to prevent the strap cutting into one or more of the cables due to any outward lateral movement of one of the cables (for example, as occurs when an electric cable is subjected
15 to a high level short circuit current).

The strap is preferably made of stainless steel.

This invention can either be used on its own for securing together two or more cables, or can be used in conjunction with a base member and bar arrangement (as
20 described and claimed in our Patent Application published under the Serial No. 2082242A) for securing one or more cables to a support, or can be used

in conjunction with a bar defined by, for example, a rung of a cable ladder, or the central portion of a U-bolt, for securing a cable or cables to the bar.

The invention is further illustrated, by way of example, with reference to the accompanying drawings in which:-

Figure 1 is a perspective view of a securing device in accordance with the invention;

Figures 2 and 3 are top and side views respectively of the strap and plate shown in Figure 1;

Figure 4 is a view of the key and split pin used with the plate and strap shown in Figures 2 and 3; and

Figure 5 is a developed view of the plate shown in Figures 2 and 3.

Referring to Figure 1, the device 1 for securing three cables 2 together, comprises a stainless steel strap 9 which passes around the cables and which is tensioned by tensioning means 10.

The tensioning means 10 (see Figures 2 to 5) comprises a stainless steel plate 30 having upstanding

- 5 -

walls 31 at each end between which the strap 9 passes. A rod, in the form of a stainless steel split pin 32, is rotatably secured in aligned apertures 33 in the upstanding walls 31 of the plate 30. In this arrangement one end 34 of the strap 9 is welded to the central portion 35 of the plate 30. The free end 36 of the strap 9 is passed around the cables 2 to be secured together and then passed through the slit in the split pin 32. Rotating the split pin 32 winds the strap 9 around the split pin and thereby tensions the strap around the cables 2. Locking means is provided by a key 37 which engages in the eye 38 of the split pin 32 and can be used to assist in rotating the split pin, and which can lock the split pin by being turned over to engage in aligned slots 39 in the upstanding walls 31 of the plate 30.

Although this invention is only illustrated by a strap and tensioning means only, it will be appreciated that a device in accordance with the invention may also comprise a base member and bar arrangement for securing together two or more cables, and for securing one or more cables to a support. Alternatively the strap may also be passed around a support member defined by a rung of a cable ladder, etc., to secure the cable or cables to the bar.



CLAIMS

1. A device for securing at least one cable to a support and/or for securing together two or more cables, comprising a strap which can pass around the cable or cables to be secured at least once, and tensioning means
5 for tensioning the strap around the cable or cables, the tensioning means comprising a plate having upstanding walls at each end between which the strap can pass; a rod in the form of a split pin being rotatably securable in aligned apertures in the upstanding walls of the
10 plate; and locking means for preventing rotation of the split pin when positioned in the apertures, the locking means comprising a key which engages in the eye of the split pin and which can be used to assist in rotating the split pin, and the upstanding walls of the plate have aligned slots, the arrangement being such that
15 after rotation of the split pin the key can be turned over to engage in the aligned slots to prevent further rotation of the split pin.

2. A device as claimed in Claim 1 when the strap is wrapped around a support member to secure the cable or
20 cables to the support member.

3. A device as hereinbefore described, with reference to, and as shown in, Figures 1 to 5 of the accompanying drawings.



4. A device as hereinbefore described, with reference to, and as shown in, Figures 1 to 5 of the accompanying drawings.