

METHOD AND APPARATUS FOR THE PRODUCTION OF NITROGEN TRIFLUORIDE

FIELD OF THE INVENTION

The present invention is directed to a process and apparatus for the production of nitrogen trifluoride from ammonia and elemental fluorine using an ammonium acid fluoride melt intermediate.

5

BACKGROUND OF THE INVENTION

The gas phase reaction of ammonia and gaseous elemental fluorine can produce nitrogen trifluoride. Reaction 1 illustrates the desired gas phase NF_3 production reaction.



10

Reaction 1

wherein (g) denotes the gas phase. A solid catalyst is often used to lower the required operating temperature, which increases the NF_3 yield. However, it is very difficult to control the reactor temperature due to the highly exothermic nature of Reaction 1. As a result, the gas phase ammonia and fluorine reaction produces
15 substantial quantities of HF, N_2 , N_2F_2 , and NH_4F , with NF_3 yields typically substantially less than ten percent.

United States Patent No. 4,091,081 teaches a process that produces much higher nitrogen trifluoride [NF_3] yields (approaching 60%) by contacting a molten ammonium acid fluoride [$\text{NH}_4\text{F}(\text{HF})_x$] with gaseous fluorine [F_2] and ammonia
20 [NH_3]. U.S. Patent No. 5,637,285 to Coronell *et al.* describes a similar process, wherein the F_2 -to- NF_3 conversion is further increased to greater than ninety percent by inputting a large amount of mechanical energy for mixing the reactants and by using an ammonium acid fluoride melt having a HF/ NH_3 molar ratio greater than 2.55. The Coronell patent teaches that improved NF_3 yields are achieved with
25 mechanical energy inputs greater than 1,000 watts per cubic meter, preferably at or



159159

200300103-9

17 JAN 2003



G00002

above 5,000 watts per cubic meter, most preferably at or above 35,000 watts per cubic meter. The Coronell patent utilizes a stirrer or turbine, such as a flat blade turbine, to input the mechanical energy.

However, inputting such large amounts of power using a stirrer or turbine poses reactor reliability problems. Typically, the mixing turbines that are used in this type of application are constructed of a metal, such as monel or nickel, coated with a metal fluoride passivating layer. The passivating layer is typically applied by contacting the metal turbine with a fluorine rich atmosphere. The passivating layer significantly reduces oxidation of the turbine substrate. However, the high power inputs suggested by the Coronell patent produce high sheer rates that can remove the passivating layer and expose the underlying turbine substrate to fluorine, thereby accelerating the rate of corrosion, particularly at the tip of the mixing impeller. In turn, the corrosion leads to excessive mixer shaft vibration and premature mixer shaft seal failure. Even if very diligent maintenance procedures essentially eliminate shaft vibration, the combination of a high-speed rotating seal and a corrosive fluorine and hydrogen fluoride atmosphere can lead to reliability problems. In addition, high mechanical energy input into a reactor, via a flat bladed turbine, can lead to a highly back-mixed reaction volume with essentially uniform operating conditions. In this case, there is no opportunity to optimize the local reactor operating conditions. Therefore, there remains a need in the art for a method and apparatus to efficiently and reliably contact gaseous fluorine with $\text{NH}_4\text{F}(\text{HF})_x$ solution to produce nitrogen trifluoride.

SUMMARY OF THE INVENTION

The present invention combines a heat engine cycle with an NF_3 reactor to eliminate or greatly reduce the need for mechanical energy inputs derived from stirrers or turbines, without sacrificing high F_2 -to- NF_3 conversion rates. The present invention utilizes a working fluid, such as hydrogen fluoride, in the form of a vapor jet to impart kinetic energy to a mixing zone of a NF_3 reactor, thereby intimately contacting a fluorine reactant with an ammonium acid fluoride melt in order to

achieve a high F_2 -to- NF_3 conversion rate. The working fluid may then be separated from the gaseous NF_3 product and recycled for continuous use in the heat engine cycle. In contrast to prior art processes, the present invention provides an NF_3 reactor that adequately mixes the reactants without the need for high mechanical energy inputs from a stirrer or turbine. Thus, the present invention avoids many of the corrosion problems associated with systems utilizing mechanical mixing devices.

In one aspect, the present invention provides a method for producing nitrogen trifluoride. The method includes providing a reactor comprising a mixing zone and a reaction zone in fluid communication with the mixing zone. The two reactants used for nitrogen trifluoride production, gaseous fluorine and liquid ammonium acid fluoride, are fed into the mixing zone of the reactor. A working fluid vapor jet, such as a hydrogen fluoride vapor jet, is also fed into the mixing zone of the reactor. The working fluid vapor jet transfers kinetic energy into the mixing zone, the kinetic energy dispersing the gaseous fluorine within the liquid ammonium acid fluoride.

The liquid ammonium acid fluoride and the fluorine dispersed therein react to produce nitrogen trifluoride as the reactant mixture passes through the reaction zone of the reactor. A gaseous reaction product stream is removed from the reactor, the reaction product stream comprising nitrogen trifluoride and the working fluid vapor.

The gaseous product stream may then be separated into a gaseous nitrogen trifluoride product stream and a liquid working fluid stream. The working fluid stream is then recycled for reuse as the working fluid vapor jet. For example, the liquid working fluid stream may be pressurized to a pressure of about 250 to about 1600 kPa and then vaporized to form a working fluid vapor. Thereafter, the working fluid vapor may be passed through a nozzle to again form the working fluid vapor jet. In this manner, the working fluid travels through a complete heat engine cycle and provides an efficient method for generating mixing intensity in the nitrogen trifluoride reactor.

In another aspect, the present invention provides an apparatus for producing nitrogen trifluoride. The apparatus includes a reactor comprising a mixing zone and a reaction zone in fluid communication with the mixing zone. The reactor further

comprises a product outlet. The apparatus includes both a gaseous fluorine feed supply and a liquid ammonium acid fluoride feed supply in fluid connection with the mixing zone of the reactor. In addition, a working fluid vapor supply is in fluid connection with the mixing zone of the reactor. A least one nozzle is operatively positioned in fluid connection with the working fluid vapor supply upstream of the mixing zone of the reactor such that the working fluid vapor passes through the nozzle, thereby forming a vapor jet. The apparatus may further comprise a separator in fluid connection or communication with the product outlet of the reactor. The separator is operatively positioned to separate a liquid working fluid stream from a gaseous nitrogen trifluoride stream. The working fluid vapor supply may comprise a liquid working fluid supply and a heat exchanger in fluid communication with the liquid working fluid supply. The heat exchanger should be capable of transferring sufficient heat energy to vaporize the liquid working fluid, thus forming a working fluid vapor. In one embodiment, the heat exchanger utilizes the heat of reaction generated in the nitrogen trifluoride reactor as the heat source for vaporizing the liquid working fluid. For example, the heat exchanger may be positioned within the reactor itself.

BRIEF DESCRIPTION OF THE DRAWINGS

Having thus described the invention in general terms, reference will now be made to the accompanying drawing, which is not necessarily drawn to scale, and wherein:

Figure 1 is qualitative pressure-volume plot for the interlocking HF and $\text{NH}_4\text{F}(\text{HF})_x$ heat engine cycle used to internally generate mechanical energy to mix the F_2 and $\text{NH}_4\text{F}(\text{HF})_x$ melt reactants for NF_3 production;

Figure 2 illustrates an up-flow reactor configuration that uses the power cycle illustrated in Figure 1 to produce NF_3 ; and


Figure 3 illustrates a down-flow reactor configuration that uses the power cycle illustrated in Figure 1 to produce NF_3 .

DETAILED DESCRIPTION OF THE INVENTION

The present invention now will be described more fully hereinafter with reference to the accompanying drawings, in which preferred embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein; rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art. Like numbers refer to like elements throughout.

As used herein, the term “ammonium acid fluoride” includes all ammonium poly(hydrogen fluoride) complexes and ammonium fluorometallate poly(hydrogen fluoride) complexes. The ammonium acid fluoride compositions can be generically described by the acid-base stoichiometry of $\text{NH}_4\text{M}_y\text{F}_z(\text{HF})_x$, wherein M is a metal selected from the group consisting of Group IA through VA, Group IB through VIIB and Group VIII of the Periodic Table of Elements or mixtures thereof; y is typically 0-12; z is typically 1-12 and is chosen to maintain the charge neutrality of the complex; and x is the melt acidity value. In a preferred embodiment, y approaches 0 and z approaches unity, thus yielding a complex with an acid-base stoichiometry of $\text{NH}_4\text{F}(\text{HF})_x$. However, other ammonium acid fluoride complexes may be used without departing from the present invention.

A simplified description of the NF_3 production process chemistry involved in the present invention is given below. The ammonium acid fluoride melt intermediate, $\text{NH}_4\text{F}(\text{HF})_x$, wherein x is the melt acidity value, is typically formed by the reaction of gaseous ammonia with either gaseous HF via Reaction 2 below or $\text{NH}_4\text{F}(\text{HF})_x$ melt via Reaction 3 below.




Reaction 2




Reaction 3

wherein (ℓ) denotes a species in the liquid phase.

The ammonium acid fluoride intermediate product from either Reaction 2 or 3 can react with a gaseous fluorine feed to produce the desired nitrogen trifluoride product via Reaction 4 below.




wherein c_1 is the fraction of the F_2 feed that reacts to produce NF_3 and α is the ratio of the $NH_4F(HF)_x$ that is in contact with the F_2 feed from mass and heat transfer viewpoints to the stoichiometric requirement. Optimum reactor performance requires high effective values of α and x to control the $NH_4F(HF)_x (\ell)$ temperature in contact with the fluorine gas bubbles in the reactor and ammonia vaporization into the fluorine gas bubbles, as illustrated in Reaction 5 below.



wherein β is the HF to NH_3 ratio that is transferred from the $NH_4F(HF)_x$ melt to the F_2 bubble.

The major competing reaction, Reaction 6 below, produces N_2 rather than NF_3 .




wherein c_2 is the fraction of the F_2 feed that reacts to produce N_2 .

Alternatively, F_2 could pass through the NF_3 reactor without reacting as shown below in Reaction 7.



wherein c_3 is the fraction of the F_2 feed that passes through the reactor without reacting. Reactions 4 to 7 describe essentially all the fluorine reactions ($c_1 + c_2 + c_3 = 1$).

The HF by-product may be removed from the $\text{NH}_4\text{F}(\text{HF})_x$ melt by vaporization via Reaction 8.



Reaction 8

5 The present invention utilizes mechanical energy derived from a heat engine to eliminate or greatly reduce the need for mechanical energy from turbines or stirrers in the NF_3 reactor to achieve high F_2 -to- NF_3 conversions (c_1 in Reaction 4). A brief description of the Carnot cycle, a well-known heat engine, serves to illustrate the underlying principles of the invention (See Walter J. Moore, Physical Chemistry, 10 Third Edition (1962), Prentice-Hall, p. 70). Heat and energy transfer occurs between the heat engine system and its environment. The Carnot cycle uses a gas working fluid system to partially convert heat transferred from a higher temperature reservoir in its environment to a separate lower temperature reservoir in its environment in order to transfer the maximum mechanical energy from the working fluid system to 15 its environment. In this context, a working fluid is any material that undergoes a series of cyclic transformations, physical and/or chemical. The Carnot cycle can be described in terms of four steps. In the first step, heat is withdrawn from a high temperature reservoir by isothermal reversible expansion of the gas working fluid, which also transfers mechanical energy to the environment. Next, an adiabatic 20 reversible expansion of gas transfers mechanical energy to the environment and cools the gas. Then, work from the environment results in isothermal (heat to the lower temperature reservoir) reversible compression of the system. Finally, an adiabatic reversible compression returns the gas working fluid to its original temperature and pressure state. The net outcome of this process is maximum net mechanical energy is 25 transferred from the system to its environment based the transfer of heat from a high temperature reservoir in the environment to a low temperature reservoir in the environment.

30 The present invention uses a heat engine to produce mechanical energy within the NF_3 reactor to establish the desired flow patterns within the reactor and intimately mix the F_2 and $\text{NH}_4\text{F}(\text{HF})_x$ reactants to efficiently produce NF_3 . Preferably, the heat

of reaction is used as the thermal energy source needed for the heat engine. In a preferred embodiment, the invention uses two working fluids [HF and $\text{NH}_4\text{F}(\text{HF})_x$] in interlocking cycles to produce mechanical work for mixing and fluid flow within the NF_3 reactor. The preferred working fluids were selected because $\text{NH}_4\text{F}(\text{HF})_x$ is a reactant for NF_3 production and HF is a product of NF_3 production and can help control NH_3 vaporization (Reaction 5). Although the remainder of the invention description refers to the exemplary working fluids [HF and $\text{NH}_4\text{F}(\text{HF})_x$], other working fluids could be used without departing from the present invention. As used herein, “working fluid” refers to any fluid capable of undergoing the cyclic compression and expansion steps of the heat engine cycle without interfering with the reaction of gaseous fluoride and liquid ammonium acid fluoride. The working fluid should also be readily separable from the NF_3 reaction product. For example, other hydrogen halides, such as hydrogen chloride, could be used.

Figure 1 provides a qualitative HF pressure-specific volume diagram illustrating the various steps of the heat engine utilized in the present invention. As shown, the interlocking cycles for the HF and $\text{NH}_4\text{F}(\text{HF})_x$ working fluids comprise transporting a hydrogen fluoride liquid working fluid 11 from a relatively low pressure zone 1 to a relatively high pressure zone 2. The higher pressure HF working fluid 12 is then heated and vaporized within the high pressure zone 2 to produce a moderate velocity, high pressure hydrogen fluoride vapor working fluid 4. The gaseous HF working fluid 4 is allowed to expand to produce a higher velocity, intermediate pressure hydrogen fluoride vapor working fluid jet 5. The HF vapor jet 5 is contacted with gaseous fluorine reactant, $\text{NH}_4\text{F}(\text{HF})_x$ melt reactant, or any mixture thereof, to form a high velocity, intermediate pressure jet 9. The mechanical energy, in the form of kinetic energy, transferred from vapor jet 9 to the reactor intimately mixes and disperses the gaseous fluorine reactant into the $\text{NH}_4\text{F}(\text{HF})_x$ melt reactant in an intermediate pressure reaction zone within the reactor. As used herein, the term “vapor jet” refers to a high velocity vapor stream, such as a vapor stream forced out of a small diameter opening or nozzle. As would be understood, kinetic energy is the energy possessed by a body because of its motion. As the HF vapor

working fluid travels through the reaction zone in the reactor, the pressure decreases as shown in Figure 1. The desired gaseous reaction product, NF_3 , and the HF vapor working fluid **23** are transported from the reaction zone and separated into a gaseous NF_3 product stream and a liquid HF working fluid stream **11** that can be recycled for reuse in the heat engine as the cycle begins anew.

Figures 2 and 3 are process flow diagrams illustrating two embodiments of the present invention. In the description of the two embodiments shown in Figures 2 and 3, reference will be made to the various working fluid states denoted in Figure 1 and discussed above. The description of the cyclic process will begin with the relatively low pressure hydrogen fluoride liquid working fluid **11** in Figures 2 and 3. Typically, the pressure of the low pressure working fluid **11** is about 15 to about 250 kPa. A pressurizing device **13** is used to increase the pressure of the hydrogen fluoride liquid working fluid from the low pressure zone **1** to the higher pressure zone **2**. The pressurizing device **13** may be a pump, such as a positive displacement pump, a heated pressure vessel, or a gas pressurized vessel. The high pressure zone **2** pressure is typically between about 250 and 1600 kPa. The preferred highest pressure (P_2) is primarily a function of the high pressure hydrogen fluoride vapor working fluid **4** temperature (T_4). Equation 1 provides a useful estimation of the preferred high pressure.

$$P_2 = 1.5 \times 10^8 e^{-4300/T_4}$$

Equation 1

wherein P_2 is the pressure of high pressure zone **2**, in kPa, and T_4 is the temperature, in °K, of the high pressure hydrogen fluoride vapor working fluid **4**.

Within the high pressure zone **2**, the high pressure hydrogen fluoride liquid working fluid **12** is heated to form high pressure vapor working fluid **4**. The vaporization may be accomplished using a heat source **19** that is external to the NF_3 reactor **20**, as shown in Figure 2. Alternatively, the energy required for vaporization can be derived from the thermal energy generated within the NF_3 reactor **20** via Reactions 3, 4, and 6. The use of thermal energy generated in the reactor **20** is illustrated in Figures 2 and 3 as heat exchanger **18**. As would be understood, the

design and size of the heat exchanger 18 will be determined by the energy required to form the vapor working fluid 4. The heat exchanger 18 may be located within the reactor 20, as shown in Figure 3, or outside of the reactor, as shown in Figure 2. As would be understood, the working fluid may be vaporized using a combination of
5 internal and external heat sources.

The NF_3 reactor 20 preferably operates substantially isothermally. The NF_3 reactor 20 can operate satisfactorily over a temperature range of about 100 to about 200°C, more preferably between about 120 and about 190°C, most preferably between about 130 and about 180°C. The primary incentive to increase the reactor
10 temperature is to increase the hydrogen fluoride vapor working fluid 4 pressure (P_2) to increase the hydrogen fluoride vapor working fluid molar thermal and pressure energy. The primary incentive to limit the reactor temperature is corrosion considerations. The NF_3 reactor heating and cooling jacket 35 is used to control the $\text{NH}_4\text{F}(\text{HF})_x$ melt 7 temperature.

15 Following vaporization, the hydrogen fluoride working fluid 4 passes through a high pressure nozzle 16, which converts a substantial portion of the pressure and thermal energy of the hydrogen fluoride vapor working fluid 4 into a high velocity hydrogen fluoride working fluid vapor jet 5. As used herein, the term “nozzle” refers to any device comprising an orifice capable of producing a vapor jet as a working
20 fluid vapor passes therethrough. As would be understood, standard design procedures can be used to design the high pressure nozzle 16 (See Robert Perry and Cecil Chilton (editors), Chemical Engineers’ Handbook, Fifth Edition, McGraw Hill Book (New York), page 5-29). The hydrogen fluoride working fluid vapor jet 5 can be initially contacted with either the $\text{NH}_4\text{F}(\text{HF})_x$ melt reactant 7 as shown in Figure 2 or the
25 gaseous fluorine reactant 6 as shown in Figure 3. Alternatively, one could simultaneously contact the hydrogen fluoride working fluid vapor jet 5 simultaneously with the gaseous fluorine reactant 6 and the $\text{NH}_4\text{F}(\text{HF})_x$ melt reactant 7. Optionally, an intermediate pressure nozzle 17 further defines the vapor jet downstream of the high pressure nozzle 16. The feed point of the fluorine feed stream

6 is preferably located proximate to the high pressure nozzle 16 or the intermediate pressure nozzle 17.

The molar ratio of the hydrogen fluoride working fluid vapor jet 5 to the gaseous fluorine reactant 6 is preferably greater than about 1:1, more preferably greater than about 3:1, most preferably greater than about 5:1. The molar ratio of the $\text{NH}_4\text{F}(\text{HF})_x$ melt reactant 7 to the gaseous fluorine reactant 6 is preferably greater than about 2,000:1, more preferably greater than about 5,000:1, most preferably greater than about 10,000:1 in order to adequately contact the gaseous fluorine reactant 6 and the $\text{NH}_4\text{F}(\text{HF})_x$ melt reactant 7 and maintain an essentially constant $\text{NH}_4\text{F}(\text{HF})_x$ melt acidity x value and temperature. The gaseous fluorine reactant stream 6 may contain other gaseous components in addition to elemental fluorine. For example, hydrogen fluoride may be periodically added to the fluorine feed stream 6 in order to remove blockages that may develop in the feed line.

The $\text{NH}_4\text{F}(\text{HF})_x$ melt reactant 7 $\text{NH}_4\text{F}(\text{HF})_x$ melt acidity x value is preferably between about 1.2 and about 2.4, more preferably between about 1.4 and about 2.2, and most preferably between about 1.6 and about 2.0. The $\text{NH}_4\text{F}(\text{HF})_x$ melt reactant 7 temperature is preferably between about 100 and about 200°C, more preferably between about 120 and about 190°C, and most preferably between about 130 and about 180°C. The $\text{NH}_4\text{F}(\text{HF})_x$ melt reactant 7 pressure is preferably between about 50 and about 400 kPa, more preferably between about 75 and about 200 kPa, and most preferably between about 100 and about 200 kPa.

After passing through the high pressure nozzle 16, and optionally the intermediate pressure nozzle 17, and contacting one or more of the NF_3 reactants, a vapor jet 9 is formed. The vapor jet 9 enters an intense mixing zone 22 downstream of the high pressure nozzle 16. Mechanical energy transferred from the high velocity vapor jet 9 creates a turbulent mixing zone 22, resulting in intimate mixing of the gaseous fluorine 6 and the liquid ammonium acid fluoride 7. A fine dispersion of the gaseous fluorine reactant 6 within the $\text{NH}_4\text{F}(\text{HF})_x$ melt reactant 7 is formed. The hydrogen fluoride vapor working fluid and the intimate mixture of fluorine and ammonium acid fluoride flow into a reaction zone 10 in fluid communication with the

mixing zone **22**. The reaction zone **10** should provide sufficient residence time between the mixing zone **22** and the NF_3 reactor vapor-liquid interface **23** for the small dispersed gaseous fluorine reactant bubbles to react with the $\text{NH}_4\text{F}(\text{HF})_x$ melt reactant to produce nitrogen trifluoride. Although not shown, modest mechanical
 5 power inputs from a stirrer or turbine could be used to supplement the mixing intensity provided by the working fluid vapor jet **9**.

The flow regime in the reaction zone **10** may be up-flow as illustrated in Figure 2 or down-flow and then up-flow as illustrated on Figure 3. Sufficient residence time for intimate contact of the two reactants should be provided in the
 10 reaction zone in order to substantially complete F_2 -to- NF_3 conversion. The space time or residence time in the reaction zone **10** is preferably greater than 0.5 seconds, more preferably greater than 2 seconds, most preferably greater than 3 seconds. Space time is the ratio of the reaction zone **10** volume to the sum of the volumetric flow rates of the gaseous fluorine reactant **6** and the $\text{NH}_4\text{F}(\text{HF})_x$ melt reactant **7**. The
 15 distance between the high pressure nozzle **16** and the vapor-liquid interface **23** is preferably greater than about 0.5 meters, more preferably greater than about 2 meters, and most preferably greater than about 3 meters.

Equation 2 provides general guidance on the relationship between the $\text{NH}_4\text{F}(\text{HF})_x$, liquid temperature (t , °C), $\text{NH}_4\text{F}(\text{HF})_x$ melt acidity x value, and the HF
 20 partial pressure (P , kPa) (See D. Filliaudeau & G Picard, "Temperature dependence of the vapor pressure and electrochemical windows of the NH_4FH_2 -HF mixtures," *Material Science Forum. Vol. 73-75*, p.669-676 (1991)).

$$P = \left[\frac{101.325}{760} \right] 10^{\frac{\left[\frac{x-1}{x} \right] - 0.5559 + 6.642 \times 10^{-3} t}{0.1620 + 1.147 \times 10^{-3} t}}$$

Equation 2

25 The HF partial pressure at the NF_3 reactor vapor-liquid interface **23** is preferably between about 5 and about 240 kPa, more preferably between about 10 and about 170 kPa, and most preferably between about 20 and about 115 kPa. Flow communication is established between the NF_3 reactor vapor-liquid interface **23** and

the high pressure nozzle 16 or intermediate pressure nozzle 17 for the $\text{NH}_4\text{F}(\text{HF})_x$ melt reactant 7 using the walls of the NF_3 reactor partition 25 as shown in Figure 3, or between the wall of the NF_3 reactor partition 25 and the NF_3 reactor 20 wall as shown in Figure 2, or using an external $\text{NH}_4\text{F}(\text{HF})_x$ reactant recycle line 26 as shown in Figure 2.

An NH_3 feed 30 is advantageously added to the vapor space above the NF_3 reactor vapor-liquid interface 23 or to the recycle $\text{NH}_4\text{F}(\text{HF})_x$ melt reactant 7 between the NF_3 reactor vapor-liquid interface 23 and the high pressure nozzle 16 or the intermediate pressure nozzle 17. The ammonia feed rate is set to maintain the desired ammonium acid fluoride 7 inventory in the reactor 20. One could alternatively replace the ammonia feed line 30 with an ammonium acid fluoride feed line to maintain the desired ammonium acid fluoride inventory in the reactor 20.

The NF_3 reactor 20 produces a liquid $\text{NH}_4\text{F}(\text{HF})_x$ by-product 29 stream and a NF_3 reactor vapor product 27. The primary function of the $\text{NH}_4\text{F}(\text{HF})_x$ by-product 29 stream is to control the $\text{NH}_4\text{F}(\text{HF})_x$ melt reactant metals content, i.e., the $\text{NH}_4\text{M}_y\text{F}_z(\text{HF})_x$ y value. Nickel is generally the most problematic metallic impurity. The nickel content is preferably keep less than about 2 wt. % of the $\text{NH}_4\text{M}_y\text{F}_z(\text{HF})_x$ melt, more preferably less than about 1 wt. % of the $\text{NH}_4\text{M}_y\text{F}_z(\text{HF})_x$ melt, most preferably less than about 0.6 wt. %.

The NF_3 reactor vapor product 27, which comprises NF_3 and the HF vapor working fluid, is advantageously treated in a conventional demister 31 that is equipped with impingement baffles 32 that coalesce the entrained $\text{NH}_4\text{F}(\text{HF})_x$, so that it can be recycled to the NF_3 reactor 20 via the NF_3 reactor vapor product 27 line. The substantially $\text{NH}_4\text{F}(\text{HF})_x$ -free NF_3 reactor vapor product 33 is treated by the HF recovery unit 34 to produce low pressure hydrogen fluoride liquid working fluid 11, the HF by-product stream 24 and a substantially HF-free crude NF_3 product 15. The HF recovery unit typically comprises a low temperature flash to remove most of the HF from the substantially $\text{NH}_4\text{F}(\text{HF})_x$ -free NF_3 reactor vapor product 33. The overhead product from the low temperature flash is preferably fed to a conventional sodium fluoride HF trap to remove essentially all remaining HF. An optional and

conventional crude NF_3 recycle blower 37 can be used to adjust the pressure at the NF_3 reactor vapor-liquid interface 23 and direct a crude NF_3 recycle stream 36 to the lower pressure HF stripping zone 14 of the NF_3 reactor 20 to control the flow rates of the HF by-product stream 24 and the low pressure hydrogen fluoride liquid working fluid 11, and ultimately the $\text{NH}_4\text{F}(\text{HF})_x$ melt acidity x value. A sparge ring 38 may advantageously used to distribute the crude NF_3 recycle stream 36, as shown in Figure 3.

The following example is given to illustrate the invention, but should not be considered in limitation of the invention.

10

EXAMPLE

This example uses the reactor configuration similar to the reactor configuration in Figure 3. The NF_3 reactor is constructed using a 4 meter long, 12 inch diameter schedule 40 monel pipe with flanged top and cap end bottom. Helical steam heating and water-cooling coils are attached to the outside of the reactor using heat transfer cement. The NF_3 reactor partition is a concentric 3.3 meter long schedule 10 monel pipe with 20 centimeter clearance between the bottom of the NF_3 reactor wall and the bottom of the NF_3 reactor partition wall. The reactor is fitted with a seal leg overflow for the $\text{NH}_4\text{F}(\text{HF})_x$, by-product stream at 0.5 meters below the top flange. A nitrogen stripping gas distribution ring is placed 3 meters from the top flange center in the annulus roughly equally spaced between the NF_3 reactor wall and the NF_3 reactor partition. The primary function of the nitrogen stripping gas is to establish uniform temperatures and reasonable $\text{NH}_4\text{F}(\text{HF})_x$, circulation rates.

A pressure vessel with the head space pressurized with nitrogen is used to provide the high pressure liquid hydrogen fluoride feed. A 0.5 inch monel pipe, along the NF_3 reactor partition axis, packed with monel gauze is used to vaporize the HF feed to a 2 mm high pressure nozzle. The $\text{NH}_4\text{F}(\text{HF})_x$ melt acidity x value is controlled by feeding gaseous ammonia into the $\text{NH}_4\text{F}(\text{HF})_x$ melt. Fluorine is fed into a one-centimeter diameter, 3-centimeter long cavity between the highest pressure nozzle with a 5 mm intermediate pressure nozzle. The intermediate pressure nozzle

outlet is positioned about 3.5 meters from the top flange, along the axis of the NF_3 reactor partition. First, the NF_3 reactor is heated to the desired temperature with a stripping nitrogen rate equivalent to the fluorine feed rate. Then, the HF tank is pressurized to the desired pressure and ammonia is fed to maintain the desired $\text{NH}_4\text{F}(\text{HF})_x$ melt acidity x value. Finally, the fluorine feed is progressively increased with equivalent molar decrease in the stripping nitrogen feed rate. With a fluorine feed rate of sixty grams per minute, no stripping nitrogen feed rate, 5 bar HF feed pressure, 150°C , and 1.8 $\text{NH}_4\text{F}(\text{HF})_x$ melt acidity x value, the crude NF_3 product contains about 76 vol.% NF_3 , 9 vol.% N_2 , and 14 vol.% fluorine on an HF-free basis, which is equivalent to a c_1 value of about 0.85.

Many modifications and other embodiments of the invention will come to mind to one skilled in the art to which this invention pertains having the benefit of the teachings presented in the foregoing descriptions and the associated drawings. Therefore, it is to be understood that the invention is not to be limited to the specific embodiments disclosed and that modifications and other embodiments are intended to be included within the scope of the appended claims. Although specific terms are employed herein, they are used in a generic and descriptive sense only and not for purposes of limitation.

THAT WHICH IS CLAIMED:

1. A method of producing nitrogen trifluoride, comprising:
providing a reactor comprising a mixing zone and a reaction zone in
5 fluid communication with the mixing zone;
feeding gaseous fluorine into the mixing zone of the reactor;
feeding liquid ammonium acid fluoride into the mixing zone of the
reactor;
feeding a working fluid vapor jet into the mixing zone of the reactor,
10 wherein the working fluid vapor jet transfers kinetic energy into the mixing zone, the
kinetic energy dispersing the gaseous fluorine within the liquid ammonium acid
fluoride;
reacting the liquid ammonium acid fluoride with the fluorine dispersed
therein to produce nitrogen trifluoride as the liquid ammonium acid fluoride and
15 fluorine pass through the reaction zone in the reactor; and
removing a gaseous reaction product stream from the reactor, the
reaction product stream comprising nitrogen trifluoride and the working fluid vapor.
2. The method of Claim 1, wherein the working fluid is a hydrogen
halide.
3. The method of Claim 1, wherein the working fluid is a hydrogen
fluoride.
4. The method of Claim 1, wherein the ammonium acid fluoride has an
acid-base stoichiometry of $\text{NH}_4\text{M}_y\text{F}_z(\text{HF})_x$, wherein M is a metal selected from the
group consisting of Group IA through VA, Group IB through VIIB and Group VIII of
the Periodic Table of Elements or mixtures thereof; y is 0-12; z is 1-12; and x is the
5 melt acidity value.

5. The method of Claim 1, wherein the ammonium acid fluoride has an acid-base stoichiometry of $\text{NH}_4\text{F}(\text{HF})_x$, wherein x is the melt acidity value.
6. The method of Claim 5, wherein the melt acidity value of the liquid ammonium acid fluoride is about 1.2 to about 2.4.
7. The method of Claim 6, wherein the melt acidity value of the liquid ammonium acid fluoride is about 1.4 to about 2.2.
8. The method of Claim 1, wherein the liquid ammonium acid fluoride has a temperature of about 100 to about 200°C.
9. The method of Claim 8, wherein the liquid ammonium acid fluoride has a temperature of about 130 to about 180°C.
10. The method of Claim 1, wherein the liquid ammonium acid fluoride has a pressure of about 50 to about 400 kPa.
11. The method of Claim 10, wherein the liquid ammonium acid fluoride has a pressure of about 100 to about 200 kPa.
12. The method of Claim 1, wherein the ratio of the reaction zone volume to the sum of the volumetric flow rates of the gaseous fluorine and the liquid ammonium acid fluoride is at least about 0.5 seconds.
13. The method of Claim 12, wherein the ratio of the reaction zone volume to the sum of the volumetric flow rates of the gaseous fluorine and the liquid ammonium acid fluoride is at least about 2.0 seconds.
14. The method of Claim 1, wherein the molar ratio of the working fluid vapor jet to the gaseous fluorine is greater than about 1:1.

15. The method of Claim 14, wherein the molar ratio of the working fluid vapor jet to the gaseous fluorine is greater than about 5:1.

16. The method of Claim 1, wherein the molar ratio of the liquid ammonium acid fluoride to the gaseous fluorine is greater than about 2,000:1.

17. The method of Claim 16, wherein the molar ratio of the liquid ammonium acid fluoride to the gaseous fluorine is greater than about 10,000:1.

18. The method of Claim 1, further comprising separating the gaseous reaction product stream into a gaseous nitrogen trifluoride product stream and a liquid working fluid stream.

19. The method of Claim 18, further comprising:

pressurizing the liquid working fluid stream to a pressure of about 250 to about 1600 kPa;

5 vaporizing the pressurized liquid working fluid stream to form a working fluid vapor; and

feeding the working fluid vapor through a nozzle to form the working fluid vapor jet.

20. The method of Claim 19, wherein said vaporizing step comprises heating the pressurized liquid working fluid stream with the heat of reaction generated in the reaction zone of the reactor.

21. A method of producing nitrogen trifluoride, comprising:

providing a reactor comprising a mixing zone and a reaction zone in fluid communication with the mixing zone;

feeding gaseous fluorine into the mixing zone of the reactor;

5 feeding liquid ammonium acid fluoride into the mixing zone of the reactor, the ammonium acid fluoride has an acid-base stoichiometry of $\text{NH}_4\text{F}(\text{HF})_x$,

wherein x is the melt acidity value, the melt acidity value being about 1.2 to about 2.4;

feeding a hydrogen fluoride vapor jet into the mixing zone of the reactor, wherein the working fluid vapor jet transfers kinetic energy into the mixing zone, the kinetic energy dispersing the gaseous fluorine within the liquid ammonium acid fluoride;

reacting the liquid ammonium acid fluoride with the fluorine dispersed therein to produce nitrogen trifluoride as the liquid ammonium acid fluoride and fluorine pass through the reaction zone in the reactor; and

removing a gaseous reaction product stream from the reactor, the reaction product stream comprising nitrogen trifluoride and the hydrogen fluoride vapor,

wherein the molar ratio of the hydrogen fluoride vapor jet to the gaseous fluorine is greater than about 3:1 and the molar ratio of the liquid ammonium acid fluoride to the gaseous fluorine is greater than about 5,000:1.

22. The method of Claim 21, further comprising separating the gaseous reaction product stream into a gaseous nitrogen trifluoride product stream and a liquid hydrogen fluoride stream.

23. The method of Claim 22, further comprising:
 pressurizing the liquid hydrogen fluoride stream to a pressure of about 250 to about 1600 kPa;
 vaporizing the pressurized liquid hydrogen fluoride stream to form a hydrogen fluoride vapor; and
 feeding the hydrogen fluoride vapor through a nozzle to form the hydrogen fluoride vapor jet.

24. The method of Claim 23, wherein said vaporizing step comprises heating the pressurized liquid hydrogen fluoride stream with the heat of reaction generated in the reaction zone of the reactor.

25. An apparatus for producing nitrogen trifluoride, comprising:

a reactor comprising a mixing zone, a reaction zone in fluid communication with said mixing zone, and a product outlet;

a gaseous fluorine feed supply in fluid connection with said mixing zone of said reactor;

5 a liquid ammonium acid fluoride feed supply in fluid connection with said mixing zone of said reactor;

a working fluid vapor supply in fluid connection with said mixing zone of said reactor; and

10 at least one nozzle operatively positioned in fluid connection with said working fluid vapor supply upstream of said mixing zone of said reactor.

26. The apparatus of Claim 25, wherein said working fluid vapor supply is a hydrogen halide vapor supply.

27. The apparatus of Claim 26, wherein said working fluid vapor supply is a hydrogen fluoride vapor supply.

28. The apparatus of Claim 25, further comprising a separator in fluid communication with said product outlet of said reactor and operatively positioned to separate a liquid working fluid stream from a gaseous nitrogen trifluoride stream, said separator comprising a working fluid outlet and a nitrogen trifluoride outlet.

29. The apparatus of Claim 25, wherein said working fluid vapor supply comprises:

a liquid working fluid supply; and

5 a heat exchanger having an inlet and an outlet, said inlet of said heat exchanger being in fluid communication with said liquid working fluid supply, said outlet being in fluid communication with said nozzle.

30. The apparatus of Claim 29, wherein said heat exchanger is positioned with said reactor.

31. The apparatus of Claim 25, wherein said reactor further comprises at least one internal partition defining a flow path between the mixing zone and the reaction zone within said reactor.