



159159

- 1 -

PORTABLE ELECTRONIC APPARATUS AND METHOD OF CONTROLLING
A PORTABLE ELECTRONIC APPARATUS

FIELD

Embodiments described herein relate generally to a
5 portable electronic apparatus and a method of
controlling a portable electronic apparatus.

BACKGROUND

Most IC cards used as portable electronic
apparatuses have a main body and an IC module. The
10 main body is made of plastics and shaped like a card.
The IC module is embedded in the main body and has an
IC chip. The IC chip has a nonvolatile memory, a
volatile memory, and a CPU. The nonvolatile memory
that can hold data even if it is not supplied with
15 power is, for example, an electrically erasable
programmable read-only memory (EEPROM) or a flash ROM.
The volatile memory is, for example, a RAM. The CPU
performs various operations.

The IC card is one that accords with the
20 International Standards ISO/IEC7816. The IC card has a
master file (MF), which is the basis of the file
structure and which is stored in the nonvolatile
memory. The IC card also has a dedicated file (DF),
which is a lower file with respect to the MF and is
25 used to group applications or the like. The IC card
further has an elementary file (EF), which is a lower
file with respect to the MF or the MF and is used to



G00002

hold various data items.

The International Standards ISO/IEC7816 defines a file structure for the MF, DF and EF, or tag-length value (TLV) type data (TLV data object). The TLV data object has data class (Tag), data length (Length) and data character (Value).

Tag of the TLV data object is a data item the CPU of the IC card uses to identify the class of the TLV data object. Length of the TLV data object is a data item that represents the length of Value of the TLV data object. Value is the main part of the TLV data object.

The International Standards ISO/IEC7816-4, cited herein as Non-Patent Document 1, defines various commands designating processes to be performed on the IC card. One of these commands is GET DATA command that is used to read any desired TLV data object from the file.

The GET DATA command has a data item (designation data) that designates a TLV data object. On receiving the GET DATA command, the IC card retrieves from the file the TLV data object that has a Tag identical to the designation data contained in the GET DATA command.

However, the TLV data object does not have a prescribed length. It inevitably takes much time to retrieve any data desired. If the file contains a plurality of TLV data objects coupled one to another,

the CPU of the IC card collates the designation data with the Tag stored at the head of the storage area.

If the Tag stored at the head of the storage area is not identical to the designation data is not
5 identical, the CPU moves the data pointer (reading position) by the distance represented by the Length recorded after the Tag. The CPU then collates the designation data with the Tag stored at the position to which the data pointer has been moved. The CPU repeats
10 this sequence of process until it finds Tag identical to the designation data.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a diagram explaining the processing system of a portable electronic apparatus according to
15 an embodiment;

FIG. 2 is a diagram explaining an IC card according to the embodiment;

FIG. 3 is a diagram explaining an IC card according to the embodiment;

20 FIG. 4 is a diagram explaining an IC card according to the embodiment;

FIG. 5 is a diagram explaining an IC card according to the embodiment;

25 FIG. 6 is a diagram explaining an IC card according to the embodiment;

FIG. 7 is a diagram explaining an IC card according to the embodiment; and

FIG. 8 is a diagram explaining an IC card according to the embodiment.

DETAILED DESCRIPTION

In general, according to one embodiment, a
5 portable electronic apparatus executing performing
process based on command input from an external
apparatus, and storing a plurality of TLV data objects,
the apparatus comprises; a storage unit configured to
store the data class and data character of each TLV
10 data object, respectively in two storage areas spaced
apart from each other, and to store addresses of a
fixed length, representing the positions of the data
characters, in association with the each data classes.

A portable electronic apparatus and a method of
15 controlling a portable electronic apparatus, both
according to an embodiment, will be described in
detail, with reference to the accompanying drawings.

FIG. 1 is a block diagram explaining an IC card
processing apparatus 1 according to an embodiment,
20 which can communicate with an IC card 2.

As shown in FIG. 1, the IC card processing
apparatus 1 has a main unit 11, a display 12, a
keyboard 13, and a card reader/writer 14.

The main unit 11 has a CPU, various memories, and
25 various interfaces. The main unit 11 is configured to
control the other components of the IC card processing
apparatus 1.

The display 12 can display various types of information when it is controlled by the main unit 11. When operated by the user of the IC card processing apparatus 1, the keyboard 13 generates operation signals.

The card reader/writer 14 is an interface device that can perform communication with the IC card 2. The card reader/writer 14 can achieve either contact communication or contactless communication, with the IC card 2.

If the card reader/writer 14 is designed to achieve contact communication, it has a connection unit that can be electrically connected to the contact terminal of the IC card 2. If the card reader/writer 14 is designed to achieve contactless communication, it has an antenna that can be magnetically connected to the antenna of the IC card 2. The card reader/writer 14 supplies power and a clock signal to the IC card 2, performs reset control on the IC card 2, and transmits and receives data to and from the IC card 2.

The main unit 11 inputs various commands to the IC card 2 via the card reader/writer 14. The card reader/writer 14 may supply a data write command to the IC card 2. In this case, the data supplied to the IC card 2 is written into the nonvolatile memory incorporated in the IC card 2.

The main unit 11 transmits a read command to the

IC card 2, reading data from the IC card 2. On the basis of the data received from the IC card 2, the main unit 11 performs various processes. For example, the main unit 11 transmits a GET DATA command to the IC card 1, in order to read the TLV data object stored in the nonvolatile memory of the IC card 2.

FIG. 2 is a block diagram explaining an exemplary configuration that the IC card 2 shown in FIG. 1 may have.

As shown in FIG. 2, the IC card 2 has a card-shaped main body 21 and an IC module 22 incorporated in the main body 21. The IC module 22 comprises one or more IC chips 23 and a communication unit 24. The IC chip 23 and the communication unit 24 are connected to each other in the IC module 22.

The IC chip 23 incorporates a data bus 20, a communication unit 24, a CPU 25, a ROM 26, a RAM 27, and a nonvolatile memory 28. The data bus 20 connects the communication unit 24, CPU 25, ROM 26, RAM 27 and nonvolatile memory 28, one to another.

If supplied with power from a higher device, such as IC card processing apparatus 1, the IC card 2 operates. The IC card 2 then performs either contact communication or contactless communication with the IC card processing apparatus 1.

The communication unit 24 is an interface configured to communicate with the card reader/writer

14 of the IC card processing apparatus 1.

The communication unit 24 may comprise a contact unit, which may contact the card reader/writer 14 of the IC card processing apparatus 1, to transmit and receive signals to and from the card reader/writer 14. In this case, the IC card 2 functions as a contact-type IC card.

The communication unit 24 may further comprise an antenna, which achieves wireless communication with the card reader/writer 14 of the IC card processing apparatus 1. If this is the case, the IC card 2 functions as a contactless-type IC card.

To perform contact communication with the IC card processing apparatus 1, the IC card 2 receives power and an operating clock signal from the IC card processing apparatus 1 through the contact unit. The IC card 2 is therefore activated.

To perform contactless communication with the IC card processing apparatus 1, the IC card 2 receives an electric wave from the IC card processing apparatus 1 through an antenna. In the IC card 2, power is generated from the electric wave. Hence, the IC card 2 is activated.

The CPU 25 functions as a control unit that controls the other components of the IC card 2. The CPU 25 performs various processes in accordance with the control programs and the control data that are

stored in the nonvolatile memory 28.

5 The ROM 26 is a nonvolatile memory that stores control programs, control data and the like. The ROM 26 has been incorporated into the IC chip 23, with the control programs and control data stored in it, during the manufacture of the IC card 2. That is, the ROM 26 had stored the control programs and the control data in accordance with the specification of the IC card 2, before it was incorporated into the IC card 2.

10 The RAM 27 is a volatile memory that functions as a working memory. The RAM 27 temporarily stores the data the CPU 25 is processing. For example, it stores, for example, the data received from the IC card processing apparatus 1 through the communication unit.
15 24. The RAM 27 also temporarily stores the program the CPU 25 is executing.

 The nonvolatile memory 28 is, for example, an EEPROM or a flash ROM in which data can be written or rewritten. The nonvolatile memory 28 stores control
20 programs, applications and various data items, in accordance with the use of the IC card 2. The CPU 25 executes the programs stored in the ROM 26, performing various processes.

 The nonvolatile memory 28 has a memory structure
25 composed of the MF, DF and EF that were generated at the time of issuing the IC card 2. The DF and the EF hold a program file or a data file.

Each file stored in the nonvolatile memory 28 shown in FIG. 2 has a first storage area 28a and a second storage area 28b. Each file further holds attribute data that represents the structure of the data held in the file.

The first storage area 28a holds the address (e.g., pointer) of the storage area in which at least Tag and Value of the TLV data object are stored. The second storage area 28b holds the data (i.e., data value) of Value of the TLV data object.

FIG. 3 is a diagram explaining the process the IC card 2 of FIG. 2 performs, and showing the information stored in the nonvolatile memory 28.

If the IC card 2 receives a command for writing the TLV data object, the CPU 25 of the IC card 2 writes the data value of Value in the second storage area 28b of the file.

The CPU 25 also writes Tag and Length in the first storage area 28a. Further, the CPU 25 writes the address (pointer) for specifying the position where the data value of Value has been written, at the back of Length written in the first storage area 28a.

The CPU 25 writes, as address, the head address of the data value of Value written in the second storage area 28b.

The CPU 25 may be configured to write, as address, the offset value between the position at which to write

the address and the position at which the data value of Value has been written in the second storage area 28b. Alternatively, the CPU 25 may be configured to write, as address, the offset value between the head of the file and the position at which the data value of Value has been written in the second storage area 28b.

Assume that Tag, Length and the address (pointer) have prescribed lengths (each defined as a number of bytes), respectively. Then, the CPU 25 stores Tag, Length and pointer, each defined by a number of bytes, as attribute data items, in the file that is stored in the nonvolatile memory 28.

On receiving a GET data command from the IC card processing apparatus 1, the CPU 25 of the IC card, in which the nonvolatile memory 28 now stores the information shown in FIG. 3, retrieves the TLV data object designated by the GET DATA command. The GET DATA command may designate "A5." In this case, the CPU 25 retrieves Tag identical to "A5" from the first storage area 28a.

In response to the GET DATA command, the CPU 25 reads data of a prescribed length, from the head of the file. That is, the CPU 25 reads Tag 1 having the prescribed length and stored in the file, from the head thereof.

The CPU 25 collates the value of Tag 1 with the value of designation data. As shown in FIG. 3, Tag 1

has value of "88," whereas the designation data has value of "A5." The CPU 25 therefore determines that the value of Tag 1 differs from that of the designation data. In this case, the CPU 25 moves the data pointer (i.e., reading position) by the distance equivalent to a specific number of bytes. More precisely, the CPU 25 moves the pointer forwards, by Length 1 contained in the attribute data and the number of bytes for the pointer. Thus, the CPU 25 can easily specify the position where Tag 2 is stored next to Tag 1.

The CPU 25 reads data of a prescribed length from the position the data pointer specifies. That is, the CPU 25 reads Tag 2 stored and extending from the data pointer for a prescribed distance. The CPU 25 collates the value of Tag 2 thus read, with the value of the designation data. As shown in FIG. 3, the value of Tag 2 is "50," and that of the designation data is "A5." Hence, the CPU 25 determines that Tag 2 differs from the designation data in terms of value. In this case, the CPU 25 move the data pointer (reading position) forwards, by Length 2 and the number of bytes for the pointer.

The CPU 25 reads the data of the prescribed length from the position the data pointer represents. To be more specific, the CPU 25 reads Tag 3 stored and extending from the data pointer for a prescribed distance. The CPU 25 collates the value of Tag 3 thus

read, with the value of the designation data. As shown in FIG. 3, the value of Tag 3 is "A3," and that of the designation data is "A5." Hence, the CPU 25 determines that Tag 3 is identical to the designation data in terms of value.

In this case, the CPU 25 reads the value of Length 3 stored at the back of Tag 3. The CPU 26 also reads the value of pointer 3 stored at the back of Length 3. In accordance with the value of the pointer 3, the CPU 25 moves the data pointer. The CPU 25 reads data (Value 3) composed of that number of bytes, which Length 3 represents.

The CPU 25 generates response data from the value of Value thus read. The CPU 25 then transmits the response data to the card reader/writer 14 through the communication unit 24.

FIG. 4 is a flowchart explaining how the TLV data object is read in the IC card 2 of FIG. 2.

On receiving a GET DATA command from an external apparatus, the CPU 25 of the IC card 2 reads Tag stored and extending for a prescribed distance from the head of the file (Step S11).

The CPU 25 collates the value of Tag, thus read, with the value of the designation data contained in the GET DATA command (Step S12). Then, the CPU 25 determines whether the value of Tag is equal to the value of the designation data (Step S13).

If the value of Tag differs from that of the designation data (NO in Step S13), the CPU 25 moves the reading position forward, by a distance equivalent to a prescribed number of bytes (Step S14). The CPU 25 then
5 return to Step S11. Note that the CPU 25 moves the data pointer by the distance equivalent to the sum of the bytes defining Length contained in file attribute data and the bytes defining the pointer. The CPU 25 repeats the sequence of Steps S11 to S14 until Tag
10 identical to the designation data is retrieved.

If the value of Tag is equal to that of the designation data (YES in Step S13), the CPU 25 reads Length stored immediately after Tag (Step S15). Further, the CPU 25 reads the pointer stored
15 immediately after Length (Step S16).

The CPU 25 moves the data pointer in accordance with the value of the pointer. Then, the CPU 25 reads Value from the position the data pointer specifies (Step S17). That is, the CPU 25 reads the data defined
20 by the bytes, the number of which is equivalent to Length read, from the position the data pointer specifies.

The CPU 25 generates response data from the value of Value thus read. The CPU 25 then transmits the
25 response data to the card reader/writer 14 through the communication unit 24 (Step S18).

In the IC card 2 according to this embodiment, the

CPU 25 stores, in the first storage area 28a, the address representing the position where Tag, Length and Value are stored. The CPU 25 further stores the data representing Value in the second storage area 28b.

5 Hence, Tag, Length, and the address, all stored in the first storage area 28a, can have prescribed lengths, respectively.

Therefore, the CPU 25 can automatically determine the position at which Tag is stored in the first
10 storage area 28a. More precisely, the CPU 25 can specify the position where Tag is stored, without reading the value of Length, in order to retrieve Tag in accordance with the data the command designates.

The CPU 25 can therefore shorten the time required
15 for retrieving the TLV data objects. As a result, a portable electronic apparatus and a method of controlling the portable electronic apparatus can be provided, in which processes can be efficiently performed in response to commands.

20 Value may contain a plurality of TLV data objects. If this is the case, the nonvolatile memory 28 stores such information as shown in FIG. 5.

FIG. 5 is a diagram explaining another process performed in the IC card 2 of FIG. 2.

25 The IC card 2 may receive a command for writing a TLV data object (higher TLV object) having Value that contains a plurality of TLV data objects (lower TLV

data objects). In this case, the CPU 25 of the IC card
2 writes such data as shown in FIG. 5.

More precisely, the CPU 25 writes the data values
of Value of the lower TLV data objects in the second
5 storage area 28b.

The CPU 25 further writes Tag and Length of the
higher TLV data object in the first storage area 28a.

Moreover, the CPU 25 replaces Value of the lower
TLV data object with the address specifying the
10 position at which the data value of Value has been
written. The CPU 25 then writes the lower TLV data
object, Value of which has been so replaced, at the
position of Value of the higher TLV data object.

Assume that Tag, Length and address of the TLV
15 data object stored in the first storage area 28a have
fixed lengths, respectively. The number of bytes
constituting Tag, the number of bytes constituting
Length, and the number of bytes constituting the
pointer are stored, as attribute data, in the file held
20 in the nonvolatile memory 28. The data showing that
Value of the higher TLV data object has lower TLV data
objects is also stored, as attribute data, in the
nonvolatile memory 28.

To select a file, the CPU 25 confirms the
25 attribute data held in the file. The CPU 25 can
therefore recognize that Value of the higher TLV data
object has lower TLV data objects.

Further, the CPU 25 examines the attribute data, determining the lengths of Tag, Length and address. That is, the CPU 25 confirms the data length of each lower TLV data object. When the CPU 25 confirms Length
5 of the higher TLV data object, it can recognize how many lower TLV objects are contained in the higher TLV data object.

The CPU 25 of the IC card 2 in which the nonvolatile memory 28 stores the data shown in FIG. 5
10 may receive, from the IC card processing apparatus 1, a GET DATA command designating "A5." In this case, the CPU 25 retrieves TLV data object whose Tag value is "A5."

That is, the CPU 25 reads Tag 1 from the head of
15 the file. Then, the CPU 25 collates the value of Tag 1 with the value of the designation data. As shown in FIG. 5, Tag 1 has value "70," and the designation data has value "A5." Therefore, the CPU 25 determines that the value of Tag 1 is not equal to that of the
20 designation data.

The CPU 25 therefore moves the data pointer to the next tag, i.e., Tag 2. That is, the CPU 25 does not read Length 1, on the basis of the length of Length previously recognized.

25 The CPU 25 then reads Tag 2. The CPU 25 collates the value of Tag 2 with the value of the designation data. As shown in FIG. 5, Tag 2 has value "88," and

the designation data has value "A5." The CPU 5 therefore determines that the value of Tag 2 is not equal to that of the designation data.

5 In this case, the CPU 25 moves the data pointer to the next tag, i.e., Tag 3. That is, the CPU 25 does not read Length 1 or Length 2, on the basis of the length of Length or pointer 2, both previously recognized.

10 Next, the CPU 25 reads Tag 3. The CPU 25 collates the value of Tag 3 with the value of the designation data. As shown in FIG. 5, Tag 3 has value "50," and the designation data has value "A5." The CPU 5 therefore determines that the value of Tag 3 is not equal to that of the designation data.

15 The CPU 25 therefore moves the data pointer to the next tag, i.e., Tag 4. That is, the CPU 25 does not read Length 3 or pointer 3, on the basis of the length of Length and the length of the address, both previously recognized.

20 Further, the CPU 25 reads Tag 4. The CPU 25 collates Tag 4 with the value of the designation data. As shown in FIG. 5, Tag 5 has value "A5," and the designation data has value "A5." The CPU 5 therefore determines that the value of Tag 3 is equal to that of
25 the designation data.

In this case, the CPU 25 reads the value of Length 4 stored at the back Tag 4. The CPU 25 also reads the

value of pointer 4 stored at the back of Length 4. The CPU 25 moves the data pointer on the basis of the value of pointer 4. Then, the CPU 25 reads data (Value 4) defined by the number of bytes, indicated by Length 4, from the position the data pointer indicates.

The CPU 25 generates response data from the value of Value thus read. The CPU 25 transmits the response data to the card reader/writer 14 through the communication unit 24.

As stated above, this embodiment can be practiced even if Value of the higher TLV data object contains a plurality of lower TLV objects. In addition, the CPU 25 can shorten the time required for retrieving TLV data objects. As a result, a portable electronic apparatus and a method of controlling the portable electronic apparatus can be provided, in which processes can be efficiently performed in response to commands.

The TLV data objects stored in the file may differ in the data length of Length. In this case, the nonvolatile memory 28 stores such data as shown in FIG. 6.

FIG. 6 is a diagram explaining still another process performed in the IC card 2 of FIG. 2. If the TLV data objects to be written in the file differ in the length of Length, the CPU 25 of the IC card 2 writes such data as shown in FIG. 6.

If the IC card 2 receives a command for writing a TLV data object, the CPU 25 writes Length and Value of the TLV data object in the second storage area 28b. In this case, Value is written immediately after Length.

5 Further, the CPU 25 writes Tag of the TLV data object in the first storage area 28a. Moreover, the CPU 25 writes address for specifying the position where Length and Value of the TLV data object have been written, in first storage area 28a and immediately
10 after Tag.

Assume that Tag and length of address of the TLV data object stored in the first storage area 28a have fixed lengths, respectively. The number of bytes constituting Tag and the number of bytes constituting
15 the pointer are stored, as attribute data, in the file held in the nonvolatile memory 28. Further, the data showing that the file hold a TLV data object having an unfixed length is also stored, as attribute data, in the nonvolatile memory 28.

20 To select a file, the CPU 25 confirms the attribute data held in the file. The CPU 25 can therefore recognize that the file holds a TLV data object having an unfixed length. Further, the CPU 25 examines the attribute data, determining the lengths of
25 Tag and address.

The CPU 25 of the IC card 2 in which the nonvolatile memory 28 stores the data shown in FIG. 6

may receive, from the IC card processing apparatus 1, a GET DATA command designating "A5." In this case, the CPU 25 retrieves TLV data object whose Tag value is "A5."

5 The CPU 25 reads Tag 1 from the head of the file. Then, the CPU 25 collates the value of Tag 1 with the value of the designation data. As shown in FIG. 6, Tag 1 has value "88," and the designation data has value "A5." Therefore, the CPU 25 determines that the value
10 of Tag 1 is not equal to that of the designation data.

 The CPU 25 therefore moves the data pointer to the next tag, i.e., Tag 2. That is, the CPU 25 does not read Length 1, on the basis of the length of Length previously recognized.

15 The CPU 25 then reads Tag 2. The CPU 25 collates the value of Tag 2 with the value of the designation data. As shown in FIG. 6, Tag 2 has value "50," and the designation data has value "A5." The CPU 5 therefore determines that the value of Tag 2 is not
20 equal to that of the designation data.

 In this case, the CPU 25 moves the data pointer to the next tag, i.e., Tag 3. That is, the CPU 25 does not read pointer 2 stored immediately after Tag 2, on the basis of the length of the address, which has been
25 previously recognized.

 Next, the CPU 25 reads Tag 3. The CPU 25 collates the value of Tag 3 with the value of the designation

data. As shown in FIG. 6, Tag 3 has value "A5," and the designation data has value "A5." The CPU 5 therefore determines that the value of Tag 3 is equal to that of the designation data.

5 In this case, the CPU 25 reads the value of pointer 3 stored at the back Tag 3. The CPU 25 moves the data pointer on the basis of the value of pointer 3. Then, the CPU 25 reads data (Value 3) defined by the number of bytes, indicated by Length 3, from the
10 position the data pointer indicates.

 The CPU 25 generates response data from the value of Value thus read. The CPU 25 transmits the response data to the card reader/writer 14 through the communication unit 24.

15 As described above, the CPU 25 of the IC card 2 according to this embodiment stores Tag and the address in the first storage area 28a, and stores Length and Value in the second storage area 28b. Tag and the address, both stored in the first storage area 28a, can
20 therefore have prescribed lengths, respectively.

 The CPU 25 can therefore automatically determine the position at which Tag is stored in the first storage area 28a. That is, the CPU 25 can easily specify the position where Tag is stored, in order to
25 retrieve Tag in accordance with the data the command designates.

 Therefore, the CPU 25 can shorten the time

required for retrieving TLV data objects. As a result,
a portable electronic apparatus and a method of
controlling the portable electronic apparatus can be
provided, in which processes can be efficiently
5 performed in response to commands.

Tag of any TLV data object stored in the file may
not have a fixed length. In this case, the nonvolatile
memory 28 stores such data as shown in FIG. 7.

FIG. 7 is a diagram explaining another process
10 performed in the IC card 2 of FIG. 2.

If the TLV data objects to be written in the file
differ in the length of Tag, the CPU 25 of the IC card
2 writes such data as shown in FIG. 7.

If the IC card 2 receives a command for writing a
15 TLV data object, the CPU 25 writes Length and Value of
the TLV data object in the second storage area 28b. In
this case, the CPU 25 writes Value immediately after
Value.

Further, the CPU 25 writes Tag of the TLV data
20 object in the first storage area 28a. Moreover, the
CPU 25 writes address for specifying the position where
Length and Value of the TLV data object have been
written, in first storage area 28a and immediately
after Tag.

25 In this case, the CPU 25 adjusts the length of Tag
to be written in the first storage area 28a, to the
length of the longest Tag. Assume that three TLV data

objects have Tag "9F 38," Tag "9F 27" and Tag "A5," respectively, as shown in FIG. 7. Then, the CPU 25 sets the length of Tag to two bytes, in order to write these TLV data objects in first storage area 28a.

5 Then, the CPU 25 performs a write process, writing Tag "A5" of the TLV data object having a 2-byte Tag length, as "A5 (NULL)." That is, the CPU 25 first adds a blank (NULL) to Tag shorter than a prescribed length, and then writes the tag. The CPU 25 thus adjusts the
10 length of Tag to be written in the first storage area 28a, to the prescribed length.

 It is here assumed that the address stored in the first storage area 28a has the prescribed length. The CPU 25 stores the lengths of Tag and pointer, as
15 attribute data, in the file held in the nonvolatile memory 28.

 To select a file, the CPU 25 confirms the attribute data held in the file. The CPU 25 can therefore recognize the lengths of Tag and address,
20 both held in the file.

 The CPU 25 of the IC card 2 in which the nonvolatile memory 28 stores the data shown in FIG. 7 may receive, from the IC card processing apparatus 1, a GET DATA command designating "A5." In this case, the
25 CPU 25 retrieves TLV data object whose Tag value is "A5."

 The CPU 25 reads Tag 1 from the head of the file.

Then, the CPU 25 collates the value of Tag 1 with the value of the designation data. As shown in FIG. 7, Tag 1 has value "9F 38," and the designation data has value "A5." Therefore, the CPU 25 determines that the value of Tag 1 is not equal to that of the designation data.

The CPU 25 therefore moves the data pointer to the next tag, i.e., Tag 2. That is, the CPU 25 does not read pointer 1 existing immediately after Tag 1, on the basis of the length of the address recognized.

The CPU 25 then reads Tag 2. The CPU 25 collates the value of Tag 2 with the value of the designation data. As shown in FIG. 7, Tag 2 has value "9F 27," and the designation data has value "A5." The CPU 5 therefore determines that the value of Tag 2 is not equal to that of the designation data.

In this case, the CPU 25 moves the data pointer to the next tag, i.e., Tag 3. That is, the CPU 25 does not read pointer 2 stored immediately after Tag 2, on the basis of the length of the address, which has been previously recognized.

Next, the CPU 25 reads Tag 3. The CPU 25 collates the value of Tag 3 with the value of the designation data. As shown in FIG. 7, Tag 3 has value "A5," and the designation data has value "A5." The CPU 5 therefore determines that the value of Tag 3 is equal to that of the designation data.

In this case, the CPU 25 reads the value of

pointer 3 stored at the back Tag 3. The CPU 25 moves the data pointer on the basis of the value of pointer 3. Then, the CPU 25 reads Length 3 from the position the data pointer indicates. Further, the CPU 25 reads data (Value 3) defined by the number of bytes, indicated by Length 3.

The CPU 25 generates response data from the value of Value thus read. The CPU 25 transmits the response data to the card reader/writer 14 through the communication unit 24.

As described above, the CPU 25 of the IC card 2 according to this embodiment performs a write process, adjusting the length of Tag to be written in the first storage area 28a, to the length of the longest Tag. Tag can therefore be written in units of a specific number of bytes, even if the TLV data objects to be written in the first storage area 28a differ in the length of Tag.

The CPU 25 can therefore automatically determine the position at which Tag is stored in the first storage area 28a. That is, the CPU 25 can easily specify the position where Tag is stored, in order to retrieve Tag in accordance with the data the command designates.

Therefore, the CPU 25 can shorten the time required for retrieving TLV data objects. As a result, a portable electronic apparatus and a method of controlling the portable electronic apparatus can be

provided, in which processes can be efficiently performed in response to commands.

Assume conventional TLV data objects are held in the file stored in the nonvolatile memory 28. Then, Tag of one TLV data object is stored immediately after Value of the preceding TLV data object. This makes the problem that any data to be updated cannot be stored if it is longer than Value already stored.

In this embodiment, the storage area for holding Tag and Length is spaced from the storage area for holding Value. Value can therefore be updated to longer data.

FIG. 8 is a diagram explaining how data is updated in the IC card of FIG. 2.

The IC card 2 may receive an update command for updating a designated TLV data object of a file stored in the nonvolatile memory 28. In this case, the CPU 25 of the IC card 2 first specifies the designated file. More precisely, the CPU 25 retrieves, from the nonvolatile memory 28, the TLV data object having Tag identical to the designation data contained in the update command.

If the designation data contained in the update command is "50," the CPU 25 retrieves Tag of the value equal to "50" from the first storage area 28a. In this case, the CPU 25 retrieves Tag identical to the designation data, performing the process explained with

reference to FIG. 3. The CPU 25 can therefore determine that the designation data is identical to Tag 2 shown in FIG. 8.

5 In this case, the CPU 25 reads Length 2 stored at the back of Tag 2. The CPU 25 then compares the value of Length of the TLV data object to update, with the value of Length 2. If the value of Length of the TLV data object to update is greater than the value of Length 2, the CPU 25 deletes Value 2 in the second
10 storage area 28b.

That is, the CPU 25 reads the value of pointer 2 stored right after Length 2. On the basis of the value of pointer 2, the CPU 25 moves the data pointer. The CPU 25 then deletes data (i.e., Value 2) composed of a
15 number of bytes, equivalent to Length 2, from the position the data pointer indicates.

The CPU 25 further moves the data pointer to another address in the second storage area 28b. The CPU 25 writes Value of the TLV data object to update
20 (i.e., Value 2') from the position of the data pointer.

The CPU 25 then rewrites the value "04" of Length 2 stored in the first storage area 28a to the value "05" of Length 2' of the TLV data object to update. Further, the CPU 25 rewrites the value of pointer 2
25 stored in the first storage area 28a, to the value of pointer 2' indicating the position at which Value 2' is stored.

In order to update Value already stored, to Value of a longer data length as described above, the CPU 25 of the IC card 2 according to this embodiment discards the storage area in which Value is stored. Moreover, the CPU 25 writes new Value in another part of the second storage area 28b. In accordance with new Value so written, the CPU 25 rewrites Length and pointer, both stored in the first storage area 28a.

Thus, Value already stored can be updated to Value of a longer data length. The restriction placed on the updating of TLV data objects can thereby be eliminated.

While certain embodiments have been described, these embodiments have been presented by way of example only, and are not intended to limit the scope of the inventions. Indeed, the novel embodiments described herein may be embodied in a variety of other forms; furthermore, various omissions, substitutions and changes in the form of the embodiments described herein may be made without departing from the spirit of the inventions. The accompanying claims and their equivalents are intended to cover such forms or modifications as would fall within the scope and spirit of the inventions.

WHAT IS CLAIMED IS:

1. A portable electronic apparatus executing performing process based on command input from an external apparatus, and storing a plurality of TLV data objects, the apparatus comprising;

a storage unit configured to store the data class and data character of each TLV data object, respectively in two storage areas spaced apart from each other, and to store addresses of a fixed length, representing the positions of the data characters, in association with the each data classes.

2. The portable electronic apparatus of claim 1, wherein the storage unit includes a first storage area configured to store the address and the data class of a TLV data object, in association with each other, and a second storage area configured to store the data character of the TLV data object.

3. The portable electronic apparatus of claim 2, further comprising:

a transmission/reception unit configured to transmit and receive data to and from the external apparatus; and

a control unit configured to retrieve the data class identical to designation data contained in a read command for reading TLV data object, the read command having been received by the transmission/reception unit, and to read the data character stored in the

second storage area, in accordance with the address associated with the data class retrieved.

4. The portable electronic apparatus of claim 2, wherein the storage unit is configured to store a data
5 length representing the length of the data character stored in the second storage area, in association with the data class stored in the first storage area.

5. The portable electronic apparatus of claim 2, wherein the storage unit is configured to store a data
10 length representing the length of the data character to be stored in the second storage area, in association with the data character stored in the second storage area.

6. The portable electronic apparatus of claim 4,
15 further comprising:

a transmission/reception unit configured to transmit and receive data to and from the external apparatus; and

a control unit configured to store the data
20 character of TLV data object to be updated and to update the address and the data length, both associated with the data class stored in the first storage area, in accordance with the data character stored in the second storage area, when the transmission/reception
25 unit receives a command for updating TLV data object.

7. The portable electronic apparatus of claim 2, wherein the storage unit is configured to store the

data class in the first storage area, adjusting the data length of the data class to the data length of the longest TLV data object.

8. The portable electronic apparatus of claim 2,
5 further comprising:

an IC module including the storage unit; and
a main body including the IC module.

9. A method of controlling a portable electronic
apparatus executing performing process based on command
10 input from an external apparatus, and storing a
plurality of TLV data objects, the method comprising:

storing the data class and data character of each
TLV data object, respectively in two storage areas
spaced apart from each other; and

15 storing addresses of a fixed length, representing
the positions of the data characters, in association
with the each data classes.