



- (51) International Patent Classification:
E21D 9/06 (2006.01) *E21D 9/08* (2006.01)
- (21) International Application Number:
PCT/US2012/025478
- (22) International Filing Date:
16 February 2012 (16.02.2012)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
61/444,081 17 February 2011 (17.02.2011) US
- (71) Applicant (for all designated States except US): **THE ROBBINS COMPANY** [US/US]; 29100 Hall Street, Solon, OH 44139 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **SHANAHAN, Aaron, J.** [US/US]; 5866 South 194th Street, Kent, WA 98032 (US). **SMADING, Stephen, M.** [US/US]; 5866 South 194th Street, Kent, WA 98032 (US). **LANG,**

Timothy, A. [US/US]; 5866 South 194th Street, Kent, WA 98032 (US). **BOX, Zachary, J.** [US/US]; 5866 South 194th Street, Kent, WA 98032 (US). **KHALIGHI, Brian, B.** [US/US]; 5866 South 194th Street, Kent, WA 98032 (US). **GROTHEN, Brad, D.** [US/US]; 5866 South 194th Street, Kent, WA 98032 (US). **LENABURG, Carl, E.** [US/US]; 5866 South 194th Street, Kent, WA 98032 (US). **MCNEELEY, Jay, M.** [US/US]; 5866 South 194th Street, Kent, WA 98032 (US). **KONDA, Shinichi** [JP/US]; 5866 South 194th Street, Kent, WA 98032 (US).

(74) Agent: **DODGE, Ryan, E., Jr.**; Christensen O'Connor Johnson Kindness PLLC, 1420 Fifth Avenue, Suite 2800, Seattle, WA 98101 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ,

[Continued on next page]

(54) Title: CUTTER ASSEMBLY FOR TUNNEL BORING MACHINE WITH PRESSURE COMPENSATION




Fig.4.

(57) Abstract: A pressure-compensated cutter assembly for a tunnel boring machine includes a shaft a cutter ring assembly rotatably mounted on the shaft, and first and second end retainers non-rotatably attached to the shaft. Rotary seal groups, immersed in lubricant, provide a moving seal between the rotating cutter ring assembly and the end retainers. A movable piston member is exposed to ambient pressures, and contacts the lubricant, such that increasing ambient pressure will increase the lubricant pressure, thereby keeping the pressure differential across the seal small. In one embodiment, the piston is a floating retainer portion. In another embodiment, the piston is an annular piston, and in another embodiment, the piston is a plurality of smaller pistons disposed in the first retainer.



OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ,

Published:

— *without international search report and to be republished upon receipt of that report (Rule 48.2(g))*