

METHODS AND APPARATUS FOR PROVIDING SERVICE NOTIFICATIONS IN A NETWORK ENVIRONMENT

Claim of Priority under 35 U.S.C. §119

[0001] The present Application for Patent claims priority to Provisional Application No. 60817,773 entitled "METHOD AND APPARATUS FOR DELIVERY OF SERVICE ALERTS TO DEVICES IN MULTICAST COMMUNICATION SYSTEMS" filed June 30, 2006, and assigned to the assignee hereof and hereby expressly incorporated by reference herein.

BACKGROUND

I. FIELD

[0002] The present application relates generally to the operation of a distribution network, and more particularly, to methods and apparatus for providing service notifications in a network environment.

II. DESCRIPTION OF THE RELATED ART

[0003] Data networks, such as wireless communication networks, have to trade off between services customized for a single terminal and services provided to a large number of terminals. For example, the distribution of multimedia content to a large number of resource limited portable devices (subscribers) is a complicated problem. Therefore, it is very important for network administrators, content retailers, and service providers to have a way to distribute content and/or other network services in a fast and efficient manner and in such a way as to increase bandwidth utilization and power efficiency.

[0004] In current content delivery/media distribution systems, real time and non real time services are packed and delivered to devices on a network. For example, a communication network may utilize Orthogonal Frequency Division Multiplexing (OFDM) to broadcast content and services from a network server to one or more mobile devices. During operation, distribution system entities would like to notify targeted devices of selected events, such as marketing promotions, price changes, programming changes, or other events of interest to device users. These same entities may also wish to notify devices of application upgrades or other information that may be available for retrieval. Unfortunately, conventional systems may not provide a fast and efficient

mechanism to notify targeted devices of events of interest, or to notify devices of application upgrade or other information that may be available for retrieval.

[0005] Therefore, it is desirable to have a system that operates to provide notifications of events of interest to targeted devices on a broadcast network. The system should also operate to notify targeted devices of available upgrades or other information and facilitate automatic retrieval of such upgrades or information.

SUMMARY

[0006] In one or more aspects, a notification system, comprising methods and apparatus, is provided that operates to provide service notifications in a network environment. For example, the system is operable to provide notifications to targeted devices on a communication network. The system is also operable to notify targeted devices of available upgrades or other information and facilitate automatic retrieval of such upgrades or information.

[0007] In an aspect, a method is provided that operates to provide a notification system. The method comprises obtaining notification information, determining a response factor, generating a notification message comprising selected notification information, wherein the notification message is generated to produce a response based on the response factor, and broadcasting the notification message.

[0008] In an aspect, an apparatus is provided that operates to provide a notification system. The apparatus comprises a notification interface configured to obtain notification information, processing logic configured to determine a response factor and generate a notification message comprising selected notification information, wherein the notification message is generated to produce a response based on the response factor, and broadcast logic configured to broadcast the notification message.

[0009] In an aspect, an apparatus is provided that operates to provide a notification system. The apparatus comprises means for obtaining notification information, means for determining a response factor, means for generating a notification message comprising selected notification information, wherein the notification message is generated to produce a response based on the response factor, and means for broadcasting the notification message.

[0010] In an aspect, a computer-readable medium is provided that has a computer program comprising instructions, which when executed by at least one processor,

operate to provide a notification system. The computer program comprises instructions for obtaining notification information, instructions for determining a response factor, instructions for generating a notification message comprising selected notification information, wherein the notification message is generated to produce a response based on the response factor, and instructions for broadcasting the notification message.

[0011] In an aspect, at least one processor is provided that is configured to perform a method for providing a notification system. The method comprises obtaining notification information, determining a response factor, generating a notification message comprising selected notification information, wherein the notification message is generated to produce a response based on the response factor, and broadcasting the notification message.

[0012] In an aspect, a method is provided that operates to provide a notification system. The method comprises receiving a notification message comprising one or more notification parameters, filtering the notification message based on at least one notification parameter to produce a filtered notification message, processing the filtered notification message to determine at least one notification, and rendering the at least one notification.

[0013] In an aspect, an apparatus is provided that is configured to provide a notification system. The apparatus comprises receiving logic configured to receive a notification message comprising one or more notification parameters, and a message filter configured to filter the notification message based on at least one notification parameter to produce a filtered notification message. The apparatus also comprises processing logic configured to process the filtered notification message to determine at least one notification, and rendering logic configured to render the at least one notification.

[0014] In an aspect, an apparatus is provided that is configured to provide a notification system. The apparatus comprises means for receiving a notification message comprising one or more notification parameters, and means for filtering the notification message based on at least one notification parameter to produce a filtered notification message. The apparatus also comprises means for processing the filtered notification message to determine at least one notification, and means for rendering the at least one notification.

[0015] In an aspect, a computer-readable medium is provided that has a computer program comprising instructions, which when executed by at least one processor, operate to provide a notification system. The computer program comprises instructions for receiving a notification message comprising one or more notification parameters, and instructions for filtering the notification message based on at least one notification parameter to produce a filtered notification message. The computer program also comprises instructions for processing the filtered notification message to determine at least one notification, and instructions for rendering the at least one notification.

[0016] In an aspect, at least one processor is provided that is configured to perform a method for providing a notification system. The method comprises receiving a notification message comprising one or more notification parameters, and filtering the notification message based on at least one notification parameter to produce a filtered notification message. The method also comprises processing the filtered notification message to determine at least one notification, and rendering the at least one notification.

[0017] Other aspects, advantages, and features will become apparent after review of the hereinafter set forth Brief Description of the Drawings, Description, and the Claims.

BRIEF DESCRIPTION OF THE DRAWINGS

[0018] The foregoing aspects described herein will become more readily apparent by reference to the following description when taken in conjunction with the accompanying drawings wherein:

[0019] **FIG. 1** shows a data network that comprises an aspect of a notification system;

[0020] **FIG. 2** shows a diagram of a server suitable for use in aspects of a notification system;

[0021] **FIG. 3** shows a notification message suitable for use in aspects of a notification system;

[0022] **FIG. 4** shows a diagram illustrating a notification detail field for use in aspects of a notification system;

[0023] **FIG. 5** shows notification types for use in aspects of a notification system;

[0024] **FIG. 6** shows a method for operating a server suitable for use in aspects of a notification system;

- [0025] FIG. 7 shows a device suitable for use in aspects of a notification system;
- [0026] FIG. 8 shows a method for operating a device suitable for use in aspects of a notification system;
- [0027] FIG. 9 shows a server suitable for use in aspects of a notification system; and
- [0028] FIG. 10 shows a device suitable for use in aspects of a notification system.

DESCRIPTION

[0029] The following description describes aspects of a notification system that operate to notify devices on a broadcast network about events of interest. For example, the system operates to notify targeted devices about marketing promotions, price changes, programming changes, or other events of interest. The system also provides user defined filtering and interactive functionality to facilitate automatic retrieval of upgrades or other information. The system is especially well suited for use in wireless network environments, but may be used in any type of network environment, including but not limited to, communication networks, public networks, such as the Internet, private networks, such as virtual private networks (VPN), local area networks, wide area networks, long haul network, or any other type of network.

[0030] FIG. 1 shows a data network 100 that comprises an aspect of a notification system. The network 100 comprises server 102, data network 104, and a plurality of devices shown generally at 106. The data network 104 may be any type and/or combination of wired and wireless networks that allow data to be transmitted between the server 102 and the devices 106. The server 102 is coupled to the network 104 via the communication link 108, which may be any type of wired and/or wireless communication link that allows the server 102 to communicate with the data network 104. The devices 106 comprise a mobile telephone, PDA, notebook computer, pager, email device, or any other type of device that may operate on the network 104. The devices 106 are in communication with the data network 104 via wireless communication links 110, which allows data to be wirelessly transmitted between the network 104 and the devices 106. In an aspect, the wireless communication links 110 comprises forward communication channels, reverse communication channels, control channels, and any other type of communication channel that may be used to communicate information between the network 104 and the devices 106.

[0031] It should also be noted that aspects of the notification system are suitable for use with virtually any number of devices that communicate with the network **104** via wired and/or wireless communication links. For the purpose of this description, the operation of the device **112** will be described in detail; however aspects of the notification system are equally applicable to all the devices shown generally at **106**.

[0032] During operation, the server **102** receives or otherwise obtains notification information **114** that is to be provided to the devices **106** as notification of one or more conditions or events. For example, the notification information **114** is provided by content providers, content retailers, system administrators or other notification providers or network entities. The notification information **114** comprises marketing promotions, price changes, programming changes, or other events of interest. These same entities may also wish to notify the devices **106** of application upgrades or other information that may be available for retrieval. For example, application upgrades may be available for retrieval from a particular network location.

[0033] The system allows operators to create notifications by specifying the scope of the notification and associating it with one or more notification types. A notification message is generated that comprises a message subject and body. The subject is the text title of the notification, and the body is a text message. The notification messages are able to support multiple languages and each notification may comprise multiple messages in different languages. For each message, the language is specified and the subject and body text are provided in that language.

[0034] For each notification, a start time and an end time are specified that define a time window during which the notification message will be delivered. After generating a notification message, the notification message can be deleted or modified before the start time of its delivery window. After the start time of a delivery window, however, only the end time of the notification message is modifiable. Each notification message is associated with a sequence number. The sequence number is used by receiving devices to avoid storing duplicate notifications.

[0035] The server **102** comprises notification generation logic **116** that operates to receive the notification information **114** and generate one or more notification messages **118**. A more detailed description of the format of a notification message is provided in another section of this document. The server **102** then transmits the notification messages **118** over a broadcast channel **120** provided by the network **104**. The

devices **106** are able to listen on the broadcast channel **120** and receive the notification messages **118**.

[0036] As illustrated by the device **112**, the devices **106** comprise notification filter **122** and notification processor **124**. The notification filter **122** operates to filter received notification messages so that only those messages of interest to a particular device are processed. For example, the notification filter **122** operates to filter the notification messages **118** based on sequence number, device model, geographic region, content subscriptions, user defined preferences or any other characteristic or parameter associated with the device **112**.

[0037] The notification processor **124** operates to process filtered notification messages to determine information that is relevant to a particular device. For example, the information comprises marketing promotions, price changes, programming changes, or other events of interest to that particular device. The notification processor **124** operates to update local system parameters with the new information, render notifications to the device user, or store notifications for later viewing.

[0038] In another aspect, the notification messages **118** comprise notifications having interactive functionality. For example, a notification may provide interactive functionality with respect to application upgrades or other information that is available for retrieval. The notification processor **124** operates to determine the location of the available upgrade or information and automatically retrieve that upgrade or information. For example, the device **112** may receive a notification message about a particular application upgrade that is available for retrieval from an upgrade server **126**. The notification processor **124** operates to contact the upgrade server **126**, as shown at **128**, to retrieve the available upgrade or information.

[0039] In an aspect, the server **102** operates to generate the notification messages **118** to control a response factor of the devices **106**. For example, the notification messages **118** are generated so that a selected number of devices will perform a particular action. The action may be to perform an application upgrade. In an aspect, parameters are included in the notification message **118** that are associated with a selected number of devices, such as a range of device identifiers. When the identified devices receive the notification message **118**, they will respond by, for example, retrieving an application update from the update server **126**. This mechanism allows the

server **102** to control how many devices attempt to access the update server **126** at any particular time so as to avoid network congestion.

[0040] Thus, in one or more aspects, a notification system is provided that operates to provide notifications to targeted devices in a network. The system also provides interactive functionality and a mechanism to control how many devices perform selected actions based on a response factor, so as to avoid network congestion. As a result, aspects of the notification system provide a way for devices to be notified of selected events and to perform selected actions in a timely and efficient manner. It should be noted that the network **100** is just one implementation and that other implementations are possible within the scope of the aspects.

[0041] **FIG. 2** shows a diagram of a server **200** suitable for use in aspects of a notification system. For example, the server **200** may be the server **102** shown in **FIG. 1**. The server **200** comprises processing logic **202**, notification storage **204**, notification provider interface (I/F) **206**, and transceiver logic **208** all coupled to a data bus **210**. It should be noted that the server **200** is just one implementation and that other implementations are possible within the scope of the aspects.

[0042] The transceiver logic **208** comprises hardware and/or software that operate to allow the server **200** to communicate data or other information over a network with remote devices or systems. For example, in an aspect, the transceiver logic **208** comprises broadcast logic that operates to broadcast notification messages over a broadcast channel **214**. The term “broadcast” is used herein to mean a broadcast, multicast or other transmission over a network that can be received by two or more devices. In an aspect, the transceiver logic **208** also comprises unicast logic to communicate over a unicast channel **212** so that the server **200** may communicate directly over a network with a particular device.

[0043] The notification provider interface (I/F) **206** comprises hardware and/or software that operate to allow the server **200** to communicate with notification providers to receive notification information for distribution to devices. For example, the notification providers comprise content providers, content retailers, or any other distribution system entity. The I/F **206** comprises communication logic that allows communication with notification providers over a wired or wireless network link or any other suitable link, such as a direct connect link. The notification storage **204** comprises

any suitable memory operable to store notification information received by the notification provider I/F **206**.

[0044] In one or more aspects, the processing logic **202** comprises a CPU, processor, gate array, hardware logic, memory elements, virtual machine, software, and/or any combination of hardware and software. Thus, the processing logic **202** generally comprises logic to execute machine-readable instructions and to control one or more other functional elements of the server **200** via the data bus **210**.

[0045] In an aspect, the processing logic **202** operates to generate one or more notification messages for distribution to devices on a network. For example, the notification messages are broadcast over the broadcast channel **212** by the transceiver logic **208**. In an aspect, the processing logic **202** operates to generate the notification messages based on a response factor to control how selected devices respond to a notification message. For example, a notification message is generated to identify selected devices that are to contact an upgrade server to retrieve an application upgrade. Thus, the processing logic **202** operates to generate the notification messages to control network congestion by identifying selected groups of devices that are to obtain the upgrade at any particular time.

[0046] In an aspect, the following elements are specified for each notification.

- a. Notification Type: Notifications can be classified into a large number of types as described below.
- b. Notification Scope: The scope of the notifications determines which devices need to process the notifications. For example, for a blackout notification associated with a specific channel, the notification will be processed by the devices that are subscribed to that particular channel. For an application upgrade notification, only those devices that need the application upgrade will process the notification. For an emergency notification, the notification needs to be delivered and processed by all the devices in the network.
- c. Notification Delivery Window: The delivery window sets the duration of the notifications to be broadcast in the network.
- d. Notification Subject: The subject is the text title of the notification.
- e. Notification Body: The body is associated with the mime type to support various types of notifications, e.g., audio, video or image etc. The body could be

a simple string, it could contain hyperlinks for users to be interactive, or it could contain multimedia content.

[0047] In an aspect, the notification system comprises program instructions stored on a computer-readable medium, which when executed by at least one processor, such as the processing logic **202**, operate to provide the functions of the notification system described herein. For example, instructions may be loaded into the server **200** from a computer-readable medium, such as a floppy disk, CDROM, memory card, FLASH memory device, RAM, ROM, or any other type of memory device or computer-readable medium that interfaces to the server **200**. In another aspect, the instructions may be downloaded into the server **200** from a network resource that interfaces to the sever **200** via the transceiver logic **208**. The instructions, when executed by the processing logic **202**, provide one or more aspects of the notification system described herein.

[0048] **FIG. 3** shows a notification message **300** for use in aspects of a notification system. For example, the format of the notification message **300** is suitable for use for the notification messages **118** shown in **FIG. 1**. In an aspect, the notification message **300** is generated by the processing logic **202** of the server **200**. It should be noted that the notification message **300** is just one implementation and that other implementations having more or less information are possible within the scope of the aspects.

[0049] The notification message **300** comprises a notification version **302**, a notification identifier (ID) **304**, a composite address **306**, and a notification record **308**.

[0050] The notification version **302** indicates the current version of the notification message **300**. The notification ID **304** identifies the notification message **300**.

[0051] The composite address **306** operates to address the notification message **300** to one or more targeted devices. For example, a notification message can be sent to a subset of devices as specified by the composite address **306**. In an aspect, there are four types of address classes **310**, namely; billing and customer service, content retailer, package, and service class. Each address class is associated with one or more addresses **312**. However, it should be noted that any number or types of address classes may be used.

[0052] In an aspect, the notification record **308** comprises three fields as follows.

- a. Notification type (NOTFN_TYPE) field **314**
- b. Notification Length (LENGTH) field **316**
- c. Notification Detail (NOTFN_DETAIL) field **318**

[0053] For example, in a marketplace notification, the text string “MARKETPLACE_NOTIFICATION” is set for the NOTFN_TYPE 314. The LENGTH field 316 indicates the length of the NOTFN_DETAIL field 318 in bytes. The NOTFN_DETAIL field 318 contains the encapsulated notification data. The format of the NOTFN_DETAIL field 318 is provided in another section of this document.

[0054] In an aspect, the system operates to periodically send the notification messages over the network. The periodicity at which the notification messages are transmitted depends on a data rate provisioned at the transmitting server. However, it should be noted that the system is operable for use with virtually any periodicity.

Notification Detail Field

[0055] FIG. 4 shows a diagram illustrating a notification detail field 400 for use in aspects of a notification system. In an aspect, the notification detail field 400 is a binary encoded instance of the following XML schema.

Notification Sequence Number (402)

[0056] This is a 2-byte unsigned integer sequence number that is incremented by one whenever a new notification is generated.

Notification Type (404)

[0057] This 1-byte unsigned integer that specifies the type of notification from one of the types illustrated in FIG. 5.

Notification Language (406)

[0058] This specifies the language used for the notification subject and body text.

Notification Body Mime Type (408)

[0059] This field indicates the type of the body. For example, the type of the body may be set to “text/plain.”

Notification Subject (410)

[0060] This is a text string describing the subject of the notification. In an aspect, the maximum length of the subject in characters is defined by a MAX_SUBJECT parameter and may be of any selected length.

Notification Body (412)

[0061] This is a text string that describes the notification. The maximum length of the text body in characters is defined by an MAX_BODY parameter and may be of any selected length.

[0062] FIG. 5 shows notification type parameters 500 for use in aspects of a notification system. For example, the notification type parameters 500 are suitable for use in the notification detail field 400 shown in FIG. 4. It should be noted that the notification type parameters 500 are provided in just one implementation and that other implementations may provide other type parameters within the scope of the aspects.

[0063] The notification type parameters 500 comprise parameters which may be formatted in any suitable format and may be encrypted using any suitable encryption technology. The notification type parameters 500 comprise marketing/promotion parameters 502 that identify particular marketing and promotional notifications. Other parameters provide for an emergency notification 504, a blackout notification 506, a price change notification 508, an end user license agreement (EULA) notification 510, terms of usage notification (TOU) 512, a TOU change notification 514, and a content rating notification 516.

[0064] The notification type parameters 500 also comprise an application upgrade notification 518 that identifies a particular application that has been upgraded. Furthermore, an upgrade link 520 is provided that identifies a network location where the application upgrade can be found. Thus, devices receiving the application upgrade notification 518 also received the upgrade link 520 to determine the network location of the upgrade for retrieval. Thus, the application upgrade notification 518 facilitates interactive functionality since a receiving device may automatically retrieve the upgrade at the location specified by the upgrade link 520.

[0065] FIG. 6 shows a method 600 for operating a server for use in aspects of a notification system. For clarity, the method 600 will be described with reference to the server 200 shown in FIG. 2. In one or more aspects, the processing logic 202 executes program instructions to control the server 200 to perform the functions described below.

[0066] At block 602, notification information is received from notification providers. For example, the notification providers comprise content providers, content retailers, application developers, or other distribution system entities. In an aspect, the notification I/F 206 operates to receive the notification information and stores the received information at the notification storage 204.

[0067] At block **604**, targeted devices and desired response factors are determined. For example, the targeted devices are determined based on device identifiers that are to be included in a notification message. The desired response factors are determined and indicate the number of devices that are to respond to a particular notification, such as an application upgrade notification. For example, an application upgrade notification may be associated with an upgrade link that identifies a network location of a particular application upgrade. To avoid network congestion, a desired response factor is determined that indicates how many devices should be allowed to respond to the notification and access the identified network location at any particular time. In an aspect, the processing logic **202** operates to determine response factors associated with any of the notifications.

[0068] At block **606**, one or more notification messages are assembled. For example, a notification message is formatted as shown in **FIG. 3**. In an aspect, the processing logic **202** operates to assemble one or more notification messages.

[0069] At block **608**, the notification messages are broadcast over a network. For example the notification messages are broadcast over a broadcast channel provided by a communication network so that devices listening on the broadcast channel can receive the notification messages. In an aspect, the transceiver logic **208** operates to broadcast the notification messages over the broadcast channel **214** within a predefined delivery window.

[0070] At block **610**, a test is performed to determine if any of the notification messages need to be re-broadcast. For example, a notification message may have a selected broadcast periodicity that requires the message to be re-broadcast at selected intervals. In another aspect, if a selected response to a notification message is not received, then the notification message is re-broadcast until the desired response is received. In an aspect, the processing logic **202** operates to determine if any notification message is to be re-broadcast based on a periodicity factor or desired device response. If a notification message is to be re-broadcast, the method proceeds to block **608**. If it is determined that a re-broadcast is not necessary, the method stops at block **612**.

[0071] It should be noted that the method **600** illustrates just one implementation and that changes, additions, deletions, or rearrangements of the described functions may be made without deviating from the scope of the described aspects.

[0072] FIG. 7 shows a device 700 suitable for use in aspects of a notification system. For example, the device 700 is suitable for use as the device 112 shown in FIG. 1. The device 700 comprises processing logic 702, notification message filter 704, device resources and interfaces 706, transceiver logic 708, system parameters 710, and notification storage 718 all coupled to a data bus 712. It should be noted that the device 700 is just one implementation and that other implementations are possible within the scope of the aspects.

[0073] The processing logic 702 comprises a CPU, processor, gate array, hardware logic, memory elements, virtual machine, software, and/or any combination of hardware and software. Thus, the processing logic 702 generally comprises logic to execute machine-readable instructions and to control one or more other functional elements of the device 700 via the data bus 712.

[0074] The device resources and interfaces 706 comprise hardware and/or software that allow the device 700 to communicate with internal and external systems. For example, internal systems may include mass storage systems, memory, display driver, modem, or other internal device resources. The external systems may include user interface devices, displays, keypad, printers, disk drives, or other local devices or systems. Thus, the device resources and interfaces 706 operate to allow notifications to be rendered in any suitable fashion on the device 700 to alert a device user. Furthermore, the device resources and interfaces 706 operate to allow user inputs that can be passed to the notification message filter 704.

[0075] The transceiver logic 708 comprises hardware and/or software that operate to allow the device 700 to transmit and receive data and other information with external devices or systems. For example, the transceiver logic 708 comprises broadcast logic that operates to allow the device 700 to receive broadcast transmissions over a broadcast channel 716. The transceiver logic 708 also comprises unicast logic that operates to allow the device 700 to transmit and receive information over a unicast channel 714. Thus, the device 700 is able to communicate with network entities, such as a broadcast server or an upgrade server.

[0076] The system parameters 708 comprise parameters that are associated with the operation of the device on a distribution network. For example, the parameters comprise device identifiers, subscription information, application information, such as types and versions, and any other parameters or related information. The system

parameters **708** are stored in any suitable memory and may be accessed, updated, or otherwise modified by the processing logic **702**.

[0077] The notification storage **718** comprises any suitable memory operable to store notification information received in filtered notification messages. For example, filtered notification messages may be stored for later viewing.

[0078] The notification message filter **704** comprises a CPU, processor, gate array, hardware logic, memory elements, virtual machine, software, and/or any combination of hardware and software. In an aspect, the notification message filter **704** operates to filter notification messages received over the broadcast channel **716**. For example, the notification messages comprise parameters that may be filtered based on the system parameters **708** to determine notification messages that are targeted to the device **700**. For example, a device identifier associated with a received notification message is processed to determine if it matches a device identifier stored in the system parameters **708**. If a match is determined, then the received notification message is determined to be a filtered notification message and is further processed by the processing logic **702**. If no match occurs, the notification message is ignored.

[0079] In another aspect, the notification message filter **704** operates to filter notification messages received over the broadcast channel **716** based on received user input. For example, the notification messages comprise parameters that may be filtered based on user input received using the device resources and interfaces **706**. The parameters provided by the user input are used to determine notification messages that are to be processed or ignored by the device. For example, the user input may specify that only emergency alerts are to be processed by the device. If a received notification message is not associated with an emergency alert, then the message is ignored. The mechanism allows a device user input preferences that are used to determine which alerts are to be processed and which are to be ignored. Thus, received notification messages may be filtered by the notification message filter **704** based on any parameter stored in the system parameters or based on user inputs to determine filtered notification messages that are to be further processed.

[0080] During operation, notification message may be periodically broadcast during a particular deliver window. Thus, the device **700** may receive the same notification multiple times. To avoid displaying previously received notifications to the user, the sequence number of each notification is saved in the notification storage **718** for a

selected time period. If a notification message has arrived with the same sequence number as a previous notification message, the newly received message will be ignored. For example, whenever the device **700** receives a notification message, it will know if the notification message has already been received or not by comparing its sequence number with saved sequence numbers. If the sequence number of the notification message has not been saved, the device **700** considers that it is a new notification message and processes it accordingly. If the sequence number of the new notification message exists in the device, the notification message will be discarded.

[0081] In an aspect, the processing logic **702** operates to notify and guide the device user to view any received notification messages. The processing logic **702** also operates to allow users to delete any received notifications. In an aspect, the processing logic **702** provides an automated memory-driven method for removing notifications. For example, when the number of stored notifications on the device **700** reaches a selected number and a new notification arrives, the oldest notification will be deleted. In another aspect, if the language of a received notification message is different from the preferred language specified for the device **700**, the notification will not be displayed on the device

[0082] During operation, the device **700** operates to receive notification messages over the broadcast channel **716**. For example, the transceiver logic **708** operates to receive notification messages and pass them to the notification message filter **704**. The notification message filter **704** operates to process the received notification messages based on the system parameters **708** and/or user input parameters to determine filtered notification messages that are to be processed by the device **700**. For example, a received notification message may have a device identifier, region identifier, application identifier, or other parameters that match or otherwise qualify the message (based on the system parameters **708**) to pass through the filter **704**. The processing logic **702** then processes those filtered notification messages that pass through the filter **704**. In an aspect, a filtered notification message may comprise an application upgrade notification having an associated upgrade link. The processing logic **702** then operates to obtain the upgrade by accessing the provided upgrade link.

[0083] Once received notification message are filtered and processed, the device **700** will notify users of the notification. For example, the processing logic **702** renders notifications on the device using the device resources and interfaces **706**. Since

notification messages may be sent multiple times during the notification delivery window, the device **700** operates to eliminate duplicate notifications to users if any. Alternatively, the filtered notification messages may be saved in the notification storage **718** for later viewing, or notification messages can be removed by the user. In an aspect, a user filtering mechanism for the notifications can be added. For example, depending on the notification type, the user can choose which type of notification should be ignored.

[0084] In an aspect, the notification system comprises program instructions stored on a computer-readable medium, which when executed by at least one processor, such as the processing logic **702**, operate to provide the functions of the notification system described herein. For example, instructions may be loaded into the device **700** from a computer-readable media, such as a floppy disk, CDROM, memory card, FLASH memory device, RAM, ROM, or any other type of memory device or computer-readable media that interfaces to the device **700**. In another aspect, the instructions may be downloaded into the device **700** from a network resource that interfaces to the device **700**. The instructions, when executed by the processing logic **702**, provide one or more aspects of a notification system as described herein.

[0085] **FIG. 8** shows a method **800** for operating a device in an aspect of a notification system. For clarity, the method **800** will be described with reference to the device **700** shown in **FIG. 7**. In one or more aspects, the processing logic **702** executes program instructions to control the device **700** to perform the functions described below.

[0086] At block **802**, one or more notification messages are received. For example, in an aspect, the transceiver logic **702** receives the notification messages over the broadcast channel **716**.

[0087] At block **804**, the received notification messages are filtered. For example, the notification messages are filtered to determine if they are targeted to the device **700**. In an aspect, a received notification message is filtered based on parameters associated with the message. For example, a device identifier, region identifier, sequence number, application version, or other parameter associated with a received notification message is compared to parameters stored in the system parameters **708**. For example, a notification message will pass through the filter if the device identifier in the notification message matches a device identifier stored in the system parameters **708**.

[0088] In another aspect, received notification messages are filtered based on user input parameters. For example, a device user provides user filter parameters using the device resources and interfaces **706**. The notification message filter operates to filter received notifications using the user filter parameters. Notification messages that do not pass through the filter are ignored. In an aspect, the notification message filter **704** operates to filter the received notification messages and pass filtered notification messages to the processing logic **702** for further processing.

[0089] At block **806**, the filtered notification messages are processed. In an aspect, the processing logic **702** operates to process a filtered notification message so that parameters in the filtered notification message are used to update the system parameters **708**. For example, a price change, blackout parameter, or other parameters in the filtered notification message is used to update the system parameters **708**.

[0090] At block **808**, the processed notifications are presented to the device user or stored for later viewing. For example, the processing logic **702** operates to render information about processed notifications to the device user through the device resources and interfaces **708**. In another aspect, the processed notifications are stored in the notification storage **718** for later viewing.

[0091] At block **810**, automatic functions are performed. For example, the processing logic **702** operates to determine an upgrade link in a filtered notification message and automatically contacts a network entity at that link to obtain upgrade information. For example, the filtered notification message comprises an application notification that indicates that a particular application has been upgraded. As part of the filtered notification message, the application notification is associated with an upgrade link address. The processing logic **702** operates to use the upgrade link address to contact a network entity to retrieve the application upgrade. Thus, the processing logic **702** automatically performs an upgrade function based on information in the filtered notification message. It should be noted that any type of interactive functionality may be automatically performed based on information in the filtered notification message.

[0092] Thus, the method **800** operates to provide aspects of a notification system for use at a device. It should be noted that the method **800** illustrates just one implementation and that changes, additions, deletions, or rearrangements of the described functions may be made without deviating from the scope of the described aspects.

[0093] FIG. 9 shows a server 900 suitable for use in aspects of a notification system. The server 900 comprises means 902 for obtaining notification information. For example, in an aspect, the means 902 comprises the notification provider interface 206.

[0094] The server 900 also comprises means 904 for determining a response factor. For example, in an aspect, the means 904 comprises the processing logic 202.

[0095] The server 900 also comprises means 906 for generating a notification message. For example, in an aspect, the means 906 comprises the processing logic 202.

[0096] The server 900 also comprises means 908 for broadcasting a notification message. For example, in an aspect, the means 908 comprises the transceiver logic 208.

[0097] FIG. 10 shows a device 1000 suitable for use in aspects of a notification system. The device 1000 comprises means 1002 for receiving a notification message. For example, in an aspect, the means 1002 comprises the transceiver logic 708.

[0098] The device 1000 also comprises means 1004 for filtering a notification message. For example, in an aspect, the means 1004 comprises the message filter 704.

[0099] The device 1000 also comprises means 1006 for processing a filtered notification message. For example, in an aspect, the means 1006 comprises the processing logic 702.

[00100] The device 1000 also comprises means 1008 for rendering a notification. For example, in an aspect, the means 1008 comprises the device resources and interfaces 706.

[00101] Thus, the various illustrative logics, logical blocks, modules, and circuits described in connection with the aspects disclosed herein may be implemented or performed with a general purpose processor, a digital signal processor (DSP), an application specific integrated circuit (ASIC), a field programmable gate array (FPGA) or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general-purpose processor may be a microprocessor, but, in the alternative, the processor may be any conventional processor, controller, microcontroller, or state machine. A processor may also be implemented as a combination of computing devices, e.g., a combination of a DSP and a microprocessor, a plurality of microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration.

[00102] The steps of a method or algorithm described in connection with the aspects disclosed herein may be embodied directly in hardware, in a software module executed by a processor, or in a combination of the two. A software module may reside in RAM memory, flash memory, ROM memory, EPROM memory, EEPROM memory, registers, a hard disk, a removable disk, a CD-ROM, or any other form of storage medium known in the art. An exemplary storage medium is coupled to the processor, such that the processor can read information from, and write information to, the storage medium. In the alternative, the storage medium may be integral to the processor. The processor and the storage medium may reside in an ASIC. The ASIC may reside in a user terminal. In the alternative, the processor and the storage medium may reside as discrete components in a user terminal.

[00103] The description of the disclosed aspects is provided to enable any person skilled in the art to make or use the present invention. Various modifications to these aspects may be readily apparent to those skilled in the art, and the generic principles defined herein may be applied to other aspects, e.g., in an instant messaging service or any general wireless data communication applications, without departing from the spirit or scope of the invention. Thus, the present invention is not intended to be limited to the aspects shown herein but is to be accorded the widest scope consistent with the principles and novel features disclosed herein. The word “exemplary” is used exclusively herein to mean “serving as an example, instance, or illustration.” Any aspect described herein as “exemplary” is not necessarily to be construed as preferred or advantageous over other aspects.

[00104] Accordingly, while one or more aspects of a notification system have been illustrated and described herein, it will be appreciated that various changes can be made to the aspects without departing from their spirit or essential characteristics. Therefore, the disclosures and descriptions herein are intended to be illustrative, but not limiting, of the scope of the invention, which is set forth in the following claims.

CLAIMS

WHAT IS CLAIMED IS:

1. A method for providing a notification system, the method comprising:
obtaining notification information;
determining a response factor;
generating a notification message comprising selected notification information,
wherein the notification message is generated to produce a response based on the
response factor; and
broadcasting the notification message.
2. The method of claim 1, wherein said obtaining comprises obtaining the
notification information from one or more notification providers.
3. The method of claim 1, wherein said generating comprises generating the
notification message to target one or more selected devices.
4. The method of claim 1, wherein said generating comprises generating the
notification message to comprise an interactive notification that identifies information
for retrieval.
5. The method of claim 1, further comprising periodically repeating said
broadcasting.
6. The method of claim 1, wherein the said broadcasting comprises
broadcasting the notification message over a wireless communication network.
7. An apparatus for providing a notification system, the apparatus
comprising:
a notification interface configured to obtain notification information;
processing logic configured to determine a response factor and generate a
notification message comprising selected notification information, wherein the

notification message is generated to produce a response based on the response factor;
and

broadcast logic configured to broadcast the notification message.

8. The apparatus of claim 7, wherein said notification interface is configured to obtain the notification information from one or more notification providers.

9. The apparatus of claim 7, wherein said processing logic is configured to generate the notification message to target one or more selected devices.

10. The apparatus of claim 7, wherein said processing logic is configured to generate the notification message to comprise an interactive notification that identifies information for retrieved.

11. The apparatus of claim 7, wherein said broadcast logic is configured to periodically broadcast the notification message.

12. The apparatus of claim 7, wherein said broadcast logic is configured to broadcast the notification message over a wireless communication network.

13. An apparatus for providing a notification system, the apparatus comprising:

means for obtaining notification information;

means for determining a response factor;

means for generating a notification message comprising selected notification information, wherein the notification message is generated to produce a response based on the response factor; and

means for broadcasting the notification message.

14. The apparatus of claim 13, wherein said means for obtaining comprises means for obtaining the notification information from one or more notification providers.

15. The apparatus of claim 13, wherein said means for generating comprises means for generating the notification message to target one or more selected devices.

16. The apparatus of claim 13, wherein said means for generating comprises means for generating the notification message to comprise an interactive notification that identifies information for retrieval.

17. The apparatus of claim 13, further comprising means for periodically repeating said broadcasting.

18. The apparatus of claim 13, wherein the said means for broadcasting comprises means for broadcasting the notification message over a wireless communication network.

19. A computer-readable medium having a computer program comprising instructions, which when executed by at least one processor, operate to provide a notification system, the computer program comprising:

instructions for obtaining notification information;

instructions for determining a response factor;

instructions for generating a notification message comprising selected notification information, wherein the notification message is generated to produce a response based on the response factor; and

instructions for broadcasting the notification message.

20. The computer program of claim 19, wherein said instructions for obtaining comprise instructions for obtaining the notification information from one or more notification providers.

21. The computer program of claim 19, wherein said instructions for generating comprise instructions for generating the notification message to target one or more selected devices.

22. The computer program of claim 19, wherein said instructions for generating comprise instructions for generating the notification message to comprise an interactive notification that identifies information for retrieval.

23. The computer program of claim 19, further comprising instructions for periodically repeating said broadcasting.

24. The computer program of claim 19, wherein the said instructions for broadcasting comprise instructions for broadcasting the notification message over a wireless communication network.

25. At least one processor configured to perform a method for providing a notification system, the method comprising:
obtaining notification information;
determining a response factor;
generating a notification message comprising selected notification information, wherein the notification message is generated to produce a response based on the response factor; and
broadcasting the notification message.

26. The method of claim 25, wherein said obtaining comprises obtaining the notification information from one or more notification providers.

27. The method of claim 25, wherein said generating comprises generating the notification message to target one or more selected devices.

28. The method of claim 25, wherein said generating comprises generating the notification message to comprise an interactive notification that identifies information for retrieval.

29. The method of claim 25, further comprising periodically repeating said broadcasting.

30. The method of claim **25**, wherein the said broadcasting comprises broadcasting the notification message over a wireless communication network.

31. A method for providing a notification system, the method comprising:
receiving a notification message comprising one or more notification parameters;
filtering the notification message based on at least one notification parameter to produce a filtered notification message;
processing the filtered notification message to determine at least one notification; and
rendering the at least one notification.

32. The method of claim **31**, wherein said receiving comprises receiving the notification message in a wireless broadcast.

33. The method of claim **31**, wherein said processing comprises updating at least one stored parameter based on the at least one notification.

34. The method of claim **31**, further comprising
determining a location for information associated with the at least one notification; and
retrieving the information based on the location.

35. The method of claim **31**, further comprising determining an interactive function to perform based on the at least one notification.

36. The method of claim **31**, wherein said filtering comprises filtering the notification message based on at least one of a system parameter and a user input parameter.

37. The method of claim **31**, further comprising storing the filtered notification message for later rendering.

38. An apparatus for providing a notification system, the apparatus comprising:

receiving logic configured to receive a notification message comprising one or more notification parameters;

a message filter configured to filter the notification message based on at least one notification parameter to produce a filtered notification message;

processing logic configured to process the filtered notification message to determine at least one notification; and

rendering logic configured to render the at least one notification.

39. The apparatus of claim **38**, wherein said receiving logic is configured to receive the notification message in a wireless broadcast.

40. The apparatus of claim **38**, wherein said processing comprises updating at least one stored parameter based on the at least one notification.

41. The apparatus of claim **38**, wherein said processing logic is configured to determine a location for information associated with the at least one notification and retrieve the information based on the location.

42. The apparatus of claim **38**, wherein said processing logic is configured to determine an interactive function to perform based on the at least one notification.

43. The apparatus of claim **38**, wherein said message filter is configured to filter the notification message based on at least one of a system parameter and a user input parameter.

44. The apparatus of claim **38**, wherein said processing logic is configured to store the filtered notification message for later rendering.

45. An apparatus configured to provide a notification system, the apparatus comprising:

means for receiving a notification message comprising one or more notification parameters;

means for filtering the notification message based on at least one notification parameter to produce a filtered notification message;

means for processing the filtered notification message to determine at least one notification; and

means for rendering the at least one notification.

46. The apparatus of claim **45**, wherein said means for receiving comprises means for receiving the notification message in a wireless broadcast.

47. The apparatus of claim **45**, wherein said means for processing comprises means for updating at least one stored parameter based on the at least one notification.

48. The apparatus of claim **45**, further comprising
means for determining a location for information associated with the at least one notification; and

means for retrieving the information based on the location.

49. The apparatus of claim **45**, further comprising means for determining an interactive function to perform based on the at least one notification.

50. The apparatus of claim **45**, wherein said means for filtering comprises means for filtering the notification message based on at least one of a system parameter and a user input parameter.

51. The apparatus of claim **45**, further comprising means for storing the filtered notification message for later rendering.

52. A computer-readable medium having a computer program comprising instructions, which when executed by at least one processor, operate to provide a notification system, the computer program comprising:

instructions for receiving a notification message comprising one or more notification parameters;

instructions for filtering the notification message based on at least one notification parameter to produce a filtered notification message;

instructions for processing the filtered notification message to determine at least one notification; and

instructions for rendering the at least one notification.

53. The computer program of claim **52**, wherein said instructions for receiving comprise instructions for receiving the notification message in a wireless broadcast.

54. The computer program of claim **52**, wherein said instructions for processing comprise instructions for updating at least one stored parameter based on the at least one notification.

55. The computer program of claim **52**, further comprising instructions for determining a location for information associated with the at least one notification; and instructions for retrieving the information based on the location.

56. The computer program of claim **52**, further comprising instructions for determining an interactive function to perform based on the at least one notification.

57. The computer program of claim **52**, wherein said instructions for filtering comprise instructions for filtering the notification message based on at least one of a system parameter and a user input parameter.

58. The computer program of claim **52**, further comprising instructions for storing the filtered notification message for later rendering.

59. At least one processor configured to perform a method for providing a notification system, the method comprising:

receiving a notification message comprising one or more notification parameters;

filtering the notification message based on at least one notification parameter to produce a filtered notification message;

processing the filtered notification message to determine at least one notification; and

rendering the at least one notification.

60. The method of claim **59**, wherein said receiving comprises receiving the notification message in a wireless broadcast.

61. The method of claim **59**, wherein said processing comprises updating at least one stored parameter based on the at least one notification.

62. The method of claim **59**, further comprising
determining a location for information associated with the at least one notification; and

retrieving the information based on the location.

63. The method of claim **59**, further comprising determining an interactive function to perform based on the at least one notification.

64. The method of claim **59**, wherein said filtering comprises the filtering notification message based on at least one of a system parameter and a user input parameter.

65. The method of claim **59**, further comprising storing the filtered notification message for later rendering.