

METHOD FOR DETECTING MALFUNCTION OF VALVE ON THE DOWNSTREAM SIDE OF THROTTLE MECHANISM OF PRESSURE TYPE FLOW CONTROL APPARATUS

Technical Field

[0001] The present invention relates to a method for detecting the malfunction of a valve installed on the downstream side of a throttle mechanism of a pressure type flow control apparatus by means of monitoring a flow output signal, and it is mainly directed at the use for fluid supply facilities with a pressure type flow control apparatus to be used with semiconductor manufacturing, food processing, chemical products-related facilities, and the like.

Technical Background

[0002] In recent years, a pressure type flow control apparatus has been increasingly used in gas supply facilities used with semiconductor manufacturing, chemical products-related facilities, and the like, replacing a thermal type flow control apparatus. The simple structure of a pressure type flow control apparatus makes it possible to reduce production costs and downsize the facilities. Furthermore, a pressure type flow control apparatus rivals, or exceeds, a thermal type flow control apparatus both in accuracy and responsiveness.

[0003] In these gas supply facilities, and the like, it is a common practice to regularly inspect devices and valves, in particular which constitute a gas supply facility, to see the operational conditions. Inspection activities on gas supply

facilities thus become indispensable for the stable supply of a gas from gas supply facilities.

[0004] In response to such a demand as described above, applicants of the present invention have developed a method for detecting the malfunction of a valve while gas is supplied using a pressure type flow control apparatus as shown in Figure 9, and disclosed the method in Japanese Patent Application No. 2005-253996. In particular, techniques in the aforementioned Japanese Patent Application No. 2005-253996 have made it possible to check operational conditions of valves V_1 , V_2 , V_3 , and to check for the existence of sheet leaks(hereinafter called a "check"), within a gas supply facility. As shown in Figure 9, the valves V_1 , V_2 , V_3 are checked without removing the valves V_1 , V_2 , V_3 from pipe passages, thus achieving excellent practical effects. In accordance with Figure 9, G_o designates a purge gas, G_p designates a process gas, FCS designates a pressure type flow control apparatus, 1a, 1b, 1c designate pipe passages, and E designates a process chamber.

[0005] In accordance with the gas supply facility shown in Figure 9, in order to determine whether valves V_1 , V_2 , V_3 are operating normally or not (i.e., being open or closed), checks are conducted by following the steps shown in Figure 10.

[0006] First, the malfunction check starts with Step So. Then, at Step S_1 , valve V_1 is closed, valve V_2 is switched from "open" to "closed", and valve V_3 is closed. After these operations, a pipe passage 1b on the downstream side of the FCS is filled with N_2 . Next, at Step S_2 , the displayed pressure P_1 of the FCS is checked to see if the increase/decrease ΔP_1 of the pressure P_1 is zero or not. In the

case that ΔP_1 is not zero and P_1 goes up, it is determined that there is an abnormal condition with either valve V_1 or valve V_2 , or both valves V_1 and V_2 (i.e., either sheet leaks or operational irregularity is present). And, in the case that P_1 goes down, it is determined that V_3 is abnormal (i.e., sheet leaks or operational irregularity are present) (Step S3).

[0007] Next, at Step S4, a process gas (i.e., a use gas) G_p is flowed into the FCS by making valve V_1 open and valve V_2 close, and the displayed pressure P_1 of the FCS is checked at Step S5. In the case when a rise of P_1 is observed, it is determined that V_1 is functioning normally (Step S7); on the other hand, in the case that there is no rise of P_1 , it is determined that valve V_1 is malfunctioning (Step S6), thus the operational conditions of V_1 are confirmed. Then, after V_1 is closed and V_2 is opened at Step S8, the displayed pressure P_1 of the FCS is checked (Step S9). In the case when there is no rise of P_1 , it is determined that valve V_2 is malfunctioning (Step S10), thus the operational conditions of valve V_2 are confirmed. On the other hand, when a rise of P_1 is observed, it is determined that valve V_2 is functioning normally (Step S11).

[0008] Then, at Step S12, it is determined whether or not the malfunction of valves found at the Step S2 is applicable to the operational malfunction of a valve V_3 . Specifically, if the result of Step S2 is "NO" (that is, one of valves V_1 , V_2 , V_3 is malfunctioning), and valves V_1 and V_2 are functioning normally, it is determined that a valve V_3 is malfunctioning (Step S13). If the result of Step S2 is "YES", then, it is determined that all the valves V_1 , V_2 , V_3 are functioning normally (Step S14).

[0009] After it is determined that the aforementioned valves V_1 , V_2 , V_3 are all

operating normally, sheet leaks are then checked at Step S15. To determine whether the operational conditions of the valves are normal or not, there exist prerequisites that

(a) there should be no outside leaks (i.e., leaks from joints, bonnets, and the like) with valves V_1 , V_2 , V_3 , FCS, pipe passages 1a, 1b, 1c, and the like, except sheet leaks,

(b) driving parts of all valves are under normal operation,

(c) the FCS is functioning normally, and

(d) V_1 and V_2 are not simultaneously released.

[0010] However, as shown in Figure 11, the system is constituted so that, with a pressure type flow control apparatus FCS, a flow rate of a gas passing through a throttle mechanism is computed on the basis of the gas pressure P_1 and gas temperature T_1 on the upstream side of a throttle mechanism 8 such as an orifice, a sonic nozzle, or the like, (Japanese Unexamined Patent Application Publication No. 8-38546 and others). Therefore, for example, even when the valve V_3 on the downstream side of the throttle mechanism is closed, and the flow rate of a gas passing through the throttle mechanism 8 is found to be zero, a gas flow rate Q_f is computed by a flow rate computation apparatus 20 of a flow rate computation circuit 13 if gas pressure P_1 is applied to pipe passage 3, thus what is computed is outputted as a flow rate output signal Q_o . Specifically, even when there occurs no gas flow due to the malfunction of releasing valve V_3 , a flow rate output signal G_o is outputted to the outside. In Figure 11, 2 designates a control valve, 12 designates a flow rate output circuit, 14 designates a flow rate setting circuit, 16 designates a computation control circuit,

21 designates a comparison circuit, and Q_y designates a control signal ($Q_y = Q_e - Q_f$).

[0011] As a result, for example, at the time when opening/closing operations of the valve V_3 on the downstream side of the FCS are conducted while the gas supply facility is at work, there is no way to find out directly if a malfunction of the releasing operations of the valve V_3 exists or not.

[0012] The reason for this is, as described above, that even when a flow rate of gas passing through the throttle mechanism 8 is found to be zero (a valve V_3 is in the state of closure), a flow rate output signal Q_o is outputted to the outside if there exists pressure P_1 on the upstream side of the throttle mechanism 8. In other words, it is assumed that valve V_3 is kept open all the time from the viewpoint of a flow rate output signal Q_o even when valve V_3 actually remains closed due to malfunction of the valve V_3 .

[0013] Patent Document 1: Japanese Unexamined Patent Application Publication No. 8-338546

Patent Document 2: Japanese Unexamined Patent Application Publication No. 2000-66732

Disclosure of the Invention

Object of the Invention

[0014] It is an object of the present invention to provide a method for detecting the malfunction of a valve on the downstream side of a throttle mechanism of a pressure type flow control apparatus with which the aforementioned problem of detecting the malfunction of the valve on the downstream side of the throttle

mechanism of the pressure type flow control apparatus occurs; that is, the problem that accurate determination of the malfunction at the time of releasing operations of the valve on the downstream side of the throttle mechanism cannot be performed by using the pressure P_1 on the upstream side of the throttle mechanism of the pressure type flow control apparatus (or a flow rate output signal Q_o) due to the structure of a pressure type flow control apparatus so that a flow rate output signal Q_o is outputted externally due to the pressure P_1 on the upstream side of the throttle mechanism when there exists no flow of a gas passing through the throttle mechanism. This problem can be overcome, thus achieving a prompt, accurate determination of malfunction of the opening operation of the valve on the downstream side of the throttle mechanism on the basis of changes of the flow rate output signal Q_o from the pressure type flow control apparatus at the time when the valve on the downstream side of the throttle mechanism is undergoing opening/closing operations without the pressure type flow control apparatus having to be converted to a malfunction detection mode by the gas supply facility.

Means to Achieve the Object

[0015] The present invention, as claimed in Claim1, is used in a gas supply facility wherein the pressure type flow control apparatus is so made that the fluid pressure P_1 is adjusted to make the flow rate control signal Q_y to be zero by computing the flow rate Q_f of fluid passing through the throttle mechanism by using the fluid pressure P_1 on the upstream side of the throttle mechanism, and a control valve 2 on the upstream side of the throttle mechanism is operated to

open or close by making a difference between the flow rate computation value Q_f of the fluid and a flow rate setting value Q_e to be a flow rate control signal Q_y . Thus, the flow rate computation value Q_f of the fluid is outputted as a flow rate output signal Q_o . A valve on the downstream side of a throttle mechanism of the pressure type flow control apparatus is released and a flow rate setting value Q_e to be inputted to a pressure type flow control apparatus is changed in order to detect the magnitude of changes ΔV of the aforementioned flow rate output signal Q_o while the flow rate setting signal Q_e changes. This determines whether the releasing operations of the valve on the downstream side of the throttle mechanism are functioning normally in the case that the magnitude ΔV of changes of the flow rate output signal Q_o is found to be above the predetermined value. On the other hand, the releasing operations are malfunctioning in the case wherein the magnitude ΔV of changes is found to be below the predetermined value.

[0016] The present invention as claimed in Claim 2 according to Claim 1 is so made that, when changing a flow rate setting value Q_e to be inputted to a pressure type flow control apparatus, a flow rate setting value Q_e' larger than a steady-state flow rate setting value Q_e'' or a flow rate setting value Q_e' smaller than a steady-state flow rate setting value Q_e'' is inputted as a flow rate setting value Q_e .

[0017] The present invention as claimed in Claim 3 is used in a gas supply facility wherein a pressure type flow control apparatus is so made that fluid pressure P_1 is adjusted to make a flow rate control signal Q_y to be zero by means that a flow rate Q_f of fluid passing through a throttle mechanism is

computed by using the fluid pressure P_1 on the upstream side of the throttle mechanism and a control valve 2 on the upstream side of the throttle mechanism is opened/closed by making the difference between the flow rate computation value Q_f and flow rate setting value Q_e to be a flow rate control signal Q_y , thus the aforementioned flow rate computation value Q_f of fluid is outputted as a flow rate output signal Q_o , a valve on the downstream side of a throttle mechanism of the pressure type flow control apparatus is closed and a flow rate setting value Q_e to be inputted to the pressure type flow control apparatus is set to zero, to detect the magnitude ΔV of changes of the aforementioned flow rate output signal Q_o while it is changing after the flow rate setting value Q_e having been set to zero. This distinguishes the situation where the releasing operations of the valve on the downstream side of the throttle mechanism are functioning normally, in which case the magnitude ΔV of changes of the flow rate output signal Q_o is found to be above the predetermined value, from the situation where the releasing operations are malfunctioning, in which case the magnitude ΔV of changes is found to be below the predetermined value.

[0018] The present invention as claimed in Claim 4 according to Claim 3 is so made that the flow rate setting value Q_e to be inputted to the pressure type flow control apparatus concurrently with the closure of the valve on the downstream side of the throttle mechanism or with the delay of a given time Δt is set to zero.

[0019] The present invention, as claimed in Claim 5, is used in a gas supply facility for which a pressure type flow control apparatus is so made that fluid pressure P_1 is adjusted to make a flow rate control signal Q_y to be zero by computing the flow rate Q_f of fluid passing through a throttle mechanism by

using the fluid pressure P_1 on the upstream side of the throttle mechanism, and a control valve 2 on the upstream side of the throttle mechanism is operated to open or close by making a difference between the flow rate computation value Q_f of the fluid and a flow rate setting value Q_e to be the flow rate control signal Q_y . Thus, the flow rate computation value Q_f of the fluid is outputted as a flow rate output signal Q_o , a valve on the downstream side of the throttle mechanism of the pressure type flow control apparatus is released and a flow rate setting signal Q_e is inputted to the pressure type flow control apparatus, in order to detect the magnitude ΔV of changes of the flow rate output signal Q_o after the valve on the downstream side of the throttle mechanism has been released. The releasing operations of the valve on the downstream side of the throttle mechanism are determined to be functioning normally in the case that the magnitude ΔV of changes of the flow rate output signal Q_o is found to be above the predetermined value; on the other hand, the releasing operations are determined to be malfunctioning in the case that the magnitude ΔV of changes is found to be below the predetermined value.

[0020] The present invention as claimed in Claim 6 according to Claim 5 is so made that the magnitude of the drop rate of the flow rate output signal Q_o is detected by means that the flow rate setting signal Q_e is inputted to the pressure type flow control apparatus with a delay of the predetermined time Δt after the command to release the valve on the downstream side of the throttle mechanism has been transmitted.

[0021] The present invention as claimed in Claim 7 according to either one of Claim 1 to Claim 6 is so made that an orifice or a sonic nozzle is used for the

throttle mechanism.

Effects of the Invention

[0022] The present invention is so constituted that changes are made by means that a flow rate setting value Q_e of a pressure type flow control apparatus is switched to "ON" or "OFF" either concurrently with opening or closing operations of a valve on the downstream side of a throttle mechanism of a pressure type flow control apparatus, or with a delay of a given time Δt after opening/closing operations of the valve on the downstream side having been made, thus determining whether the valve on the downstream side of the throttle mechanism is functioning normally or not by observing the changes of a flow rate output signal Q_o between opening or closing operations of the valve on the downstream side of the throttle mechanism and also between "ON" or "OFF" of the flow rate setting value Q_e . As a result, it can be determined whether opening operations of the valve on the downstream side of the throttle mechanism of the pressure type flow control mechanism are functioning normally or not, easily and simply, while a gas supply facility is at work. This is accomplished without installing or adding an extra testing device and without the pressure type flow control apparatus being switched to a malfunction detecting mode for the gas supply facility, but simply by monitoring a flow rate output signal Q_o of the pressure type flow control apparatus. Thus, the problem that "the existence of a flow rate output signal Q_o of a pressure type flow control apparatus does not lead directly to the opening operations of a valve on the downstream side of a throttle mechanism" is overcome easily.

Brief Description of Drawings

[0023] Figure 1 shows one example of a pressure type flow control apparatus FCS used with the present invention.

Figure 2 is an execution explanatory drawing of a method for detecting malfunction of a valve downstream of a throttle mechanism with the pressure type flow control apparatus in accordance with Embodiment 1 of the present invention.

Figure 3 shows the relationship of timing of a flow rate setting input signal Q_e to the pressure type flow control apparatus FCS, a valve releasing current IV_2 to a valve V_2 on the downstream side of the throttle mechanism and a flow rate output signal Q_o from the FCS with Embodiment 1, where

(a) shows the case when the flow rate setting signal Q_e' at the time of testing is made to be larger than a steady-state flow rate setting signal Q_e'' and

(b) shows the case when the flow rate setting signal Q_e' at the time of testing is made to be smaller than the steady-state flow rate setting signal Q_e'' .

Figure 4 is an execution explanatory drawing of a method for detecting the malfunction of the valve on the downstream side of the throttle mechanism with the pressure type flow control apparatus, in accordance with Embodiment 1 of the present invention.

Figure 5 shows the relationship of timing of the flow rate setting input signal Q_e to the FCS, the electro-magnetic current IV_2 to an electro-magnetic valve EV which actuates valve V_2 downstream of the throttle mechanism, and the flow rate output signal Q_o from the FCS with Embodiment 2, where

(a) shows the case when the closure of the valve V_2 on the downstream side of the throttle mechanism and the closure of the FCS are conducted nearly at the same time, and

(b) shows the case when the flow rate setting input Q_e to the FCS is made to be zero (the closure of the FCS) with a delay of time $\Delta t = 0.2$ sec after the closure of the valve on the downstream side of the throttle mechanism respectively.

Figure 6 is an explanatory drawing to show the relationship of a drop rate of a flow rate output signal Q_o of the FCS by means of the multi-step method shown in Figure 5(b) and a time Δt_V with a delay in the operation of the valve V_2 on the downstream side of a throttle mechanism.

Figure 7 is an explanatory drawing similar to Figure 6 with Embodiment 3 (the case when the malfunction is determined from the rate of changes of a flow rate output signal Q_o of the FCS at the time of start-up of a pressure type flow control apparatus FCS by means of the multi-step method).

Figure 8 shows the state of changes of the flow rate output signal Q_o of the FCS in Embodiment 3 where

(a) flow rate setting input Q_e is set to 100% (5V),

(b) flow rate setting input Q_e is set to 50%, and

(c) flow rate setting input Q_e is set to 5%

(in the case of one (1) valve on the downstream side of the throttle mechanism and in the case of four (4) valves in parallel).

Figure 9 shows one example of a gas supply facility for which a conventional pressure type flow control apparatus is used.

Figure 10 is a flow chart of a method for detecting the malfunction of a

valve with a gas supply facility using a pressure type flow control apparatus incorporating the previous invention.

Figure 11 is a basic block diagram of a conventional pressure type flow control apparatus.

Reference Characters and Numerals

[0024] Qe A flow rate setting value (a flow rate setting signal)

Qe" A steady-state flow rate setting value

Qe' A flow rate setting value

Qc A flow rate computation value

Qf A switching flow rate computation value

Qo A flow rate output signal

Qy A flow rate control signal

P₁ Gas pressure on the upstream side of a throttle mechanism

K A flow rate conversion rate

IV₂ A current for operating a valve V₂

ΔV Deviation of a flow rate output signal at the time when a valve V₂ on the downstream side of a throttle mechanism is not released

Qo' A flow rate output at the time when a valve V₂ on the downstream side of a throttle mechanism is not released

Qo A flow rate output at the time when a valve V₂ on the downstream side of a throttle mechanism is normally functioning

EV An electro-magnetic valve

U A pressure supply line for operating a valve

- Pe A vacuum pump
- VR A flow rate valve
- Pb Baratron vacuum pump
- PG A process gas
- N₂ A gas for operating a valve
- C A chamber
- V₁, V₂ Air actuating valves
- PLC A programmable controller
- PL A data logger
- S A gas supply source (N₂)
- Q_e" A steady-state flow rate
- Q_e' A set flow rate different from a steady-state flow rate
- 1 A gas supply
- 2 A control valve
- 3 A pipe passage on the upstream side of a throttle mechanism
- 4 A valve actuating part
- 5 A pipe passage on the downstream side of a throttle mechanism
- 6 A pressure detector
- 7 A temperature detector
- 8 A throttle mechanism
- 9 A gas outlet
- 10 An amplifier
- 11 An amplifier
- 12 A flow rate output circuit

- 13 A flow rate computation circuit
- 14 A flow rate setting circuit
- 15 A flow rate conversion circuit
- 16 A computation control circuit
- 17 An A/D converter
- 18 An A/D converter
- 19 A temperature compensation circuit
- 20 A computation circuit
- 21 A comparison circuit
- 22 An amplifier

Best Mode for Carrying Out the Invention

[0025] Preferred embodiments in accordance with the present invention are explained hereinafter in reference to drawings. Figure 1 shows the components of a pressure type flow control apparatus used with the present invention. Figure 2 is an illustration of a method for detecting malfunction of a valve on the downstream side of a throttle mechanism in accordance with Embodiment 1 of the present invention.

[0026] Referring now to Figure 1, the major part of a pressure type flow rate control apparatus FCS comprises a gas supply 1, a control valve 2, a valve actuating part 4, a pressure detector 6, a throttle mechanism 8, a gas outlet 9, a flow rate output circuit 12, a flow rate computation circuit 13, a flow rate setting circuit 14, a computation control circuit 16 and others. In accordance with Figure 1, 3 designates a pipe passage on the upstream side of a throttle

mechanism, 5 designates a pipe passage on the downstream side of a throttle mechanism, 7 designates a temperature detector, 15 designates a flow rate conversion circuit, 10, 11, and 22 designate amplifiers, 17 and 18 designate A/D converters, 19 designates a temperature compensation circuit, 20 designates a flow rate computation device, 21 designates a comparison circuit, Q_c designates a computation flow rate signal, Q_f designates a switching computation flow rate signal, Q_e designates a flow rate setting signal, Q_o designates a flow rate output signal, Q_y designates a flow rate control signal, P_1 designates gas pressure on the upstream side of a throttle mechanism, and k designates a flow rate conversion rate. With preferred embodiments shown in Figure 1, Figure 2 and others, a so-called orifice has been used for throttle mechanism 8. However, it goes without saying that the orifice can be replaced by a sonic nozzle or a diaphragm valve.

[0027] The aforementioned pressure type flow control apparatus FCS shown in Figure 1 is mainly used in the case wherein the ratio P_2/P_1 of the gas pressure P_1 on the upstream side of the throttle mechanism and the gas pressure P_2 on the downstream side of the throttle mechanism is equal to or lower than the critical value of a fluid (that is, at the time when the gas flow is in the critical state). A flow rate Q_c of gas passing through the throttle mechanism 8 is given by Equation $Q_c = KP_1$ (where K is a proportionality constant). A pressure type flow control apparatus is used to control the flow rate of a gas, which can exhibit both critical and non-critical states of flow. With some other types, the flow rate Q_c of gas passing through throttle mechanism 8 is given by Equation $Q_c = KP_2^m (P_1 - P_2)^n$ (where K is a proportionality constant, m and n constants, and P_2 the

gas pressure on the downstream side of a throttle mechanism). However, the fundamental constitutions of these other flow control systems are the same as that of the pressure type flow control apparatus FCS shown in Figure 1. Therefore, explanations are omitted herewith.

[0028] In the pressure type flow control apparatus FCS, the setting value of the control flow rate is given by a voltage value as the flow rate setting signal Q_e . For example, when the pressure control range 0~3 (kgf/cm² abs) of the pressure P_1 on the upstream side is expressed by the voltage range 0~5V, it means that $Q_e = 5V$ (a full scale value) is the flow rate Q_c under the pressure P_1 of 3 (kgf/cm² abs). More specifically, when the conversion rate k of a flow rate conversion circuit 15 is set at 1 and the flow rate setting signal $Q_e=5V$ is inputted, a switching computation flow rate signal Q_f ($Q_f=kQ_c$) becomes 5V, thus the control valve 2 is operated for opening/closing until the pressure P_1 on the upstream side gets to 3 (kgf/cm²abs). This means that gas of a flow rate $Q_c=KP_1$, corresponding to $P_1 = 3$ (kgf/cm²abs), flows through throttle mechanism 8.

Embodiment 1

[0029] Figure 2 is an explanatory drawing of a test unit used for executing a method for detecting the malfunction of a valve on the downstream side of a throttle mechanism in accordance with Embodiment 1 of the present invention. Namely, as shown in Figure 2, the test unit is so constituted that a gas supply valve V_1 and a valve V_2 on the downstream side of the throttle mechanism are connected to the upstream side and downstream side of a pressure type flow

control apparatus FCS respectively, thereon a programmable controller PLC and a data logger DL are set, and following the prescribed program from the programmable controller PLC, a flow rate setting signal Q_e is supplied to valves V_1 , V_2 and a flow rate setting circuit 14 of a pressure type flow control apparatus FCS, and a valve releasing signal IV_2 to a valve V_2 , a flow rate setting signal Q_e to the FCS and a flow rate output signal Q_o from the FCS are recorded on the data logger respectively. With Figure 2, S designates a gas source and C designates a chamber.

[0030] Specifically, such a test system as shown in Figure 2 has been formed in order to detect the malfunction of valve V_2 on the downstream side of the throttle mechanism of the pressure type flow control apparatus FCS (operations from closure to opening not being able to be performed), and as shown in Figure 3, first a flow rate value Q_e' which differs from a steady-state flow rate value Q_e'' is sent as a flow rate setting signal Q_e to the FCS, and then the flow rate setting signal Q_e equal to the steady-state flow rate value Q_e'' is inputted. Figure 3(a) shows the case wherein the flow rate setting value Q_e' , which differs from the steady-state flow rate value Q_e'' , is made to be larger than a steady-state flow rate value Q_e'' , and Figure 3(b) shows the case wherein the flow rate setting value Q_e' , which differs from a steady-state flow rate value Q_e'' , is made to be smaller than the steady-state flow rate value Q_e'' .

[0031] As shown in Figure 3, when the flow rate setting signal Q_e is inputted to the FCS and a releasing operation current IV_2 (an exciting current) is supplied concurrently to the valve V_2 on the downstream side of the throttle mechanism, the flow rate output Q_o from the pressure type flow control apparatus FCS

shows changes as shown by the lowermost parts of Figure 3(a) and (b). Specifically, a deviation ΔV in a flow rate output occurs between a flow rate output Q_o' in the case that the valve V_2 on the downstream side of the throttle mechanism is not released and a flow rate output Q_o'' in the case that the valve V_2 is released normally, thus making it possible to determine whether the valve V_2 on the downstream side of the throttle mechanism has been normally released or not, by means of monitoring the flow rate output signal Q_o from the pressure type flow control apparatus FCS.

[0032] Specifically, at the preparatory stage for finishing a process treatment operation or starting a process treatment operation for which a chamber C is used, the flow rate setting signal Q_e and the valve releasing current I_{V_2} are supplied to a pressure type flow control apparatus FCS and to a valve V_2 on the downstream side of a throttle mechanism, respectively, through the mediation of the programmable controller PLC, and then the state of changes of the flow rate output signal Q_o from the FCS is observed, thus determining whether valve V_2 on the downstream side of the throttle mechanism has been released normally, if the deviation ΔV is found to be above the set value, or whether valve V_2 has not been released properly or malfunctioning in the releasing operation, if the aforementioned deviation ΔV is found to be below the prescribed value.

Embodiment 2

[0033] Embodiment 2 is made so that an operational malfunction of a valve V_2 on the downstream side of a throttle mechanism is detected at the time of the completion of a process treatment. Figure 4 is an explanatory drawing of a test

system used with Embodiment 2. In Figure 4, EV designates an operational electro-magnetic valve, V₁ designates a valve on the FCS upstream side, Pe designates a vacuum pump, Pb designates a Baratron, VR designates a flow rate valve, N₂ designates an operational gas, and PG designates a process gas.

[0034] The detection of the operational malfunction of the valve V₂ on the downstream side of the throttle mechanism has been performed in a manner such that changes of a FCS flow rate output signal Q_o are monitored after a flow rate setting signal Q_e to the FCS is set to zero (the FCS shutdown) at the time when a treatment process is terminated, for two distinct cases. In one case, as shown in Figure 5(a), the shutdown of a flow rate setting signal Q_e of the pressure type flow control apparatus FCS and the closure of the valve V₂ on the downstream side of the throttle mechanism are conducted concurrently (hereinafter called a normal step), and in the other case, as shown in Figure 5(b), some delay of time Δt is made between the closure of the valve V₂ on the downstream side of the throttle mechanism and the shutdown of a flow rate setting signal of the FCS (hereinafter called a multi-step).

[0035] As shown in Figure 5(a) and (b), it is assumed that there exists a malfunction in releasing of the valve V₂ on the downstream side of the throttle mechanism in the case that the flow rate output signal Q_o shows no drop after the closure of the valve V₂ on the downstream side of a throttle mechanism and the closure of the FCS (the closure of the control valve 2 of the FCS) and the same state of flow rate output signal Q_o' is maintained. The reason for this assumption is that the fact that there is seen a flow rate output Q_o' without the flow rate output Q_o not becoming zero means there remains a gas pressure

between throttle mechanism 8 and the valve V_2 on the downstream side of the throttle mechanism, and there is seen no decrease in the remaining pressure (that is, a valve V_2 not releasing the pressure).

[0036] With regard to actually determining the malfunction of a valve, it is required that first the internal capacity of a pressure supply line U for operating a valve between an electro-magnetic valve EV and the valve V_2 on the downstream side of the throttle mechanism, and also the delay time between the input of a current signal for closing the valve V_2 on the downstream side of the throttle mechanism and an actual closing operation of valve V and others are taken into consideration, and then a threshold value of the drop rate of a flow rate output signal Q_o of the FCS is established; thus it is determined that there exists a malfunction with the releasing operation of a valve V_2 on the downstream side of the throttle mechanism in the case that the drop rate of the flow rate output signal Q_o is below the prescribed drop rate.

[0037] Figure 6 shows the relationship of the difference Δt_V between the closing operation signal input for the valve V_2 on the downstream side of the throttle mechanism and an actual operating time and also the flow rate output Q_o of the FCS (the pressure P_1 on the upstream side of a throttle mechanism) and the pressure P_2 on the downstream side of a throttle mechanism. As apparent from Figure 6(a) and (b), in the case that the aforementioned Δt_V is small (Figure 6(b)), the amount of change of a flow rate output Q_o of the FCS (the pressure P_1 on the upstream side of a throttle mechanism) becomes small, thus making it difficult to determine whether a valve V_2 is malfunctioning by monitoring the drop rate of the flow rate output signal Q_o .

[0038] It goes without saying that the magnitude of Δt_V differs largely with valve V_2 , electro-magnetic valve EV, the internal capacity of a pressure supply line U for operating a valve, and the like, and further that changes of the pressure P_2 on the downstream side of the throttle mechanism varies largely according to the conditions, such as the flow rate range in use of a pressure type flow control apparatus, the pressure on the camber side, and the like.

Embodiment 3

[0039] With Embodiment 3, the malfunction of a valve V_2 on the downstream side of a throttle mechanism (releasing not functioning) is detected by monitoring a FCS flow rate output signal at the time of a startup of a pressure type flow control apparatus FCS. This is mainly used to detect any operational malfunction of valve V_2 on the downstream side of the throttle mechanism during the preparatory stage of starting up a process system.

[0040] A test device used with Embodiment 3 is same as that shown in Figure 4. Specifically, with Embodiment 3, the malfunction of a releasing operation of a valve V_2 on the downstream side of the throttle mechanism is determined by monitoring the drop quantity of a FCS flow rate output signal Q_o which occurs within a time Δt (a delay time $\Delta t=0.2$ sec) from a valve V_1 on the primary side of the pressure type flow control apparatus FCS, and valve V_2 on the downstream side of the throttle mechanism is released until a flow rate setting signal Q_e being inputted to the FCS and by making the drop quantity as a basis.

[0041] Figure 7 shows the relationship of the FCS flow rate output signal Q_o , a delay time $\Delta t=0.2$ sec, a delay time Δt_V in releasing valve V_2 on the

downstream side of the throttle mechanism, and the like, with Embodiment 3. At the preparatory stage of starting up the process, when valve V_1 on the upstream side of the FCS and valve V_2 on the downstream side of the throttle mechanism are made open, and the FCS is operated with a delay time $\Delta t = 0.2$ sec (a flow rate setting signal Q_e in), the FCS flow rate output signal Q_o drops during the delay time Δt in the case that valve V_2 on the downstream side of a throttle mechanism is functioning normally for a releasing operation, and conversely there would be no changes in the FCS flow rate output signal Q_o during a delay time Δt when valve V_2 on the downstream side of the throttle mechanism is not functioning normally for the releasing operation.

[0042] As with Embodiment 2, a degree (a drop rate) of change of the aforementioned FCS flow rate output signal varies largely depending on the delay time in releasing valve V_2 on the downstream side of the throttle mechanism. Accordingly, it is found that the drop rate during the delay time Δt of the FCS flow rate output signal Q_o is largely affected by the length of pressure supply line U for operating valve V_2 on the downstream side of the throttle mechanism, the type of an electro-magnetic valve EV, the flow rate setting range for the pressure type flow control apparatus FCS, and the like.

[0043] Figure 8 shows the results of monitoring the state of the drop of the flow rate output signal Q_o when a flow rate setting signal Q_e of a pressure type flow control apparatus FCS and the number of valves V_2 on the downstream side of a throttle mechanism are changed. A standard type with a rated flow rate of 1SLM is employed for the pressure type flow control apparatus FCS. A valve having a C_v value of 0.1 and a valve having a C_v value of 0.2 are used for valves

V₁ and V₂ respectively. Furthermore, pressure supply line U for operating valves V₁ and V₂ has an internal diameter of 2.5mm ϕ and the length of 1m. A flow rate control valve VR and a vacuum pump Pe are so adjusted that pressure P₂ downstream of the throttle mechanism is 120 Torr when N₂ =2SLM is supplied.

[0044] As apparent from Figure 8, the average pressure drop rate of the FCS flow rate output signal Q_o was 89.9% (with one valve V₂) to 79.4% (with four (4) valves V₂) when the setting flow rate signal Q_e of the FCS was Q_e=100%; the results were 85.4% (V₂=1) to 79.7% (V₂=4) when Q_e=50%; the results were 86.3% (V₂=1) to 70.6% (V₂=4) when Q_e=5%. It is thus possible to detect the malfunction of a valve (releasing not functioning) in any case. A pressure drop rate is obtained by computing the value as $(B - A) / A \times 100\%$, where B is a flow rate output signal Q_o of the FCS after completing the process, and A is a value of a flow rate output signal Q_o' after 0.2 sec at the time of a multi-step (see Figure 8(a)).

Feasibility of Industrial Use

[0045] The present invention can be applied to any gas supply facility as long as a pressure type flow control apparatus FCS is being used. Releasing operations of a valve on the downstream side of a throttle mechanism of a pressure type flow control apparatus FCS can be accurately detected with the conditions of changes of a flow rate output signal Q_o when a flow rate setting input Q_e of a pressure type flow control apparatus FCS is changed.

Scope of Claim

[1] A method for detecting the malfunction of a valve on the downstream side of a throttle mechanism of a pressure type flow control apparatus characterized by that it is so constituted that with a gas supply facility for which a pressure type flow control apparatus is so made that the fluid pressure P_1 is adjusted to make a flow rate control signal Q_y to be zero by means that the flow rate Q_f of a fluid passing through a throttle mechanism is computed by using the fluid pressure P_1 on the upstream side of a throttle mechanism and a control valve 2 on the upstream side of a throttle mechanism is operated for opening/closing by making the difference between said flow rate computation value Q_f of a fluid and flow rate setting value Q_e to be a flow rate control signal Q_y , thus the aforementioned flow rate computation value Q_f of a fluid being outputted as a flow rate output signal Q_o , a valve on the downstream side of a throttle mechanism of a pressure type flow control apparatus is released and a flow rate setting value Q_e to be inputted to a pressure type flow control apparatus is changed to detect the magnitude of changes ΔV of the aforementioned flow rate output signal Q_o while said flow rate setting signal Q_e changes so that it is determined that the releasing operations of a valve on the downstream side of a throttle mechanism are functioning normally in the case that the magnitude ΔV of changes of said flow rate output signal Q_o is found to be above the predetermined value, while the releasing operations are malfunctioning in the case that the magnitude ΔV of changes is found to be below the predetermined value.

[2] A method for detecting the malfunction of a valve on the downstream

side of a throttle mechanism of a pressure type flow control apparatus as claimed in Claim 1 wherein it is so made that at the time of changes of a flow rate setting value Q_e to be inputted to a pressure type flow control apparatus, a flow setting value Q_e' larger than a steady-state flow rate setting value Q_e'' or a flow rate setting value Q_e' smaller than a steady-state flow rate setting value Q_e'' is inputted as a flow rate setting value Q_e .

[3] A method for detecting the malfunction of a valve on the downstream side of a throttle mechanism of a pressure type flow control apparatus characterized by that it is so constituted that with a gas supply facility for which a pressure type flow control apparatus is so made that the fluid pressure P_1 is adjusted to make a flow rate control signal Q_y to be zero by means that the flow rate Q_f of a fluid passing through a throttle mechanism is computed by using the fluid pressure P_1 on the upstream side of a throttle mechanism and a control valve 2 on the upstream side of a throttle mechanism is operated for opening/closing by making the difference between said flow rate computation value Q_f of a fluid and flow rate setting value Q_e to be a flow rate control signal Q_y , thus the aforementioned flow rate computation value Q_f of a fluid being outputted as a flow rate output signal Q_o , a valve on the downstream side of a throttle mechanism of a pressure type flow control apparatus is closed and a flow rate setting value Q_e to be inputted to a pressure type flow control apparatus is made to be zero, to detect the magnitude ΔV of changes of the aforementioned flow rate output signal Q_o while it is changing after said flow rate setting value Q_e having made to be zero so that it is determined that the releasing operations of a valve on the downstream side of a throttle mechanism

are functioning normally in the case that the magnitude ΔV of changes of said flow rate output signal Q_o is found to be above the predetermined value, while the releasing operations are malfunctioning in the case that the magnitude ΔV of changes is found to be below the predetermined value.

[4] A method for detecting the malfunction of a valve on the downstream side of a throttle mechanism of a pressure type flow control apparatus as claimed in Claim 3 wherein it is so made that a flow rate setting value Q_e to be inputted to a pressure type flow control apparatus concurrently with the closure of a valve on the downstream side of a throttle mechanism or with the delay of a given time Δt is made to be zero.

[5] A method for detecting the malfunction of a valve on the downstream side of a throttle mechanism of a pressure type flow control apparatus characterized by that it is so constituted that with a gas supply facility for which a pressure type flow control apparatus is so made that the fluid pressure P_1 is adjusted to make a flow rate control signal Q_y to be zero by means that the flow rate Q_f of a fluid passing through a throttle mechanism is computed by using the fluid pressure P_1 on the upstream side of a throttle mechanism and a control valve 2 on the upstream side of a throttle mechanism is operated for opening/closing by making the difference between said flow rate computation value of a fluid and flow rate setting value Q_e to be a flow rate control signal Q_y , thus the aforementioned flow rate computation value Q_f of a fluid being outputted as a flow rate output signal Q_o , a valve on the downstream side of a throttle mechanism of a pressure type flow control apparatus is released and a flow rate setting signal Q_e is inputted to a pressure type flow control apparatus,

to detect the magnitude ΔV of changes of the aforementioned flow rate output signal Q_o after the aforementioned valve on the downstream side of a throttle mechanism had been released so that it is determined that the releasing operations of a valve on the downstream side of a throttle mechanism are functioning normally in the case that the magnitude ΔV of changes of said flow rate output signal Q_o is found to be above the predetermined value, while the releasing operations are malfunctioning in the case that the magnitude ΔV of changes is found to be below the predetermined value.

[6] A method for detecting the malfunction of a valve on the downstream side of a throttle mechanism of a pressure type flow control apparatus as claimed in Claim 5 wherein it is so made that the magnitude of the drop rate of a flow rate output signal Q_o is detected by means that a flow rate setting signal Q_e is inputted to a pressure type flow control apparatus with a delay of the predetermined time Δt after the command to release a valve on the downstream side of a throttle mechanism having been transmitted.

[7] A method for detecting the malfunction of a valve on the downstream side of a throttle mechanism of a pressure type flow control apparatus as claimed in Claim 1, Claim 2, Claim 3, Claim 4, Claim 5 or Claim 6 wherein it is so made that an orifice or a sonic nozzle is used for a throttle mechanism.