

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
12 March 2009 (12.03.2009)

PCT

(10) International Publication Number
WO 2009/030474 A1

(51) International Patent Classification:
E06B 9/174 (2006.01)

(74) Agents: SMITH, Samuel, Leonard et al.; J.A. Kemp & Co., 14 South Square, Gray's Inn, London WC1R 5JJ (GB).

(21) International Application Number:
PCT/EP2008/007204

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(22) International Filing Date:
3 September 2008 (03.09.2008)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
07253547.9 7 September 2007 (07.09.2007) EP

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (for all designated States except US): **HUNTER DOUGLAS INDUSTRIES B.V.** [NL/NL]; Piekstraat 2, NL-3071 EL Rotterdam (NL).


(72) Inventor; and

(75) Inventor/Applicant (for US only): **KOOP, Lars** [DE/DE]; Schiffdorfer Grenzweg 34, 27574 Bremerhaven (DE).

Published:
— with international search report

(54) Title: UNIVERSAL CONNECTOR

Fig. 1.



(57) Abstract: A universal connector (5) is provided for connecting an architectural covering to an architectural surface. The connector has an adaptor plate (6) that is substantially circular and has one or more radially outwardly projecting flanges (16) and is arranged to be inserted into a ring-shaped engagement member (7) having one or more openings (18) in a front cover (17). The adaptor plate and the engagement member are configured such that the adaptor plate may be inserted into the engagement member by aligning the one or more flanges of the adaptor plate with a respective opening in the front cover of the engagement member and removal of the adaptor plate from the engagement member may subsequently be prevented by a partial rotation of the adaptor plate relative to the engagement member.