

ELECTRONIC TEST HEAD MANIPULATOR

FIELD OF THE INVENTION

This invention relates to the field of art of
5 electronic test head positioners.

BACKGROUND OF THE INVENTION

In the automatic testing of integrated circuits
(IC) and other electronic devices, special device
handlers have been used which brings the device to the
10 proper temperature and places the device to be tested in
position. The electronic testing itself is provided by a
large and expensive automatic testing system which

2-1299022

includes a test head which has been required to connect to and dock with the device handler. In such testing systems, the test head has usually been very heavy — on the order of 40 to 300 kilograms. The reason for this heaviness is that the test head uses precision high frequency control and data signals so that the electronic circuits may be located as close as possible to the device under test. Accordingly, the test head has been densely packaged with electronic circuits in order to achieve the accurate high speed testing of the sophisticated devices.

Test head positioner systems may be used to position the test head with respect to the device handler. When the test head is accurately in position with respect to the device handler, the test head and the device handler are said to be aligned. When the test head and device handler are aligned, the fragile test head and device handler electrical connectors can be brought together (i.e. docked), enabling the transfer of test signals between the test head and the device handler. Prior to docking, the fragile test head and device handler electrical connectors must be precisely aligned to avoid damaging the fragile electrical connectors.

A positioner, able to move along a support structure, carries the test head to the desired location

at which the test head is positioned to connect to and dock with the device handler. The test head is attached to the positioners so that the test head can achieve six degrees of freedom (X, Y, Z, θX , θY , θZ).

5 Test heads, and their respective positioners, are often used in an ultraclean room environment. However, ultraclean room environments are often extremely expensive to provide. Thus, the useable space within an ultraclean environment is only available at a premium.

10 A variety of test head manipulators are currently available for use in ultraclean room environments. Although some of these test head manipulators have a variety of desirable features, the amount of space which each of these test head
15 manipulators requires for proper operation may be undesirable.

SUMMARY OF THE INVENTION

20 A positioner facilitates docking and undocking of an electronic test head with a device handler. The positioner provides for rotation of the test head about a first axis. The positioner includes a linkage arm structure for moving the test head along a second axis orthogonal to the first axis.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a perspective drawing which illustrates an exemplary embodiment of the present invention.

5 Figure 2 is a partially exploded perspective drawing which illustrates coupling between a test head adapter ring and a carriage base.

10 Figure 3 is a perspective drawing which illustrates coupling between a test head adapter ring and a carriage base.

 Figures 4 and 5 are further perspective drawings which illustrate an exemplary embodiment of the present invention.

15 Figure 6 is an exploded perspective drawing which illustrates coupling between a linkage arm structure and a carriage rail.

 Figure 7 is a perspective drawing which illustrates a further exemplary embodiment of the present invention.

20 Figure 8 diagrammatically shows the six degrees of freedom of the system shown in Figures 1, 4 and 5.

DETAILED DESCRIPTION OF THE INVENTION

Referring now to Figure 1, there is shown a test head positioner system 200 in accordance with an exemplary embodiment of the present invention. As shown, positioner system 200 carries a test head 110 for a test system for docking with an electrical connector (not shown) of an integrated circuit handler 120. It will be understood that other electronic devices may be handled by the device handler, such as transistors, chips or dies, etc. In operation, positioner system 200 moves test head 110 accurately and precisely so that it may be docked to handler 120. Docking may be accomplished, for example, as more fully described in a previous patent by Smith (U.S. Patent No. 4,705,447), herein incorporated by reference, and in a previous patent by Holt (U.S. Patent No. 4,893,074), which is herein incorporated by reference. As will be described in detail, the position of test head 110 may be accurately manipulated to another position with six degrees of freedom X, Y, Z, θX , θY , θZ . As shown in Figure 8, it is important for the proper installation of test head 110 that it have six degrees of freedom so that it can accurately be positioned with respect to handler 120. Furthermore, the motion of test head 110 can be restricted so that it moves with only two degrees of motion (for example θY , Z). In this manner, test head 110 can be readily undocked and redocked with handler 120, so that maintenance of test head 110 can be

performed. In addition, the motion of test head 110 can be restricted so that it moves with only one degree of motion (for example Z). In this manner, test head 110 can be readily undocked and redocked with handler 120
5 when position assembly 200 is being used by an operator.

The details of positioner assembly 200 are shown in Figure 1 in which there are provided two I-shaped beams 42a, 42b and two rails 8, 9 forming the top of the carriage support structure assembly. Two legs
10 43b, 43d (partially shown) are attached to I-shaped beam 42b at opposite ends so as to support beam 42b a predetermined distance from the floor. In addition, two legs 43a (partially shown), 43c are disposed at opposite ends of I-shaped beam 42a to support beam 42a at a
15 predetermined distance from the floor. At the bottom of each leg 43a, 43b, 43c, 43d, a leveling pad 86 may be installed to facilitate leveling of the gantry. Alternatively, the test head positioner system (without, for example, legs) could be suspended from the ceiling
20 over the integrated circuit handler 120.

In an exemplary embodiment of the present invention, test head 110 may be mounted either directly or via a yoke 112 to test head adapter ring 130. The use of test head adapter ring 130 is more fully described in
25 U.S. Patent No. 5,030,869 which is incorporated herein by reference. By use of test head adapter ring 130, test

head 110 is able to rotate at least 180° about an axis which shall be defined as a Y axis. The ability of test head 110 to rotate about the Y axis facilitates maintenance of test head 110 as will be more fully described below.

As shown in Fig. 2, test head adapter ring 130 is coupled to cradle side 46. Cradle side 46 may be, for example, a rectangular beam. Cradle side 46 may be coupled, in turn, to cradle back 37. Cradle back 37 is coupled to cradle side 46 at substantially right angles. Spacers 38, 39 and 40 may be interposed between cradle back 37 and cradle side 46 in order to assure that the combined center of gravity of the test head 110, test head adapter ring 130, cradle side 46 and cradle back 37 desirably coincides with the axis of side-to-side shafts 35a and b.

Side-to-side shafts 35a, b are each coupled to wrist block 34 at respective openings. Thus, wrist block 34 is stationary relative to side-to-side shafts 35a, b. An additional opening is situated in the bottom of the wrist block 34. Wrist shaft 36 extends from the opening in the bottom of wrist block 34 through a further opening in cradle back 37. Wrist shaft 36 is coupled to wrist block 34. A flange 136 may be situated at the opposite end of wrist shaft 36 supporting cradle back 37. Wrist shaft 36 defines a Z axis. Cradle back 37 rotates about

- 8 -

the Z axis by rotating relative to wrist shaft 36.
Thrust bearing 80 (not shown), situated between the
flange of wrist shaft 36 and cradle back 37 facilitates
rotation of cradle back 37. Movement of cradle back 37
5 about the Z axis may be prevented by actuating lock
wrench 3.

Wrist shaft 36 is coupled to carriage base 26.
Coupling between wrist shaft 36 and carriage base 26 is
illustrated by Figure 3.

10 As shown in Fig. 3, carriage base 26 includes
rectangular opening 103. Wrist shaft 36 extends between
wrist block 34 and cradle back 37 by going through
rectangular opening 103. Stop block 44 and lock collar
31 are respectively situated on opposite sides of the
15 rectangular opening 103. Carriage walls 29a, 29b, 29c,
29d (not shown), are situated about rectangular opening
103. Carriage ceiling 29e (not shown) may be situated on
top of carriage walls 29a-d to form a partially enclosed
space. Side-to-side shaft 35a extends through carriage
20 wall 29a and lock collar 31 and is terminated with shaft
collar 74a. Similarly, side-to-side shaft 35b extends
through carriage wall 29b and stop block 44 and is
terminated with shaft collar 74b.

Side-to-side shafts 35a, 35b, define an X axis.
25 Thus, wrist block 34 is able to move along the X axis by

This Sheet Has Been Replaced



the sliding motion of side-to-side shafts 35a, 35b relative to lock collar 31 and stop block 44 respectively. Movement along the X axis is limited by shaft collars 74a, b. Wrist block 34 is also able to
5 move about the X-axis defined by side-to-side shafts 35a, b. Movement of wrist block 34 both along and about the X-axis is facilitated by bearings 72a, 72b which may be situated, for example, adjacent to carriage walls 29a, 29b respectively. Wrist block 34 may be prevented from
10 moving both along and about the X axis by actuating clamping knob 4c, shown coupled to lock collar 31.

As shown in Fig. 3, carriage base 26 includes bearing blocks 30a, 30b, 30c, 30d. Bearing blocks 30a, b, c, d enable carriage base 26 to be coupled to carriage
15 rails 22a, b as shown in Fig. 4. Specifically, pillow blocks 24a, b are coupled to carriage rail 22a by each extending from the surface of carriage rail 22a. Similarly, pillow blocks 24c, d are coupled to carriage rail 22b by each extending from the surface of carriage
20 rail 22b. In-out shaft 25a extends from pillow block 24a to pillow block 24b and is held in position by retaining rings 69a, 69b (not shown). In-out shaft 25b extends from pillow block 24c to pillow block 24d and is held in position by retaining rings 69c, 69d (not shown). In-out
25 shaft 25a extends through lock collar 32 which is also coupled to carriage rail 22a.

In-out shafts 25a, b each define a Y axis. Thus, carriage base 26 is capable of moving along the Y axis as a result of bearing blocks 30a, b, c, d sliding along in-out shafts 25a, b. The Y axis movement is
5 facilitated by bearings 79 mounted in bearing blocks 30a, b, c, d. Movement of carriage base 26 along the Y axis may be prevented by actuating clamping knob 4b, shown coupled to lock collar 32.

As shown in Figure 5, linkage arm 20 (shown to
10 the left in the figures) includes linkage arm structure 20a and linkage arm structure 20b. Linkage arm 20 (shown to the right in the figures) includes linkage arm structure 20c and linkage arm structure 20d. Linkage
15 axle 33 includes ends of diminished diameter which extend through openings in linkage arm structures 20a, 20c and is coupled to carriage rails 22a, 22b. In this way, linkage arm structures 20a, 20c are coupled to carriage rails 22a, 22b.

Linkage axle 21 also includes ends of
20 diminished diameter. This is more clearly shown in Figure 6. One end of linkage axle 21 extends through an opening near the bottom of arm component 20b, and through a further opening in trolley 17a. A similar
25 configuration may be found on the opposite end of linkage axle 21 which extends through an opening in linkage arm structure 20d, and through an opening in a further

trolley 17b (not shown). Each trolley 17a, b includes cam followers 76 which engage the slots in carriage rails 22a, b and thrust bearings 75 which make contact with carriage rails 22a, b. Cam followers 75, 76 facilitate movement of trolleys 17a, 17b relative to carriage rails 22a, b. As the left-most and right-most linkage arms function and are coupled to the remaining apparatus similarly, the operation of linkage arm structures 20a, 20b only will be described.

10 Linkage arm structure 20a and linkage arm structure 20b are coupled together by pivot pin 18. Movement of linkage arm structure 20a relative to linkage arm structure 20b is facilitated by needle bearing 84 (not shown).

15 Linkage arm structure 20a is capable of a limited amount of rotation about linkage axle 33. Furthermore, linkage arm structure 20b is capable of a limited amount of rotation about linkage axle 21. This rotation is useful for vertical motion of test head 110 along the z axis as will be described later.

20 As shown in Figure 4, linkage arm structure 20b rotates about pivot pin 19. This pivot pin 19 is fixed to carriage rail 9. As will be described below, this rotation also facilitates vertical movement of test head 110 along the z axis.

As shown in Figure 4, motor 212 is included. Motor 212 rotates gear box 113. Rotation of gear box 113 may be selectively prevented by the actuation of brake 115. Gear box 113 rotates ball screw 41. As ball screw 41 rotates, ball nut 114 moves along the axis defined by ball screw 41. Ball nut 114 is coupled to ball screw axle 16. Ball screw axle 16 includes a shoulder at each end which projects through respective holes in linkage arm structures 20a, 20d and trolleys 17c, d. Trolleys 17c, d each include cam followers 76 which engage and move along respective tracks which are formed in carriage rails 8, 9. Trolleys 17c, d each also include cam followers 75 which contact and facilitate movement relative to carriage rails 8, 9.

A further exemplary embodiment of the present invention is illustrated by Figure 7. The exemplary embodiment of the present invention which is illustrated by Figure 7 has similarities with the exemplary embodiment of the present invention which is illustrated by Figures 1, 4, 5. However, in Figure 7, fixture 201 is attached to test head 110. Fixture 201 includes a projection 202 which engages an opening 204 in extension bar 203. A bearing (not shown) may be coupled to projection 202 to facilitate rotation of test head 110 about the Y axis as previously discussed. In this further exemplary embodiment, cradle back 37 has sufficient length so that it may be coupled to extension

THIS SHEET HAS BEEN
REPLACED

- 13 -

bar 203. In this manner, test head 110 may be supported by yoke 112 and extension bar 203. Furthermore, the placement of projection 202 within opening 204 maintains the ability of test head 110 to rotate about the Y axis.
5 This total configuration enables test heads having weights on the order of 500 pounds to be supported and manipulated.

Vertical motion of test head 110 (i.e. Z axis motion) is accomplished as follows. As motor 112 turns, ball screw 41 also turns. This results in motion of ball nut 114 along the axis defined by ball screw 41. As ball nut 114 moves along the axis defined by ball screw 41, ball screw axle 16 (through trolleys 17c, 17d with cam followers 76) moves along horizontal rails 8, 9.
10 This, in turn, results in the movement of the top portion of linkage arm structures 20a, 20c along horizontal rails 8, 9. As the upper portions of linkage arm structures 20a, 20c move along horizontal rails 8, 9, the bottom portion of linkage arm structures 20a, 20c also moves.
15 This motion of the bottom portion of linkage arm structures 20a, 20c is vertical. The vertical motion of linkage arm structures 20a, 20c results in the vertical movement of carriage rails 22a, 22b. As the front portion of carriage rails 22a, 22b moves vertically, the
20 rear portion of carriage rails 22a, 22b also moves vertically. Thus, as carriage rails 22a, 22b move vertically, test head 110 moves vertically as well.
25

This Sheet Has Been Replaced



Thus, the linkage arm structures 20a, b, c, d provide a lifting mechanism while at the same time determining the path of motion of test head 110.

During the course of installation, the test
5 head 110 will be moved with six degrees of motion (X, Y, Z, θX , θY , θZ) so that it may be aligned and placed in contact with device handler 120. Thus, after installation has been completed, movement of the test head 110 in all six degrees of motion will be temporarily
10 restricted until maintenance or operation is required. When an operator wishes to undock the test Head 110 from the device handler 120 (e.g. during operation), an operator can undock the test head by moving the test head up and away from the device handler. To accomplish this
15 motion, freedom of motion limited only to the Z direction is adequate. After the test head has been moved upwards in the Z direction, the test head can be moved downwards in the Z direction. In this way, the test head 110 can be redocked with the device handler 120 without losing
20 alignment. Furthermore, should maintenance be required, the test head 110 can be moved upwards in the Z direction and then rotated in the θY direction so that the test head contact face upwards (as opposed to downwards, facing the device handler 120 when the test head is in
25 use). Thus, for maintenance purposes, only two degrees of freedom of motion is adequate. After maintenance has been completed, the test head can be rotated in the θY

direction and moved downwards in the Z direction. In this way, alignment between the test head 110 and the device handler 120 is again maintained.


5 The invention has been described with regard to a motor for accomplishing vertical motion. In an exemplary embodiment of the present invention, an electrical stepper motor may be used. In alternate exemplary embodiments of the present invention, a pneumatic motor or a hydraulic motor may be used.
10 However, one skilled in the art would readily recognize that the motor can be replaced with a counter balance system bearing the load of the carriage base 26 with the test head 110 attached. In this manner, operator and equipment safety may be enhanced.

15 When a motor is used, operator and equipment safety may be enhanced by proximity sensors (not shown) and/or limit switches (not shown). Exemplary proximity sensors (e.g. light or sound activated) may be located, for example, adjacent to the test head 110 in order to
20 determine the position of test head 110 relative to device handler 120. Furthermore, such sensors could also readily determine obstructions between test head 110 and device handler 120. Such sensors could be coupled to the motor in order to disengage the motor if an irregular
25 condition is sensed. Limit switches can be placed at numerous locations (for example, adjacent to the slots

located in carriage rails 22a, b) in order to disengage the motor if trolleys 17 reach predetermined positions. One skilled in the art will readily recognize that proximity sensors and/or limit switches may be placed at numerous other locations to ensure proper motion of test head 110.

The invention has been described with regard to a single positioner system. However, additional positioner systems, incorporating for example gantry beams 42a, 42b, may be used adjacent to the positioner system presently illustrated in the figures

While the invention has been described in terms of an exemplary embodiment, it is contemplated that it may be practiced as outlined above with modifications within the spirit and scope of the appended claims.



1 CLAIMS

2

3 1. A positioner for docking and undocking an
4 electronic test head with a device handler comprising:

5

6 head rotation means for rotating said electronic
7 test head about a first axis;

8

9 vertical motion means, including a plurality of
10 linkage arm structures coupled to said head rotation
11 means;

12

13 a first one of said plurality of linkage arm
14 structures coupled to a second one of said plurality of
15 linkage arm structures to form a scissor shaped member
16 of increasable and decreasable length for moving said
17 electronic test head vertically along a second axis
18 orthogonal to said first axis.

19

20 2. A positioner for docking and undocking an
21 electronic test head with a device handler comprising:

22

23 head rotation means for rotating said electronic
24 test head about a first axis;

25

26 cradle back means, coupled to said head rotation
27 means, for rotating said electronic test head about a
28 second axis orthogonal to said first axis; and vertical
29 motion means, including a plurality of linkage arm
30 structures coupled to and situated above said cradle
31 back means;

32

33 a first one of said plurality of linkage arm
34 structures coupled to a second one of said plurality of
35 linkage arm structures to form a scissor shaped member
36 of increasable and decreasable length for moving said





THIS SHEET HAS BEEN
REPLACED

- 18 -

1 electronic test head up and down along said second
2 axis.

3

4 3. A positioner according to claim 1, further
5 comprising first horizontal motion means, coupled to
6 the head rotation means, for moving said electronic
7 test head along said first axis.

8

9 4. A positioner according to claim 3, wherein
10 said first horizontal motion means includes:

11

12 a) a carriage base coupled to said head rotation
13 means, said carriage base including a first bearing
14 block having a first opening and a second bearing block
15 having a second opening;

16

17 b) a first shaft and a second shaft, said first
18 shaft and said second shaft each coupled to said
19 vertical motion means;

20

21 c) said first shaft extending through said first
22 opening of said first bearing block and said second
23 shaft extending through said second opening of said
24 second bearing block so that said electronic test head
25 moves along said first axis by said carriage base
26 sliding along said first shaft and said second shaft.

27

28 5. A positioner according to claim 1, further
29 including horizontal motion means for moving said
30 electronic test head along a third axis orthogonal to
31 both said first axis and said second axis, said
32 horizontal motion means comprising:


33

34 a) a wrist block coupled to said head rotation
35 means;

36

This Sheet Has Been Replaced





- 1 b) a carriage base coupled to said vertical
2 motion means, said carriage base including a first
3 carriage wall having a third opening and a second
4 carriage wall having a fourth opening;
5
6 c) shaft means including at least one shaft
7 extending from said wrist block at opposite ends
8 thereof, said shaft means extending through said third
9 opening of said first carriage wall and through said
10 fourth opening of said second carriage wall;
11
12 d) locking means, coupled to said carriage base,
13 for selectively preventing movement of said electronic
14 test head along said third axis.
15
16 6. A positioner according to claim 1, further
17 including horizontal motion means for moving said
18 electronic test head about a third axis orthogonal to
19 both said first axis and said second axis, said
20 horizontal motion means comprising:
21
22 a) a wrist block coupled to said head rotation
23 means;
24
25 b) a carriage base coupled to said vertical
26 motion means, said carriage base including a first
27 carriage wall having a third opening and a second
28 carriage wall having a fourth opening;
29
30 c) shaft means including at least one shaft
31 extending from said wrist block at opposite ends
32 thereof, said shaft means extending through said third
33 opening of said first carriage wall and through said
34 fourth opening of said second carriage wall;
35
36 d) locking means, coupled to said carriage basem





THIS SHEET HAS BEEN
REPLACED

- 20 -

1 for selectively preventing movement of said electronic
2 test head about said third axis.

3

4 7. A positioner according to claim 2, further
5 comprising first horizontal motion means, coupled to the
6 head rotation means, for moving said electronic test
7 head along said first axis.

8

9 8. A positioner according to claim 7, wherein
10 said first horizontal motion means includes:

11

12 a) a carriage base coupled to said head rotation
13 means, said carriage base including a first bearing
14 block having a first opening and a second bearing block
15 having a second opening;

16

17 b) a first shaft and a second shaft, said first
18 shaft and said second shaft each coupled to said
19 vertical motion means;

20

21 c) said first shaft extending through said first
22 opening of said first bearing block and said second
23 shaft extending through said second opening of said
24 second bearing block so that said electronic test head
25 moves along said first axis by said carriage base
26 sliding along said first shaft and said second shaft.

27

28 9. A positioner according to claim 2, further
29 including horizontal motion means for moving said
30 electronic test head along a third axis orthogonal to
31 both said first axis and said second axis, said
32 horizontal motion means comprising:

33

34 a) a wrist block coupled to said head rotation
35 means;

36

This Sheet Has Been Replaced





THIS SHEET HAS BEEN
REPLACED

- 21 -

1 b) a carriage base coupled to said vertical
2 motion means, said carriage base including a first
3 carriage wall having a third opening and a second
4 carriage wall having a fourth opening;
5

6 c) shaft means including at least one shaft
7 extending from said wrist block at opposite ends
8 thereof, said shaft means extending through said third
9 opening of said first carriage wall and through said
10 fourth opening of said second carriage wall;
11

12 d) locking means, coupled to said carriage base,
13 for selectively preventing movement of said electronic
14 test head along said third axis.
15

16 10. A positioner according to claim 2, further
17 including horizontal motion means for moving said
18 electronic test head about a third axis orthogonal to
19 both said first axis and said second axis, said
20 horizontal motion means comprising:
21

22 a) a wrist block coupled to said head rotation
23 means;
24

25 b) a carriage base coupled to said vertical
26 motion means, said carriage base including a first
27 carriage wall having a third opening and a second
28 carriage wall having a fourth opening;
29

30 c) shaft means including at least one shaft
31 extending from said wrist block at opposite ends
32 thereof, said shaft means extending through said third
33 opening of said first carriage wall and through said
34 fourth opening of said second carriage wall;
35

36 d) locking means, coupled to said carriage base,

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED



- 22 -

- 1 for selectively preventing movement of said electronic
- 2 test head along said third axis.
- 3
- 4
- 5
- 6
- 7
- 8
- 9

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

1/8




FIG. 1

This Sheet Has Been Replaced






FIG.2

THIS SHEET HAS BEEN
REPLACED

3/8




FIG. 3

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED




FIG. 4

This Sheet Has Been Replaced






FIG. 5






FIG.6

THIS SHEET HAS BEEN
REPLACED

7/8




FIG. 7

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED




FIG.8

This Sheet Has Been Replaced



ABSTRACT

(Figure 1)

ELECTRONIC TEST HEAD MANIPULATOR

A positioner facilitates docking and undocking of an electronic test head with a device handler. The position provides for rotation of the test head about a first axis. The positioner includes a scissor arm structure for moving the test head along a second axis orthogonal to the first axis

8-7200000

1980 9-1-10

REPLACEMENT SHEET

Date 09 OCT 1997

the Z axis by rotating relative to wrist shaft 36.
Thrust bearing 80 (not shown), situated between the
flange of wrist shaft 36 and cradle back 37 facilitates
rotation of cradle back 37. Movement of cradle back 37
5 about the Z axis may be prevented by actuating lock
wrench 3.

Wrist shaft 36 is coupled to carriage base 26.
Coupling between wrist shaft 36 and carriage base 26 is
illustrated by Figure 3.

10 As shown in Fig. 3, carriage base 26 includes
rectangular opening 103. Wrist shaft 36 extends between
wrist block 34 and cradle back 37 by going through
rectangular opening 103. Stop block 44 and lock collar
31 are respectively situated on opposite sides of the
15 rectangular opening 103. Carriage walls ^{29A, 29B, 29C}~~29a, 29b, 29c~~,
29d (not shown), are situated about rectangular opening
103. Carriage ceiling 29e (not shown) may be situated on
top of carriage walls 29a-d to form a partially enclosed
space. Side-to-side shaft ^{35A}~~35a~~ extends through carriage
20 wall 29a and lock collar 31 and is terminated with shaft
collar 74a. Similarly, side-to-side shaft 35b extends
through carriage wall 29b and stop block 44 and is
terminated with shaft collar 74b.

Side-to-side shafts 35a, 35b, define an X axis.
25 Thus, wrist block 34 is able to move along the X axis by

bar 203. In this manner, test head 110 may be supported by yoke 112 and extension bar 203. Furthermore, the placement of projection 202 within opening 204 maintains the ability of test head 110 to rotate about the Y axis.

5 This total configuration enables test heads having weights on the order of 500 pounds to be supported and manipulated.

Vertical motion of test head 110 (i.e. Z axis motion) is accomplished as follows. As motor ~~112~~²¹² turns, ball screw 41 also turns. This results in motion of ball nut 114 along the axis defined by ball screw 41. As ball nut 114 moves along the axis defined by ball screw 41, ball screw axle 16 (through trolleys 17c, 17d with cam followers 76) moves along horizontal rails 8, 9.

10 This, in turn, results in the movement of the top portion of linkage arm structures 20a, 20c along horizontal rails 8, 9. As the upper portions of linkage arm structures 20a, 20c move along horizontal rails 8, 9, the bottom portion of linkage arm structures 20a, 20c also moves.

15 This motion of the bottom portion of linkage arm structures 20a, 20c is vertical. The vertical motion of linkage arm structures 20a, 20c results in the vertical movement of carriage rails 22a, 22b. As the front portion of carriage rails 22a, 22b moves vertically, the rear portion of carriage rails 22a, 22b also moves vertically. Thus, as carriage rails 22a, 22b move vertically, test head 110 moves vertically as well.

20

25

Claims

1. A positioner for docking and undocking an electronic test head with a device handler comprising;

head rotation means for rotating said electronic test head about a first axis;

vertical motion means, including a plurality of linkage arms coupled to said head rotation means;

a first of said plurality of linkage arms coupled to a second of said plurality of linkage arms to define a scissor shape of increasable and decreasable length in a vertical direction for moving said electronic test head vertically along a second axis orthogonal to said first axis as an upper end of said first of said plurality of linkage arms moves towards and away from an upper end of said second of said plurality of linkage arms.

2. A positioner according to claim 1, further comprising first horizontal motion means, coupled to the head rotation means, for moving said electronic test head along said first axis.

3. A positioner according to claim 1, further including horizontal motion means for moving said electronic test head about a third axis orthogonal to both said first axis and said second axis, said horizontal motion means comprising:

a) a wrist block coupled to said head rotation means;

b) a carriage base coupled to said vertical motion means, said carriage base including a first carriage wall having a third opening and a second carriage wall having a fourth opening;

c) shaft means including at least one shaft extending from said wrist block at opposite ends thereof, said shaft means extending through said



third opening of said first carriage wall and through said fourth opening of said second carriage wall;

d) locking means, coupled to said carriage base, for selectively preventing movement of said electronic test head about said third axis.

4. A positioner according to claim 1, wherein said electronic test head is vertically disposed relative to said vertical motion means.

5. A positioner according to claim 1, further comprising motor means coupled to the upper ends of said first and second of said plurality of linkage arms, for moving the upper ends of said first and second of said plurality of linkage arms towards and away from each other without causing vertical movement of the upper ends of said first and second of said plurality of linkage arms.

6. A positioner according to claim 5, wherein said vertical motion means further comprises means for rotatably supporting said second linkage arm and for permitting horizontal sliding of said upper end of said first linkage arm with respect to the vertical motion means.

7. A positioner according to claim 5, wherein said vertical motion means further comprises means for rotatably supporting a lower end of said first linkage arm and for permitting horizontal sliding of said lower end of said second linkage arm.

8. A positioner according to claim 7, wherein said vertical motion means further comprises a third linkage arm coupled to a fourth linkage arm to define a further scissor shape and means for rotatably supporting said fourth linkage arm and for permitting horizontal sliding of said upper end of said third linkage arm with respect to the vertical motion means.

9. A positioner according to claim 7, wherein said vertical motion means further comprises a third linkage arm coupled to a fourth linkage



arm to define a further scissor shape and means for rotatably supporting a lower end of said third linkage arm and for permitting horizontal sliding of said lower end of said fourth linkage arm.

10. A positioner for docking and undocking an electronic test head with a device handler comprising:

head rotation means for rotating said electronic test head about a first axis;

cradle back means, coupled to said head rotation means, for rotating said electronic test head about a second axis orthogonal to said first axis; and

vertical motion means, including a plurality of linkage arms coupled to and situated above said cradle back means;

a first of said plurality of linkage arms coupled to a second of said plurality of linkage arms to define a scissor shape of increasable and decreasable length in a vertical direction for moving said electronic test head up and down vertically along said second axis orthogonal to said first axis as an upper end of said first of said plurality of linkage arms moves towards and away from an upper end of said second of said plurality of linkage arms.

11. A positioner according to claim 10, wherein said vertical motion means includes a linkage arm structure.

12. A positioner according to claim 10, further comprising first horizontal motion means, coupled to the head rotation means, for moving said electronic test head along said first axis.

13. A positioner according to claim 10, further including horizontal motion means for moving said electronic test head about a third axis



orthogonal to both said first axis and said second axis, said horizontal motion means comprising:

- a) a wrist block coupled to said head rotation means;
- b) a carriage base coupled to said vertical motion means, said carriage base including a first carriage wall having a third opening and a second carriage wall having a fourth opening;
- c) shaft means including at least one shaft extending from said wrist block at opposite ends thereof, said shaft means extending through said third opening of said first carriage wall and through said fourth opening of said second carriage wall;
- d) locking means, coupled to said carriage base, for selectively preventing movement of said electronic test head about said third axis.

14. A positioner according to claim 10, further comprising motor means coupled to the upper ends of said first and second of said plurality of linkage arms, for moving the upper ends of said first and second of said plurality of linkage arms towards and away from each other without causing vertical movement of the upper ends of said first and second of said plurality of linkage arms.

15. A positioner for docking and undocking a electronic test head with a device handler comprising:

head rotation means for rotating said electronic test head about a first axis;

vertical motion means, including a linkage arm structure coupled to said head rotation means for moving said electronic test head along a second axis orthogonal to said first axis; and



first horizontal motion means, coupled to the head rotation means, for moving said electronic test head along said first axis, said first horizontal motion means including:

- a) a carriage base coupled to said head rotation means, said carriage base including a first bearing block having a first opening and a second bearing block having a second opening;
- b) a first shaft and a second shaft, said first shaft and said second shaft each coupled to said vertical motion means;
- c) said first shaft extending through said first opening of said first bearing block and said second shaft extending through said second opening of said second bearing block so that said electronic test head moves along said first axis by said carriage base sliding along said first shaft and said second shaft.

16. A positioner for docking and undocking a electronic test head with a device handler comprising:

head rotation means for rotating said electronic test head about a first axis;

vertical motion means, including a linkage arm structure coupled to said head rotation means for moving said electronic test head along a second axis orthogonal to said first axis; and

horizontal motion means for moving said electronic test head along a third axis orthogonal to both said first axis and said second axis, said horizontal motion means comprising:

- a) a wrist block coupled to said head rotation means;



b) a carriage base coupled to said vertical motion means, said carriage base including a first carriage wall having a third opening and a second carriage wall having a fourth opening;

c) shaft means including at least one shaft extending from said wrist block at opposite ends thereof, said shaft means extending through said third opening of said first carriage wall and through said fourth opening of said second carriage wall;

d) locking means, coupled to said carriage base, for selectively preventing movement of said electronic test head along said third axis.

17. A positioner for docking and undocking an electronic test head with a device handler comprising:

head rotation means for rotating said electronic test head about a first axis;

cradle back means, coupled to said head rotation means, for rotating said electronic test head about a second axis orthogonal to said first axis; and

vertical motion means, coupled to and situated above said cradle back means for moving said electronic test head up and down along said second axis and first horizontal motion means, coupled to the head rotation means, for moving said electronic test head along said first axis, said vertical motion means including:

a) a carriage base coupled to said head rotation means, said carriage base including a first bearing block having a first opening and a second bearing block having a second opening;

b) a first shaft and a second shaft, said first shaft and said second shaft each coupled to said vertical motion means;



c) said first shaft extending through said first opening of said first bearing block and said second shaft extending through said second opening of said second bearing block so that said electronic test head moves along said first axis by said carriage base sliding along said first shaft and said second shaft.

18. A positioner for docking and undocking an electronic test head with a device handler comprising:

head rotation means for rotating said electronic test head about a first axis;

cradle back means, coupled to said head rotation means, for rotating said electronic test head about a second axis orthogonal to said first axis; and

vertical motion means, coupled to and situated above said cradle back means for moving said electronic test head up and down along said second axis; and

horizontal motion means for moving said electronic test head along a third axis orthogonal to both said first axis and said second axis, said horizontal motion means comprising:

- a) a wrist block coupled to said head rotation means;
- b) a carriage base coupled to said vertical motion means, said carriage base including a first carriage wall having a third opening and a second carriage wall having a fourth opening;
- c) shaft means including at least one shaft extending from said wrist block at opposite ends thereof, said shaft means extending through said third opening of said first carriage wall and through said fourth opening of said second carriage wall;




REPLACEMENT SHEET
09 OCT 1997
Date :


24

Substitute sheet - 2 October 1997


d) locking means, coupled to said carriage base, for selectively preventing movement of said electronic test head along said third axis.

1 Substitute sheet - 21 October 1997





4 Substitute sheet - 21 October 1997



5 Substitute sheet - 21 October 1997




FIG. 5




FIG.7




FIG.8