

CLAIMS

1. OBP measuring and monitoring device comprising a contact lens presenting an inner surface and an outer surface and a sensing unit, said sensing unit
5 being united with said contact lens such that it is applied against an eye of a user for sensing at least a first OBP and a second OBP of said eye when said contact lens is worn by said user, said sensing unit being adapted to measure simultaneously or consecutively the first and second OBPs and transmit these OBPs to a CPU such that said CPU receiving said measurement is able to determine at least one new biomarker based on a
10 combination between at least these two OBPs.
2. OBP measuring and monitoring device according to claim 1 characterized in that the sensing unit comprises a single sensor capable of measuring at least two different OBPs.
3. OBP measuring and monitoring device according to claim 1,
15 characterized in that the sensing unit comprises at least two single sensors each capable of measuring a single OBP.
4. OBP measuring and monitoring device according to claim 3, characterized in that the at least two single sensors are each capable of measuring a single OBP different from each other.
- 20 5. OBP measuring and monitoring device according to any one of preceding claims, characterized in that the first OBP is the intraocular pressure and the second OBP is the eye's temperature.
6. OBP measuring and monitoring device according to any one of claims 1 to 4, characterized in that the first OBP is the intraocular pressure and the second OBP
25 is the eye's dimensional variation.
7. OBP measuring and monitoring device according to claim 6, wherein the sensing unit comprises an eye's dimensional variation sensor as an active strain gauge

presenting a circular or arc shape and is situated in an outer portion around the an inner portion of said soft contact lens.

8. OBP measuring and monitoring device according to claim 7, characterized in that the eye's dimensional variation sensor comprises several active strain gauges.

9. OBP measuring and monitoring device according to claim 7 or 8, wherein said strain gauge is made of a resistive material, such as a metal or an alloy.

10. OBP measuring and monitoring device according to claims 7-9, wherein said strain gauge is a continuous longitudinal element.

11. OBP measuring and monitoring device according to claims 7-10, wherein the eye's dimensional variation sensor comprises four gauges in a Wheatstone bridge configuration, such as two active gauges and two passive ones being placed alternatively on the bridge.

12. OBP measuring and monitoring device according to any one of preceding claims, characterized in that the sensing unit comprises a direct pressure sensor.

13. OBP measuring and monitoring device according to claim 12, characterized in that the contact lens is a soft contact lens comprising an inner portion and an outer portion, said inner portion being more rigid than said outer portion.

14. OBP measuring and monitoring device according to claim 13, characterized in that the direct pressure sensor is located in said inner portion.

15. OBP measuring and monitoring device according to claim 13 or 14, wherein the inner portion is adapted to at least partially rigidify a central portion of the inner surface of said contact lens so as to maintain said rigidified inner surface with a curvature radius adapted to flatten at least a portion of the eye surface in contact with the direct pressure sensor so as to reach a pressure equilibrium around the direct pressure sensor when said contact lens is worn by said user.

16. OBP measuring and monitoring device according to claims 13-15, characterized in that the inner portion has a general shape similar to a meniscus lens.

17. OBP measuring and monitoring device according to claims 13-16, characterized in that the inner portion is smaller in dimension compared to the outer portion and is centered in the contact lens.

18. OBP measuring and monitoring device according to claims 13-17,
5 characterized in that the inner portion comprises a rigid insert.

19. OBP measuring and monitoring device according to claim 18, characterized in that the rigid insert comprises a plurality of through holes.

20. OBP measuring and monitoring device according to claim 18 or 19, characterized in that the rigid insert is made of a material chosen in the group of polymers,
10 biopolymers, ceramics, glasses, metals and RGP.

21. OBP measuring and monitoring device according to claims 13-20, characterized in that the outer portion of said contact lens is made of a material chosen in the group of hydrogels, silicone-hydrogels and silicones.

22. OBP measuring and monitoring device according to claims 13-21,
15 characterized in that any one of the inner portion and the outer portion of said contact lens is made of a material having a tunable stiffness or a stiffness gradient.

23. OBP measuring and monitoring device according to claims 12-22, characterized in that the pressure sensor is in direct contact with the eye of the user when the user is wearing the contact lens.

20 24. OBP measuring and monitoring device according to claims 12-22, characterized in that the pressure sensor is in indirect contact with the eye of the user when the user is wearing the contact lens.

25. OBP measuring and monitoring device according to claims 12-24, characterized in that the pressure sensor is located within a cavity formed in an inner
25 concave side of the rigid insert, and wherein the cavity is filled with a pressure transmitting filler material that covers the pressure sensor such that a layer of the filler material is located between the pressure sensor and the inner surface of the contact lens.

26. OBP measuring and monitoring device according to claim 25, characterized in that the filler material is a material softer than the inner portion.

27. OBP measuring and monitoring device according to claim 25, characterized in that the filler material is softer than the material of the outer portion.

28. OBP measuring and monitoring device according to claim 25, characterized in that the filler material is the same material as the material of the outer
5 portion.

29. OBP measuring and monitoring device according to claims 25 to 28 characterized in that the cavity is formed in the center of the inner portion.

30. OBP measuring and monitoring device according to claims 25 to 29, characterized in that the inner surface of the contact lens beneath the cavity presents a
10 softer surface than the rest of the inner surface beneath the inner portion.

31. OBP measuring and monitoring device according to claims 25 to 29, characterized in that the inner surface of the contact lens beneath the cavity presents a surface softness similar than the rest of the inner surface beneath the inner portion.

32. OBP measuring and monitoring device according to any one of preceding
15 claims, characterized in that the contact lens further comprises an antenna and a microprocessor for telemetry powering and data transfer.

33. OBP measuring and monitoring device according to any one of preceding claims, characterized in that the sensing unit comprises a plurality of sensors adapted to measure the same OBP.

20 34. Kit comprising:

- an OBP measuring and monitoring device according to any one of claims
1 to 33;

- a portable recording device configured for communicating with said OBP
25 measuring and monitoring device and for storing data received from said OBP measuring and monitoring device.

35. Kit according to claim 34, wherein said portable recording device is configured for powering said OBP measuring and monitoring device over a wireless inductive communication channel.

36. Kit according to claim 34 or 35, wherein the contact lens comprises a miniaturized power source embedded within it.

37. Kit according to any one of claims 34 to 36, wherein the contact lens further comprises a data storage embedded within it.

38. OBP monitoring system comprising:

- an OBP measuring and monitoring device according to any one of the claims 1 to 33;

- a portable recording device configured for communicating with said OBP measuring and monitoring device and for storing data received from said OBP measuring and monitoring device;

- a computing device configured for communicating with said portable recording device for receiving and/or processing and/or storing data received from said portable recording device.

39. OBP monitoring system according to claim 38, wherein said portable recording device is configured for powering said OBP measuring and monitoring device over a wireless inductive communication channel.

40. OBP monitoring system according to claim 38 or 39, wherein the OBP monitoring system comprises two OBP measuring and monitoring devices, one for a left eye, one for a right eye, and the portable recording device is configured for communicating with the two OBP measuring and monitoring devices and for storing data received from the two OBP measuring and monitoring devices.

41. OBP measuring and monitoring method comprising the steps of placing the kit according to any one of claims 34 to 36 on the patient, starting a measurement of at least one of the OBPs, recording the OBP signals in the portable recording device,

sending the recorded OBP data to a computing device configured for communicating with the portable recording device for receiving and/or processing and/or storing data received from the portable recording device, wherein the computing device is adapted to calculate and determine at least one new biomarker based on a combination between at least two

5 OBPs.

42. OBP measuring and monitoring method according to claim 41, comprising the steps of measuring a temperature of the eye and use the temperature for running a fine tuning of the OBP measurements.

10