

Description

A PALLET

Technical Field

- [1] The present invention relates to a pallet made of a plastics or metal material such as aluminum adopted or used for the solidity and durability thereof, and more particularly, to a pallet in which sharp cut edges of the members are prevented from being exposed.

Background Art

- [2] Generally, pallets have been widely used to stack bulky and heavy goods for lifting and transporting, especially by forklift trucks. Among various kinds of pallets, known are robust and durable pallets comprising supporting members, upper plate members and prop members, which are formed by cutting extrusion-molded basic materials of different shapes into desired lengths of pieces.
- [3] Since the pieces or members obtained as above have sharp cut edges, the pallets made of such members also have cut edges directly exposed to the danger of harming the workers involved and/or damaging the workers' clothes or other objects touched by them.
- [4] To lift a pallet with goods stacked thereon, forks of a forklift truck should be inserted into spaces between prop members of the pallet. However, even a driver skilled in operating the truck may have difficulties in accurate insertion of the forks. Thus, the prop members, among others, are liable to be deformed or damaged, thereby shortening the life of the pallet itself, if the forks strike against the prop members while being inserted into the spaces between the prop members.

Disclosure of Invention

Technical Problem

- [5] Accordingly, the present invention is conceived to solve the problems in the prior art as above. An object of the invention is to provide a pallet which may reduce possible injuries to the workers or damages to the objects involved in using, operating or keeping in custody thereof with or without goods stacked thereon.
- [6] Another object of the present invention is to provide a pallet with improved robustness or solidity.

Technical Solution

- [7] The objects of the present invention are achieved by making cut edges of respective members of a pallet to be buried in or hidden by a cover or the like and by constructing prop members to have a reinforced double structure.

Brief Description of the Drawings

- [8] Figs. 1 and 2 are perspective views of a pallet according to an embodiment of the present invention and a modification thereof;
- [9] Fig. 3 is an exploded perspective view of a supporting member and prop members shown in Fig. 1;
- [10] Fig. 4 is a partial exploded perspective view showing a coupled state of the supporting member and the prop members shown in Fig. 1; and
- [11] Fig. 5 is a sectional view along the line A-A of Fig. 4.

Best Mode for Carrying Out the Invention

- [12] Hereinafter, pallets according to the preferred embodiments of the present invention will be described in detail with reference to the accompanying drawings.
- [13] Figs. 1 is a perspective view of a pallet according to an embodiment of the present invention; Figs. 3 and 4 are overall and partial exploded views of the assembly of a supporting member and prop members in Fig. 1, respectively; and Fig. 5 is a sectional view along the line A-A of Fig. 4.
- [14] In Fig. 1, the pallet comprises three supporting members 10 arranged parallel at a certain interval with one another, five upper plate members 20 placed parallel at a certain interval with one another, across and on the supporting members 10, and a pair of prop members 30 and an auxiliary prop member 30' fixed on both ends and the central portion of the bottom surface of each of the supporting members, respectively.
- [15] The supporting members 10 are formed into a rectangular tubular shape and comprises a body 11 having opposite walls 111 and a reinforcing wall 112 therebetween and a roof portion 15 with opposite wings 13 provided with a downward projection for defining a longitudinal groove 14.
- [16] The upper plate members 20 may have a cross section in the form of
- 
- or
- 
- . A conventional upper plate members including those disclosed in the Korean Utility Model Registration Nos. 334246 and 338716 in the name of the applicant may also be used.
- [17] Further, both ends of the upper plate member 20 are covered by guards 40 which have a cross section in the form of
- 
- or
- 
- to prevent sharp cut edges thereof from being exposed to the outside.
- [18] The prop member 30 comprises a body 31 and a reinforcement 32 with a size to be

coupled within the body 31, and the auxiliary prop member 30' also comprises a body 31' and a reinforcement 32, as the prop members 30.

[19] The body 31 may be made by cutting an elongated tubular material, extruded to have integral inner and outer walls 311 and sidewalls 312, into a desired length. Two bodies 31 are attached under the both ends of the supporting member 10. In the body 31 of the prop member, the inner wall 311 has a rectangular groove made by cutting away the upper portion thereof in proportion to the height of the wall 111 of the supporting member 10 so as to receive the body 11 of the supporting member therein. In the body 31' of the auxiliary prop member 30' to be attached under the central portion of the supporting member 10, both inner and outer walls 311 thereof have a rectangular groove formed by cutting away the upper portions thereof to receive the body 11 of the supporting member in the same manner as described above for the prop member 30.

[20] The body 11 of the supporting member 10 constructed as above is accommodated and engaged in the upper space of the bodies 31 and 31', while the bottom portion of the body 11 is seated on the upper ends of the inner and outer walls 311 forming the bottom of the grooves.

[21] The front and rear ends of the supporting member 10 abut on upper ends of the outer walls 311 of the bodies 31 of the prop members, while upper ends of the sidewalls 312 thereof are placed in the longitudinal grooves 14 of the supporting member 10 and then covered with the wings 13. Thus, sharp cut edges at the both ends of the supporting member 10 and the upper ends of the sidewalls of the bodies 31 of the prop members 30 are covered not to be exposed so that accidents of injuries or damages due to such sharp cut edges may be prevented. This is also true of the auxiliary prop member 30'.

[22] Each of the reinforcements 32 comprises opposite sidewalls 322 with a transverse partition 323 formed therebetween, and a bottom portion 321 with extensions 324 formed outwardly.

[23] The reinforcement 32 may be made by cutting an elongated tubular body, extruded to have a sectional shape of "

⊞

", into a desired length. The length of the reinforcement is around the same as the distance between the inner and outer walls 311 of the body 31 or 31', and the distance between outer surfaces of the both sidewalls 322 is almost the same as that between inner surfaces of the both sidewalls 312 of the body 31.

[24] Thus, upper ends of the sidewalls 312 and 322 with the same height are flush with each other, when the reinforcement 32 is coupled into the body 31. Walls 111 of the body 11 are placed in the space between the sidewalls of the reinforcement, as the

body 11 of the supporting member 10 is fitted into the prop member 30. This is also true of the body 31' of the auxiliary prop member 30'.

[25] Meanwhile, the height of the sidewalls 322 of the reinforcement 32 may be made lower than that of the sidewalls 312 of the body 31 or 31'. In this case, the upper portions of the both sidewalls 312 of the body 31 or 31' are preferably thicker than the other portions thereof such that those portions may be tightly caught in the groove 14.

[26] In this state, the upper ends of the sidewalls 322 of the reinforcement 32 are not exposed to the outside, as they are received within the grooves 14 of the supporting member 10, together with the upper ends of the sidewalls 312 of the body 31 or 31'. At the same time, lower ends of the both sidewalls 312 of the body 31 or 31' are seated on upper surfaces of the extensions 324 of the reinforcement so that they may not be exposed to the outside. Consequently, sharp cut edges of the upper ends of the sidewalls of the reinforcement and the lower ends of the sidewalls of the body are not exposed, thereby preventing accidents of injuries or damages.

[27] Since the prop member 30 has a double structure in which the reinforcement 32 is fitted into the body 31 and the body 11 of the supporting member 10 is mounted in the upper portion of the prop member and the transverse partition 323 is formed at the intermediate portion of the reinforcement, the strength of the prop member is increased so that the prop member may not be easily deformed or damaged, even in the case that a strong impact is applied thereto. Accordingly, the life of the pallet can be prolonged. This is also true of the auxiliary prop member 30'.

[28] However, depending on the size or weight of articles to be stacked on the pallet, the prop member may consist of only the body 31 without the reinforcement. In this case, it is preferred that a cover is attached to the lower opening of the body.

[29] The gaps or intervals between and numbers of supporting members 10, upper plate members 20, prop members 30 and auxiliary prop members 30' are determined in consideration of the sizes or weights of articles to be stacked on the pallet. Coupling portions of the supporting members 10 and the upper plate members 20 are preferably fixed to each other by means of fasteners such as rivets 50.

[30] The auxiliary prop member 30' may be constructed of a tubular body with a closed top face, which may be directly coupled to the bottom surface of the body of the supporting member 10 by means of spot welding, rivetting or the like.

[31] Meanwhile, the top surfaces of the upper plate member 20 and the outer surface of the body 31 of the prop member 30 are preferably provided with a plurality of nonslip protrusions 60 to prevent slipperiness of the pallet and sliding of articles stacked on the pallet and to reinforce the strength of the members themselves.

[32] Fig. 2 is a perspective view of a pallet according to a modification of the pallet in Fig. 1, which comprises three supporting members 10, five upper plate members 20, a

pair of prop members 30 and an auxiliary prop member 30' combined in the same manner as in the embodiment of Fig. 1, and further three reinforcing members 70 with the same construction as the upper plate members 20 in Fig. 1 fixed to the bottom surfaces of the prop members 30 and the auxiliary prop member 30' respectively.

[33] The pallet in Fig. 2 has the same functions as that in Fig. 1 except that the durability and solidity of the prop members 30 and the auxiliary prop member 30' are improved by the addition of the reinforcing members 70 and detailed description of the pallet in Fig. 2 will, therefore, be not necessary.

[34] The construction of the reinforcing members 70, is not limited to that in Fig. 2, of course.

[35] Although the pallets of the present invention have been described in connection with the preferred embodiments, it is to be noted that the present invention is not limited thereto. For instance, the supporting members 10 may be made without the roof portion and with the wings extending outwardly from the upper ends of the walls.

[36] Moreover, it will be apparent to those skilled in the art that variations, modifications and changes can be made to the embodiments described above without departing from the spirit and scope of the present invention and those variations, modifications and changes fall within the scope of the present invention.

Industrial Applicability

[37] According to the present invention, the pallets are made such that sharp cut edges of the supporting members, upper plate members and prop members are not exposed to the outside. Thus, it is possible to reduce the possible accidents of injuries and damages. Accordingly, there is an advantage in that the pallet can be safely used.

[38] Particularly, with the double structure of the prop members in which the body and the reinforcement are coupled together and the body of the supporting member is coupled to the upper portion of the prop member and the transverse partition is provided at the intermediate portion of the reinforcement, deformation or damage of the pallet can hardly be caused by force of impact thereon. Thus, there is an advantage in that the life of the pallet itself is prevented from being shortened by such impact.

Claims

- [1] A pallet comprising a plurality of supporting members arranged parallel at a certain interval with one another, a plurality of upper plate members placed parallel at a certain interval with one another across top surfaces of the supporting members, and at least a pair of prop members attached to both ends of the bottom surface of each of the supporting members, wherein said supporting members have a body in the tubular shape and said prop members have a body with an open top, inner and outer walls and opposite sidewalls, characterized in that;
- said supporting members are provided with opposite downward grooves defined by a downward projection at the distal ends of the respective wings thereof; and said prop members have a groove formed between the sidewalls and above the inner wall of the body thereof so that the height of the inner wall is lower than that of the sidewalls thereof;
- wherein upper ends of the sidewalls of said prop members are received and fitted in the corresponding downward grooves of said supporting members, and the bodies of said supporting members are received and coupled in the corresponding grooves of the body of said prop member.
- [2] The pallet as claimed in claim 1, further comprising at least one auxiliary prop member which is attached to the bottom surfaces of said supporting members and between said prop members.
- [3] The pallet as claimed in claim 2, wherein said auxiliary prop member comprises a tubular body with a closed top portion, inner and outer walls and opposite sidewalls, which is fixed to the bottom surface of the body of said supporting member.
- [4] The pallet as claimed in claim 2, wherein said auxiliary prop member having an open top, inner and outer walls and opposite sidewalls is provided with opposite grooves at upper ends of the inner and outer walls thereof such that the heights of the inner and outer walls thereof are the same and lower than that of the sidewalls thereof and the body of said supporting member may be received and coupled in the corresponding grooves thereof.
- [5] The pallet as claimed in any one of claims 1 to 4, wherein said prop member further comprises a reinforcement, comprising inner and outer walls and opposite sidewalls to be engaged within the space defined by inner and outer walls and sidewalls of said body and a bottom portion with outward extensions at both sides thereof for sitting and covering of the lower ends of the sidewalls of said body thereon.

- [6] The pallet as claimed in claim 5, wherein the height of the sidewalls of the body of said prop member is identical to that of the sidewalls of the reinforcement of said prop member.
- [7] The pallet as claimed in claim 5, wherein the height of the sidewalls of the reinforcement of said prop member is lower than that of the sidewalls of the body of said prop member.
- [8] The pallet as claimed in claim 4, wherein said auxiliary prop member further comprises a reinforcement, comprising inner and outer walls and opposite sidewalls to be engaged within the space defined by inner and outer walls and sidewalls of said body and a bottom portion with outward extensions at both sides thereof for sitting and covering of the lower ends of the sidewalls of said body thereon.
- [9] The pallet as claimed in claim 5, wherein said auxiliary prop member further comprises a reinforcement, comprising inner and outer walls and opposite sidewalls to be engaged within the space defined by inner and outer walls and sidewalls of said body and a bottom portion with outward extensions at both sides thereof for sitting and covering of the lower ends of the sidewalls of said body thereon.
- [10] A pallet comprising a plurality of supporting members arranged parallel at a certain interval with one another, a plurality of upper plate members placed parallel at a certain interval with one another across top surfaces of the supporting members, and at least a pair of prop members attached to both ends of the bottom surface of each of the supporting members, wherein said supporting members have a body in the tubular shape and said prop members have a body with an open top, inner and outer walls and opposite sidewalls, characterized in that;
lower ends of opposite outer walls of said upper plate member extend inwardly to some extent so that said upper plate member may have a cross section in the form of


; and
said prop members have a groove between the sidewalls and above the inner wall such that the height of the inner wall is lower than that of the sidewalls, wherein the body of said supporting member is received and coupled in the grooves.
- [11] The pallet as claimed in claim 10, wherein opposite ends of said upper plate members are covered with a guard having a cross section in the form of


or

- [12] The pallet as claimed in claim 10 or 11, wherein lower ends of opposite outer walls of said upper plate member extend inwardly to meet or almost reach the adjacent inner wall thereof so that said upper plate member may have a cross section in the form of



- [13] The pallet as claimed in claim 10 or 11, wherein said supporting members have opposite downward grooves defined by a downward projection at the distal ends of the respective wings thereof and upper ends of the sidewalls of said prop members are received and coupled in the corresponding grooves.
- [14] The pallet as claimed in claim 10 or 11, wherein at least one auxiliary prop member comprising a tubular body with a closed top portion, inner and outer walls and opposite sidewalls is attached to the bottom surface of said supporting member and between said prop members.
- [15] The pallet as claimed in claim 10 or 11, further comprising at least one auxiliary prop member having an open top, inner and outer walls, and both sidewalls, said auxiliary prop member being provided with opposite grooves at upper ends of the inner and outer walls thereof such that the heights of the inner and outer walls thereof are the same and lower than that of the sidewalls thereof and the body of said supporting member may be received and coupled in the corresponding grooves thereof.
- [16] The pallet as claimed in claim 10 or 11, wherein said prop member further comprises a reinforcement, comprising inner and outer walls and opposite sidewalls to be engaged within the space defined by inner and outer walls and sidewalls of said body and a bottom portion with outward extensions at both sides thereof for sitting and covering of the lower ends of the sidewalls of said body thereon.
- [17] The pallet as claimed in claim 16, wherein the height of the sidewalls of the body of said prop member is identical to that of the sidewalls of the reinforcement of said prop member.
- [18] The pallet as claimed in claim 16, wherein the height of the sidewalls of the reinforcement of said prop member is lower than that of the sidewalls of the body of said prop member.
- [19] The pallet as claimed in claim 15, wherein said auxiliary prop member further comprises a reinforcement, comprising inner and outer walls and opposite sidewalls to be engaged within the space defined by inner and outer walls and

sidewalls of said body and a bottom portion with outward extensions at both sides thereof for sitting and covering of the lower ends of the sidewalls of said body thereon.

[20] The pallet as claimed in claim 16, wherein said auxiliary prop member further comprises a reinforcement, comprising inner and outer walls and opposite sidewalls to be engaged within the space defined by inner and outer walls and sidewalls of said body and a bottom portion with outward extensions at both sides thereof for sitting and covering of the lower ends of the sidewalls of said body thereon.

[21] A pallet comprising a plurality of supporting members arranged parallel at a certain interval with one another, a plurality of upper plate members placed parallel at a certain interval with one another across top surfaces of the supporting members, and at least a pair of prop members attached to both ends of the bottom surface of each of the supporting members, wherein said supporting members have a body in the tubular shape and said prop members have a body with an open top, inner and outer walls and opposite sidewalls, characterized in that;

lower ends of opposite outer walls of said upper plate member extend inwardly to some extent so that said upper plate member may have a cross section in the form of



; and

said supporting members are provided with opposite downward grooves defined by a downward projection at the distal ends of the respective wings thereof.

[22] The pallet as claimed in claim 21, wherein opposite ends of said upper plate members are covered with a guard.

[23] The pallet as claimed in claim 21 or 22, wherein lower ends of opposite outer walls of said upper plate member extend inwardly to meet or almost reach the adjacent inner wall thereof so that said upper plate member may have a cross section in the form of



.

[24] The pallet as claimed in claim 21 or 22, wherein said prop members have a groove formed between the sidewalls and above the inner wall of the body thereof so that the height of the inner wall is lower than that of the sidewalls thereof; upper ends of the sidewalls of said prop members being received and fitted in the corresponding downward grooves of said supporting members and the bodies of said supporting members being received and coupled in the cor-

responding grooves of the body of said prop member.

- [25] The pallet as claimed in claim 21 or 22, wherein at least one auxiliary prop member comprising a tubular body with a closed top portion, inner and outer walls and opposite sidewalls is attached to the bottom surface of said supporting member and between said prop members.
- [26] The pallet as claimed in claim 21 or 22, further comprising at least one auxiliary prop member having an open top, inner and outer walls, and both sidewalls, said auxiliary prop member being provided with opposite grooves at upper ends of the inner and outer walls thereof such that the heights of the inner and outer walls thereof are the same and lower than that of the sidewalls thereof and the body of said supporting member may be received and coupled in the corresponding grooves thereof.
- [27] The pallet as claimed in claim 21 or 22, wherein said prop member further comprises a reinforcement, comprising inner and outer walls and opposite sidewalls to be engaged within the space defined by inner and outer walls and sidewalls of said body and a bottom portion with outward extensions at both sides thereof for sitting and covering of the lower ends of the sidewalls of said body thereon.
- [28] The pallet as claimed in claim 27, wherein the height of the sidewalls of the body of said prop member is identical to that of the sidewalls of the reinforcement of said prop member.
- [29] The pallet as claimed in claim 27, wherein the height of the sidewalls of the reinforcement of said prop member is lower than that of the sidewalls of the body of said prop member.
- [30] The pallet as claimed in claim 26, wherein said auxiliary prop member further comprises a reinforcement, comprising inner and outer walls and opposite sidewalls to be engaged within the space defined by inner and outer walls and sidewalls of said body and a bottom portion with outward extensions at both sides thereof for sitting and covering of the lower ends of the sidewalls of said body thereon.
- [31] The pallet as claimed in claim 27, wherein said auxiliary prop member further comprises a reinforcement, comprising inner and outer walls and opposite sidewalls to be engaged within the space defined by inner and outer walls and sidewalls of said body and a bottom portion with outward extensions at both sides thereof for sitting and covering of the lower ends of the sidewalls of said body thereon.