

Description

The present invention relates to an apparatus and method for cleaning electronic fuel injectors, and other electronic controlled injections such as air injectors.

Prior art methods of cleaning electronic fuel injectors comprise generally of two methods. The first utilises immersing the injectors or injector tips in the ultrasonic bath of cleaning fluid. This method, however, only cleans the injector nozzle tip and the filter basket. A second method, such as the RAM FIC-109 (trade mark) system, utilises a forced flow and/or forced back flow of cleaning fluid through the injector. Whilst each system has its advantages, they also have their disadvantages in that they do not fully clean all of the pathway of the injector and hence the injector will not operate at optimum efficiency or may need to be replaced.

A third method is that described in U. S. Patent No. 4082565. This device uses a gravity feed of cleaning fluid through the injectors in the normal direction as they are being periodically pulsed with tips being immersed in an ultrasonic bath. This method suffers from disadvantages in that it does not allow impurity particles trapped in the filter basket to be readily removed during cleaning and also requires a separate reservoirs of cleaning fluid and connections to the inlets of the injectors to flow fluid therethrough. The present invention seeks to ameliorate the disadvantage by providing a method and apparatus for cleaning injectors which allows readily flushing out of the filter basket of the injector.

According to the present invention there is provided a method of cleaning an electronically controllable injector, which method comprises the steps of supporting an electronically controllable injector in an ultrasonic bath of cleaning fluid such that at least the outlet tip is immersed and pulsing the injector, characterised in that the frequency of the ultrasonics and the frequency of the pulses are such that the cleaning fluid flows in the reverse direction through the injector as a result of the interaction of the ultrasonics and the pulsing of the injector.

There is disclosed a method of cleaning an electronic fuel injector comprising the steps of supporting an electronic fuel injector in a bath of cleaning fluid such that at least the outlet tip is immersed and then pulsing said injector at frequencies such that the cleaning fluid flows in the reverse direction through the injector.

There is disclosed a method of cleaning an electronic fuel injector comprising the steps of supporting an electronic fuel injector in a ultrasonic bath of cleaning fluid such that at least the outlet tip is immersed and pulsing said injector whereby the cleaning fluid, while being resonated by the ultrasonics, flows in the reverse direction through the injector as a result of the

interaction of the ultrasonics and the pulsing of the injector.

There is disclosed a method of cleaning an electronic fuel injector comprising the steps of supporting an electronic fuel injector in an ultrasonic bath of cleaning fluid such that at least the inlet of the fuel injector is immersed in the cleaning fluid, and pulsing said injectors such that the cleaning fluid flows upwardly through the injector as a result of the interaction of the ultrasonics and the pulsing of the injector.

The present invention will now be described with reference to the accompanying drawings in which:

FIG. 1 shows schematically a partially sectional view of an injector positioned in one embodiment of the present invention;

FIG. 2 illustrates schematically a group of injectors being held in position for cleaning in accordance with one embodiment of the present invention;

FIG. 3 illustrates schematically a group of injectors being held in position for cleaning in accordance with a further embodiment of the present invention;

FIG. 4 illustrates schematically another means of holding an injector for cleaning, not according to the present invention; and

FIG. 5 illustrates schematically another method of cleaning in accordance with a further embodiment of the present invention

In electronic fuel injectors, deposits build up around the nozzle tip, causing the petrol to issue as a stream of fuel, rather than as a fine spray, resulting in a loss of power.

Further the filter basket (3) can be blocked, restricting the flow of petrol through the injectors. Deposits can also, and do, build up around the shaft of the injector pin and on the internal surface of the petrol flow paths thus resulting in loss of efficiency of the injector. The prior art methods do not adequately clean the injector as for example with the use of an ultrasonic bath on its own, the ultrasonics only effectively interact with deposits at the very tip of outlet and do not always remove all of the residue from the filter basket, while with the forced flow or back flow under pressure of cleaning fluid through the injector, reliance is only placed on the cleaning property of the fluid flow and/or pressure to remove the deposits.

Further if a plastic, nylon, or other non-metallic filter basket is used weaker cleaning fluids must be used to prevent degradation of the plastic, nylon or other non-metallic basket. In the case of full immersion in the ultrasonic bath, degradation of plastic, nylon or other non-metallic components of the injector can occur.

In the embodiment of the present invention shown in Figure 1 the fuel injector (10) is held in a plate (4) with the injector outlet nozzle (2) submerged in the cleaning fluid (6) of an ultrasonic bath (not shown)

and is connected to the solenoid input (7). The injector (1) is pulsed at 1.0 - 40.0 m sec at a R.P.M. of between 50-15,000, with the ultrasonic at a frequency of between 10 to 50kHz.

Preferably as shown in Figure 2 the outlet tips (5) are held in a holder (4) such that they are aligned with the epicentre (10) of the transducer, or in the case of a flat or mat transducer (11) the outlet tips (5) are aligned vertically above the transducer to produce optimum ultrasonic interaction to improve the reverse flow and cleaning. Preferably the ultrasonics are operated at a frequency in the range of 25-30 kHz.

Because of the interaction between pulsing of the injector and the ultrasonic resonating of the cleaning fluid, the cleaning fluid (6) flows into the outlet nozzle (2) of the injector and back flows through the filter basket (3) and out of the open inlet (8) of the injector. The cleaning fluid (6) as it flows up through the injector (1) is resonated by the ultrasonics and effectively removes the deposits and residues from all the surfaces throughout the flow path of injector.

Any suitable cleaning fluid can be used such as white spirits, RAM 903 or RAM 904 (trade marks), or warm water with caustic soda if a plastic, nylon or other non-metallic filter basket is used or Carboisol NF (trade mark) in the case of a metal filter basket, High Tech's own specially formulated ASNU™ injector cleaning fluid should be used.

The injectors (1) not according to the present invention could be held in an upright position as shown in Figure 4 wherein the inlet (8) of the injector is immersed in the cleaning fluid (6) and the injectors (1) pushed to draw cleaning fluid through the connectors. Preferably the cleaning fluid is resonated by ultrasonics at a frequency of between 20kHz - 30 kHz.

The injectors (1) not according to the present invention could be fully immersed as shown in Figure 5 with the injectors (1) pulsed to provide flow in either direction or in alternate direction or in alternate directions for specific periods of time. Preferably the cleaning fluid is resonated by ultrasonics.

Claims

1. A method of cleaning an electronically controllable injector, which method comprises the steps of supporting an electronically controllable injector in an ultrasonic bath of cleaning fluid such that at least the outlet tip is immersed and pulsing the injector, characterised in that the frequency of the ultrasonics and the frequency of the pulses are such that the cleaning fluid flows in the reverse direction through the injector as a result of the interaction of the ultrasonics and the pulsing of the injector.
2. A method of cleaning an electronic fuel injector

according to Claim 1 wherein the ultrasonics resonate at a frequency between 10 and 50 kHz.

3. A method of cleaning an electronic fuel injector according to Claim 1 or 2 wherein the injector is pulsed at between 1.0 and 40.0 m sec. at a R.P.M. of between 50-15,000.
4. A method of cleaning an electronic fuel injector according to any one of the preceding claims wherein the injectors are aligned with the epicentre of the transducer of the ultrasonics.
5. A method of cleaning an electronic fuel injector according to Claims 1 to 3 wherein the transducer is a mat transducer and the injectors are aligned substantially normal thereto.
6. A method of cleaning an electronic fuel injector according to any one of the preceding claims wherein the cleaning fluid is white spirits.

Patentansprüche

1. Ein Verfahren zum Reinigen eines elektronisch steuerbaren Einspritzers, mit den Schritten des Halten eines elektronisch steuerbaren Einspritzers in einem Ultraschallbad eines Reinigungsfluids derart, daß wenigstens die Auslaßspitze eingetaucht ist und Pulsieren des Einspritzers, dadurch gekennzeichnet, daß die Frequenz des Ultraschalls und die Frequenz der Pulsation derart sind, daß die Reinigungsflüssigkeit infolge des Zusammenwirkens des Ultraschalls und der Pulsation des Injektors in umgekehrter Richtung durch den Einspritzer strömt.
2. Verfahren zum Reinigen eines elektronischen Kraftstoffeinspritzers nach Anspruch 1, wobei die Resonanzfrequenz des Ultraschalls bei Frequenzen zwischen 10 und 50 kHz liegt.
3. Verfahren zum Reinigen eines elektronischen Kraftstoffeinspritzers nach Anspruch 1 oder 2, wobei der Einspritzer zwischen 1,0 und 40,0 msec bei Drehzahlen zwischen 50 und 15.000 pulsiert wird.
4. Verfahren zum Reinigen eines elektronischen Kraftstoffeinspritzers nach einem der vorangehenden Ansprüche, wobei die Einspritzer mit dem Epizentrum des Wandlers des Ultraschalls ausgerichtet sind.
5. Verfahren zum Reinigen eines elektronischen Kraftstoffeinspritzers nach Anspruch 1 bis 3, wobei der Wandler ein matteder Wandler ist und die

and is connected to the solenoid input (7). The injector (1) is pulsed at 1.0 - 40.0 m sec at a R.P.M. of between 50-15,000, with the ultrasonic at a frequency of between 10 to 50kHz.

Preferably as shown in Figure 2 the outlet tips (5) are held in a holder (4) such that they are aligned with the epicentre (10) of the transducer, or in the case of a flat or mat transducer (11) the outlet tips (5) are aligned vertically above the transducer to produce optimum ultrasonic interaction to improve the reverse flow and cleaning. Preferably the ultrasonics are operated at a frequency in the range of 25-30 kHz.

Because of the interaction between pulsing of the injector and the ultrasonic resonating of the cleaning fluid, the cleaning fluid (6) flows into the outlet nozzle (2) of the injector and back flows through the filter basket (3) and out of the open inlet (8) of the injector. The cleaning fluid (6) as it flows up through the injector (1) is resonated by the ultrasonics and effectively removes the deposits and residues from all the surfaces throughout the flow path of injector.

Any suitable cleaning fluid can be used such as white spirits, RAM 903 or RAM 904 (trade marks), or warm water with caustic soda if a plastic, nylon or other non-metallic filter basket is used or Carboisol NF (trade mark) in the case of a metal filter basket, High Tech's own specially formulated ASNU™ injector cleaning fluid should be used.

The injectors (1) not according to the present invention could be held in an upright position as shown in Figure 4 wherein the inlet (8) of the injector is immersed in the cleaning fluid (6) and the injectors (1) pushed to draw cleaning fluid through the connectors. Preferably the cleaning fluid is resonated by ultrasonics at a frequency of between 20kHz - 30 kHz.

The injectors (1) not according to the present invention could be fully immersed as shown in Figure 5 with the injectors (1) pulsed to provide flow in either direction or in alternate direction or in alternate directions for specific periods of time. Preferably the cleaning fluid is resonated by ultrasonics.

Claims

1. A method of cleaning an electronically controllable injector, which method comprises the steps of supporting an electronically controllable injector in an ultrasonic bath of cleaning fluid such that at least the outlet tip is immersed and pulsing the injector, characterised in that the frequency of the ultrasonics and the frequency of the pulses are such that the cleaning fluid flows in the reverse direction through the injector as a result of the interaction of the ultrasonics and the pulsing of the injector.
2. A method of cleaning an electronic fuel injector

according to Claim 1 wherein the ultrasonics resonate at a frequency between 10 and 50 kHz.

3. A method of cleaning an electronic fuel injector according to Claim 1 or 2 wherein the injector is pulsed at between 1.0 and 40.0 m sec. at a R.P.M. of between 50-15,000.
4. A method of cleaning an electronic fuel injector according to any one of the preceding claims wherein the injectors are aligned with the epicentre of the transducer of the ultrasonics.
5. A method of cleaning an electronic fuel injector according to Claims 1 to 3 wherein the transducer is a mat transducer and the injectors are aligned substantially normal thereto.
6. A method of cleaning an electronic fuel injector according to any one of the preceding claims wherein the cleaning fluid is white spirits.

Patentansprüche

1. Ein Verfahren zum Reinigen eines elektronisch steuerbaren Einspritzers, mit den Schritten des Halten eines elektronisch steuerbaren Einspritzers in einem Ultraschallbad eines Reinigungsfluids derart, daß wenigstens die Auslaßspitze eingetaucht ist und Pulsieren des Einspritzers, dadurch gekennzeichnet, daß die Frequenz des Ultraschalls und die Frequenz der Pulsation derart sind, daß die Reinigungsflüssigkeit infolge des Zusammenwirkens des Ultraschalls und der Pulsation des Injektors in umgekehrter Richtung durch den Einspritzer strömt.
2. Verfahren zum Reinigen eines elektronischen Kraftstoffeinspritzers nach Anspruch 1, wobei die Resonanzfrequenz des Ultraschalls bei Frequenzen zwischen 10 und 50 kHz liegt.
3. Verfahren zum Reinigen eines elektronischen Kraftstoffeinspritzers nach Anspruch 1 oder 2, wobei der Einspritzer zwischen 1,0 und 40,0 msec bei Drehzahlen zwischen 50 und 15.000 pulsiert wird.
4. Verfahren zum Reinigen eines elektronischen Kraftstoffeinspritzers nach einem der vorangehenden Ansprüche, wobei die Einspritzer mit dem Epizentrum des Wandlers des Ultraschalls ausgerichtet sind.
5. Verfahren zum Reinigen eines elektronischen Kraftstoffeinspritzers nach Anspruch 1 bis 3, wobei der Wandler ein matteder Wandler ist und die



Injektoren im wesentlichen rechtwinklig zu diesem ausgerichtet sind.

6. Verfahren zum Reinigen eines elektronischen Kraftstoffeinspritzers nach einem der vorangehenden Ansprüche, wobei die Reinigungsflüssigkeit Testbenzin ist. 5

Revendications 10

1. Procédé de nettoyage d'un injecteur contrôlé électroniquement, ce procédé comprenant les étapes de fixation d'un injecteur contrôlé électroniquement dans un bain ultrasonique de fluide nettoyant, de telle sorte qu'au moins l'embout de sortie soit immergé, et d'impulsion de l'injecteur, caractérisé en ce que la fréquence des ultrasons et la fréquence des impulsions soient telles que le fluide nettoyant circule en direction inverse à travers l'injecteur, ceci résultant de l'interaction des ultrasons et de l'impulsion de l'injecteur. 15 20
2. Procédé de nettoyage d'un injecteur électronique de carburant, selon la revendication 1, dans lequel les ultrasons résonnent à une fréquence comprise entre 10 et 50 kHz. 25
3. Procédé de nettoyage d'un injecteur électronique de carburant, selon l'une des revendications 1 ou 2, dans lequel l'injecteur est soumis à des impulsions de durées comprises entre 1,0 et 40,0 ms, à une fréquence comprise entre 50 et 15 000 par minute. 30 35
4. Procédé de nettoyage d'un injecteur électronique de carburant, selon l'une quelconque des revendications précédentes, dans lequel les injecteurs sont alignés avec l'épicentre du transducteur des ultrasons. 40
5. Procédé de nettoyage d'un injecteur électronique de carburant, selon les revendications 1 à 3, dans lequel le transducteur est un transducteur mat, et les injecteurs sont sensiblement alignés à la perpendiculaire de celui-ci. 45
6. Procédé de nettoyage d'un injecteur électronique de carburant, selon l'une quelconque des revendications précédentes, dans lequel le fluide de nettoyage est du white spirit. 50

55

4

