

CABLE CONNECTION CASING

FIELD OF THE INVENTION

[0001] The present invention relates to a cable splice box, and specifically relates a cable splice box treated with an elastic contracting sleeve for a mid-span branch connection. The present invention provides improvements regarding the issues of difficulty of operation, high cost and the inconsistency of construction quality.

BACKGROUND OF THE INVENTION

[0002] In the technical field of wire transmissions such as telecommunications, cable TV and monitoring systems, fiber-optic cable is widely used for transmitting audio, data and video messages. The fiber-optic cable transmits messages to any designated location with the assistance of a cable splice box to operate a connection and a splice of the cables. The cable splice box is equipped with an end surface for a cable passing therethrough, and the end surface or a cable passing therethrough is disposed with a cable inlet and a cable outlet to allow the cable to pass in and out the cable splice box through the end surface or a cable passing therethrough to perform a connection and branch connection with the fiber-optic cable.

[0003] The conventional fiber-optic cable is mostly used as an intermediate backbone cable. The cable splice box is mostly used for a linear splice operation, which is an operation of connecting a truncated fiber-optic cable with one other truncated fiber-optic cable, and a branching splice operation, which is an operation of connecting a cable having more cores with a number of other cables having fewer of the cores. Accordingly, the end surface

of a cable passing through the cable splice box is equipped with a plurality of cable inlets and outlets, each of which usually provide a truncated fiber-optic cable to pass in and out the cable splice box.

[0004] Present communication networks have expanded into a wide band service era called fiber-to-the-home (FTTH). Telecommunication vendors have to utilize cable splice boxes to connect a variety of main fiber-optic cables distributed everywhere along the way to the respective optic equipment at the user end through branch cable connections by utilizing the cable splice boxes without entirely cutting off the existing cables. Therefore, the cable splice boxes must be applicable not only to the truncated cables passing in and out of the cable splice boxes, but also to the non-truncated cables passing in and out of the cable splice boxes, which means that the cable splice boxes must be applicable for a mid-span branch connection operation, which is an operation to further connect some small quantity of unused cables split from a backbone cable with multi-core optical fibers in the middle portion via a cable splice box to one other intermediate splice cable to connect to a new user end when fiber-optic cable service is required for a customer. In most such cases, the backbone fiber-optic cable, and specifically the fiber-optic cable in use, cannot be cut off.

[0005] The waterproofing treatment operation to the cable inlet and outlet of the cable splice box is very important. Especially because the cable splice boxes installed therein are immersed in water for a long period of time because there is always water accumulation in the manhole and hand hole underground. Therefore, the cable splice boxes must prevent water leakage. Otherwise, once water flows into the cable splice boxes, the fiber-optic cables capable of being used normally for over 20 years will deteriorate and become brittle in only a

couple of years, which adversely affects the quality of the transmission of the broadband signals.

[0006] In the prior art, the methods of waterproofing treatment to a cable splice box, a cable entering the cable splice box through the cable inlet and outlet disposed on the end surface of a cable splice box include three types: the bolt mechanical type, the heat-shrinkable type, and the elastic contracting sleeve type. The components of the bolt mechanical type are complicated, the construction requirements are complicated, and the cost is high. The cost of the heat-shrinkable type is comparatively low. However, the heat-shrinkable type requires the use of torching to heat the heat-shrinkable tube made of plastic material during construction. The procedure may generate toxic gases and cause accidents. It is also difficult to control and maintain consistent construction quality, and it will adversely influence the waterproof effect due to cable bending and distortion. This is inadequate for an underground fiber-optic cable installed in a manhole where water accumulates all year round although it is adequate for use in a hanging or a wall-mounted environment. The elastic contracting sleeve type is the most convenient for construction. In addition, the elastic contracting sleeve type also has the advantages of highly consistent construction quality, an excellent water-proof effect, and a low cost of materials. Therefore, the adoption of the elastic contracting sleeve for performing the waterproofing treatment is the best choice.

[0007] When the waterproofing treatment to the cable inlet and outlet of the cable splice box is performed using the elastic contracting sleeve, the end surface passing through the cable must be formed with a hollow cylindrical tube in a circle-like or ellipse-like shape. The hollow cylindrical tube provides passage for the cable implemented in the connection operation in the cable

splice box to pass therethrough. If waterproofing treatment is implemented using an elastic contracting sleeve, the portion enveloped by contracting the elastic contracting sleeve must be a cylindrical object having no dent or gap on its outer surface and having a cross-section in one of a circle-like or ellipse-like shape. For example, the elastic contracting sleeve is disposed on a cable having a cross-section in a circle-like shape, a cable inlet and outlet of a hollow cylindrical tube, each of which is in a circle-like or ellipse-like shape, and a cable having a cross-section in an ellipse-like shape, to achieve a good waterproof effect. However, for a cable splice box where the waterproofing treatment is done using the elastic contracting sleeve, during the intermediately introduced branched connection operation, on the condition that the cable must not be truncated, the portion of the cable to be operated with the intermediately introduced branched connection must be folded in a U shape, and then the U-shaped cable having two cable segments is inserted and passes through the elastic contracting sleeve and the hollow cylindrical tube, which is the cable inlet and outlet, disposed on the end surface for the cable passing through the cable splice box, and so the cable enters the cable splice box, to implement the intermediately introduced branched connection operation. However, the cross-sections of the two cable segments of the U shaped cable are circle-like and have different circle centers. After the two cable segments are directly enveloped with an elastic contracting sleeve, there will be gaps between the two cable segments and so it is unable to form a waterproof structure. Therefore, it is necessary to utilize a gap-filling waterproof auxiliary device disposed on the U-shaped cable with two cable segments to form a first waterproof structure which is cylindrical, which makes the two cross-sections of the two cable segments into one cross-section in a circle-like or ellipse-like shape without having any

dent or gap on the outer surface of the first waterproof structure. And then the U-shaped cable with two cable segments is inserted and passes through the elastic contracting sleeve and the hollow cylindrical tube, i.e. the cable inlet and outlet, disposed on the end surface for the cable passing through the cable splice box, wherein a portion of the first waterproof structure is not inserted into the hollow cylindrical tube, and the elastic contracting sleeve contracts to envelop an external portion of the hollow cylindrical tube and an external portion of the first waterproof structure that is not inserted into the hollow cylindrical tube. Due to the fact that there is no dent or gap on the outer surface of the first waterproof structure with a cross-section in a circle-like or ellipse-like shape, a second waterproof structure is accordingly formed. Therefore, it is possible to complete an intermediately introduced branched connection operation by using an elastic contracting sleeve to implement a waterproofing treatment between the cables to be intermediately introduced branched connected and the cable inlet and outlet when using a cable splice box to implement an intermediately introduced branched connection operation.

[0008] In the prior art, the methods to form the first waterproof structure by using a gap-filling waterproof auxiliary device include the following.

[0009] 1. Only a waterproof adhesive substance, or tape, having adhesion and plasticity is used in a great amount to wind and envelop a position of the two cable segments of the U-shaped cable to be inserted into the elastic contracting sleeve to implement the waterproofing treatment. A short section of the wound and enveloped position is hand moulded to obtain a cylindrical body having a cross-section of a circle-like or ellipse-like shape. Accordingly, the first waterproof structure is formed. However, disadvantages include that the resultant shapes and sizes of the cylindrical bodies, and the appearances are free

from any dent or gap formed on the surfaces of the cylindrical bodies, each of which has a cross-section having a circle-like or ellipse-like shape, formed each time by each person after being hand moulded will never be identical, so as to cause the issues of inconsistency to the construction quality. After being hand moulded and before being enveloped by the elastic contracting sleeve, the shape of the position of the short section could be changed because of an impact or squeeze in the construction process.

[0010] 2. Each position of the two cable segments of the U-shaped cable to undergo the waterproofing treatment by using an elastic contracting sleeve is wound and enveloped with an adequate amount of adhesive tape having adhesion and plasticity. And then a solid bundling body having two pieces capable of matching the two cable segments is assembled thereto to form a structure having a circle-like or ellipse-like cross-section without a dent or gap therebetween. The bundling body is tightly screwed to form the first waterproof structure. This type of construction can prevent the inconsistency problem of construction quality previously mentioned. However its disadvantages include that the components and construction sequence are complicated, the operation is difficult, and the cost is high. In addition, it is impossible to take advantage of the radial contracting force exerted by the elastic contracting sleeve to continuously maintain tightness between the solid bundling body and the two cable segments.

[0011] Based on the above descriptions, global telecommunication vendors and the related suppliers began to widely adopt fiber-optic cables to replace traditional cables, and widely utilize cable slice boxes for the mid-span branch connection operations to connect a variety of optical fibers in the main fiber-optic cables distributed everywhere along the way to the respective optic

equipment at the user end through branch cable connections. It is possible to solve the problems of difficult operation, high cost and inconsistent construction quality when implementing a waterproofing treatment to the cable for a mid-span branch connection by using an elastic contracting sleeve, and to develop and manufacture a novel and advanced cable splice box with easier operation, much lower cost, more consistent construction quality and sufficient utilization of the radial contracting force of the elastic contracting sleeve to continuously maintain the tightness of the first waterproof structure in the cable splice box. Accordingly, the construction quality of the fiber-optic cable network of the related vendors will be significantly improved.

[0012] Therefore, based on the drawbacks of the prior art, “the cable splice box” of the present invention is disclosed after dedicated development and research. The brief description of the present invention is as follows.

SUMMARY OF THE INVENTION

[0013] To overcome the shortages of the prior art, the purpose of the present invention is to provide a cable splice box. The cable splice box includes an end surface passing therethrough a cable having two cable segments respectively passing in and out of the cable splice box; a first waterproof structure, including a pillar including a pillar body having at least two longitudinal grooves, each of which has a bore diameter X configured to accommodate one of the two cable segments; a longitudinal surface having at least two longitudinal slits, each of which has a width Y larger than or equal to X , corresponds to one of the at least two longitudinal grooves, and forms an opening thereon; and at least two elastic pieces, each of which forms one edge of one of the at least two longitudinal slits; and a hollow cylindrical tube

disposed on the end surface, having an outer surface and providing a mid-span branch connection; and a second waterproof structure including an elastic contracting sleeve disposed on the outer surface and enveloping the first waterproof structure. In addition, the outer surfaces of the at least two longitudinal elastic pieces jointly (integrally, or combined) and partly define the longitudinal surface. In addition, the pillar is an elastic body. In addition, the bore diameter X is one of the minimum and maximum bore diameters of each of the at least two longitudinal grooves. In addition, in the cable splice box, each of the at least two longitudinal elastic pieces has two extensions defining two edges of each of the at least two longitudinal slits; the slit width Y is selected from the group consisting of an original slit width W_1 less than X and greater than zero, an original slit width W_2 equal to zero, and an original slit width W_3 which is unmeasurable as a result of the two overlapping extensions. In addition, the cable splice box further includes a waterproof glue having adhesiveness and plasticity and disposed between one of the at least two longitudinal grooves and one of the two cable segments passing therethrough. In addition, the first waterproof structure has a cross-section being one of a circle-like or ellipse-like shape.

[0014] The present invention also discloses a pillar used for a cable splice box to form therein a waterproof structure. The pillar includes a pillar body having at least two longitudinal grooves, each of which has a bore diameter X configured to accommodate a cable segment; a longitudinal surface having at least two longitudinal slits, each of which has a width Y larger than or equal to X , corresponds to one of the two longitudinal grooves, and forms an opening thereon; and two longitudinal elastic pieces, each of which is disposed on one of the at least two longitudinal slits to keep the cable segment in the respective

longitudinal groove. In addition, the outer surfaces of the at least two longitudinal elastic pieces jointly (integrally, or combined) and partly define the longitudinal surface. In addition, the pillar is an elastic body. In addition, the bore diameter X is one of the minimum and maximum bore diameters of each of the at least two longitudinal grooves. In addition, in the pillar, each of the at least two longitudinal elastic pieces has two extensions defining two edges of each of the at least two longitudinal slits; the slit width Y is selected from the group consisting of an original slit width W_1 less than X and greater than zero, an original slit width W_2 equal to zero, and an original slit width W_3 which is unmeasurable as a result of the two overlapping extensions. In addition, the pillar coordinates with an elastic contracting sleeve to form a waterproof splice box unit. In addition, the pillar further includes a waterproof glue having adhesiveness and plasticity and disposed between one of the at least two longitudinal grooves and the cable segment passing therethrough. In addition, the first waterproof structure has a cross-section being one of a circle-like or ellipse-like shape.

[0015] The cable splice box of the present invention includes a pillar, by which the cable for the mid-span branch connection and the pillar form the first waterproof structure in a cylindrical shape having no dent or gap between the cable and the pillar. And the first waterproof structure has a cross-section in a circle-like or ellipse-like shape. Accordingly, the waterproofing treatment between the cable inlet and outlet, which is disposed on the hollow cylindrical tube on the end surface for a cable passing through the cable splice box, and the cables by using the cable splice box with the elastic contracting sleeve is novel and advanced over the prior technique. So the operation is much easier, the cost is much lower, and the construction quality is more consistent. Moreover, in the

cable splice box, the radial contracting force of the elastic contracting sleeve continuously maintains the tightness of the first waterproof structure. The contraction quality of the fiber-optic cable network built by the related suppliers will substantially improve.

BRIEF DESCRIPTION OF THE DRAWINGS

[0016] Fig. 1(A) is a diagram showing a cable splice box according to the first Embodiment of the present invention;

[0017] Fig. 1(B) is a diagram showing an end surface for a cable passing therethrough and a hollow cylindrical tube in the cable splice box according to the first Embodiment of the present invention;

[0018] Fig. 1(C) is a diagram showing a cable for a mid-span branch connection, which passes through a hollow cylindrical tube and so passes in and out of the cable splice box according to the first Embodiment of the present invention;

[0019] Fig. 2(A) is a diagram showing a pillar in the cable splice box according to the first Embodiment of the present invention;

[0020] Fig. 2(B) is a diagram showing a cross-section of a cylindrical portion of the pillar in the cable splice box according to the first Embodiment of the present invention;

[0021] Fig. 2(C) is a diagram showing a cross-section of a cylindrical portion of the pillar according to the first Embodiment of the present invention, wherein a longitudinal slit having a width Y is larger than a bore diameter X of the longitudinal groove;

[0022] Fig. 3(A) is a diagram showing an elastic contracting sleeve in the cable splice box according to the first Embodiment of the present invention;

[0023] Fig. 3(B) is a diagram showing a waterproof glue having adhesiveness and plasticity in the cable splice box according to the first Embodiment of the present invention;

[0024] Fig. 3(C) is a diagram showing a waterproof band having adhesiveness and plasticity in the cable splice box according to the first Embodiment of the present invention;

[0025] Fig. 4(A) is a diagram showing a pillar in the cable splice box according to the first Embodiment of the present invention;

[0026] Fig. 4(B) is a diagram showing the position that two cable segments for a mid-span branch connection are wound by the waterproof band having adhesiveness and plasticity before the elastic contracting sleeve is used for a waterproofing treatment in the cable splice box according to the first Embodiment of the present invention;

[0027] Fig. 4(C) is a diagram showing a first waterproof structure formed by the pillar and the cables having two cable segments for a mid-span branch connection in the cable splice box according to the first Embodiment of the present invention;

[0028] Fig. 4(D) is a diagram showing a cross-section of a cylindrical portion of the first waterproof structure in the cable splice box according to the first Embodiment of the present invention;

[0029] Fig. 5(A) is a diagram showing the cable splice box according to the first Embodiment of the present invention, wherein the elastic contracting sleeve is going to contract to envelop an outer surface of the hollow cylindrical tube and an outer surface of the first waterproof structure;

[0030] Fig. 5(B) is a diagram showing the cable splice box according to the first Embodiment of the present invention, wherein the elastic contracting

sleeve is going to contract to envelop an outer surface of the hollow cylindrical tube and an outer surface of the first waterproof structure, to form the second waterproof structure;

[0031] Fig. 5(C) is a diagram showing the cable splice box according to the first Embodiment of the present invention, wherein the elastic contracting sleeve is going to contract to envelop an outer surface of the hollow cylindrical tube and an outer surface of the first waterproof structure, and form the second waterproof structure;

[0032] Fig. 5(D) is a diagram showing the cable splice box according to the first Embodiment of the present invention, wherein the cable splice box is implemented with the waterproofing treatment by using the elastic contracting sleeve for a mid-span branch connection;

[0033] Fig. 6(A) is a diagram showing a cross-section of a pillar in a cable splice box according to the second Embodiment of the present invention, wherein the original slit width W_2 of the two grooves of the pillar equals 0, representing that the two edges of the longitudinal elastic pieces contact each other;

[0034] Fig. 6(B) is a diagram showing a cross-section of a pillar in a cable splice box according to the second Embodiment of the present invention, wherein a longitudinal slit has a slit width Y after operation being larger than the bore size X of the longitudinal groove of the pillar;

[0035] Fig. 6(C) is a diagram showing a cross-section of a pillar of the first waterproof structure in a cable splice box according to the second Embodiment of the present invention;

[0036] Fig. 7(A) is a diagram showing a cross-section of a pillar in a cable splice box according to the third Embodiment of the present invention, wherein

the original slit width W_3 of the two grooves of the pillar is unable to be measured as a result of the two overlapping extensions, and W_2 equals 0, representing that the two edges of the longitudinal elastic pieces are in contact with each other;

[0037] Fig. 7(B) is a diagram showing a cross-section of a pillar in a cable splice box according to the third Embodiment of the present invention, wherein a longitudinal slit has a slit width Y after the operation being larger than the bore size X of the longitudinal groove of the pillar;

[0038] Fig. 7(C) is a diagram showing a cross-section of a pillar of the first waterproof structure in a cable splice box according to the third Embodiment of the present invention;

[0039] Description of the reference numerals

- 1 cable splice box
- 2 end surface
- 3 hollow cylindrical tube
- 4 cable for mid-span branch connection
- 401 two cable segments of the cable for the mid-span branch connection
- 402 portion of the cable for the mid-span branch connection
- 5 pillar
- 6 pillar body
- 7 longitudinal groove
- 8 longitudinal surface
- 9 longitudinal slit
- 10 opening
- 11 elastic piece
- 12 first waterproof structure

13 elastic contracting sleeve

14 outer surface of the hollow cylindrical tube

15 outer surface of the first waterproof structure

16 second waterproof structure

17 adhesive glue having adhesiveness and plasticity

X bore size of the longitudinal groove

Y slit width after the operation

W₁ original slit width of the longitudinal groove of the pillar of the first Embodiment

W₂ original slit width of the longitudinal groove of the pillar of second Embodiment

W₃ original slit width of the longitudinal groove of the pillar of third Embodiment

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0040] The cable splice box disclosed in the present invention will now be described for more concrete understanding with reference to the following embodiments, so it can be implemented by the person skilled in the art. However, the implementation of the present invention is not restricted to the following embodiments. The person skilled in the art can predict other embodiments according to the technical spirit of the embodiments disclosed in the present invention. Those predicted embodiments still belong to the scope of the present invention.

[0041] The first Embodiment

[0042] Please refer to Figs. 1(A)-5(D), each of which shows a cable splice box 1 according to the First Embodiment of the present invention. The cable

splice box 1 includes an end surface 2 passing therethrough a cable 4 having two cable segments 401 respectively passing in and out the cable splice box 1; a first waterproof structure 12 including a pillar 5 (please refer to Fig. 2(A)) including a pillar body 6 having at least two longitudinal grooves 7, each of which has a bore diameter X configured to accommodate one of the two cable segments 401; a longitudinal surface 8 having at least two longitudinal slits 9, each of which has a width Y not less than X, corresponds to one of the at least two longitudinal grooves 7, and forms an opening 10 thereon; and at least two elastic pieces 11, each of which forms on one edge of one of the at least two longitudinal slits 9; and a hollow cylindrical tube 3 disposed on the end surface 2, having an outer surface 14 and providing a mid-span branch connection; and a second waterproof structure 16 including an elastic contracting sleeve 13 disposed on the outer surface 15 and enveloping the first waterproof structure 12 (please refer to Figs. 5(A) to 5(D)). In addition, according to the cable splice box 1 of the first Embodiment of the present invention, the outer surfaces of the at least two longitudinal elastic pieces 11 jointly (integrally, or combined) and partly define the longitudinal surface 8 (please refer to Figs. 2(A) to 2(C)). In addition, according to the cable splice box 1 of the first Embodiment of the present invention, the pillar 5 is an elastic body 6. In addition, according to the cable splice box 1 of the first Embodiment of the present invention, the bore diameter X is the maximum bore diameters of each of the at least two longitudinal grooves 7. In addition, according to the cable splice box 1 of the first Embodiment of the present invention, each of the at least two longitudinal elastic pieces 11 has two extensions defining two edges of each of the at least two longitudinal slits 9; the slit width Y is selected from the group consisting of an original slit width W_1 less than X and greater than zero, an original slit width

W_2 equal to zero, and an original slit width W_3 which is unmeasurable as a result of the two overlapping extensions. In addition, according to the cable splice box 1 of the first Embodiment of the present invention, the cable splice box 1 further includes a waterproof glue having adhesiveness and plasticity (please refer to Figs. 3(B) to 3(C)) and disposed between one of the at least two longitudinal grooves 7 and one of the two cable segments 401 passing therethrough (please refer to Figs. 4(A) to 4(D)). In addition, the first waterproof structure 12 has a cross-section being one of a circle-like and ellipse-like shape (please refer to Fig. 4(D)). A cable splice box 1 used in the first Embodiment of the present invention includes an end surface 2 for a cable 4 passing in and out of the cable splice box 1. The end surface 2 is disposed thereon with a hollow cylindrical tube 3 for the cable 4 for the mid-span branch connection to pass in and out of the cable splice box 1. A hard plastic skin of a portion 402 on the cable 4 for the mid-span branch connection should be unskinned, and then the cable 4 is bent into a U shape. The unskinned portion of the U-shaped cable and the other skinned portion of the two cables segments 401 pass through the hollow cylindrical tube 3 and pass into the cable splice box 1 in a dual-cable manner. The waterproofing treatment between the two cable segments 401 and the hollow cylindrical tube 3 is implemented by using an elastic contracting sleeve 13 (please refer to Fig. 1(C)). Due to the fact that the cross-sections of the two cable segments 401 are circle-like and have different circle centers, if an elastic contracting sleeve 13 is merely used to envelop them and the cylindrical tube 3 by contracting the elastic contracting sleeve 13, there will be a gap between the two cable segments 401 when aligned in parallel and it is not possible to form an effective waterproof structure. Furthermore, the outer diameter of the cable 4 is less than the bore diameter X of the longitudinal

groove 7. Therefore, the positions of each of the two cable segments 401 for the waterproofing treatment by the elastic contracting sleeve 13 should be wound with an adequate amount of the adhesive band 17 having adhesiveness and plasticity (please refer to Fig. 4(B)), so that the cross-sections of each of the two segments wound with the adhesive band 17 having adhesiveness and plasticity is in a circle-like shape and the diameters thereof are equal to or fairly greater than the bore diameter X of the cross-section in a circle-like shape of the longitudinal slit 7 of the pillar 5 (please refer to Figs. 2(B) and 4(D)). The portion of the U-shaped cable segments 402 for the mid-span branch connection and the portions of the two cable segments 401 wound with the adhesive band 17 having adhesiveness and plasticity are put and accommodated in the longitudinal groove 7 of the pillar 5. Only manual operation is required to outwardly open the elastic pieces 11 of the opening 10 of the longitudinal groove 7 with fingers to make the original slit width W_1 of the longitudinal groove 7 form the slit width Y after the operation larger than the maximum bore diameter X of the longitudinal groove 7. This makes it easier to put and accommodate the portions of the two cable segments 401, each of which is wound with an adequate amount of the adhesive band having adhesiveness and plasticity in the opening 10. When the fingers release to allow the elastic pieces of the opening 10 to return to their original locations, a first waterproof structure 12 being cylindrical and having a cross-section in a circle-like shape is easily formed between the two cable segments 401 and the pillar 5 (please refer to Figs. 4(A) to 4(D)). Each of the two cable segments 401 is accommodated in and matches the longitudinal groove 7, and therefore each of the two cable segments 401 is not easily separated therefrom before the first waterproof structure 12 is enveloped and contracted by the elastic contracting sleeve 13. In addition, an outer surface

of the first waterproof structure 12 being cylindrical can be wound with one more round or an adequate amount of the adhesive band 17 having adhesiveness and plasticity to more perfectly secure the waterproof effect. After the operation of the first waterproof structure 12, the portions 402 for the mid-span branch connection are passed through, or inserted into, the elastic contracting sleeve 13 and the portions of the two cable segments 401, which excludes a portion of the first waterproof structure to be wound with the elastic contracting sleeve 13, are passed into the hollow cylindrical tube 3, so that a portion of the first waterproof structure 12 to be enveloped and contracted by the elastic contracting sleeve 13 connects to each other at a position outside of the hollow cylindrical tube 3. And then the two cable segments 401 passing through the hollow cylindrical tube and passing into the cable splice box 1 are fixed in the cable splice box 1. The elastic contracting tube 13 contracts to envelop the outer surface 14 of the hollow cylindrical tube 3 and connects to the outer surface 15 of the waterproof structure at a position outside of the hollow cylindrical tube 3. Accordingly, the second waterproof structure 16 is formed between the hollow cylindrical tube 3 and the first waterproof structure 12. The cable splice box 1 used in the first Embodiment of the present invention can form a first waterproof structure having a cross-section in a circle-like shape between the pillar 5 and the two cable segments 401 via a simple operation. It will be very convenient to use an elastic contracting sleeve 13 to implement the waterproofing treatment between the cable 4 for a mid-span branch connection and the hollow cylindrical tube 3, by which the problems of the difficult operation, high cost and inconsistent construction quality in the prior art can be overcome. Moreover, each of the elastic pieces 11 of the longitudinal groove 7 matches the gap between the pillar 5 and the two cable segments 401 to form the first waterproof structure 12, and

the elastic contracting sleeve 13 contracts to the first waterproof structure. Therefore, the radial contracting force exerted by the elastic contracting sleeve 13 is sufficient and long-lasting and used to maintain the tightness between the pillar 5 and the two cable segments 401. It is clear to see that the cable splice box in the first Embodiment of the present invention can certainly overcome the shortages of the prior art.

[0043] The second Embodiment

[0044] Please refer to Figs. 6(A) to 6(C) and Figs. 1(A) to 5(D). Fig. 6(A) is a diagram showing a cross-section of a pillar included in a cable splice box 1 according to the second Embodiment of the present invention. The difference between the pillar 5 of the second Embodiment and that of the first Embodiment is that the original slit width W_2 of the two grooves 7 of the pillar 5 used in the second Embodiment equals 0 (please refer to Figs. 6(A) to 6(C)), representing that the two edges of the openings 10 on the longitudinal groove 7 contact each other.

[0045] The third Embodiment

[0046] Please refer to Figs. 7(A) to 7(C) and Figs. 1(A) to 5(D). Fig. 7(A) is a diagram showing a cross-section of a pillar included in a cable splice box 1 according to the third Embodiment of the present invention. The difference between the pillar 5 of the third Embodiment and that of the first Embodiment is that the original slit width W_3 of the two grooves 7 of the pillar 5 is unable to be measured as a result of the two overlapping extensions (please refer to Fig. 7(A) to 7(C)), indicating that the two edges of the openings 10 of the two grooves 7 surpass each other.

[0047] Based on the descriptions of the above first, second and third Embodiments, the cable splice box of the present invention overcomes the

shortcomings of the prior art and is more convenient to implement the waterproofing treatment using the elastic contracting sleeve for the operation between the cable for a mid-span branch connection and the cable inlet and outlet of the cable splice box. This makes the operation much easier, the cost lower and the construction quality more consistent, and thereby improves the construction quality of the fiber-optic network of the telecommunication vendors.

[0048] Embodiments:

1. A cable splice box, comprising an end surface passing therethrough a cable having two cable segments respectively passing in and out the cable splice box; a first waterproof structure, including a pillar including a pillar body having at least two longitudinal grooves, each of which has a bore diameter X configured to accommodate one of the two cable segments; a longitudinal surface having at least two longitudinal slits, each of which has a width Y not less than X , corresponds to one of the at least two longitudinal grooves, and forms an opening thereon; and at least two elastic pieces, each of which forms on one edge of one of the at least two longitudinal slits; and a hollow cylindrical tube disposed on the end surface, having an outer surface and providing a mid-span branch connection; and a second waterproof structure including an elastic contracting sleeve disposed on the outer surface and enveloping the first waterproof structure.
2. The cable splice box according to Embodiment 1, wherein outer surfaces of the at least two longitudinal elastic pieces jointly and partly define the longitudinal surface.
3. The cable splice box according to Embodiment 1 or 2, wherein the pillar is an elastic body.

4. The cable splice box according to any one of Embodiments 1 to 3, wherein the bore diameter X is one of the minimum and maximum bore diameters of each of the at least two longitudinal grooves.
5. The cable splice box according to any one of Embodiments 1 to 4, wherein:
each of the at least two longitudinal elastic pieces has two extensions defining two edges of each of the at least two longitudinal slits;
the slit width Y is selected from the group consisting of an original slit width W_1 less than X and greater than zero, an original slit width W_2 equal to zero, and an original slit width W_3 which is unmeasurable as a result of the two overlapping extensions.
6. The cable splice box according to any one of Embodiments 1 to 5, further comprising a waterproof glue having adhesiveness and plasticity and disposed between one of the at least two longitudinal grooves and one of the two cable segments passing therethrough.
7. The cable splice box according to any one of Embodiments 1 to 6, wherein the first waterproof structure has a cross-section being one of a circle-like and ellipse-like shape.
8. A pillar used for a cable splice box to form therein a waterproof structure, comprising a pillar body having at least two longitudinal grooves, each of which has a bore diameter X configured to accommodate a cable segment; a longitudinal surface having at least two longitudinal slits, each of which has a width Y larger than or equal to X , corresponds to one of the two longitudinal grooves, and forms an opening thereon; and two longitudinal elastic pieces, each of which is disposed on one of the at least two longitudinal slits to keep the cable segment in the respective longitudinal groove.

9. The pillar according to Embodiment 8, wherein outer surfaces of the at least two longitudinal elastic pieces jointly and partly define the longitudinal surface.
10. The pillar according to Embodiment 8 or 9, wherein the pillar is an elastic body.
11. The pillar according to any one of Embodiments 8 to 10, wherein the bore diameter X is one of the minimum and maximum bore diameters of each of the at least two longitudinal grooves.
12. The pillar according to any one of Embodiments 8 to 11, wherein each of the at least two longitudinal elastic pieces has two extensions defining two edges of each of the at least two longitudinal slits; the slit width Y is selected from the group consisting of an original slit width W_1 less than X and greater than zero, an original slit width W_2 equal to zero, and an original slit width W_3 which is unmeasurable as a result of the two overlapping extensions.
13. The pillar according to any one of Embodiments 8 to 12, wherein the pillar coordinates with an elastic contracting sleeve to form a waterproof splice box unit.
14. The pillar according to any one of Embodiments 8 to 13, further comprising a waterproof glue having adhesiveness and plasticity and disposed between one of the at least two longitudinal grooves and the cable segment passing therethrough.
15. The pillar according to any one of Embodiments 8 to 14, wherein the first waterproof structure has a cross-section being one of a circle-like and ellipse-like shape.

[0049] This disclosure is intended to cover various modifications and similar arrangements included within the spirit and scope of the appended claims, which are to be accorded with the broadest interpretation so as to encompass all such modifications and similar structures.

WHAT IS CLAIMED IS:

1. A cable splice box, comprising:

an end surface passing therethrough a cable having two cable segments respectively passing in and out the cable splice box;

a first waterproof structure, including:

a pillar including:

a pillar body having at least two longitudinal grooves, each of which has a bore diameter X configured to accommodate one of the two cable segments;

a longitudinal surface having at least two longitudinal slits, each of which has a width Y larger than or equal to X , corresponds to one of the at least two longitudinal grooves, and forms an opening thereon; and

at least two elastic pieces, each of which forms on one edge of one of the at least two longitudinal slits; and

a hollow cylindrical tube disposed on the end surface, having an outer surface and providing a mid-span branch connection; and

a second waterproof structure including an elastic contracting sleeve disposed on the outer surface and enveloping the first waterproof structure.

2. The cable splice box according to Claim 1, wherein outer surfaces of the at least two longitudinal elastic pieces jointly and partly define the longitudinal surface.

3. The cable splice box according to Claim 1, wherein the pillar is an elastic body.

4. The cable splice box according to Claim 1, wherein the bore diameter X is one of the minimum and maximum bore diameters of each of the at least two

longitudinal grooves.

5. The cable splice box according to Claim 1, wherein:

each of the at least two longitudinal elastic pieces has two extensions defining two edges of each of the at least two longitudinal slits;

the slit width Y is selected from the group consisting of an original slit width W_1 less than X and greater than zero, an original slit width W_2 equal to zero, and an original slit width W_3 which is unmeasurable as a result of the two overlapping extensions.

6. The cable splice box according to Claim 1, further comprising a waterproof glue having adhesiveness and plasticity and disposed between one of the at least two longitudinal grooves and one of the two cable segments passing therethrough.

7. The cable splice box according to Claim 1, wherein the first waterproof structure has a cross-section being one of a circle-like and ellipse-like shape.

8. A pillar used for a cable splice box to form therein a waterproof structure, comprising:

a pillar body having at least two longitudinal grooves, each of which has a bore diameter X configured to accommodate a cable segment;

a longitudinal surface having at least two longitudinal slits, each of which has a width Y larger than or equal to X , corresponds to one of the two longitudinal grooves, and forms an opening thereon; and

two longitudinal elastic pieces, each of which is disposed on one of the at least two longitudinal slits to keep the cable segment in the respective longitudinal groove.

9. The pillar according to Claim 8, wherein outer surfaces of the at least two

- longitudinal elastic pieces jointly and partly define the longitudinal surface.
10. The pillar according to Claim 8, wherein the pillar is an elastic body.
 11. The pillar according to Claim 8, wherein the bore diameter X is one of the minimum and maximum bore diameters of each of the at least two longitudinal grooves.
 12. The pillar according to Claim 8, wherein:
 - each of the at least two longitudinal elastic pieces has two extensions defining two edges of each of the at least two longitudinal slits;
 - the slit width Y is selected from the group consisting of an original slit width W_1 less than X and greater than zero, an original slit width W_2 equal to zero, and an original slit width W_3 which is unmeasurable as a result of the two overlapping extensions.
 13. The pillar according to Claim 8, wherein the pillar coordinates with an elastic contracting sleeve to form a waterproof splice box unit.
 14. The pillar according to Claim 8, further comprising a waterproof glue having adhesiveness and plasticity and disposed between one of the at least two longitudinal grooves and the cable segment passing therethrough.
 15. The pillar according to Claim 8, wherein the first waterproof structure has a cross-section being one of a circle-like and ellipse-like shape.