

An Agent-Based Authentication And Key Agreement Method For Devices Without SIM Card

Field of the Invention

This invention relates to a method and system for granting devices without Subscriber Identity Module (SIM) card access to the core network. Particularly, this invention relates to a method and system for registering devices without SIM card to the core network and subsequently accessing other servers via the core network.

Summary of the Prior Art

In current 3G/4G cellular networks, mutual authentications are employed between User Equipment (UE) and networks, to protect mobile devices and networks from being eavesdropped or manipulated during data communication. The current mutual authentication protocol employed by 3G/4G is Authentication and Key Agreement (AKA). To perform AKA, the UE and the Core Network are required to have some pre-shared confidential information kept on both sides.

In 3G/4G networks, at the network side, the credentials are kept in servers named Home Subscriber Server (HSS); while at the UE side, the credentials are kept in an isolated device named Universal Subscriber Identity Module (USIM) card. The USIM card is a device embedded in a USIM slot inside a UE. USIM and UE can exchange information via a special interface. Currently, 3G/4G networks use symmetric keys in the mutual authentication. Hence, for a given International Mobile Subscriber Identification (IMSI), the credentials kept in the corresponding USIM and HSS are the same.

The cost of USIM is around 1 US dollar. This is acceptable for UE such as mobile phones. However, in future, most of the Internet of Thing (IoT) devices are low cost devices. The cost of USIM may be too much for this kind of devices. Thus, one skilled in the art strives to a method of connecting IoT devices to the Internet at a low cost.

When UE wants to access the network and transmits data, it has to do mutual authentication with the core network based on AKA. In the Evolved Packet System (EPS) AKA procedure, UE first sends an Attach Request to the Mobility Management Entity (MME). The MME forwards the Attach request to the HSS which subsequently generates one or multiple authentication vector based on the credentials shared with UE. The authentication vectors are sent to MME which subsequently sends authentication material to UE. The UE authenticates the network and then sends an authentication code to MME. The MME then verifies the authentication code and authenticates the UE. After authentication, UE exchanges key material with MME and eNB to further generate session keys for control and data plane.

It is important to note that this authentication scheme requires many rounds of interactions between the UE and the core network. This is acceptable for the current network with the current volume of mobile devices connected. However, with the increasing implementation of IoT devices, which is believed to reach 50 billion in 2020, the network overhead and the computing burden of the core network will be heavily stressed. Hence, there is a need to modify the current authentication scheme or implement a new authentication scheme.

Summary of the Invention

The above and other problems are solved and an advance in the art is made by systems and methods provided by embodiments in accordance with the invention. A first advantage of embodiments of systems and methods in accordance with the invention is that IoT devices having no SIM card can access the core network directly. Inevitably, this reduces the cost of equipping IoT devices with SIM card. A second advantage of embodiments of systems and methods in accordance with the invention is that the authentication process is improved as the number of interactions is required between the IoT devices and core network is substantially reduced.

The above advantages are provided by embodiments of a system and a method for devices without SIM card (SD) to communicate directly with a core network in accordance with the invention operating in the following manner.

According to a first aspect of the invention, a method for a cellular device (MD) for registering devices without SIM card (SD) to communicate directly with a core network comprising:

- receiving a Device ID from the SD;
- generating an Access ID and key (Ki) for the SD;
- transmitting the Access ID and Ki to the SD.

With reference to the first aspect, in a first possible implementation manner of the first aspect, wherein before the receiving a Device ID from the SD, the method further comprises:

- establishing a first security channel between the SD and the MD;
- transmitting a request to the SD for an identity information of the SD (Device ID);

wherein the receiving a Device ID from the SD comprises:

- receiving the Device ID from the SD within the first security channel;

wherein after the generating an Access ID and key (K_i) for the SD, the method further comprises;

creating a new entry;

appending the new entry to include the Access ID and K_i .

With reference to the first aspect or the first possible implementation manner of the first aspect, in a second possible implementation manner of the first aspect, wherein the generating the Access ID for the SD comprises:

combining the MD's identity with Device ID to obtain the Access ID.

With reference to the first aspect or the first possible implementation manner of the first aspect, in a third possible implementation manner of the first aspect, wherein the generating the Access ID for the SD comprises:

combining the MD's identity with a random number to obtain the Access ID.

With reference to the first aspect or the first possible implementation manner of the first aspect, in a fourth possible implementation manner of the first aspect, wherein the generating the Access ID for the SD comprises:

combining a sequence number assigned to MD with the Device ID to obtain the Access ID.

With reference to anyone of the above possible implementation manner of the first aspect, in a fifth possible implementation manner of the first aspect, wherein the generating the key (K_i) for the SD comprises:

generate K_i using a Key Derivation Function (KDF) with input parameter being one or more of MD's identity, Device ID and Access ID.

With reference to the first aspect, in a sixth possible implementation manner of the first aspect, wherein the generating the Access ID and key (K_i) for the SD comprises:

transmitting the Device ID to the core network; and
receiving the Access ID and K_i from the core network.

With reference to the sixth possible implementation manner of the first aspect, in a seventh possible implementation manner of the first aspect, wherein before the transmitting the Device ID to the core network, the method further comprises:

establishing a second security channel between the SD and the core network;
wherein the transmitting the Device ID to the core network comprises:
transmitting the Device ID to the core network upon establishing the second security channel.

[Note: Method for device without SIM]

According to a second aspect of the invention, a method for communicating a device without SIM card (SD) with a core network comprising:

registering with the core network through a cellular device (MD) to obtain a credential for the SD, the credential comprises an Access ID and a key (K_i);
performing a mutual authentication directly with the core network using the Access ID and K_i ; and
accessing servers via the core network in response to authenticating successfully with the core network.

With reference to the second aspect, in a first possible implementation

manner of the second aspect, wherein the registering with the core network through the MD comprises:

- retrieving the Device ID;
- transmitting the Device ID to the MD;
- receiving the Access ID and K_i from the MD; and
- storing the Access ID and K_i .

With reference to the second aspect or the first possible implementation manner of the second aspect, in a second possible implementation manner of the second aspect, wherein the performing the mutual authentication directly with the core network using the credential comprises:

sending an Attach Request to the core network, the Attach Request comprising the Access ID;

receiving a User Authentication Request from the core network, the User Authentication Request comprising a random number (RAND) and an authentication token ($AUTN_{HSS}$) generated by the core network using Evolved Packet System (EPS) Authentication and Key Agreement (AKA) algorithm;

computing an authentication vector using EPS AKA algorithm with the RAND, the K_i , a serving network identity (SN ID), a sequence number (SQN) as the input parameters and an authentication token ($AUTN_{UE}$) and a response parameter (RES) as the output parameter;

determining whether the $AUTN_{UE}$ is equal to the $AUTN_{HSS}$; and

generating and transmit a User Authentication Response message to the MME in response to the $AUTN_{UE}$ being equal to $AUTN_{HSS}$, the User Authentication Response comprising RES.

With reference to the second aspect or the first possible implementation manner of the second aspect, in a third possible implementation manner of the second aspect, wherein the performing the mutual authentication directly with the core network using the credential comprises:

determining a new key ($K1_i$) using a Key Derivation Function (KDF) with input as K_i and a random number (RAND 1);

generating a Message Authentication Code for Integrity 1 (MAC 1) using $K1_i$ with input parameters comprising Access ID, RAND 1, and Fresh Parameter 1;

generating and transmit an Attach Request to the core network, the Attach Request comprising the Access ID, RAND 1, Fresh Parameter 1, and MAC 1;

receiving an Authentication Success message from the core network, the Authentication Success message includes a one-bit sign (AuthSuccess), a random number (RAND 2) generated by the core network, Fresh Parameter 2, and MAC 2, wherein MAC 2 is generated by the core network using another key ($K2_i$) with AuthSuccess, RAND 2 and Fresh Parameter 2 as input parameters, wherein the Fresh Parameters 1 and 2 are one of a timestamp, counter and sequence number

determining another key ($K2_i$) using KDF with K_i , RAND 1, and RAND 2 as input parameters;

determining a validity of MAC 2 using $K2_i$; and

transmitting and receiving data with the core network in response to MAC 2 being valid.

With reference to the second aspect or the first possible implementation manner of the second aspect, in a fourth possible implementation manner of the second aspect, wherein the performing the mutual authentication directly with the core network using the credential comprises:

generating a Message Authentication Code for Integrity 1 (MAC 1) using K_i with input parameters comprising Access ID and Fresh Parameter 1;

generating and transmitting an Attach Request to the core network, the Attach Request comprising the Access ID, Fresh Parameter 1, and MAC 1, wherein the Fresh Parameter 1 is one of a timestamp, counter and sequence number;

receiving an Authentication Success message from the core network, the Authentication Success message includes a one-bit sign (AuthSuccess), Fresh Parameter 2, and MAC 2;

determining a validity of MAC 2 using K_i ; and

transmitting and receiving data with the core network in response to MAC 2 being valid.

[Note: Cellular device]

According to a third aspect of the invention, a cellular device (MD) for registering devices without SIM card (SD) to communicate directly with a core network comprising:

a processor;

a storage medium;

instructions stored on the storage medium and executable by the processor to:

receive a Device ID from the SD;

generate an Access ID and key (K_i) for the SD;

transmit the Access ID and K_i to the SD.

With reference to the third aspect, in a first possible implementation manner of the third aspect, wherein before the receiving a Device ID from the SD, wherein the instructions stored on the storage medium and executable by the processor to:

establish a first security channel between the SD and the MD;

transmit a request to the SD for an identity information of the SD (Device ID);

wherein the instruction to receiving Device ID from the SD comprises instructions to:

receive the Device ID from the SD within the first security channel;

wherein after the generating an Access ID and key (Ki) for the SD, the instructions stored on the storage medium and executable by the processor to:

create a new entry;

append the new entry to include the Access ID and Ki.

With reference to the third aspect or the first possible implementation manner of the third aspect, in a second possible implementation manner of the third aspect, wherein the instructions to generate the Access ID for the SD comprises instructions to:

combine the MD's identity with Device ID to obtain the Access ID.

With reference to the third aspect or the first possible implementation manner of the third aspect, in a third possible implementation manner of the third aspect, wherein the instruction to generate the Access ID for the SD comprises instructions to:

combining the MD's identity with a random number to obtain the Access ID.

With reference to the third aspect or the first possible implementation manner of the third aspect, in a fourth possible implementation manner of the third aspect, wherein the instruction to generate the Access ID for the SD comprises instructions to:

combine a sequence number assigned to MD with the Device ID to obtain the Access ID.

With reference to anyone of the above possible implementation manner of the third aspect, in a fifth possible implementation manner of the third aspect, wherein

the instruction to generate the key (K_i) for the SD comprises instructions to:

generate K_i using a Key Derivation Function (KDF) with input parameter being one or more of MD's identity, Device ID and Access ID.

With reference to the third aspect, in a sixth possible implementation manner of the third aspect, wherein the generating the Access ID and key (K_i) for the SD comprises:

transmitting the Device ID to the core network; and
receiving the Access ID and K_i from the core network.

With reference to the sixth possible implementation manner of the third aspect, in a seventh possible implementation manner of the third aspect, wherein before the transmitting the Device ID to the core network, instructions stored on the storage medium and executable by the processor to::

establish a second security channel between the SD and the core network;
wherein the instruction to transmit the Device ID to the core network comprises instructions to:

transmit the Device ID to the core network upon establishing the second security channel.

[Note: Device without SIM]

According to a fourth aspect of the invention, a device without SIM card (SD) for communicating with a core network comprising:

a processor;
a storage medium;
instructions stored on the storage medium and executable by the processor to:

register with the core network through a cellular device (MD) to obtain a credential for the SD, the credential comprises an Access ID and a key (K_i);

perform a mutual authentication directly with the core network using the Access ID and K_i ; and

access servers via the core network in response to authenticating successfully with the core network.

With reference to the fourth aspect, in a first possible implementation manner of the fourth aspect, wherein the instruction to register with the core network through the MD comprises instructions to:

retrieve the Device ID;

transmit the Device ID to the MD;

receive the Access ID and K_i from the MD; and

store the Access ID and K_i in the storage medium.

With reference to the fourth aspect or the first possible implementation manner of the fourth aspect, in a second possible implementation manner of the fourth aspect, wherein the instruction performing the mutual authentication directly with the core network using the credential comprises instructions to:

send an Attach Request to the core network, the Attach Request comprising the Access ID;

receive a User Authentication Request from the core network, the User Authentication Request comprising a random number (RAND) and an authentication token ($AUTN_{HSS}$) generated by the core network using Evolved Packet System (EPS) Authentication and Key Agreement (AKA) algorithm;

compute an authentication vector using EPS AKA algorithm with the RAND, the K_i , a

serving network identity (SN ID), a sequence number (SQN) as the input parameters and an authentication token ($AUTN_{UE}$) and a response parameter (RES) as the output parameter;

determine whether the $AUTN_{UE}$ is equal to the $AUTN_{HSS}$; and

generate and transmit a User Authentication Response message to the MME in response to the $AUTN_{UE}$ being equal to $AUTN_{HSS}$, the User Authentication Response comprising RES.

With reference to the fourth aspect or the first possible implementation manner of the fourth aspect, in a third possible implementation manner of the fourth aspect, wherein the instruction performing the mutual authentication directly with the core network using the credential comprises instructions to:

determine a new key ($K1_i$) using a Key Derivation Function (KDF) with input as K_i and a random number (RAND 1);

generate a Message Authentication Code for Integrity 1 (MAC 1) using $K1_i$ with input parameters comprising Access ID, RAND 1, and Fresh Parameter 1;

generate and transmit an Attach Request to the core network, the Attach Request comprising the Access ID, RAND 1, Fresh Parameter 1, and MAC 1;

receive an Authentication Success message from the core network, the Authentication Success message includes a one-bit sign (AuthSuccess), a random number (RAND 2) generated by the core network, Fresh Parameter 2, and MAC 2, wherein MAC 2 is generated by the core network using another key ($K2_i$) with AuthSuccess, RAND 2 and Fresh Parameter 2 as input parameters, wherein the Fresh Parameters 1 and 2 are one of a timestamp, counter and sequence number

determine another key ($K2_i$) using KDF with K_i , RAND 1, and RAND 2 as input parameters;

determine a validity of MAC 2 using K_2 ; and

transmit and receive data with the core network in response to MAC 2 being valid.

With reference to the fourth aspect or the first possible implementation manner of the fourth aspect, in a fourth possible implementation manner of the fourth aspect, wherein the instruction performing the mutual authentication directly with the core network using the credential comprises instructions to:

generate a Message Authentication Code for Integrity 1 (MAC 1) using K_1 with input parameters comprising Access ID and Fresh Parameter 1;

generate and transmit an Attach Request to the core network, the Attach Request comprising the Access ID, Fresh Parameter 1, and MAC 1, wherein the Fresh Parameter 1 is one of a timestamp, counter and sequence number;

receive an Authentication Success message from the core network, the Authentication Success message includes a one-bit sign (AuthSuccess), Fresh Parameter 2, and MAC 2;

determine a validity of MAC 2 using K_2 ; and

transmit and receive data with the core network in response to MAC 2 being valid.

According to a fifth aspect of the invention, a core network for registering devices without SIM card (SD) to communicate directly with the core network comprising:

a Mobility Management Entity (MME) and a Home Subscriber Server (HSS) communicatively connected together, each of the MME and HSS comprising a processor, a storage medium, and instructions stored on the respective storage medium and executable by the respective processor to:

register an SD through a cellular device (MD) to obtain a credential for the SD, the credential comprises an Access ID and a key (K_1);

perform a mutual authentication directly with the SD using the Access ID and key; and

grant the SD access to servers in response to authenticating successfully with the SD.

With reference to the fifth aspect, in a first possible implementation manner of the fifth aspect, wherein the instructions to register the SD through the MD comprise instructions stored on the storage medium of the MME to:

- establish a security channel between the MD and the MME;
- receive and review a message from the MD within the security channel;
- generate data based on the message received;
- transmit the data to the HSS;
- receive a response message from the HSS; and
- transmit the response message to the MD within the security channel.

With reference to the first possible implementation manner of the fifth aspect, in a second possible implementation manner of the fifth aspect, wherein the data comprises an identity of the MD (MD ID), Device ID and control parameter to the HSS in response to the message containing a Device ID and control parameter, wherein MD ID is obtainable via the message received from the MD.

With reference to the first possible implementation manner of the fifth aspect, in a third possible implementation manner of the fifth aspect, wherein the data comprises an identity of the MD (MD ID), Device ID, Access ID, key and control parameter to the HSS in response to the message containing a Device ID, Access ID, key and control parameter, wherein MD ID is obtainable via the message received from the MD.

With reference to the second or third possible implementation manner of the fifth aspect, in a fourth possible implementation manner of the fifth aspect, wherein the instructions to register the SD through the MD comprise instructions stored on the storage medium of the HSS to:

receive the data from the MME;

determine whether the data contains an Access ID;

generate a Access ID and K_i in response to the data not containing an Access ID;

and

store the Access ID and K_i from the data in the storage medium of the HSS in response to the data containing an Access ID.

With reference to the fourth possible implementation manner of the fifth aspect, in a fifth possible implementation manner of the fifth aspect, wherein the instruction to generate Access ID and K_i comprises instructions stored on the storage medium of the HSS to:

retrieve a record for a list of MDs from the storage medium;

determine whether the Device ID is in the list of MDs;

create a new entry in the list of MDs in response to determining the Device ID is not in the list of MDs;

generate the Access ID by combining the MD ID and Device ID; and

generate the K_i by using a Key Derivation Function (KDF) on one or a few of MD ID and Device ID;

append the new entry to include Access ID, key, and control parameter; and

generate and transmit a response message containing the generated Access ID and key for the Device ID to the MME.

With reference to the fourth possible implementation manner of the fifth aspect, in a sixth possible implementation manner of the fifth aspect, wherein the instruction to store the Access ID and K_i comprises instructions stored on the storage medium of the HSS to:

determine whether the Access ID is acceptable;

create a new entry in a list of MDs in the HSS database comprising the Device ID, Access ID, Key and control parameter in response to the Access ID being acceptable; and

generate and transmit a response message containing an acceptance message to the MME.

With reference to the sixth possible implementation manner of the fifth aspect, in a seventh possible implementation manner of the fifth aspect, wherein the instruction to determine whether the Access ID is acceptable comprises instruction to:

verify whether a format of the Access ID is in a pre-determined format.

With reference to the fifth aspect, in a eighth possible implementation manner of the fifth aspect, wherein the instructions to perform a mutual authentication directly with the SD using the Access ID and key comprise instructions stored on the storage medium of the MME to:

receive an Attach Request from the SD, the Attach Request comprising the Access ID;

generate an Authentication Data Request based on the Attach Request received;

transmit the Authentication Data Request to the HSS, wherein the Authentication Data Request comprises Access ID, Serving Network Identity (SN ID) and network type,

and wherein the SN ID and network type are obtainable on the Attach Request received from the SD.

With reference to the eighth possible implementation manner of the fifth aspect, in a ninth possible implementation manner of the fifth aspect, wherein the instructions to perform a mutual authentication directly with the SD using the Access ID and key comprise instructions stored on the storage medium of the HSS to:

receive the Authentication Data Request from the MME;

compute a plurality of first authentication vectors based on Evolved Packet System (EPS) Authentication and Key Agreement (AKA) algorithm with a random number (RAND), Key, SN ID, SQN as the input parameters and $AUTN_{HSS}$, XRES, and K_{ASME} as the output parameter; and

generate and transmit an Authentication Data Response comprising the plurality of first authentication vectors, each first authentication vector comprises RAND, $AUTN_{HSS}$, XRES, K_{ASME} .

With reference to the ninth possible implementation manner of the fifth aspect, in a tenth possible implementation manner of the fifth aspect, wherein the instructions to perform a mutual authentication directly with the SD using the Access ID and key comprise instructions stored on the storage medium of the MME to:

receive the Authentication Data Response from the HSS;

select one of the plurality of first authentication vectors;

generate and transmit a User Authentication Request to the SD, the User Authentication Request comprising the RAND and the $AUTN_{HSS}$ from the selected first authentication vector;

receive a User Authentication Response message from the SD, the User

Authentication Response comprising a response parameter (RES) generated by the SD using EPS AKA algorithm;

determine whether RES is equal to XRES received from HSS in response to receiving the User Authentication Response from the SD; and

grant SD access to gateways in response to RES being equal to XRES.

With reference to the fifth aspect, in a eleventh possible implementation manner of the fifth aspect, wherein the instructions to perform a mutual authentication directly with the SD using the Access ID and key comprise instructions stored on the storage medium of the MME to:

receive an Attach Request from the SD, the Attach Request comprising the Access ID, a random number (RAND 1), Fresh Parameter 1, and a Message Authentication Code for Integrity 1 (MAC 1), wherein the Fresh Parameter 1 is one of a timestamp, counter and sequence number;

determine a validity of the Attach Request in response to receiving the Attach Request from the SD; and

generate and transmit an Authentication Data Request to the HSS in response to determining the Attach Request is valid, the Authentication Data Request includes the Access ID and RAND 1.

With reference to the eleventh possible implementation manner of the fifth aspect, in a twelfth possible implementation manner of the fifth aspect, wherein the instruction to determine the validity of the Attach Request comprises instruction to:

determine whether the timestamp for the Attach Request is within a pre-determined time range.

With reference to the eleventh possible implementation manner of the fifth aspect, in a thirteenth possible implementation manner of the fifth aspect, wherein the instruction to determine the validity of the Attach Request comprises instruction to:

determine whether the counter is in running order with respect to previous Attach Request.

With reference to the eleventh possible implementation manner of the fifth aspect, in a fourteenth possible implementation manner of the fifth aspect, wherein the instruction to determine the validity of the Attach Request comprises instruction to:

determine whether the number of the Attach Request is in accordance with a pre-determined sequence with respect to the number in the previous Attach Request.

With reference to the eleventh possible implementation manner of the fifth aspect, in a fifteenth possible implementation manner of the fifth aspect, wherein the instructions to perform a mutual authentication directly with the SD using the Access ID and key comprise instructions stored on the storage medium of the HSS to:

receive the Authentication Data Request from the MME;
 retrieve the K_i that corresponds to the Access ID from the storage medium;
 determine a new key $K1_i$ using the KDF with K_i and RAND 1;
 generate another random number (RAND 2);
 determine another key ($K2_i$) using the KDF with K_i , RAND 1, and RAND 2; and
 generate and transmit an Authentication Data Response to the MME, the Authentication Data Response comprises $K1_i$, $K2_i$, and RAND 2.

With reference to the fifteenth possible implementation manner of the fifth aspect, in a sixteenth possible implementation manner of the fifth aspect, wherein

the instructions to perform a mutual authentication directly with the SD using the Access ID and key comprise instructions stored on the storage medium of the MME to:

receive the Authentication Data Response from the HSS;

determine a validity of MAC 1 using $K1_i$;

compute a Message Authentication Code for Integrity 2 (MAC 2) using $K2_i$ with a one-bit sign (AuthSuccess), RAND 2 and Fresh Parameter 2 as input parameters in response to MAC 1 being valid;

generate and transmit an Authentication Success message to SD, the Authentication Success message includes AuthSuccess, RAND 2, Fresh Parameter 2, and MAC 2; and

transmit a message to gateways to grant access to the SD.

With reference to the fifth aspect, in a seventeenth possible implementation manner of the fifth aspect, wherein the instructions to perform a mutual authentication directly with the SD using the Access ID and key comprise instructions stored on the storage medium of the MME to:

receive an Attach Request from the SD, the Attach Request comprising the Access ID, Fresh Parameter 1, and a Message Authentication Code for Integrity 1 (MAC 1), wherein the Fresh Parameter 1 is one of a timestamp, counter and sequence number;

determine a validity of the Attach Request in response to receiving the Attach Request from the SD; and

generate and transmit an Authentication Data Request to the HSS in response to determining the Attach Request is valid, the Authentication Data Request includes the Access ID.

With reference to the seventeenth possible implementation manner of the fifth aspect, in an eighteenth possible implementation manner of the fifth aspect, wherein

the instructions to perform a mutual authentication directly with the SD using the Access ID and key comprise instructions stored on the storage medium of the HSS to:

- receive the Authentication Data Request from the MME;
- retrieve the Key that corresponds to the Access ID from the storage medium;
- generate and transmit an Authentication Data Response to the MME, the Authentication Data Response comprises the Key.

With reference to the eighteenth possible implementation manner of the fifth aspect, in a nineteenth possible implementation manner of the fifth aspect, wherein the instructions to perform a mutual authentication directly with the SD using the Access ID and key comprise instructions stored on the storage medium of the MME to:

- receive the Authentication Data Response from the HSS;
- determine a validity of MAC 1 using the Key;
- compute a Message Authentication Code for Integrity 2 (MAC 2) using the key with a one-bit sign (AuthSuccess), and Fresh Parameter 2 as input parameters in response to MAC 1 being valid;
- generate and transmit an Authentication Success message to SD, the Authentication Success message includes AuthSuccess, Fresh Parameter 2, and MAC 2; and
- transmit a message to gateways to grant access to the SD.

According to a sixth aspect of the invention, a Home Subscriber Server (HSS) for registering devices without SIM card (SD) to communicate directly with the core network comprising:

- a processor,
- a storage medium,
- and instructions stored on the storage medium and executable by the processor to:

receive the data from the MME;

determine whether the data contains an Access ID;

generate an Access ID and K_i in response to the data not containing an Access ID.

With reference to the sixth aspect, in a first possible implementation manner of the sixth aspect, wherein the instruction to generate a Access ID and K_i comprises instructions stored on the storage medium of the HSS to:

retrieve a record for a list of MDs from the storage medium;

determine whether the Device ID is in the list of MDs;

create a new entry in the list of MDs in response to determining the Device ID is not in the list of MDs;

generate the Access ID by combining the MD ID and Device ID; and

generate the K_i by using a Key Derivation Function (KDF) on one or a few of MD ID and Device ID;

append the new entry to include Access ID, key, and control parameter; and

generate and transmit a response message containing the generated Access ID and key for the Device ID to the MME.

With reference to the sixth aspect or the first possible implementation manner of the sixth aspect, in a second possible implementation manner of the sixth aspect, wherein the instructions stored on the storage medium and executable by the processor to:

store the Access ID and K_i from the data in the storage medium of the HSS in response to the data containing an Access ID.

With reference to the second possible implementation manner of the sixth

aspect, in a third possible implementation manner of the sixth aspect, wherein the instruction to store the Access ID and K_i comprises instructions stored on the storage medium of the HSS to:

determine whether the Access ID is acceptable;

create a new entry in a list of MDs in the HSS database comprising the Device ID, Access ID, Key and control parameter in response to the Access ID being acceptable; and

generate and transmit a response message containing an acceptance message to the MME.

According to a seventh aspect of the invention, a Home Subscriber Server (HSS) for registering devices without SIM card (SD) to communicate directly with the core network comprising:

a processor,

a storage medium,

and instructions stored on the storage medium and executable by the processor to:

receive an Authentication Data from the HSS, wherein the Authentication Data includes a RAND and a $AUTN_{HSS}$;

generate and transmit a User Authentication Request to the SD, the User Authentication Request comprising the RAND and the $AUTN_{HSS}$;

receive a User Authentication Response message from the SD, the User Authentication Response comprising a response parameter (RES) generated by the SD using EPS AKA algorithm;

determine whether RES is equal to XRES received from HSS in response to receiving the User Authentication Response from the SD; and

grant SD access to gateways in response to RES being equal to XRES.

According to a eighth aspect of the invention, a cellular device (MD) for registering devices without SIM card (SD) to communicate directly with a core network comprising:

receiving unit ,configured to receive a Device ID from the SD;

generation unit, configured to generate an Access ID and key (Ki) for the SD;

transmitting unit, configured to transmit the Access ID and Ki to the SD.

With reference to the eighth aspect, in a first possible implementation manner of the eighth aspect, wherein the MD comprises first connection unit and adding unit;

the first connection unit ,configured to establish a first security channel between the SD and the MD;

the transmitting unit, configured to transmit a request to the SD for an identity information of the SD (Device ID);

wherein the instruction to receiving Device ID from the SD comprises instructions to:

the receiving unit ,configured to receive the Device ID from the SD within the first security channel;

the adding unit, configured to create a new entry; and append the new entry to include the Access ID and Ki.

With reference to the eighth aspect or the first possible implementation manner of the eighth aspect, in a second possible implementation manner of the eighth aspect, wherein the generating unit is configured to:

combine the MD's identity with Device ID to obtain the Access ID.

With reference to the eighth aspect or the first possible implementation manner of the eighth aspect, in a third possible implementation manner of the

eighth aspect, wherein the generating unit is configured to:

combining the MD's identity with a random number to obtain the Access ID.

With reference to the eighth aspect or the first possible implementation manner of the eighth aspect, in a fourth possible implementation manner of the eighth aspect, wherein the generating unit is configured to:

combine a sequence number assigned to MD with the Device ID to obtain the Access ID.

With reference to anyone of the above possible implementation manner of the eighth aspect, in a fifth possible implementation manner of the eighth aspect, wherein the generating unit is configured to:

generate K_i using a Key Derivation Function (KDF) with input parameter being one or more of MD's identity, Device ID and Access ID.

With reference to the eighth aspect, in a sixth possible implementation manner of the eighth aspect, wherein the generating unit is configured to:

transmit the Device ID to the core network; and

receive the Access ID and K_i from the core network.

With reference to the sixth possible implementation manner of the eighth aspect, in a seventh possible implementation manner of the eighth aspect, wherein the MD comprises a second connection unit;

the second connection unit, configured to establish a second security channel between the SD and the core network;

the transmitting unit, configured to transmit the Device ID to the core network upon

establishing the second security channel.

According to a ninth aspect of the invention, a device without SIM card (SD) for communicating with a core network comprising:

registering unit, configured to register with the core network through a cellular device (MD) to obtain a credential for the SD, the credential comprises an Access ID and a key (K_i);

authentication unit, configured to perform a mutual authentication directly with the core network using the Access ID and K_i ; and

accessing unit, configured to access servers via the core network in response to authenticating successfully with the core network.

With reference to the ninth aspect, in a first possible implementation manner of the ninth aspect, wherein the registering unit is configured to :

retrieve the Device ID;

transmit the Device ID to the MD;

receive the Access ID and K_i from the MD; and

store the Access ID and K_i in the storage medium.

With reference to the ninth aspect or the first possible implementation manner of the ninth aspect, in a second possible implementation manner of the ninth aspect, wherein the authentication unit is configured to:

send an Attach Request to the core network, the Attach Request comprising the Access ID;

receive a User Authentication Request from the core network, the User Authentication Request comprising a random number (RAND) and an authentication

token ($AUTN_{HSS}$) generated by the core network using Evolved Packet System (EPS) Authentication and Key Agreement (AKA) algorithm;

compute an authentication vector using EPS AKA algorithm with the RAND, the K_i , a serving network identity (SN ID), a sequence number (SQN) as the input parameters and an authentication token ($AUTN_{UE}$) and a response parameter (RES) as the output parameter;

determine whether the $AUTN_{UE}$ is equal to the $AUTN_{HSS}$; and

generate and transmit a User Authentication Response message to the MME in response to the $AUTN_{UE}$ being equal to $AUTN_{HSS}$, the User Authentication Response comprising RES.

With reference to the ninth aspect or the first possible implementation manner of the ninth aspect, in a third possible implementation manner of the ninth aspect, wherein the authentication unit is configured to:

determine a new key ($K1_i$) using a Key Derivation Function (KDF) with input as K_i and a random number (RAND 1);

generate a Message Authentication Code for Integrity 1 (MAC 1) using $K1_i$ with input parameters comprising Access ID, RAND 1, and Fresh Parameter 1;

generate and transmit an Attach Request to the core network, the Attach Request comprising the Access ID, RAND 1, Fresh Parameter 1, and MAC 1;

receive an Authentication Success message from the core network, the Authentication Success message includes a one-bit sign (AuthSuccess), a random number (RAND 2) generated by the core network, Fresh Parameter 2, and MAC 2, wherein MAC 2 is generated by the core network using another key ($K2_i$) with AuthSuccess, RAND 2 and Fresh Parameter 2 as input parameters, wherein the Fresh Parameters 1 and 2 are one of a timestamp, counter and sequence number

determine another key (K_{2i}) using KDF with K_i , RAND 1, and RAND 2 as input parameters;

determine a validity of MAC 2 using K_{2i} ; and

transmit and receive data with the core network in response to MAC 2 being valid.

With reference to the ninth aspect or the first possible implementation manner of the ninth aspect, in a fourth possible implementation manner of the ninth aspect, wherein the authentication unit is configured to:

generate a Message Authentication Code for Integrity 1 (MAC 1) using K_i with input parameters comprising Access ID and Fresh Parameter 1;

generate and transmit an Attach Request to the core network, the Attach Request comprising the Access ID, Fresh Parameter 1, and MAC 1, wherein the Fresh Parameter 1 is one of a timestamp, counter and sequence number;

receive an Authentication Success message from the core network, the Authentication Success message includes a one-bit sign (AuthSuccess), Fresh Parameter 2, and MAC 2;

determine a validity of MAC 2 using K_i ; and

transmit and receive data with the core network in response to MAC 2 being valid.

Brief Description of the Drawings

The above advantages and features in accordance with this invention are described in the following detailed description and are shown in the following drawings:

Figure 1 illustrating a simplified network infrastructure in accordance with an embodiment of this disclosure;

Figure 2 illustrating a simplified block diagram of a core network in accordance with an embodiment of this disclosure;

Figure 3 illustrating a block diagram of a basic network interface in accordance with an embodiment of this disclosure;

Figure 4 illustrating a timing diagram of a first process of registration of a device without SIM in accordance with an embodiment of this disclosure;

Figure 5 illustrating a process flow performed by a cellular device according to the first process of registration in accordance with an embodiment of this disclosure;

Figure 6 illustrating a process flow performed by a MME in a core network according to the first process of registration in accordance with an embodiment of this disclosure;

Figure 7 illustrating a process flow performed by a HSS in a core network according to the first process of registration in accordance with an embodiment of this disclosure;

Figure 8 illustrating a process flow performed by a device without SIM card according to the first process of registration in accordance with an embodiment of this disclosure;

Figure 9 illustrating a timing diagram of a second process of registration of a device without SIM in accordance with an embodiment of this disclosure;

Figure 10 illustrating a process flow performed by the cellular device according to the second process of registration in accordance with an embodiment of this disclosure;

Figure 11 illustrating a process flow performed by the MME in the core network according to the second process of registration in accordance with an embodiment of this disclosure;

Figure 12 illustrating a process flow performed by the HSS in the core network according to the second process of registration in accordance with an embodiment of this disclosure;

Figure 13 illustrating a process flow performed by the cellular device according to the combination of the first and second process of registration in accordance with an embodiment of this disclosure;

Figure 14 illustrating a process flow performed by the MME in the core network according to the combination of the first and second process of registration in accordance with an embodiment of this disclosure;

Figure 15 illustrating a process flow performed by the HSS in the core network according to the combination of the first and second process of registration in accordance with an embodiment of this disclosure;

Figure 16 illustrating a timing diagram of a first mutual authentication process in accordance with an embodiment of this disclosure;

Figure 17 illustrating a process flow performed by the device without SIM card according to the first mutual authentication process in accordance with an embodiment of this disclosure;

Figure 18 illustrating a process flow performed by the MME in the core network according to the first mutual authentication process in accordance with an embodiment of this disclosure;

Figure 19 illustrating a process flow performed by the HSS in the core network according to the first mutual authentication process in accordance with an embodiment of this disclosure;

Figure 20 illustrating a timing diagram of a second mutual authentication process in accordance with an embodiment of this disclosure;

Figure 21 illustrating a process flow performed by the device without SIM card according to the second mutual authentication process in accordance with an embodiment of this disclosure;

Figure 22 illustrating a process flow performed by the MME in the core network according to the second mutual authentication process in accordance with an embodiment of this disclosure;

Figure 23 illustrating a process flow performed by the HSS in the core network according to the second mutual authentication process in accordance with an embodiment of this disclosure;

Figure 24 illustrating a process flow performed by the device without SIM card according to the third mutual authentication process in accordance with an embodiment of this disclosure;

Figure 25 illustrating a process flow performed by the MME in the core network according to the third mutual authentication process in accordance with an embodiment of this disclosure; and

Figure 26 illustrating a process flow performed by the HSS in the core network according to the third mutual authentication process in accordance with an embodiment of this disclosure.

Detailed Description

This invention relates to a method and system for granting devices without Subscriber Identity Module (SIM) card access to the core network. Particularly, this invention relates to a method and system for registering devices without SIM card to the core network and subsequently accessing other servers via the core network.

It is envisioned that embodiments of this invention provide an authentication scheme for future low cost cellular devices without SIM card such as Internet of Things (IoT). The current mutual authentication schemes (such as AKA and GBA) between a UE and the core network is based on the pre-shared key stored in the UE's SIM card and the HSS. For a wireless device without SIM card such as IoTs, the current authentication schemes (such as AKA and GBA) cannot be applied.

Current authentication schemes need many rounds of interactions between the UE and the core network. This overly burdens the core network. Thus, one skilled in the art strives to reduce the number of interactions needed for the mutual authentication between the UE and the core network.

Figure 1 illustrates a simplified network infrastructure 100. Particularly, the network infrastructure 100 shows a wireless cellular device 110 with SIM card acting as a bridge to build up connection between the IoT devices 120-123 without SIM card and the Core Network 130. One skilled in the art will recognise that between cellular device 110 and core network 130, other system such as base stations to connect the device 110 to the core network 130 are required. Hence, figure 1 is not meant to be exhaustive and merely for illustrative purposes only.

Figure 2 illustrates a simplified block diagram of a core network 130. The Home Subscriber Server (HSS) 132 is a central database containing information such as Access ID and Key of the network operator's subscribers. The Mobility Management Entity (MME) 131

controls high level operations. One of the operations includes authenticating the user by interacting with the HSS. The Serving Gateway 133 routes and forwards user data packets between cellular device 110 and PDN Gateway 134. The PDN Gateway 134 communicates with the external servers 140 internal servers 141. Internal servers 141 are owned by the operator of the core network while external servers are owned by other operators. In order for a cellular device 110 to communicate with other devices via the external or internal servers 140 and 141, it has to authenticate with the MME 131. The MME 131 interacts with the HSS 132 and authenticate with the cellular device 110. If authentication is successful, the MME 131 would grant the cellular device 110 access to the external or internal servers 140 and 141 via the Serving Gateway and PDN Gateway. In short, before a cellular device 110 can connect to the internet with a core network 130, the cellular device 110 must be a registered user with Access ID and Key stored on the HSS 132 in order to correctly authenticate with the MME so that MME would grant the cellular device 110 access to the respective gateways.

In the current network arrangement, a cellular device 110 is allocated an Access Identification and a Key (K) for authenticating with the core network 130. IoT devices 120-123 without the SIM card, they are not able to communicate directly with the core network 130. This is because the cellular device 110 authenticates the core network based on its IMSI and a pre-shared key which are stored in a SIM card.

For purposes of this disclosure, the cellular device 110 with SIM card is referred to as the Master Device (MD), and the IoT devices 120-123 without SIM card are referred to as the Secondary Devices (SDs). Further, the term “Internet of Things” (IoT) devices refer to any apparatus having a communication interface to allow transferring and receiving of information among the IoT devices over a wired or wireless connection. IoT devices comprise, but not limited to, sensor devices, embedded systems, network-based cameras,

gateways, mobile phones, computers, laptops, personal digital assistants (PDAs), white goods, appliances, etc.

For embedded systems, gateways, mobile phones, computers, laptops, and PDAs, such IoT devices are typically equipped with wireless network interface (e.g. Bluetooth, Wi-Fi, Wi-Fi Direct, Long-Term Evolution (LTE) Direct, RF antenna, etc.) or wired network interface (e.g. an Ethernet connection, a USB or Firewire connection, etc.) to allow transferring and receiving of data.

For white goods such as fridge and washing machine, such appliances may not be equipped with any wired or wireless network interface. Hence, it is common that a network interface module be provided to allow such appliances to be communicatively connected to the mobile device 110 so that these IoT devices can communicate with the core network 130. Figure 3 illustrates the block diagram of a basic network interface 300. The network interface 300 can receive and transmit data, execute software applications. Network interface 200 comprises a processor 310, memory 320, transceiver 330 and input/output ports 340.

The processor 310 is a processor, microprocessor, microcontroller, application specific integrated circuit, digital signal processor (DSP), programmable logic circuit, or other data processing device that executes instructions to perform the processes in accordance with the present invention. The processor 310 has the capability to execute various applications that are stored in the memory 320.

The memory 320 may include read-only memory (ROM), random-access memory (RAM), electrically erasable programmable ROM (EEPROM), flash cards, or any memory commonly used for computers.

One or more input/output (I/O) ports 340 can be configured to allow the processor 310 to communicate with and control from various I/O devices for the IoT devices. Peripheral

devices that may be connected to network interface 300 via the I/O ports 340 include a USB storage device, an SD card or other storage device for transmitting information to or receiving information from the core network 330. In addition to updating applications stored on memory 320 or installing new applications onto the memory via the transceiver 330, a user may alternatively install new applications or update applications on the memory 320 through a user interface such as a USB via the I/O ports 340.

The transceiver 330 comprises a transmitter and a receiver for transmitting data to the core network 130 and receiving data from the core network 130. The transceiver 330 may transmit and receive data via one or more of the following wireless or wired technology standards, Bluetooth, Wi-Fi, Wi-Fi Direct, Long-Term Evolution (LTE) Direct, RF antenna, Ethernet connection, a USB or Firewire connection, etc.

One skilled in the art will recognize that other features may be included in the network interface 300. Further, the components in network interface 300 may be replaced by other components that perform similar functions. In brief, the network interface 200 as shown in figure 3 is considered merely illustrative and non-limiting.

Embodiments of this disclosure propose a method of registering IoT devices with the core network 130 and mutual authentication between the IoT devices and core network 130. The method is provided in the form of instructions stored on storage medium and executable by processors of respective IoT devices, cellular devices and core networks.

Registration

In order for an IoT device to access the internal and/or external servers via the core network, the IoT device and the core network are required to have some pre-shared confidential information kept on both sides in order to authenticate with each other. The pre-shared confidential information (i.e. credential) is kept in the HSS of a core network and a

secured database of the IoT device. The credential may include Access ID, Key and control parameters.

Registration of an IoT device, i.e. SD, can be performed in a few approaches such as (1) MD initiates the request and core network creates an Access ID and a key for the SD, (2) MD creates an Access ID and a key for a SD, and sends the Access ID and the key to both the SD and the core network, or (3) combination of approaches (1) and (2). Further details will be described below.

Figure 4 illustrates a timing diagram 400 on the process of MD_i initiating a request for Access ID and a key for the SD_i in accordance with an embodiment of this disclosure. Timing diagram begins with step 410 where SD_i and MD_i establish a security channel. Further details of the establishing the security channel will be described below with reference to figure 5.

In step 420, SD_i sends its identity information (such as Device ID_i) to MD_i within the security channel. The MD_i and core network then establish a security channel through the conventional 3GPP authentication schemes in step 430. Further details of the security channel will be described below with reference to figure 5.

In step 440, within the security channel, MD_i sends Device ID_i and control parameters (optional) to the MME. In response to receiving the Device ID_i, the MME then sends Device ID_i and control parameters (optional) to the HSS in step 450.

Upon receiving the Device ID_i, the HSS generates an Access ID_i and a Key K_i based on the Device ID_i in step 460. Thereafter, the HSS sends the Access ID_i and the K_i to the MME in step 470. Further details of generating the Access ID_i and a Key K_i will be described below with reference to figure 7.

In response to receiving the Access ID_i and the K_i, the MME/Local RAN controller sends the Access ID_i and the K_i to the MD_i inside the security channel in step 480. The MD_i then sends the Access ID_i and the K_i to SD_i inside the security channel in step 480. Timing diagram ends after step 480.

Each MD may manage several SDs. The allocated Access IDs, Keys, and Control Parameter for each associated SD are stored with the MD or tag to the MD. A possible storage format is given in the following table.

Device ID ₁	Access ID ₁	K ₁	Control Parameter 1 (optional)
Device ID ₂	Access ID ₂	K ₂	Control Parameter 2 (optional)
Device ID ₃	Access ID ₃	K ₃	Control Parameter 3 (optional)
Device ID ₄	Access ID ₄	K ₄	Control Parameter 4 (optional)
...	...	...	...

Each HSS stores details of several MDs. The allocated Access IDs, Keys, and Control Parameter for each associated SD tagged to the MD may be stored on the HSS in a storage format in the following table.

Master Device 1 IMSI	Device ID ₁	Access ID ₁	K ₁	Control Parameter 1 (optional)
	Device ID ₂	Access ID ₂	K ₂	Control Parameter 2 (optional)
	Device ID ₃	Access ID ₃	K ₃	Control Parameter 3 (optional)
	Device ID ₄	Access ID ₄	K ₄	Control Parameter 4 (optional)
	...	...	...	...
Master Device 2 IMSI	Device ID ₁	Access ID ₁	K ₁	Control Parameter 1 (optional)
	Device ID ₂	Access ID ₂	K ₂	Control Parameter 2 (optional)
	...	...	...	...

In the procedure, two network elements namely, MME and HSS are involved. HSS is a network element that stores the root key of the MD and stores the Access ID_i and K_i for SD_i. In practice, one skilled in the art will recognise that any network element such as AAA

having the same function as the HSS can replace the HSS in this procedure without departing from this disclosure. MME is responsible for authenticating the MD and build up security channel using the existing technologies such as AKA. In practice, one skilled in the art will recognise that any network element such as the Local RAN Controller having the same function as the MME can replace the MME in this procedure without departing from this disclosure.

Figure 5 illustrates a process flow 500 performed by the MD in accordance with the registration procedure of timing diagram 400. Process 500 beings with step 505 by establishing a connection with the SD_i. Particularly, the MD_i establishes a security channel to allow transferring of data between the MD_i and the SD_i. The security channel establishment between the SD_i and MD can be through any form of short distance wireless communications technologies such as WiFi, Bluetooth, Zigbee, or through any wired communications technologies.

Upon establishing a security channel, the MD_i request for an identity information (Device ID_i) from each of the SD_i in step 510. In response to receiving the Device ID_i from each of the SD_i in step 510, process 500 proceeds to step 515 to create a new entry if the Device ID_i has not been recorded in the database of the MD_i. Each entry comprises Device ID_i, Access ID_i, Key_i and control parameter. The control parameter in this regard may be setting of a limit on the cellular data usage for the SD_i. The control parameter is set to a default parameter which may be a limit of a pre-determined data limit. One skilled in the art will recognise that other control parameters may be implemented without departing from this disclosure.

In step 520, process 500 establishes a connection with the core network. Particularly, the MD_i and the core network establish a security channel to allow transferring of data

between the MD and the core network. The security channel establishment between the MD_i and core network can be through any of the existing mutual authentication protocols such as AKA, GAA/GBA.

In step 522, the MD_i generates and transmits a message containing the Device ID_i and the control parameter to the MME of the core network upon establishing the security channel.

In step 525, the MD_i receives a response message containing the Access ID_i and key from the core network. In response, the MD_i append to the entry associated to the Device ID_i in step 530 to include the Access ID_i and key. Thereafter, the MD_i transmits the Access ID_i and key to the SD_i in step 535. Process 500 ends after step 535.

Figure 6 illustrates a process flow 600 performed by the MME in accordance with the registration procedure of timing diagram 400. Process 600 begins with step 605 by establishing a connection with the MD_i. Particularly, the core network and the MD_i establish a security channel to allow transferring of data between the core network and the MD_i. The security channel establishment between the core network and the MD_i can be through any of the existing mutual authentication protocols such as AKA, and GAA/GBA.

Upon establishing a security channel with the MD_i, the MME receives a message containing the Device ID_i and control parameters from the MD_i in step 610. The identity of the MD (MD ID_i) is also obtained via the message received from the MD_i. The identity of the MD may be International Mobile Subscriber Identity (IMSI) or International Mobile Station Equipment Identity (IMEI). In response to receiving the Device ID_i and control parameters, the MME forward the MD ID_i, Device ID_i and the parameters to the HSS in step 615.

In step 620, the MME receives a response message containing the Access ID_i and key from the HSS. The Access ID_i and Key_i are then transmitted to the MD_i. Process 600 ends after step 625.

Figure 7 illustrates a process flow 700 performed by the HSS in accordance with the registration procedure of timing diagram 400. Process 700 begins by receiving MD ID_i, Device ID_i and control parameters from the MME. In response to receiving MD ID_i, Device ID_i and parameters, the HSS retrieves the record for MD_i in step 710. The record for MD_i is a list containing all the MDs being registered with the HSS. Process 700 then determines if the Device ID_i has already been recorded in the record for the MD_i. If the Device ID_i has not been recorded in the record for the MD_i, process 700 proceeds to step 720 to create a new entry in database for the new Device ID_i. If the Device ID_i has been recorded in the record for the MD_i, process 700 ends.

In step 725, the HSS generates an Access ID_i and Key_i for the Device ID_i. Access ID_i may be generated by combining the MD_i's identity with SD_i's identity. For example, by combining 1) MD IMSI with Device ID_i, 2) MD IMSI with SD_i's IMEI, 3) MD IMEI with Device ID_i, or 4) MD IMEI with SD_i's IMEI. In another embodiment, the Access ID_i may be generated by combining the MD_i's identity with a Sequence Number that is assigned to SD_i by the HSS. In yet another embodiment, the Access ID_i may be generated by combining the MD_i's identity with a randomly generated number generated by HSS for SD_i. Alternatively, the Access ID_i may be generated by a sequence number assigned to SD_i by the HSS or a random number generated by the HSS for SD_i. One skilled in the art will recognise that any combination may be implemented without departing from the disclosure.

Key_i may be generated by the following methods: 1) randomly chosen by the HSS; 2) obtained by using Key Derivation Function (KDF); 3) parameters used for key derivation

which may include the identity of the MD_i (such as MD IMSI, MD IMEI), the identity of the SD_i (such as Device ID_i, Device IMEI), the key of MD, Access ID_i, and other optional parameters. One skilled in the art will recognise that in addition to the random alphanumeric chosen by HSS/AAA, alphanumeric obtained by KDF or alphanumeric of parameters, hash function may be used to further encrypt the alphanumeric without departing from the disclosure.

The HSS then stores the Access ID_i and key to the new entry in step 730. Thereafter, the HSS generates and transmits a response message containing the Access ID_i and key to the MME. Process 700 ends after step 735.

Figure 8 illustrates a process flow 800 performed by the SD_i in accordance with the registration procedure of timing diagram 400. Process 800 begins with step 805 by establishing a connection with the MD_i.

In step 810, the SD_i transmits its Device ID_i to the MD_i upon establishing a security channel with the MD_i. The SD_i then waits for the Access ID_i, Key_i and parameters from the MD_i.

In step 815 receives the Access ID_i, key and parameters from the MD_i and stores the Access ID_i, Key_i and parameters in step 820. Process 800 ends after step 820.

Figure 9 illustrates a timing diagram 900 on the process of MD_i generating an Access ID_i and a key for the SD_i in accordance with an embodiment of this disclosure. Timing diagram 900 begins with step 910 where SD_i and MD_i establish a security channel. The details of the establishing the security channel is similar to that described above with reference to figure 5.

In step 920, SD_i sends its identity information (such as Device ID_i) to MD_i within the security channel. The MD_i then generates an Access ID_i and a Key_i based on the Device ID_i

or other information. Further details on generating of the Access ID_i and a Key_i will be described below with reference to figure 10.

In step 940, the MD_i and core network establish a security channel through the conventional 3GPP authentication schemes. The details of the security channel are similar to that described above with reference to figure 5.

In step 950, within the security channel, MD_i transmits Device ID_i, Access ID_i, Key_i and control parameters (optional) to the MME. In response to receiving the data from the MD_i, the MME transmits the data to the HSS in step 960.

Upon receiving the data, the HSS stores the data in a new entry and transmits an Access ID_i acceptance message to the MME in step 970. Thereafter, the MME transmits the Access ID_i acceptance message to the MD_i in step 980.

In response to receiving the Access ID_i message, the MD_i stores the Access ID_i and the K_i and transmits the Access ID_i, the K_i and parameters to the SD_i in step 990. Timing diagram 900 ends after step 990.

Figure 10 illustrates a process flow 1000 performed by the MD_i in accordance with the registration procedure of timing diagram 900. Process 1000 begins with step 1005 by establishing a connection with the SD_i. Particularly, the MD_i establishes a security channel to allow transferring of data between the MD_i and the SD_i. The security channel establishment between the SD_i and MD_i can be through any form of short distance wireless communications technologies such as WiFi, Bluetooth, Zigbee, or through any wired communications technologies.

Upon establishing a security channel, the MD_i request for Device ID_i from each of the SD_i in step 1010. In response to receiving the Device ID_i from each of the SD_i in step 1010,

process 1000 determines if the Device ID_i has been recorded in the database of the MD in step 1015. Each Device ID_i is recorded in the database of the MD_i and comprises Device ID_i, Access ID_i, key and control parameter. The control parameter in the regard may be setting of a limit on the cellular data usage for the SD_i. The control parameter is set to a default parameter which may be a limit of a pre-determined data limit. One skilled in the art will recognise that other parameters may be implemented without departing from this disclosure.

In step 1020, the MD_i generates an Access ID_i and key for the Device ID_i. Access ID_i may be generated by combining the MD's identity with SD_i's identity. For example, by combining 1) MD IMSI with Device ID_i, 2) MD IMSI with Device i's IMEI, 3) MD IMEI with Device ID_i, or 4) MD IMEI with Device i's IMEI. In another embodiment, the Access ID_i may be generated by combining the MD's identity with a Sequence Number that is assigned to SD_i by the MD_i. In yet another embodiment, the Access ID_i may be generated by combining the MD's identity with a randomly generated number generated by MD_i for SD_i. Alternatively, the Access ID_i may be generated by a sequence number assigned to SD_i by the MD_i or a random number generated by the MD_i for SD_i. One skilled in the art will recognise that any combination may be implemented without departing from the disclosure.

K_i may be generated by the following methods: 1) randomly chosen by the MD_i; and 2) parameters used for key derivation which may include the identity of the MD_i (such as MD IMSI, MD IMEI), the identity of the SD_i (such as Device ID_i, Device IMEI), the key of MD_i, Access ID_i, and other optional parameters. One skilled in the art will recognise that in addition to the random alphanumeric chosen by MD, or alphanumeric of parameters, hash function may be used to further encrypt the alphanumeric without departing from the disclosure.

In step 1025, the MD_i establishes a connection with the core network. Particularly, the MD_i and the core network establish a security channel to allow transferring of data between the MD_i and the core network. The security channel establishment between the MD_i and core network can be through any of the existing mutual authentication protocols such as AKA, GAA/GBA.

In step 1030, the MD_i generates and transmits a message containing the Device ID_i, Access ID_i, Key_i and control parameter to the MME of the core network. The MD_i then waits for a response from the core network. In step 1035, the MD_i receives a response message containing an acceptance message from the core network. In response to receiving the acceptance message, the MD_i creates a new entry, comprising Device ID_i, Key_i and control parameter for the SD_i and stores the entry in the database. Thereafter, the MD_i transmits the Access ID_i, key and control parameter to the SD_i in step 1040. Process 1000 ends after step 1040.

Figure 11 illustrates a process flow 1100 performed by the MME in accordance with the registration procedure of timing diagram 900. Process 1100 begins with step 1005 by establishing a connection with the MD_i. Particularly, the core network and the MD_i establish a security channel to allow transferring of data between the core network and the MD_i. The security channel establishment between the core network and the MD_i can be through any of the existing mutual authentication protocols such as AKA, and GAA/GBA.

Upon establishing a security channel with the MD_i, the MME receives a message containing the Device ID_i, Access ID_i, Key_i and parameters from the MD_i in step 1110. In response to receiving the Device ID_i and parameters, the MME forward the MD ID_i, Device ID_i, Access ID_i, Key_i and control parameters to the HSS in step 1115.

In step 1120, the MME receives a response message containing an acceptance message from the HSS. The acceptance message is then transmitted to the MD_i in step 1125. Process 1100 ends after step 1125.

Figure 12 illustrates a process flow 1200 performed by the HSS in accordance with the registration procedure of timing diagram 900. Process 1200 begins with step 1205 by receiving the Device ID_i, Access ID_i, key and parameter.

In step 1210, HSS checks whether the Access ID_i is acceptable. In particular, the HSS checks the format of the Access ID is in a standardised format. The standardised format of the Access ID is the same as that generated in step 1020, i.e. combination of the MD's identity with SD's identity. Further details and examples are described above with reference to step 1020. In other words, the process of generating the Access ID by the MD is shared with the HSS. If the format of the Access ID follows certain rules, then the Access ID is acceptable. Otherwise, it will not accept the Access ID.

If the Access ID_i is acceptable, process 1200 proceeds to step 1215. If the Access ID_i is not acceptable, process 1200 generates a response message containing a non-acceptance message and proceeds to step 1220 to transmit the non-acceptance message to the MME.

In step 1215, the HSS creates a new entry a list of MDs in the database comprising the Device ID_i, Access ID_i, Key_i and parameters. The HSS then generates a response message containing an acceptance message.

In step 1220, the HSS transmits the response message containing either the acceptance message or non-acceptance message to the MME. Process 1200 ends after step 1220.

The process flow of the SD_i in accordance with the registration procedure of timing diagram 900 is similar to that of process 800.

The combination of timing diagrams 400 and 900 will now be described below with reference to figure 13-15.

Figure 13 illustrates the process flow 1300 performed by the MD_i in accordance with the registration procedure of a combination of timing diagrams 400 and 900. Process 1300 begins with step 1305 by establishing a connection with the SD_i . Particularly, the MD_i establishes a security channel to allow transferring of data between the MD_i and the SD_i . The security channel establishment between the SD_i and MD_i can be through any form of short distance wireless communications technologies such as WiFi, Bluetooth, Zigbee, or through any wired communications technologies.

Upon establishing a security channel, the MD_i request for Device ID_i from each of the SDs in step 1310. In response to receiving the Device ID_i from each of the SDs in step 1310, process 1300 retrieves the information of approaches from the database in step 1315. The MD_i then determines which approach to prosecute in step 1320.

If the information of approaches is approach 1, process 1300 proceeds to step 1325 and continue with steps 515-535 of process 500 where the Access ID and key are generated by the HSS. If the information of approaches is approach 2, process 1300 proceeds to step 1330 and continue with steps 1015-1040 of process 1000 where the Access ID and key are generated by the MD. Process 1300 ends after 1325 or 1330.

Figure 14 illustrates the process flow 1400 performed by the MME in accordance with the registration procedure of a combination of timing diagrams 400 and 900. Process 1400 begins with step 1405 by establishing a connection with the MD_i . Particularly, the core network and the MD_i establish a security channel to allow transferring of data between the

core network and the MD_i. The security channel establishment between the core network and the MD_i can be through any of the existing mutual authentication protocols such as AKA, and GAA/GBA.

Upon establishing a security channel with the MD_i, the MME receives data from the MD_i in step 1410. The MME reviews the data and forward the necessary data from the data received to the HSS. For example, if the data from the MD_i are Device ID_i, Access ID_i, key and parameters, the MME forwards the MD ID_i, Device ID_i, Access ID_i, Key_i and parameters to the HSS in step 1415. If the MME receives the Device ID_i and parameters from the MD_i, the MME forwards the MD ID_i, Device ID_i and the parameters to the HSS in step 1515.

In step 1420, the MME receives a response message from the HSS and forward the response message to the MD_i in 1425. The response message may contain one of the followings: 1) Access ID_i and Key_i; 2) acceptance message; or 3) non-acceptable message. Process 1400 ends after step 1425.

Figure 15 illustrates the process flow of the performed by the HSS in accordance with the registration procedure of a combination of timing diagrams 400 and 900. Process 1500 begins with step 1505 by receiving data from the MME.

In step 1510, HSS determines whether the data contains Access ID_i. If the data contains Access ID_i, process 1500 proceeds to step 1515 and continues with steps 1210-1220. If the data does not contains Access ID_i, process 1500 proceeds to step 1520 and continues with steps 710-735. Process 1500 ends after step 1515 or 1520.

Mutual Authentication

Mutual authentication between an IoT device and the core network can be performed in a few schemes based on the credential for each IoT device such as Access ID and the key.

A first mutual authentication between the IoT devices and core network is based on a modified AKA. Figure 16 illustrates a timing diagram 1600 on the process of the first mutual authentication between the IoT device and core network in accordance with an embodiment of this disclosure.

Timing diagram begins with step 1610 by transmitting an Attach Request comprising its Access ID_i to the MME.

Upon receipt of the Attach Request from the SD_i, the MME transmits an Authentication Data Request to the HSS in step 1620. The Authentication Data Request includes the Access ID_i, the Serving Network Identity (SN ID_i), and the Network Type.

In response to receiving the Authentication Data Request from the MME, the HSS locates K_i according to the Access ID_i, and computes the authentication vector using EPS AKA algorithm. The HSS then sends an Authentication Data Response with the authentication vectors to the MME in step 1630.

In step 1640, the MME transmits the User Authentication Request to the SD_i. The User Authentication Request includes the random number (RAND), and the authentication token AUTN_{HSS} derived from the authentication vector.

Upon receipt of the RAND and AUTN_{HSS}, SD_i computes AUTN_{UE} and then authenticates the core network by verifying whether AUTN_{UE} is equal to AUTN_{HSS}. If AUTN_{UE} is equal to AUTN_{HSS}, SD_i sends the User Authentication Response to the MME in step 1650.

Upon receipt of the User Authentication Response, the MME authenticates SD_i between the information in the User Authentication Response and the information in the Authentication Data Response. If authentication is successful, the MME grants the SD_i access to the gateways. Timing diagram 1600 ends after step 1650.

Figure 17 illustrates a process flow 1700 performed by the SD_i in accordance with the first mutual authentication procedure of timing diagram 1600. Process 1700 begins with step 1705 by retrieving its Access ID $_i$ and K_i . In step 1710, the SD_i generates and transmits an Attach Request comprising the Access ID $_i$.

In step 1715, the SD_i receives a User Authentication Request from the MME. The User Authentication Request includes the random number (RAND), and the authentication token $AUTN_{HSS}$ derived from the authentication vector generated by the HSS.

In step 1720, the SD_i computes the authentication vector using the EPS AKA algorithm 1790. The input parameters for the EPS AKA algorithm include K_i , RAND, SN ID $_i$, and SQN. The output parameters from the EPS AKA key derivation function algorithm include an authentication token ($AUTN_{UE}$), a response parameter (RES), and K_{ASME} .

In step 1725, the SD_i authenticates with the core network by verifying whether $AUTN_{UE}$ is equal to $AUTN_{HSS}$. If the $AUTN_{UE}$ is not equal to $AUTN_{HSS}$, process 1700 ends. If $AUTN_{UE}$ is equal to $AUTN_{HSS}$, the SD_i generates and transmits a User Authentication Response message to the MME in step 1730. The User Authentication Response message includes RES determined in step 1720. Process 1700 ends after step 1730.

Figure 18 illustrates a process flow 1800 performed by the MME in the core network in accordance with the first mutual authentication procedure of timing diagram 1600. Process 1800 begins with step 1805 by receiving the Attach Request from the SD_i .

In step 1810, the MME generates and transmits an Authentication Data Request to the HSS based on the Attach Request received from the SD_i. Other information such as the SN ID_i and network type can be retrieved by the MME based on the request received from the SD_i. The Authentication Data Request includes Access ID_i, SN ID_i, and the network type.

In step 1815, the MME receives the Authentication Data Response from the HSS. The MME is aware of the order of the authentication vectors and selects one authentication vector to authenticate with the SD_i. In step 1820, the MME generates and transmits a User Authentication Request based on the selected authentication vector to the SD_i. The User Authentication Request comprises the RAND and the AUTN_{HSS} from the selected first authentication vector

In step 1825, the MME receives the User Authentication Response from the SD_i. In response, the MME determines whether RES (from the User Authentication Response) is equal to XRES (from the Authentication Data Response). If RES is not equal to XRES, process 1800 ends. If RES is equal to XRES, MME grants the SD_i access to its gateways in step 1830. Particularly, the MME sends a message to the gateways to grant access to the SD. Process 1800 ends after step 1830.

Figure 19 illustrates a process flow 1900 performed by the HSS in the core network in accordance with the first mutual authentication procedure of timing diagram 1600. Process 1900 begins with step 1905 by receiving the Authentication Data Request from the MME.

In step 1910, the HSS generates an Authentication Data Response using EPS AKA algorithm 1990 to obtain authentication vectors. Particularly, the HSS computes a number of authentication vectors based on the EPS AKA algorithm and generates the Authentication Data Response using the authentication vectors. The input parameters for the EPS AKA algorithm include K_i, RAND, SN ID_i, SQN. The output parameters for the EPS AKA algorithm

include $AUTN_{HSS}$, $XRES$, and K_{ASME} . $RAND$ is a random number derived by the HSS. Each of the authentication vectors includes $RAND$, $AUTN_{HSS}$, $XRES$, and K_{ASME} .

The Authentication Data Response is then transmitted to the MME in step 1915. Process 1900 ends after step 1915.

A second mutual authentication between the IoT devices and core network is based on the Access ID and the key. Figure 20 illustrates a timing diagram 2000 on the process of the second mutual authentication between the IoT device and core network in accordance with an embodiment of this disclosure. Timing diagram 2000 begins with step 2010 by transmitting an Attach Request comprising its Access ID_i, $RAND$ 1, Fresh Parameter 1, MAC 1, and other optional parameters to the MME.

In step 2015, in response to receiving the Attach Request, the MME verifies the validity of the Attach Request based on the Fresh Parameter 1. Further details on the verification of the validity of the Attach Request will be described below with reference to figure 22.

In step 2020, if the Attach Request is valid, the MME generates and transmits an Authentication Data Request to the HSS. The Authentication Data Request includes the Access ID_i and $RAND$ 1.

In step 2025, in response to receiving the Authentication Data Request, the HSS locates from its database key K_i that corresponds to the Access ID_i, derives $K1_i$ using the KDF with K_i and $RAND$ 1, generates another random number $RAND$ 2 and uses K_i , $RAND$ 1, $RAND$ 2 and other optional parameters to derive $K2_i$. Further details in this regard will be described below with reference to figure 23.

In step 2030, the HSS generates and transmits an Authentication Data Response to the MME after deriving $K2_i$. The Authentication Data Response shall include $K1_i$, $K2_i$, RAND 2, Control Parameters (Optional).

In step 2035, the MME authenticates SD_i by verifying MAC 1 using $K1_i$. Further details in this regard will be described below with reference to figure 22.

In step 2040, if the authentication is successful, the MME generates and transmits an Authentication Success message to the SD_i . The Authentication Success message includes a one-bit sign to indicate that the authentication is success, RAND2, Fresh Parameter 2, other Parameters (Optional), and MAC 2. Further details in this regard will be described below with reference to figure 22.

In step 2045, the SD derives $K2_i$ and authenticates the core network by verifying MAC 2 using $K2_i$. If authentication is successful, the SD continues to transmit and receive data with the core network. Timing diagram 2000 ends after step 2045.

Figure 21 illustrates a process flow 2100 performed by the IoT device in accordance with the second mutual authentication procedure of timing diagram 2000. Process 2100 begins with step 2105 by retrieving its Access ID_i and K_i and determining a new key $K1_i$ using the key derivation function (KDF) 2190. The input parameters include K_i , a random number denoted as RAND 1, and other optional parameters.

In step 2110, the IoT device generates a Message Authentication Code for Integrity 1 (MAC 1) using $K1_i$. The input parameters of MAC 1 include Access ID_i, RAND 1, Fresh Parameter 1, and other parameters (optional) and can be expressed in the following manner,

MAC 1 = MAC _{$K1_i$} (Access ID_i||RAND 1||Fresh Parameter 1||Other Parameters (Optional))

In step 2115, the SD_i generates and transmits an Attach Request to the MME. The Attach Request includes its Access ID_i, RAND 1, Fresh Parameter 1, MAC 1, and other optional parameters. The fresh parameter can be timestamp, counter or sequence number (SQN) which can be used by the MME to verify the validity of the Attach Request.

In step 2120, the SD_i receives an Authentication Success message from the MME. The Authentication Success message includes a one-bit sign to indicate that the authentication is success, RAND2, Fresh Parameter 2, other Parameters (Optional), and MAC 2.

In step 2125, the SD_i determines $K2_i$ using the key derivation function (KDF) 2195. The input parameters include K_i , RAND 1, another random number denoted as RAND 2 and other optional parameters.

In step 2130, the SD_i authenticates with the core network by verifying MAC 2 using $K2_i$. In order to verify the MAC 2, the SD_i generates the MAC for the received Authentication Success message using the same MAC generation function used by the MME with $K2_i$. One example of the MAC generation function is keyed Hash Message Authentication Code (HMAC). If authentication is successful, process 2100 proceeds to 2135 and continue to transmit and receive data with the core network. Otherwise, process 2100 ends.

Figure 22 illustrates a process flow 2200 performed by the MME in the core network in accordance with the second mutual authentication procedure of timing diagram 2000. Process 2200 begins with step 2205 by receiving the Attach Request.

In step 2210, the MME verifies the Fresh Parameter 1. This is to identify whether the authentication session is a replay attack. The fresh parameter can be timestamp, counter or sequence number (SQN). For example, if the fresh parameter is timestamp, the MME can verify whether the timestamp for the Attach Request is within an acceptable time range. If

the timestamp is within an acceptable time range, the MME considers the Attach Request new and valid. If not, the MME considers the Attach Request as an out-dated message which could be a replay attack. If the fresh parameter is a counter, the MME can verify the counter is in running order with respect to the previous Attach Request. If the counter is in running order, the MME considers the Attach Request new and valid. If not, the MME considers the Attach Request as an out-dated message which could be a replay attack. If the fresh parameter is a SQN, the MME can verify the number of the Attach Request is in accordance with a pre-determined sequence with respect to the number in the previous Attach Request. If the counter is according to the pre-determined sequence, the MME considers the Attach Request new and valid. If not, the MME considers the Attach Request as an out-dated message which could be a replay attack. If the Fresh Parameter 1 is valid, process 2200 proceeds to step 2215. Otherwise, process 2200 ends.

In step 2215, the MME generates and transmits an Authentication Data Request to the HSS. The Authentication Data Request includes the Access ID_i and RAND 1.

In step 2220, the MME receives an Authentication Data Response from the HSS. The Authentication Data Response includes K1_i, K2_i, RAND 2, Control Parameters (Optional).

In step 2225, the MME authenticates SD_i by verifying MAC 1 using K1_i. In order to verify the MAC 1, the MME generates the MAC for the received Attach Request message using the same MAC generation function used by the SD_i with K1_i. One example of the MAC generation function is keyed Hash Message Authentication Code (HMAC). If the MAC 1 is valid, process 2200 proceeds to step 2230. Otherwise, process 2200 ends.

In step 2230, the MME generates and transmits an Authentication Success message to SD_i. The Authentication Success message includes a one-bit sign to indicate that the

authentication is success, RAND2, Fresh Parameter 2, other Parameters (Optional), and MAC 2. The MAC 2 is computed using $K2_i$. The input parameters of computing MAC 2 include AuthSuccess, RAND 2, Fresh Parameter 2, and other parameters (optional) and can be expressed in the following manner,

$$\text{MAC 2} = \text{MAC}_{K2_i}(\text{AuthSuccess} || \text{RAND 2} || \text{Fresh Parameter 2} || \text{Other Parameters (Optional)})$$

In step 2235, the MME grants access to the SD_i . Particularly, the MME sends a message to the gateways to grant access to the SD. Process 2200 ends after step 2235.

Figure 23 illustrates a process flow 2300 performed by the HSS in the core network in accordance with the second mutual authentication procedure of timing diagram 2000. Process 2300 begins with step 2305 by receiving the Authentication Data Request.

In step 2310, the HSS retrieves key K_i corresponding to the Access ID $_i$.

In step 2315, the HSS first derives $K1_i$ using the KDF 2190 with K_i and RAND 1.

In step 2320, the HSS generates another random number RAND 2 and uses K_i , RAND 1, RAND 2 and other optional parameters to derive another key ($K2_i$) using KDF 2195.

In step 2325, the HSS generates and transmits an Authentication Data Response to the MME. The Authentication Data Response includes $K1_i$, $K2_i$, RAND 2, Control Parameters (Optional).

Process 2300 ends after step 2325.

Similar to the second mutual authentication, a third mutual authentication between the IoT devices and core network is also based on the Access ID and the key. The timing diagram 2000 is also applicable to the third mutual authentication. However, there are some

slight difference in how the data is being handled by the IoT devices, MME and HSS. Further details will be described below with reference to figures 24-26.

Figure 24 illustrates a process flow 2400 performed by the IoT device in accordance with the third mutual authentication procedure. Process 2400 begins with step 2405 by generating MAC 1 using K_i . The input parameters of generating MAC 1 include the Access ID_i of the IoT device, Fresh Parameter 1, and other parameters (optional) and can be expressed in the following manner,

$$\text{MAC 1} = \text{MAC}_{K_i}(\text{Access ID}_i || \text{Fresh Parameter 1} || \text{Other Parameters (Optional)})$$

In step 2410, the SD_i generates and transmits an Attach Request. The Attach Request includes the Access ID_i of the SD_i, Fresh Parameter 1, MAC 1, and other optional parameters. The fresh parameter can be timestamp, counter or sequence number (SQN) which can be used by the MME to verify the validity of the Attach Request.

In step 2415, the SD_i receives an Authentication Success message from the MME. The Authentication Success message includes a one-bit sign to indicate that the authentication is success, Fresh Parameter 2, other Parameters (Optional), and MAC 2.

In step 2420, the SD_i authenticates with the core network by verifying MAC 2 using K_i . In order to verify the MAC 2, the SD_i generates the MAC for the received Authentication Success message using the same MAC generation function used by the MME with K_i . One example of the MAC generation function is keyed Hash Message Authentication Code (HMAC). If authentication is successful, process 2400 proceeds to 2425 and continue to transmit and receive data with the core network. Otherwise, process 2400 ends.

Figure 25 illustrates a process flow 2500 performed by the MME in the core network in accordance with the third mutual authentication procedure. Process 2500 begins with step 2505 by receiving the Attach Request.

In step 2510, the MME verifies the Fresh Parameter 1. This is to identify whether the authentication session is a replay attack. Similar to step 2210 in process 2200, the verification of the validity of the Attach Request can be based timestamp, counter and/or sequence number (SQN). If the Fresh Parameter 1 is valid, process 2500 proceeds to step 2515. Otherwise, process 2500 ends.

In step 2515, the MME transmits an Authentication Data Request to the HSS. The Authentication Data Request includes the Access ID_i.

In step 2520, the MME receives an Authentication Data Response from the HSS. The Authentication Data Response includes K_i and Control Parameters (Optional).

In step 2525, the MME authenticates SD_i by verifying MAC 1 using K_i. In order to verify the MAC 1, the MME generates the MAC for the received Attach Request message using the same MAC generation function used by the SD_i with K_i. One example of the MAC generation function is keyed Hash Message Authentication Code (HMAC). If the MAC 1 is valid, process 2500 proceeds to step 2530. Otherwise, process 2500 ends.

In step 2530, the MME generates and transmits an Authentication Success message to the SD_i. The Authentication Success message includes a one-bit sign to indicate that the authentication is success, Fresh Parameter 2, other Parameters (Optional), and MAC 2. The MAC 2 is computed using K_i. The input parameters of computing MAC 2 include AuthSuccess, Fresh Parameter 2, and other parameters (optional) and can be expressed in the following manner,

$$\text{MAC 2} = \text{MAC}_{K_i}(\text{AuthSuccess}||\text{Fresh Parameter 2}||\text{Other Parameters (Optional)})$$

In step 2535, the MME grants access to the SD_i . Particularly, the MME sends a message to the gateways to grant access to the SD_i . Process 2500 ends after step 2535.

Figure 26 illustrates a process flow 2600 performed by the HSS in the core network in accordance with the third mutual authentication procedure. Process 2600 begins with step 2605 by receiving the Authentication Data Request.

In step 2610, the HSS retrieves key K_i corresponding to the Access ID_i .

In step 2615, the HSS generates and transmits an Authentication Data Response to the MME. The Authentication Data Response includes K_i and Control Parameters (Optional). Process 2600 ends after step 2615.

It is noted that the IoT device communicate with the core network via either a MD or any networks that connects both IoT device and the core network. Hence, security channels between SD and MD, and between MD and core network are established in order for the IoT device to communicate with the core network. For brevity, the establishing of the security channels are omitted when discussing the first, second and third mutual authentications. Details of the establishment of the security channels are described above with reference to figure 5.

Revoke of Access ID_i

Access ID_i can be revoked when necessary. Particularly, the Access ID_i can be revoked when the relevant SD_i is compromised. The revoke of Access ID_i is allowed at any time after the Access ID_i is created. To revoke the Access ID_i , the Master Device sends a Revoke Message to the core network within the security channel. The Revoke Message includes the Access ID_i , and RevokeFlag. The RevokeFlag is a binary indicator, with either

“0” or “1” representing the command to revoke the Access ID. Upon receiving the Revoke Message, the MME would transmit the Revoke Message to the HSS which will in turn deactivate the Access ID_i.

Change of Control Parameters

Parameters can be changed or amended as and when required by the Master Device. For example, if the data usage for a SD₁ is minimal while the SD₂ is substantially more than SD₁, the Master Device may want to adjust the parameters of both SD₁ and SD₂ so that the data usage limit for SD₂ can be increased while the data usage limit for SD₁ can be decreased.

The change of parameters is allowed at any time after the Access ID is created. To change the control parameters of SD_i, Master Device sends the Parameters Change Message to the core network inside the security channel. The Parameters Change Message includes the Access ID_i, Control Parameters, and Timestamp. The core network will manage the network access of SDs according to the Parameters with the latest Timestamp.

The processes described above for MME, HSS, and MD can be implemented to current MME, HSS and MD by way of a modification to existing processes. Alternatively, the process described above for MME, HSS, and MD can be implemented by way of a new communication protocol.

It is envisioned that embodiments of this disclosure can be applied to low-cost wireless devices without SIM but require access to the cellular network directly. Some examples of wireless devices without SIM are wearable devices such as smart watches and smart glasses and home consumer goods such as televisions, air-conditioners, refrigerators.

The above is a description of embodiments of a method and system of granting devices without SIM card to access the core network. It is foreseeable that those skilled in the art can and will design alternative method and system based on this disclosure that infringe upon this invention as set forth in the following claims.

CLAIMS:

1. A method for a cellular device (MD) for registering devices without SIM card (SD) to communicate directly with a core network comprising:

- receiving a Device ID from the SD;
- generating an Access ID and key (Ki) for the SD;
- transmitting the Access ID and Ki to the SD.

2. The method according to claim 1, wherein before the receiving a Device ID from the SD, the method further comprises:

- establishing a first security channel between the SD and the MD;
- transmitting a request to the SD for an identity information of the SD (Device ID);

wherein the receiving a Device ID from the SD comprises:

- receiving the Device ID from the SD within the first security channel;
- wherein after the generating an Access ID and key (Ki) for the SD, the method further comprises:
 - creating a new entry;
 - appending the new entry to include the Access ID and Ki.

3. The method according to claim 1 or 2, wherein the generating the Access ID for the SD comprises:

- combining the MD's identity with Device ID to obtain the Access ID.

4. The method according to claim 1 or 2, wherein the generating the Access ID for the SD comprises:

- combining the MD's identity with a random number to obtain the Access ID.

5. The method according to claim 1 or 2, wherein the generating the Access ID for the SD comprises:

combining a sequence number assigned to MD with the Device ID to obtain the Access ID.

6. The method according to anyone of claim 1- 5, wherein the generating the key (K_i) for the SD comprises:

generate K_i using a Key Derivation Function (KDF) with input parameter being one or more of MD's identity, Device ID and Access ID.

7. The method according to claim 1, wherein the generating the Access ID and key (K_i) for the SD comprises:

transmitting the Device ID to the core network; and

receiving the Access ID and K_i from the core network.

8. The method according to claim 7, wherein before the transmitting the Device ID to the core network, the method further comprises:

establishing a second security channel between the SD and the core network;

wherein the transmitting the Device ID to the core network comprises:

transmitting the Device ID to the core network upon establishing the second security channel.

9. A method for communicating a device without SIM card (SD) with a core network comprising:

registering with the core network through a cellular device (MD) to obtain a

credential for the SD, the credential comprises an Access ID and a key (K_i);

performing a mutual authentication directly with the core network using the Access ID and K_i ; and

accessing servers via the core network in response to authenticating successfully with the core network.

10. The method according to claim 9, wherein the registering with the core network through the MD comprises:

retrieving the Device ID;

transmitting the Device ID to the MD;

receiving the Access ID and K_i from the MD; and

storing the Access ID and K_i .

11. The method according to claim 9 or 10, wherein the performing the mutual authentication directly with the core network using the credential comprises:

sending an Attach Request to the core network, the Attach Request comprising the Access ID;

receiving a User Authentication Request from the core network, the User Authentication Request comprising a random number (RAND) and an authentication token ($AUTN_{HSS}$) generated by the core network using Evolved Packet System (EPS) Authentication and Key Agreement (AKA) algorithm;

computing an authentication vector using EPS AKA algorithm with the RAND, the K_i , a serving network identity (SN ID), a sequence number (SQN) as the input parameters and an authentication token ($AUTN_{UE}$) and a response parameter (RES) as the output parameter;

determining whether the $AUTN_{UE}$ is equal to the $AUTN_{HSS}$; and

generating and transmit a User Authentication Response message to the MME in response to the $AUTN_{UE}$ being equal to $AUTN_{HSS}$, the User Authentication Response comprising RES.

12. The method according to claim 9 or 10 wherein the performing the mutual authentication directly with the core network using the credential comprises:

determining a new key ($K1_i$) using a Key Derivation Function (KDF) with input as K_i and a random number (RAND 1);

generating a Message Authentication Code for Integrity 1 (MAC 1) using $K1_i$ with input parameters comprising Access ID, RAND 1, and Fresh Parameter 1;

generating and transmit an Attach Request to the core network, the Attach Request comprising the Access ID, RAND 1, Fresh Parameter 1, and MAC 1;

receiving an Authentication Success message from the core network, the Authentication Success message includes a one-bit sign (AuthSuccess), a random number (RAND 2) generated by the core network, Fresh Parameter 2, and MAC 2, wherein MAC 2 is generated by the core network using another key ($K2_i$) with AuthSuccess, RAND 2 and Fresh Parameter 2 as input parameters, wherein the Fresh Parameters 1 and 2 are one of a timestamp, counter and sequence number

determining another key ($K2_i$) using KDF with K_i , RAND 1, and RAND 2 as input parameters;

determining a validity of MAC 2 using $K2_i$; and

transmitting and receiving data with the core network in response to MAC 2 being valid.

13. The method according to claim 9 or 10 wherein the performing the mutual authentication directly with the core network using the credential comprises:

generating a Message Authentication Code for Integrity 1 (MAC 1) using K_i with input parameters comprising Access ID and Fresh Parameter 1;

generating and transmitting an Attach Request to the core network, the Attach Request comprising the Access ID, Fresh Parameter 1, and MAC 1, wherein the Fresh Parameter 1 is one of a timestamp, counter and sequence number;

receiving an Authentication Success message from the core network, the Authentication Success message includes a one-bit sign (AuthSuccess), Fresh Parameter 2, and MAC 2;

determining a validity of MAC 2 using K_i ; and

transmitting and receiving data with the core network in response to MAC 2 being valid.

14. A cellular device (MD) for registering devices without SIM card (SD) to communicate directly with a core network comprising:

a processor;

a storage medium;

instructions stored on the storage medium and executable by the processor to:

receive a Device ID from the SD;

generate an Access ID and key (K_i) for the SD;

transmit the Access ID and K_i to the SD.

15. The MD according to claim 14, wherein before the receiving a Device ID from the SD, wherein the instructions stored on the storage medium and executable by the processor to:

establish a first security channel between the SD and the MD;

transmit a request to the SD for an identity information of the SD (Device ID);

wherein the instruction to receiving Device ID from the SD comprises instructions to:

receive the Device ID from the SD within the first security channel;

wherein after the generating an Access ID and key (K_i) for the SD, the instructions stored on the storage medium and executable by the processor to:

create a new entry;

append the new entry to include the Access ID and K_i .

16. The MD according to claim 14 or 15, wherein the instructions to generate the Access ID for the SD comprises instructions to:

combine the MD's identity with Device ID to obtain the Access ID.

17. The MD according to claim 14 or 15, wherein the instruction to generate the Access ID for the SD comprises instructions to:

combining the MD's identity with a random number to obtain the Access ID.

18. The MD according to claim 14 or 15, wherein the instruction to generate the Access ID for the SD comprises instructions to:

combine a sequence number assigned to MD with the Device ID to obtain the Access ID.

19. The MD according to anyone of claim 14- 18, wherein the instruction to generate the key (K_i) for the SD comprises instructions to:

generate K_i using a Key Derivation Function (KDF) with input parameter being one or more of MD's identity, Device ID and Access ID.

20. The MD according to claim 14, wherein the generating the Access ID and key (K_i) for the SD comprises:

transmitting the Device ID to the core network; and
 receiving the Access ID and K_i from the core network.

21. The method according to claim 20, wherein before the transmitting the Device ID to the core network, instructions stored on the storage medium and executable by the processor to:

establish a second security channel between the SD and the core network;

wherein the instruction to transmit the Device ID to the core network comprises instructions to:

transmit the Device ID to the core network upon establishing the second security channel.

22. A device without SIM card (SD) for communicating with a core network comprising:

a processor;

a storage medium;

instructions stored on the storage medium and executable by the processor to:

register with the core network through a cellular device (MD) to obtain a credential for the SD, the credential comprises an Access ID and a key (K_i);

perform a mutual authentication directly with the core network using the Access ID and K_i ; and

access servers via the core network in response to authenticating successfully with the core network.

23. The SD according to claim 22, wherein the instruction to register with the core network through the MD comprises instructions to:

retrieve the Device ID;

transmit the Device ID to the MD;
 receive the Access ID and K_i from the MD; and
 store the Access ID and K_i in the storage medium.

24. The method according to claim 22 or 23, wherein the instruction performing the mutual authentication directly with the core network using the credential comprises instructions to:

send an Attach Request to the core network, the Attach Request comprising the Access ID;

receive a User Authentication Request from the core network, the User Authentication Request comprising a random number (RAND) and an authentication token ($AUTN_{HSS}$) generated by the core network using Evolved Packet System (EPS) Authentication and Key Agreement (AKA) algorithm;

compute an authentication vector using EPS AKA algorithm with the RAND, the K_i , a serving network identity (SN ID), a sequence number (SQN) as the input parameters and an authentication token ($AUTN_{UE}$) and a response parameter (RES) as the output parameter;

determine whether the $AUTN_{UE}$ is equal to the $AUTN_{HSS}$; and

generate and transmit a User Authentication Response message to the MME in response to the $AUTN_{UE}$ being equal to $AUTN_{HSS}$, the User Authentication Response comprising RES.

25. The SD according to claim 23 or 24 wherein the instruction performing the mutual authentication directly with the core network using the credential comprises instructions to:

determine a new key (K_{1i}) using a Key Derivation Function (KDF) with input as K_i and a random number (RAND 1);

generate a Message Authentication Code for Integrity 1 (MAC 1) using $K1_i$ with input parameters comprising Access ID, RAND 1, and Fresh Parameter 1;

generate and transmit an Attach Request to the core network, the Attach Request comprising the Access ID, RAND 1, Fresh Parameter 1, and MAC 1;

receive an Authentication Success message from the core network, the Authentication Success message includes a one-bit sign (AuthSuccess), a random number (RAND 2) generated by the core network, Fresh Parameter 2, and MAC 2, wherein MAC 2 is generated by the core network using another key ($K2_i$) with AuthSuccess, RAND 2 and Fresh Parameter 2 as input parameters, wherein the Fresh Parameters 1 and 2 are one of a timestamp, counter and sequence number

determine another key ($K2_i$) using KDF with K_i , RAND 1, and RAND 2 as input parameters;

determine a validity of MAC 2 using $K2_i$; and

transmit and receive data with the core network in response to MAC 2 being valid.

26. The SD according to claim 23 or 24 wherein the instruction performing the mutual authentication directly with the core network using the credential comprises instructions to:

generate a Message Authentication Code for Integrity 1 (MAC 1) using K_i with input parameters comprising Access ID and Fresh Parameter 1;

generate and transmit an Attach Request to the core network, the Attach Request comprising the Access ID, Fresh Parameter 1, and MAC 1, wherein the Fresh Parameter 1 is one of a timestamp, counter and sequence number;

receive an Authentication Success message from the core network, the Authentication Success message includes a one-bit sign (AuthSuccess), Fresh Parameter 2, and MAC 2;

determine a validity of MAC 2 using K_i ; and

transmit and receive data with the core network in response to MAC 2 being valid.

27. A core network for registering devices without SIM card (SD) to communicate directly with the core network comprising:

a Mobility Management Entity (MME) and a Home Subscriber Server (HSS) communicatively connected together, each of the MME and HSS comprising a processor, a storage medium, and instructions stored on the respective storage medium and executable by the respective processor to:

register an SD through a cellular device (MD) to obtain a credential for the SD, the credential comprises an Access ID and a key (K_i);

perform a mutual authentication directly with the SD using the Access ID and key; and

grant the SD access to servers in response to authenticating successfully with the SD.

28. The core network according to claim 27 wherein the instructions to register the SD through the MD comprise instructions stored on the storage medium of the MME to:

establish a security channel between the MD and the MME;

receive and review a message from the MD within the security channel;

generate data based on the message received;

transmit the data to the HSS;

receive a response message from the HSS; and

transmit the response message to the MD within the security channel.

29. The core network according to claim 28 wherein the data comprises an identity of the MD (MD ID), Device ID and control parameter to the HSS in response to the message

containing a Device ID and control parameter, wherein MD ID is obtainable via the message received from the MD.

30. The core network according to claim 28 wherein the data comprises an identity of the MD (MD ID), Device ID, Access ID, key and control parameter to the HSS in response to the message containing a Device ID, Access ID, key and control parameter, wherein MD ID is obtainable via the message received from the MD.

31. The core network according to claims 29 and 30 wherein the instructions to register the SD through the MD comprise instructions stored on the storage medium of the HSS to:

- receive the data from the MME;

- determine whether the data contains an Access ID;

- generate a Access ID and K_i in response to the data not containing an Access ID;

and

- store the Access ID and K_i from the data in the storage medium of the HSS in response to the data containing an Access ID.

32. The core network according to claim 31 wherein the instruction to generate Access ID and K_i comprises instructions stored on the storage medium of the HSS to:

- retrieve a record for a list of MDs from the storage medium;

- determine whether the Device ID is in the list of MDs;

- create a new entry in the list of MDs in response to determining the Device ID is not in the list of MDs;

- generate the Access ID by combining the MD ID and Device ID; and

- generate the K_i by using a Key Derivation Function (KDF) on one or a few of MD ID and Device ID;

append the new entry to include Access ID, key, and control parameter; and
generate and transmit a response message containing the generated Access ID and key for the Device ID to the MME.

33. The core network according to claim 31 wherein the instruction to store the Access ID and K_i comprises instructions stored on the storage medium of the HSS to:

determine whether the Access ID is acceptable;

create a new entry in a list of MDs in the HSS database comprising the Device ID, Access ID, Key and control parameter in response to the Access ID being acceptable;
and

generate and transmit a response message containing an acceptance message to the MME.

34. The core network according to claim 33 wherein the instruction to determine whether the Access ID is acceptable comprises instruction to:

verify whether a format of the Access ID is in a pre-determined format.

35. The core network according to claim 27 wherein the instructions to perform a mutual authentication directly with the SD using the Access ID and key comprise instructions stored on the storage medium of the MME to:

receive an Attach Request from the SD, the Attach Request comprising the Access ID;

generate an Authentication Data Request based on the Attach Request received;

transmit the Authentication Data Request to the HSS, wherein the Authentication Data Request comprises Access ID, Serving Network Identity (SN ID) and network type, and wherein the SN ID and network type are obtainable on the Attach Request received

from the SD.

36. The core network according to claim 35 wherein the instructions to perform a mutual authentication directly with the SD using the Access ID and key comprise instructions stored on the storage medium of the HSS to:

receive the Authentication Data Request from the MME;

compute a plurality of first authentication vectors based on Evolved Packet System (EPS) Authentication and Key Agreement (AKA) algorithm with a random number (RAND), Key, SN ID, SQN as the input parameters and $AUTN_{HSS}$, XRES, and K_{ASME} as the output parameter; and

generate and transmit an Authentication Data Response comprising the plurality of first authentication vectors, each first authentication vector comprises RAND, $AUTN_{HSS}$, XRES, K_{ASME} .

37. The core network according to claim 36 wherein the instructions to perform a mutual authentication directly with the SD using the Access ID and key comprise instructions stored on the storage medium of the MME to:

receive the Authentication Data Response from the HSS;

select one of the plurality of first authentication vectors;

generate and transmit a User Authentication Request to the SD, the User Authentication Request comprising the RAND and the $AUTN_{HSS}$ from the selected first authentication vector;

receive a User Authentication Response message from the SD, the User Authentication Response comprising a response parameter (RES) generated by the SD using EPS AKA algorithm;

determine whether RES is equal to XRES received from HSS in response to

receiving the User Authentication Response from the SD; and

grant SD access to gateways in response to RES being equal to XRES.

38. The core network according to claim 27 wherein the instructions to perform a mutual authentication directly with the SD using the Access ID and key comprise instructions stored on the storage medium of the MME to:

receive an Attach Request from the SD, the Attach Request comprising the Access ID, a random number (RAND 1), Fresh Parameter 1, and a Message Authentication Code for Integrity 1 (MAC 1), wherein the Fresh Parameter 1 is one of a timestamp, counter and sequence number;

determine a validity of the Attach Request in response to receiving the Attach Request from the SD; and

generate and transmit an Authentication Data Request to the HSS in response to determining the Attach Request is valid, the Authentication Data Request includes the Access ID and RAND 1.

39. The core network according to claim 38 wherein the instruction to determine the validity of the Attach Request comprises instruction to:

determine whether the timestamp for the Attach Request is within a pre-determined time range.

40. The core network according to claim 38 wherein the instruction to determine the validity of the Attach Request comprises instruction to:

determine whether the counter is in running order with respect to previous Attach Request.

41. The core network according to claim 38 wherein the instruction to determine the validity of the Attach Request comprises instruction to:

determine whether the number of the Attach Request is in accordance with a pre-determined sequence with respect to the number in the previous Attach Request.

42. The core network according to claim 38 wherein the instructions to perform a mutual authentication directly with the SD using the Access ID and key comprise instructions stored on the storage medium of the HSS to:

receive the Authentication Data Request from the MME;

retrieve the K_i that corresponds to the Access ID from the storage medium;

determine a new key $K1_i$ using the KDF with K_i and RAND 1;

generate another random number (RAND 2);

determine another key ($K2_i$) using the KDF with K_i , RAND 1, and RAND 2; and

generate and transmit an Authentication Data Response to the MME, the Authentication Data Response comprises $K1_i$, $K2_i$, and RAND 2.

43. The core network according to claim 42 wherein the instructions to perform a mutual authentication directly with the SD using the Access ID and key comprise instructions stored on the storage medium of the MME to:

receive the Authentication Data Response from the HSS;

determine a validity of MAC 1 using $K1_i$;

compute a Message Authentication Code for Integrity 2 (MAC 2) using $K2_i$ with a one-bit sign (AuthSuccess), RAND 2 and Fresh Parameter 2 as input parameters in response to MAC 1 being valid;

generate and transmit an Authentication Success message to SD, the Authentication Success message includes AuthSuccess, RAND 2, Fresh Parameter 2, and MAC 2; and

transmit a message to gateways to grant access to the SD.

44. The core network according to claim 27 wherein the instructions to perform a mutual authentication directly with the SD using the Access ID and key comprise instructions stored on the storage medium of the MME to:

receive an Attach Request from the SD, the Attach Request comprising the Access ID, Fresh Parameter 1, and a Message Authentication Code for Integrity 1 (MAC 1), wherein the Fresh Parameter 1 is one of a timestamp, counter and sequence number;

determine a validity of the Attach Request in response to receiving the Attach Request from the SD; and

generate and transmit an Authentication Data Request to the HSS in response to determining the Attach Request is valid, the Authentication Data Request includes the Access ID.

45. The core network according to claim 44 wherein the instructions to perform a mutual authentication directly with the SD using the Access ID and key comprise instructions stored on the storage medium of the HSS to:

receive the Authentication Data Request from the MME;

retrieve the Key that corresponds to the Access ID from the storage medium;

generate and transmit an Authentication Data Response to the MME, the Authentication Data Response comprises the Key.

46. The core network according to claim 45 wherein the instructions to perform a mutual authentication directly with the SD using the Access ID and key comprise instructions stored on the storage medium of the MME to:

receive the Authentication Data Response from the HSS;

determine a validity of MAC 1 using the Key;

compute a Message Authentication Code for Integrity 2 (MAC 2) using the key with a one-bit sign (AuthSuccess), and Fresh Parameter 2 as input parameters in response to MAC 1 being valid;

generate and transmit an Authentication Success message to SD, the Authentication Success message includes AuthSuccess, Fresh Parameter 2, and MAC 2; and

transmit a message to gateways to grant access to the SD.

47. A Home Subscriber Server (HSS) for registering devices without SIM card (SD) to communicate directly with the core network comprising:

a processor,

a storage medium,

and instructions stored on the storage medium and executable by the processor to:

receive the data from the MME;

determine whether the data contains an Access ID;

generate an Access ID and K_i in response to the data not containing an Access ID.

48. The HSS according to claim 47, wherein the instruction to generate a Access ID and K_i comprises instructions stored on the storage medium of the HSS to:

retrieve a record for a list of MDs from the storage medium;

determine whether the Device ID is in the list of MDs;

create a new entry in the list of MDs in response to determining the Device ID is not in the list of MDs;

generate the Access ID by combining the MD ID and Device ID; and

generate the K_i by using a Key Derivation Function (KDF) on one or a few of MD ID and Device ID;

append the new entry to include Access ID, key, and control parameter; and
 generate and transmit a response message containing the generated Access ID and
 key for the Device ID to the MME.

49. A HSS according to claim 47 or 48, wherein the instructions stored on the storage
 medium and executable by the processor to:

store the Access ID and K_i from the data in the storage medium of the HSS in
 response to the data containing an Access ID.

50. The HSS according to claim 49, wherein the instruction to store the Access ID and K_i
 comprises instructions stored on the storage medium of the HSS to:

determine whether the Access ID is acceptable;

create a new entry in a list of MDs in the HSS database comprising the Device ID,
 Access ID, Key and control parameter in response to the Access ID being acceptable;
 and

generate and transmit a response message containing an acceptance message to
 the MME.

51. A Home Subscriber Server (HSS) for registering devices without SIM card (SD) to
 communicate directly with the core network comprising:

a processor,

a storage medium,

and instructions stored on the storage medium and executable by the processor to:

receive an Authentication Data from the HSS, wherein the Authentication Data
 includes a RAND and a $AUTN_{HSS}$;

generate and transmit a User Authentication Request to the SD, the User Authentication Request comprising the RAND and the $AUTN_{HSS}$;

receive a User Authentication Response message from the SD, the User Authentication Response comprising a response parameter (RES) generated by the SD using EPS AKA algorithm;

determine whether RES is equal to XRES received from HSS in response to receiving the User Authentication Response from the SD; and

grant SD access to gateways in response to RES being equal to XRES.