166166

G00002

-1 DEC 2003

DISPLAYING A COMPLEX TREE STRUCTURE AMONG MULTIPLE WINDOWS

BACKGROUND OF THE INVENTION

1. Technical Field:

The present invention generally relates to computer system management and in particular to visual representations of computer data. Still more particularly, the present invention relates to improved representations of tree structures in a computer system.

2. Description of the Related Art:

A variety of application programs and operating systems include a user interface feature enabling users to view a listing of information stored on a computer. For example, the Windows 98 operating system from Microsoft Corporation includes a Windows Explorer program to help the user keep track of files stored in the computer. Since even simple PCs have the capacity to store thousands of files, it is important for many applications to include an effective means for viewing lists of information stored on a computer.

Large lists of files, directories and other computer resources are much easier to understand when portrayed in a hierarchical fashion. A hierarchical representation is an effective method of listing computer resources because it

=1 DEC 2003

groups related subject matter together in a manner that enables the user to locate desired items more easily. One way to represent a hierarchy is to use a tree structure. A tree structure includes a number of reference points called nodes that together comprise a tree. The origin or base of a tree is called the root node, which is characterized as having no parent nodes. Every other node has only one parent and potentially one or more children nodes. A leaf is the lowest node in the hierarchy of the tree and thus has no children. This concept of a tree structure can be applied to many types of data or computer resource classifications.

One example of this tree structure is a file system where related information is grouped together using a hierarchy of sub-directories. In this example, the main directory is the root node of the tree, and a number of sub-directories to the main directory are its child nodes. Each sub-directory can be broken into a number of other sub-directories to achieve additional layers of hierarchy. At each level of hierarchy, there may be a number of files, which are leaf nodes of the tree structure. In addition to directories of files, the concept of a tree structure can be extended to other arbitrary groupings of data.

While using a tree structure is an effective way to represent complex information stored in a computer, it is important for the computer to display information such that the user can easily browse through it. It is quite typical

-1 DEC 2003

to have complex tree structures in today's computer systems, especially considering the growing memory capacity of the typical personal computer. Computer network applications add further complexity because of the vast amount of data that can be distributed across a network.

Network database applications especially require an effective user interface to represent database resources distributed across a network. In a typical network database configuration, it is not unusual to have a large number of server database applications distributed throughout a computer network. Each server database application in the network can be associated with a very complex hierarchy of information. As a result, it is very difficult for users to locate desired information without an effective user interface to view and navigate through the complex hierarchy of information distributed across the network.

A text-based user interface can be used to navigate information stored in a hierarchical tree structure, but such user interfaces are rather limited. These text-based user interfaces do not convey enough information about the overall hierarchy to the user because they can only display a flat listing of one level of the hierarchy at a time. Unless the user can remember where an item is located in the tree structure, he/she often has to repeatedly page through levels of hierarchy before finding the proper path to the desired item.

-1 DEC 2003

User interfaces displaying a graphical representation of a tree structure offer a more effective interface than the text-based approach. The Windows Explorer interface, for example, graphically displays the hierarchy of a file system. It allows the user to view several layers of hierarchy at once, and also enables the user to interactively expand nodes in the tree structure. A user can "expand" a node by selecting and clicking on a parent node, causing the Windows Explorer to show child nodes of the parent node.

While graphical user interfaces such as the Windows Explorer feature in Windows operating systems provide better performance, they do not provide an effective interface for very large and complex tree structures such as those typically encountered in network database applications. One drawback of the Windows Explorer product is that it only allows the user to view one portion of a tree at one time. The user cannot break up the tree into smaller more manageable pieces of information while maintaining the tree structure. The Windows Explorer does allow a user to expand a leaf in the tree, but the utility of this feature is limited. When a user expands a tree in a node, the Windows Explorer interface displays a separate window containing a flat list of child nodes of the parent node. This separate window does not represent a separate and new hierarchical tree; but rather, it merely represents a flat list of nodes similar to the flat list provided in

-1 DEC 2003

text-based interfaces.

In general, graphical user interfaces for navigating hierarchical structures are limited by the standard size of display screens on today's computer systems. It is very difficult for a user to navigate through complex tree structures when the display screen can only accommodate a very small portion of the tree structure. To navigate from one node to another requires using the up and down or left and right scrollbar. There is a need, therefore, for an improved user interface that enables users to more easily and effectively navigate through complex hierarchies of information stored in a computer system.

-1 DEC 2003

SUMMARY OF THE INVENTION

It is therefore one object of the present invention to provide improved computer system management capabilities.

It is another object of the present invention to provide improved visual representations of computer data.

It is yet another object of the present invention to provide improved representations of tree structures in a computer system.

According to one aspect of the invention there is provided a computer system, comprising:

a processor;

a memory connected to a read from and written to by the processor, the memory containing a hierarchial representation of data; and

a display connected to display the data in a plurality of tree structures in respective windows on the display;

wherein the display shows connections between parent nodes and child nodes when parent and child nodes are displayed in different windows.

According to another aspect of the invention there is provided a method for displaying data in a computer system, comprising the steps of:

displaying data in a first tree structure, having parent and child nodes, in a first area of a computer display;

removing a portion of the data from said first area and displaying the portion in a second tree structure in a second area of the computer display;

displaying a visual connection between parent and child nodes in different areas of the display.

According to yet another aspect of the invention there is provided a method for displaying data in a computer system, comprising the steps of:

displaying first data in a first tree structure, having parent and child nodes, in a first area of a computer display;

displaying second data in a second tree structure, having parent and child nodes, in a second area of the computer display, wherein a root node of the second data is a child of a node of the first data;

displaying a link between the root node of the second data and the parent node of that root node in the first data;

upon receipt of input from a user, combining the first data and the second data in the same area of the display.

According to yet another aspect of the invention there is provided a method for displaying hierarchically arranged data in a computer system, comprising the steps of:

displaying a first tree structure having a plurality of nodes sharing parent/child relationships, in a first window within a computer display; and

responsive to a tree window open selection of one of said plurality of nodes within the first tree structure:

displaying a second tree structure having a plurality of nodes sharing parent/child relationships, in a second window within the computer display, wherein the root node of the second tree structure is the tree window open selected node, and wherein the tree window open selected node is removed from the first tree structure displayed within the first window; and

displaying an inter-window link between the root node of the second tree structure and a corresponding parent node within the first tree structure such that visual connectivity is maintained between the first tree structure within the first window and the second tree structure within the second window.

According to yet another aspect of the invention there is provided a computer program product within a computer usable medium for displaying hierarchically arranged data in a computer system, comprising:

instructions for displaying a first tree structure having a plurality of nodes sharing parent/child relationships, in a first window within a computer display; and

instructions responsive to a tree window open selection of one of said plurality of nodes within the first tree structure for:

displaying a second tree structure having a plurality of nodes sharing parent/child relationships, in a second window within the computer display, wherein the root node of the

-1 DEC 2003

second tree structure is the tree window open selected node, and wherein the tree window open selected node is removed from the first tree structure displayed within the first window; and

displaying an inter-window link between the root node of the second tree structure and a corresponding parent node within the first tree structure such that visual connectivity is maintained between the first tree structure within the first window and the second tree structure within the second window.

-1 DEC 2003

BRIEF DESCRIPTION OF THE DRAWINGS

The novel features believed characteristic of the invention are set forth in the appended claims. The invention itself however, as well as a preferred mode of use, further objects and advantages thereof, will best be understood by reference to the following detailed description of an illustrative embodiment when read in conjunction with the accompanying drawings, wherein:

Figure 1 depicts a data processing system in accordance with a preferred embodiment of the present invention;

Figure 2 is an exemplary computer display with a window showing a system tree in accordance with a preferred embodiment of the invention;

Figure 3 depicts an exemplary computer display with windows showing a system tree and subtree in accordance with a preferred embodiment of the invention;

Figure 4 is an exemplary computer display with windows showing a system tree and two subtrees in accordance with a preferred embodiment of the invention;

Figure 5 depicts an exemplary computer display with windows showing a system tree and subtree in accordance with a preferred embodiment of the invention;

1 DEC 2003

Figure 6 is a flowchart of a process in accordance with a preferred embodiment of the invention;

Figure 7 depicts a flowchart of another process in accordance with a preferred embodiment of the invention; and

Figure 8 is an exemplary pop-up menu in accordance with a preferred embodiment of the invention.

-1 DEC 2003

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

The following description details the operation and features of several preferred embodiments of the present invention, but it will be understood by those of skill in the art that the scope of the invention is defined only by the issued claims, and not by any description herein.

With reference now to the figures, and in particular with reference to **Figure 1**, a block diagram of a data processing system in which a preferred embodiment of the present invention can be implemented is depicted. Data processing system **100** can be, for example, one of the computers available from International Business Machines Corporation of Armonk, New York. Data processing system **100** includes processors **101** and **102**, which in the exemplary embodiment are each connected to level two (L2) caches **103** and **104**, respectively, which are connected in turn to a system bus **106**.

Also connected to system bus **106** is system memory **108** and Primary Host Bridge (PHB) **122**. PHB **122** couples I/O bus **112** to system bus **106**, relaying and/or transforming data transactions from one bus to the other. In the exemplary embodiment, data processing system **100** includes graphics adapter **118** connected to I/O bus **112**, receiving user interface information for display **120**. Peripheral devices such as nonvolatile storage **114**, which can be a hard disk

01 DEC 2003

drive, and keyboard/pointing device **116**, which can include a conventional mouse, a trackball, or the like, are connected via an Industry Standard Architecture (ISA) bridge **121** to I/O bus **112**. PHB **122** is also connected to PCI slots **124** via I/O bus 112.

The exemplary embodiment shown in **Figure 1** is provided solely for the purposes of explaining the invention and those skilled in the art will recognize that numerous variations are possible, both in form and function. For instance, data processing system **100** might also include a compact disk read-only memory (CD-ROM) or digital video disk (DVD) drive, a sound card and audio speakers, and numerous other optional components. All such variations are believed to be within the spirit and scope of the present invention. Data processing system **100** and the exemplary figures below are provided solely as examples for the purposes of explanation and are not intended to imply architectural limitations.

The keyboard/pointing device **116** includes, in the preferred embodiment, a pointing device which allows "click-and-drag" operation, such as a mouse, trackball, or touchpad. This type of input device is common on most typical systems running a windowed interface, and is the preferred means for manipulating windows and the tree structures described below.

01 DEC 2003

While this description mentions in particular the Windows operating system developed by the Microsoft Corporation, it will be understood by one of skill in the art that the innovative techniques described below can be applied to many other "windowed" systems, such as X-Windows, and in fact can be applied to any system which uses tree structures to represent data hierarchies.

According to the preferred embodiment, multiple windows are used to represent different branches of a single tree structure. The user can select any tree node and choose a "start new window" action, or may simply "drag" that node out of the tree window. A new window is created, and displays a subtree using the selected node as the root. A visual link is attached from the parent node, in the original window, to the root node of the subtree in the new window. This link allows the user at any time to see exactly where, in the larger structure, the subtree belongs.

The user can repeat this process to decompose a complex tree structure into a set of windows. Within each window, information is displayed in a more manageable manner. To merge a subtree window back to its parent, the user can select the root of that subtree and choose a "merge back to parent" action, or simply drag the root of the subtree back to the parent node window. When the user has done so, the subtree window will become part of the parent node window,

and any links to remaining subtree windows will be redrawn accordingly.

With reference now to **Figure 2**, a computer display **200** with an exemplary tree structure window **210** is shown. Note that this is a very simple structure, compared to many encountered on typical systems, and is used for ease of illustration.

The basic tree structure is shown in window **210**. In this and the following figures, node "A" **240** is the root node of system. It has two child nodes "B" **250** and "C" **260**, and node "A" **240** is referred to as the parent of those nodes. Node "B" **250** has two child nodes "D" **252** and "E" **254**. Node C **260** has two child nodes "F" **262** and "G" **268**. Node **262** has two child nodes "H" **264** and "I" **266**.

If the user wished to work only with the subtree beginning with node C, the user would select node C, then select "Start New Window" on a pop-up window, as shown in **Figure 8**, or the user may simply drag Node B out of window **210**, using a mouse or other pointing device. When the user has done so, a new window **315** opens in the system, as in **Figure 3**.

Referring now to **Figure 3**, another exemplary computer display **300** is shown, which contains tree windows **310** and **315**. Window **310** shows the original system tree, as in

-1 DEC 2003

Figure 2, except that node C **360** and its subtree are now displayed in new window **315**. Node C **260** has two child nodes "F" **262** and "G" **268**, and node **262** has two child nodes "H" **264** and "I" **266**, as in the previous figure, but the tree display **315** is greatly simplified. Note that a link **370**, which extends between windows **310** and **315**, still connects node C to its parent node A. In this manner, the user can immediately see the relation of this subtree to the actual root.

Referring now to **Figure 4**, if the user then selected "Start New Window" after selecting node F **462**, or dragged node F **462** out of window **315**, another window **420** would open with a subtree structure having node F **462** as the virtual root. Nodes H **464** and I **466** are shown as the children of node F, as in **Figure 2**, but the tree display in window **420** again is even more simplified. Note that link **472** shows the connection from the virtual root F **462** in window **420** to its parent node C **460** in window **415**, and then link **470** shows the connected between node C **460** and the actual root A **440**. Again, in this manner, the user can immediately see the relation of each subtree window to its parent node, all the was up the tree to the actual root.

Referring now to **Figure 5**, if the user then selected "Merge Back to Parent" after selecting node C **560**, or dragged node C **560** back to window **510**, node C's window (**415** in **Figure 4**) is closed and that subtree is displayed back in

-1 DEC 2003

place in window **510**. Here, node C **560** and node G **568** are shown in their places in the tree of window **510**, which corresponds to their original locations as shown in **Figure 2**. Note that window **520**, with the node F **562** subtree, is unaffected by this change; the only difference is that the link **574** from node F **562** to its parent node C **560** now connects between windows **520** and **510**. Again, in this manner, the user can immediately see the relation of each subtree window to its parent nodes, and all the way up the tree to the actual root.

Referring now to **Figure 6**, a flowchart of a process to form a new subtree window is shown. First, the system will display a hierarchical data tree in a window on the display (**step 600**). Next, the user selects a node and drags it out of the window, to another area of the display (**step 610**). The system then will open a new window (**step 620**), and will display a new data tree in that window, using the node the user selected as the root (**step 630**). Of course, any subtrees of the selected node are removed from the original window when they are shown in the new window.

Finally, the system draws a connection between the virtual-root node of the new subtree window and that node's parent node in the original window (**step 640**). This step is important since it allows the user to still view the overall tree hierarchy while working with the much-simpler subtrees.

=1 DEC 2003

With reference now to **Figure 7**, a flowchart of a process to merge a subtree window back into its parent tree window is shown. Here, it is assumed that the system is already displaying at least two related tree windows, one of which is the parent of the other (**step 700**). Of course a link will be displayed linking the subtree root to its parent node in the parent tree window.

Next, the user drags the subtree root node from the subtree window to the parent tree window (**step 710**). Note that if the user were to drag some other node out of one of the windows this would indicate a process as in **Figure 6**.

After the user has done so, the parent tree window is redrawn to include the subtree as a part of its parent tree (**step 720**). The child tree window is closed (**step 730**). Finally, the links from any other visible subtree to the respective parent nodes are redrawn, if the parent node was moved (**step 740**).

Of course, although the "dragging" technique is described in the examples below, the same function is achieved using the "pop-up menu" technique, as described.

With reference now to **Figure 8**, an exemplary pop-up menu **800** for tree navigation is shown. While such a pop-up window may have many different and conventional functions **830**, the preferred embodiment also provides additional

-1 DEC 2003

functions.

The first additional function is "Start New Window" **810**, as discussed above. When this is activated, a new window is opened on the system and a new hierarchical tree is drawn, using the currently selected node as a virtual root.

When "Merge Back to Parent" **820** is selected, the current window with a virtual-root is closed, and the selected subtree is merged back into its parent tree, as described above. Note that if the virtual-root is the actual root, as in **Figure 2**, then the "Merge Back to Parent" **820** menu option would not be available.

If desired, a notebook can be used to maintain all the subtree windows. The connection between each window can use the page tab as the intermediate connection. A node can connect to an icon on the page tab by a visual link. A single click on that icon within the page tab will flip the notebook to the page which contains the subtree information.

The above as well as additional objectives, features, and advantages of the present invention will become apparent in the following detailed written description.

It is important to note that while the present invention has been described in the context of a fully

-1 DEC 2003

functional data processing system and/or network, those skilled in the art will appreciate that the mechanism of the present invention is capable of being distributed in the form of a computer usable medium of instructions in a variety of forms, and that the present invention applies equally regardless of the particular type of signal bearing medium used to actually carry out the distribution. Examples of computer usable mediums include: nonvolatile, hard-coded type mediums such as read only memories (ROMs) or erasable, electrically programmable read only memories (EEPROMs), recordable type mediums such as floppy disks, hard disk drives and CD-ROMs, and transmission type mediums such as digital and analog communication links.

While the invention has been particularly shown and described with reference to a preferred embodiment, it will be understood by those skilled in the art that various changes in form and detail may be made therein without departing from the spirit and scope of the invention.

-1 DEC 2003

CLAIMS:

What is claimed is:

1. A computer system, comprising:

a processor;

a memory connected to be read from and written to by the processor, the memory containing a hierarchical representation of data; and

a display connected to display the data in a plurality of tree structures in respective windows on the display;

wherein the display shows connections between parent nodes and child nodes when parent and child nodes are displayed in different windows.

2. The computer system of claim 1, wherein said system executes a graphical user interface.

3. The computer system of claim 1, wherein each of said tree structures represents a portion of a master tree structure.

21 DEC 2003

4. A method for displaying data in a computer system, comprising the steps of:

displaying data in a first tree structure, having parent and child nodes, in a first area of a computer display;

removing a portion of the data from said first area and displaying the portion in a second tree structure in a second area of the computer display;

displaying a visual connection between parent and child nodes in different areas of the display.

5. The method of claim 4, wherein said system executes a graphical user interface.

6. The method of claim 4, wherein each of said tree structures represents a portion of a master tree structure.

7. The method of claim 4, wherein the root of the second tree structure is a child of a node in the first tree structure.

8. A method for displaying data in a computer system, comprising the steps of:

displaying first data in a first tree structure, having parent and child nodes, in a first area of a computer display;

displaying second data in a second tree structure, having parent and child nodes, in a second area of the computer display, wherein a root node of the second data is a child of a node of the first data;

displaying a link between the root node of the second data and the parent node of that root node in the first data;

upon receipt of input from a user, combining the first data and the second data in the same area of the display.

9. The method of claim 8, wherein said system executes a graphical user interface.

10. The method of claim 8, wherein each of said tree structures represents a portion of a master tree structure.

11. The method of claim 8, wherein when the first data and second data are combined, a single tree structure is formed.

-1 DEC 2003

12. A computer program product within a computer usable medium, comprising:

instructions for displaying data in a tree structure, having parent and child nodes, in a first area of a computer display;

instructions for removing a portion of the data from said first area and displaying the portion in a second area of the computer display; and

instructions for displaying a visual connection between parent and child nodes in different areas of the display.

13. The computer program product of claim 12, wherein said program product executes within a graphical user interface.

14. The computer program product of claim 12, wherein said tree structures represents a computer file system.

15. The computer program product of claim 12, further comprising instructions for receiving input from a user.

1 DEC 2003

16. A computer program product within a computer usable medium, comprising:

instructions for displaying first data in a first tree structure, having parent and child nodes, in a first area of a computer display;

instructions for displaying second data in a second tree structure, having parent and child nodes, in a second area of the computer display, wherein a root node of the second data is a child of a node of the first data;

instructions for displaying a link between the root node of the second data and the parent node of that root node in the first data; and

instructions for combining the first data and the second data in the same area of the display, upon receipt of input from a user.

17. The computer program product of claim 16, wherein said program product executes within a graphical user interface.

18. The computer program product of claim 16, wherein said tree structures represents a computer file system.

19. The computer program product of claim 16, further comprising instructions for receiving input from a user.

20. A method for interactively displaying a tree structure for representing hierarchical data in a programmed computer system, the method comprising:

storing a master tree structure in memory of the programmed computer system;

displaying in a first window a hierarchical master tree corresponding to at least a portion of the master tree structure;

in response to a user command to separate the master tree into a subtree beginning at a user-specified node in the master tree:

creating the hierarchical client subtree;

creating a second window for displaying the hierarchical subtree;

displaying the subtree in the second window with the user-specified node forming a root node of the subtree; and

creating a visible link between the user-specified node in the subtree and its parent node in the master tree.

21. A method for displaying hierarchically arranged data in a computer system, comprising the steps of:

displaying a first tree structure having a plurality of nodes sharing parent/child relationships, in a first window within a computer display; and

responsive to a tree window open selection of one of said plurality of nodes within the first tree structure:

displaying a second tree structure having a plurality of nodes sharing parent/child relationships, in a second window within the computer display, wherein the root node of the second tree structure is the tree window open selected node, and wherein the tree window open selected node is removed from the first tree structure displayed within the first window; and

displaying an inter-window link between the root node of the second tree structure and a corresponding parent node within the first tree structure such that visual connectivity is maintained between the first tree structure within the first window and the second tree structure within the second window.

22. The method of claim 21, wherein said computer system executes a graphical user interface.

23. The method of claim 21, wherein each of said first and second tree structures represents a portion of a master tree structure.

24. The method of claim 21, further comprising the step of:

responsive to a tree window close selection of the second tree

structure root node:

combining the second tree structure displayed within the second window into the first tree structure displayed within the first window such that when the first tree structure and second tree structure are combined, a single tree structure is formed within the first window; and

closing the second window.

25. The method of claim 24, wherein said tree window close selection comprises dragging and dropping the second tree structure root node from the second window into the first window.

26. A computer program product within a computer usable medium for displaying hierarchically arranged data in a computer system, comprising:

instructions for displaying a first tree structure having a plurality of nodes sharing parent/child relationships, in a first window within a computer display; and

instructions responsive to a tree window open selection of one of said plurality of nodes within the first tree structure for:

displaying a second tree structure having a plurality of nodes sharing parent/child relationships, in a second window within the computer display, wherein the root node of the second tree structure is the tree window open selected node, and wherein the tree window open selected node is removed from the first tree structure displayed within the first window; and

displaying an inter-window link between the root node of the second tree structure and a corresponding parent node within the first tree structure such that visual connectivity is maintained between the first tree structure within the first window and the second tree structure within the second window.

27. The computer program product of claim 26, wherein said program product executes within a graphical user interface.

28. The computer program product of claim 26, wherein said first and second tree structures represent a computer file system.

29. The computer program product of claim 26, further comprising instructions for receiving input from a user.

30. The computer program product of claim 26, further comprising:

instructions responsive to a tree window close selection of the second tree structure root node for:

combining the second tree structure displayed within the second window into the first tree structure displayed within the first window such that when the first tree structure and second tree structure are combined, a single tree structure is formed within the first window; and closing the second window.