

**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H01S 3/00	A1	(11) International Publication Number: ✓WO 97/05676
		(43) International Publication Date: 13 February 1997 (13.02.97)
<p>(21) International Application Number: PCT/US96/10616 ✓</p> <p>(22) International Filing Date: 22 July 1996 (22.07.96) ✓</p> <p>(30) Priority Data: 08/508,093 27 July 1995 (27.07.95) ✓ US</p> <p>(71) Applicant: METHODE ELECTRONICS, INC. [US/US]; 7444 West Wilson Avenue, Chicago, IL 60656-4549 (US). ✓</p> <p>(72) Inventors: GILLILAND, Patrick, B.; 5451 North East River Road, Chicago, IL 60656 (US). GORYACHEV, Andy, A.; 722 East North Broadway, 2W, Lombard, IL 60148 (US).</p> <p>(74) Agent: BARRETT, Robert, M.; Hill, Steadman & Simpson, Sears Tower, 85th floor, 233 South Wacker Drive, Chicago, IL 60606 (US).</p>		<p>(81) Designated States: AU, DE, GB, RU, SG, European patent (IE).</p> <p>Published With international search report.</p> 

(54) Title: OPTOELECTRONIC TRANSCEIVER MODULE LASER DIODE STABILIZER AND BIAS CONTROL METHOD

(57) Abstract

A power stabilizer maintains a constant level of output power from a laser transmitter. The laser transmitter has a laser diode which produces an optical output which corresponds to the level of bias current received. In addition, the laser transmitter has a photodiode which produces a feedback signal which corresponds to the optical output power being produced by the laser diode. Furthermore, the power stabilizer consists of a digitally controlled potentiometer for producing a reference input signal and an op-amp for comparing the feedback signal and the reference input signal to produce a control signal to supply the bias current.