

RESOURCE TRANSFER METHOD BASED ON NEAR FIELD COMMUNICATION

CROSS-REFERENCE TO RELATED APPLICATIONS

The disclosure claims priority to Chinese Patent Application No. 201810123291.1,
5 entitled "Target User Position Information Management Method, Device and System and
Electronic Equipment", filed on February 7, 2018, and Chinese Patent Application No.
201810124221.8, entitled "Resource Transfer Method, Device and System Based on Near
Field Communication and Electronic Equipment", filed on February 7, 2018, which are
incorporated herein by reference in entirety.

BACKGROUND

Technical Field

The disclosure relates to the technical field of computers, and more particularly to
resource transfer based on near field communication and target user position information
management.

Related Art

With the development of near field communication (NFC) technology, data transmission
and payment based on near field communication gradually enter daily life of people, for
example, the use of a near field communication acceptance terminal. A user can transmit data
or other resources through a mobile phone with a built-in near field communication module
20 and the near field communication acceptance terminal by means of near field communication.
For example, the user performs order payment through an acceptance terminal of a merchant
to realize monetary resource transfer. However, the near field communication acceptance
terminal is high in cost and needs to be connected to a network, so that an application scenario
is limited, and the near field communication acceptance terminal is not widely applied at
25 present.

SUMMARY

In order to solve the above problems, in a first aspect, an embodiment of the disclosure

provides a resource transfer method based on near field communication, applied to a resource transfer terminal including a near field communication module. The method includes:

5 acquiring a user identifier of a current login user in a first resource management client by a resource transfer terminal of a target merchant according to the triggering of the first resource management client, and outputting target merchant authentication information;

when it is determined that the resource transfer terminal has enabled a fixed quantity resource transfer mode, generating a resource transfer order by the resource transfer terminal according to a preset quantity of resources transferred by each order;

10 adding a merchant signature of the target merchant and a user signature generated according to the acquired user identifier to the resource transfer order by the resource transfer terminal, and storing the resource transfer order with the signatures; and

sending an acceptance state of the resource transfer order to the first resource management client by the resource transfer terminal by means of near field communication.

15 The fixed quantity resource transfer mode and the quantity of resources transferred by each order are set according to data sent by a second resource management client.

In a second aspect, an embodiment of the disclosure provides a resource transfer method based on near field communication, including:

20 sending an instruction of acquiring target merchant authentication information stored in a resource transfer terminal by a first resource management client by means of near field communication;

receiving output information of the resource transfer terminal by the first resource management client by means of near field communication; and

25 when the output information includes a resource transfer order generated by the resource transfer terminal, sending the resource transfer order to a resource management platform by the first resource management client through a network, so as to complete resource transfer corresponding to the resource transfer order through the resource management platform, and sending a completion state of the resource transfer order to a resource transfer target merchant

through the resource management platform.

In a third aspect, an embodiment of the disclosure provides a resource transfer method based on near field communication, including:

5 acquiring a resource transfer order stored in a resource transfer terminal by means of near field communication, where the resource transfer order is a resource transfer order generated when a first resource management client transfers resources to a target merchant in an offline scenario; and

sending the resource transfer order to a resource management platform through a network, so as to complete resource transfer corresponding to the resource transfer order.

10 In a fourth aspect, an embodiment of the disclosure provides a resource transfer device based on near field communication, including:

a communication establishing module, configured to acquire a user identifier of a current login user in a first resource management client by a resource transfer terminal of a target merchant according to the triggering of the first resource management client, and output
15 target merchant authentication information;

a resource transfer order generating module, configured to generate a resource transfer order by the resource transfer terminal according to a preset quantity of resources transferred by each order when it is determined that the resource transfer terminal has enabled a fixed quantity resource transfer mode;

20 a resource transfer order storage module, configured to add a merchant signature of the target merchant and a user signature generated according to the user identifier to the resource transfer order by the resource transfer terminal, and store the resource transfer order with the signatures; and

an order state output module, configured to send an acceptance state of the resource
25 transfer order to the first resource management client by the resource transfer terminal by means of near field communication.

In a fifth aspect, an embodiment of the disclosure provides a resource transfer device

based on near field communication, including:

a handshaking module, configured to send an instruction of acquiring target merchant authentication information stored in a resource transfer terminal by a first resource management client by means of near field communication;

5 a feedback information receiving module, configured to receive output information of the resource transfer terminal by the first resource management client by means of near field communication; and

an online resource transfer module, configured to send a resource transfer order generated by the resource transfer terminal to a resource management platform by the first
10 resource management client through a network when the output information includes the resource transfer order generated by the resource transfer terminal, so as to complete resource transfer corresponding to the resource transfer order through the resource management platform, and send a completion state of the resource transfer order to a resource transfer target merchant through the resource management platform.

15 In a sixth aspect, an embodiment of the disclosure provides a resource transfer device based on near field communication, including:

a resource transfer order exporting module, configured to acquire a resource transfer order stored in a resource transfer terminal by means of near field communication, where the resource transfer order is a resource transfer order generated when a first resource
20 management client transfers resources to a target merchant in an offline scenario; and

a resource transfer module, configured to send the resource transfer order to a resource management platform through a network, so as to complete resource transfer corresponding to the resource transfer order.

25 In a seventh aspect, an embodiment of the disclosure provides a resource transfer system based on near field communication, including:

a resource management platform, a resource transfer terminal, and a first resource management client and a second resource management client respectively communicated with the resource management platform through a network.

The resource management platform is configured to manage the resource transfer terminal and complete a resource transfer order.

5 The resource transfer terminal, the first resource management client and the second resource management client are respectively configured to perform a resource transfer method based on near field communication.

In an eighth aspect, an embodiment of the disclosure provides a target merchant position information management method based on near field communication, including:

10 acquiring at least one resource transfer order stored in a resource transfer terminal by a second resource management client by means of near field communication, where the resource transfer terminal includes a near field communication module; and

managing position information of a target merchant by the second resource management client according to information included in the resource transfer order.

The information included in the resource transfer order at least includes a geographic position.

15 In a ninth aspect, an embodiment of the disclosure further discloses electronic equipment, including a storage medium, a processor and a machine executable instruction stored in the storage medium and capable of running on the processor. When the processor executes the machine executable instruction, a resource transfer method based on near field communication according to the embodiment of the disclosure is implemented.

20 In a tenth aspect, an embodiment of the disclosure provides a computer readable storage medium. A computer program is stored thereon. When the program is executed by a processor, steps of a resource transfer method based on near field communication disclosed by the embodiment of the disclosure are implemented.

25 The resource transfer method based on near field communication disclosed by the embodiments of the disclosure solves problems of limited use scenario and high cost of a resource transfer method in the prior art by: acquiring the user identifier of the current login user in the first resource management client by the resource transfer terminal of the target merchant according to the triggering of the first resource management client, outputting

target merchant authentication information, generating the resource transfer order by the resource transfer terminal according to the preset quantity of resources transferred by each order when it is determined that the resource transfer terminal has enabled the fixed quantity resource transfer mode, adding the merchant signature and the user signature to the resource transfer order, and storing the resource transfer order with the signatures.

The target merchant position information management method based on near field communication provided by the embodiment of the disclosure solves the problem that position information of an offline user cannot be managed in the prior art by managing the position information of the target merchant according to the information included in an offline resource transfer order by the first resource management terminal of the target merchant after the offline resource transfer order stored in the resource transfer terminal of the target merchant is acquired. The geographic position information management on an offline target merchant is realized, and the accuracy of the geographic position information management on the target merchant is greatly improved by acquiring geographic position information of the user during offline trading between the user and the target merchant, storing the geographic position information into the offline resource transfer order, and then, further using the geographic position information in the offline resource transfer order as an offline geographic position of the target merchant.

BRIEF DESCRIPTION OF THE DRAWINGS

To describe the technical solutions in the embodiments of this disclosure more clearly, the following briefly describes the accompanying drawings required for describing the embodiments. Apparently, the accompanying drawings in the following description show merely some embodiments of the present invention, and a person of ordinary skill in the art may still derive other drawings from these accompanying drawings without creative efforts.

Figure 1 is a flow diagram of a resource transfer method according to Embodiment 1 of the disclosure.

Figure 2 is a flow diagram of a modified embodiment of the resource transfer method according to Embodiment 1 of the disclosure.

Figure 3 is a flow diagram of a resource transfer method according to Embodiment 2 of the disclosure.

Figure 4 is a flow diagram of a modified embodiment of the resource transfer method according to Embodiment 2 of the disclosure.

5 Figure 5 is a flow diagram of a resource transfer method according to Embodiment 3 of the disclosure.

Figure 6 is a flow diagram of a modified embodiment of the resource transfer method according to Embodiment 3 of the disclosure.

10 Figure 7 is a schematic structure diagram of a resource transfer device according to Embodiment 4 of the disclosure.

Figure 8 is a schematic structure diagram of a modified embodiment of the resource transfer device according to Embodiment 4 of the disclosure.

Figure 9 is a schematic structure diagram of a resource transfer device according to Embodiment 5 of the disclosure.

15 Figure 10 is a schematic structure diagram of a modified embodiment of the resource transfer device according to Embodiment 5 of the disclosure.

Figure 11 is a schematic structure diagram of a resource transfer device according to Embodiment 6 of the disclosure.

20 Figure 12 is a schematic structure diagram of a modified embodiment of the resource transfer device according to Embodiment 6 of the disclosure.

Figure 13 is a schematic structure diagram of a resource transfer system according to Embodiment 7 of the disclosure.

Figure 14 is a first schematic diagram of a work flow of the system shown in Figure 13.

25 Figure 15 is a flow diagram of a target merchant position information management method according to Embodiment 8 of the disclosure.

Figure 16 is a schematic structure diagram of a target merchant position information

management system according to Embodiment 9 of the disclosure.

Figure 17 is a flow diagram of specific application of a target merchant position information management method in the system shown in Figure 16.

Figure 18 is a first schematic structure diagram of a target merchant position information management device according to Embodiment 10 of the disclosure.

Figure 19 is a second schematic structure diagram of the target merchant position information management device according to Embodiment 10 of the disclosure.

DETAILED DESCRIPTION

The following clearly and completely describes the technical solutions in the embodiments of the disclosure with reference to the accompanying drawings in the embodiments of the disclosure. Apparently, the described embodiments are merely some but not all of the embodiments of the disclosure. All other embodiments obtained by a person of ordinary skill in the art based on the embodiments of the disclosure without creative efforts shall fall within the protection scope of the disclosure.

Embodiment 1

A resource transfer method based on near field communication disclosed by the present embodiment is applied to a resource transfer terminal. The resource transfer terminal includes a near field communication module. As shown in Figure 1, the method includes step 100 to step 130.

Step 100, a resource transfer terminal of a target merchant acquires a user identifier of a current login user in a first resource management client according to the triggering of the first resource management client, and outputs target merchant authentication information.

The resource transfer terminal includes a casing and the near field communication module, and is equipment of the target merchant. During specific implementation, the resource transfer terminal may be portable equipment with a built-in near field communication module, such as a card or a name plate. The resource transfer terminal is preset with a merchant signature and authentication information of the target merchant. The

authentication information may be a merchant name or an icon, etc. The merchant signature is a numeral string generated according to a merchant identifier of the target merchant. The merchant identifier is a unique identifier acquired by the target merchant through a resource management platform.

5 The first resource management client is an application client of the resource management platform. During specific application, the first resource management client is application software installed in equipment with a near field communication module, such as a mobile phone of a user, and may also be user equipment with a near field communication module. In the present embodiment, the first resource management client is supposed to be the
10 application software installed in the equipment with the near field communication module, such as the mobile phone of the user.

When the user wants to transfer resources with the target merchant by means of near field communication, for example, the user wants to perform order payment to the merchant by means of near field communication, the user logs in the first resource management client
15 installed in the mobile phone enabling a near field communication function, and then initiates a payment flow process. The first resource management client may transmit a signal of reading the resource transfer terminal through a near field communication module of a host machine.

After sensing the signal of reading the resource transfer terminal, the near field
20 communication module of the resource transfer terminal processes the received signal, and resolves information sent by the first resource management client through a near field communication signal. Here, the resource transfer terminal resolves the user identifier of the current login user in the first resource management client, and an instruction of acquiring locally stored merchant authentication information (i.e., the target merchant authentication
25 information). The resource transfer terminal outputs the locally stored authentication information (i.e., the target merchant authentication information), and stores the resolved user identifier, i.e., the user identifier of the current login user in the first resource management client.

Step 110, when it is determined that the resource transfer terminal has enabled a fixed

quantity resource transfer mode, the resource transfer terminal generates a resource transfer order according to a preset quantity of resources transferred by each order.

The fixed quantity resource transfer mode and the quantity of resources transferred by each order are set according to data sent by a second resource management client.

- 5 During specific implementation, the quantity of resources transferred by each order may also be sent to the resource transfer terminal through the second resource management client to realize transfer of a fixed quantity of resources in single time. When receiving the quantity of resources transferred by each order sent by the second resource management client, the resource transfer terminal may locally store the quantity of resources transferred by each
10 order, and starts the fixed quantity resource transfer mode.

- When the user initiates a resource transfer flow process through the first resource management client, and moves close to the resource transfer terminal to read the merchant authentication information stored in the resource transfer terminal, the near field communication module of the resource transfer terminal starts at an induced voltage
15 generated in response to a signal sent by the first resource management client, and extracts the user identifier carried in the signal. At the same time, the resource transfer terminal judges whether the fixed quantity resource transfer mode is enabled or not. When it is determined that the fixed quantity resource transfer mode has been enabled, the resource transfer terminal generates the resource transfer order according to a locally prestored quantity of resources
20 transferred by each order.

Step 120, the resource transfer terminal adds a merchant signature of the target merchant and a user signature generated according to the acquired user identifier to the resource transfer order, and stores the resource transfer order with the signatures.

- Then, the user signature is generated according to the acquired user identifier. For
25 example, a user signature of a resource transfer-out user is generated according to a user identifier of the resource transfer-out user, and the locally prestored merchant signature of the target merchant and the user signature of the resource transfer-out user are added to the resource transfer order.

Step 130, the resource transfer terminal sends an acceptance state of the resource transfer order to the first resource management client by means of near field communication.

Finally, the resource transfer terminal locally stores the resource transfer order with the signatures. Additionally, after the order is successfully stored, successful acceptance
5 information of the resource transfer order is output to the first resource management client. If the order storage fails, failed acceptance information of the resource transfer order is output to the first resource management client.

The resource transfer terminal is passive equipment, and power is supplied through an induced voltage generated in response to an induced signal of a user terminal. Therefore, in
10 order to improve the order generating efficiency, the quantity of resources of each order may be preset. When the user performs offline resource transfer through resource transfer equipment, the resource transfer quantity does not need to be input. A fixed quantity of resource transfer can be realized only by moving close to the resource transfer terminal for reading, and the resource transfer efficiency is greatly improved. Generally, for example,
15 when the user performs payment by scanning a two-dimensional code, the mobile phone of the user needs to be connected to a network. By using the resource transfer method based on near field communication disclosed by the embodiment of the disclosure, the order payment can be realized without connecting the mobile phone of the user to the network, so that great convenience is provided for a payment behavior of the user.

20 Hereto, the user completes offline resource transfer once with the target merchant through a terminal with the built-in near field communication module.

According to the resource transfer method based on near field communication disclosed by the embodiment of the disclosure, the resource transfer terminal of the target merchant acquires the user identifier of the current login user in the first resource management client
25 according to the triggering of the first resource management client, and outputs the target merchant authentication information. At the same time, when it is determined that the resource transfer terminal has enabled the fixed quantity resource transfer mode, the resource transfer terminal generates the resource transfer order according to the preset quantity of resources transferred by each order, adds the user signature and the merchant signature to the

resource transfer order, and then stores the resource transfer order with the signatures. The problems of limited use scenario and high cost of the resource transfer method in the prior art are solved.

5 According to the resource transfer method based on near field communication disclosed by the embodiment of the disclosure, resource transfer can be completed by means of near field communication under the condition that a near field communication terminal of the user is not connected to the network. At the same time, the resource transfer terminal does not need to be connected to the network, and the use scenario is not limited. Additionally, a host of the first resource management terminal in the disclosure may be the mobile phone with the near field communication function. The resource transfer terminal only needs to include the near field communication module, for example, may be an electronic card with the near field communication module. The cost is very low. Wide application is facilitated. The near field communication module can realize self power supply after sensing a radio frequency signal, additionally, a certain storage space exists in the near field communication module, 10 and a control program may be developed on an embedded secure element included in the near field communication module. Therefore, the resource transfer terminal can complete reception and storage of the resource transfer order and complete offline resource transfer. 15

In one modification of the present embodiment, as shown in Figure 2, the method further includes:

20 Step 140, the resource transfer terminal outputs the stored resource transfer order according to the triggering of the second resource management client, so that the second resource management client completes resource transfer corresponding to the resource transfer order through the resource management platform.

25 During specific implementation, the second resource management client may be an application program running on a mobile phone of the target merchant (such as a merchant) with a near field communication module, and may also be other equipment with a near field communication module. The second resource management client may read resource transfer order data stored in the resource transfer terminal by means of near field communication in real time or in regular time.

By taking a condition that the second resource management client is an application program running on the mobile phone of the merchant with the near field communication module as an example, when the merchant moves the mobile phone close to the resource transfer terminal, the resource transfer terminal starts under the effect of the induced voltage generated in response to the induced signal of the mobile phone, and outputs the locally stored resource transfer order according to the received instruction of reading the resource transfer order sent by the second resource management client. The second resource management client further sends the read resource transfer order to the resource management platform through the network. The resource management platform resolves the resource transfer order, and transfers the specified quantity of resources from an account of the transfer-out user to an account of the target merchant according to information in each resource transfer order, so as to complete resource transfer.

By taking code scanning payment as an example, the user needs to be connected to a network to perform code scanning payment, so that the application scenario is limited. By using the resource transfer method based on near field communication disclosed by the embodiment of the disclosure, offline resource transfer can be realized between users by using the resource transfer terminal as a medium. The problem that the resource transfer can only be completed under the network connected condition by a resource transfer-out user and a resource transfer-in user is solved, convenience is provided for the resource transfer of the users, and the application scenarios of the resource transfer are expanded. Additionally, the resource transfer terminal is used as the medium between the users, the resource transfer is performed by means of near field communication, and the security is higher.

In one modification of the present embodiment, as shown in Figure 2, after the step that the resource transfer terminal of the target merchant acquires the user identifier of the current login user in the first resource management client according to the triggering of the first resource management client, the step that the resource transfer terminal receives the resource transfer order sent by the first resource management client by means of near field communication is further included.

After the first resource management client receives the target merchant authentication

information sent by the resource transfer terminal, generally, the first resource management client may show information of the target merchant according to the target merchant authentication information. When the target merchant authentication information is an icon of the target merchant or an authentication icon of the resource management platform, the first resource management client shows the icon for the current login user to confirm. Then, the first resource management client acquires the resource transfer quantity input by the user, such as a payment amount. After the user confirms the payment order, the resource transfer order is generated according to the user identifier of the user, the resource transfer quantity, the current system time, information corresponding to the resource and the like. The generated resource transfer order is sent to the resource transfer terminal by means of near field communication. The resource transfer terminal may receive the resource transfer order sent by the first resource management client by means of near field communication.

Then, the resource transfer terminal adds the merchant signature of the target merchant and the user signature generated according to the user identifier to the resource transfer order, and stores the resource transfer order with the signatures.

The resource transfer terminal generates the user signature of the current login user of the first resource management client according to a preset rule according to the user identifier of the current login user of the first resource management client. Then, the resource transfer terminal adds the signatures to the received resource transfer order, including adding the user signature generated according to the user identifier of the current login user of the first resource management client and the signature of the target merchant (i.e., the merchant signature) stored in the resource transfer terminal, and locally stores the resource transfer order with the signatures.

Finally, the resource transfer terminal sends the acceptance state of the resource transfer order to the first resource management client by means of near field communication.

The resource transfer terminal sends the successful acceptance state of the resource transfer order to the first resource management client by means of near field communication according to a storage result of the resource transfer order. For example, after the resource transfer terminal successfully stores the resource transfer order, the successful acceptance

information of the order is sent to the first resource management client by means of near field communication. If the storage of the resource transfer order fails, the resource transfer terminal sends failed acceptance information of the order to the first resource management client by means of near field communication.

5 By feeding the merchant authentication information back to the first resource management client for the user to perform identity verification on the target merchant, the security of resource transfer and the user experience can be improved. The first resource management client generates the order, the user can manually input the resource transfer quantity, and the operation flexibility of resource transfer is improved. Encrypted storage is
10 performed by the resource transfer terminal, so the security of resource transfer can be further guaranteed.

In one modification of the present embodiment, as shown in Figure 2, after the resource transfer terminal of the target merchant acquires the user identifier of the current login user in the first resource management client according to the triggering of the first resource
15 management client, the method further includes:

Step 150, whether the current login user is a blacklist user or not is determined according to a prestored user blacklist and the user identifier. If YES, step 160 is performed.

Through the prestored user blacklist, according to the user identifier, whether the current login user is the blacklist user or not is judged. If the current login user is the blacklist user,
20 the resource transfer terminal outputs failed resource transfer information, so that the first resource management client executes a blacklist prompt on the current login user.

Step 160, when it is determined that the user identifier corresponds to the user in the blacklist based on the user blacklist, a blacklist setting instruction of setting the user into the blacklist user is sent to the first resource management client by means of near field
25 communication, and the user is removed from the user blacklist.

During specific implementation, as shown in Figure 2, before the resource transfer terminal of the target merchant acquires the user identifier of the current login user in the first resource management client according to the triggering of the first resource management

client, the method further includes:

Step 170, the user blacklist sent by the second resource management client is received and stored by means of near field communication.

During specific implementation, after successful acceptance of the offline resource transfer order, the second resource management client may read the resource transfer order in the resource transfer terminal after a period of time, and then settles accounts with the resource management platform to finally complete resource transfer. A condition that the resource quantity in the account of the resource transfer-out user is smaller than the quantity of to-be-transferred resources in the order may occur, so that the resource management platform cannot successfully complete the settlement between the transfer-out user and the target merchant. By aiming at this condition, the resource transfer method of the disclosure sets the user blacklist. When the number of times of settlement incapable of being successfully completed by the resource management platform on one transfer-out user exceeds a preset quantity, the transfer-out user is added into the user blacklist to be issued to each first resource management client or resource transfer terminal, and the first resource management client or the resource transfer terminal is notified to refuse to perform resource transfer with the blacklist user, so as to reduce resource loss of the target merchant and the resource management platform.

According to the present embodiment, the resource transfer terminal prestores the user blacklist and indicates the first resource management client to set the user blacklist, the problem that the blacklist user cannot issue the user blacklist to the first resource management client without being connected to the network is solved, so that a resource transfer risk is avoided, and the resource loss of the target merchant and the resource management platform is reduced. For example, after the user is connected to the network to log in the resource management platform, the network is disconnected, the multi-time offline resource transfer is performed through the resource transfer terminal, but the resource management platform cannot successfully complete resource transfer due to resource insufficiency in the account, and the target merchant may suffer greater loss if the user is not added to the user blacklist in time to be issued to the resource transfer terminal. By issuing the user blacklist to the

resource transfer terminal by means of near field communication through the second resource management client, the blacklist user can be discovered under the condition that the user is not connected to the network, and the security of resource transfer is improved.

5 However, with the gradual increase of the blacklist users, the user blacklist may occupy a great storage space of the resource transfer terminal. In order to improve the utilization efficiency of resources stored in the resource transfer terminal, when the user reads the resource transfer terminal through the first resource management client, the resource transfer terminal determines whether the user identifier of the user is a user in the user blacklist or not according to the locally stored user blacklist. If it is determined that the user identifier is
10 a user in the user blacklist, the blacklist setting instruction is sent by means of near field communication to notify the first resource management client to locally set the user into the blacklist user in the first resource management client. Then, the resource transfer terminal removes the user from the locally stored user blacklist in the resource transfer terminal, so as to save the storage space of the resource transfer terminal.

15 Optionally, before the resource transfer order with the user signature is stored, the method further includes:

The resource transfer order with the user signature is subjected to encryption processing through a preset key.

20 During specific implementation, a root key issued by the built-in resource management platform of the resource transfer terminal is configured to manage the resource transfer terminal by the resource management platform. At the same time, the resource management platform further issues a data transmission key or a trading key to the resource transfer terminal according to application of the second resource management client, and the data transmission key or the trading key is sent by the second resource management client to the
25 resource transfer terminal to be stored. When the resource transfer terminal sends the resource transfer order to the first resource management client, or locally stores the resource transfer order, transmission and storage are performed after the order is encrypted through the preset trading key or the data transmission key, so as to improve the security of resource transfer.

The key is stored in the resource transfer terminal of the target merchant, and may be updated at any time. Additionally, the resource transfer terminal, the first resource management client and the second resource management client do not have permission to resolve the key, and only the resource management platform controls the generation of the key and resolves the key, so that the security of resource transfer can be further improved.

Embodiment 2

The present embodiment discloses a resource transfer method based on near field communication. As shown in Figure 3, the method includes: step 300 to step 330.

Step 300, a first resource management client sends an instruction of acquiring target merchant authentication information stored in a resource transfer terminal by means of near field communication.

The first resource management client is an application client of a resource management platform. During specific application, the first resource management client is application software installed in equipment with a near field communication module, such as a mobile phone of a user, and may also be user equipment with a near field communication module. In the present embodiment, the first resource management client is supposed to be the application software installed in the equipment with the near field communication module, such as the mobile phone of the user.

When the user wants to transfer resources with a target merchant by means of near field communication, for example, the user wants to perform order payment to the merchant by means of near field communication, the user logs in the first resource management client installed in the mobile phone enabling a near field communication function, and then initiates a payment flow process. The first resource management client may transmit a signal of reading the resource transfer terminal through a near field communication module of a host machine.

Step 310, the first resource management client receives output information of the resource transfer terminal by means of near field communication.

The resource transfer terminal includes a casing and a near field communication module,

and is equipment of the target merchant. During specific implementation, the resource transfer terminal may be portable equipment with a built-in near field communication module, such as a card or a name plate. The resource transfer terminal is preset with a merchant signature and authentication information of the target merchant. The authentication
5 information may be a merchant name or an icon, etc. The merchant signature is a numeral string generated according to a merchant identifier of the target merchant. The merchant identifier is a unique identifier acquired by the target merchant through the resource management platform.

After sensing a near field communication signal of reading the resource transfer terminal,
10 the near field communication module of the resource transfer terminal processes the received signal, and resolves information sent by the first resource management client. Here, the resource transfer terminal resolves the user identifier of a current login user in the first resource management client, and an instruction of acquiring merchant authentication information (i.e., the target merchant authentication information) locally stored by the
15 resource transfer terminal. The resource transfer terminal outputs the locally stored authentication information, i.e., the target merchant authentication information. At the same time, the resource transfer terminal stores the resolved user identifier, i.e., the user identifier of the current login user in the first resource management client for sending the information of reading the resource transfer terminal is stored.

20 Step 320, when the output information includes a resource transfer order generated by the resource transfer terminal, the first resource management client sends the resource transfer order generated by the resource transfer terminal to the resource management platform through a network, so as to complete resource transfer corresponding to the resource transfer order through the resource management platform, and sends a completion state of
25 the resource transfer order to a second resource management client of a resource transfer target merchant through the resource management platform.

During specific implementation, the target merchant may send the quantity of resources transferred by a single order to the resource transfer terminal through the second resource management client to realize transfer of a fixed quantity of resources in a single time. When

receiving the quantity of resources transferred by each order sent by the second resource management client, the resource transfer terminal may locally store the quantity of resources transferred by each order, and enables a fixed quantity resource transfer mode.

5 When the user initiates a resource transfer flow process through the first resource management client, and moves close to the resource transfer terminal to read the authentication information of the resource transfer terminal, the near field communication module of the resource transfer terminal starts at an induced voltage generated in response to an induced signal of the first resource management client, and extracts the user identifier carried in the signal sent by the first resource management client. At the same time, the
10 resource transfer terminal judges whether the fixed quantity resource transfer mode is enabled or not. When it is determined that the fixed quantity resource transfer mode has been enabled, the resource transfer terminal generates the resource transfer order according to a locally prestored quantity of resources transferred by each order. Then, a user signature is generated according to the user identifier. For example, a user signature of a resource
15 transfer-out user is generated according to a user identifier of the resource transfer-out user, and the locally prestored merchant signature of the target merchant and the user signature of the resource transfer-out user are added to the resource transfer order. Finally, the resource transfer terminal outputs the resource transfer order with the signatures by means of near field communication.

20 After receiving the resource transfer order output by the resource transfer terminal, the first resource management client sends the resource transfer order generated by the resource transfer terminal to the resource management platform through the network, so as to complete resource transfer corresponding to the resource transfer order through the resource management platform. The resource management platform resolves and processes the
25 received resource transfer order, completes transfer of the corresponding quantity of resources in the resource transfer order from the transfer-out user to the target merchant, and sends the completion state of the resource transfer order to the second resource management client of the resource transfer target merchant.

Step 330, the first resource management client receives the completion state of the

resource transfer order sent by the resource management platform through the network.

After resource transfer is completed, the resource management platform sends the completion state of the resource transfer order (such as successful resource transfer or failed resource transfer) to the first resource management client of the resource transfer order through the network.

According to the resource transfer method based on near field communication disclosed by the present embodiment, the first resource management client sends the instruction of acquiring the target merchant authentication information stored in the resource transfer terminal by means of near field communication, and receives output information of the resource transfer terminal by means of near field communication. When the output information includes the resource transfer order generated by the resource transfer terminal, the first resource management client sends the resource transfer order generated by the resource transfer terminal to the resource management platform through the network, so as to complete resource transfer corresponding to the resource transfer order through the resource management platform. Finally, the first resource management client receives the completion state of the resource transfer order sent by the resource management platform through the network. The problem of limited use scenario of the resource transfer method is solved. By using the resource transfer method disclosed by the present embodiment, the resource transfer terminal of the target merchant can complete resource transfer without being connected to the network, so that the user can initiate a resource transfer operation at any time in any place, and great convenience is provided for the resource transfer of the user. At the same time, the resource transfer terminal may only include the near field communication module, so that the equipment cost of the target merchant is reduced, and the popularization of a resource transfer system is better facilitated.

Optionally, the resource transfer order generated by the resource transfer terminal is an encrypted resource transfer order generated according to the user signature of the current login user of the first resource management client, the merchant signature of the target merchant and a preset key. The user signature is generated according to the user identifier carried in the instruction of acquiring the target merchant authentication information stored

in the resource transfer terminal.

During specific implementation, a root key issued by the built-in resource management platform of the resource transfer terminal is configured to manage the resource transfer terminal by the resource management platform. At the same time, the resource management
5 platform further issues a data transmission key or a trading key to the resource transfer terminal according to application of the second resource management client, and the data transmission key or the trading key is sent by the second resource management client to the resource transfer terminal to be stored. When the resource transfer terminal sends the resource transfer order to the first resource management client, preferably, transmission and
10 storage are performed after the order is encrypted through the preset trading key or the data transmission key, so as to improve the security of resource transfer.

The key is stored in the resource transfer terminal of the target merchant, and may be updated at any time. Additionally, the resource transfer terminal, the first resource management client and the second resource management client do not have permission to
15 resolve the key, and only the resource management platform controls the generation of the key and resolves the key, so that the security of resource transfer can be further improved.

Optionally, in one modification of the present embodiment, as shown in Figure 4, after the first resource management client sends the instruction of acquiring the target merchant authentication information stored in the resource transfer terminal to the resource transfer
20 terminal by means of near field communication, the first resource management client receives output information of the resource transfer terminal by means of near field communication.

During specific implementation, the output information of the resource transfer terminal includes various conditions. According to different conditions, the first resource management client performs different operations.

25 Step 340, when the output information includes a blacklist setting instruction, the first resource management client locally sets the current login user into a blacklist user, so as to execute a blacklist prompt when the current login user initiates the resource transfer operation.

During specific implementation, after successful acceptance of the offline resource

transfer order, the second resource management client may read the resource transfer order in the resource transfer terminal after a period of time, and then settles accounts with the resource management platform to finally complete resource transfer. A condition that the resource quantity in the account of the resource transfer-out user is smaller than the quantity of to-be-transferred resources in the order may occur, so that the resource management platform cannot successfully complete the settlement between the transfer-out user and the target merchant. By aiming at this condition, the resource transfer method of the disclosure sets the user blacklist. When the number of times of settlement incapable of being successfully completed by the resource management platform on one transfer-out user exceeds a preset quantity, the transfer-out user is added into the user blacklist to be issued to each first resource management client or resource transfer terminal, and the first resource management client or the resource transfer terminal is notified to refuse to perform resource transfer with the blacklist user, so as to reduce resource loss of the target merchant and the resource management platform.

However, with the gradual increase of the blacklist users, the user blacklist may occupy a great storage space of the resource transfer terminal. In order to improve the utilization efficiency of resources stored in the resource transfer terminal, when the user reads the resource transfer terminal through the first resource management client, the resource transfer terminal determines whether the user identifier of the user is a user in the user blacklist or not according to the locally stored user blacklist. If it is determined that the user identifier is a user in the user blacklist, the blacklist setting instruction is sent by means of near field communication to notify the first resource management client to locally set the user into the blacklist user in the first resource management client. Then, the resource transfer terminal removes the user from the locally stored user blacklist in the resource transfer terminal, so as to save the storage space of the resource transfer terminal.

When the first resource management client detects that the user initiates the resource transfer flow process, the first resource management client acquires the user identifier of the current login user, and matches the user identifier with the user identifier of the preset blacklist user. If the matching is successful, it is confirmed that the current login user is the

blacklist user. Then, the first resource management client executes the blacklist prompt. For example, the user is prompted for the existence of resources not successfully transferred, or the user is prompted to be blacklisted, and the user is prompted to be in contact with the blacklist through the resource management platform.

- 5 Optionally, during specific implementation, after the first resource management client receives the output information of the resource transfer terminal by means of near field communication, the method further includes:

Step 350, when the output information includes the target merchant authentication information, the first resource management client generates the resource transfer order
10 according to the target merchant authentication information.

When the output information of the resource transfer terminal received by the first resource management client includes the target merchant authentication information, the first resource management client authenticates the authentication information, for example, information carried in the authentication information, such as a target merchant icon, is
15 shown for the current login user to confirm. The target merchant authentication information further includes a target merchant identifier. Then, the first resource management client generates the resource transfer order according to the resource transfer quantity input by the user and an operation of confirming generation of the resource transfer order. The resource transfer order includes information such as a user tag of the current login user of the first
20 resource management client, a merchant tag of the target merchant, and the resource transfer quantity. The merchant tag of the target merchant is generated according to the merchant identifier of the target merchant included in the output information.

Step 360, the first resource management client sends the resource transfer order to the resource management platform through the network, so as to complete resource transfer
25 corresponding to the resource transfer order through the resource management platform, and sends the completion state of the resource transfer order to the second resource management client of the resource transfer target merchant through the resource management platform.

In an online state, the first resource management client sends the resource transfer order

to the resource management platform through the network. After receiving the resource transfer order, the resource management platform resolves and processes the order, extracts the resource transfer-out user, the target merchant and the resource transfer quantity in the order, then transfers a corresponding quantity of resources from the account of the resource transfer-out user to the account of the target merchant, and stores resource transfer information. After resource transfer is completed, the resource management platform sends the completion state of the resource transfer order to the second resource management client of the resource transfer target merchant.

Embodiment 3

The present embodiment discloses a resource transfer method based on near field communication. As shown in Figure 5, the method includes: step 500 to step 510.

Step 500, a resource transfer order stored in a resource transfer terminal is acquired by means of near field communication. The resource transfer order is a resource transfer order generated when a first resource management client transfers resources to a target merchant in an offline scenario.

A second resource management client is an application client of the target merchant of the resource management platform. During specific application, the second resource management client is application software installed in equipment with a near field communication module, such as a mobile phone of a target merchant, and may also be other equipment of the target merchant with a near field communication module. In the present embodiment, the second resource management client is supposed to be the application software installed in the equipment with the near field communication module, such as the mobile phone of the target merchant.

After a current login user of the first resource management client performs offline resource transfer with the target merchant by means of near field communication, an offline resource transfer order will be stored in the resource transfer terminal. During specific implementation, the second resource management client may read the resource transfer order stored in the resource transfer terminal in real time or in regular time or according to the

triggering of the resource management platform.

During specific implementation, the second resource management client acquires the resource transfer order stored in the resource transfer terminal by means of near field communication. The second resource management client transmits a signal of reading the resource transfer order to the resource transfer terminal by means of near field communication. The resource transfer terminal starts to work under the effect of an induced voltage generated in response to a near field communication signal, and outputs the locally stored resource transfer order.

Step 510, the resource transfer order is sent to the resource management platform through the network, so as to complete resource transfer corresponding to the resource transfer order.

After the second resource management client reads the resource transfer order stored in the resource transfer terminal by means of near field communication, the resource transfer order is uploaded to the resource management platform through the network, and the resource management platform resolves and processes the order, and further completes resource transfer corresponding to each resource transfer order. Finally, the second resource management client receives a completion state of the resource transfer order fed back by the resource management platform.

According to the resource transfer method based on near field communication disclosed by the present embodiment, the offline resource transfer order stored in the resource transfer terminal is acquired by means of near field communication. Then, the resource transfer order is sent to the resource management platform through the network, so as to complete resource transfer corresponding to the resource transfer order. The problem of limited use scenario of the resource transfer method is solved. According to the resource transfer method based on near field communication disclosed by the present embodiment, when the user is not connected to the network, the resource transfer order is determined by means of near field communication, and the offline resource transfer order is stored in the resource transfer terminal. Then, the second resource management client uploads the offline resource transfer order to the resource management platform to complete resource transfer, so that the user can

complete resource transfer without being connected to the network. The use scenarios of the resource transfer method are increased, convenience is provided for resource transfer, and the popularization and application of the resource transfer method based on near field communication are facilitated.

- 5 Optionally, as shown in Figure 6, in one modification of the embodiment, before the resource transfer order stored in the resource transfer terminal is acquired by means of near field communication, the method further includes:

Step 520, merchant registration is performed on the resource management platform through the network, so as to acquire target merchant authentication information.

- 10 Firstly, the target merchant (i.e., a merchant receiving a transfer-in resource) is registered on the resource management platform through the second resource management client, and acquires a merchant identifier of the target merchant and the target merchant authentication information.

- 15 Step 530, a key issued by the resource management platform is received. The key includes a trading key or a transmission key.

- During specific implementation, the resource management platform may further issue the key to the registered target merchant to perform encrypted storage and/or encrypted transmission of the resource transfer order. During specific implementation, the resource management platform may issue the key to the successfully registered target merchant, and
20 may further issue the key in real time according to application of the target merchant.

Step 540, the target merchant authentication information and the key are sent to the resource transfer terminal to be stored by means of near field communication.

- After receiving the authentication information and the key issued by the resource management platform, the second resource management client transmits a near field
25 communication signal of write-in data to the resource transfer terminal. The resource transfer terminal starts to work under the triggering of an induced voltage generated in response to the near field communication signal, and stores the target merchant authentication information and the key according to a write-in instruction of the second resource

management client.

Optionally, the resource transfer order is an encrypted order subjected to encryption processing through a preset key in the resource transfer terminal.

When the current login user of the first resource management client performs offline
5 resource transfer to the resource transfer terminal by means of near field communication, the resource transfer terminal generates the resource transfer order and performs encryption processing on the resource transfer order through the prestored key, and then locally stores the encrypted order. During specific implementation, when the second resource management client reads the resource transfer order, the resource transfer terminal may further encrypt the
10 resource transfer order through the transmission key, so as to improve security of resource transfer.

Optionally, in another modification of the embodiment, after the target merchant authentication information and the key are sent to the resource transfer terminal to be stored by means of near field communication, the method further includes: a resource transfer
15 function is enabled on the resource management platform through the network, so that the resource management platform completes resource transfer corresponding to the resource transfer order according to the resource transfer order sent by the first resource management client and the resource transfer order sent by the second resource management client. During specific implementation, the second resource management client makes an application to the
20 resource management platform to enable a resource transfer function of the resource management client through the network. Then, the resource management platform may generate a unique trading key and/or a payment key for the target merchant according to the merchant identifier of the target merchant sent by the second resource management client, and feeds the trading key and/or the payment key to the second resource management client
25 through the network. The second resource management client sends the key to the resource transfer terminal by means of near field communication. The key is transmitted through the second resource management client, and is configured to encrypt data indirectly transmitted between the resource transfer terminal and the resource management platform. The transmission security of the resource transfer order can be further improved.

Embodiment 4

The present embodiment discloses a resource transfer device based on near field communication. As shown in Figure 7, the device includes:

5 a communication establishing module 700, configured to acquire a user identifier of a current login user in a first resource management client according to the triggering of the first resource management client, and output target merchant authentication information;

10 a resource transfer order generating module 710, configured to generate a resource transfer order according to a preset quantity of resources transferred by each order when it is determined that a resource transfer terminal has enabled a fixed quantity resource transfer mode;

a resource transfer order storage module 720, configured to add a merchant signature of a target merchant and a user signature generated according to the acquired user identifier to the resource transfer order, and store the resource transfer order with the signatures; and

15 an order state output module 730, configured to send an acceptance state of the resource transfer order to the first resource management client by means of near field communication.

The fixed quantity resource transfer mode and the quantity of resources transferred by each order are set according to data sent by a second resource management client.

Optionally, as shown in Figure 8, the device further includes:

20 a resource transfer module 740, configured to output the stored resource transfer order according to the triggering of the second resource management client, so that the second resource management client completes resource transfer corresponding to the resource transfer order through a resource management platform.

25 By taking code scanning payment as an example, a user needs to be connected to a network to perform code scanning payment, so that the application scenario is limited. By using a resource transfer method based on near field communication disclosed by the embodiments of the disclosure, offline resource transfer can be realized by using the resource transfer terminal as a medium. The problem that resource transfer can only be completed

under the network connected condition by a resource transfer-out user and a resource transfer-in user is solved, convenience is provided for the resource transfer of the users, and the application scenarios of resource transfer are expanded. Additionally, the resource transfer terminal is used as the medium, resource transfer is performed by means of near field communication, and the security is higher.

Optionally, as shown in Figure 8, the device further includes:

a resource transfer order receiving module 750, configured to receive the resource transfer order sent by the first resource management client by means of near field communication;

the resource transfer order storage module 720, configured to add the target merchant signature and the user signature generated according to the user identifier to the received resource transfer order sent by the first resource management client by means of near field communication, and store the resource transfer order with the signatures; and

the order state output module 730, configured to send the acceptance state of the resource transfer order to the first resource management client by means of near field communication after the resource transfer order storage module 720 locally stores the resource transfer order with the signatures.

Optionally, as shown in Figure 8, the device further includes:

a blacklist receiving module 760, configured to receive and store a user blacklist sent by the second resource management client by means of near field communication; and

a blacklist management module 770, configured to send a blacklist setting instruction of setting a user into a blacklist user to the first resource management client by means of near field communication when it is determined that the user identifier corresponds to a user in the blacklist based on the user blacklist, and remove the user from the user blacklist.

According to the present embodiment, the blacklist of the first resource management client is set through the resource transfer terminal. The problem that the blacklist user cannot issue the user blacklist to the first resource management client without being connected to the network is solved, so that a resource transfer risk is avoided, and the resource loss of the

target merchant and the resource management platform is reduced. For example, after the user is connected to the network to log in the resource management platform, the network is disconnected, the multi-time offline resource transfer is performed through the resource transfer terminal, but the resource management platform cannot successfully complete resource transfer due to resource insufficiency in the account, and the target merchant may suffer greater loss if the user is not added to the user blacklist in time to be issued to the resource transfer terminal. By issuing the user blacklist to the resource transfer terminal by means of near field communication through the second resource management client, the blacklist user can be discovered under the condition that the user is not connected to the network, and the security of resource transfer is improved.

However, with the gradual increase of the blacklist users, the user blacklist may occupy a great storage space of the resource transfer terminal. In order to improve the utilization efficiency of resources stored in the resource transfer terminal, when the user reads the resource transfer terminal through the first resource management client, the resource transfer terminal determines whether the user identifier of the user is a user in the user blacklist or not according to the locally stored user blacklist. If it is determined that the user identifier is a user in the user blacklist, the blacklist setting instruction is sent by means of near field communication to notify the first resource management client to locally set the user into the blacklist user in the first resource management client. Then, the resource transfer terminal removes the user from the locally stored user blacklist in the resource transfer terminal, so as to save the storage space of the resource transfer terminal.

Optionally, as shown in Figure 8, the device further includes an order encryption module 780, configured to perform encryption processing on the resource transfer order with the user signature through a preset key.

During specific implementation, a root key issued by the built-in resource management platform of the resource transfer terminal is configured to manage the resource transfer terminal by the resource management platform. At the same time, the resource management platform further issues a data transmission key or a trading key to the resource transfer terminal according to application of the second resource management client, and the data

transmission key or the trading key is sent by the second resource management client to the resource transfer terminal to be stored. When the resource transfer terminal sends the resource transfer order to the first resource management client, or locally stores the resource transfer order, preferably, transmission and storage are performed after the order is encrypted
5 through the preset trading key or the data transmission key, so as to improve the security of resource transfer.

The key is stored in the resource transfer terminal of the target merchant, and may be updated at any time. Additionally, the resource transfer terminal, the first resource management client and the second resource management client do not have permission to
10 resolve the key, and only the resource management platform controls the generation of the key and resolves the key, so that the security of resource transfer can be further improved.

For specific implementations of each module, reference is made to Embodiment 1, and the descriptions thereof are omitted herein.

According to the resource transfer device based on near field communication disclosed
15 by the embodiment of the disclosure, the user identifier of the current login user in the first resource management client is acquired according to the triggering of the first resource management client, and the target merchant authentication information is output. Then, the resource transfer order sent by the first resource management client by means of near field communication is received. The user signature and the merchant signature are added to the
20 resource transfer order, and then the resource transfer order with the signatures is stored. The problems of limited use scenario and high cost of the resource transfer method are solved. According to the resource transfer device based on near field communication disclosed by the embodiment of the disclosure, resource transfer can be completed by means of near field communication under the condition that a near field communication terminal of the user is
25 not connected to the network. At the same time, the resource transfer terminal does not need to be connected to the network, and the use scenario is not limited. Additionally, a host of the first resource management client in the disclosure may be a mobile phone with a near field communication function. The resource transfer terminal only needs to include a field communication module, for example, may be an electronic card with the near field

communication module. The cost is very low. Wide application is facilitated. The near field communication module can realize self power supply after sensing a radio frequency signal, additionally, a certain storage space exists in the near field communication module, and a control program may be developed on an embedded secure element included in the near field communication module. Therefore, the resource transfer terminal can complete reception and storage of the resource transfer order and complete offline resource transfer.

Embodiment 5

The present embodiment discloses a resource transfer device based on near field communication. As shown in Figure 9, the device includes:

10 a handshaking module 900, configured to send an instruction of acquiring target merchant authentication information stored in a resource transfer terminal by means of near field communication;

a feedback information receiving module 910, configured to receive output information of the resource transfer terminal by means of near field communication; and

15 an online resource transfer module 920, configured to send a resource transfer order to a resource management platform through a network when the output information includes the resource transfer order generated by the resource transfer terminal, so as to complete resource transfer corresponding to the resource transfer order through the resource management platform, and send a completion state of the resource transfer order to a resource transfer target merchant through the resource management platform.

According to the resource transfer device based on near field communication disclosed by the present embodiment, the instruction of acquiring the target merchant authentication information stored in the resource transfer terminal is sent by means of near field communication, and the output information of the resource transfer terminal is received by means of near field communication. When the output information includes the resource transfer order generated by the resource transfer terminal, a first resource management client sends the resource transfer order generated by the resource transfer terminal to the resource management platform through the network, so as to complete resource transfer corresponding

to the resource transfer order through the resource management platform. Finally, the first resource management client receives the completion state of the resource transfer order sent by the resource management platform through the network. The problem of limited use scenario of the resource transfer device is solved. By using the resource transfer device disclosed by the present embodiment, the resource transfer terminal of the target merchant can complete the resource transfer without being connected to the network, so that the user can initiate a resource transfer operation at any time in any place, and great convenience is provided for resource transfer. At the same time, the resource transfer terminal only needs to include a near field communication module, so that the equipment cost of the target merchant is reduced, and the popularization of a resource transfer system is better facilitated.

Optionally, the resource transfer order generated by the resource transfer terminal is an encrypted resource transfer order generated according to a user signature of a current login user of the first resource management client, a merchant signature of the target merchant and a preset key. The user signature is generated according to a user identifier carried in the instruction of acquiring the target merchant authentication information stored in the resource transfer terminal.

During specific implementation, a root key issued by the built-in resource management platform of the resource transfer terminal is configured to manage the resource transfer terminal by the resource management platform. At the same time, the resource management platform further issues a data transmission key or a trading key to the resource transfer terminal according to application of a second resource management client, and the data transmission key or the trading key is sent by the second resource management client to the resource transfer terminal to be stored. When the resource transfer terminal sends the resource transfer order to the first resource management client, preferably, transmission and storage are performed after the order is encrypted through the preset trading key or the data transmission key, so as to improve the security of resource transfer.

The key is stored in the resource transfer terminal of the target merchant, and may be updated at any time. Additionally, the resource transfer terminal, the first resource management client and the second resource management client do not have permission to

resolve the key, and only the resource management platform controls the generation of the key and resolves the key, so that the security of resource transfer can be further improved.

Optionally, as shown in Figure 10, the device further includes: a blacklist establishing module 930, configured to locally set the current login user into a blacklist user in the first
5 resource management client when the output information includes a blacklist setting instruction, so as to execute a blacklist prompt when the current login user initiates the resource transfer operation.

During specific implementation, after successful acceptance of the offline resource transfer order, the second resource management client may read the resource transfer order
10 in the resource transfer terminal after a period of time, and then settles accounts with the resource management platform to finally complete resource transfer. A condition that the resource quantity in the account of the resource transfer-out user is smaller than the quantity of to-be-transferred resources in the order may occur, so that the resource management platform cannot successfully complete the settlement between the transfer-out user and the
15 target merchant. By aiming at this condition, the resource transfer method of the disclosure sets the user blacklist. When the number of times of settlement incapable of being successfully completed by the resource management platform on one transfer-out user exceeds a preset quantity, the transfer-out user is added into the user blacklist to be issued to each first resource management client or resource transfer terminal, and the first resource
20 management client or the resource transfer terminal is notified to refuse to perform resource transfer with the blacklist user, so as to reduce resource loss of the target merchant and the resource management platform.

However, with the gradual increase of the blacklist users, the user blacklist may occupy a great storage space of the resource transfer terminal. In order to improve the utilization
25 efficiency of resources stored in the resource transfer terminal, when the user reads the resource transfer terminal through the first resource management client, the resource transfer terminal determines whether the user identifier of the user is a user in the user blacklist or not according to the locally stored user blacklist. If it is determined that the user identifier is a user in the user blacklist, the blacklist setting instruction is sent by means of near field

communication to notify the first resource management client to locally set the user into the blacklist user in the first resource management client. Then, the resource transfer terminal removes the user from the locally stored user blacklist in the resource transfer terminal, so as to save the storage space of the resource transfer terminal.

- 5 When the first resource management client detects that the user initiates a resource transfer flow process, the first resource management client acquires the user identifier of the current login user, and matches the user identifier with the user identifier of the preset blacklist user. If the matching is successful, it is confirmed that the current login user is the blacklist user. Then, the first resource management client executes the blacklist prompt. For
10 example, the user is prompted for the existence of resources not successfully transferred, or the user is prompted to be blacklisted, and the user is prompted to be in contact with the blacklist through the resource management platform.

- Optionally, during specific implementation, after the first resource management client receives the output information of the resource transfer terminal by means of near field
15 communication, the method further includes: when the output information includes the target merchant authentication information, the first resource management client generates the resource transfer order according to the target merchant authentication information.

- When the output information of the resource transfer terminal received by the first resource management client includes the target merchant authentication information, the first
20 resource management client authenticates the authentication information, for example, information carried in the authentication information, such as a target merchant icon, is shown for the current login user to confirm. The target merchant authentication information further includes a target merchant identifier. Then, the first resource management client generates the resource transfer order according to the resource transfer quantity input by the
25 user and an operation of confirming generation of the resource transfer order. The resource transfer order includes information such as a user tag of the current login user of the first resource management client, a merchant tag of the target merchant, and the resource transfer quantity. The merchant tag of the target merchant is generated according to the merchant identifier of the target merchant included in the output information.

The first resource management client sends the resource transfer order to the resource management platform through the network, so as to complete resource transfer corresponding to the resource transfer order through the resource management platform, and sends the completion state of the resource transfer order to the second resource management client of the resource transfer target merchant through the resource management platform.

In an online state, the first resource management client sends the resource transfer order to the resource management platform through the network. After receiving the resource transfer order, the resource management platform resolves and processes the order, extracts the resource transfer-out user, the target merchant and the resource transfer quantity in the order, then transfers a corresponding quantity of resources from the account of the resource transfer-out user to the account of the target merchant, and stores resource transfer information. After resource transfer is completed, the resource management platform sends the completion state of the resource transfer order to the second resource management client of the resource transfer target merchant.

Embodiment 6

The present embodiment discloses a resource transfer device based on near field communication. As shown in Figure 11, the device includes:

a resource transfer order exporting module 1100, configured to acquire a resource transfer order stored in a resource transfer terminal by means of near field communication, where the resource transfer order is a resource transfer order generated when a first resource management client transfer resources to a target merchant in an offline scenario; and

a resource transfer module 1110, configured to send the resource transfer order to a resource management platform through a network, so as to complete resource transfer corresponding to the resource transfer order.

Optionally, as shown in Figure 12, the device further includes:

a registration module 1120, configured to perform user registration on the resource management platform through the network, so as to acquire target merchant authentication information;

a key receiving module 1130, configured to receive a key issued by the resource management platform, where the key includes a trading key or a transmission key; and

5 a key issuing module 1140, configured to send the target merchant authentication information and the key to the resource transfer terminal to be stored by means of near field communication.

Optionally, the resource transfer order is an encrypted order subjected to encryption processing through a preset key in the resource transfer terminal.

When a current login user of the first resource management client performs offline resource transfer to the resource transfer terminal by means of near field communication, the
10 resource transfer terminal generates the resource transfer order and performs encryption processing on the resource transfer order through the prestored key, and then locally stores the encrypted order. During specific implementation, when a second resource management client reads the resource transfer order, the resource transfer terminal may further encrypt the resource transfer order through the transmission key, so as to improve security of resource
15 transfer.

Optionally, in another modification of the embodiment, the registration module 1120 is further configured to enable a resource transfer function on the resource management platform through a network, so that the resource management platform completes resource transfer corresponding to the resource transfer order according to the resource transfer order
20 sent by the first resource management client or the resource transfer order sent by the second resource management client.

During specific implementation, the second resource management client makes an application to the resource management platform to enable a resource transfer function of the resource management client through the network. Then, the resource management platform
25 may generate a unique trading key and/or a payment key for the target merchant according to a merchant identifier of the target merchant sent by the second resource management client, and feeds the trading key and/or the payment key to the second resource management client through the network. The second resource management client sends the key to the resource

transfer terminal by means of the near field communication. The key is transmitted through the second resource management client, and is configured to encrypt data indirectly transmitted between the resource transfer terminal and the resource management platform. The transmission security of the resource transfer order can be further improved.

5 According to the resource transfer device based on near field communication disclosed by the present embodiment, the offline resource transfer order stored in the resource transfer terminal is acquired by means of near field communication. Then, the resource transfer order is sent to the resource management platform through the network, so as to complete resource transfer corresponding to the resource transfer order. The problem of limited use scenario of
10 the resource transfer method is solved. According to the resource transfer device based on near field communication disclosed by the disclosure, when the user is not connected to the network, the resource transfer order is determined by means of near field communication, and the offline resource transfer order is stored in the resource transfer terminal. Then, the second resource management client uploads the offline resource transfer order to the resource
15 management platform to complete resource transfer, so that the user can complete resource transfer without being connected to the network. The wideness of use scenarios of the resource transfer method is improved, convenience is provided for resource transfer, and the popularization and application of the resource transfer method based on near field communication are facilitated.

20 Embodiment 7

The present embodiment discloses a resource transfer system based on near field communication. As shown in Figure 13, the resource transfer system includes: a resource management platform 1300, a resource transfer terminal 1310, and a first resource management client 1320 and a second resource management client 1330 respectively
25 communicated with the resource management platform through a network.

The resource management platform 1300 is configured to manage the resource transfer terminal 1310 and complete resource transfer of a resource transfer order.

The resource transfer terminal 1310 is configured to perform the resource transfer

method based on near field communication according to Embodiment 1.

The first resource management client 1320 is configured to perform the resource transfer method based on near field communication according to Embodiment 2.

5 The second resource management client 1330 is configured to perform the resource transfer method based on near field communication according to Embodiment 3.

The resource transfer terminal 1310 is pre-authenticated and issued by the resource management platform 1300. The first resource management client 1320 and the second resource management client 1330 may be hardware equipment with a near field communication module pre-authenticated and issued by the resource management platform
10 1300, and may also be an application program installed in hardware equipment with a near field communication module.

An offline resource transfer flow process of the resource transfer system based on near field communication disclosed by the embodiment of the disclosure is illustrated by examples in conjunction with Figure 14.

15 Step 1400, a target merchant is registered to the resource management platform through the second resource management client, and applies for the resource transfer terminal.

During specific implementation, the target merchant may be a merchant. After the second resource management client of the target merchant completes registration on the resource management platform, the resource management platform will issue the resource transfer terminal to the successfully registered second resource management client. The
20 resource transfer terminal may be preset with a verification key configured to manage the resource transfer terminal by the resource management platform, or configured to perform equipment verification on the resource transfer terminal by the first resource management client and the second resource management client.

25 During specific implementation, when the second resource management client registers on the resource management platform, self-related merchant information needs to be uploaded, such as a merchant name, resource receiving account information or an icon. The resource management platform generates a key according to the merchant information

uploaded by the second resource management client. The key includes a trading key and/or a transmission key, and is sent to the second resource management client, and the second resource management client sends the key generated by the resource management platform to the resource transfer terminal to be stored.

- 5 Step 1401, the second resource management client makes an application to the resource management platform to enable resource transfer through the resource transfer terminal.

 The second resource management client sends a request of applying to the resource management client to enable resource transfer through the network, and at the same time, the second resource management client may further apply to enable online resource transfer and
10 offline resource transfer.

 Step 1402, the second resource management client sends the key and/or a resource transfer mode to the resource transfer terminal by means of near field communication.

 During specific implementation, the second resource management client sends resource transfer-related information issued by the resource transfer platform to the resource transfer
15 terminal to be stored by means of near field communication. The resource transfer-related information includes, but is not limited to, any one of the following: the key, the quantity transferred by each order, and the resource transfer mode.

 Step 1403, the first resource management client sends an instruction of acquiring target merchant authentication information stored in the resource transfer terminal by means of near
20 field communication.

 During specific implementation, the first resource management client may be client software installed in a mobile phone of the user with the near field communication module. When performing resource transfer by reading the resource transfer terminal, the first resource management client needs to firstly register on the resource management platform,
25 and acquires a unique user identifier sent by the resource management platform to the first resource management client.

 Then, the first resource management client sends the instruction of acquiring the target merchant authentication information stored in the resource transfer terminal by means of near

field communication. During specific implementation, the instruction of acquiring the target merchant authentication information stored in the resource transfer terminal includes a user identifier. Optionally, the instruction of acquiring the target merchant authentication information stored in the resource transfer terminal may further include information about whether the first resource management client is online or not.

Step 1404, the resource transfer terminal of the target merchant acquires the user identifier of a current login user in the first resource management client according to the triggering of the first resource management client.

Step 1405, the resource transfer terminal judges whether to enable a fixed quantity resource transfer mode or not. If YES, step 1406 is performed. Otherwise, step 1407 is performed.

Step 1406, when it is determined that the resource transfer terminal has enabled the fixed quantity resource transfer mode, the resource transfer terminal generates the resource transfer order according to the preset quantity of resources transferred by each order.

When it is determined that the resource transfer terminal has enabled the fixed quantity resource transfer mode, the resource transfer terminal generates the resource transfer order according to the preset quantity of resources transferred by each order. Then, the flow jumps to step 1410, a merchant signature of the target merchant and a user signature generated according to the user identifier are added to the generated resource transfer order, and the resource transfer order is locally stored in the resource transfer terminal.

Step 1407, the resource transfer terminal outputs the target merchant authentication information.

Step 1408, the first resource management client generates the resource transfer order according to a user operation, and sends the resource transfer order by means of near field communication.

Step 1409, the resource transfer terminal receives the resource transfer order sent by the first resource management client by means of near field communication.

Step 1410, the resource transfer terminal adds the merchant signature of the target

merchant and the user signature generated according to the user identifier to the resource transfer order, and stores the resource transfer order with the signatures.

Step 1411, the resource transfer terminal sends an acceptance state of the resource transfer order to the first resource management client by means of near field communication.

5 Hereto, the user completes offline resource transfer once with the target merchant through a terminal with a built-in near field communication module.

Step 1412, the second resource management client acquires the resource transfer order stored in the resource transfer terminal by means of near field communication, and the resource transfer order is a resource transfer order generated when the first resource
10 management client transfers resources to the target merchant in an offline scenario.

Step 1413, the second resource management client sends the resource transfer order to the resource management platform through the network.

Step 1414, the resource management platform resolves the resource transfer order, and completes resource transfer corresponding to the resource transfer order.

15 The resource management platform decrypts the received resource transfer order according to the key applied by the second resource management client, resolves the resource transfer order, determines a resource transfer-out user, the target merchant and a resource transfer quantity, and finally transfers the resources of the resource transfer quantity from the account of the resource transfer-out user to the account of the target merchant.

20 During specific implementation, the resource transfer system based on near field communication disclosed by the embodiment of the disclosure may further realize online transfer of resources. For example, after the step that the resource transfer terminal of the target merchant acquires the user identifier of the current login user in the first resource management client according to the triggering of the first resource management client, if the
25 resource transfer terminal judges that the first resource management client is online, and the resource transfer terminal enables the fixed quantity resource transfer mode, the resource transfer terminal generates encrypted order information and outputs the encrypted order information to the first resource management client,. The encrypted order information is

transmitted to the resource management platform by the first resource management client, so as to complete a fixed quantity of resource transfer. If the resource transfer terminal judges that the first resource management client is online, and the resource transfer terminal does not enable the fixed quantity resource transfer mode, the resource transfer terminal outputs
5 the target merchant authentication information and the target merchant identifier to the first resource management client, and the resource transfer order is generated by the first resource management client according to input of the user, and is sent to the resource management platform, so as to complete the specified quantity of resource transfer.

During specific implementation of the disclosure, when the first resource management
10 client reads the target merchant authentication information stored in the resource transfer terminal, the offline or online state information of the first resource management client can be simultaneously sent to the resource transfer terminal, so that the resource transfer terminal determines output data aiming at the first resource management client.

Correspondingly, the disclosure further discloses electronic equipment, including a
15 storage medium, a processor and a machine executable instruction stored in the storage medium and capable of running on the processor. When the processor executes the machine executable instruction, the resource transfer method based on near field communication according to Embodiment 1 to Embodiment 3 of the disclosure is implemented. The electronic equipment may be a PC machine, a mobile terminal, a personal digital assistant, a
20 tablet computer and the like.

The disclosure further discloses a computer readable storage medium. A computer program is stored thereon. When the program is executed by the processor, steps of the resource transfer method based on near field communication according to Embodiment 1 to Embodiment 3 of the disclosure are implemented.

25 Embodiment 8

In the above description aiming at Embodiment 1 to Embodiment 7, the offline resource transfer order can be stored in the resource transfer terminal. Besides information such as the user signature of the resource transfer-out user, the merchant signature of the resource

transfer-in target merchant, the order time and the order content, the offline resource transfer order may further include a geographic position of a user requesting for resource transfer. In the present embodiment, a method of managing the position information of the target merchant by using the geographic position information in the resource transfer order is
5 described in the present embodiment.

The present embodiment discloses a target merchant position information management method. As shown in Figure 15, the method includes step 1510 to step 1520.

Step 1510, at least one resource transfer order stored in a resource transfer terminal of a target merchant is acquired through a second resource management client of the target
10 merchant.

During specific implementation, the second resource management client of the target merchant is a trading management client of the merchant. A resource management platform sends settlement notification to the second resource management client of the target merchant or acquires an instruction of acquiring offline geographic position information of the
15 merchant resource transfer terminal through a network, so as to acquire an offline resource transfer order of the target merchant. During specific implementation, the target merchant may actively read the offline resource transfer order in the resource transfer terminal through the second resource management client, and uploads the offline resource transfer order to the resource management platform through a network.

20 The offline resource transfer order stored in the resource transfer terminal is generated by the resource transfer terminal according to a resource transfer request sent by a user by means of near field communication or Bluetooth communication, or is received by means of near field communication or Bluetooth communication and generated by a first resource management client.

25 Step 1520, the position information of the target merchant is managed according to information included in the resource transfer order.

The offline resource transfer order includes information such as the user signature of the resource transfer-out user, the merchant signature of the resource transfer-in target merchant,

the order time and the order content. The offline resource transfer order further includes the geographic position of the user requesting for resource transfer.

After acquiring the resource transfer order stored in the resource transfer terminal, the resource management platform acquires the transfer-out user and the target merchant of each resource transfer order, and the geographic position by resolving the resource transfer order. Then, the resource management platform uses the geographic position in each resource transfer order as the offline geographic position of the target merchant of the corresponding source transfer order. During specific implementation, the resource transfer order further includes the time of generating the resource transfer order, i.e., the time of the target merchant in the offline geographic position. The resource management platform manages the geographic position information of the target merchant according to each offline geographic position of the target merchant and the time in the offline geographic position. For example, a conventional moving route of the target merchant is determined, the permanent geographic position of the merchant is determined, the current position of an offline target merchant is estimated, and the like.

The target merchant position information management method disclosed by the present embodiment solves the problem that position information of an offline user cannot be managed by managing the position information of the target merchant according to the information included in the resource transfer order by the second resource management client of the target merchant after the resource transfer order stored in the resource transfer terminal of the target merchant is acquired. The geographic position information management on the offline target merchant is realized, and the accuracy of the geographic position information management on the target merchant is greatly improved by acquiring geographic position information of the user during offline trading between the user and the target merchant, storing the geographic position information into the resource transfer order, and then, further using the geographic position information in the resource transfer order as the offline geographic position of the target merchant.

Embodiment 9

The embodiment of the disclosure discloses a target merchant position information

management system. As shown in Figure 16, the system includes:

a resource transfer terminal 1622 with a built-in near field communication module or Bluetooth module;

5 a first resource management client 1620 and a second resource management client 1621, respectively performing data transmission with the resource transfer terminal 1622 by means of near field communication or Bluetooth communication; and

10 a resource management platform 1623, performing data transmission with the first resource management client 1620 or the second resource management client 1621 through a network and including a storage medium, a processor and a machine executable instruction stored in the storage medium and capable of running on the processor, where when the processor executes the machine executable instruction, the target merchant position information management method according to the embodiment of the disclosure is implemented.

15 The target user geographic position information management method disclosed by the embodiment of the disclosure is applied to the resource transfer system as shown in Figure 16. The resource transfer system includes: a first resource management client 1620 of a user, a second resource management client 1621 of a target client, a resource transfer terminal 1622 of a target merchant and a resource management platform 1623. A near field communication module or a Bluetooth communication module is built in the resource transfer terminal 1622. In an offline resource transfer state, the resource transfer terminal 1622 performs data transmission with the first resource management client 1620 of the user by means of near field communication or Bluetooth communication. The resource transfer terminal 1622 and the second resource management client 1621 of the target merchant perform data transmission by means of near field communication or Bluetooth communication. The first resource management client 1620 and the resource management platform 1623 perform data transmission through the network. The near field communication module and the Bluetooth communication module have data transmission, data processing and storage functions. The first resource management client 1620 is client software installed in user equipment, and equipment provided with the first resource management client 1620

needs a built-in communication module matched with the resource transfer terminal 1622. The second resource management client 1621 of the target merchant is client software installed in target merchant equipment, and equipment provided with the second resource management client 1621 of the target merchant needs a built-in communication module
5 matched with the resource transfer terminal 1622.

During specific implementation, the resource transfer terminal is a terminal with a built-in near field communication module or Bluetooth communication module. Preferably, the resource transfer terminal is a card type movable device. The resource transfer terminal is provided with a built-in near field communication module, and can work in a passive mode.
10 The near field communication module includes an embedded secure element (eSE), a contactless frontend (CLF) chip (also called as NFC controller) and a near field communication (NFC) antenna. The embedded secure element includes a storage space, can run a preset program, and is configured to perform interaction with the first resource management client of the user to generate or store an offline resource transfer order. When
15 the Bluetooth communication is built in the resource transfer terminal, the resource transfer terminal needs a built-in power supply to supply electricity to the Bluetooth communication module. The Bluetooth communication module includes a Bluetooth chip and a microcontroller. The microcontroller includes a storage space, can run a preset program, and is configured to perform interaction with the first resource management client of the user to
20 generate or store the offline resource transfer order.

The present embodiment illustrates a specific implementation of the target merchant geographic position information management method in detail in conjunction with the specific application scenario of the target merchant geographic position information management method.

25 As shown in Figure 17, the method includes specific application processes: step 1700 to step 1740.

Step 1700, A merchant signature of the target merchant is sent to the resource transfer terminal of the target merchant through the second resource management client of the target merchant.

During specific implementation, the resource transfer terminal is a terminal issued by the resource management platform to the target merchant and configured to perform online or offline payment. When the target merchant applies to enable the resource transfer function of the resource transfer terminal through the second resource management client, the resource management platform generates the merchant signature of the target merchant according to registration information of the target merchant, such as a merchant name, and sends the merchant signature to the second resource management client of the target merchant through the network. Then, the second resource management client of the target merchant sends the merchant signature to the resource transfer terminal of the target merchant by means of near field communication or Bluetooth communication.

During specific implementation, the offline resource transfer order may be generated by the resource transfer terminal, and may also be generated by the first resource management client. The present embodiment illustrates an offline resource transfer order generation scheme by taking the resource transfer terminal generating the offline resource transfer order as an example. That is, the offline resource transfer order is generated and stored by the resource transfer terminal according to an offline resource transfer request received by means of near field communication or Bluetooth communication.

Step 1710, the first resource management client of the user sends the offline resource transfer request to the resource transfer terminal of the target merchant by means of near field communication or Bluetooth communication according to an operation of the user.

During specific implementation, when the user transfers resources to the target merchant, the user initiates an offline resource transfer flow process through the first resource management client. By taking the resource transfer terminal being a built-in near field communication module as an example, the first resource management client may be client software installed in equipment (such as an NFC mobile phone) with a built-in near field communication module. Then, the user operates the first resource management client, and sends the offline resource transfer request to the resource transfer terminal of the target merchant by means of near field communication. The offline resource transfer request includes information such as the user signature of the user, the current geographic position

of the user, the current time, and resource transfer content. The current geographic position may be a GPS position coordinate of the user.

Step 1720, the resource transfer terminal generates the offline resource transfer order according to the offline resource transfer request.

5 During specific implementation, the offline resource transfer order is generated and stored according to the merchant signature of the affiliated target merchant of the resource transfer terminal and the offline resource transfer request. The offline resource transfer request is sent by the user applying for resource transfer by means of near field communication or Bluetooth communication. The offline resource transfer request at least
10 includes the geographic position of the user when the user sends the offline resource transfer request. The resource transfer terminal generates the offline resource transfer order according to information included in the received offline resource transfer request, such as the user signature of the user, the current geographic position, the current time and the resource transfer content, and the locally prestored single-time resource transfer quantity, and the
15 target merchant signature. Then, the resource transfer terminal locally stores the generated offline resource transfer order, and sends successful acceptance information of the offline resource transfer order to the user by means of near field communication. Hereto, the user completes one offline resource transfer order by reading the resource transfer terminal of the target merchant.

20 Step 1730, the resource management platform acquires the offline resource transfer order stored in the resource transfer terminal of the target merchant through the second resource management client of the target merchant.

 The offline resource transfer order is read by the second resource management client of the target merchant from the resource transfer terminal of the target merchant by means of
25 near field communication or Bluetooth communication. During specific implementation, the resource management platform sends settlement notification or an instruction of acquiring the offline geographic position of the merchant resource transfer terminal to the second resource management client of the target merchant through the network, so as to acquire the offline resource transfer order of the target merchant. During specific implementation, the

target merchant may actively read the offline resource transfer order in the resource transfer terminal through the second resource management client, and uploads the offline resource transfer order to the resource management platform through the network.

5 During specific implementation, when both the resource transfer terminal and equipment of the merchant provided with the second resource management client are provided with built-in near field communication modules, the second resource management client of the merchant transmits the offline resource transfer order with the resource transfer terminal by means of near field communication. When both the resource transfer terminal and equipment of the merchant provided with the second resource management client are provided with
10 built-in Bluetooth communication modules, the second resource management client of the merchant transmits the offline resource transfer order with the resource transfer terminal by means of Bluetooth communication.

Step 1740, the position information of the target merchant is managed according to information included in the offline resource transfer order.

15 During specific implementation, information included in the offline resource transfer order at least includes the geographic position. According to the information included in the offline resource transfer order, management on the position information of the target merchant includes: according to the geographic position included in the offline resource transfer order, the position information of the target merchant is managed; or according to
20 the geographic position and the order time included in the offline resource transfer order, the position information of the target merchant is managed. The geographic position included in the offline resource transfer order is real-time geographic position of the user applying to generate the offline resource transfer order.

During specific implementation, the offline resource transfer order at least includes
25 information such as the user signature of the resource transfer-out user, the target merchant signature, the order time, the geographic position, the resource transfer quantity and the order content. The geographic position is a geographic position where the offline resource transfer order, i.e., a geographic position when the resource transfer-out user in the offline resource transfer order applies to generate the offline resource transfer order, is generated. According

to different information included in the order, the geographic position information of the target merchant may be further managed. For example, according to the time and the geographic position in each offline resource transfer order, a conventional moving route of the target merchant is determined, a permanent geographic position of the target merchant is determined, a current position of an offline target merchant is pre-estimated, etc.

Optionally, according to the geographic position included in the offline resource transfer order, management on the position information of the target merchant includes: for each offline resource transfer order, the geographic position included in the offline resource transfer order is used as one offline geographic position of the target merchant of the offline resource transfer order; and according to the respective offline geographic position of each target merchant, the permanent geographic position of the target merchant is determined.

During specific implementation, when the resource management platform acquires the offline resource transfer order stored in the resource transfer terminal, by resolving the offline resource transfer order, the resource transfer-out user, the target merchant and the geographic position of each offline resource transfer order are determined. Then, for each offline resource transfer order, the included geographic position is taken to be used as the offline geographic position of the target merchant of the offline resource transfer order to build an association relationship of the target merchant corresponding to each offline resource transfer order and the offline geographic position. Finally, according to the association relationship, the offline geographic position associated with each target merchant is respectively determined, and the offline geographic position associated with each target merchant is respectively subjected to clustering analysis to determine a cluster center including the most offline geographic positions as the permanent geographic position of the corresponding target merchant.

During offline trading of the user and the target merchant, the geographic position information of the user is acquired, and is stored into the offline resource transfer order. Then, the geographic position information in the offline resource transfer order is further analyzed, so as to acquire the offline geographic position of the target merchant to further perform geographic position information management on the target merchant according to the offline

geographic position, so that the accuracy of the geographic position information management is improved.

Optionally, according to the geographic position and order time included in the offline resource transfer order, management on the position information of the target merchant includes: for each offline resource transfer order, the geographic position included in the offline resource transfer order is used as one offline geographic position of the target merchant of the offline resource transfer order, and the order time included in the offline resource transfer order is used as the time of the target merchant appearing in the offline geographic position; and a moving route of the target merchant is determined according to each offline geographic position of the target merchant and the time of appearing in each offline geographic position.

During specific implementation, after the resource management platform acquires the offline resource transfer order stored by the resource transfer terminal, by resolving the offline resource transfer order, the resource transfer-out user, the target merchant, the order time and the geographic position of each offline resource transfer order are determined. Then, for each offline resource transfer order, the included geographic position is taken to be used as the offline geographic position of the target merchant of the offline resource transfer order. The included order time is used as the time of the target merchant of the offline resource transfer order appearing in the offline geographic position, and the association relationship among the target merchant corresponding to each offline resource transfer order, the offline geographic position and the appearing time is built. Finally, according to the association relationship, the associated offline geographic position of each target merchant and the time of appearing in each associated offline geographic position are respectively determined, and the moving route of each target merchant is trained through a machine learning model. Or, firstly, each day is divided into a preset quantity of time periods. Then, for each target merchant, the offline geographic position of the target merchant appearing in each time period is determined. Next, the most frequently appearing offline geographic position of the target merchant in each time period is selected to be used as the permanent geographic position of the target merchant in the time period. Finally, according to the sequence of the

time periods, the moving route of the target merchant in a day, i.e., the appearing geographic position of the target merchant in different time periods in a day is determined.

By combining the order time and the geographic position of the offline resource transfer order, the geographic position information of the target merchant is analyzed to determine the moving route of the target merchant, so that the resource management platform can predict the current position of the target merchant according to the moving route under the condition that the target merchant is offline. When the merchant is subjected to position information management, it mainly relies on the self position information reported by the merchant in real time, such as GPS positioning information reported in real time by a mobile terminal. When the merchant is offline, the merchant cannot be positioned. By the target merchant position information management method disclosed by the embodiment of the disclosure, the geographic position of the merchant can be determined according to the geographic position of the user, so that the management on the position information of the offline target merchant becomes possible, and a necessary condition is provided for the service based on the geographic position of the merchant.

In other embodiments of the disclosure, the offline resource transfer order may further be generated by the first resource management client of the user applying to the target merchant for resource transfer, and is sent to the resource transfer terminal to be stored by means of near field communication or Bluetooth communication.

For example, the user may firstly send a request of acquiring authentication information of the resource transfer terminal of the target merchant through the first resource management client, and performs identity authentication on the resource transfer terminal according to the acquired authentication information of the resource transfer terminal. Then, the first resource management client of the user generates the offline resource transfer order according to the resource transfer quantity input by the user, the pre-acquired user signature and target merchant signature, the current geographic position of host equipment of the first resource management client, the current time, and other order information. Finally, the first resource management client of the user sends the offline resource transfer order to the resource transfer terminal to be stored by means of near field communication or Bluetooth communication.

During specific implementation, when both the resource transfer terminal and the host equipment of the first resource management client are provided with built-in near field communication modules, the first resource management client of the user and the resource transfer terminal transmit the offline resource transfer order and other resource transfer-related information by means of near field communication. When both the resource transfer terminal and the host equipment of the first resource management client of the user are provided with built-in Bluetooth communication modules, the first resource management client of the user and the resource transfer terminal transmit the offline resource transfer order and other resource transfer-related information by means of Bluetooth communication.

According to the target merchant position information management method disclosed by the present embodiment, after the offline resource transfer order stored in the resource transfer terminal of the target merchant is acquired through the second resource management client of the target merchant, the position information of the target merchant is managed according to the information included in the offline resource transfer order, so that the problem that the position information management cannot be performed on the offline user is solved. According to the target merchant position information management method disclosed by the present embodiment, the user applies for resource transfer to the merchant by means of near field communication or Bluetooth communication, so as to generate the offline resource transfer order. The position information in the offline resource transfer order is a geographic position of the user performing resource transfer to the target merchant, such as a GPS position coordinate. By using the geographic position of the user performing resource transfer to the target merchant as the offline geographic position of the target merchant, the management on the position information of the offline target merchant becomes possible.

Embodiment 10

The present embodiment discloses a target merchant position information management device. As shown in Figure 18, the device includes:

an offline resource transfer order acquiring module 1800, configured to acquire an offline resource transfer order stored in a resource transfer terminal of a target merchant

through a second resource management client of the target merchant; and

a target merchant position information management module 1810, configured to manage position information of the target merchant according to information included in the offline resource transfer order acquired by the offline resource transfer order acquiring module 1800.

- 5 The information included in the offline resource transfer order at least includes a geographic position.

10 The target merchant position information management device disclosed by the present embodiment solves the problem that position information of an offline user cannot be managed by managing the position information of the target merchant according to information included in the offline resource transfer order by a first resource management terminal of the target merchant after the offline resource transfer order stored in the resource transfer terminal of the target merchant is acquired. The geographic position information management on an offline target merchant is realized, and the accuracy of the geographic position information management on the target merchant is greatly improved by acquiring

15 the geographic position information of the user during offline trading between the user and the target merchant, storing the geographic position information into the offline resource transfer order, and then, further using the geographic position information in the offline resource transfer order as an offline geographic position of the target merchant.

20 Optionally, as shown in Figure 19, the target merchant position information management module 1810 further includes:

a first target merchant position information management unit 1901, configured to manage the position information of the target merchant according to the geographic position included in the offline resource transfer order; or

25 a second target merchant position information management unit 1902, configured to manage the position information of the target merchant according to the geographic position and an order time included in the offline resource transfer order.

The geographic position included in the offline resource transfer order is a real-time geographic position of the user applying to generate the offline resource transfer order.

During specific implementation, the offline resource transfer order at least includes information such as a user signature of a resource transfer-out user, a target merchant signature, the order time, the geographic position, the resource transfer quantity and the order content. The geographic position is a geographic position where the offline resource transfer order, i.e., the geographic position when the resource transfer-out user in the offline resource transfer order applies to generate the offline resource transfer order, is generated. According to different information included in the order, the geographic position information of the target merchant can be further managed. For example, according to the time and the geographic position in each offline resource transfer order, a conventional moving route of the target merchant is determined, a permanent geographic position of the merchant is determined, a current position of the offline target merchant is pre-estimated, etc.

Optionally, the first target merchant position information management unit 1901 is further configured to:

for each offline resource transfer order, use the geographic position included in the offline resource transfer order as one offline geographic position of the target merchant of the offline resource transfer order; and

according to the respective offline geographic position of each target merchant, determine the permanent geographic position of the target merchant.

Optionally, the second target merchant position information management unit 1902 is further configured to:

for each offline resource transfer order, use the geographic position included in the offline resource transfer order as one offline geographic position of the target merchant of the offline resource transfer order, and use the order time included in the offline resource transfer order as the time of the target merchant appearing in the offline geographic position; and

according to the respective offline geographic position of each target merchant and the time of appearing in each offline geographic position, determine the moving route of the target merchant.

According to the target merchant position information management method disclosed by the present embodiment, the user applies for resource transfer to the merchant by means of near field communication or Bluetooth communication, so as to generate the offline resource transfer order. The position information in the offline resource transfer order is a geographic position of the user performing resource transfer to the target merchant, such as a GPS position coordinate. By using the geographic position of the user performing resource transfer to the target merchant as the offline geographic position of the target merchant, the management on the position information of the offline target merchant becomes possible.

Optionally, the offline resource transfer order is read from the resource transfer terminal of the target user by the first resource management client of the target user by means of near field communication or Bluetooth communication.

Optionally, the offline resource transfer order is generated and stored by the resource transfer terminal through the offline resource transfer request received by means of near field communication or Bluetooth communication, or the offline resource transfer order is generated by the first resource management client of the user applying to the target client for resource transfer, and is sent to the resource transfer terminal to be stored by means of near field communication or Bluetooth communication.

Under the condition that the user and the target merchant are not connected to the network, the generation and acceptance of the resource transfer order are completed by means of near field communication or Bluetooth communication, and the resource transfer order is stored in the resource transfer terminal of the target merchant, so as to subsequently complete resource transfer through the resource management platform. Therefore, resource transfer between the user and the target merchant is more flexible, and the popularization of a resource transfer system is facilitated.

The payment flexibility is improved by WeChat code scanning payment in a sense. For mobile merchants, the WeChat code scanning payment may also be performed, and certain convenience is brought to the user and the merchant. However, for the WeChat code scanning payment, a mobile phone of the user needs to be connected to the network. The acceptance of the payment order cannot be completed without being connected to the network. For near

field communication (NFC) (i.e., near field communication technology) payment, generally, the resource transfer terminal (such as a POS machine) of a merchant is required to be in a network connected state. The acceptance of the payment order can also be not completed without being connected to the network. Additionally, under the two conditions, the offline
5 position information of the merchant is not managed, only the order position reported by the merchant is recorded in the online payment order, so that inquiry is facilitated.

Correspondingly, the application further discloses electronic equipment, including a storage medium, a processor and a machine executable instruction stored in the storage medium and capable of running on the processor. When the processor executes the machine
10 executable instruction, the target merchant position information management method according to Embodiment 8 and Embodiment 9 of the application is implemented. The electronic equipment may be a PC machine, a mobile terminal, a personal digital assistant, a tablet computer, an intelligent loudspeaker and the like.

The embodiments in this specification are all described in a progressive manner, each
15 embodiment focuses on a difference from other embodiments, and for same or similar parts in the embodiments, mutual reference may be made to these embodiments. An apparatus embodiment is basically similar to a method embodiment, and therefore is described briefly. For related parts, refer to partial descriptions in the method embodiment.

The resource transfer method, device and system based on near field communication
20 provided by the disclosure are described above in detail. Specific examples are used in this specification to describe the principle and implementation manners of the disclosure, but the foregoing descriptions of the embodiments are merely intended to help understand the method of the disclosure and the core idea thereof. Besides, a person of ordinary skill in the art may make alterations to the specific implementation manners and application scope
25 according to the idea of the disclosure. In conclusion, the content of this specification shall not be understood as a limitation on the disclosure.

Based on the descriptions of the foregoing implementations, a person skilled in the art may clearly understand that the embodiments may be implemented by software and a necessary universal hardware platform or by hardware only. Based on such an understanding,

the foregoing technical solutions essentially or the part contributing to the related technology may be implemented in a form of a software product. The computer software product may be stored in a computer-readable storage medium, such as a read-only medium (ROM)/a random access memory (RAM), a magnetic disk, or an optical disc, and includes several
5 instructions for instructing a computer device (which may be a personal computer, a server, a network device, or the like) to perform the methods described in the embodiments or some parts of the embodiments.

CLAIMS

What is claimed is:

1. A resource transfer method based on near field communication, comprising:
acquiring a user identifier of a current login user in a first resource management client
5 by a resource transfer terminal of a target merchant according to the triggering of the first
resource management client, and outputting target merchant authentication information,
wherein the resource transfer terminal comprises a near field communication module;
when it is determined that the resource transfer terminal has enabled a fixed quantity
resource transfer mode, generating a resource transfer order by the resource transfer terminal
10 according to a preset quantity of resources transferred by each order;
adding a merchant signature of the target merchant and a user signature generated
according to the acquired user identifier to the resource transfer order by the resource transfer
terminal, and storing the resource transfer order with the signatures; and
sending an acceptance state of the resource transfer order to the first resource
15 management client by the resource transfer terminal by means of near field communication,
wherein the fixed quantity resource transfer mode and the quantity of resources
transferred by each order are set according to data sent by a second resource management
client.
2. The method according to claim 1, further comprising:
20 outputting the stored resource transfer order by the resource transfer terminal according
to the triggering of the second resource management client, so that the second resource
management client completes resource transfer corresponding to the resource transfer order
through a resource management platform.
3. The method according to claim 2, wherein after the step of acquiring the user
25 identifier of the current login user in the first resource management client by the resource
transfer terminal of the target merchant according to the triggering of the first resource
management client, the method further comprises:

receiving the resource transfer order sent by the first resource management client by means of near field communication by the resource transfer terminal;

adding the merchant signature of the target merchant and the user signature generated according to the acquired user identifier to the resource transfer order, and storing the
5 resource transfer order with the signatures; and

sending an acceptance state of the resource transfer order to the first resource management client by the resource transfer terminal by means of near field communication.

4. The method according to any one of claims 1 to 3, further comprising:

receiving and storing a user blacklist sent by the second resource management client by
10 means of near field communication; and

when the user identifier corresponds to a user in the user blacklist, sending a blacklist setting instruction of setting the user into a blacklist user to the first resource management client by means of near field communication, and removing the user from the user blacklist.

5. The method according to any one of claims 1 to 4, wherein before the resource transfer
15 order with the signatures is stored, the method further comprises:

performing encryption processing on the resource transfer order with the signatures through a preset key.

6. A target merchant position information management method based on near field communication, comprising:

20 acquiring at least one resource transfer order stored in a resource transfer terminal by a second resource management client by means of near field communication, wherein the resource transfer terminal comprises a near field communication module; and

managing position information of a target merchant by the second resource management client according to information comprised in the resource transfer order,

25 wherein the information comprised in the resource transfer order at least comprises a geographic position.

7. The method according to claim 6, wherein the step of managing the position information of the target merchant according to the information comprised in the resource transfer order comprises:

managing the position information of the target merchant by the second resource management client according to the geographic position comprised in the resource transfer order; or

managing the position information of the target merchant by the second resource management client according to the geographic position and order time comprised in the resource transfer order,

wherein the geographic position comprised in the resource transfer order is a real-time geographic position of the resource transfer terminal generating the resource transfer order.

8. The method according to claim 7, wherein the step of managing the position information of the target merchant according to the geographic position comprised in the resource transfer order comprises:

using the geographic position comprised in the resource transfer order as an offline geographic position of the target merchant corresponding to the resource transfer order by the second resource management client; and

determining a permanent geographic position of the target merchant by the second resource management client according to each offline geographic position of the target merchant.

9. The method according to claim 7, wherein the step of managing the position information of the target merchant according to the geographic position and the order time comprised in the resource transfer order comprises:

using the geographic position comprised in the resource transfer order as an offline geographic position of the target merchant corresponding to the resource transfer order, and using the order time comprised in the resource transfer order as the time of the target merchant appearing in the offline geographic position by the second resource management client; and

determining a moving route of the target merchant by the second resource management client according to each offline geographic position of the target merchant and the time of appearing in each offline geographic position.

10. The method according to any one of claims 6 to 9, wherein the resource transfer order is read by the second resource management client from the resource transfer terminal of the target merchant by means of near field communication or Bluetooth communication.

11. The method according to claim 6, wherein before the step of acquiring at least one resource transfer order stored in the resource transfer terminal by the second resource management client, the method further comprises:

10 performing merchant registration on a resource management platform by the second resource management client through the network, so as to acquire target merchant authentication information;

receiving a key issued by the resource management platform by the second resource management client, wherein the key comprises a trading key or a transmission key; and

15 sending the target merchant authentication information and the key to the resource transfer terminal to be stored by the second resource management client by means of near field communication.

12. A resource transfer method based on near field communication, comprising:

20 sending an instruction of acquiring target merchant authentication information stored in a resource transfer terminal by a first resource management client by means of near field communication;

receiving output information of the resource transfer terminal by the first resource management client by means of near field communication; and

25 when the output information comprises a resource transfer order generated by the resource transfer terminal, sending the resource transfer order to a resource management platform by the first resource management client through a network, so as to complete resource transfer corresponding to the resource transfer order through the resource

management platform, and sending a completion state of the resource transfer order to a resource transfer target merchant through the resource management platform.

13. The method according to claim 12, wherein the resource transfer order generated by the resource transfer terminal is an encrypted resource transfer order generated according to
5 a user signature of a current login user of the first resource management client, a merchant signature of the target merchant and a preset key, wherein the user signature is generated according to a user identifier carried in the instruction of acquiring the target merchant authentication information stored in the resource transfer terminal.

14. The method according to claim 12, wherein further comprising:
10 when the output information comprises a blacklist setting instruction, locally setting the current login user into a blacklist user by the first resource management client, so as to execute a blacklist prompt when the current login user initiates a resource transfer operation.

15. A resource transfer device based on near field communication, applied to a resource transfer terminal, wherein the resource transfer terminal comprises a near field
15 communication module, and the resource transfer device comprises:

a communication establishing module, configured to acquire a user identifier of a current login user in a first resource management client according to the triggering of the first resource management client, and output target merchant authentication information;

a resource transfer order generating module, configured to generate a resource transfer
20 order according to a preset quantity of resources transferred by each order when it is determined that the resource transfer terminal has enabled a fixed quantity resource transfer mode;

a resource transfer order storage module, configured to add a merchant signature of the target merchant and a user signature generated according to the acquired user identifier to the
25 resource transfer order, and store the resource transfer order with the signatures; and

an order state output module, configured to send an acceptance state of the resource transfer order to the first resource management client by means of near field communication,

wherein the fixed quantity resource transfer mode and the quantity of resources transferred by each order are set according to data sent by a second resource management client.

16. The resource transfer device according to claim 15, further comprising:

- 5 a resource transfer module, configured to output the stored resource transfer order according to the triggering of the second resource management terminal, so that the second resource management client completes resource transfer corresponding to the resource transfer order through a resource management platform.

17. A resource transfer device based on near field communication, comprising:

- 10 a handshaking module, configured to send an instruction of acquiring target merchant authentication information stored in a resource transfer terminal by means of near field communication;

a feedback information receiving module, configured to receive output information of the resource transfer terminal by means of near field communication; and

- 15 an online resource transfer module, configured to send a resource transfer order generated by the resource transfer terminal to a resource management platform through a network when the output information comprises the resource transfer order generated by the resource transfer terminal, so as to complete resource transfer corresponding to the resource transfer order through the resource management platform, and send a completion state of the
20 resource transfer order to a resource transfer target merchant through the resource management platform.

18. A resource transfer system based on near field communication, comprising: a resource management platform, a resource transfer terminal, and a first resource management client and a second resource management client respectively communicated with the resource
25 management platform through a network, wherein

the resource management platform is configured to manage the resource transfer terminal and complete resource transfer of the resource transfer order;

the resource transfer terminal is configured to perform the resource transfer method based on near field communication according to any one of claims 1 to 5;

the first resource management client is configured to perform the resource transfer method based on near field communication according to any one of claims 12 to 14; and

5 the second resource management client is configured to perform the resource transfer method based on near field communication according to any one of claims 6 to 11.

19. Electronic equipment, comprising: a storage medium, a processor and a machine executable instruction stored in the storage medium and capable of running on the processor, wherein when the processor executes the machine executable instruction, the resource
10 transfer method based on near field communication according to any one of claims 1 to 14 is implemented.

20. A computer readable storage medium, a computer program being stored thereon, wherein when the program is executed by a processor, steps of the resource transfer method based on near field communication according to any one of claims 1 to 14 are implemented.

15