Figure 18A is a perspective view of the second embodiment of the present invention and showing the needle in the retracted safety position with the grip in locked position.

Figure 18B is an enlarged view of the locking mechanism with the needle retracted in the safety position with the grip in the locked position.

Figure 19 is a side view of the second embodiment of the present invention and showing the needle in the retracted position with the grip locked.

Figure 20 is a plan view of the second embodiment of the present invention showing the needle in the retracted position with the grip locked.

Figure 21 is a side view of the second embodiment of the present invention showing the needle in the extended position

SUMMARY OF THE INVENTION

An I.V. infusion or blood collection apparatus comprises an I.V. infusion set and a safety shield adapted to surround the I.V. infusion set or blood collection apparatus. The I.V. infusion or blood collection apparatus comprise a wing body having a central portion having a proximal end to which a needle is connected, a distal end to which tubing is connected. Also provided is a bore extending through the wing body to permit the flow of fluid between the needle and the medical tubing. The wing body includes a pair of substantially coplanar wings extending horizontally outward from the opposite sides of the central portion and a grip extending upwardly from the central portion substantially perpendicular to the wings.

For ease of reading, in the description that follows the I.V. infusion or blood collection apparatus will at times be referred to as the "BCS", blood collection set.

As shown in the figures, the BCS 50 according to the present invention comprises an I.V. infusion set 100 and a safety shield 200.

I.V. infusion set 100 comprises a wing body 105 having a central portion 110 with a proximal end 115 to which a needle 120 is connected and a distal end 125 to which tubing 130 is connected. A longitudinal bore 135 extends through the central portion 110 of wing body 105 to permit the flow of fluid between the medical tubing 130 and needle 120. Wing body 105 further includes a pair of substantially coplanar wings 140 that extend horizontally outward from opposite sides of central portion 110. A grip 145 extends upwardly from the central portion 110 substantially perpendicular to the wings140. According to convention in the industry, the wing body 105 and wings 140 are referred to as a "butterfly". It will be noted that generally, the wings 140, central portion 110, bore 135 and grip 145 are molded as a single unit. The area where the respective wings140 connect to wing body105 is thinner than the wings such that the wings 140 are bendable with respect to the wing body 105. Fabrication techniques and materials for the wing body 105 are well known to those skilled in the art. Further, the needle 120 and medical tubing 130 are connected to wing body 105 by suitable means, again well known to those skilled in the art, such as glue, cyanoacrylate, heat bond or other type of bonding.

As briefly mentioned herein above, grip 145 is integrally molded with wing body 105 and extends upwardly there from between approximately 80% the width and 33% the length thereof. The top of grip 145 is angled upward from the proximal 115 end to the

distal end 120 and includes a series of axially extending ridges 150 which aid in handling the BCS as will be explained in further detail herein below.

Safety shield generally indicated at 200 is adapted to overlie the patient's skin and comprises an upper shield section 210 having a first hinge end 215 and a lower shield section 220 having a second hinge end 225 that are adapted to be connected together to form a chamber 227. In the illustrated embodiment, the respective first and second ends 215, 225 terminate in living hinge 222 and the respective opposite upper shield end 230 and lower shield opposite end 240 are adapted to be snapped together as best shown in figure 16. The snap closure 244 is a standard cantilever beam type of snap fit connection. Those skilled in the art will note that other types of closure mechanisms may be employed such as a post and hold, glue together method or other types of closures, well known to those skilled in the art.

The sides of the safety shield are contoured to form elongate slots or grooves 250 in opposite sides thereof when the respective shield sections 210, 220 are connected to form chamber 225. Additionally, an elongate longitudinal slot 255 is located in upper shield section 210 and terminates in a widened zone 260 which acts to lock the I.V. infusion set in the locked position after use. In another embodiment of the invention, the terminating end of slot 255 additionally includes a pair of flexible "fingers" 242, which extend from the opposite sides of slot 235 and point towards the medical tubing end of the safety shield 200 and collectively form a locking means for maintaining the I.V. infusion set in a locked position after use. It will be noted that the rear end of I.V. shield should be of sufficient length to enable single handed retraction of the needle 120 into the "safety" or locked position. More specifically, the distance from the tubing end of the

safety shield 200 to the terminating end of the locking means should be long enough to permit the safety shield to be gripped with the thumb and middle finger of the user while the pointer finger engages the needle end of the grip 145 and slides the needle 120 into the safety shield 200 until the locking means fully engages the grip whereupon the needle will be fully retracted and permanently locked within the safety shield for safe disposal.

Elongate slots 250 and 255 are constructed and arranged to enable the wings 140 of the IV infusion set to move from an operative position wherein the needle 120 is exposed for use to a safety position wherein the needle 120 is fully retracted into the chamber 225. Upon full retraction, the wings 140 are positioned proximate the tubing end of the safety shield and the grip 145 is lockingly received in the locking means portion of the elongate slot in the top wall of the safety shield.

While certain illustrative embodiments have been described, it is evident that many alternatives, modifications, permutations and variations will become apparent to those skilled in the art in light of the foregoing description.

THAT WHICH IS CLAIMED IS:

1. An I.V. infusion or blood collection apparatus, comprising:
an I.V. infusion set (100), comprising:

a wing body (105) having a central portion (110) having a proximal end (115) to which a needle (120) is connected, a distal end (125) to which tubing (130) is connected and further including a bore (135) there through to permit the flow of fluid between said needle (120) and said medical tubing (130), and wherein the wing body (105) includes a pair of flexible opposing wings (140) extending outward from said central portion (110) in a first direction, wherein said central portion (110) includes a grip (145) extending outward from said central portion (110) in a second direction; and

a safety shield (200) constructed and arranged to surround said wing body (105) and comprising;

a lower shield section (200) adapted to overlie the patient's skin;
an upper shield section (210), said lower shield section (200) and said upper shield section (210) adapted to be connected at a first end (215/225) and adapted to be connected to each other at said respective opposite ends to form a chamber (225), said chamber (225) having a top, a bottom and opposing side walls, said safety shield (200) being adapted to receive within said chamber (225) said I.V. infusion set (100) and further, wherein said safety shield (200) includes a front end through which the needle (120) of the I.V. infusion set (100) is extendable for use and a rear end through which the IV infusion set tubing (130) extends; and

a pair of opposing slots (250) in the respective side walls of said safety shield (200) through which the respective flexible wings (140) of said I.V. infusion set (100) are adapted to be positioned for slidable movement;

an elongate slot (255) in the top wall of said safety shield (200) through which said grip (145) is adapted to be positioned for slidable movement of said central portion (110); and

wherein said pair of opposing slots (250) and said elongate slot (250, 255) are constructed and arranged to enable said I.V. infusion set (100) to move from an operative position wherein said needle (120) is exposed for use to a safety position wherein said needle (120) is fully retracted into said chamber (225).

2. The I.V. infusion or blood collection apparatus according to claim 1, further including:
means for locking said I.V. infusion set (100) in the safety position operatively associated with said top wall slot and being positioned proximate the rear end thereof,
whereby upon movement of said I.V. infusion set (100) to the retracted position, the grip (145) is engaged by the locking means and the needle (120) is permanently locked within said chamber (225).

3. The I.V. infusion or blood collection apparatus according to claim 2, wherein said means for locking comprises a pair of flexible fingers (242) extending from opposite sides of said slot and further, wherein said fingers point towards the medical tubing (130) end of the safety shield (200).

4. The I.V. infusion or blood collection apparatus according to claim 1, wherein said grip (145) is substantially perpendicular to said flexible wings.

5. The I.V. infusion or blood collection apparatus according to claim 1, wherein said lower shield section (200) and said upper shield section (210) are connected at one end with a living hinge (222).

6. The I.V. infusion or blood collection apparatus according to claim 1, wherein said top wall slot is tapered, the wide end being proximate the needle (120) end of said safety shield (200) and the narrow end being proximate the tubing end of the safety shield (200).

7. The I.V. infusion or blood collection apparatus according to claim 6, wherein the narrow end of said top wall slot terminates at a means for locking said I.V. infusion set (100) in the safety position,
whereby upon movement of said I.V. infusion set (100) to the retracted position, the grip (145) is engaged by the locking means and the needle (I20) is permanently locked within said chamber (225).

8. The I.V. infusion or blood collection of claim 1, wherein the pair of flexible opposing wings (140) extends horizontally outward from said central portion (110).

9. The I.V. infusion or blood collection section connected to each other with a living hinge (222) at a first end apparatus according to claim 8 wherein said locking means is positioned at the needle (120) end of said slot and is adapted to lockingly receive said grip (145).

10. The I.V. infusion or blood collection apparatus according to claim 9, wherein said locking means further includes a pair of flexible fingers (242) extending from opposite sides of said slot and further, wherein said fingers point towards the medical tubing (130) end of the safety shield (200).

11. The I.V. infusion or blood collection apparatus according to claim 1, further comprising a locking means for locking said needle (120) in the retracted position operatively associated with said elongate slot (250, 255).

12. The I.V. infusion or blood collection apparatus according to claim 1, further not comprising a lock member to lock the I.V. infusion set when positioned in the safety shield in the operative position wherein said needle is exposed for use.

13. A method of using an I.V. infusion or blood collection apparatus, from a patient's arm or vein, comprising:

providing an I.V. infusion set (100), comprising:
a wing body (105) having a central portion (110) having a proximal end (115) to which a needle (120) is connected, a distal end (125) to which tubing (130) is connected and further including a bore (135) there through to permit the flow of fluid between said needle (120) and said medical tubing (130), and wherein the wing body (105) includes a pair of flexible opposing wings (140) extending outward from said central portion (110) in a first direction, wherein said central portion (110) includes a grip (145) extending outward from said central portion (110) in a second direction; and

disposing the I.V. fusion set (100) in a safety shield (200), comprising:

a lower shield section (200) adapted to overlie the patient's skin;

an upper shield section (210), said lower shield section (200) and said upper shield section (210) adapted to be connected at a first end *(215/225)* and adapted to be connected to each other at said respective opposite ends to form a chamber (225), said chamber (225) having a top, a bottom and opposing side walls, said safety shield (210) being adapted to receive within said chamber (225) said I. V. infusion set (l00) and further, wherein said safety shield (210) includes a front end through which the needle (120) of the I.V. infusion set (100) is extendable for use and a rear end through which thle IV infusion set tubing (130) extends; and

a pair of opposing slots (250) in the respective side walls of said safety shield (210) through which the respective flexible wings (140) of said I.V. infusion set (100) are adapted to be positioned for slidable movement;

an elongate slot (255) in the top wall of said safety shield (210) through which said grip (145) is adapted to be positioned for slidable movement of said central portion (110); and

wherein said pair of opposing slots (250) and said elongate slot (250, 255) are constructed and arranged to enable said I.V. infusion set (100) to move from an operative position wherein said needle (120) is exposed for use to a safety 14 position wherein said needle (120) is fully retracted into said chamber (225); and

moving the grip (145) of the I.V. fusion set (100) within the elongate slot (250) of the safety shield (210) forward toward the front end of the safety shield (210);
gripping the flexible wings (140) with one hand; and
guiding the needle (120) Into a patient's arm or vein while gripping the flexible wings (140) with one hand.

14. The method according to claim 13, further comprising:
gripping the safety shield (210) with one hand;
moving the grip (145) of the I.V. fusion set (100) within the elongate slot (250) of the safety shield (210) backward toward the rear end of the safety shield (210) with a finger of the one hand to remove the needle (120) from the patient's arm or vein.

15. The method according to claim 13, further comprising locking said I.V. infusion set (100) in the safety position operatively associated with said top wall slot and being positioned proximate the rear end thereof, whereby upon movement of said I.V. infusion set (100) to the retracted position, the grip (145) is engaged by the locking means and the needle (120) is permanently locked within said chamber (225).

16. The method according to claim 15, wherein said means for locking comprises a pair of flexible fingers (242) extending from opposite sides of said elongate slot (250) and further, wherein said fingers point (242) towards the medical tubing (130) end of the safety shield (210).

17. The method according to claim 13, wherein said grip (145) is substantially perpendicular to said flexible wings (140).

18. The method according to claim 13, wherein said lower shield section (200) and said upper shield section (210) are connected at one end with a living hinge (222).

19. The method according to claim 13, wherein said top wall slot is tapered, the wide end being proximate the needle end of said safety shield (200) and the narrow end being proximate the tubing end of the safety shield (200).

20. The method according to claim 19, wherein the narrow end of said top wall slot terminates at a means for locking said I.V. infusion set (100) in the safety position, whereby upon movement of said I.V. infusion set (100) to the retracted position, the grip (145) is engaged by the locking means and the needle (120) is permanently locked within said chamber (225).

21. The method according to claim 13, further comprising not locking the I.V. infusion set when the I.V. fusion set is positioned in the safety shield in the operative position wherein said needle is exposed for use.

Figure 18A is a perspective view of the second embodiment of the present invention and showing the needle in the retracted safety position with the grip in locked position.

Figure 18B is an enlarged view of the locking mechanism with the needle retracted in the safety position with the grip in the locked position.

Figure 19 is a side view of the second embodiment of the present invention and showing the needle in the retracted position with the grip locked.

Figure 20 is a plan view of the second embodiment of the present invention showing the needle in the retracted position with the grip locked.

Figure 21 is a side view of the second embodiment of the present invention showing the needle in the extended position

SUMMARY OF THE INVENTION

An I.V. infusion or blood collection apparatus comprises an I.V. infusion set and a safety shield adapted to surround the I.V. infusion set or blood collection apparatus. The I.V. infusion or blood collection apparatus comprises a wing body having a central portion having a proximal end to which a needle is connected and a distal end to which tubing is connected. Also provided is a bore extending through the wing body to permit the flow of fluid between the needle and the medical tubing. The wing body includes a pair of substantially coplanar wings extending horizontally outward from the opposite sides of the central portion and a grip extending upwardly from the central portion substantially perpendicular to the wings.

For ease of reading, in the description that follows the I.V. infusion or blood collection apparatus will at times be referred to as the "BCS", blood collection set.

As shown in the figures, the BCS 50 according to the present invention comprises an I.V. infusion set 100 and a safety shield 200.

I.V. infusion set 100 comprises a wing body 105 having a central portion 110 with a proximal end 115 to which a needle 120 is connected and a distal end 125 to which tubing 130 is connected. A longitudinal bore 135 extends through the central portion 110 of wing body 105 to permit the flow of fluid between the medical tubing 130 and needle 120. Wing body 105 further includes a pair of substantially coplanar wings 140 that extend horizontally outward from opposite sides of central portion 110. A grip 145 extends upwardly from the central portion 110 substantially perpendicular to the wings 140. According to convention in the industry, the wing body 105 and wings 140 are referred to as a "butterfly". It will be noted that generally, the wings 140, central portion 110, bore 135 and grip 145 are molded as a single unit. The area where the respective wings 140 connect to wing body 105 is thinner than the wings such that the wings 140 are bendable with respect to the wing body 105.
Fabrication techniques and materials for the wing body 105 are well known to those skilled in the art. Further, the needle 120 and medical tubing 130 are connected to wing body 105 by suitable means, again well known to those skilled in the art, such as glue, cyanoacrylate, heat bond or other type of bonding.

As briefly mentioned herein above, grip 145 is integrally molded with wing body 105 and extends upwardly there from between approximately 80% the width and 33% the length thereof. The top of grip 145 is angled upward from the proximal 115 end to the

distal end 120 and includes a series of axially extending ridges 150 which aid in handling the BCS as will be explained in further detail herein below.

Safety shield generally indicated at 200 is adapted to overlie the patient's skin and comprises an upper shield section 210 having a first hinge end 215 and a lower shield section 220 having a second hinge end 225 that are adapted to be connected together to form a chamber 227. In the illustrated embodiment, the respective first and second ends 215, 225 terminate in living hinge 222 and the respective opposite upper shield end 230 and lower shield opposite end 240 are adapted to be snapped together as best shown in figure 16. The snap closure 244 is a standard cantilever beam type of snap fit connection. Those skilled in the art will note that other types of closure mechanisms may be employed such as a post and hold, glue together method or other types of closures, well known to those skilled in the art.

The sides of the safety shield are contoured to form elongate slots or grooves 250 in opposite sides thereof when the respective shield sections 210, 220 are connected to form chamber 227. Additionally, an elongate
longitudinal slot 255 is located in upper shield section 210 and terminates in a widened zone 260 which acts to lock the I.V. infusion set in the locked position after use. In another embodiment of the invention, the terminating end of slot 255 additionally includes a pair of flexible "fingers" 265, which extend from
the opposite sides of slot 235 and point towards the medical tubing end of the safety shield 200 and collectively form a locking means for maintaining the I.V. infusion set in a locked position after use. It will be noted that the rear end of the safety shield 200 should be of sufficient length to enable single handed retraction of the needle 120 into the "safety" or locked position. More specifically, the distance from the tubing end of the safety shield 200 to the terminating end of the locking means

should be long enough to permit the safety shield to be gripped with the thumb and middle finger of the user while the pointer finger engages the needle end of the grip 145 and slides the needle 120 into the safety shield 200 until the locking means fully engages the grip whereupon the needle 120 will be fully retracted and permanently locked within the safety shield 200 for safe disposal.

Elongate slots 250 and 255 are constructed and arranged to enable the wings 140 of the I.V. infusion set 100 to move from an operative position wherein the needle 120 is exposed for use to a safety position wherein the needle 120 is fully retracted into the chamber 227. Upon full retraction, the wings 140 are positioned proximate the tubing end of the safety shield 200 and the grip 145 is lockingly received in the locking means portion of the elongate slot 255 in the top wall 210 of the safety shield 200.

THAT WHICH IS CLAIMED IS:

1. An I.V. infusion or blood collection apparatus, comprising:

an I.V. infusion set, comprising:

a wing body having a central portion having a proximal end to which a needle is connected, a distal end to which tubing is connected, and further including a bore therethrough to permit a flow of fluid between said needle and said tubing, and wherein the wing body includes a pair of flexible opposing wings extending outward from said central portion in at least one first direction, wherein said central portion includes a grip extending outward from said central portion in a second direction; and

a safety shield constructed and arranged to surround said wing body and comprising;

a lower shield section adapted to overlie a patient's skin;

an upper shield section, said lower shield section and said upper shield section adapted to be connected at a first end and adapted to be connected to each other at said respective opposite ends to form a chamber, said chamber having a top, a bottom, and opposing side walls, said safety shield being adapted to receive within said chamber said central portion of the wing body, said safety shield including a front end through which the needle of the I.V. infusion set is extendable for use, and said safety shield including a rear end through which the IV infusion set tubing extends; and

a pair of opposing slots in the respective opposing side walls of said safety shield through which respective wings of the pair of flexible opposing wings of said I.V. infusion set are adapted to be positioned for slidable movement; and

an elongate slot in the top wall of the chamber of said safety shield through which said grip is adapted to be positioned for slidable movement of said central portion;

wherein said pair of opposing slots and said elongate slot are constructed and arranged to enable said I.V. infusion set to move from an operative position in which said needle is exposed for use to a safety position in which said needle is fully retracted into said chamber; and

wherein said grip is configured for unimpeded slidable movement within the elongate slot from the operative position towards the safety position.

2. The I.V. infusion or blood collection apparatus according to claim 1, comprising:

a lock member configured to lock said I.V. infusion set in the safety position, wherein the lock member is operatively associated with said elongate slot in the top wall and is positioned proximate a rear end of the elongate slot,

whereby upon movement of said I.V. infusion set to the safety position, the grip is configured to be engaged by the lock member, and the needle is configured to permanently lock within said chamber.

3. The I.V. infusion or blood collection apparatus according to claim 2, wherein said lock member comprises a pair of flexible fingers extending from opposite sides of said slot, and wherein said pair of flexible fingers point towards the rear end of the safety shield.

4. The I.V. infusion or blood collection apparatus according to claim 1, wherein said grip is substantially perpendicular to said pair of flexible opposing wings.

5. The I.V. infusion or blood collection apparatus according to claim 1, wherein said lower shield section and said upper shield section are connected at one end with a living hinge.

6. The I.V. infusion or blood collection apparatus according to claim 1, wherein said elongate slot is tapered, including a wide end proximate the front end of said safety shield and including a narrow end proximate the rear end of the safety shield.

7. The I.V. infusion or blood collection apparatus according to claim 6, wherein the narrow end of said elongate slot terminates at a locking member adapted to lock said I.V. infusion set in the safety position, and

wherein upon movement of said I.V. infusion set to the safety position, the grip is engaged by the locking member and the needle is permanently locked within said chamber.

8. The I.V. infusion or blood collection apparatus according to claim 1, wherein the pair of flexible opposing wings extends horizontally outward from said central portion.

9. The I.V. infusion or blood collection apparatus according to claim 8, wherein said elongate slot comprises a locking member positioned at one end of said elongate slot and adapted to lockingly receive said grip.

10. The I.V. infusion or blood collection apparatus according to claim 9, wherein said locking member further includes a pair of flexible fingers extending from opposite sides of said elongate slot and wherein said pair of flexible fingers point towards the rear end of the safety shield.

11. The I.V. infusion or blood collection apparatus according to claim 1, further comprising a locking member adapted to lock said needle in the safety position, wherein said locking member is operatively associated with said elongate slot.

12. The I.V. infusion or blood collection apparatus according to claim 1, wherein the I.V. infusion set is unlocked when the I.V. infusion set is positioned in the operative position and said needle is exposed for use.

13. A method of using an I.V. infusion or blood collection apparatus according to claim 1 for transferring fluid to or from a patient's arm or vein, the method comprising:

moving the grip of the I.V. infusion set within the elongate slot of the safety shield forward toward the front end of the safety shield;

gripping the pair of flexible opposing wings with one hand; and

guiding the needle into a patient's arm or vein while the pair of flexible opposing wings is gripped with the one hand.

14. The method according to claim 13, further comprising:

gripping the safety shield with the one hand;

moving the grip of the I.V. infusion set within the elongate slot of the safety shield backward toward the rear end of the safety shield with a finger of the one hand to remove the needle from the patient's arm or vein.

15. The method according to claim 13, further comprising locking said I.V. infusion set in the safety position utilizing a locking member operatively associated with said elongate slot and being positioned proximate the rear end thereof, whereby upon movement of said I.V.

infusion set to the safety position, the grip is engaged by the locking member and the needle is permanently locked within said chamber.

16. The method according to claim 15, wherein said locking member comprises a pair of flexible fingers extending from opposite sides of said elongate slot, and wherein said pair of flexible fingers point towards the rear end of the safety shield.

17. The method according to claim 13, wherein said grip is substantially perpendicular to said pair of flexible opposing wings.

18. The method according to claim 13, wherein said lower shield section and said upper shield section are connected at one end with a living hinge.

19. The method according to claim 13, wherein said elongate slot is tapered, including a wide end proximate the front end of said safety shield and including a narrow end proximate the rear end of the safety shield.

20. The method according to claim 19, wherein the narrow end of said elongate slot terminates at a locking member adapted to lock said I.V. infusion set in the safety position, wherein upon movement of said I.V. infusion set to the safety position, the grip is engaged by the locking member and the needle is permanently locked within said chamber.

21. The method according to claim 13, wherein the I.V. infusion set is unlocked when the I.V. infusion set is positioned in the operative position and the needle is exposed for use.