

HUMAN BEHAVIORAL MODELING AND SIMULATION FRAMEWORK

RELATED PROVISIONAL APPLICATION

The present disclosure is related to and claims the benefit of priority of provisional U.S. Patent Application
5 Serial No. 60/892,422 entitled "Human Behavior Modeling and Simulation Framework", filed on March 01, 2007, which is hereby incorporated by reference.

BACKGROUND OF THE INVENTION

The present disclosure provides an improved data
10 processing system and in particular, a method and apparatus for processing data. Still more particularly, the present disclosure relates to a computer implemented method, apparatus, and computer usable program code for modeling and simulating human behavior.

15 Human behavior is a collection of activities performed by human beings. These activities are influenced by factors, such as, for example, culture, attitudes, emotions, values, ethics, authority, persuasion, and/or coercion. The behavior of human beings falls within a range in which some behavior is common,
20 some behavior is considered unusual, some other behavior is considered acceptable, and other behavior is outside of acceptable limits. The behavior of people has been studied by many academic disciplines, such as psychology, sociology, and anthropology. More recently, the use of computers have been
25 applied to the study of human behavior.

Additionally, simulations of human behavior have been used perform military exercises and planning. Human behavior simulation also may be used with respect to predicting other situations, such as economic and social actions. An ability to
30 predict human behavior would be useful in developing training programs. Knowing how trainees will respond do different stimuli may be used to develop and modify training programs.

Current models and simulation programs do not properly simulate human behavior for different reasons. As an example, currently available simulation programs are suited only for a particular type of simulation. As a result, when a different
5 type of simulation is required, a new program is required to be written to perform that simulation. Additionally, the number of relations and the ability to modify those relations is limited.

Therefore, it would be advantageous to have an improved computer implemented method, apparatus, and computer usable
10 program code for modeling and simulating human behavior for use in a training program.

SUMMARY OF THE INVENTION

The advantageous embodiments provide a computer implemented method, apparatus, and computer usable program code
15 for simulating human behavior. Source code is located on a storage system in a network data processing system. This source code is written in a language for predicting human behavior. An interpreter executes on hardware in the network data processing system, in which the interpreter includes a language interpreter
20 and a communications module. The language interpreter executes a simulation with the source code using artificial intelligence to generate a new definition and interpreted source code. A graphical user interface processor executes on the hardware in the network data processing system. The graphical user
25 interface processor receives the interpreted source code from the language interpreter to form received interpreted source code and generates device dependent output using the received interpreted source code. A set of devices is in communication with the graphical user interface processor. This set of
30 devices displays the device dependent output, receives user input to form received user input, and sends the received user input to the graphical user interface processor. The communications module receives the received user input from the

graphical user interface processor and the new definition from the language interpreter and modifies the source code with the received user input and the new definition to form modified source code that is executed by the language interpreter.

5 Another advantageous embodiment provides a computer implemented method for simulating human behavior. Data is retrieved from source code stored in a storage system in a network data processing system to form retrieved data. The retrieved data is interpreted to perform a simulation of the
10 human behavior using an interpreter executing on the network data processing system to generate results. Device dependent data is generated from the results using a graphical user interface processor executing on the network data processing system. The device dependent data may be used to present the
15 results. The source code is modified using the results to form modified source code. The modified source code provides new data utilized in subsequent interpretations to predict the human behavior.

 Another advantageous embodiment provides a data
20 processing system for simulating human behavior. This data processing system includes retrieving means for retrieving data from source code stored in a storage system in a network data processing system to form retrieved data. Interpreting means are present for interpreting the retrieved data to perform a
25 simulation of the human behavior using an interpreter executing on the network data processing system to generate results. The data processing system also includes generating means for generating device dependent data from the results using a graphical user interface processor executing on the network data
30 processing system. The device dependent data may be used to present the results. Modifying means are present for modifying the source code using the results to form modified source code. The modified source code provides new data utilized in subsequent interpretations to predict the human behavior.

The features, functions, and advantages can be achieved independently in various embodiments of the present disclosure or may be combined in yet other embodiments.

BRIEF DESCRIPTION OF THE DRAWINGS

5 The novel features believed characteristic of the disclosure are set forth in the appended claims. The disclosure itself, however, as well as a preferred mode of use, further objectives and advantages thereof, will best be understood by reference to the following detailed description of an
10 advantageous embodiment when read in conjunction with the accompanying drawings, wherein:

Figure 1 is a pictorial representation of a network of data processing systems in which the advantageous embodiments may be implemented;

15 **Figure 2** is a diagram of a data processing system in accordance with an advantageous embodiment;

Figure 3 is a diagram illustrating a simulation system in accordance with an advantageous embodiment;

20 **Figure 4** is a diagram of a human behavioral modeling and simulation development framework in accordance with an advantageous embodiment;

Figure 5 is a diagram illustrating a distribution of modules in a framework in accordance with an advantageous embodiment;

25 **Figure 6** is a diagram illustrating a source module code in accordance with an advantageous embodiment;

Figure 7 is a diagram illustrating a definition portion of a source code in accordance with an advantageous embodiment;

30 **Figure 8** is a block diagram of an object in accordance with an advantageous embodiment;

Figure 9 is a diagram of an object in accordance with an advantageous embodiment;

Figure 10 is a diagram of an action object in accordance with an advantageous embodiment;

Figure 11 is a diagram illustrating the application of actions in accordance with an advantageous embodiment;

5 **Figure 12** is a diagram illustrating the application of actions on a timeline with a scheduler interrupt in accordance with an advantageous embodiment;

10 **Figure 13** is a diagram illustrating the application of events in which time slots overlap in accordance with an advantageous embodiment;

Figures 14, 15, and 16 are diagrams illustrating lasting events in accordance with an advantageous embodiment;

Figure 17 is a diagram illustrating an interpreter in accordance with an advantageous embodiment;

15 **Figure 18** is a diagram illustrating the data flow for a lexical analyzer in accordance with an advantageous embodiment;

Figure 19 is a diagram illustrating parsing or syntax analysis performed by a grammar parser in accordance with an advantageous embodiment;

20 **Figure 20** is a diagram illustrating another example of a parse tree in accordance with an advantageous embodiment;

Figure 21 is a diagram of a execute module in an interpreter in accordance with an advantageous embodiment;

25 **Figure 22** is a flowchart of a process for generating tokens in accordance with an advantageous embodiment;

Figure 23 is a flowchart of a process for executing the simulation of human behavior in accordance with an advantageous embodiment;

30 **Figure 24** is a flowchart of a process for generating sentences or productions in accordance with an advantageous embodiment;

Figure 25 is a flowchart of a process for executing statements for productions in accordance with an advantageous embodiment;

Figure 26 is a diagram illustrating a graphical user interface (GUI) processor in accordance with an advantageous embodiment;

Figure 27 is of a diagram illustrating data flow through a graphical user interface processor in accordance with an advantageous embodiment;

Figure 28 is a diagram illustrating a display in accordance with an advantageous embodiment;

Figure 29 is a diagram illustrating manipulation of a display in accordance with an advantageous embodiment;

Figure 30 is a flowchart of a process for identifying changes in bitmaps in accordance with an advantageous embodiment;

Figure 31 is a flowchart of a process for handling difference data in accordance with an advantageous embodiment;

Figure 32 is a diagram illustrating components for use in providing a human transparency paradigm in accordance with an advantageous embodiment;

Figure 33 is a flowchart of a process for replacing a synthetic human with a live human in accordance with an advantageous embodiment;

Figure 34 is a diagram of examples of input neurons in accordance with an advantageous embodiment;

Figure 35 is a diagram of examples of input ranges defined for the input neuron left operand in accordance with an advantageous embodiment;

Figure 36 is a diagram of a statement for input behavior in accordance with an advantageous embodiment;

Figure 37 is a diagram illustrating an output declaration in accordance with an advantageous embodiment;

Figure 38 is a diagram illustrating statements for output ranges in a neural network in accordance with an advantageous embodiment;

Figure 39 is a diagram illustrating a statement for modifying output behavior in accordance with an advantageous embodiment;

Figure 40 is a diagram illustrating statements for hidden
5 layers in accordance with an advantageous embodiment;

Figure 41 is a diagram illustrating a sample neural network in accordance with an advantageous embodiment;

Figure 42 is example statements for training a neural network in accordance with an advantageous embodiment;

10 **Figure 43** is a diagram illustrating a compute function in a neural network in accordance with an advantageous embodiment;

Figure 44 is a diagram illustrating an example of a neural network in accordance with an advantageous embodiment;

Figure 45 is a diagram illustrating the results from the
15 operation of a neural network in accordance with an advantageous embodiment;

Figure 46 is a diagram illustrating an example of a list in accordance with an advantageous embodiment;

Figure 47 is a diagram illustrating deleting a variable
20 from the list in accordance with an advantageous embodiment;

Figure 48 is a diagram of code for deleting items in accordance with an advantageous embodiment;

Figure 49 is a diagram illustrating code to manipulate items in the list is depicted in accordance with an advantageous
25 embodiment;

Figure 50 is a diagram illustrating the use of the list as a queue in accordance with an advantageous embodiment;

Figure 51 is a diagram illustrating reading items in the list in accordance with an advantageous embodiment;

30 **Figure 52** is a diagram illustrating a sort attribute in a list in accordance with an advantageous embodiment;

Figure 53 is an example of a fuzzy logic implementation using fuel distance and speed in accordance with an advantageous embodiment;

Figure 54 is a diagram illustrating the solving of an equation using a genetic algorithm in accordance with an advantageous embodiment; and

Figures 55A and **55B** are a diagram illustrating code for an object in source code in accordance with an advantageous embodiment.

DETAILED DESCRIPTION OF THE DISCLOSURE

With reference now to the figures and in particular with reference to **Figures 1-2**, exemplary diagrams of data processing environments are provided in which illustrative embodiments may be implemented. It should be appreciated that **Figures 1-2** are only exemplary and are not intended to assert or imply any limitation with regard to the environments in which different advantageous embodiments may be implemented. Many modifications to the depicted environments may be made.

As used herein, the phrase "at least one of", when used with a list of items, means that different combinations one or more of the items may be used and only one of each item in the list is needed. For example, "at least one of item A, item B, and item C" may include, for example, without limitation, item A or item A and item B. This example also may include item A, item B, and item C, or item B and item C.

With reference now to the figures, **Figure 1** depicts a pictorial representation of a network of data processing systems in which the advantageous embodiments may be implemented. In these depicted examples, network data processing system **100** is used to implement a human behavioral modeling and simulation development framework. This framework provides an ability to predict human behavior.

Network data processing system **100** is a network of computers and other devices in which advantageous embodiments may be implemented. Network data processing system **100** contains network **102**, which is the medium used to provide communications

links between various devices and computers connected together within network data processing system 100. Network 102 may include connections, such as wire, wireless communication links, and/or fiber optic cables.

5 In the depicted example, server 104 and server 106 connect to network 102 along with storage unit 108. In addition, clients 110, 112, and 114 connect to network 102. These clients 110, 112, and 114 may be, for example, personal computers, workstations computers, and personal digital
10 assistants. In the depicted example, server 104 provides data, such as boot files, operating system images, and applications to clients 110, 112, and 114. Clients 110, 112, and 114 are clients to server 104 and server 106 in this example. Network data processing system 100 may include additional servers,
15 clients, and other devices not shown. The framework for predicting human behavior in the advantageous embodiments may be implemented using one or more data processing systems in network data processing system 100.

Turning now to **Figure 2**, a diagram of a data processing
20 system is depicted in accordance with an illustrative embodiment. In this illustrative example, data processing system 200 includes communications fabric 202, which provides communications between processor unit 204, memory 206, persistent storage 208, communications unit 210, input/output
25 (I/O) unit 212, and display 214.

Processor unit 204 serves to execute instructions for software that may be loaded into memory 206. Processor unit 204 may be a set of one or more processors or may be a multi-processor core, depending on the particular implementation.
30 Further, processor unit 204 may be implemented using one or more heterogeneous processor systems in which a main processor is present with secondary processors on a single chip. As another illustrative example, processor unit 204 may be a symmetric multi-processor system containing multiple processors of the same type.

Memory **206**, in these examples, may be, for example, a random access memory or any other suitable volatile or non-volatile storage device. Persistent storage **208** may take various forms depending on the particular implementation. For example, persistent storage **208** may contain one or more components or devices. For example, persistent storage **208** may be a hard drive, a flash memory, a rewritable optical disk, a rewritable magnetic tape, or some combination of the above. The media used by persistent storage **208** also may be removable. For example, a removable hard drive may be used for persistent storage **208**.

Communications unit **210**, in these examples, provides for communications with other data processing systems or devices. In these examples, communications unit **210** is a network interface card. Communications unit **210** may provide communications through the use of either or both physical and wireless communications links.

Input/output unit **212** allows for input and output of data with other devices that may be connected to data processing system **200**. For example, input/output unit **212** may provide a connection for user input through a keyboard and mouse. Further, input/output unit **212** may send output to a printer. Display **214** provides a mechanism to display information to a user.

Instructions for the operating system and applications or programs are located on persistent storage **208**. These instructions may be loaded into memory **206** for execution by processor unit **204**. The processes of the different embodiments may be performed by processor unit **204** using computer implemented instructions, which may be located in a memory, such as memory **206**. These instructions are referred to as program code, computer usable program code, or computer readable program code that may be read and executed by a processor in processor unit **204**. The program code in the different embodiments may be

embodied on different physical or tangible computer readable media, such as memory 206 or persistent storage 208.

Program code 216 is located in a functional form on computer readable media 218 that is selectively removable and may be loaded onto or transferred to data processing system 200 for execution by processor unit 204. Program code 216 and computer readable media 218 form computer program product 220 in these examples. In one example, computer readable media 218 may be in a tangible form, such as, for example, an optical or magnetic disc that is inserted or placed into a drive or other device that is part of persistent storage 208 for transfer onto a storage device, such as a hard drive that is part of persistent storage 208. In a tangible form, computer readable media 218 also may take the form of a persistent storage, such as a hard drive, a thumb drive, or a flash memory that is connected to data processing system 200. The tangible form of computer readable media 218 is also referred to as computer recordable storage media. In some instances, computer readable media 218 may not be removable.

Alternatively, program code 216 may be transferred to data processing system 200 from computer readable media 218 through a communications link to communications unit 210 and/or through a connection to input/output unit 212. The communications link and/or the connection may be physical or wireless in the illustrative examples. The computer readable media also may take the form of non-tangible media, such as communications links or wireless transmissions containing the program code.

The different components illustrated for data processing system 200 are not meant to provide architectural limitations to the manner in which different embodiments may be implemented. The different illustrative embodiments may be implemented in a data processing system including components in addition to or in place of those illustrated for data processing system 200.

Other components shown in **Figure 2** can be varied from the illustrative examples shown.

As one example, a storage device in data processing system **200** is any hardware apparatus that may store data.

5 Memory **206**, persistent storage **208** and computer readable media **218** are examples of storage devices in a tangible form.

In another example, a bus system may be used to implement communications fabric **202** and may be comprised of one or more buses, such as a system bus or an input/output bus. Of course,
10 the bus system may be implemented using any suitable type of architecture that provides for a transfer of data between different components or devices attached to the bus system. Additionally, a communications unit may include one or more devices used to transmit and receive data, such as a modem or a
15 network adapter. Further, a memory may be, for example, memory **206** or a cache such as found in an interface and memory controller hub that may be present in communications fabric **202**.

In the depicted example, network data processing system **100** is the Internet with network **102**, representing a worldwide
20 collection of networks and gateways that use the Transmission Control Protocol/Internet Protocol (TCP/IP) suite of protocols to communicate with one another. Of course, network data processing system **100** also may be implemented as a number of different types of networks in addition to or in place of the
25 Internet. These other networks include, for example, an intranet, a local area network (LAN), and a wide area network (WAN). **Figure 1** is intended as an example, and not as an architectural limitation for different embodiments.

Turning now to **Figure 2**, a diagram of a data processing
30 system is depicted in accordance with an advantageous embodiment. Data processing system **200** may be used to implement servers and clients, such as servers **104** and **106** and clients **110**, **112**, and **114** in **Figure 1**. In this illustrative example, data processing system **200** includes communications fabric **202**,

which provides communications between processor unit **204**, memory **206**, persistent storage **208**, communications unit **210**, input/output (I/O) unit **212**, and display **214**.

Processor unit **204** serves to execute instructions for software that may be loaded into memory **206**. Processor unit **204** may be a set of one or more processors or may be a multi-processor core, depending on the particular implementation. Further, processor unit **204** may be implemented using one or more heterogeneous processor systems in which a main processor is present with secondary processors on a single chip. As another illustrative example, processor unit **204** may be a symmetric multi-processor system containing multiple processors of the same type.

Memory **206**, in these examples, may be, for example, a random access memory or any other suitable volatile or non-volatile storage device. Persistent storage **208** may take various forms depending on the particular implementation. For example, persistent storage **208** may contain one or more components or devices. For example, persistent storage **208** may be a hard drive, a flash memory, a rewritable optical disk, a rewritable magnetic tape, or some combination of the above. The media used by persistent storage **208** also may be removable. For example, a removable hard drive may be used for persistent storage **208**.

Communications unit **210**, in these examples, provides for communications with other data processing systems or devices. In these examples, communications unit **210** is a network interface card. Communications unit **210** may provide communications through the use of either or both physical and wireless communications links.

Input/output unit **212** allows for input and output of data with other devices that may be connected to data processing system **200**. For example, input/output unit **212** may provide a connection for user input through a keyboard and mouse. Further, input/output unit **212** may send output to a printer.

Display **214** provides a mechanism to display information to a user.

Instructions for the operating system and applications or programs are located on persistent storage **208**. These
5 instructions may be loaded into memory **206** for execution by processor unit **204**. The processes of the different embodiments may be performed by processor unit **204** using computer implemented instructions, which may be located in a memory, such as memory **206**. These instructions are referred to as program
10 code, computer usable program code, or computer readable program code that may be read and executed by a processor in processor unit **204**. The program code in the different embodiments may be embodied on different physical or tangible computer readable media, such as memory **206** or persistent storage **208**.

15 Program code **216** is located in a functional form on computer readable media **218** that is selectively removable and may be loaded onto or transferred to data processing system **200** for execution by processor unit **204**. Program code **216** and computer readable media **218** form computer program product **220** in
20 these examples. In one example, computer readable media **218** may be in a tangible form, such as, for example, an optical or magnetic disc that is inserted or placed into a drive or other device that is part of persistent storage **208** for transfer onto a storage device, such as a hard drive that is part of
25 persistent storage **208**. In a tangible form, computer readable media **218** also may take the form of a persistent storage, such as a hard drive, a thumb drive, or a flash memory that is connected to data processing system **200**. The tangible form of computer readable media **218** is also referred to as computer
30 recordable storage media. In some instances, computer readable media **218** may not be removable.

Alternatively, program code **216** may be transferred to data processing system **200** from computer readable media **218** through a communications link to communications unit **210** and/or

through a connection to input/output unit **212**. The communications link and/or the connection may be physical or wireless in the illustrative examples. The computer readable media also may take the form of non-tangible media, such as communications links or wireless transmissions containing the program code.

The different components illustrated for data processing system **200** are not meant to provide architectural limitations to the manner in which different embodiments may be implemented. The different illustrative embodiments may be implemented in a data processing system including components in addition to or in place of those illustrated for data processing system **200**. Other components shown in **Figure 2** can be varied from the illustrative examples shown.

As one example, a storage device in data processing system **200** is any hardware apparatus that may store data. Memory **206**, persistent storage **208** and computer readable media **218** are examples of storage devices in a tangible form.

In another example, a bus system may be used to implement communications fabric **202** and may be comprised of one or more buses, such as a system bus or an input/output bus. Of course, the bus system may be implemented using any suitable type of architecture that provides for a transfer of data between different components or devices attached to the bus system.

Additionally, a communications unit may include one or more devices used to transmit and receive data, such as a modem or a network adapter. Further, a memory may be, for example, memory **206** or a cache such as found in an interface and memory controller hub that may be present in communications fabric **202**.

As a client, data processing system **200** may take various forms. For example, data processing system **200** may take the form of a tablet computer, laptop computer, a work station, a personal computer, a telephone device, or a personal digital assistant (PDA).

The different embodiments provide a simulation environment that may be used to predict how a group of people may react individually and/or as a group when subjected to a series of actions and/or events. In this manner, different
5 "what if" scenarios may be simulated with the results being used to help decision making on a final set of actions to be taken against the group.

The different embodiments provide a computer implemented method, apparatus, and computer usable program code for
10 simulating human behavior. In one embodiment, source code is located in a storage system in a network data processing system, such as network data processing system 100 as shown in **Figure 1**. The source code is used for predicting human behavior. An interpreter executes on hardware in the network data processing
15 system. This interpreter executes the simulation with the source code to generate a new definition and interpreted source code. A graphical user interface processor executing on the hardware in the network data processing system receives the interpreted source code and generates device dependent output
20 using this interpreted source code. The device dependent output is sent to a set of devices in communication with the graphical user interface processor.

These devices display device dependent output and receive user input. Received user input is returned to the graphical
25 user interface processor, which, in turn, sends the received user input to the interpreter. The interpreter uses the received user input and the new definition to alter or modify the source code. In these examples, a new definition is information used to modify existing source code or add new
30 information to existing source code. This modified source code is then executed to generate new definitions and new interpreted source code. In this manner, the feedback loop is generated to change the source code in these advantageous embodiments.

Turning next to **Figure 3**, a diagram illustrating a simulation system is depicted in accordance with an advantageous embodiment. System **300** is an example of a simulation system that may be implemented in network data processing system **100** in **Figure 1**. In particular, system **300** may be implemented using one or more data processing systems, such as data processing system **200** in **Figure 2**.

In these examples, definition **302** is processed by system **300** based on actions **304**. Actions **304** are applied to definition **302** to perform the simulation of human behavior. Actions **304** may be selected by a user of system **300** in these examples. Actions **304** also may be selected from a configuration file or by a program or process. Definition **302** is part of the source code used for the simulation in these examples.

System **300** modifies definition **302** using actions **304** to generate definition **306**. In these depicted examples, definition **306** is a new definition used as an output to provide results based on actions **304** taken on definition **302**. Additionally, definition **306** is used to modify definition **302**, which is then used to continue performing the simulation. This continual feedback occurs to provide system **300** an ability to learn from different iterations. Additionally, the results of previous simulations are stored in definition **302** allowing system **300** to learn from previous simulations.

In these examples, definition **302** is a representation of a group of humans and the environment in which the group of humans live. The description of the environment contains the assets, in both tangible and non-tangible form. Additionally, definition **302** also contains a description of the different humans that may populate the group in addition to internal relations that define actions and reactions to different events or input applied to the group of humans and the environment.

System **300** may be used as a simulation tool to predict the outcome and various reactions and/or impact when certain

actions are taken against the group of humans described in definition 302. In other words, system 300 may be programmed to access impacts such as, for example, economic, social, and psychological, when actions 304 are applied or taken against
5 definition 302.

In the illustrative examples, definition 302 is written using a computer language. In the depicted examples, the computer language is an interpreted language, which uses an interpreter to execute the simulation, but does not require
10 compiling for execution. Any language may be used that allows for defining various objects that are involved in a simulation process. For example, C and C++ are examples of interpreted languages that may be used in these examples. In these examples, the definition of objects include humans and the
15 environments in which the humans live. The different advantageous embodiments provide a framework for system 300 as well as definition 302 and actions 304.

With reference now to **Figure 4**, a diagram of a human behavioral modeling and simulation development framework is
20 depicted in accordance with an advantageous embodiment. Framework 400 is an example of an architecture for system 300 in **Figure 3**. In this example, framework 400 contains source code 402, interpreter 404, graphical user interface (GUI) processor 406, and devices 408.

25 Source code 402 is a module in framework 400 that contains all of the information for the database. Everything known about the simulation is stored in this particular component. Source code 402 contains all of the information needed to run a simulation. This information includes, for
30 example, the definition for a group of humans and the code needed to execute the simulation using the definition. Source code 402 also includes actions that may be taken on the definition as well as code used to present the results.

The language used for source code **402** may be modified to include functions and features that are specific to simulating and predicting human behavior. The language with these features is referred to as Human Behavior Definition Language (HBDL).

5 HBDL may be implemented using currently available languages such as C or C++. Of course, any interpreted language may be used to implement HBDL in these examples.

Further, HBDL may be implemented using an entirely new language rather than using an existing language with
10 modifications to provide for simulating human behavior. In the illustrative embodiments, different languages may be used to implement different components of HBDL. In these examples, source code **402** is a database written in HBDL and may be distributed across different storage devices that may be located
15 in different geographical locations.

Interpreter **404** collects data **410** from source code **402** to perform a simulation. In these illustrative examples, data **410** includes definitions of a group of humans and their environment, as well as actions that are to be applied to the humans.
20 Further, data **410** also includes statements or lines from the programming language used to generate source code **402**. These statements in data **410** are used by interpreter **404** to perform the simulation.

The statements in data **410** may include, for example, code
25 for an artificial intelligence program to simulate a synthetic human. These statements also may include, for example, code for fuzzy logic, neural networks and other processes used to perform the simulation. In addition, data **410** also may include processes or code for generating a graphical user interface
30 (GUI) to present the results. In this manner, source code **402** includes both the information regarding the group of humans and the environment as well as the processes or code needed to execute the simulation. Depending on the implementation, these statements may be in C or C++. Alternatively, the statements

may be in a higher level language that interpreter **404** translates into C or C++ statements for execution.

This simulation generates graphics data **412**, which is sent to GUI processor **406**. In these examples, graphics data **412** is in a form that does not require large amounts of data transmission that may slow down a network. In the illustrative embodiments, graphics data **412** takes the form of primitives. By transmitting primitives, rather than bitmaps or other formats that require more data to be transferred, the amount of bandwidth used in the network is reduced. In some cases, it may be necessary to send some bitmaps in graphics data **412**, but primitives are used when possible.

Instead, graphics data **412** is processed by GUI processor **406** to generate device data **414**, which is displayed by devices **408**. In these examples, device data **414** may be, for example, pixel data or bitmaps that are displayed by devices **408**.

Devices **408** may also receive user input to generate device data **416**, which is received by GUI processor **406**. GUI processor **406** translates device data **416** into a format that requires less use of network resources for transmission. In these examples, user input **418** is returned to interpreter **404**. User input **418** and results from the simulation from data **410** are used to generate modifications **420**. Modifications **420** are used to overwrite or modify source code **402**. These modifications are used to modify definitions in source code **402**. Modifications **420** are similar to definition **306** in **Figure 3**, which is used to modify definition **302** in **Figure 3**. In this manner, source code **402** may be altered to take into account the results of the simulation performed by interpreter **404** and user input received from devices **408**.

Modifications **420** also may include, for example, a selection of actions to be applied to or included in the simulation being performed by interpreter **404**. This selection

of actions and modifications 420 may be received from user input generated at devices 408 in these examples.

Data 410 may include information, such as definitions 302 and actions 304 in Figure 3. Modifications 420 may include information, such as changes to definition 306 in Figure 3. These changes may be, for example, modifications to existing definitions or the addition of new definitions. Graphics data 412 is used to present definition 306 in Figure 3 in these examples.

The illustration of the different modules in framework 400 is not meant to imply architectural limitations to the manner in which these modules may be implemented. For example, the different modules may include different sub-modules or processes to implement the different features in framework 400. Also, a particular module may be implemented on a single data processing system or spread across multiple data processing systems.

With the modularity of framework 400, the different modules may be distributed to different locations across a network to maximize the use of hardware resources. This modularity in framework 400 also allows for the centralization of some functionality while allowing other functionality to be migrated or distributed to remote locations in a network data processing system. For example, placing graphics processing and device dependent data in a centralized environment and then sending this information over a network to remote device provides few advantages. Graphics data, in general, is large in size and may slow down a network. As a result, centralization of this type of information and processing introduces problems with respect to latency, data transmission and data synchronization. Framework 400 is designed such that implementations of framework 400 may avoid these problems.

With reference next to Figure 5, a diagram illustrating a distribution of modules in a framework is depicted in accordance

with an advantageous embodiment. In this example, the different modules illustrated in system 500 are from framework 400 in **Figure 4**. As can be seen in this depicted example, system 500 contains internet 502, local area network (LAN) 504, wide area network (WAN) 506 and local area network (LAN) 508. These different networks are an example of components in network 102 in **Figure 1**.

As depicted, source code 510 is found in storage device 512, 514, and 516. Storage device 512 is connected to local area network 504; storage device 514 is connected to wide area network 506; storage device 516 is connected to local area network 508. The distribution of source code 510 from different devices in different networks is an example of one manner in which source code 510 may be stored.

Source code 510 also may be stored on a single storage system on a particular network rather than across different locations. Some storage devices storing source code 510 may be backup devices that store duplicate copies of source code 510. With this implementation, it is possible to migrate portions of the system of other locations to leverage advantages that may be found in those locations, rather than limiting the implementation to a particular place.

Interpreter 518 is located on data processing system 520 in this example. Data processing system 520 may be implemented using a data processing system, such as data processing system 200 in **Figure 2**. Data processing system 520 is connected to local area network 508. Interpreter 518 collects data from source code 510 in the different storage devices across the different networks to perform a simulation.

The results of the simulation are sent to GUI processor 522, which is also located on data processing system 520. GUI processor 522 generates device data for display on devices 523. Additionally, interpreter 518 may send graphics data to GUI processor 524 executing on data processing system 526 and GUI

processor 528 executing on data processing 530. GUI processor 524 generates device data for display on devices 530, while GUI processor 528 generates device data for display on devices 532. GUI processors 522, 524, and 528 are located close to devices 523, 530, and 532, respectively.

In this manner, the data generated by these processors does not require the use of large amount of network resources. In these examples, the GUI processor module described in framework 400 in **Figure 4** is duplicated in several different locations within system 500 to minimize the use of transmitting graphics data over a network to remote device in a manner that may slow down or use large amounts of network resources.

With reference now to **Figure 6**, a diagram illustrating a source module code is depicted in accordance with an advantageous embodiment. In this example, source code 600 is a more detailed illustration of source code 402 in **Figure 4**.

Source code 600 contains definition 602, actions 604, and graphical user interface (GUI) language 606. Definition 602 and actions 604 are directed towards the simulation of a group of humans in an environment. GUI language 606 is employed to present results and receive user input from the end user of the simulation. With GUI language 606, source code 600 controls the appearance of the presentation of results on the devices. This appearance of results is controlled using GUI language 606 in these examples.

Further, source code 600 is adaptive and open in these examples. Source code 600 includes both the information for the simulation and the actual language used to execute or perform the simulation. Source code 600 takes away decision making from a traditional application that reads and interprets a database. In contrast, source code 600 is a database that contains both the information and the application in which the information and application may be altered based on results generated through performing simulations.

Data 608 represents a flow of data to an interpreter, such as interpreter 404 in Figure 4. Modifications 610 presents changes to source code 600 being received from the interpreter. Data 608 includes information from definition 602, actions 604, and GUI language 606 to the interpreter for use in performing the simulation. In these examples, source code 600 is a free format database.

In these illustrative examples, source code 600 is written in HBDL. As a free format database, source code 600 does not require success of separators between different components. A program within source code 600 may be written using a single line. Source code 600 also contains loops, case statements, conditional jumps, and other similar statements to alter the execution of the simulation.

Further, source code 600 contains objects, which store portions of code. As a result, objects may be called over and over without the need for repetitions. Further, within source code 600, objects may be indexed and defined to contain default parameters. In this manner, the creation of intelligent objects is enabled within source code 600.

Also, different types of variables may be defined within source code 600. These types of variables may be directed toward particular tasks. For example, in addition to conventional numerical types, source code 600 may include types, such as humans, persons, family, action, timeline, date, and others. Additionally, source code 600 provides a timeline based execution model for performing simulations. Artificial intelligence components may be provided within source code 600 along with function commands to support these components.

Within source code 600, definition 602 describes a group of humans and the environment in which the groups of humans live. Actions 604 represent influences that are applied to definition 602 during the simulation. In these examples,

actions 604 are portions or snippets of code referred to as events that are put into a timeline.

In these examples, humans taking part in the simulation as well as humans using the simulation are handled by source code 600. The humans taking part in the simulation may be real or synthetic humans. Definition 602, actions 604, and GUI language 606 include functioning code as well as parameters. The functioning code and parameters along with other information are output as data 608 for interpretation by an interpreter.

By moving this information into source code 600, source code 600 is able to take control of the simulation. In this manner, the simulation is no longer application specific, like those written currently used styles and languages. For example, once a particular item is defined in definition 602, this item may be used with a predefined set of actions in actions 604. For example, a human of type X may be defined in definition 602 used along with actions run in actions 604. As a result, an infinite number of simulations may be created and run without recoding human X and run for each simulation.

Further, having GUI language 606 located within source code 600 means that definition 602 and actions 604 may control the display presented to users. In this manner, source code 600 is essentially a database that is in charge of what users of the simulation see. This feature also supports the reusability of definitions and knowledge to allow an infinite number of simulations to be created without having to custom write a simulation for application or program for each simulation.

Current systems employ data that is static in a single simulation that is coded from scratch. At best, the code that simulates a single object is kept in a library, but the action for each object is unique to each simulation. The action is typically written in a separate program. As a result, currently used techniques require substantial coding for each particular type of simulation. Further, with current practices, a

graphical user interface is typically reused and in control of the application.

As a result, these interfaces do not change a particular simulation without having to recode or rewrite the application.

5 In this manner, with the source code design in the advantageous embodiments, greater flexibility is presented to display results and receive user input in contrast to currently used techniques for simulations.

GUI language **606** provides code that is selectively sent
10 by interpreter through a graphical user interface processor, such as GUI processor **406** in **Figure 4**. This code provides the displays or visuals to the end user as well as input and output controls that are provided at various displays. GUI language **606** controls what every end user sees on their screens and the
15 way every user interacts with the system. In these illustrative examples, GUI language **606** is a subset of HBDL. Depending on the particular implementation, GUI language **606** may be implemented using a different language to provide the different advantageous features. In this manner, the different
20 advantageous embodiments show the control to source code **600**.

An advantage of having the input and output controlled by GUI language **606** within source code **600** is that the user interface provided at the end devices may be controlled by the simulation. A simulation often involves users having different
25 backgrounds. An ability to customize the various user interfaces helps these users to quickly understand the system. Thus, the learning curve for executing simulations is reduced. Further, only the most relevant information is presented to different users, which enhances the relevance of the simulation.

30 For example, different users may require different user interfaces for a particular simulation. Some users may be provided a user interface to select particular actions from actions **604** to apply to definition **602**. Other users may be able to take the place of a synthetic human defined in definition

602. This type of user is provided a different user interface from the user that selects actions.

Further, different simulations being executed also require different types of interfaces. This type of architecture also provides an ability to dynamically add or simplify user interfaces. In this manner, user interfaces may be provided in an implementation dependent manner.

Additionally, different simulations may impose new parameters and new environments. These new and changing situations mean that different data sets are to be analyzed. These situations also may involve the need for different users or experts to be involved. This type of ever changing nature of the task at hand imposes a need for a versatile adaptive environment as provided through source code 600. Source code 600 provides this paradigm within definition 602, actions 604, and GUI language 606.

In these illustrative examples, the GUI processor is under the control of source code 600 and not a static application as currently occurs with presently used simulation systems. GUI language 606 provides a layer of abstraction for the hardware. The content of GUI language 606 ensures that the simulation process occurs in a predictable fashion and that appropriate information is delivered and received from a variety of users and devices. GUI language 606 contains all of the code needed to run on any hardware on which an interpreter and a GUI processor are implemented. In this manner, only lower layer portions that wrap around hardware need to be rewritten when hardware changes occur.

In these illustrative examples, GUI language 606 provides a variety of constructs to build necessary elements of a user interface during runtime. These elements include, for example, mouse tracking movement, mouse clicking movement, an analog joy stick, menus, windows, dialog boxes, check boxes, radio buttons, list boxes, and forms. With these and other elements,

implementing a graphical user interface is made easier. Further, the output generated in building a graphical user interface using GUI language 606 may be saved within GUI language 606 for later uses.

5 GUI language 606 provides a number of different features to allow source code 600 to present and receive input with respect to a simulation of a group of people and the environment in which they are living in. GUI language 606 provides a set of three dimensional primitives. These three dimensional
10 primitives support features such as a set of commands to control a hypothetical camera and view port. Mathematical functions, including vector and matrix operations, are also included along with an ability to import and export graphics file formats of different types.

15 The features provided within GUI language 606 also include creating three dimensional objects that embed more than just three dimensional data. For example, these three dimensional objects may include other information, such as, for example, price, weight, color, value, or rules regarding the
20 three dimensional object. Of course, any kind of information may be imbedded or associated with these three dimensional objects.

Further, GUI language 606 also includes a three dimensional model and stack, and a set of commands to manage
25 this model and stack. The three dimensional model and stack allows for a creation of complex transformations to be applied to different three dimension entities. In this manner, different worlds may be created in which objects are temporarily affected.

30 GUI language 606 provides for an easy creation and maintenance of large three dimensional databases. These databases may be found within definition 602. The databases may be used to represent any three dimensional object regardless of the size, complexity, or nature of the object.

Moreover, GUI language **606** provides a graphical user interface building language. This language allows source code **600** to control the look and feel of every end user device. GUI language **606** may include two dimensional primitives, such as points, lines, curves, and surfaces. Further, a set of two dimensional control objects also are present. These two dimensional control objects include, for example, windows, dialog boxes, requestors, check boxes, radio buttons, and menus.

With reference next to **Figure 7**, a diagram illustrating a definition portion of a source code is depicted in accordance with an advantageous embodiment. Definition **700** is a more detailed illustration of definition **602** in **Figure 6**. Definition **700** includes assets **702**, humans **704**, and internal relations **706**.

Assets **702** includes both tangible assets **708** and non-tangible assets **710** in the environment in which the humans are present. Tangible assets **708** include both live and inanimate objects. Live objects may include, for example, livestock, birds, bacteria, and plants. Inanimate objects may include, for example, a house, a mountain, a lake, a car, a table, a pen, an aircraft, or a gun.

Non-tangible assets **710** may include, for example, rules, laws, and regulations for a group of humans being simulated. Non-tangible assets **710** may also include information used by the interpreter to handle the assets. This information also includes general code, libraries, and routines.

More specifically, this type of asset includes, for example, a math library, a graphics library, a two dimensional primitives library, a three dimensional primitives library, a model and stack management library, an artificial intelligence library, an input/output library, an encryption library, a networking library, a system calls library, and a time management library. In other words, non-tangible assets **710** may include any information needed to execute the simulation.

Humans **704** describe the various human characters that are present in a group of humans. Humans **704** may include information that details various family trees and relationships among the people in the group of humans. Further, humans **704**
5 contain information needed to create psychological profiles for the various individuals.

Internal relations **706** contain actions and reactions that are used by the artificial intelligence in definition **700**.

These actions and reactions may be triggered in various manners.
10 For example, the trigger may be random, alarm based, a state machine, or as a reaction to a set of events that are applied to definition **700**.

Different objects within assets **702** may rely upon non-tangible assets **710** to perform necessary functions and
15 computations. The general code, libraries, and routines are the code needed to support different programming tasks. These different components may be sent as data to an interpreter for use in executing a simulation. The three dimensional objects are all objects that make up the different world, including live
20 and inanimate objects.

With reference now to **Figure 8**, a block diagram of an object is depicted in accordance with an advantageous embodiment. In this example, object **800** is an example of one illustrative implementation of an object within definition **602**
25 in **Figure 6**. In this illustrative example, object **800** includes artificial intelligence **802**, characteristics **804**, and internal relations **806**.

Artificial intelligence **802** contains code used to simulate a particular object. In these examples, object **800** is
30 a living object, such as a human being, a plant, or an animal. Artificial intelligence **802** contains the code necessary to simulate the actions and reactions of the selected object.

Characteristics **804** include an identification of characteristics for the particular object. For example, if

object **802** is a human, characteristics **804** may include, for example, height, weight, skin color, hair color, eye color, body build, and any other suitable characteristic of a person.

Characteristics **804** may include other physical characteristics, such as, for example, how fast the person can run, the agility of the person, and the stamina of the person.

Non-physical characteristics in characteristics **804** may include, such as, for example, without limitation, patience, compassion, emotions, intelligence, and interpersonal relationships. Characteristics **804** are used by artificial intelligence **802** to simulate actions and reactions of object **800**. In particular, characteristics **804** are used to simulate human behavior in the depicted examples.

The complexity of artificial intelligence **802** and the number of characteristics within characteristics **804** will vary depending on the particular implementation. The complexity of these components increase as the desired ability to make the simulation indistinguishable from real objects increases.

Internal relations **806** contains actions and reactions that may be used by artificial intelligence **802** to trigger events. These events include, for example, actions taken by object **800**. These actions may be initiated by object **800**, or the actions may be ones that occur in response to actions taken on object **800**. These actions taken on by object **800** may be actions directed towards object **800** or may be ones that are perceived by object **800** based on the environment in which **800** is in during a simulation.

Turning now to **Figure 9**, a diagram of an object is depicted in accordance with an advantageous embodiment. In this example, object **900** is an example of an inanimate object that may be simulated with definition **602** in **Figure 6**. Object **900** may be, for example, a car, a pen, an aircraft, a mountain, or a lake.

Object 900, in this example, includes model 902 and characteristics 904. Model 902 includes code that is used to simulate the particular object. Model 902 includes code to simulate the functions of the particular object. For example, if object 900 is a car, various actions may be performed on the car that generates certain results. For example, the engine may be turned on and the wheels may turn.

Model 902 may be, for example, a mathematical model. For example, set of finite state machines may be used to model the functions and operation of a car. Other functions and processes may be included in model 902, such as those to simulate aging of the object being modeled through use and exposure to environments over time.

Characteristics 904 identifies various characteristics of the car, such as, for example, tire size, engine size, paint color, type of radio, and amount of interior space. Further, characteristics 904 also may include other information about features of the car for object 900. For example, the amount of tread on a tire may be identified for the particular tire type within characteristics 904.

Model 902 is used to simulate what the car does in response to various actions taken on by object 900, such as a user driving the car, wear and tear that occurs on the tires identified in characteristics 904. This wear and tear is recorded within characteristics 904. The wear and tear may be part of an algorithm within model 902. Further, environmental exposure such as sun and hail may be taken into account by model 902 to present an aged look for model 902 in the car example. The different actions performed by object 800 in Figure 8 and object 900 in Figure 9 may be performed on these objects and may be defined within actions 604 in Figure 6.

With reference now to Figure 10, a diagram of an action object is depicted in accordance with an advantageous

embodiment. In this example, action object 1000 is an example of an action that may be found within actions 604 in **Figure 6**.

Action object 1000 includes action 1002, object 1004, user permissions 1006, and graphical user interface (GUI) 1008.

5 Action 1002 may be, for example, an action that may be performed, such as talk, strike, move, sit, grasp, speak, or look. Object 1004 is an identification of the object in which the action may be taken. User permissions 1006 determines whether the particular user may perform action 1002 on object
10 1004. Graphical user interface 1008 identifies the type of user interface that is presented to a particular user.

Object 1004 may be an inanimate object or a live object. User permissions 1006 are used to determine whether certain users are able to perform selective actions on an object. In
15 some cases, it is undesirable for a particular user to perform an action on an object. Graphical user interface 1008 identifies the manner in which the action on the object is presented to the user as well as how user interactions with the object may occur.

20 The illustrations of objects in **Figures 8, 9, and 10** are presented for purposes illustrating one manner in which source code 600 in **Figure 6** may be implemented using currently available programming languages and methodologies. These examples, however, are not meant to imply limitations on the
25 manner in which source code 600 in **Figure 6** may be implemented.

Turning now to **Figure 11**, a diagram illustrating the application of actions is depicted in accordance with an advantageous embodiment. In these examples, timeline 1100 illustrates influences that a definition, such as definition 602
30 in **Figure 6**, is subjected to during a simulation. In these illustrative examples, actions such as actions 604 in **Figure 6** are referred to as events on timeline 1100. These actions are snippets or portions of code. In particular, the actions include events 1102, events 1104, events 1106, and events 1108.

In this example, events **1102** are applied at time slot **1110**. Events **1104** occur during time slot **1112** and events **1106** are applied during time slot **1114**. Events **1108** occur during time slot **1116**. These events may be procedural in nature or event driven. In other words, the events may be applied in response to various messages emitted or generated by the interpreter.

In these examples, a master interrupt issued by the execution of timeline **1100** interrupts these events during mid-execution, if necessary, and the simulation passes immediately to the next time slot of the simulation. Unlike currently used program languages, in which the execution of source code is either procedural or event driven, the actions in the source code follow a time-based execution model in the advantageous embodiments. In these examples, the time slots may have various granularities. For example, each time slot may represent a week, a day, an hour, a minute, or some other period of time.

In the depicted embodiments, timeline **1100** runs under the supervision of a scheduler, which is described in more detail below. The scheduler runs events **1102**, **1104**, **1106**, and **1108**, which are associated or attached to timeline **1100**. The scheduler has full control over these events and may interrupt them as necessary. Further, the scheduler runs a memory manager and a memory recovery facility. In this manner, all memory allocated for an interrupted task may be made available to upcoming events.

Turning now to **Figure 12**, a diagram illustrating the application of actions on a timeline with a scheduler interrupt is depicted in accordance with an advantageous embodiment. In this example, timeline **1200** includes events **1202** and events **1204**. Events **1202** begins executing during time slot **1206** on timeline **1200**. In this example, events **1202** includes input **1208**, decisions **1210**, and process **1212**. Events **1202** begins execution during time slot **1206**. When time slot **1206** ends, the scheduler interrupts the execution of events **1202** at point **1214**.

Execution then is transferred to events **1204** for time slot **1216**, which begins after time slot **1206**. In this example, no overlap is present between time slot **1206** and time slot **1216**.

Turning next to **Figure 13**, a diagram illustrating the application of events in which time slots overlap is depicted in accordance with an advantageous embodiment. In this example, the scheduler executes timeline **1300**, which has events **1302**, **1304**, **1306**, and **1308** attached to various time slots. Events **1302** are attached to time slot **1310**. Events **1304** are attached or associated with time slot **1312**. Events **1306** and **1308** are attached to time slots **1314** and **1316**, respectively.

In this illustrative example, the different time slots may overlap with each other. In other words, one time slot may last for a longer period of time than another time slot. As illustrated, time slot **1310** and time slot **1312** overlap with each other. As a result, events **1302** and events **1304** may run concurrently during a certain period of time, in which time slots **1310** and time slots **1312** overlap. In this particular example, events **1302** are provided with more time to execute.

The overlapping of time slots does not mean that events are merged during the moment of time in which the overlap occurs. In these illustrative examples, if for any reason an interrupt of events **1302** for time slot **1310** occur, control passes to time slot **1312** if this interrupt occurred before the start of or during the execution of time slot **1312**. If, however, the interrupt occurred during time slot **1310**, but after the end of time slot **1312**, control is passed to the execution of events **1306** in time slot **1314**.

With reference now to **Figures 14, 15, and 16**, diagrams illustrating lasting events are depicted in accordance with an advantageous embodiment. As illustrated, timeline **1400** contains events **1402**, lasting event **1404**, and events **1406**, which are attached to or assigned to time slot **1408**. Events **1410** are associated with time slot **1412** on timeline **1400**. Events **1414**

are attached to time slot **1416**, while events **1418** are attached to time slot **1420**. Events may be made uninterruptible or given extensions. This type of event may be present when waiting for an input coming from an end user or from some other event that has not yet terminated but is needed. In these examples, this type of event is a lasting event, such as lasting event **1404**. Lasting event **1404** may be carried over from one time slot to another time slot until the event fully occurs.

As illustrated in **Figure 15**, lasting event **1404** becomes attached to time slot **1412**. In **Figure 16**, lasting event **1404** is again extended or moved to time slot **1416**. Lasting event **1404** is completed during this particular time slot in these examples.

Turning now to **Figure 17**, a diagram illustrating an interpreter is depicted in accordance with an advantageous embodiment. Interpreter **1700** is a more detailed illustration of interpreter **404** in **Figure 4**. Interpreter **1700** is a program that transforms a source code written in one language into a target code written in another language. Interpreter **1700** also executes the target code as the interpreter proceeds in processing the source code. This target language may be written in another high-level language or in the language used by the particular data processing system or processor.

For any program to be correctly interpreted and executed, the source code is structured according to constructs defined by the language. In particular, these constructs are syntactical constructs. The complete set of constructs forms the grammar of the language for the source code. Any code that is not structured according to these constructs or is grammatically incorrect is discarded by interpreter **1700**.

Interpreter **1700** includes communication modules **1702** and language interpreter **1704**. Additionally, interpreter **1700** includes encryption/decryption modules **1706**, which provide for secure sending and receiving of information between interpreter **1700** and a GUI processor, such as GUI processor **406** in **Figure 4**.

In these illustrative examples, language interpreter 1704 receives HBDL 1708. HBDL 1708 is an example of data, such as data 410 in Figure 4 received from a source code module, such as source code 402 in Figure 4. HBDL 1708 is interpreted by language interpreter 1704 to execute a simulation. The results are interpreted HBDL (IHBDL) 1710, which are sent to encryption/decryption module 1706 for encryption. After encryption, the encryption results are sent as encrypted interpreted HBDL (EIHBDL) 1712 to the GUI processor, such as GUI processor 406 in Figure 4. EIHBDL 1712 is an example of graphics data 412 in Figure 4. User input is received as encrypted HBDL (EHBDL) 1714 as collected by a GUI processor from a set of devices. EHBDL 1714 is an example of user input 418 in Figure 4. This encrypted information is decrypted and sent to communication modules 1702 as HBDL 1716.

HBDL 1716 is an example of user input that is used to modify the source code. This modification may be, for example, changing definitions within the source code or to select actions to be applied to the definitions. Additionally, the output of language interpreter 1704 is sent to communications module 1702 as HBDL 1718 for use in modifying the source code. HBDL 1716 and HBDL 1718 are used by communication modules 1702 to form HBDL 1720, which is used to modify the source code. HBDL 1720 is an example of a format for modifications 420 in Figure 4, which are used to modify the source code. As can be seen, HBDL 1718 provides a feedback for the output generated by language interpreter 1704 to modify the source code.

More specifically, communication modules 1702 includes dispatcher module 1722, input module 1724, and registration module 1726. Language interpreter 1704 includes lexical analyzer 1728, grammar parser 1730, and execute modules 1732.

Language interpreter 1704 contains modules that deal with lexical analysis, grammar parsing, and decision making. When data is received as HBDL 1708, lexical analyzer 1728 dissects

the data in HBDL **1708** into individual tokens or words in the source code language. In these illustrative examples, the source code is written in HBDL. In other words, lexical analyzer **1728** identifies the different tokens or components in HBDL **1708**. These tokens are sent to grammar parser **1730** which groups the tokens into meaningful sentences or statements for HBDL **1708**. Once a sentence or statement in HBDL **1708** is constructed, grammar parser **1730** sends this statement to execute module **1732**. Action based on this statement is then accordingly taken.

Execute module **1732** includes a number of different sub-modules for performing simulations. In these examples, execute module **1732** generates interpreted HBDL (IHBDL) **1710** and HBDL **1718**. HBDL **1710** takes the form of graphics data, such as graphics primitives. HBDL **1718** is a modified or new definition that is used to modify the source code. HBDL **1718** is returned to input module **1724** for use in modifying or rewriting the source code. Input module **1724** passes the new definition in HBDL **1718** to dispatcher module **1722** which dispatches HBDL **1720** to be written into the source code.

In these illustrative embodiments, grammar parser **1730** launches lexical analyzer **1728** and execute module **1732**. Grammar parser **1730** requests tokens from lexical analyzer **1728**. Lexical analyzer **1728** receives characters from HBDL **1708** to generate tokens. Each time a token is generated, lexical analyzer **1728** sends the token to grammar parser **1730**. Grammar parser **1730** generates one or more parse trees using the token. When a parse tree is completed, grammar parser **1730** requests an action to be executed by execute module **1732** based on the completed parse tree.

In these illustrative examples, each parse tree represents a production. A production has a set of one or more actions that are fired or executed each time a stream of tokens matches a definition for a production. In response to the

request from grammar parser **1730**, execute module **1732** performs a semantic analysis to determine whether any semantic errors are found in the instructions for the actions. If an error occurs, the error is reported. Otherwise, the instructions for the set
5 of actions are executed. A recursive return to non-terminal callers is made with actions being fired for the assigned completed productions along the way.

In these examples, execute module **1732** determines whether the instructions generated in the parse trees created by grammar
10 parser **1730** are semantically correct. If semantic errors occur, execution module **1732** generates an error and ignores the instruction in these examples. In some cases, however, the errors may be corrected if enough information is present for execute module **1732** to make corrections.

15 When user input is received as EHBDL **1714**, encryption/decryption modules **1706** decrypt the information to form HBDL **1716**. HBDL **1716** is the user input in an un-encrypted form of HBDL, which is received by registration modules **1702**. Registration module **1726** registers and validates each of the
20 users that return user input. This registration module ensures that only authorized or registered users are allowed to return input into the system. For example, registration module **1726** may validate the password for a particular user.

Once a user is validated, the user input in HBDL **1716** is
25 passed on to input module **1724**. Input module **1724** acts as a focal point to centralize all forms of input and send the input with specific instructions to dispatcher module **1722**. Input module **1724** may add instructions needed by dispatcher module **1722** to process the input. The input defines what to change in
30 the source code in these examples.

The specific instructions include instructions, such as, instructions regarding what portions of the source code can be modified by a particular user in these examples. For example, if the user input modifies a definition, the instruction tells

what portion of the source code is to be modified. The portion of the source code to be modified by the input may be identified using the identification of the user generating the input and the input itself.

5 Then, dispatcher module **1722** ensures that the appropriate section of source code is rewritten when HBDL **1720** is sent back to the source code. Dispatcher module **1722** determines whether to write to the source code using a policy with the identification of the user, the input, and the portion of the
10 source code to be written. The policy is a set of rules used to determine whether writes should be made to the source code in response to the input. This policy provides a redundancy to prevent cases in which an unauthorized user may get past registration module **1726**. For example, an unauthorized user may
15 spoof a real user and submit input. The policy may identify the input as changes that are not to be made by the real user or not characteristic of the input made by the real user. In this case, the input is rejected by dispatcher module **1722**.

 In these examples, each user has their own set of actions
20 that the user may add to or modify. As a result, users can only modify the action segment of the source code. The output, HBDL **1718**, from execute module **1732**, may be used to rewrite the definitions as well as actions. In these examples, language interpreter **1704** is also considered another user in the system.
25 The interpreter, however, is a permanently authenticated user. Dispatcher module **1722** sees language interpreter **1704** as such to rewrite definitions using HBDL **1718**.

 As a result, at any given point of the simulation, a real human end user may replace any defined human in the database.
30 Through this data flow, interpreter **1700** may rewrite or alter the source code. As time passes and simulations are run, definitions are constantly being generated for rewriting the source code.

Input module **1724** provides a connection between the "virtual world" being executed in the simulation and the "real world" as being received through user input by users at devices in communication with the system. Dispatcher module **1722**
5 provides a mechanism to write new definitions to modify the source code.

Turning next to **Figure 18**, a diagram illustrating the data flow for a lexical analyzer is depicted in accordance with an advantageous embodiment. As illustrated, lexical analyzer
10 **1800** receives source **1802** and processes source **1802** to generate tokens **1804**. Lexical analyzer **1800** is an example of lexical analyzer **1728** in **Figure 17**. Lexical analyzer **1800** reads the content from source **1802** character by character and groups the incoming characters from source **1802** into basic units referred
15 to as tokens, such as tokens **1804**.

The grouping of characters in source **1802** into tokens **1804** is performed in these illustrative examples using a set of token descriptions in regular expressions **1806**. Regular expressions **1806** contains the descriptions needed to group
20 characters in source **1802** into tokens **1804**. In these examples, regular expressions **1806** may be implemented using scripts. These scripts use symbols of a language that describes character patterns for use in grouping characters into tokens.

Each regular expression defined in regular expressions
25 **1806** is assigned a symbol. This symbol typically is a number. The token generated in tokens **1804** by lexical analyzer **1800** is identified using the symbol for the particular regular expression in regular expressions **1806**.

In addition to regular expressions **1806**, lexical analyzer
30 **1800** also uses reserved words **1808**. Words within reserved words **1808** also are assigned a symbol when a token is identified within source **1802**. A reserved word is a word that has special grammatical meaning to a language and cannot be used as an identifier in that language.

Turning now to **Figure 19**, a diagram illustrating parsing or syntax analysis performed by a grammar parser is depicted in accordance with an advantageous embodiment. The parsing illustrated in **Figure 19** may be performed by grammar parser **1730** in **Figure 17**. Tree **1900** is an example of a parse tree that may be used by a grammar parser to group tokens. In this example, parsing of statement **1902** is illustrated. Statement **1902** is var1=20. This statement is used to manage or define actions to be carried out by the interpreter.

In particular, the grammar parser identifies relationships between tokens produced by the lexical analyzer based on a set of syntactic constructs also called productions. Each production represents a logical unit and is typically defined in terms of tokens in other logical units. Most languages define two broad types of logical units. These logical units are statements and expressions in these examples. Expressions are usually syntactic language constructs that provide values. Statements are syntactic constructs that change the state of variables, control the flow of the program, or perform other operations supported by the language.

The grammar parser groups the stream of tokens into logical units and instructs the execute module to execute actions based on the logical units. In this example, statement **1902** contains a stream of tokens produced by the lexical analyzer. These tokens are varname **1904**, EQ **1906**, expression **1908**, and NL **1910**. Expression **1908** contains an integer, INT **1912**. The value for varname **1904** is var1; the value for EQ **1906** is =; the value for INT **1912** is 20; and the value for NL **1910** is \n. As can be seen, given a stream of tokens, the grammar parser regenerates the grammar based on the sequence of tokens in the stream.

Turning now to **Figure 20**, a diagram illustrating another example of a parse tree is depicted in accordance with an advantageous embodiment. In this example, parse tree **2000** is

generated from statement **2002**. Statement **2002**, in this example, is $\text{output}=\text{var1}+\text{var2}*\text{var3}$.

In this example, tokens for statement **2002** include varname **2004**, EQ **2006**, varname **2008**, plus **2010**, varname **2012**,
 5 MUL **2014**, varname **2016**, and NL **2018**. Varname **2004** has a value output; EQ **2006** has a value =; varname **2008** has a value var1; plus **2010** has a value +; varname **2012** has a value var2; MUL **2014** has a value *; varname **2016** has a value var3; and NL **2018** has a value \n. The expression on the other side of the = sign for
 10 statement **2002** is defined by tokens varname **2008**, plus **2010**, varname **2012**, MUL **2014**, and varname **2016**.

The identification of these expressions and their usage in the language is indicated within parse tree **2000** through the location of these tokens with respect to identifying nodes. For
 15 example, expression **2020** indicates that expressions **2022** and **2026** are operated upon using operator **2024**. In this case, operator **2024** is plus **2010**. Expression **2020** also includes expression **2026**, which identifies expressions **2028** and **2030** as being operated upon using operator **2032**. In this example,
 20 expression **2022** contains varname **2008**, while expression **2026** includes the results of applying operator **2032** to expressions **2028** and **2030**.

Turning now to **Figure 21**, a diagram of a execute module in an interpreter is depicted in accordance with an advantageous
 25 embodiment. In this example, execute module **2100** is a more detailed illustration of execute module **1732** in **Figure 17**. As illustrated, execute module **2100** includes master timeline control module **2102**, math module **2104**, physics module **2106**, artificial intelligence (AI) module **2108**, report generator **2110**,
 30 and graphics module **2112**.

Master timeline control module **2102** is a scheduler that is used to apply events to the definitions over time within execute module **2100**. Math module **2104** and physics module **2106** provide for calculations needed to determine effects of actions

on different objects. Artificial intelligence module **2108** is a component used to run source code for different artificial intelligence components to aid in the simulation of human behavior as events are applied to definitions by master timeline control module **2102**.

Graphics module **2112** generates graphics data to send to the GUI processor for presentation at the end devices. Report generator **2110** generates two types of outputs in these examples. One type of output is a new definition that is used to modify the source code. This output generated is, for example, HBDL **1718** in **Figure 17**. The other type of output generated by report generator **2110** is the graphics data, which also is formatted in HBDL in these examples. This output is, for example, IHBDL **1710** in **Figure 17**.

Graphics module **2112** includes a number of different types of processes used to generate output representing results of a simulation to a user. These types of processes include, two dimensional graphics pipelines, two dimensional graphics primitives, three dimensional graphics pipelines, three dimensional graphics primitives, two dimensional and three dimensional model and stacks, a display list generator, and two dimensional and three dimensional rendering engines. These, as well as other types of graphics processes, may be present in graphics module **2112** for use in generating output for presentation to a user.

Turning now to **Figure 22**, a flowchart of a process for generating tokens is depicted in accordance with an advantageous embodiment. The process illustrated in **Figure 22** may be implemented in a software component, such as lexical analyzer **1728** in **Figure 17**.

The process begins by receiving the next character from the source (operation **2200**). In these examples, the source of characters is HBDL **1708** in **Figure 17**. The character is placed into a queue (operation **2202**).

Next, a determination is made as to whether a match is present between the string in the queue and regular expression or a reserved word (operation **2204**). If a match is present, a token is created using the string in the queue (operation **2206**).

5 The queue is then cleared (operation **2208**).

Thereafter, a determination is made as to whether an end of file has been reached in the source (operation **2210**). If an end of file has been reached, the process terminates.

Otherwise, the process returns to operation **2200** to obtain the next character. If a string match does not occur in operation **2204**, the process proceeds to operation **2210** as described above.

Turning now to **Figure 23**, a flowchart of a process for executing the simulation of human behavior is depicted in accordance with an advantageous embodiment. The process illustrated is **Figure 23**, may be implemented in a framework, such as framework **400** in **Figure 4**. In particular, this simulation may be executed using source code, such as source code **600** in **Figure 6**.

The process begins by populating a virtual environment with a set of humans defined in a definition within a source code (operation **2300**). In these examples, the definition is a definition, such as definition **602** in **Figure 6**. The process executes a set of actions on the set of humans in the virtual environment using actions within the source code to form a result that simulates the human behavior (operation **2302**). In these examples, the set of actions may be taken from actions, such as actions **604** in **Figure 6**.

Thereafter, an output is generated from the result using graphical interface language in the source code to form a formatted output (operation **2304**). In these examples, the graphical user interface language may be GUI language **606** in **Figure 6**. Thereafter, the formatted output is presented on a set of devices in the network data processing system as the

simulation occurs (operation **2306**), with the process terminating thereafter.

In this manner, the different advantageous embodiments simulate human behavior through a source code that may change as the simulation occurs. Further, the graphical user interface language allows for the manner in results are presented to a user to change and be controlled by the simulation itself.

Turning now to **Figure 24**, a flowchart of a process for generating sentences or productions is depicted in accordance with an advantageous embodiment. The process illustrated in **Figure 19** may be implemented in a software component, such as grammar parser **1730** in **Figure 17**.

The process begins by obtaining the next token for processing (operation **2400**). In these examples, the token is received from a lexical parser, such as lexical parser **1728** in **Figure 17**. A determination is made as to whether an end of file has been encountered with respect to the token (operation **2402**). If an end of file has not been encountered, a determination is made as to whether the token fits into a parse tree (operation **2404**). If the token does not fit into a parse tree, an error is generated (operation **2406**) with the processing then returning to operation **2400**.

Otherwise, a determination is made as to whether the token completes a parse tree (operation **2408**). If the token completes the parse tree, execution of instructions for a production corresponding to the completed parse tree occurs (operation **2410**). Thereafter, the process recursively returns to the caller (operation **2412**) with the process then returning to operation **2400** as described above.

With reference again to operation **2408**, if the parse tree is not complete, the process also returns to operation **2400**. With reference back to operation **2402**, if an end of file has been reached, a determination is made as to whether the grammar has been partially regenerated (operation **2414**). This operation

is performed to determine whether incomplete statements or productions are present. This determination may be made by examining the parse trees to see if incomplete parse trees are present. If the grammar is partially regenerated, an error is generated (operation **2416**) with the process terminating thereafter. Otherwise, the process terminates without generating an error.

Turning now to **Figure 25**, a flowchart of a process for executing statements for productions is depicted in accordance with an advantageous embodiment. The process illustrated in **Figure 25** may be implemented in a software component, such as execute module **1732** in **Figure 17**.

The process begins by performing semantic analysis on the set of instructions for a production (operation **2500**). This operation is performed to determine whether semantic errors occur in any instructions for a production. The set of instructions is one or more instructions in these examples. Thereafter, a determination is made as to whether a semantic error is present (operation **2502**).

If a semantic error is not present, the process executes the set of instructions (operation **2504**) with the process terminating thereafter. If in operation **2502** a semantic error occurs, the error is reported (operation **2506**) with the process terminating thereafter. In some cases, rather than terminating, the process may attempt to correct the error to allow for execution of the instructions.

Turning now to **Figure 26**, a diagram illustrating a graphical user interface (GUI) processor is depicted in accordance with an advantageous embodiment. GUI processor **2600** is a more detailed illustration of GUI processor **406** in **Figure 4**. In this example, GUI processor **2600** includes encryption/decryption modules **2602**, graphics module **2604**, output module **2606**, input module **2608**, and HBDL generator **2610**.

In these illustrative examples, GUI processor 2600 executes statements received from source code, such as source code 600 in **Figure 6**. In particular, the statements include those from GUI language 606 in source code 600 in **Figure 6**. The actual code for generating the displays are found in these sources, rather than being a separate application.

GUI processor 2600 executes the statements and receives user input. GUI processor 2600 receives encrypted interpreted HBDL (EIHBDL) 2612 from an interpreter such as interpreter 1700 in **Figure 17**. Encryption/decryption module 2602 decrypts information to form interpreted HBDL (IHBDL) 2614, which is processed by graphics module 2604. In these examples, IHBDL 2614 represents primitives or a set of statements that may be used to generate the display for devices 2618.

Graphics module 2604 may generate the pixels for display in the devices 2618 and send that data to output module 2606, which in turn, transmits the data as device 2616 to devices 2618. User input is received as device 2620 from devices 2618 by input module 2608. This module sends the device data to HBDL generator 2610, which represents this user input in the form of HBDL 2622. HBDL 2622 is the user input written in HBDL. This input is encrypted by encryption/decryption module 2602 and returned to the interpreter as encrypted HBDL (EHBDL) 2624.

In these illustrative examples, GUI processor 2600 executes on hardware that is close to devices 2618. In fact, in many cases a portion of GUI processor 2600 may actually execute on devices 2618 with another portion executing on a data processing system, such as a server. GUI processor 2600 is located close to devices 2618 in a manner to reduce the use of network resources needed to present the data. Further, the placement of GUI processor 2600 is made in these examples to reduce latency in displaying data and receiving user input.

Turning now to **Figure 27**, a flowchart of a diagram illustrating data flow through a graphical user interface (GUI)

processor is depicted in accordance with an advantageous embodiment. In this example, graphics module 2700 is an example of graphics module 2604 in **Figure 26**. Graphics module 2700 receives interpreted HBDL in the form of primitives 2702 in these examples. These primitives are the results of interpretation of the source code by the interpreter.

Graphics module 2700 processes these primitives to generate pixels for bitmaps and data identifying how the bitmaps may be manipulated or displayed. This information is sent as bitmap data 2704 to client process 2706. In these examples, client process 2706 is a process executing on a device, such as those in devices 1918 in **Figure 19**. This client process performs the operations needed to display the bitmap data on display 2708. In this manner, the graphics processing necessary to render images for display are executed by graphics module 2700. Client process 2706 only displays the bitmap data provided and does not need the different processes and processing power needed to render bitmap graphics from primitives. With this division of processing, the devices displaying the data do not need the different graphic processors and graphics pipelines used in rendering graphics such as those used in workstations.

As a result, graphics may be displayed on a number of different devices that normally do not have sufficient processing power to handle the primitives. For example, client process 2706 and display 2708 may be implemented in a mobile phone, personal digital assistant, or tablet PC.

Input device 2710 receives user input with respect to data being displayed in display 2708. This user input may manipulate graphics, such as selecting a button, entering data, or sending a command. When a user modifies the displayed image through manipulating the bitmaps on display 2708, the difference or changes in the modification of the image being displayed are identified by client process 2706. These differences in the

image form difference data **2712**, which is returned to HBDL generator **2714**.

HBDL generator **2714** is similar to HBDL generator **2610** in **Figure 26**. HBDL generator **2210** identifies this change or delta in information and translates it into HBDL **2716** for transmission to the interpreter. HBDL **2716** contains statements or code in the language of the source code module and may be used to make changes to the source code. Graphics module **2700** uses primitives **2702** to generate pixels for the different bitmaps.

Turning now to **Figure 28**, a diagram illustrating manipulation of a display is depicted in accordance with an advantageous embodiment. In this illustrative example, display **2800** is an example of a display presented at display **2708** in **Figure 27**. Display **2800** is presented using bitmaps generated from primitives. In this example, bitmaps are used to represent different components, such as slider **2802**, and field **2804**. The bitmap data used to represent slider **2802** and field **2804** are sent with data indicating how these bitmaps may be manipulated. In this example, slider **2802** may be moved through user input from position **2806** in **Figure 28** to position **2900** within display **2902** in **Figure 29**, which is a modified version of display **2800**. Further, a value, such as fifty may be entered into field **2804** as depicted in display **2902** in **Figure 29**. These changes in the bitmaps are returned in accordance with an advantageous embodiment to the GUI processor, which then generates an appropriate statement for the source code based on these changes.

Turning now to **Figure 30**, a flowchart of a process for identifying changes in bitmaps is depicted in accordance with an advantageous embodiment. The process illustrated in **Figure 30** is an example of the process that may be implemented in a client process at a device, such as client process **2706** in **Figure 27**.

The process begins by monitoring for user input (operation **3000**). A determination is then made as to whether

user input is detected with respect to the display (operation 3002). If user input is not detected, the process returns to operation 3000. Otherwise, a determination is made as to whether the user input manipulates a control (operation 3004).

5 If the user input manipulates a control, the change made to the control is identified in the bitmap (operation 3006). This difference or change in the bitmap is sent back to the GUI processor (operation 3008) with the process then returning to operation 3000 to monitor for additional user input. The data
10 change may be the actual bitmap that is changed or an identification of the change in position of the bitmap, depending on the particular implementation. Of course, other types of changes may be used depending on the embodiment.

With reference again to operation 3004, if the user input
15 is not a manipulation of a control, a determination is made as to whether the user input is an entry of data into a field (operation 3010). If the user input is not an entry of data, the process returns to operation 3000. Otherwise, the process proceeds to (operation 3006) to identify the change made in the
20 bitmap.

The particular decisions made with respect to user input, in these examples, are ones for identifying changes to fields and controls in a display, such as execute module 2100 in **Figure 21**. A determination may be for any type of change to a bitmap
25 of interest. For example, the change may be whether a particular button has been selected or turned.

Turning now to **Figure 31**, a flowchart of a process for handling difference data is depicted in accordance with an advantageous embodiment. The process illustrated in **Figure 31**
30 may be implemented in a GUI processor, such as GUI processor 2600 in **Figure 26**. In particular, the process illustrated in **Figure 31** may be implemented in HBDL generator 2714 in **Figure 27**.

The process begins by receiving the difference data from a client process (operation **3100**). In these examples, the difference data contains the changes in a bitmap made through user input. The process then identifies the user input based on the difference (operation **3102**). This user input may be identified as, for example, a change of a slider position, an entry of data into a data field, or some other user input. The identification made in operation **3102** may be made by comparing the original bitmap sent to the device with the changed bitmap. For example, the user input may be to change the timeliness of a human if the difference is identified as a movement of a slider upwards along this type of control. An example of this type of difference is illustrated in **Figure 21** with respect to execute module **2100**.

Thereafter, the user input is converted into a format used by the source code (operation **3104**). In these examples, the user input is changed into a HPDL format. The converted user input is sent to the interpreter (operation **3106**) with the process terminating thereafter.

With reference now to **Figure 32**, a diagram illustrating components for use in providing a human transparency paradigm is depicted in accordance with an advantageous embodiment. In this illustrative example, simulation **3200** is executed using a framework, such as framework **400** in **Figure 4**. In particular, simulation **3200** is executed through the interpretation of the source code by an interpreter, such as interpreter **404** in **Figure 4**.

In this particular example, simulation **3200** includes artificial intelligence (AI) **3202**, which represents a human within simulation **3200**. This human being executed by artificial intelligence **3202** is a synthetic human in these examples. The code for artificial intelligence **3202** is retrieved from definition **3204** in addition to other information that is used for simulation **3200**. Definition **3204** is found in source code,

such as source code 402 in **Figure 4**. Definition 3204 includes the definition of the synthetic human as well as other humans and the environment in which the humans are present for simulation 3200.

5 As results are generated during simulation 3200, these results are sent to communication modules 3206 as user input 3208. These communications modules, in this example, are also found in an interpreter, such as interpreter 404 in **Figure 4**. Communication modules 3206 takes user input 3208 from simulation
10 3200 and modifies or writes new definitions into definition 3204. This forms modified source code, which is then used by simulation 3200 to produce additional results. Artificial intelligence 3202 logs into the framework in the same manner as a live user in these examples.

15 Further, results 3210 from simulation 3200 are sent to device 3212 for presentation to user 3214. In these examples, user 3214 is a real human.

 The illustrative embodiments allow for the use of a human transparency paradigm. In this paradigm, user input 3208,
20 generated by artificial intelligence 3202 that is rewritten into definition 3204, may be replaced with live user input from user 3214. In other words, user 3214 may send user input 3216 to communication modules 3206 to modify or write new definitions into definition 3204 in place of user input 3208, generated by
25 the synthetic human simulated through artificial intelligence 3202 within simulation 3200. In these examples, user 3214 may be a subject matter expert, providing user input 3216. In these examples, user input 3216 is provided during simulation 3200. This user input may be in response to results received and
30 presented at device 3212.

 The synthetic human, simulated by artificial intelligence 3202, generates user input 3208 that is associated with unique identifier (UI) 3218 for the synthetic human. User input 3208 is generated by artificial intelligence 3202 during simulation

3200. User input 3216 is associated with unique identifier
3218. User input 3208 is sent to communication modules 3206.
Communication modules 3206 modify definition 3204 by adding new
definitions or modifying current definitions using user input
5 3208. Communication modules 3206 knows which portion of
definition 3204 to modify based on unique identifier 3218.

When user 3214 generates user input 3216, user input 3216
is received by communication modules 3206. In these
illustrative examples, user input 3216 also may include unique
10 identifier 3218. In this manner, communication modules 3206
modifies definition 3204 for the synthetic human associated with
unique identifier 3218.

In this manner, user 3214 may replace the synthetic human
simulated through artificial intelligence 3202 within simulation
15 3200. User 3214 may turn artificial intelligence 3202 on and
off on the fly, based on requests sent to communication modules
3206.

In initiating a replacement of user input 3208 with user
input 3216, user 3214 at device 3212 sends a request to
20 communication modules 3206. At this point, user 3214 is assumed
to have logged on and have been authenticated by communication
modules 3206. Communication modules 3206 determines whether
user 3214 is authorized to turn on and off artificial
intelligence 3202. In other words, communication modules 3206
25 determines whether user 3214 may replace the synthetic human.
If user 3214 is authorized, communication modules 3206 sets a
flag to stop using artificial intelligence 3202. In other
words, functions for artificial intelligence 3202 are no longer
called within simulation 3200.

30 At this point in time, user 3214 generates user input
3216 that includes unique identifier 3218. Depending on the
particular implementation, unique identifier 3218 may be added
by communication modules 3206 based on recognizing that user
3214 sends user input at device 3212.

With reference now to **Figure 33**, a flowchart of a process for replacing a synthetic human with a live human is depicted in accordance with an advantageous embodiment. In this example, the process illustrated in **Figure 33** may be implemented in an interpreter, such as interpreter **404** in **Figure 4**. In particular, the process may be implemented in communication modules within interpreter **404**.

The process begins by receiving a request from a user to replace a synthetic human (operation **3300**). Thereafter, a determination is made as to whether the user is authorized to replace the simulated human (operation **3302**). In these examples, the determination may be made by comparing the user with a list or database defining what users may replace synthetic humans during a simulation. For example, certain users may be subject matter experts in certain areas and allowed to replace synthetic humans for those particular areas. For example, a particular user may be a subject matter expert with respect to politics. That user may be allowed to replace a synthetic human that is a politician in the simulation. That subject matter user, however, may not be allowed to replace a synthetic human that is a farmer or a soldier because the subject matter expert does not have expertise in those areas.

The particular rules for what users may replace synthetic humans depend entirely on the particular implementation. If the user is authorized to replace the synthetic human, the use of the artificial intelligence for the synthetic human is turned off in the definitions (operation **3304**).

Thereafter, the process waits for user input from the user (operation **3306**). When user input is received, a determination is made as to whether the user input is to write a new definition in the definitions (operation **3308**). If the user input is to write a new definition, the user input is formatted into a form for writing the new definition (operation **3310**). Thereafter, the definition is written into the source code

(operation **3312**) with the process then returning to operation **3306** as described above.

With reference again to operation **3308**, if the user input is not to write a new definition, a determination is made as to whether the user input is to turn on the artificial intelligence (operation **3314**). If the user input is not to turn on the artificial intelligence, the process returns to operation **3306**. Otherwise, the artificial intelligence is turned back on for use in simulating the synthetic human (operation **3316**) with the process terminating thereafter. Operation **3316** places the synthetic human back in place in a simulation and removes the live human from the simulation.

With reference again to operation **3302**, if the user is not authorized to replace the synthetic human, an error message is generated (operation **3318**) with the process terminating thereafter.

The simulations provided by the framework are not intended predict human behavior with one-hundred percent certainly, but are intended to provide probabilities that may decisions or changes. The results from simulations provide guidance and predictions that are otherwise not possible without the simulations made by framework.

In the different advantageous embodiments, source code **600** may be implemented using a language specifically designed to provide the different features in definition **602**, actions **604**, and GUI language **606** in **Figure 6**. In other advantageous embodiments, source code **600** in **Figure 6** also may include functions and features from other existing languages or programming methodologies.

In the different advantageous embodiments, artificial intelligence systems may be used to implement portions of source code **600**, such as, for example, definition **602** and/or actions **604** in **Figure 6**. In some advantageous embodiments, artificial intelligence, in the form of a neural network (or other forms of

artificial intelligence), may be used to simulate various objects. For example, a neural network may be used to simulate a living or live object, such as a person or an animal.

The artificial intelligence may be, for example,
5 conventional artificial intelligence in which machine learning characterized by formalism and statistical analysis is used. Additionally, artificial intelligence may be, for example, in the form of computational intelligence. Computational intelligence involves an iterative development or learning.
10 This type of artificial intelligence may learn based on empirical data. Examples of computational intelligence include, for example, without limitation, neural networks, fuzzy logic, and genetic algorithms. These programming techniques may be used to supplement or provide additional features within source
15 code 600 in **Figure 6**. In other advantageous embodiments, source code 600 in **Figure 6** may be implemented using an existing programming language in addition to or in conjunction with various programming techniques.

In one advantageous embodiment, a programming technique
20 such as a neural network may be used to implement portions of source code 600 in **Figure 6**. For example, portions or all of definition 602 in **Figure 6** may be implemented using neural networks. A neural network is a mathematical computational model based on biological neural networks. Neural networks
25 provide non-linear statistical data modeling pools and may be used to model complex relationships between inputs and outputs. Neural networks may be employed to provide learning functions for various objects within definition 602 in **Figure 6**.

In one example, neural network techniques may be used to
30 provide learning features for different objects such as people, animals, or other suitable objects within definition 602 of source code 600 in **Figure 6**. In this type of example, NN denotes a neural network type variable. An example of declaration may be "NN n;". This type of statement declares a

neural network variable, in this example. Children, n.input, n.output, and n.hidden also may be created. These other variables represent input, output, and hidden layers in the neural network. These layers allow a user to add neurons to the different layers. With these different layers, input neurons may be added as children to the input neural network layer.

Turning to **Figure 34**, statements **3400** and **3402** are examples of input neurons. Section **3404** in statement **3400** declares "left operand" as an input neuron for the neural network n. This input member also may be used to read the total number of input neurons. The value of the member "input" is incremented by one each time a new member is added. As a result, the input value is the total number of input neurons. These statements are examples of HBDL pseudo code that could be implemented using C language. Other languages, such as, for example, C+ and/or Objective-C.

In these examples, input neuron variables may range from a value of zero to a value of one. Each input neuron variable has a minimum range and a maximum range. These ranges allow a user to enter any value within the range. These values also may be normalized before use, depending on the particular implementation.

With reference to **Figure 35**, statements **3500** and **3502** are examples of input ranges defined for the input neuron left operand. In this example, statement **3500** defines a minimum value of minus ten and statement **3502** defines a maximum value of ten.

With reference now to **Figure 36**, a diagram of a statement for input behavior is depicted in accordance with an advantageous embodiment. Statement **3600** allows an input neuron to be modified before the input neuron is used. In other words, an input neuron may have code attached or associated with the neuron to allow manipulation of the user input by that neuron. For example, the user input may be short and long. In this

example, the neuron input behavior interprets short and long to evaluate between zero and one. Statement **3600** is an example of a code that may be used to attach this type of behavior to the input neuron.

5 Turning next to **Figure 37**, a diagram illustrating an output declaration is depicted in accordance with an advantageous embodiment. Statement **3700** is an example of a statement used to add children to the output neural network layer.

10 With reference now to **Figure 38**, a diagram illustrating statements for output ranges in a neural network is depicted in accordance with an advantageous embodiment. In this example, statements **3800** and **3802** are examples of ranges that may be set for an output neuron. A minimum and maximum range is set by
15 statements **3800** and **3802**.

In this particular example, the minimum value is minus fifty while the maximum value is fifty for the output neuron. Further, a user may convert an implicit normalized output to a value within the specified ranges. For example, an output of
20 one may be converted to 50, while an output of 0.5 is converted to 0. Further, an output neuron also may be associated with the code to manipulate the output.

Turning now to **Figure 39**, a diagram illustrating a statement for modifying output behavior is depicted in
25 accordance with an advantageous embodiment. Statement **3900** is an example of code that may be associated with an output neuron. In this example, the user output may be low and high. With this particular example, the output behavior of the neuron may interpret a value between zero and one to low and high.

30 Turning now to **Figure 40**, a diagram illustrating statements for hidden layers is depicted in accordance with an advantageous embodiment. Statements **4000** and **4002** are examples of statements that may be used to declare hidden layers of any neural network. A hidden layer order follows the order of

hidden layer declarations, in these examples. The value of a hidden layer variable specifies the number of neurons assigned to a particular hidden layer. Statements **4000** and **4002** declare two hidden layers, in these examples. The first layer defined
5 by statement **4000** includes five neurons and the second layer declared in statement **4002** defines three neurons.

With reference now to **Figure 41**, code **4100** illustrates a sample neural network member being used to specify a neural sample value. Different samples may be specified. Each input
10 and output neuron includes "sample [int]" within the statements. When a neural network is completed, a user may train and use the neural network.

With reference now to **Figure 42**, example statements for training a neural network are depicted in accordance with an
15 advantageous embodiment. Statements **4200**, **4202**, and **4204** are examples of statements used to perform neural network training. Statement **4200** indicates that the neural network will be trained 500 times. Statement **4202** indicates 300 times, and statement **4204** indicates 200 times for the training. In these examples,
20 the training is cumulative with results being stored. These different results may be stored within definition **602** or source code **602** in **Figure 6** for a particular object.

Turning now to **Figure 43**, a diagram illustrating a compute function in a neural network is depicted in accordance
25 with an advantageous embodiment. In this example, statement **4300** and statement **4302** provide an example of statements used to have the input neuron perform a function and return a result. Statement **4304** is an alternative expression of statements **4300** and **4302**, in these examples.

30 With reference now to **Figure 44**, a diagram illustrating an example of a neural network is depicted in accordance with an advantageous embodiment. In this example, code **4400** includes a definition of a neural network along with statements to train and execute the neural network. Input declarations are found in

section **4402**. Input ranges are found in sections **4404** and **4406**. Code associated with neurons are found in statements **4408** and **4410**. Output ranges are found in section **4412** and behavior for the output is found in statement **4414**.

5 Hidden layers are defined in section **4416** and the functionality is found in statement **4418**. Samples may be found in section **4420** and statement **4422** is an example of a training statement. Section **4424** illustrates examples of statements used to operate the neural network. Statement **4426** within section
10 **4424** displays the results.

Turning now to **Figure 45**, a diagram illustrating the results from the operation of a neural network is depicted in accordance with an advantageous embodiment. In this example, display **4500** is an example of a display generated in response to
15 a show statement **4426** from code **4400** in **Figure 44**.

In addition to neural networks, dynamic lists may be used to manage various attributes and properties of objects within definition **602** in **Figure 6**. Dynamic lists may be used to define characteristics, such as characteristics **804** in object **800** in
20 **Figure 8** and characteristics **904** for object **900** in **Figure 9**.

For example, dynamic lists may be used to provide an identification of components, capabilities, characteristics, or other suitable parameters for an object. For example, if an object is a car, a dynamic list may be used to identify
25 components, such as wheels, engine, body, paint, transmission, windows, and other components. As components are added to or removed from a car, the list may be modified to identify these changes.

In the different advantageous embodiments, any variable
30 may be used in a list. With a dynamic list, definitions are not constrained by having to predefine list sizes based on expected components or parameters. Instead, the list size may change as various parameters or components are added or removed from a particular definition.

With reference to **Figure 46**, a diagram illustrating an example of a list is depicted in accordance with an advantageous embodiment. In this example, code **4600** defines a list one in statement **4600**. Statements **4602**, **4604**, and **4606** identify three
5 variables with values in list one. In this example, list one acts as an array. Statement **4608** in code **4600** is an example of a size function that returns a value identifying the size of the array. In this example, statement **4608** returns a value of three.

10 Statements **4610** and **4612** are examples of statements used to search the list in code **4600**. Statement **4610** returns a value of two which is equivalent to true, while statement **4612** returns a value of zero which is equivalent to false. These search functions in statements **4610** and **4612** may be used to determine
15 whether the list contains a certain value. If the certain value is present in the list, the index to that value in the list is returned. Otherwise, a value of zero is returned.

Turning now to **Figure 47**, a diagram illustrating deleting a variable from the list is depicted in accordance with an
20 advantageous embodiment. In this example, code **4700** includes a list as defined in section **4702**. Statement **4704** is a delete function that may be used to delete an item from the list in code **4700**. Statement **4704** searches the list to determine whether a particular item is present in the list. If the item
25 is found, the item is removed from the list. Statement **4704** returns an index identifying the item removed. Otherwise, statement **4704** returns a zero. In this example, the value twenty-five is not present in the list in code **4700**, a zero is returned, and no action is taken. In this example, items are
30 deleted by identifying values.

With reference now to **Figure 48**, a diagram of code for deleting items is depicted in accordance with an advantageous embodiment. In this example, code **4800** defines a list in section **4802**. Statements **4804** and **4806** are statements used to

delete items in the list based on index values. If a statement identifies an index value less than the list size, the item is located in the list and deleted. The function then returns a value for the deleted item. Otherwise, a zero is returned

5 meaning that the item was not found in the list. Statement **4804** returns a zero because only three items are present in the list as defined in section **4802**. Statement **4806** results in a twenty being returned with the item defined in statement **4808** being deleted.

10 With reference now to **Figure 49**, a diagram illustrating code to manipulate items in the list is depicted in accordance with an advantageous embodiment. In this example, code **4900** may be used to manipulate items in a list. In these examples, code **4900** contains push and pop functions to use the list of the
15 stack. Statement **4902** identifies the list for which manipulations are to be made. In this example, section **4904** identifies three pushes made to the list. Statement **4906** illustrates a pop made to the list. Statement **4906** returns a value from the item popped from the front of the list.

20 These types of functions are similar to those used to manipulate stacks in computer systems. A push is used to push or move a particular item to the top of the list. A pop is used to return a value for the item at the top of the list. If a pop statement includes a value or parameter, this statement pops or
25 returns values from the stack according to the value of the parameter. In statement **4908**, the item being popped is the item that has an index value of three, which is the third item in the list, in these examples.

Turning now to **Figure 50**, a diagram illustrating the use
30 of the list as a queue is depicted in accordance with an advantageous embodiment. In this example, code **5000** illustrates enqueue and dequeue functions that may be used to manipulate a list as a queue. An enqueue function, such as that shown in statement **5002**, adds an argument to the bottom of the list.

A dequeue function, such as that shown in statement **5004**, removes the top item from the list and returns a value of that item. In this example, statement **5002** adds an item to list one, statement **5006** adds another item to the top of the queue. The
5 item in statement **5002** is now second in the queue. Statement **5008** adds yet another item to the queue pushing the other items lower into the queue.

Turning now to **Figure 51**, a diagram illustrating reading items in the list is depicted in accordance with an advantageous
10 embodiment. In this example, code **5100** illustrates reading items from the top and bottom of the list as defined in section **5102**. Statement **5104** reads the item located at the top of the list and statement **5106** reads the item contained at the bottom of the list.

15 Turning now to **Figure 52**, a diagram illustrating a sort attribute in a list is depicted in accordance with an advantageous embodiment. Code **5200** contains statements used to identify the sorting status for a list. Statement **5202** identifies whether a sorting status is set for the list. If
20 statement **5202** is set equal to true, then items are inserted into the list according to their value. Statement **5204** identifies a sorting order.

If statement **5204** is set equal to true, the list is sorted in descending order from smallest to largest. In this
25 example, statement **5204** is set equal to false. As a result, items are added to the list in descending order as shown in section **5206**. Further, additional statements may be used to sort the list in various orders.

Another example of a programming technique that may be
30 used to implement source code **600** in **Figure 6** is fuzzy logic. An example of a language used to implement fuzzy logic is Prolog, which is a logic programming language that may be used for fuzzy logic and artificial intelligence programming.

In the depicted examples, the fuzzy logic system may be based on logical statements in which operands are terms taken from several sets. In one example, the sets may be, for example, fuel, distance, and speed. Fuel may contain three
5 terms, low, medium, and high. Distance may be near and far. Speed may be low, medium, and high, in these examples. These sets may be used to apply rules, such as if the fuel is low or the distance is near, then the speed is low. Another rule is if the fuel is medium and the distance is far, then the speed is
10 medium. A third rule is if the fuel is high and the distance is far, then the speed is high. With fuzzy logic, ranges may be set for the different members of the set. These ranges include a minimum and a maximum range.

Turning now to **Figure 53**, an example of a fuzzy logic
15 implementation using fuel distance and speed is depicted in accordance with an advantageous embodiment. In this example, code **5300** defines these sets in section **5302**. The fuel integer, while distance and speed are floating variables. Section **5304** identifies a minimum and maximum range for the fuel as being
20 between 0 and 100.

Starting and ending terms for the fuel are defined in section **5306**. This section identifies the left and right edges of a fuzzy set. Sections **5308**, **5310**, and **5312** identify terms for the fuel. Section **5308** identifies a trapezoid term, section
25 **5310** identifies a triangular term, and section **5312** identifies a bell curve term.

Similar definitions for distance are found in section **5314**. The rules for the fuzzy logic are defined in section **5316**, in this example. Section **5318** identifies the initial
30 values for fuel and distance. Statement **5320** is used to compute the speed.

Another type of programming technique that may be used to simulate various objects within source code **600** in **Figure 6** involves evolutionary computation. Evolutionary computation is

a type of artificial intelligence. One specific method or methodology is a genetic algorithm. This algorithm is a search technique used to identify solutions. This type of technique is considered a global search heuristic type of technique. With a genetic algorithm, genes may be declared as well as chromosomes. Fitness function, selection process, and recombination functions also are specified using this type of technique.

Turning now to **Figure 54**, a diagram illustrating the solving of an equation using a genetic algorithm is depicted in accordance with an advantageous embodiment. In this example, code **5400** is used to solve equation $2X+3Y=20$.

In this example, two genes are initialized in section **5402**. These two genes correspond to variables X and Y. Chromosomes are added to the genes in section **5404**. Code for a fitness function may be identified in statement **5406**. Code for a selection function may be specified using statement **5408**. Code for a recombination function may be specified in statement **5410**.

The code for these functions may be implemented using any available function for the particular statement. These selection processes are used to select the most appropriate or best fit chromosome as specified by a code. For example, a roulette wheel selection process may be used. With respect to a recombination function in statement **5410**, this statement may be used to identify code to build a new generation of chromosomes.

In one example, a binary variable cross-over method may be used. Statement **5412** specifies an error margin for the process and statement **5414** calls an evolve function in code **5400**. The evolution process identified in statement **5414** stops whenever the error margin of the most fit chromosome is less than the error specified in statement **5412**, in these examples. By executing the process as defined in code **5400**, gene X returns the values of X that most fit the chromosome and gene Y returns the values of Y that most fit the chromosome.

Turning now to **Figures 55A** and **55B**, a diagram illustrating code for an object in source code is depicted in accordance with an advantageous embodiment. In this example, code **5500** is an example of a definition for an object in the form of a forest. Section **5502** identifies colors for trees in the forest. Section **5504** in code **5500** identifies a grid for the forest. Section **5506** defines trees that may be present in the grid for the forest. Section **5508** identifies a row of tree for the forest. Section **5510** is used to generate a patch of trees, which contains one or more rows of trees as defined in section **5508**. Section **5512** is an example of code that may be used to present the forest. In these examples, lines 5514 and 5516 are translation statements used to provide for randomness within the forest. Other statements, such as, for example, rotation and/or scale statements also may be used in addition to or in place of these statements.

In these examples, code **5500** is written using C language. Of course, any language may be used to generate a definition for a forest. Further, the presentation of a forest is the example of one object that may be found in definition **602** in source code **600** in **Figure 6**. Of course, code may be generated using any language or for any object, depending on the particular implementation.

The flowcharts and block diagrams in the different depicted embodiments illustrate the architecture, functionality, and operation of some possible implementations of apparatus, methods and computer program products. In this regard, each block in the flowchart or block diagrams may represent a module, segment, or portion of computer usable or readable program code, which comprises one or more executable instructions for implementing the specified function or functions. In some alternative implementations, the function or functions noted in the block may occur out of the order noted in the figures. For example, in some cases, two blocks shown in succession may be

executed substantially concurrently, or the blocks may sometimes be executed in the reverse order, depending upon the functionality involved.

The different advantageous embodiments can take the form of an entirely hardware embodiment, an entirely software embodiment, or an embodiment containing both hardware and software elements. Some embodiments are implemented in software, which includes but is not limited to forms, such as, for example, firmware, resident software, and microcode.

Furthermore, the different embodiments can take the form of a computer program product accessible from a computer-usable or computer-readable medium providing program code for use by or in connection with a computer or any device or system that executes instructions. For the purposes of this disclosure, a computer-usable or computer readable medium can generally be any tangible apparatus that can contain, store, communicate, propagate, or transport the program for use by or in connection with the instruction execution system, apparatus, or device.

The computer usable or computer readable medium can be, for example, without limitation an electronic, magnetic, optical, electromagnetic, infrared, or semiconductor system, or a propagation medium. Non limiting examples of a computer-readable medium include a semiconductor or solid state memory, magnetic tape, a removable computer diskette, a random access memory (RAM), a read-only memory (ROM), a rigid magnetic disk, and an optical disk. Optical disks may include compact disk - read only memory (CD-ROM), compact disk - read/write (CD-R/W) and DVD. In these examples, a physical or tangible computer readable medium is referred to as a recordable computer storage medium.

Further, a computer-usable or computer-readable medium may contain or store a computer readable or usable program code such that when the computer readable or usable program code is executed on a computer, the execution of this computer readable

or usable program code causes the computer to transmit another computer readable or usable program code over a communications link. This communications link may use a medium that is, for example without limitation, physical or wireless.

5 A data processing system suitable for storing and/or executing computer readable or computer usable program code will include one or more processors coupled directly or indirectly to memory elements through a communications fabric, such as a system bus. The memory elements may include local memory
10 employed during actual execution of the program code, bulk storage, and cache memories which provide temporary storage of at least some computer readable or computer usable program code to reduce the number of times code may be retrieved from bulk storage during execution of the code.

15 Input/output or I/O devices can be coupled to the system either directly or through intervening I/O controllers. These devices may include, for example, without limitation to keyboards, touch screen displays, and pointing devices. Different communications adapters may also be coupled to the
20 system to enable the data processing system to become coupled to other data processing systems or remote printers or storage devices through intervening private or public networks. Non-limiting examples are modems and network adapters are just a few of the currently available types of communications adapters.

25 The description of the present disclosure has been presented for purposes of illustration and description, and is not intended to be exhaustive or limited to the disclosure in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art. Further,
30 different advantageous embodiments may provide different advantages as compared to other advantageous embodiments. The embodiment or embodiments selected are chosen and described in order to best explain the principles of the disclosure, the practical application, and to enable others of ordinary skill in

the art to understand the disclosure for various embodiments with various modifications as are suited to the particular use contemplated.

CLAIMS

What is claimed is:

1. An apparatus for simulating human behavior, the apparatus comprising:

5 source code (402, 510, 600) located on a storage system in a network data processing system (100), wherein the source code (402, 510, 600) is written in a language for predicting human behavior;

10 an interpreter (404, 518, 1700) executing on hardware in the network data processing system (100), the interpreter (404, 510, 600) including a language interpreter (1704) and a communications module (1702), wherein the language interpreter (1704) executes a simulation with the source code (402, 510, 600) using artificial intelligence (802, 3202) to generate a new
15 definition and interpreted source code;

a graphical user interface processor (406, 522, 524, 528, 2600) executing on the hardware in the network data processing system (100), wherein the graphical user interface processor (406, 522, 524, 528, 2600) receives the interpreted source code from
20 the language interpreter (1704) to form received interpreted source code and generates device dependent output using the received interpreted source code; and

a set of devices (408, 523, 530, 532, 2618) in communication with the graphical user interface processor
25 (406, 522, 524, 528, 2600), wherein the set of devices (408, 523, 530, 532, 2618) displays the device dependent output, wherein the set of devices (408, 523, 530, 532, 2618) receives user input to form received user input and sends the received user input to the graphical user interface processor
30 (406, 522, 524, 528, 2600), and wherein the communications module (1702) receives the received user input from the graphical user interface processor (406, 522, 524, 528, 2600) and the new definition from the language interpreter (1704), modifies the

source code (402, 510, 600) with the received user input and the new definition to form modified source code that is executed by the language interpreter (1704).

2. The apparatus of claim 1, wherein interpreter (404, 518, 1700) further includes a first encryption and decryption module (1706, 2602) and wherein the graphical user interface processor (406, 522, 524, 528, 2600) further includes a second encryption and decryption module (1706, 2602), wherein the first encryption module (1706, 2602) encrypts the device dependent output to form encrypted output and sends the encrypted output to the second encryption and decryption module (1706, 2602), wherein the second encryption and decryption module (1706, 2602) decrypts to encrypted output to form the received interpreted source code.

3. The apparatus of claim 1, wherein the language interpreter (1704) comprises:

a language analyzer, wherein the language analyzer identifies tokens in the source code (402, 510, 600) to form identified tokens;

a grammar parser (1730), wherein grammar parser (1730) creates sentences using the identified tokens; and

an execution module (1732), wherein the execution module (1732) executes the sentences created by the grammar parser (1730) using the artificial intelligence (802, 3202).

4. The apparatus of claim 3, wherein the communications module comprises:

a registration module (1726);
an input module (1724); and
a dispatcher module (1722).

5. The apparatus of claim 1, wherein the storage system is a plurality of storage devices.

6. The apparatus of claim 5, wherein the plurality of storage devices are in different locations in the network data processing system (100).

7. The apparatus of claim 1, wherein the graphical user interface processor (406, 522, 524, 528, 2600) executes on a first portion of the hardware and wherein the interpreter (404, 518, 1700) executes on a second portion of the hardware.

8. The apparatus of claim 1, wherein the language interpreter (1704) identifies tokens in the language in the source code (402, 510, 600), creates sentences for the language, and executes actions from sentences.

9. The apparatus of claim 1, wherein the language interpreter (1704) generates device dependent output in a form of a set of device dependent output streams.

10. A computer implemented method for simulating human behavior, the computer implemented method comprising:

retrieving data from source code (402, 510, 600) stored in a storage system in a network data processing system (100) to form retrieved data;

interpreting the retrieved data to perform a simulation of the human behavior using an interpreter (404, 518, 1700) executing on the network data processing system (100) to generate results;

generating device dependent data from the results using a graphical user interface processor (406, 522, 524, 528, 2600) executing on the network data processing system (100), wherein the device dependent data may be used to present the results; and

modifying the source code (402, 510, 600) using the results to form modified source code, wherein the modified source code

provides new data utilized in subsequent interpretations to predict the human behavior.

11. The computer implemented method of claim 15 further comprising:

presenting the device dependent data on a set of devices (408, 523, 530, 532, 2618).

12. The computer implemented method of claim 16 further comprising:

receiving user input from the set of devices (408, 523, 530, 532, 2618) at the interpreter (404, 518, 1700) to form received user input;

modifying the source code (402, 510, 600), by the interpreter (404, 518, 1700), using the received user input to form the modified source code; and

continuing to perform the simulation of the human behavior at the interpreter (404, 518, 1700) using the modified source code.

13. The computer implemented method of claim 15 further comprising:

sending the results from the interpreter (404, 518, 1700) to the graphical user interface processor (406, 522, 524, 528, 2600) in an encrypted format.

14. The computer implemented method of claim 15, wherein the graphical user interface processor (406, 522, 524, 528, 2600) is located on a plurality of different data processing systems.