

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04L 12/26		A1	(11) International Publication Number: WO 96/20549
			(43) International Publication Date: 4 July 1996 (04.07.96)
(21) International Application Number: PCT/GB95/03025		(81) Designated States: AL, AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG , SI, SK, TJ, TM, TT, UA, UG, US, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, LS, MW, SD, SZ, UG).	
(22) International Filing Date: 22 December 1995 (22.12.95)			
(30) Priority Data: 94309760.0 23 December 1994 (23.12.94) EP			
(34) Countries for which the regional or international application was filed: AT et al.			
(71) Applicant (for all designated States except US): BRITISH TELECOMMUNICATIONS PUBLIC LIMITED COMPANY [GB/GB]; 81 Newgate Street, London EC1A 7AJ (GB).		Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.	
(72) Inventors; and			
(75) Inventors/Applicants (for US only): DOWDEN, Antoinette [GB/GB]; 17 St. Mark Drive, Colchester, Essex CO4 4LP (GB). EDWARDS, Michael, John [GB/GB]; 85 Westerfield Road, Ipswich, Suffolk IP4 2XP (GB). CHAPMAN, Steven, John [GB/GB]; 35 Congreve Road, Ipswich, Suffolk IP1 6AH (GB). O'MALLEY, Michael [GB/GB]; Willow Barn Lower Ufford, Woodbridge, Suffolk IP13 6EB (GB).			
(74) Agent: LIDBETTER, Timothy, Guy, Edwin; BT Group Legal Services, Intellectual Property Dept., 8th floor, Holborn Centre, 120 Holborn, London EC1N 2TE (GB).			

(54) Title: **FAULT MONITORING**

(57) Abstract

Faults occurring in a telecommunications system (21) are monitored identifying their time of onset and reporting them to an operator through an interface (16) if they have not cleared within a predetermined interval. Transient faults, which do clear within that interval, are not reported directly, but only if such faults occur more frequently than a predetermined rate. This is determined by establishing a scan interval, and an analysis period equal to a plurality of scan intervals, monitoring the system (21) continuously for the occurrences of faults, and storing their times of occurrence in a store (8). At the end of each scan interval, the number of occurrences of the fault during the analysis period which ends at the end of the scan interval are counted by a counter (11). If the number of occurrences of the fault in the analysis period is equal to or greater than a threshold value selected by user input (16), an alarm indicator (17) is activated. This allows isolated transient faults to be disregarded, allowing the user to concentrate on recurrent intermittent faults.

