

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
29 April 2004 (29.04.2004)

PCT

(10) International Publication Number  
**WO 2004/036322 A1**

(51) International Patent Classification<sup>7</sup>: **G05B 19/00**,  
H04Q 1/00, 1/18, G06F 7/04, G08B 21/00

(21) International Application Number:  
PCT/US2003/000587

(22) International Filing Date: 9 January 2003 (09.01.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
10/273,819 18 October 2002 (18.10.2002) US

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant and

(72) Inventor: **KADY, Darren** [US/US]; 6001 Morgan's Glen Place, Glen Allen, VA 23059 (US).



Published:

— with international search report

(74) Agent: **PARKER, Sheldon, H.**; Parker & DeStefano, 300 Preston Avenue, Suite 300, Charlottesville, VA 22902 (US).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: LOCKING DEVICE FOR ELECTRONIC EQUIPMENT



(57) Abstract: The operating control system (80) can be used on electronic equipment, such as cell phones, computers, engine analyzers (Fig. 1), etc. An input device (12) enables the input of user access data and a readout panel (14) monitors the equipment status. A programmable feature selection member enables the user to select at least one programmable feature and respective activation time period. An internal member controls operation of the equipment by controlling access to one or more said programmable features based upon user selection, to enable full or partial activation of the device. A user is able to program specific events, such as TV shows (15), to be activated at specific times with controlled access by secondary access codes.

## **LOCKING DEVICE FOR ELECTRONIC EQUIPMENT**

### **BACKGROUND OF THE INVENTION**

#### **Field of the Invention**

The device relates to a safety and security device that, once activated, allows the electronic equipment to run for a preprogrammed period. In some embodiments, the device is used as an antitheft device as without the code use of the device is prohibited, preventing theft and resale of protected equipment.

#### **Brief Description of the Prior Art**

Electronic devices offer a temptation to thieves, as they are easy to resell due to lack of distinctive features. Although people will mark their electronic devices, such as cell phones, computers, etc. , unless the stolen device is resold through a legitimate vendor, there is no hope for recovery.

### **SUMMARY OF THE INVENTION**

A locking device disclosed is for use on electronics, such as computers, cameras, cell phones, VCRs, DVDs, etc. and mechanical equipment, tools, heavy equipment and machinery, gas-powered vehicles, as well as various other wheeled vehicles. The device provides the option of permitting the equipment to be operable or inoperable for a predetermined period of time, selection of specific operable features or being completely shut down with operation permitted only through code entry.

Electronic circuitry within the device, in conjunction with an unlocking and timer operation, requires that the equipment be unlocked prior to use. A time period for operation can

Appl. No. pct/us03/00587  
Amdt. dated July 19, 2004  
Article 34 Amendment

2

**Replacement Page 2**

be programmed into the equipment, after which time the unit shuts off or, conversely, the equipment can be shut down for a specific time period and automatically reactivated. This reduces theft as well as preventing unauthorized use of the item.

The operating control device is for use with equipment having an exterior case, a power source, an input device, at least one activation/deactivation member, and a control member. The control member, such as a separate chip or programming embedded into existing chips, either has its own input device to enable the input of user access codes or uses an input device inherent in the equipment, such as the buttons on a cell phone. In the preferred embodiments, a readout panel, such as a cell phone, computer or camera screen, is used to monitor the status of the equipment. The readout can also be an audio output. The control member is in communication with the input device, readout panel, power source, and activation/deactivation member. The control member prevents operation of the equipment without the entry of a user code. The control member can also be programmed to control the internal functions of the electronic device, such as permitting the viewing of certain channels on a TV during a predetermined time, and other channels during other times. Secondary access codes permit the system to be programmed to permit activation of the device only by those containing the secondary codes. The device can also permit cell phone calls out, but not in, or vice versa, during set time periods. Any equipment having electronic components can be incorporated with the disclosed device to provide the ability to selectively determine which features are active for specific time periods. In digital equipment, such as cameras, camcorders, etc; the capabilities are increased due to the versatility of the digital technology and it should be noted that any of the capabilities disclosed herein with one digital device can be incorporated in other digital devices.

The control device includes a programmable timer to communicate with the control member thereby enabling access to the selected feature for the predetermined period of time entered at the input device. Preferably the memory within all embodiments is nonvolatile thereby preventing a loss of the setting upon loss of power. A clock member, if not already inherent in the device, can be added to track time, activate, and deactivate the timer based on user input. In cellular phones, computers, cameras, etc. , the operation of the equipment is dependent upon microchips, or microprocessors, and would not require the wiring of a power tool, or other non-processor based equipment. The versatility of the locking device enables it, as disclosed in co-pending application SN 09/178,837, to be use on equipment such as hand tools, electronics or wheeled vehicles as well as cell phones, digital and non-digital cameras, etc.

### **BRIEF DESCRIPTION OF THE DRAWINGS**

The advantages of the instant disclosure will become more apparent when read with the specification and the drawings, wherein:

**FIGURE 1** is a side view of an example hand tool incorporating the locking device;

**FIGURE 2** is a cutaway view of the interior of the locking arm and solenoid of the instant invention;

**FIGURE 3** is a top view of an example controller configuration;

**FIGURE 4** is the schematic of an example wiring for the locking device for use with a hand tool;

**FIGURE 5** is a cutaway side view of the interior of the hand tool of Figure 1;

**FIGURE 6** is a cutaway side view of an alternate embodiment of a hand tool utilizing the disclosed locking device;

**FIGURE 7** is a side view of the instant device for use with a air tool system;

Appl. No. pct/us03/00587  
Amdt. dated July 19, 2004  
Article 34 Amendment

5

**Replacement Page 5**

**FIGURE 8** is a schematic of the wiring for use with the locking device used in conjunction with air tools;

**FIGURE 9** is a schematic of the wiring for use with electronic devices;

**FIGURE 10** is a schematic of the wiring for use with the locking device incorporating the analogue function;

**FIGURE 11** is a flow chart for programming a multi-operation device;

**FIGURE 12** is a flow chart for programming a single operation device;

**FIGURE 13** is a flow chart for programming an electronic device including a reset option;

and

**FIGURE 14** is a flow chart for programming an electronic device designating specific events, times and users.

**DETAILED DESCRIPTION OF THE INVENTION**

The disclosed invention relates to a programmable device having multiple programmable features including, but not limited to, restricting accessibility to specific portions of the device and a coded locking mechanism that discourages theft and restricts or eliminates use during a predetermined time frame. In addition to the inherent advantages obtained through the locking device as disclosed, further safety advantages are achieved simply by its existence. It will be obvious to anyone who buys an item containing the locking device that unless the seller has the code, the item is most likely stolen. The disclosed locking device controls the activation of the item, preventing activation without the entry of user codes. Without access to the codes, the item is useless and unsaleable.

**AMENDED SHEET**

PCT/US03/00587 .19072004

IPEA/US

5/1

Appl. No. pct/us03/00587  
Amdt. dated July 19, 2004  
Article 34 Amendment

Electronic devices, such as cell phones, palm pilots and other hand held data access  
devices, cameras, computers, VCRs, televisions, MP3 players, etc. all fall into the category of

AMENDED SHEET

easy theft devices with high resale value. Their use of programmable chips, however, makes these valuable devices easy to modified to incorporate the advantages of the disclosed system. Alternatively, in devices such as VCRs and televisions, the device can be retrofitted into the power source, such as the power cord or plug. The use of microchips, microprocessors or analog, technology, however, permits various functions to be monitored, such as scheduling service, based on use time or the number of hours an item has been used.

The locking mechanism is preferably of a type that does not require the use of a key, or other device, thereby avoiding an additional item to lose or carry. Access through keypads or other locking means can be used, such as magnetic card readers, fingerprint or retinal recognition, standard keys, telephone signals, or any applicable wireless technology, etc. The method of programming the device is dependent upon the type of device, size, etc. For example, touch key scanning, or other method of transmission having static data, can easily be incorporated into the device, thereby permitting data relating to the item to be tracked.

The disclosed technology provides benefits in a laboratory or other setting where equipment is centralized and removed for use. Each employee would have a personalized touch key, or other wireless or non-wireless access means, that would record the employee name, time of activation, and any other information required by the employer. In instances where security or training levels are required to use a device, the personalized access device can also carry the ID code enabling use of the device, thus preventing use by unauthorized personnel.

When the device cannot be programmed using systems inherent for the use of the device, such as a digital camera or cell phone, alternative programming "keys" containing static data, such as a touch key, can be used. The disclosed technology provides the advantage that an employer, or parent, can program the touch key with the pertinent data, including activation time,

Appl. No. pct/us03/00587  
Amdt. dated July 19, 2004  
Article 34 Amendment

**Page 7, paragraph 2 through Page 9, paragraph 1**

and that data cannot be changed except by someone with top level programming rights. This is advantageous when using equipment that must be shut down after a specific period of use as the preprogrammed time relieves the user from the responsibility of watching a clock. Although shut down could also be obtained through other methods, the disclosed system provides the additional advantages as set forth herein, thereby consolidating systems.

When installed on a computer, the disclosed device can be connected directly to the power supply or programmed into the chip, hard drive or other storage/memory device; permitting businesses that sell computer time to automatically shut down the computer unless additional time is purchased. In home use, the device permits scheduling the amount of time, or specific time periods, the computer, or other electronic devices such as a TV, cell phones, VCR, camcorders, etc., can be used by someone without the full access code. Thus, the computer, VCR, cell phone or TV could only be activated after homework time is over, etc. Computers are especially adaptable to keyboard programming of the device, although a keyboard interface can be included with any of the locking devices disclosed. A program embedded in the device's microchip and/or hard drive can allow for a simple timer setting that is activated through key input on the keyboard. As an option, a direct coding key can be incorporated on the keyboard that automatically accesses the program and permits activation, setting changes, etc. Although computer lock out programs are known in the prior art, they totally lock out use of the computer in an all or nothing method. The disclosed device permits access to the computer for a predetermined period of time either at random times until the predetermined time is met, or within a specifically scheduled time frame. Optionally, the user can have the ability to extend the amount of time to use the device without interruption. For example, the system can be set to enable the computer to be turned at a predetermined time, used for a specific time period, after which the computer cannot be used until

PCT/US03/00587 .19072004

IP EA/US

Appl. No. pct/us03/00587  
Amdt. dated July 19, 2004  
Article 34 Amendment

7/1

the preprogrammed activation time. This enables a parent to leave the house after programming  
the use schedule of the computer, or

AMENDED SHEET

Appl. No. pct/us03/00587  
Amdt. dated July 19, 2004  
Article 34 Amendment

Replacement page 8

other electronic device or equipment, to activate at 6 pm until 10 pm after which it deactivates until the follow day at 6 pm or in response to other programming. The user scheduling the time restraints would set up the program with a primary, or programming, user code to prevent unauthorized changes to the program.

One of the programmable features disclosed herein is a partial activation feature, as described in detail hereinafter with relationship to cell phones. Using this feature, the user can restrict partial use of the electronic equipment, for example a computer can be programmed to restrict certain programs, such as web access, instant messages, email, specific websites or type of site, during specific blackout time periods. For example, children could be prevented from surfing the web except during specific time periods. Or computer games could only be accessed for a restricted time, however the computer could be used for word processing or other homework related activities. This feature enables the computer to be used, but in a restricted manner, based upon primary user programming. Additionally, sub-user ID's can be used to permit individual access to an electronic device. This is advantageous with children having different age restrictions by permitting the older children to access programs, make long distance calls, etc., that are unavailable to younger children.

The disclosed locking device is also advantageous for rental equipment, such as generators, compressors, VCR's, etc., in that the rented equipment can be programmed for a specific period of time and after that point be automatically deactivated. This discourages the theft of rental equipment, thereby reducing insurance and liability, since by preventing unauthorized use, especially when used in conjunction with larger equipment, insurance rates would potentially be reduced.

AMENDED SHEET

IPEA/US

PCT/US03/00587.19072004

8/1

Appl. No. pct/us03/00587  
Amdt. dated July 19, 2004  
Article 34 Amendment

In electronic equipment, such as TVs, VCRs, etc. containing infrared remote controllers,  
the timing activation device can be activated through the remote controller. Once activated the

program would appear on the screen and utilize either existing or specific keys to set the shut down time, user time periods, or extend the time period, etc. This would be an inexpensive addition to a controller and increase user convenience. Alternatively, the controller itself can be used to set the time of use, without the appearance of the setting program on the screen.

It should be noted that the use of analogue, key scanners, infrared, fingerprint or retinal recognition, etc. taught herein for use by a specific embodiment, is not limited to that embodiment. Each embodiment of the locking device disclosed herein can incorporate the electronics, memory, etc. as described herein in relation to any other embodiment.

A hand drill, as illustrated in Figures 1 and 2, is used to illustrate the disclosed mechanism used to limit user time, however this is as an example only and is not intended to limit the invention. The power tool 10 is illustrated in Figure 1 ready for use, incorporating a numeric keypad 1 as the locking mechanism and other activating mechanisms will be apparent to those skilled in the art.

The time can be set through any means appropriate to the equipment being used as well as the final use. For example, the time can be through repeatedly touching a specific key, jumping the time by predetermined increments. Alternatively, an "enter" key can be provided which allows entry of the unlocking code and subsequent entry of a predetermined period of time. Preferably, all timed locking devices are provided with nonvolatile memory to prevent the loss of programmed instructions in the event the item's battery goes dead or is removed. This is more critical with rechargeable hand tools where completely discharging the battery is sometimes required to fully recharge.

The incorporation of a microchip to register the locking codes and program the activation time further provides the added ability to monitor various other tool functions. For example, an LED display 14 of Figure 1 can be included which indicates the activation time remaining and, if desired, the current status of the tool. The status can include, for example, current battery power (both during recharge and discharge), pressure remaining when air tools are used, rpm and direction of drills, etc. This is of optimum use in monitoring the status of rechargeable batteries. Since many rechargeable batteries do not either fully charge unless fully discharged prior to recharging, the battery-monitoring device permits optimum use and management of the battery. It should also be noted that an LED could be provided on the recharging device to monitor the battery recharge thereby serving as a double check to the LED on the device being charged.

In Figure 2, one design of the internal activation unit 40 is illustrated. The locking arm 48 is supported between the upper case side 42 and the lower case side 44. The spring tension 50 is designed to place the solenoid contact 56 in physical contact with the solenoid 52 when the locking arm 48 is pulled back during use. Once the locking arm 48 is released, the solenoid contact 56 is removed from contact with the solenoid 52. The solenoid 52 receives power from the battery 108 (Figure 5) through the controller 80, an example of which is illustrated in more detail in Figure 3. As can be seen from the example schematic of Figure 4, the controller 80 serves as the central processing area, with all input and output passing through the controller 80. The controller 80 is connected directly to the locking mechanism, such as a numeric keypad 12, through the keypad wiring 100. The battery wiring 102 and motor wiring 104 also feed into the controller 80. Once the locking means, such as numeric keypad 12, is activated, all connections are made and power is free to go to the driver specific to the power tool 10. The exact schematic of the wiring is not critical, as the criticality lies with in the interaction between the locking means and the controller 80. The interior of the hand tool 10, as shown in Figure 5, is traditionally spaced, with the controller 80 located within the handle area. In this embodiment, the various connecting wires 100, 102 and 104 are exposed and, in the event of theft, the case can be opened and the wires cut and crossed to bypass the controller 80. In order to prevent a thief from opening the case and by passing the controller 80, the case is provided with a safety lock key having a number of different embodiments. One embodiment is to incorporate a locking member, wired to the control through the locking wire 156, that is deactivated by a locking code, key or other compatible methods. The controller 80 can be programmed to allow the case to release, for example through a separate code being entered or by holding down the last number of the existing code for a predetermined time period. A separate code is preferable in that it prevents any unauthorized access to the interior of the case.

In an alternative embodiment to the safety lock key, the solenoid 126 and wiring 122 are encased in an epoxy, indicated herein as region 128, as illustrated in Figure 6. By encasing the wiring 122 within the epoxy, it is impossible to rewire the unit and bypass the controller 124. Other materials, known in the art, can be used to replace the epoxy. To facilitate the placement of the epoxy region 128, the wiring 122 from the motor 120 exits the motor casing proximate the controller 124, which has been placed as close as possible to the solenoid 126. This revised placement reduces the area to be protected, thereby reducing material and labor costs. Revising the placement of the battery 130 is difficult, preventing in some instances the battery wiring 132

from being covered. However, with the controller 124 and solenoid 126 both encased in epoxy, there would be no value to cutting the battery wire 132, as there would not be any accessible power connections.

In Figure 7, the locking device is illustrated being used with an air tool 200, although it should be noted that the device can also be used with propane, gas, and diesel tools and equipment. The controller unit 202, as illustrated, is located in the handle 204 of the air tool. As can be seen in the example schematic of Figure 4 (battery) and Figure 8 (air tool) there is little difference in wiring between the two. As stated, in the schematic of Figure 4 the touch key-wiring 100 goes to the controller 80, as does the battery wire 102 and the motor wire 104. In the air tool, or other removed power source, the touch key wiring 150 and solenoid 154 wiring feed into the controller 152 and onto the driver, the battery and motor connections being eliminated.

As stated heretofore, the disclosed device can be easily incorporated with electronic equipment. The programming of the equipment can be through a number of methods and additional methods will become evident as technology changes and will be evident to those skilled in the art.

Rewrite swipe cards are gaining popularity and can easily be incorporated with the disclosed device. The cards can be rewritten with the new codes using a computer or other applicable device, such as a palm or remote control. For example, a computer program can contain the applicable coding for all the electronic devices which incorporate the disclosed technology. A user can select the functions to be incorporated for each device and write them to the card. The user can then use the same swipe the card to program each of the electronic devices available as each device will recognize its codes and ignore programming for other devices. Alternatively, a small hard drive, such as used in digital cameras, can be used to program the various electronic devices.

The schematic of Figure 15 is an example of the electronics for a device being incorporated into a computer, VCR, television, etc. As can be seen, the basic functioning of the antitheft device is the same as used for a battery operated, air or electric tools or other devices. As in the schematics disclosed heretofore, the touch key wiring 302 feeds into the controller 304. In this embodiment, however, the electric wiring 306 is connected to the controller 304 through

Appl. No. pct/us03/00587  
Amdt. dated July 19, 2004  
Article 34 Amendment

## Replacement Page 12

the latching relay wires 308. The schematic of Figure 16 provides an example of the electronic layout, disclosed in Figure 15, to incorporate the analogue function into the device through analog wiring 350.

As stated heretofore, cellular phones are a small sized, high dollar theft item that is difficult to protect. Most people leave their phones on all of the time so that the implementation of an on/off-activated lock would not prevent theft; as the phone would most likely be turned on when stolen and a thief would simply leave the phone on. Incorporating the disclosed system, the thief would know that there was no way to stop the phone from shutting down at a pre-designated time and that once the predesignated time had expired the phone would be unusable. Using the disclosed system, the user could program the phone to shut off permanently at the expiration of a predetermined time or, alternatively at a preset time. For example, this would enable the user to tell the system that it should shut off at 9:00 p.m., or alternatively once the timer reach three hours from the programming time. Once shut down, the device would require reentry of the access codes. The disclosed system further enables a user to set the phone to shut down for a predetermined period of time, with automatic reactivation at the end of the time period. The ability to turn the phone off for a predetermined period of time, after which it automatically reactivates for a predetermined time based upon user programming, is beneficial for people attending meetings, movies, or some other activity that requires the phone to be turned off. Since the phone will automatically reactivate, the user does not need to worry about turning the phone back on. In the preferred embodiment, the phone can also be set to either receive calls or make calls, during a user programmed time period, as well as the standard incoming/outgoing feature. Thus, if the phone is being loaned out and the owner of the phone does not want his/her calls to be

AMENDED SHEET

IPEA/US

PCT/US03/00587 .19072004

12/1

Appl. No. pct/us03/00587  
Amdt. dated July 19, 2004  
Article 34 Amendment

picked up by anyone else, the phone can be set to forward all of the phone owner's incoming calls  
to their voice mail or other call forwarded location, while still allowing the person

AMENDED SHEET

Appl. No. pct/us03/00587  
Amdt. dated July 19, 2004  
Article 34 Amendment

### Replacement Page 13

having the phone to make outbound calls. In the reverse mode, the person having the phone can receive calls, but cannot use the phone to call out.

It should be noted that for maximum security, the code enabling the programming disclosed herein is preferably on the phone's, or other equipment's, permanent memory device, such as hard drive, microchip, etc. and is not solely dependent upon any temporary software, phone card or other removable system.

A delayed activation can also be programmed into any of the devices to schedule activation/deactivation at a specific time or after a certain amount of time has lapsed. Thus, in applications such as the electric tools used on a construction site, the foreman can program the tool to activate in thirty minutes and to stay activated for an additional eight hours.

In any electronic device the commands can be set through a variety of methods. On equipment that has a built in a screen, such as a digital camera or cell phone, the screen can be used to monitor the exiting settings and program new settings. In devices without screens an external LED display, voice activation, or some other means of forming communicating between the device and the user can be incorporated. The existing command or program buttons can be used to program the device or additional buttons can be incorporated into the design at the time of manufacture. Additionally, remotes, infrared, Bluetooth, Internet, telephone or cell phone or other wired or wireless devices can be used as a programming tool.

A sample of a sequence for the user to follow when programming a cell phone is illustrated in Figure 18. Once the device is activated 600 the system inquires whether the user would like to activate the locking system 602 or, if already activated, deactivate the system 701, thereby turning off the device.

### Deactivation

Appl. No. pct/us03/00587  
Amdt. dated July 19, 2004  
Article 34 Amendment

## Replacement Page 14

A sample of a sequence for the user to follow when programming a cell phone is illustrated in Figure 18. Once the device is activated 600 the system inquires whether the user would like to activate the locking system 602 or, if already activated, deactivate the system 701, thereby turning off the device.

### Deactivation

A sample of a sequence for the user to follow when programming a cell phone is illustrated in Figure 18. Once the device is activated 600 the system inquires whether the user would like to activate the locking system 602 or, if already activated, deactivate the system 701, thereby turning off the device.

In Figure 13, the additional option of resetting the system is added, enabling the user to either deactivate or reset the system 803. If the system is deactivated, the user enters their personal code 812 and selects whether they wish to deactivate 812 or reset 814. If deactivate 812 is selected the system enters normal operation 810, again incorporating the preferred restriction of a maximum operating time. If the user selects to reset 814 the system then goes to the timed operation sequence 816, the system continues following arrows A1000 and A1002, as set forth in Figure 12. It should be noted that arrow A1004 serves as the return from the "no" selection at the end of the programmable options.

### Activation

If user answers "yes" to the Program Mode 602, or activate, the system 602, the system, as illustrated in Figures 11 and 12, asks the user if they wish to program and proceeds to request the personal code 604 and then, if the code is correct, enters normal either enters into the programming selections 706 or fall back operation 610, again for the maximum operational

IPEA/US

PCT/US03/00587 . 19072004

14/1

Appl. No. pct/us03/00587  
Amdt. dated July 19, 2004  
Article 34 Amendment

period. This permits the previously set parameters to be repeated until a change in programming is required. If, however, the user answers "yes", the system requests the personal code be entered 604 and, if correct, the user is then presented with several modes from which to select. These modes can be viewed by scrolling or, depending upon the size of the screen, all displayed with the arrow keys enabling selection. It should be noted that the sequence discussed herein in respect to this Figure is not intended to limit the invention in any way and different sequencing, alternative actions, etc. can be incorporated.

The Timed Operation mode 614, provides the user the ability to shut down the operation of the device by clock setting 636 or number of minutes 640. In the event the clock setting 636 is

AMENDED SHEET

Appl. No. pct/us03/00587  
Amdt. dated July 19, 2004  
Article 34 Amendment

15

### Replacement Page 15

selected, the user then enters the time of day that the device shuts down 638. If the minutes 640 module is selected, the number of minutes prior to shutting down is requested 642. Preferably, a preset maximum time of operation will still prevail after which the user a code would be required to reactivate the phone. The selection of "no" as a response brings up the sleep mode 620 operation which, if entered through, enables the user to set a start time 644 and an end time 646 during which the device is inoperable. "No" again bypasses the sleep mode 620 to the delay start 626 mode which enables the user to set the commencement of the start time 648 at a time later than the time of entry. The end time 650 is similar to the sleep mode end time 646. The partial operation mode 634 enables the user to separate the ability to make calls 652 from the ability to receive calls 654. When the make calls 652 operation is selected, the user enters the start time 656 and the end time 658 during which calls can be made. The receive calls 654 also permits start time 660 and end time 662 entry. In the event the user selects none of the modules the system returns to the activate locking system mode 604.

Depending upon the end cost, the device can be programmed to accept multiple different commands, such as a sleep mode 620 where it does not operate from the start time 644 to the end time 646, as well as a timed operation 614 in which the device shuts down 638 at 8:00 pm.

### Extend Time

The devices can be provided with an extend time feature 822, as illustrated in Figure 20, and it should be noted that although the devices can be provided with this feature, as noted heretofore, it cannot permit endless extended time as that would eliminate the security concept. In this embodiment, the user activates the device 802, selects to activate/reset the system 803 and enters

PCT/US03/00587 .19072004

EPEA/US

15/1

Appl. No. pct/us03/00587  
Amdt. dated July 19, 2004  
Article 34 Amendment

the personal code 812, the option of extend time 822 is presented. In the extend time option 822,  
the user can extend the time of the current programming equal to, or less than, the

AMENDED SHEET

Appl. No. pct/us03/00587  
Amdt. dated July 19, 2004  
Article 34 Amendment

16

**Replacement Page 16**

original program period. The amount of time for extension can be determined by the manufacturer and would be unchangeable by the user. For example, the phone can either shut down upon expiration of a preprogrammed maximum operational period or after a preset number of extensions 822.

In Figure 12, rather than enter a specific start time, as set forth in the prior Figure, a default time has been entered. Once the user activates the device 700, responds positively to activating the locking system 702 and enters the personal code 704, the timed operation mode 706 appears. Upon positive selection of the timed operation mode 706, the default start time 708 is displayed, giving the user the opportunity to increase 710 or decrease 718 the time by either minutes 712 or hours 714. It should be noted that the use of minute and hours for example only and the time categories can be days, weeks, or any increment selected by the manufacturer. The default end time 716 is adjusted in the same fashion. Each of the modes in this Figure provide the default time options, however it should be noted that the default modes illustrated in Figure 12 can be also included in conjunction with the timer setting modes illustrated in Figure 11. Alternatively the user can be provided with the choice of whether to select the default or the timer settings.

Figure 13 would be more applicable for cameras, TVs, computers and other devices that have only one type of operation. In other words do not have the dual operations, send and receive, as does a cell phone or a VCRs record and play. It should be noted that the system as disclosed in Figure 13 is used in the same way as explained in Figure 12.

PCT/US03/00587 .19072004

IPEA/US

Appl. No. pct/us03/00587  
Amdt. dated July 19, 2004  
Article 34 Amendment

16/1

In the embodiment of Figure 14, the user is able to schedule one or more specific events and their playing time. As used herein, an event includes computer programs, television shows, radio stations, or any other specific event that is viewed or listened to through the electronic device. For example, between 7:00 pm and bedtime, by controlling the stations that can be viewed, a 12 year old could only watch specific

AMENDED SHEET

IP EA/US

PCT/US03/00587 .19072004

Appl. No. pct/us03/00587  
Amdt. dated July 19, 2004  
Article 34 Amendment

17

Replacement page 17

shows and, at bed time, the TV would no longer be accessible. To accomplish this the primary, or programming, user activates the device 900, and is asked whether they are to program 934 or view 932. Entry of program 934 inquires whether the primary user would like to activate the locking system 902 or deactivate the system 903. As with the prior embodiments, if the primary user decides not to activate the system, the personal code 904 is requested and the device enters normal operation 910, again with the maximum running period. If the primary user wishes enter a programmed operation 614, they enter the start time 940, end time 942, user code 946 and the program code 952. This tells the system that at the start time 940 the secondary, or non-programming, user matching secondary user code 946 can watch the program entered into the program code 952 while other programs are blocked. To facilitate programming, multiple user codes 946 can be entered, or checked off on a list. Once the program code 952 is entered, the user can either repeat 948 the programming event 914 or end 950 the event. When returned to the programmed event 914, the user can either program another event or continue on to other modes contained on the device, such as those illustrated in Figure 13. Alternatively, a next mode 954 can be accessed directly from the program code 952 module.

If the user wishes to view 932, the user code 930 is entered and the system permits viewing of the preprogrammed events. This system is for use predominately on TV's and computers, however other applications will be evident to those skilled in the art.

AMENDED SHEET

One use of the disclosed invention is in commercial industries with workers using company owned tools and equipment, computers, motel TVs and VCRs, etc. The tools, or other equipment, are activated in the morning to run for an entire shift, at which point they shut down. This prevents theft from outside sources as well as employees. Additionally by reactivating the tools each morning, a "safety check" can be incorporated with the activation to prevent faulty equipment from being used.

The locking device can further be used with bicycles, shopping carts, wheelchairs, etc. It should be noted, however, that since the locking devices disclosed herein operate on bicycles by stopping movement of the pedals, this device is not recommended for bikes, or other items that have foot brakes. In the event, that the device was activated during use, the user would be unable to activate the brakes. The example used herein is a bicycle, however the device, as disclosed, can easily be adapted for a variety of other wheeled devices. The locking device for use with bicycles, or other applicable devices, preferably has a weight of about one (1) pound or less.

Figures 9,10 and 11 illustrate a manual version of the locking device 200 for use with wheeled vehicles and is illustrated on a bicycle. The locking mechanisms within the locking device are located within a protective case 202 to prevent tampering. The case 202 is welded to the front frame 230 and rear frame 232 as currently done in the art replacing the standard joint at the juncture of the front and rear supports. The case 202 is slightly larger than standard cases to accommodate the locking device 200. The pedal axle 204 passes through the case 202 and is attached to the pedals 236 as known in the art. The engagement disk 208 has a centered receiving hole 220 that permits the disk 208 to be mounted on the axle 204. The disk 208 is welded to the axle 204 to cause the disk 208 to rotate with the axle 204 as the bicycle is pedaled. The disk 208 contains a series of receiving holes 222 around its periphery. The receiving holes 222 are dimensioned to receive the locking bar 210 that has been encased in the locking brace 216. The locking brace 216 is secured to the case 202 to prevent movement of the bar 210 and therefore movement of the pedals 236 once the bar 210 is in the locked position. When in the unlocked position, the locking bar 210 is drawn into the locking brace 216. Once placed into the locked position, the bar 210 engages the receiving holes 222 of the disk 208 and prevents the pedals 236 from turning. The locking brace 216 must be securely affixed to the case 202 to prevent the brace 216 from dislodging when a user attempts to pedal during the locked mode. Additionally, the locking bar 210 must have sufficient strength to prevent the bar 210 from snapping or bending. In the embodiment of Figure 9 the bar 210 is placed into either the locked or unlocked position by a key lock 206, or other mechanically operated device. The interior mechanisms moving the locking bar 210 in response to the key lock 206 are like those of dead bolts for doors and other methods will be known to those skilled in the art.

To provide the ability to repair the locking device in the event a problem arises; a bottom plate 214 is incorporated into the locking device 200. The bottom plate 214 illustrated has a rotating lock 212 that is secured to a locking plate 220. The flanges 218 extend into the open area of the case 202 and provide support for the locking plate 220 when rotated to the locked position. Rotation of the rotating lock 212 moves the locking plate 220 into a position to clear the flanges, thereby permitting removal of the bottom plate 214. The locking mechanism for the bottom plate is an example of a method for locking the bottom plate onto the case and other methods known in the art can be used.

An automatic embodiment of the locking mechanism for use with bicycles is illustrated in Figures 12-14. The engagement disk 308 is welded to the pedal axle 324 as described heretofore. Rather than the manual lock of Figure 9, the interacting locking bar 326 is operated by a battery-powered solenoid 304. The solenoid 304 is maintained in position through use of a casing 306 that is securely affixed to the outer case 302. As stated heretofore, the locking bar 326 must be capable of withstanding the pressure exerted by a person attempting to pedal the bike. The batteries 340 to power the solenoid 304 can be contained within the front support 342 or other location convenient for manufacture. The use of a battery-powered solenoid also permits the use of a timer as disclosed for use with the hand tool of Figure 1. The analogue timer is advantageous for companies renting bikes by the hour or day as the timer can be activated upon the bike being removed from the shop and the time read and calculated upon return. The timer readout, entry method, etc. , can be incorporated in either the front support 342 or back support 344.

The base plate 312 uses an alternate design to the embodiment of Figure 9. In this embodiment, the base plate 312 is provided with a key lock 314 that is attached to dual rotating bars 320 and 322. The sides of the case 302 are provided with flange pairs 318 and 316 that are dimensioned to interact with the rotating bars 320 and 322. Thus, as the key lock 314 is turned, the bars 320 and 322 move out of their interaction with the flange pairs 318 and 316, thereby releasing the base plate 312.

Since other modifications and changes varied to fit particular operating requirements and environments will be apparent to those skilled in the art, the invention is not considered limited to the example chosen for the purposes of disclosure, and covers all changes and modifications that do not constitute departures from the true spirit and scope of this invention.

Appl. No. pct/us03/00587  
Amdt. dated July 19, 2004  
Article 34 Amendment

### In the Claims

1. An operating control system for equipment having an exterior case and a power source, said control system having:
  - a. at least one user access code,
  - b. an activation/deactivation member
  - c. at least one programmable feature,
  - d. a user programmable feature selection member, said user programmable feature selection member enabling said at least one programmable feature to be selected by said user,
  - e. at least one user programmable feature activation time period, said user programmable feature activation time period set by a user for each of said at least one programmable feature,
  - f. input means, said input means to enter said user access code, said programmable feature selection and said programmable feature activation time period;
  - g. an internal control member, said control member being in direct communication with said input device, said programmable feature activation time period and said programmable feature selection member,wherein said internal control member controls operation of said equipment by controlling access to one or more of said programmable features based upon user selection of said programmable feature and said programmable feature activation time.
2. The control system of Claim 1 further comprising a status panel, said status panel providing a report of said operating control device.
3. The control system of Claim 2 wherein said equipment is a cell phone.

Appl. No. pct/us03/00587  
Amdt. dated July 19, 2004  
Article 34 Amendment

4. The control system of claim 3 wherein said programmable features include at least one member from the group of normal operation, timed operation, sleep mode, delayed start and partial operation.
5. The control system of claim 4 wherein said partial operation includes making outbound calls and blocking inbound calls.
6. The control system of claim 5 wherein said partial operation is operational for a preprogrammed time period.
7. The control system of claim 4 wherein said partial operation includes receiving inbound calls and blocking outbound calls.
8. The control system of claim 7 wherein said partial operation is operational for a preprogrammed time period.
9. The control system of claim 1 wherein at least one of said at least one user access code is a primary code to program said programmable features.
10. The control system of claim 9 wherein another of said at least one user access code is a second code that enables access only to said at least one programmable feature.
11. The control system of claim 4 wherein said equipment is a TV.
12. The control system of claim 11 wherein one of said at least one programmable feature is station selection to program selected stations be viewed and one of said at least one programmable feature activation time period is to schedule the time said station selection can be viewed.
13. The control system of claim 4 wherein said equipment is a computer.
14. The control system of claim 13 wherein one of said at least one programmable feature is the selection of a specific computer program permitted to be accessed and one of said at least one

Appl. No. pct/us03/00587  
Amdt. dated July 19, 2004  
Article 34 Amendment

programmable feature activation time period is to schedule the time said specific computer program can be activated.

15. The control system of claim 1 wherein said equipment is a digital camera.
16. The control system of claim 1 wherein said input means is removable from said equipment.
17. The control system of claim 1 wherein at least one of said said at least one user access code, said programmable feature selection member and said programmable feature activation time period are programmed into said electronic equipment by a remote member.
18. The control system of claim 1 wherein at least one of said at least one user access code, said programmable feature selection member and said programmable feature activation time period are programmed into said electronic equipment by a removable member.
19. The control system of claim 1 further comprising an time extension mode, said time extension mode extending said the current activation time period by a preprogrammed time period.
20. The control system of claim 19 further comprising a maximum operation time, said maximum operation time being the maximum number of consecutive time extension mode activated.
21. The control system of claim 20 wherein said maximum operation time is unchangeable by a user.
22. The control system of claim 1 wherein said readout panel is remote from said electronic equipment.
23. The control system of claim 1 wherein at least one of said at least one user access code is a primary access code, said primary access code enabling access to b, c, d e and f.
24. The control system of claim 1 wherein at least one of said at least one user access code is a second access code, said secondary access code enabling access to b and f.

Appl. No. pct/us03/00587  
Amdt. dated July 19, 2004  
Article 34 Amendment

25. The control system of claim 1 wherein said user selecting normal operation returns said electronic equipment to the previously programmed sequence.
26. A method of scheduling the use of electronic equipment using a locking system, comprising the steps of:
- a. activating said electronic equipment,
  - b. selecting an activation mode,
  - c. entering a primary user code,
  - d. selecting at least one programmable feature,
  - e. selecting a programmable feature activation time period,
  - f. saving said programmable feature and said programmable feature activation time period in said locking system memory.
27. The method of claim 26 further comprising the step of repeating steps c-f until all user selected programmable features are entered.
28. The method of claim 26 wherein said feature activation time period is set by entering specific activation and deactivation times.
29. The method of claim 26 wherein said feature activation time period is set based upon lapsed time from the time of programming.
30. The method of claim 26 wherein said programmable feature enables a sleep mode.
31. The method of claim 30 further comprising the step of programming a start time and an end time to said sleep mode.
32. The method of claim 26 wherein said programmable feature enables a delayed start mode.

Appl. No. pct/us03/00587  
Amdt. dated July 19, 2004  
Article 34 Amendment

33. The method of claim 32 further comprising the step of programming a start time and an end time to said delayed start mode.

34. The method of claim 26 wherein said programmable feature enables a partial operation mode.

35. The method of claim 34 further comprising the step of electing to permit outgoing calls and block incoming calls for a user predetermined, programmable, time period.

36. The method of claim 34 further comprising the step of electing to permit incoming calls and block outgoing calls for a user predetermined, programmable, time period.

37. An operating control system for equipment having an exterior case, a power source, an internal feature activation member, said control system having:

at least one primary user access code, said at least one primary user access code have use and programming rights,

at least one second user access code, said at least one second user access code have only use rights,

a programmable feature selection member, said programmable feature selection member enabling at least one programmable feature to be selected by said user, said at least one user programmable feature selected from the group of:

normal operation;

timed operation, said timed operation operating said equipment for a predetermined period of time set by a user;

sleep mode, said sleep mode preventing operation of said equipment for a user selected period of time, returning to operation at the expiration of said user selected period of time;

delayed start, said delayed start preventing operation until a user sent time; and

Appl. No. pct/us03/00587  
Amdt. dated July 19, 2004  
Article 34 Amendment

partial operation, said partial operation enabling a user to selection one or more functions of said equipment for operation and selecting one or more functions of said equipment for non operation,

at least one programmable feature activation time period, said programmable feature activation time period being set by a user for each of said at least one programmable feature,

an input device, said input device permitting input of said predetermined user access code, said programmable feature selection and said programmable feature activation time period;

a readout panel, said readout panel providing a status report of said operating control device;

an internal control member, said control member being in direct communication with said input device, said power source, said programmable feature activation time period and said programmable feature selection member,

wherein said internal control member controls operation of said equipment by limiting programming access to said at least one programmable feature selection member and said at least one programmable feature activation period to a user having said primary user access code and controlling access to one or more of said programmable features for a user having said second access code based upon programming by said user having said primary access code of said at least one programmable feature, said partial operation and said at least one programmable feature activation period.

38. The operating control system of claim 37 further comprising a battery power source, said battery power source's status being monitored by said operating control device.

39. An operating control system for controlling access to electrical equipment having:  
at least one first user access code;

Appl. No. pct/us03/00587  
Amdt. dated July 19, 2004  
Article 34 Amendment

at least one second user access code;

an activate, deactivate mode;

at least one user programmable feature;

at least one programmable feature activation time period, said programmable feature

activation time period set by a user for each of said at least one programmable feature;

input means, for entering said first user access code, said programmable feature selection and  
said programmable feature activation time period;

wherein said internal control member prevents activation of said equipment without correct  
entry of one of said at least one first user access code or said at least one second user access code.

40. The operating system of Claim 39 wherein said first user access code permits a user to  
program said at least one user programmable feature, at least one programmable feature activation  
time period and operate said equipment.

41. The operating system of Claim 39 wherein said second user access code permits a user to  
operate said equipment.

42. The operating system of Claim 39 further comprising a readout panel, said readout panel  
reflecting the prompting said user.

43. An operating control device for equipment having a power source, an internal activation  
member and a driver member, said control device having:

a predetermined user access code,

a user determined programmable activation time period, said programmable activation  
time period being entered subsequent to entry of said access code,

Appl. No. pct/us03/00587  
Amdt. dated July 19, 2004  
Article 34 Amendment

an input device, said input device for entry of said predetermined user access code and  
said programmable activation time period;

a readout panel, said readout panel providing a status of said operating control device;

an internal control member, said control member being in direct communication with said  
input device, said power source, said driver member and said activation member,

wherein said internal control member prevents operation of said equipment by preventing  
power to transfer from said power source to said driver member without entry of said  
predetermined user code, entry of said user code enabling power to transfer from said power  
source to said activation member to said driver member to permit both continuous and  
intermittent operation of said equipment during said programmable activation time period and  
prevent operation of said equipment upon expiration of said programmable activation time period.

44. The operating control device of claim 43 further comprising an a locking device for  
preventing nonuser access to said control device.

45. An operating control device for at least one piece of equipment, said equipment having a  
power source, an internal activation member and a drive member, said control device having:

an input device, said input device permitting input of a user access code;

a readout panel, said readout panel providing a status of said operating control device;

an internal control member, said control member being in direct communication with  
said input device, said power source, said driver member and said activation member,

a user programmable timer, said user programmable timer communicating with said  
control member and enabling power to flow from said power source to said driver member for

Appl. No. pct/us03/00587  
Amdt. dated July 19, 2004  
Article 34 Amendment

a user determined period of time, said user determined period of time being enterable by said user at said input device subsequent to entry of said user code;

a clock member, said clock member activating and deactivating said programmable timer based on user input;

wherein said internal control member prevents operation of said equipment by preventing power to transfer from said power source to said driver member without entry of said user code, and entry of said user code permits power to transfer from said power source to said activation member to said driver member to permit both continuous and intermittent operation of said equipment for the duration of said user determined period of time, said user determined period of time being monitored by said programmable timer.

46. A method of controlling the use of electronic equipment using a locking system, comprising the steps of:

- a. activating said electronic equipment,
- b. selecting activation of said locking system,
- c. entering a user code,
- d. selecting at least one programmable feature,
- e. selecting a programmable feature activation time period,
- f. saving said programmable feature and said programmable feature activation time period in

said locking system memory.

47. The method of claim 46 further comprising the step of repeating steps c-f until all intended programmable features are selected.

Appl. No. pct/us03/00587  
Amdt. dated July 19, 2004  
Article 34 Amendment

48. The method of claim 46 further comprising the step of selecting the programmable feature enabling timed operation.
49. The method of claim 48 further comprising the step of electing to set said timed operation by clock setting.
50. The method of claim 48 further comprising the step of electing said timed operation by the number of minutes of operation from the time of entering the programming.
51. The method of claim 46 further comprising the step of selecting the programmable feature enabling sleep mode.
52. The method of claim 51 further comprising the step of programming a start time and an end time to said sleep mode.
53. The method of claim 46 further comprising the step of selecting the programmable feature enabling a delayed start mode.
54. The method of claim 53 further comprising the step of programming a start time and an end time to said delayed start mode.
55. The method of claim 46 further comprising the step of selecting the programmable feature enabling a partial operation mode.
56. The method of claim 55 further comprising the step of electing to permit outgoing calls and block incoming calls for a predetermined, programmable, time period.

29

Appl. No. pct/us03/00587  
Amdt. dated July 19, 2004  
Article 34 Amendment

57. The method of claim 55 further comprising the step of electing to permit incoming calls and block outgoing calls for a predetermined, programmable, time period.