

DESCRIPTION

METHOD AND APPARATUS FOR CHANGING AND PUSHING A SOUND SOURCE OF A SUPPLEMENTARY SERVICE USING A RING BACK TONE ON CALLING

5

Technical Field

10 The present invention relates, in general, to a method
of changing the ringback tone replacing sound of a called
party to the sound source of another supplementary service of
a calling party using a dual tone multi-frequency shortcut
key during the placing of a call, a method of changing the
ringback tone replacing sound or service sound source (title
15 song) of the calling party to the sound source of the
supplementary service of the called party, a method of
pushing the service sound source of the calling party as the
service sound source of the called party in real time during
the placing of a call, and apparatuses for performing the
20 methods.

Background Art

25 Generally, a ringback tone refers to a signal tone sent
from an switching center to a calling terminal subscriber to
inform the calling terminal subscriber that a calling signal
is transmitting to a called terminal subscriber in a Public
Switched Telephone Network (PSTN) or a mobile communication
30 network. Recently, various ringback tone replacement
services for replacing typical ringback tones represented by
a conventional simple signal tone have been developed and
used. For example, services, such as 2Ring, COLORing or
FeelRing of Korea that allow a user to select a ringback tone
35 replacing sound for replacing a ringback tone equally
provided depending on the recommendations of the

International Telecommunication Union-Telecommunication (ITU-T), have been tremendously popularized. Such a ringback tone replacement service is described in detail below.

5 First, if a calling terminal subscribes to a ringback tone replacement service and requests a call connection to a called terminal managed by a called party's Mobile Switching Center (MSC), a calling party's MSC requests call termination location information (location request) from a Home Location Register (HLR). The HLR requests routing information
10 (routing request) from the called party's MSC in response to the request for the call termination location information, received from the calling party's MSC. The called party's MSC transmits routing information (Temporary Local Directory Number: TLDN) to the HLR in response to the routing
15 information request signal received from the HLR. Thereafter, the HLR transmits call termination location information to the calling party's MSC using the received routing information.

The calling party's MSC requests an Integrated Services
20 Digital Network (ISDN) User part (ISUP) call connection from the called party's MSC on the basis of the routing information. The called party's MSC reads ringback tone replacement service setting information, previously stored in a storage device, in response to the ISUP call connection
25 request signal transmitted from the calling party's MSC. Thereafter, in the case where a user corresponding to the called terminal has subscribed to the ringback tone replacement service, the called party's MSC transmits the ISUP call connection request signal to a sound source control
30 device, which is an Intelligent Peripheral (IP), through the use of the previously stored routing information of the sound source control device. At this time, the ISUP call connection request signal includes a called terminal identifier and calling terminal identifier. As a result of
35 the above procedure, channels are established between the

calling party's MSC, the called party's MSC and a sound source providing device.

5 The sound source providing device requests a sound source code from a sound source providing control server, which is a Service Control Point (SCP), on the basis of the called terminal identifier and calling terminal identifier. After the sound source providing control server searches for a sound source code, stored in connection with the called terminal identifier or the calling terminal identifier, in
10 response to the sound source code request signal, and transmits the searched sound source code to the sound source providing device. Thereafter, the sound source providing device transmits a ringback tone replacing sound corresponding to the sound source code, received from the
15 sound source providing control server, to the calling terminal through the established channel. When recognizing that the called terminal answers during the transmission of the ringback tone replacing sound to the calling terminal, the called party's MSC requests the sound source providing
20 device to release the ISUP call. After receiving the ISUP call release request signal from the called party's MSC, the sound source providing device releases a channel established with the calling terminal. Thereafter, the called terminal performs normal communication using a channel established
25 with the calling terminal.

 As described above, a conventional ringback tone replacement service allows a called terminal subscriber to let a calling terminal subscriber listen to a ringback tone replacing sound that is selected by the called terminal
30 subscriber and replaces a typical uniform ringback tone, through the use of the ringback tone replacement service. The reason that such a ringback tone replacement service commercially achieves success would be the fact that the service satisfies the desires of modern people for expressing
35 their individualities to some degree.

However, in a conventional ringback tone replacement service, sound sources can be changed only when a user subscribes to a communication service provider having a corresponding sound source. In this way, various current
5 supplementary services, such as a ringback tone replacement service, a background music service, a ringer service, a Karaoke service, a music mail service and a Music-On-Demand (MOD)/Video-On-Demand (VOD) service, are limited in that a
10 user can use the services only when he or she has subscribed to a communication service provider having corresponding sound sources. Further, there is an inconvenience in that, in order to change the sound sources of conventional supplementary services, a user should access the home page, wireless Internet or Automatic Response System (ARS) of a
15 communication service provider providing supplementary services, and enter the phone number of a called party.

Further, a conventional method of changing the sound sources of supplementary services is problematic in that, even when, for example, a calling party listens to the
20 ringback tone replacing sound of a called party and is impressed thereby, the calling party cannot immediately set the sound source of his or her supplementary service, such as a ringback tone replacement service, to the sound source of the ringback tone replacing sound of the called party.
25 Moreover, the conventional sound source change method for supplementary services is disadvantageous in that, since a supplementary service subscriber cannot change the sound sources of corresponding supplementary services in real time, the subscriber may forget that he or she will change a sound
30 source later or forget the phone number of a called party, so that there may occur the case where he or she cannot change the sound sources of supplementary services.

Further, communication services providing various pieces of information to mobile information terminals, such as the
35 mobile phones of subscribers, through various channels have recently increased with the development of electrical,

electronic and communication fields. Under such environments, communication service providers provide supplementary services, such as a ringback tone replacement service, a background music service, a ringer service, a
5 Karaoke service, a music mail service and a VOD/MOD service, to subscribers to comply with the demands of the subscribers desiring to use communication services more interestedly and individually. Recently, these supplementary services have been spotlighted by subscribers.

10 For example, a subscriber can wait for the establishment of a channel without tediousness while listening to an individual ringback tone replacing sound set by a calling party or called party, instead of a simple ringback tone, during the placing of a call. Further, the subscriber may
15 freely register the popular songs of singers, popular sound effects and mentions, classical music, his or her own sound effects, etc., and use them as his or her ringers. Further, the subscriber may select a desired song or music as a background sound, and then talks to an opposite party while
20 listening to the background sound during telephone conversation. In this way, conventional supplementary services allow the subscriber to more individually and interestedly use various communication services using the sound sources of the supplementary services selected by the
25 subscriber.

However, in the conventional supplementary services, sound sources can be changed only when a user subscribes to a communication service provider having a corresponding sound source. That is, various current supplementary services,
30 such as a ringback tone replacement service, a background music service, a ringer service, a Karaoke service, a music mail service and a Music-On-Demand (MOD)/Video-On-Demand (VOD) service, are limited in that a user can use the services only when he or she has subscribed to a
35 communication service provider having corresponding sound sources. Further, there is an inconvenience in that, in

order to change the sound sources of conventional supplementary services, a user should access the home page, wireless Internet or Automatic Response System (ARS) of a communication service provider providing supplementary services, and enter the phone number of a called party.

Further, a conventional method of changing the sound sources of supplementary services is problematic in that, even when, for example, a calling party listens to the ringback tone replacing sound of a called party and is impressed thereby, the calling party cannot immediately set the sound source of his or her supplementary service, such as a ringback tone replacement service, to the sound source of the ringback tone replacing sound of the called party. Moreover, the conventional sound source change method for supplementary services is disadvantageous in that, since a supplementary service subscriber cannot change the sound sources of corresponding supplementary services in real time, the subscriber may forget that he or she will change a sound source later or forget the phone number of a called party, so that the subscriber cannot easily change the sound sources of supplementary services at a desired time. Moreover, the conventional supplementary services are disadvantageous in that a calling party cannot immediately push his or her service sound source as the service sound source of a called party in real time while the calling party listens to the ringback tone replacing sound of the called party.

Description of Drawings

FIG. 1 is a view schematically showing the construction of a communication network to which a service according to a first embodiment of the present invention is applied;

FIG. 2 is a block diagram showing a service providing apparatus according to a first embodiment of the present invention;

FIG. 3 is a diagram showing a service of changing the sound source of another supplementary service using a ringback tone replacing sound during the placing of a call according to a first embodiment of the present invention;

5 FIG. 4 is a signal flowchart showing the signal processing method of the service according to a first embodiment of the present invention;

FIG. 5 is a signal flowchart showing the signal processing method of the service according to a first
10 embodiment of the present invention;

FIG. 6 is a signal flowchart showing the signal processing method of the service according to a first embodiment of the present invention;

FIG. 7 is a view showing a CP server according to a
15 first embodiment of the present invention;

FIG. 8 is a signal flowchart showing the signal processing method of the service of changing the sound source of another supplementary service using a ringback tone replacing sound during the placing of a call according to a
20 first embodiment of the present invention;

FIG. 9 is a diagram showing the signal processing method of the service according to a first embodiment of the present invention;

FIG. 10 is a diagram showing a processing method
25 including network interworking in the service according to a first embodiment of the present invention;

FIG. 11 is a diagram showing a processing method including network interworking in the service according to a first embodiment of the present invention;

30 FIG. 12 is a signal flowchart showing a subscription procedure for a sound source change service according to a first embodiment of the present invention;

FIG. 13 is a view showing shortcut keys for the service according to a first embodiment of the present invention;

35 FIG. 14 is a view showing a title song for the service according to a first embodiment of the present invention;

FIG. 15 is a view schematically showing the construction of a communication network to which a service according to a second embodiment of the present invention is applied;

5 FIG. 16 is a block diagram showing a service proving apparatus according to a second embodiment of the present invention;

FIG. 17 is a signal flowchart showing the subscription procedure of a sound source push service according to a second embodiment of the present invention;

10 FIG. 18 is a signal flowchart of a process of setting a service sound source in the sound source push service according to a second embodiment of the present invention;

15 FIG. 19 is a view showing the definition of shortcut keys for the sound source push service according to a second embodiment of the present invention;

FIG. 20 is a view showing the subscription to the sound source push service and the setting of service sound sources, and the list of sound sources pushed to a called party through the wired Internet in the sound source push service according to a second embodiment of the present invention;

20 FIG. 21 is a view showing the subscription to the sound source push service and the setting of service sound sources, and the list of sound sources pushed to a called party through the wireless Internet in the sound source push service according to a second embodiment of the present invention;

FIG. 22 is a signal flowchart showing the sound source push service according to a second embodiment of the present invention;

30 FIG. 23 is a diagram showing the sound source push service according to a second embodiment of the present invention;

FIG. 24 is a view schematically showing a process of providing the sound source push service according to a second embodiment of the present invention; and

FIG. 25 is a view showing a procedure of allowing a calling party to push at least one supplementary service sound source, preset by the calling party, as at least one supplementary service sound source of a called party, having
5 subscribed to another communication network, through the use of a DTMF shortcut key during the placing of a call using a mobile phone in the sound source push service according to a second embodiment of the present invention.

10 **Discousure**

Technical Problem

Accordingly, the present invention has been made keeping in mind the above problems occurring in the prior art, and an
15 object of the present invention is to provide a service method and apparatus, which allows a calling party to set or change the sound source of his or her supplementary service to a ringback tone replacing sound, set by a called party, in real time through the use of a DTMF shortcut key on a
20 wired/wireless telephone during the placing of a call in a wired/wireless communication network regardless of whether the calling party subscribes to a ringback tone replacement service.

Another object of the present invention is to provide
25 a service method and apparatus, which allows a calling party to present his or her ringback tone replacing sound or specific sound source (title song) to a called party as the sound source of the supplementary service thereof during the placing of a call.

30 Still another object of the present invention is to provide a service method and apparatus, which allows a non-subscribed called party to set the sound source of his or her supplementary service to a sound source gifted from a calling terminal subscriber, at the same time that the called
35 party subscribes to a corresponding supplementary service, in real time during the placing of a call.

Still another object of the present invention is to provide a service method and apparatus, which allows a calling party to use the sound source of a ringback tone replacing sound from another communication service provider, which the calling party listens to, after placing a call using a mobile phone or a normal telephone in a wired/wireless communication network, as the sound source of the supplementary service provided from a communication service provider to which the calling party subscribes.

Still another object of the present invention is to provide a service method and apparatus, which allows a calling party to push the sound source of the supplementary service, set by the calling party through the wired/wireless Internet or ARS, or a basic sound source provided from a service provider, as the sound source of the supplementary service of a called party in real time through the use of a DTMF shortcut key during the placing of a call using a wired/wireless telephone in the wired/wireless communication network, regardless of whether the calling party subscribes to a ringback tone replacement service or a background music service.

Still another object of the present invention is to provide a service method and apparatus, which allows a called party to set the sound source of his or her supplementary service to a sound source gifted from a calling party and use the gifted sound source, at the same time that the called party automatically subscribes to a corresponding service in real time even though the called party is not a subscriber to the corresponding service.

Still another object of the present invention is to provide a service method and apparatus, which allows a calling party to immediately set the service sound source of a called party to the title song or ringback tone replacing sound, set by the calling party through the wired/wireless Internet or ARS, or a basic sound source provided from a

service provider, using a DTMF shortcut key during the placing of a call.

Technical Solution

5
In accordance with an aspect of the present invention, there is provided a method of providing a sound source change service, which changes a sound source of at least one supplementary service of a calling party using a sound source
10 of a ringback tone replacing sound of a called party during placing of a call, in a service providing system connected to a Mobile Switching Center (MSC) managing at least one calling terminal and at least one called terminal through a mobile communication network, a service IP server and a Contents
15 Provider (CP) server, comprising detecting a DTMF shortcut key signal received from the calling terminal through the service IP server during the placing of a call using the calling terminal, receiving collected information from the service IP server in response to the DTMF shortcut key
20 signal, processing the collected information in a predetermined form, transmitting a ringback tone replacing sound code included in the collected information to the CP server on the basis of the processed information, the CP server extracting a sound source code of the supplementary
25 service corresponding to the ringback tone replacing sound code using a mapping table formed to allow a plurality of sound source codes, provided from at least a first Master Contents Provider (MCP) and a second MCP that provides the supplementary service to the calling party, and names of
30 singers and titles of songs corresponding to the plurality of sound source codes to refer to each other, receiving the sound source code from the CP server, and transmitting a sound source change request signal including calling party information, included in the collected information, and the
35 sound source code to the second MCP.

In accordance with another aspect of the present invention, there is provided a method of providing a sound source change service, which changes a sound source of at least one supplementary service of a calling party using a sound source of a ringback tone replacing sound of a called party during placing of a call, in a service providing system connected to a Mobile Switching Center (MSC) managing at least one calling terminal and at least one called terminal through a mobile communication network, a service IP server and a Contents Provider (CP) server, comprising detecting a DTMF shortcut key signal received from the calling terminal through the service IP server during the placing of a call using the calling terminal, receiving collected information from the service IP server in response to the DTMF shortcut key signal, processing DTMF shortcut key information, included in the collected information, transmitting a ringback tone replacing sound code included in the collected information to a first Master Contents Provider (MCP) that provides the ringback tone replacing sound of the called party on the basis of the processed information, receiving sound source information corresponding to the ringback tone replacing sound code from the first MCP, transmitting the sound source information to the CP server, the CP server extracting a sound source code of the supplementary service corresponding to the sound source information using a mapping table, receiving the sound source code from the CP server, and transmitting a sound source change request signal including calling party information, included in the collected information, and the sound source code, to a second MCP that provides the supplementary service.

Preferably, the service IP server may be placed in the MSC. Further, the service IP server may be placed in the service providing system.

Preferably, the collected information may include subscriber information, including a calling terminal identifier and a called terminal identifier corresponding to

the called terminal, a sound source code including MCP identification (ID) and serial number corresponding to the first MCP, and the DTMF shortcut key information.

5 Preferably, the collected information may be stored in a database of the service providing system, read in a First-In First-Out (FIFO) manner, and then sequentially transmitted to the CP server or the first MCP.

10 Preferably, the CP server may be a service providing Master Contents Provider (MCP) system including at least one CP and an Automatic Response System (ARS).

15 Preferably, the sound source change service providing method may further comprise the second MCP transmitting a sound source change request signal to a Service Control Point (SCP) when the supplementary service sound source is a ringback tone replacing sound source or a ringback tone sound source.

20 Preferably, the sound source change service providing method may further comprise notifying the calling terminal of change results for the supplementary service sound source using a short message through a Short Message Service Center (SMSC).

25 Preferably, the sound source change service providing method may further comprise the calling terminal accessing an ARS server or a Web/WAP (ME) server using a callback number to the ARS server or a callback URL to the Web/WAP (ME) server, included in the short message.

30 In accordance with a further aspect of the present invention, there is provided a method of providing a sound source change service, which changes a sound source of at least one supplementary service of a calling party using a sound source of a ringback tone replacing sound of a called party during placing of a call, in a plurality of service providing systems each connected to at least one Mobile Switching Center (MSC) managing at least one calling terminal and at least one called terminal through a mobile communication network, at least one service IP server and at

35

least one Contents Provider (CP) server, the service providing systems interworking with each other, comprising: detecting a DTMF shortcut key signal received from the calling terminal through a first service IP server in a first communication service provider network to which a called terminal subscriber subscribes during the placing of a call using the calling terminal, a first service providing system in the first communication service provider network receiving collected information from the first service IP server in response to the DTMF shortcut key signal, processing the collected information in a predetermined form, transmitting a ringback tone replacing sound code, included in the collected information, to a first MCP that provides the ringback tone replacing sound to the called party, on the basis of the processed information, receiving first sound source information corresponding to the ringback tone replacing sound code from the first MCP, the first service providing system transmitting the first sound source information to a second service providing system in a second communication service provider network to which a calling terminal subscriber subscribes, transmitting the first sound source information to a CP server in the second communication service provider network, the CP server extracting a sound source code of the supplementary service, corresponding to the first sound source information, using a mapping table formed to allow a plurality of pieces of sound source code information for the supplementary service of the calling party, and name information of a plurality of singers and title information of a plurality of songs corresponding to the sound source code information to refer to each other, receiving the sound source code from the CP server, and transmitting a sound source change request signal including calling party information, included in the collected information, and the sound source code to a second MCP that provides the supplementary service in the second communication service provider network.

Preferably, the sound source change service providing method may further comprise the second service providing system transmitting the calling party information and the first sound source information to a third MCP in the second communication service provider network interworking with the first MCP, receiving second sound source information, which corresponds to the first sound source information and is usable in the second communication service provider network, from the third MCP, and transmitting the second sound source information to the CP server so as to obtain the sound source code corresponding to the second sound source information.

In accordance with yet another aspect of the present invention, there is provided a method of providing a sound source change service, which changes a sound source of at least one supplementary service of a called party using a sound source of a ringback tone replacing sound of a calling party during placing of a call, in a service providing system connected to a Mobile Switching Center (MSC) managing at least one calling terminal and at least one called terminal through a mobile communication network, a service IP server, a Contents Provider (CP) server, and an Automatic Response System (ARS) server, comprising detecting a DTMF shortcut key signal received from the calling terminal through the service IP server during the placing of a call using the calling terminal, receiving collected information from the service IP server in response to the DTMF shortcut key signal, processing the collected information in a predetermined form, transmitting calling party information included in the collected information to a first MCP that provides the ringback tone replacing sound to the calling party on the basis of the processed information, receiving sound source information of the ringback tone replacing sound corresponding to the calling party information from the first MCP, transmitting the sound source information to the CP server, the CP server extracting a sound source code of the supplementary service corresponding to the sound source

information using a mapping table formed to allow a plurality of sound source codes, provided from at least the first MCP and a second MCP that provides supplementary services to the called party, and names of a plurality of singers and titles of a plurality of songs corresponding to the sound source codes to refer to each other, receiving the sound source code from the CP server, transmitting called party information, included in the collected information, and the sound source code to the second MCP, and transmitting a short message to the called terminal through a Short Message Service Center (SMSC), the short message including information used to request setting of the sound source of the supplementary service, and a callback number to the ARS server or a callback URL to a Web/WAP (ME) server, wherein the second MCP sets a sound source of the supplementary service to the sound source code in response to a sound source change request signal from the called terminal, while interworking with the ARS server or the Web/WAP (ME) server.

In accordance with still another aspect of the present invention, there is provided a method of providing a sound source change service, which changes a sound source of at least one supplementary service of a called party using a sound source of a title song of a calling party during placing of a call, in a service providing system connected to a Mobile Switching Center (MSC) managing at least one calling terminal and at least one called terminal through a mobile communication network, a service IP server and a Contents Provider (CP) server, and an Automatic Response System (ARS) server, comprising detecting a DTMF shortcut key signal received from the calling terminal through the service IP server during the placing of a call using the calling terminal, receiving collected information from the service IP server in response to the DTMF shortcut key signal, processing the collected information in a predetermined form, transmitting a sound source request signal for the title song to the CP server on the basis of the processed information,

receiving the sound source code from the CP server,
transmitting called party information, included in the
collected information, and the sound source code to a MCP
that provides the supplementary service to the called party,
5 and transmitting a short message to the called terminal
through a Short Message Service Center (SMSC), the short
message including information used to request setting of the
sound source of the supplementary service, and a callback
number to the ARS server or a callback URL to a Web/WAP (ME)
10 server, wherein the MCP sets a sound source of the
supplementary service to the sound source code in response to
a sound source change request signal from the called
terminal, while interworking with the ARS server or the
Web/WAP (ME) server.

15 Preferably, the sound source change service providing
method may further comprise transmitting a service
subscription request signal for the called party to a
subscriber management server.

Preferably, the sound source change service providing
20 method may further comprise the ARS server transmitting a
sound source change request signal to a Service Control Point
(SCP) through the CP server or the first MCP when the
supplementary service sound source is a ringback tone
replacing sound source or a ringback tone sound source.

25 Preferably, the supplementary service may include at
least one of a ringback tone replacement service, a ringer
service, a background music service, a Karaoke service, a
music mail service, a morning call service, a Music-On-Demand
(MOD) service and a Video-On-Demand (VOD) service.

30 In accordance with still another aspect of the present
invention, there is provided a method of providing a sound
source change service, which changes a sound source of at
least one supplementary service of a called party using a
specific sound source of a calling party during placing of a
35 call, in a plurality of service providing systems each
connected to a Mobile Switching Center (MSC) managing at

least one calling terminal and at least one called terminal through a mobile communication network, a service IP server, a Contents Provider (CP) server, and an Automatic Response System (ARS) server, comprising detecting a DTMF shortcut key signal received from the calling terminal through a first service IP server in a first communication service provider network to which a calling terminal subscriber subscribes during the placing of a call using the calling terminal, a first service providing system in the first communication service provider network receiving collected information from the first service IP server in response to the DTMF shortcut key signal, processing the collected information in a predetermined form, transmitting calling party information to a first CP server in the first communication service provider network that provides the specific sound source on the basis of the processed information, receiving sound source information of the specific sound source corresponding to the calling party information from the first CP server, the first service providing system transmitting the sound source information to a second service providing system in a second communication service provider network to which a called terminal subscriber subscribes, transmitting the sound source information to a second CP server in the second communication service provider network, the second CP server extracting a sound source code of the supplementary service, corresponding to the sound source information, using a mapping table formed to allow a plurality of pieces of sound source code information for the supplementary service, and name information of a plurality of singers and title information of a plurality of songs corresponding to the sound source code information to refer to each other, receiving the sound source code from the second CP server, transmitting a sound source change request signal including the called party information, included in the collected information, and the sound source code to a second MCP that provides the supplementary service in the second communication service

provider network, and transmitting a short message to the called terminal through a Short Message Service Center (SMSC), the short message including information used to request setting of the sound source of the supplementary service, and a callback number to the ARS server or a callback URL to a Web/WAP (ME) server, wherein the second MCP sets a sound source of the supplementary service to the sound source code in response to a sound source change request signal from the called terminal, while interworking with the ARS server or the Web/WAP (ME) server.

Preferably, the second CP server may include the second MCP.

In accordance with still another aspect of the present invention, there is provided a service providing apparatus for providing a sound source change service, which is connected to a Mobile Switching Center (MSC) managing at least one calling terminal and at least one called terminal through a mobile communication network, a service IP server and a contents provider (CP) server and adapted to provide the sound source change service, which includes a first service of changing a sound source of at least one supplementary service of a calling party using a sound source of a ringback tone replacing sound of a called party during placing of a call and a second service of changing a sound source of at least one supplementary service of the called party using a specific sound source of the calling party during the placing of a call, comprising a DTMF signal detecting unit detecting a DTMF shortcut key signal received from the calling terminal through the service IP server during the placing of a call using the calling terminal, a collected information processing unit processing collected information, received from the service IP server, in a predetermined form, a data transmitting/receiving unit receiving the collected information from the service IP server in response to the DTMF shortcut key signal, transmitting a sound source information request signal

adapted to request sound source information for the first supplementary service to a first MCP that provides the first supplementary service, receiving the sound source information from the first MCP, transmitting the sound source information to the CP server, receiving a sound source code from the CP server, and transmitting a sound source change request signal to a second MCP that provides the second supplementary service, and a control unit storing the processed information in a database, reading the processed information in a First-In First-Out (FIFO) manner, sequentially transmitting the read information to the first MCP, and controlling the DTMF signal detecting unit, the collected information processing unit and the data transmitting/receiving unit.

In accordance with still another aspect of the present invention, there is provided a service providing system, which is connected to a Mobile Switching Center (MSC) managing at least one calling terminal and at least one called terminal through a mobile communication network, a service IP server and a contents provider (CP) server and adapted to provide a sound source change service of changing a sound source of at least one supplementary service of a calling party using a sound source of a ringback tone replacing sound of a called party during placing of a call, comprising a memory storing therein a program, and a processor connected to the memory to execute the program, and wherein, by the program, the processor performs operations of detecting a DTMF shortcut key signal received from the calling terminal through the service IP server during the placing of a call using the calling terminal, receiving collected information from the service IP server in response to the DTMF shortcut key signal, processing the collected information in a predetermined form, transmitting, on the basis of the processed information, a ringback tone replacing sound code included in the collected information to the CP server, which extracts a sound source code of the supplementary service corresponding to the ringback tone

replacing sound code using a mapping table formed to allow a plurality of sound source codes, provided from at least a first MCP providing the ringback tone replacing sound to the called party and a second MCP providing the supplementary
5 service to the calling party, and names of a plurality of singers and titles of a plurality of songs corresponding to the sound source codes to refer to each other, receiving the sound source code from the CP server and transmitting a sound source change request signal including calling party
10 information, included in the collected information, and the sound source code to the second MCP.

In accordance with still another aspect of the present invention, there is provided a service providing system, which is connected to a Mobile Switching Center (MSC)
15 managing at least one calling terminal and at least one called terminal through a mobile communication network, a service IP server and a contents provider (CP) server and adapted to provide a sound source change service of changing a sound source of at least one supplementary service of a
20 calling party using a sound source of a ringback tone replacing sound of a called party during placing of a call, comprising a memory storing therein a program, and a processor connected to the memory to execute the program, and wherein, by the program, the processor performs operations of
25 detecting a DTMF shortcut key signal received from the calling terminal through the service IP server during the placing of a call using the calling terminal, receiving collected information from the service IP server in response to the DTMF shortcut key signal, processing DTMF shortcut key
30 information included in the collected information, transmitting a ringback tone replacing sound code included in the collected information to a first MCP that provides the ringback tone replacing sound to the called party on the basis of the processed information, receiving sound source
35 information corresponding to the ringback tone replacing sound code from the first MCP, transmitting the sound source

information to the CP server, which extracts a sound source code of the supplementary service corresponding to the sound source information using a mapping table formed to allow sound source code information of at least one supplementary service and a name of a singer and a title of a song corresponding to the sound source code information to refer to each other, receiving the sound source code from the CP server, and transmitting a sound source change request signal including calling party information, included in the collected information, and the sound source code to the second MCP.

In accordance with still another aspect of the present invention, there is provided a service providing system, which is connected to at least one Mobile Switching Center (MSC) managing at least one calling terminal and at least one called terminal through a mobile communication network, a service IP server and a contents provider (CP) server and adapted to provide a sound source change service of changing a sound source of at least one supplementary service of a calling party using a sound source of a ringback tone replacing sound of a called party during placing of a call, comprising a memory storing therein a program, and a processor connected to the memory to execute the program, and wherein, by the program, the processor performs operations of detecting a DTMF shortcut key signal received from the calling terminal through a first service IP server in a first communication service provider network to which a called terminal subscriber subscribes during the placing of a call using the calling terminal, allowing a first service providing system in the first communication service provider network to receive collected information from the first service IP server in response to the DTMF shortcut key signal, processing the collected information in a predetermined form, transmitting a ringback tone replacing sound code included in the collected information to a first MCP that provides the ringback tone replacing sound to the

called party on the basis of the processed information, receiving sound source information corresponding to the ringback tone replacing sound code from the first MCP, allowing the first service providing system to transmit the sound source information to a second service providing system in a second communication service provider network to which the calling terminal subscriber subscribes, allowing the second service providing system to transmit the sound source information to a CP server, which extracts a sound source code of the supplementary service corresponding to the sound source information using a mapping table formed to allow a plurality of pieces of sound source code information for the supplementary service of the calling party, and name information of a plurality of singers and title information of a plurality of songs corresponding to the sound source code information to refer to each other, in the second communication service provider network, receiving the sound source code from the CP server, and transmitting a sound source change request signal including calling party information, included in the collected information, and the sound source code to a second MCP that provides the supplementary service in the second communication service provider network.

In accordance with still another aspect of the present invention, there is provided a service providing system, which is connected to at least one Mobile Switching Center (MSC) managing at least one calling terminal and at least one called terminal through a mobile communication network, a service IP server, a contents provider (CP) server and an Automatic Response System (ARS) server, and adapted to provide a sound source change service of changing a sound source of at least one supplementary service of a called party using a specific sound source of a calling party during placing of a call, comprising a memory storing therein a program, and a processor connected to the memory to execute the program, and wherein, by the program, the processor

performs operations of detecting a DTMF shortcut key signal received from the calling terminal through the service IP server during the placing of a call using the calling terminal, receiving collected information from the service IP server in response to the DTMF shortcut key signal, processing the collected information in a predetermined form, transmitting a sound source code request signal for the specific sound source to the CP server on the basis of the processed information, receiving a sound source code from the CP server, transmitting called party information, included in the collected information, and the sound source code to a MCP that provides the supplementary service to the called party, transmitting a short message, including information used to request setting of the sound source of the supplementary service and a callback number to the ARS server or a callback URL to a Web/WAP (ME) server, to the called terminal through a Short Message Service Center (SMSC), and allowing the MCP to set the sound source of the supplementary service to the sound source code in response to a sound source change request signal from the called terminal while interworking with the ARS server or the Web/WAP (ME) server.

In accordance with still another aspect of the present invention, there is provided a service providing system, which is connected to a Mobile Switching Center (MSC) managing at least one calling terminal and at least one called terminal through a mobile communication network, a service IP server, a contents provider (CP) server and an Automatic Response System (ARS) server, and adapted to provide a sound source change service of changing a sound source of at least one supplementary service of a called party using a specific sound source of a calling party during placing of a call, comprising a memory storing therein a program, and a processor connected to the memory to execute the program, and wherein, by the program, the processor performs operations of detecting a DTMF shortcut key signal received from the calling terminal through the service IP

server during the placing of a call using the calling terminal, receiving collected information from the service IP server in response to the DTMF shortcut key signal, processing the collected information in a predetermined form, transmitting calling party information included in the collected information to a first MCP that provides the specific sound source on the basis of the processed information, receiving sound source information of the ringback tone replacing sound corresponding to the calling party information from the first MCP, transmitting the sound source information to the CP server, which extracts a sound source code of the supplementary service corresponding to the sound source information using a mapping table formed to allow a plurality of sound source codes, provided from at least the first MCP and a second MCP that provides the supplementary service to the called party, and names of a plurality of singers and titles of a plurality of songs corresponding to the sound source codes to refer to each other, receiving the sound source code from the CP server, transmitting called party information, included in the collected information, and the sound source code to the second MCP, transmitting a short message, including information used to request setting of the sound source of the supplementary service and a callback number to the ARS server or a callback URL to a Web/WAP (ME) server, to the called terminal through a Short Message Service Center (SMSC), and allowing the second MCP to set the sound source of the supplementary service to the sound source code in response to a sound source change request signal from the called terminal while interworking with the ARS server or the Web/WAP (ME) server.

In accordance with still another aspect of the present invention, there is provided a service providing system, which is connected to at least one Mobile Switching Center (MSC) managing at least one calling terminal and at least one called terminal through a mobile communication network, a

service IP server, a contents provider (CP) server and an Automatic Response System (ARS) server, and adapted to provide a sound source change service of changing a sound source of at least one supplementary service of a called party using a specific sound source of a calling party during placing of a call, comprising a memory storing therein a program, and a processor connected to the memory to execute the program, and wherein, by the program, the processor performs operations of detecting a DTMF shortcut key signal received from the calling terminal through a first service IP server in a first communication service provider network to which a called terminal subscriber subscribes during the placing of a call using the calling terminal, allowing a first service providing system in the first communication service provider network to receive collected information from the first service IP server in response to the DTMF shortcut key signal, processing the collected information in a predetermined form, transmitting calling party information to a first CP server in the first communication service provider network that provides the specific sound source on the basis of the processed information, receiving sound source information of the specific sound source corresponding to the calling party information from the first CP server, allowing the first service providing system to transmit the sound source information to a second service providing system in a second communication service provider network to which the called terminal subscriber subscribes, allowing the second service providing system to transmit the sound source information to a second CP server, which extracts a sound source code of the supplementary service corresponding to the sound source information using a mapping table formed to allow a plurality of pieces of sound source code information for the supplementary service, and name information of a plurality of singers and title information of a plurality of songs corresponding to the sound source code information to refer to each other, in the second communication service

provider network, receiving the sound source code from the second CP server, transmitting a sound source change request signal including called party information, included in the collected information, and the sound source code to a second
5 MCP that provides the supplementary service in the second communication service provider network, transmitting a short message, including information used to request setting of the sound source of the supplementary service and a callback number to the ARS server or a callback URL to a Web/WAP (ME)
10 server, to the called terminal through a Short Message Service Center (SMSC), and allowing the second MCP to set the sound source of the supplementary service to the sound source code in response to a sound source change request signal from the called terminal while interworking with the ARS server or
15 the Web/WAP (ME) server.

In accordance with still another aspect of the present invention, there is provided a method of providing a sound source push service, which pushes a sound source of at least one first supplementary service, set to correspond to at
20 least one calling terminal, as a sound source of at least one second supplementary service, set to correspond to at least one called terminal, during placing of a call, in a service providing system connected to a Mobile Switching Center (MSC) managing the calling terminal and the called terminal through
25 a mobile communication network, a service IP server and a contents provider (CP) server, comprising detecting a DTMF shortcut key signal received from the calling terminal through the service IP server during the placing of a call by the calling terminal, receiving collected information from
30 the service IP server in response to the DTMF shortcut key signal, processing the collected information in a predetermined form, transmitting a sound source information request signal, adapted to request sound source information for the first supplementary service, to a first MCP that
35 provides the first supplementary service on the basis of the processed information, the sound source information request

signal including a calling terminal identifier corresponding to the calling terminal, receiving the sound source information from the first MCP, transmitting the sound source information to the CP server, the CP server extracting a
5 sound source code corresponding to the sound source information using a mapping table, receiving the sound source code from the CP server, transmitting a sound source change request signal including called party information, included in the collected information, and the sound source code to a
10 second MCP that provides the second supplementary service.

Preferably, the service IP server may be placed in the MSC. Further, the service IP server may be placed in the service providing system.

Preferably, the CP server, the first MCP and the second
15 MCP may be included in a single contents provider.

Preferably, the first and second MCPs may be integrated into a single MCP.

Preferably, the collected information may include subscriber information, including calling party information
20 corresponding to the calling terminal and called party information corresponding to the called terminal, the sound source code including identifiers and serial numbers of contents providers (CP/MCP) that provide the supplementary service, and the DTMF shortcut key information.

Preferably, the processed information may be stored in a
25 database of the service providing system, read in a First-In First-Out (FIFO) manner, and then sequentially transmitted to the first MCP.

Preferably, the sound source information may include
30 names of singers and titles of songs.

Preferably, the mapping table may include a database formed to allow a plurality of sound source codes for supplementary services, provided from the first and second MCPs, and names of singers and titles of songs corresponding
35 to the plurality of sound source codes to refer to each other.

Preferably, the sound source push service providing method may further comprise the second MCP transmitting a sound source change request signal to a Service Control Point (SCP) when the second supplementary service is a ringback tone replacement service or a ringback tone service.

Preferably, the sound source push service providing method may further comprise notifying the called terminal of sound source change results for the second supplementary service. In this case, the notification of the sound source change results for the second supplementary service may be performed using a Short Message Service (SMS) through a Short Message Service Center (SMSC). The short message transmitted to the called terminal may include a callback number to an ARS server or a callback URL to a Web/WAP (ME) server.

In accordance with still another aspect of the present invention, there is provided a method of providing a sound source push service, which pushes a sound source of at least one first supplementary service, set to correspond to at least one calling terminal, as a sound source of at least one second supplementary service, set to correspond to at least one called terminal, during placing of a call, in a plurality of service providing systems each connected to a Mobile Switching Center (MSC) managing the calling terminal and the called terminal through a mobile communication network, a service IP server and a contents provider (CP) server, comprising detecting a DTMF shortcut key signal received from the calling terminal through a first service IP server in a first communication service provider network to which a calling terminal subscribes during the placing of a call using the calling terminal, a first service providing system in the first communication service provider network receiving collected information from the first service IP server in response to the DTMF shortcut key signal, processing the collected information in a predetermined form, transmitting a first sound source information request signal, adapted to request first sound source information for the first

supplementary service, to a first MCP that provides the first supplementary service, on the basis of the processed information, the first sound source information request signal including a calling terminal identifier corresponding to the calling terminal, receiving the first sound source information from the first MCP, the first service providing system transmitting the first sound source information to a second service providing system in a second communication service provider network to which the called terminal subscribes, the second service providing system transmitting the first sound source information to a CP server in the second communication service provider network, the CP server extracting a sound source code corresponding to the first sound source information using a mapping table, receiving the sound source code from the CP server, and transmitting a sound source change request signal including called party information, included in the collected information, and the sound source code to a second MCP that provides the second supplementary service in the second communication service provider network.

In accordance with still another aspect of the present invention, there is provided a service providing apparatus, which is connected to a Mobile Switching Center (MSC) managing at least one calling terminal and at least one called terminal through a mobile communication network, a service IP server and a contents provider (CP) server, and adapted to provide a sound source push service of pushing a sound source of at least one first supplementary service, set to correspond to the calling terminal, as a sound source of at least one second supplementary service, set to correspond to the called terminal, during placing of a call, comprising a data transmitting/receiving unit including an IP interface connected to at least one service IP server, a CP server interface connected to the CP server, a Short Message Service Center (SMSC) interface connected to a SMSC, an Internet Detail Record (IDR) interface connected to an IDR, a WAP/ME

push server interface connected to a WAP/ME push server, and a Web interface connected to a WAP/ME gateway, the data transmitting/receiving unit receiving and transmitting data through at least one of the interfaces, a control unit
5 including a task manager that processes data received through the data transmitting/receiving unit, a database processing unit including a database connected to the task manager and a Common Gateway Interface (CGI) connected to the database, and a network interworking unit including a SMSC interworking
10 unit, an IDR interworking unit, a Network Management System (NMS) interworking unit, a CP server interworking unit, a MCP interworking unit, and a Simple Network Management Protocol (SNMP) agent connected to the NMS.

Preferably, the sound source push service providing
15 apparatus may further comprise a MCP server interface connected to at least one MCP including the first and second MCPs.

In accordance with still another aspect of the present invention, there is provided a service providing apparatus,
20 which is connected to a Mobile Switching Center (MSC) managing at least one calling terminal and at least one called terminal through a mobile communication network, a service IP server and a contents provider (CP) server, and adapted to provide a sound source push service of pushing a
25 sound source of at least one first supplementary service, set to correspond to the calling terminal, as a sound source of at least one second supplementary service, set to correspond to the called terminal, during placing of a call, comprising a DTMF signal detecting unit detecting a DTMF shortcut key
30 signal received from the calling terminal through the service IP server during the placing of a call using the calling terminal, a collected information processing unit processing collected information received from the service IP server in a predetermined form, a data transmitting/receiving unit
35 receiving the collected information from the service IP server in response to the DTMF shortcut key signal,

transmitting a sound source information request signal adapted to request sound source information for the first supplementary service to a first MCP that provides the first supplementary service on the basis of information processed
5 by the collected information processing unit, receiving the sound source information from the first MCP, transmitting the sound source information to the CP server, receiving a sound source code from the CP server, and transmitting a sound source change request signal to a second MCP that provides
10 the second supplementary service, and a control unit storing the processed information in a database, reading the processed information in a First-In First-Out (FIFO) manner, sequentially transmitting the read information to the first MCP, and controlling the DTMF signal detecting unit, the
15 collected information processing unit and the data transmitting/receiving unit.

In accordance with still another aspect of the present invention, there is provided a service providing system, which is connected to a Mobile Switching Center (MSC)
20 managing at least one calling terminal and at least one called terminal through a mobile communication network, a service IP server and a contents provider (CP) server, and adapted to provide a sound source push service of pushing a sound source of at least one first supplementary service, set
25 to correspond to the calling terminal, as a sound source of at least one second supplementary service, set to correspond to the called terminal, during placing of a call, comprising a memory storing therein a program, and a processor connected to the memory to execute the program, and wherein, by the
30 program, the processor performs operations of detecting a DTMF shortcut key signal received from the calling terminal through the service IP server during the placing of a call using the calling terminal, receiving collected information from the service IP server in response to the DTMF shortcut
35 key signal, processing the collected information in a predetermined form, transmitting a sound source information

request signal, adapted to request sound source information for the first supplementary service and provided with a calling terminal identifier corresponding to the calling terminal, to a first MCP that provides the first
5 supplementary service, on the basis of the processed information, receiving the sound source information from the first MCP, transmitting the sound source information to the CP server, which extracts a sound source code corresponding to the sound source information using a mapping table,
10 receiving the sound source code from the CP server, and transmitting a sound source change request signal including called party information, included in the collected information, and the sound source code to a second MCP that provides the second supplementary service.

15 In accordance with still another aspect of the present invention, there is provided a service providing system, which is connected to a Mobile Switching Center (MSC) managing at least one calling terminal and at least one called terminal through a mobile communication network, a
20 service IP server and a contents provider (CP) server, and adapted to provide a sound source push service of pushing a sound source of at least one first supplementary service, set to correspond to the calling terminal, as a sound source of at least one second supplementary service, set to correspond
25 to the called terminal, during placing of a call, performing the steps of detecting a DTMF shortcut key signal received from the calling terminal through a first service IP server in a first communication service provider network to which a calling terminal subscribes during the placing of a call
30 using the calling terminal, a first service providing system in the first communication service provider network receiving collected information from the first service IP server in response to the DTMF shortcut key signal, processing the collected information in a predetermined form, transmitting a
35 first sound source information request signal, adapted to request first sound source information for the first

supplementary service, to a first MCP that provides the first supplementary service, on the basis of the processed information, the first sound source information request signal including a calling terminal identifier corresponding to the calling terminal, receiving the first sound source information from the first MCP, the first service providing system transmitting the first sound source information to a second service providing system in a second communication service provider network to which the called terminal subscribes, the second service providing system transmitting the first sound source information to a CP server in the second communication service provider network, the CP server extracting a sound source code corresponding to the first sound source information using a mapping table, receiving the sound source code from the CP server, and transmitting a sound source change request signal including called party information, included in the collected information, and the sound source code to a second MCP that provides the second supplementary service in the second communication service provider network.

Advantageous Effect

According to the present invention, a subscriber having subscribed to a service, who is a calling terminal user, can conveniently set the sound source of his or her supplementary service (for example, a ringback tone replacing sound source, a ringer sound source, a Karaoke sound source, a music mail sound source, a background music sound source, and MOD and VOD sound sources) to the ringback tone replacing sound of a called party immediately after listening to the ringback tone replacing sound of the called party at the time of attempting each call on-line.

Further, according to the present invention, the calling party can gift his or her set sound source (title song) or

ringback tone replacing sound to an opposite party (called party) as the sound source of a plurality of supplementary services thereof (a ringback tone replacement service, a background music service, a ringer change service, a Karaoke service, a music mail service, and a MOD/VOD service).

Further, according to the present invention, bi-directional, real-time services are possible during the placing of a call of a calling terminal subscriber, and the calling terminal subscriber can very conveniently use services, such as the change of the sound sources of supplementary services, using DTMF shortcut keys during the placing of a call.

Further, according to the present invention, a non-subscriber, who is a calling terminal user, can subscribe to the service and set his or her supplementary service sound source to the ringback tone replacing sound of the opposite party, immediately after listening to the ringback tone replacing sound of the opposite party at the time of attempting each call on-line. Further, the present invention provides the convenience of allowing the called party given the specific sound source or ringback tone replacing sound of the calling party as a gift to conveniently subscribe to the service and set the sound source.

Further, according to the present invention, a communication service provider network provides convenience in changing sound sources and subscribing to the service to users, thus obtaining subscription fees, monthly-incomings based on new subscription, and high-value added profits based on the setting of sound sources due to the increase of the number of changes of sound sources and new subscriptions.

Further, the present invention provides a service of allowing people inexperienced in on-line environments, such as the Internet, to subscribe to the service and change sound sources by pressing a DTMF key (DTMF shortcut key) during the placing of a call, thus enabling communication network service providers to yield additional profits due to the easy

inducement of new subscriptions and the increase of subscribers. Further, the subscribers can frequently change their sound sources, thus enabling communication network service providers, MCPs and CPs to increase additional profits due to the change of sound sources.

Further, according to the present invention, the calling terminal subscriber can push service sound sources set by the calling terminal subscriber through the wired/wireless Internet and ARS (in this case, the service sound sources include the title song or supplementary service sound source of the calling terminal subscriber) to the sound sources of a plurality of supplementary services of the called party (in this case, the supplementary services include a ringback tone replacement service, a background music service, a ringer service, a music mail service, a morning call service, and a MOD/VOD service) in real time using DTMF shortcut keys during the placing of a call. That is, according to the present invention, the calling party can easily and compulsorily set the supplementary service sound source of the called party to the supplementary service sound source of the calling party using the DTMF shortcut keys during the placing of a call, thus providing convenience and simplicity in the change of supplementary service sound sources.

According to the present invention, even in the case of a user who does not subscribe to the service yet, a calling party automatically subscribes to the sound source push service by pressing shortcut keys for service sound sources during the placing of a call, so that a procedure of subscribing to the service is greatly simplified.

Further, according to the present invention, a communication network service provider provides to users the convenience of service subscription procedure and an opportunity to make changes of various supplementary service sound sources from existing sound sources to other sound sources, thus yielding subscription fees, service fees and monthly incomings based on new subscription, and high value-

added profits based on the setting of sound sources due to the increase of the number of changes and the increase of new subscriptions.

Moreover, the present invention provides a service of
5 allowing people inexperienced in on-line environments, such as the Internet, to subscribe to the service and set/change sound sources by pressing a specific shortcut key on a telephone terminal during the placing of a call, thus enabling communication network service providers to yield
10 additional profits due to the easy inducement of new subscriptions and the increase of subscribers, and enabling the communication network service providers, MCPs and CPs to increase additional profits due to the change of sound sources because the subscribers can frequently change sound
15 sources.

Best Mode

20 Hereinafter, embodiments of the present invention will be described in detail with reference to the attached drawings.

First embodiment:

For reference, a service allowing a calling party to
25 change the sound source of his or her supplementary service using the ringback tone replacing sound of a called party or to present the ringback tone replacing sound of the calling party to the called party as the sound source of the supplementary service thereof during the placing of a call is
30 referred to as a sound source change service or a sound source change service during the placing of a call in the first embodiment to be described in the present specification.

FIG. 1 is a view schematically showing the construction
35 of a communication network to which a service according to a first embodiment of the present invention is applied.

Referring to FIG. 1, the communication network according to a first embodiment of the present invention includes at least a Mobile Switching Center (MSC) 103 and a Home Location Register (HLR) as components constituting the communication network. Further, in order to provide, for example, a ringback tone replacement service and a background music service, the communication network includes a SCP 111 that manages subscriber information for both the ringback tone replacement service and the background music service, and the ringback tone replacing sound codes and background music codes thereof, and an Intelligent Peripheral (IP) 109 that plays the sound source of a supplementary service, such as a ringback tone. The IP 109 is some other service IP that plays the sound sources of other supplementary services (other services) on the channel of a subscriber besides the service of the present invention. Further, the communication network includes a plurality of Mater Contents Providers (MCPs) 131, 133, 135 and 137 that register sound sources and manage the files thereof with respect to respective supplementary services, such as a ringback tone replacement service, a background music service, a ringer service, a music mail service, a morning call service, and a MOD/VOD service. Further, the communication network performs basic functions while interworking with a service IP server 100 providing the service of the present invention as well as the above-described other service IP 109, the plurality of MCPs 131 to 137 providing conventional supplementary services, and a service providing MCP system 260, which is additional equipment to provide the service of the present invention.

In detail, the communication network of the present invention includes a Mobile Switching Center (MSC) 103 managing at least one mobile communication terminal 101, a Service Switching point (SSP) 105, the other service IP 109 connected to both the MSC 103 and the SSP 105 through a MSC network 107, the service IP server 100, and the SCP 111 connected to both the other service IP 109 and the service IP

server 100. The SCP 111 is connected to a Wireless Information System Environment (WISE)/Client Care System (CS) 115, which is a kind of subscriber management server, through a WISE (CS/BS) network 113, which is a kind of subscriber management network, to a Network Management System (NMS) 119 through a NMS network 117, to a Short Message Service Center (SMSC) 123 through a SMSC network 121, and to an Internet Detail Record (IDR) system 127 through an IDR network 125.

Further, the communication network includes the plurality of MCPs 131, 133, 135 and 137. The MCPs 131 to 137 are coupled to Automatic Response Systems (ARSs) 132, 134, 136 and 138, respectively. The ARSs 132 to 138 are coupled to a mobile communication terminal 143 and a wired telephone 145 through a public switched telephone network or a mobile communication network 141. Further, the MCPs 131 to 137 and the ARSs 132 to 138 are coupled to at least one Internet user terminal 149 through the Internet 147.

Further, the communication network includes a service providing system 200 that provides a service (sound source change service during the placing of a call) of changing the sound source of another supplementary service using a ringback tone replacing sound during the placing of a call (hereinafter referred to as a "service providing system"). The service providing system 200 is coupled to the service IP server 100, the SCP 111 and the MCPs 131 to 137 through a firewall. The service providing system 200 includes a gateway (G/W) as a basic service providing apparatus. For example, the service providing system 200 includes a first service providing G/W 200A and a second service providing G/W 200S, as shown in FIG. 1. In this case, the first and second service providing G/Ws 200A and 200S are operated as active-active servers or active-standby servers.

Further, the service providing system 200 may include a Redundant Array of Inexpensive Disks (RAID) 251 coupled to the first and second service providing G/Ws 200A and 200S, as

shown in FIG. 1. The RAID 251 represents a device of repeatedly storing the same important data in various devices. If the RAID 251 is used, data input/output operations are balanced and overlapped, thus improving an entire system performance.

Further, the service providing system 200 may include an Operation, Administration and Maintenance Server (OA&M server: OMS) 253 coupled to both the first and second service providing G/Ws 200A and 200S. The OMS 253 has a function of operating and administering the system and executing billing processing and statistical processing at a remote place. The OMS 253 provides graphic user environments for convenience of operators. The OMS 253 is comprised of a server that operates/administers the service providing system 200, and subscribers. The OMS 253 functions as OA&M that performs configuration management, statistics management, operation management and fault management for the service providing system 200 and the RAID 251. For this function, the OMS 253 includes an interworking function with a Contents Provider (CP) server 261 and a CP ARS 263, which will be described later, a Web-based OA&M function, a Man Machine Communication (MMC) and Common Line Interface (CLI) processing function, a system configuration management function, a mapping table code management and statistics inquiry function, a system status and fault management function, and an interworking function with the NMS.

Further, the communication network of the present invention includes the CP server 261 and the CP ARS 263 coupled to the SCP 111, the MCPs 131 to 137, and the service providing system 200. The CP server 261 and the CP ARS 263 are adapted to provide the service of the present invention, and used as a service providing MCP system 260 for the present service. The CP ARS 263 may be included in the CP server 261. In this case, the CP server 261 represents the service providing MCP system 260. Further, both a service providing Web server 265 and a service providing Wireless

Application Protocol (WAP)/Mobile Explorer (ME) server 267 coupled to the Internet 147 may be coupled to the CP server 261. The CP ARS 263 is coupled to at least one telephone terminal 153 through the mobile communication network/public switched telephone network 151.

In the means time, when a subscriber requests the setting or change of a sound source to a supplementary service sound source through the use of a DTMF signal during the placing of a call, the CP server 261 of the present invention functions to change the sound source code of another supplementary service to correspond to the service provided from the service providing system 200 using subscriber information and corresponding sound source information while interworking with the service providing system 200. Further, the CP server 261 includes a connection protocol processing unit with the service providing system 200, a sound source managing unit for a communication supplementary service of the present invention (hereinafter referred to as a "sound source change service"), a subscriber managing unit for the sound source change service, a code managing unit for sound sources in the service providing system, a code managing unit for sound sources provided from other service providers, an update functioning unit of the service providing system for sound source codes, a database managing unit managing a sound source code DB, a sound source change service subscriber information DB, an external CP/MCP information DB and an external CP/MCP sound source code DB, a backup functioning unit, a statistics managing unit managing protocol message processing statistics, sound source code change statistics according to service providers and system load factor statistics, and a fault management functioning unit managing the connection failures of the service providing system and system failures.

The CP ARS 263 of the present invention allows a calling terminal subscriber or a called terminal subscriber to set/change and listen to the sound source of his or her

supplementary service using a mobile communication terminal,
or to use other services, such as gifts of the sound sources
for friends. For this operation, the CP ARS 263 includes an
interworking function with the service providing system 200,
5 an interworking function based on ITU-T No. 7 signaling or
R2/PRI signaling with the mobile switching center (MSC) and
the PSTN switching center, a first connection protocol
processing function that processes a connection protocol with
the CP server 261, a second connection protocol processing
10 function that processes a connection protocol with the MCP
131 providing conventional supplementary services, such as
ringback tone replacement services including conventional
FeelRing, COLORing and 2Ring, and a third connection protocol
processing function that processes a connection protocol with
15 other external MCPs.

Further, the CP ARS 263 includes a sound source download
and management function for the sound source change service
of the present invention, a supplementary service function of
gifting a selected sound source to a subscriber to another
20 service provider, copying the supplementary service sound
source of the subscriber to another service provider and
interworking between different network service providers, a
statistic function including the statistics of selected sound
sources, call processing statistics and system load factor
25 statistics, and a fault management function for system
failure management and TCP/IP interworking fault processing.
Further, the CP ARS 263 may process ITU-T No. 7 signaling
user part SS7 ISUP and Interactive Voice Response (IVR)
signals in the CP ARS server.

30 In the meantime, the above-described service IP server
100 is predicted to be placed in the MSC 103 or the service
providing system 200 with the later technical development of
electronic communication equipment. Therefore, the present
invention includes an example in which the service IP server
35 100 is an independent device, or in which it is an IP

functioning unit placed in the MSC 103 or the service providing system 200.

FIG. 2 is a block diagram showing a service providing apparatus according to a first embodiment of the present invention.

Referring to FIG. 2, the service providing apparatus according to the first embodiment of the present invention is a service device for allowing a calling terminal subscriber to change the sound source of the ringback tone replacing sound of a called party to the sound source of the supplementary service of the calling party using a DTMF shortcut key during the placing of a call, or to gift the sound source of the ringback tone replacing sound or title song of the calling party or specific sound source corresponding thereto to the called party as the sound source of the supplementary service of the called party. The service providing apparatus 200A basically includes an external data receiving unit receiving a user signal from an external intelligent network, a data processing unit processing received data, a database processing unit, and an external data transmitting unit transmitting processed data to another server.

In detail, for parts for the transmission/reception of external data, the service providing apparatus 200A includes an IP interface 201 coupled to at least one service IP server 100, an MCP interface 203 coupled to the MCPs 131, 133 and 135, a CP server interface 205 coupled to the CP server 261, an SMSC interface 207 coupled to the SMSC 123, an IDR interface 209 coupled to the IDR 127, a WAP/ME push server interface 211 coupled to the WAP/ME push server 155, a Web interface 213 coupled to a WAP/ME gateway 157, and a Simple Network Management Protocol (SNMP) agent 215 coupled to the NMS 119. The above-described SMSC interface 207 is an interface for Short Message Service (SMS) notification according to new subscription. For this operation, the SMSC interface 207 may use Short Message Peer-to-Peer (SMPP)

protocol. The IDR interface 209 is an interface interworking with the IDR 127 for the billing for services. The IDR interface 209 complies with standards defined by respective communication network service providers.

5 Further, the service providing apparatus 200A includes a task manager 217 managing all tasks in the system, a database 227 connected to the task manager 217, a Common Gateway Interface (CGI) 229 connected to the task manager 217, and a high availability module 231 increasing the availability of
10 the system. The task manager 217 includes a request processing task 219 adapted to request the setting or change of sound sources from the SCP 111 through the CP server 261 or the MCPs 131, 133 and 135, a code conversion tasks 221 converting the different sound source codes of the respective
15 MCPs into the sound source codes of required supplementary services, a log task 223 recording a log for tasks performed by the task manager 217, and a statistics task 225 processing the statistics of the tasks performed by the task manager 217.

20 Through the above-construction, the present invention can provide the following advantages to service users. First, a service subscriber can immediately set the sound source of his or her at least one supplementary service to the ringback tone replacing sound of an opposite party after
25 listening to the ringback tone replacing sound, using a DTMF shortcut key at the time of attempting each telephone call on-line. Second, a non-subscriber can immediately subscribe to a corresponding service and set a sound source in real time after listening to the ringback tone replacing sound of
30 the opposite party at the time of attempting a telephone call on line. Third, a calling subscriber can conveniently set and manage a sound source (title song) to be gifted to an opposite party (a called party) through the wired/wireless Internet and the CP ARS. Fourth, the calling subscriber can
35 induce an opposite party to subscribe to the corresponding service and to set a service sound source to the sound source

of the corresponding service by gifting a sound source (title song or ringback tone replacing sound), set by the calling subscriber, to the opposite party as the sound source of the supplementary service thereof using a DTMF shortcut key at
5 the time of attempting each telephone call on line.

Further, the present invention can provide the following advantages to communication service providers. First, a mobile communication service provider can yield additional profits due to the inducement of new subscription to
10 supplementary services and the increased number of subscribers. Second, in the case of the mobile communication service provider, the MCP and the CP, a subscriber can frequently change previously produced sound sources and then increase additional profits due to the change/reuse of the
15 sound sources. Third, the inducement of the new subscription of users, who do not know a method and procedure of subscribing to the service and are incapable of subscribing to the service, can be increased.

FIG. 3 is a view showing a service of allowing a calling
20 party to set the sound source of his or her supplementary service to the sound source of the ringback tone replacing sound of a called party using a DTMF shortcut key during the placing of a call according to a first embodiment of the present invention. FIG. 4 is a signal flowchart showing the
25 signal processing method of the service according to a first embodiment of the present invention.

Referring to FIGS. 3 and 4, if the calling party places a call to a called party who has subscribed to a ringback tone replacement service, the calling party receives the
30 ringback tone replacing sound of the called party depending on a ringback tone replacement service scenario at step 401. At this time, if the calling party is impressed thereby the ringback tone replacing sound of the called party and desires to change the ringback tone replacing sound to his or her own
35 service sound source, the calling party presses a DTMF shortcut key for the service sound source on a calling

terminal at step 403. The service IP server detects the corresponding shortcut key, and transmits information on a calling party phone number (calling party Mobile Identification Number: MIN), a called party phone number (called party MIN), a ringback tone replacing sound code and a DTMF shortcut key, which the service IP server collects for a current service, to the service providing system at step 405. The shortcut key for the service sound source is preset in such a way that, for example, 1# is used to change a ringback tone replacing sound, 2# is used to change background music, 3# is used to change a ringer, 4# is used to change a music mail, 5# is used to change MOD, and 6# is used to change VOD. Further, the service providing system includes a gateway (G/W) as the service providing apparatus of the present invention.

Next, the service providing system analyzes data received from the service IP server. That is, after analyzing at least the DTMF shortcut key, the service providing system transmits subscriber information and sound source information to the ringback tone replacement service MCP so as to detect the sound source information of the called party, for example, the name of a singer and the title of a song at step 407. The ringback tone replacement service MCP extracts the name of the singer name and the title of the song corresponding to the ringback tone replacing sound code and transmits the extracted information to the service providing system at step 409.

The service providing system requests a sound source code, which will be used for a supplementary service whose sound source is to be adopted in response to the request of the calling party and which corresponds to the name of the singer and the title of the song, from the CP server interworking with the service providing system to perform the service of the present invention at step 411. In response to the request, the CP server extracts the sound source code and transmits the extracted sound source code to the service

providing system at step 413. The service providing system requests a corresponding supplementary service providing MCP that provides the supplementary service of the calling party to set and change a sound source using the received sound source code at step 415.

5 The supplementary service providing MCP, having received the sound source change request signal from the service providing system, changes service setting information set with respect to the calling party at step 417. At this time,
10 if the service to be changed is a ringback tone replacement service, the supplementary service providing MCP requests the SCP to change the sound source of the ringback tone replacing sound of the calling party at step 419. Thereafter, the service providing system may notify the calling party of the
15 sound source change results using SMS, as shown in FIG. 3 (10). If the calling party does not subscribe to the corresponding service yet, the service providing system may request the WISE (CS) to register the calling party as a new subscriber, allow the calling party to automatically
20 subscribe to the corresponding service, and notify the calling party of sound source change results together with the subscription contents thereof. After a telephone conversation, the calling party accesses the ARS using a
25 callback number or URL address included in an SMS message to subscribe to the service, listen to the sound source, and confirm the change of the sound source (11).

FIG. 5 is a signal flowchart showing the signal processing method of the service according to a first embodiment of the present invention.

30 Referring to FIG. 5, if the CP server is constructed to include a plurality of MCP functions of providing respective supplementary services, the present invention can provide the service through a simplified procedure compared to the above-described embodiment. In detail, if the calling party places
35 a call to a called party, who has subscribed to a ringback tone replacement service, the calling party receives the

ringback tone replacing sound of the called party depending on a ringback tone replacement service scenario at step 501. At this time, if the calling party is impressed thereby the ringback tone replacing sound of the called party and desires to change the ringback tone replacing sound to his or her supplementary service sound source, the calling party presses a DTMF shortcut key for the service sound source on a calling terminal at step 503. The service IP server detects the corresponding shortcut key, and transmits information on a calling party phone number (calling party MIN), a called party phone number (called party MIN), a ringback tone replacing sound code and a DTMF shortcut key, which the service IP server collects for a current service, to the service providing system at step 505.

15 The service providing system detects a service request from the calling party by analyzing data received from the service IP server. Thereafter, the service providing system transmits subscriber information and sound source information to the CP server that provides the service of the present invention while interworking with the service providing system at step 507. At this time, the CP server recognizes the received information as a sound source change request signal for the specific supplementary service of the calling party, and changes the service setting information for the specific supplementary service of the calling party at step 509. If the service requested to be changed by the calling party is the ringback tone replacement service, the CP server requests the SCP to change the sound source of the ringback tone replacing sound of the calling party at step 511. Thereafter, the service providing system notifies the calling party of the sound source change results using SMS at step 513. If the calling party does not subscribe to the ringback tone replacement service yet, the service providing system may request the WISE (CS) to register the calling party as a new subscriber, allow the calling party to automatically subscribe to the corresponding service, and notify the

calling party of sound source change results together with the subscription contents thereof using SMS, as described in the above-embodiment. After a telephone conversation, the calling party accesses the ARS using a callback number or URL address included in an SMS message to subscribe to the service, listen to the sound source, and confirm the change of the sound source.

As described above, the service providing system according to the first embodiment of the present invention receives sound source information, such as the name of a singer and the title of a song, from the above-described ringback tone replacement service MCP, requests and obtains a sound source code corresponding to the sound source information from the CP server providing the present service. Thereafter, the service providing system extracts the corresponding sound source code from the CP server and changes the service setting information without requesting the above-described supplementary service providing MCP to change a sound source, thus providing the service of the present invention. At this time, the CP server includes the sound source information of respective ringback tone replacement service MCPs, and the service providing function of the supplementary service providing MCP. Especially, the CP server includes a mapping table formed to allow the sound source codes of various supplementary services, provided from the supplementary service providing MCPs, to refer to each other through the use of the sound source codes corresponding to ringback tone replacing sounds provided from the ringback tone replacement service MCP. The information in the mapping table is periodically updated by the respective MCPs.

FIG. 6 is a signal flowchart showing the signal processing method of the service according to a first embodiment of the present invention.

Referring to FIG. 6, if the CP server is constructed to include a plurality of MCP functions of providing respective supplementary services, the present invention can provide the

service through a simplified procedure compared to the above-described embodiment. In detail, if a calling party places a call to a called party, who has subscribed to the ringback tone replacement service, the calling party receives the ringback tone replacing sound of the called party depending on a ringback tone replacement service scenario at step 601. At this time, if the calling party is impressed thereby the ringback tone replacing sound of the called party and desires to change the ringback tone replacing sound to his or her own service sound source, the calling party presses a DTMF shortcut key for the service sound source on a calling terminal at step 603. The service IP server detects the corresponding shortcut key, and transmits information on a calling party phone number (calling party MIN), a called party phone number (called party MIN), a ringback tone replacing sound code and a DTMF shortcut key, which the service IP server collects for a current service, to the service providing system at step 605.

The service providing system requests a sound source code, which will be used for a supplementary service whose sound source is to be changed, from the CP server that provides the service of the present invention while interworking with the service providing system at step 607. At this time, the CP server extracts a sound source code from a mapping table by applying the subscriber information and the ringback tone replacing sound code, received from the service providing system, to the mapping table, and then transmits the sound source code to the service providing system at step 609. Further, the service providing system requests the supplementary service providing MCP that provides the supplementary service requested to be changed by the calling party to change the sound source using the received sound source code at step 611.

The supplementary service providing MCP, having received the sound source change request signal from the service providing system, changes service setting information set

with respect to the calling party at step 613. At this time, if the sound source to be changed is a ringback tone replacing sound source, the supplementary service providing MCP requests the SCP to change the sound source of the ringback tone replacing sound of the calling party at step 615. Thereafter, the service providing system may notify the calling party of the sound source change results using SMS. If the calling party does not subscribe to the corresponding service yet, the service providing system may request the WISE (CS) to register the calling party as a new subscriber, allow the calling party to automatically subscribe to the corresponding service, and notify the calling party of sound source change results together with the subscription contents thereof using SMS, as described in the above-described embodiments. After a telephone conversation, the calling party accesses the ARS using a callback number or URL address included in an SMS message to subscribe to the service, listen to the sound source, and confirm the change of the sound source.

As described above, the service providing system according to the first embodiment of the present invention may be adapted to request and obtain subscriber information and a sound source code corresponding to the ringback tone replacing sound code of the called party from the CP server and then request the supplementary service providing MCP to change the sound source, without receiving sound source information, such as the name of a singer and the title of a song, from the above-described ringback tone replacement service MCP. At this time, the CP server includes the sound source information of respective ringback tone replacement service MCPs. Especially, the CP server includes a mapping table adapted to map the sound source codes of various supplementary services, provided from the supplementary service providing MCPs, through the use of subscriber information and the ringback tone replacing sound codes provided from the ringback tone replacement service MCPs.

The information in the mapping table is periodically updated by at least MCPs provided in called and calling party sides.

FIG. 7 is a view showing the CP server according to a first embodiment of the present invention.

5 Referring to FIG. 7, the CP server 261 of the present invention frequently registers/uploads sound source information and sound source codes used for the provision of services through the plurality of MCP servers 131, 133, 135 and 137 that provide contents to the respective communication
10 network service providers. At this time, the CP server 261 configures a table using information on the service sound sources used in the respective communication networks, and configures and stores a mapping table 701 in which different service sound sources in the plurality of MCPs or the
15 plurality of communication networks can be mutually converted into actually identical sound sources.

Table 1

MCP code	Song	Singer	A communication network service provider	B communication network service provider	C communication network service provider
1	With sweetheart	A	0101010	0101010	0101010
2	Wedding invitation	B	257890	257890	437821
3	Wedding invitation	B	437821	257821	257890
4	Summer	C	123456	234567	345678

20 As described above, the CP server of the present invention includes, for example, a mapping table for the conversion of sound source codes shown in Table 1, thus enabling, for example, a calling party to use the ringback tone replacing sound of a called party as the supplementary service sound source of the calling party while interworking
25 with the service providing system, the ringback tone replacement service MCP and the supplementary service providing MCPs.

FIG. 8 is a signal flowchart showing the signal processing method of the service of allowing a calling party to set the supplementary service sound source of a called party to the ringback tone replacing sound source of the calling party or a title song, designated by the calling party through a Web/WAP (ME) or ARS, through the use of a DTMF shortcut key during the placing of a call using a mobile phone according to a first embodiment of the present invention. FIG. 9 is a diagram showing the processing method of the service according to a first embodiment of the present invention. In this embodiment, there is described a method of allowing a calling party to gift his or her preset sound source or ringback tone replacing sound to a called party as the sound source of the supplementary service of the called party during the placing of a call.

Referring to FIGS. 8 and 9, if the calling party places a call to a called party, who has subscribed to a ringback tone replacement service, the calling party receives the ringback tone replacing sound depending on the ringback tone replacement service scenario of the called party at step 801. At this time, the calling party presses a DTMF shortcut key for the service sound source on a calling terminal when desiring to gift his or her preset specific sound source (hereinafter referred to as a "title song") or ringback tone replacing sound to a called party as the sound source of the supplementary service of the called party at step 803. For example, DTMF shortcut keys for service sound sources may include a shortcut key "+1" for a gift of a ringback tone replacing sound, a shortcut key "+2" for a gift of background music, a shortcut key "+3" for the gift of a ringer sound source, a shortcut key "+4" for the gift of a music mail sound source, a shortcut key "+5" for the gift of a MOD sound source, and a shortcut key "+6" for the gift of a VOD sound source.

If the shortcut key for the service sound source is input from the calling terminal, the service IP server

detects the corresponding shortcut key, and transmits information on a calling party phone number (calling party MIN), a called party phone number (called party MIN), a ringback tone replacing sound code and a DTMF shortcut key, which the service IP server collects for the current ringback tone replacement service, to the service providing system at step 805. The service providing system includes a gateway (G/W) as the service providing apparatus of the present invention.

10 The service providing system requests the registration of a gift while requesting first service information including the title song information of the calling party from the CP server that interworks with the service providing system to provide the present service at step 807. Further,

15 the service providing system receives the first service information from the CP server at step 809. If the title song of the calling party is registered, the service providing system notifies the called party of the request for the setting of the sound source using SMS at step 811.

20 If the title song of the calling party is not registered, the service providing system transmits calling party information to the ringback tone replacement service MCP of the calling party, and receives the name of a singer and the title of a song corresponding to the ringback tone

25 replacing sound from the ringback tone replacement service MCP at steps 813 and 815. Further, the service providing system requests the registration of a gift while requesting second service information including a sound source code corresponding to the name of a singer and the title of a song

30 to be used for the gift service from the CP server at step 817. Further, the service providing system receives the second service information from the CP server at step 819. Thereafter, the service providing system notifies the called party of a setting request for a gift of the sound source

35 using SMS at step 821. The called party accesses the CP ARS to listen to, set and change the sound source at steps 823

and 825. At this time, if, for example, the called party is a non-subscriber to the ringback tone replacement service, the called party may subscribe to the service depending on the guidance of the CP ARS.

5 As described above, the calling terminal subscriber gifts his or her title song or ringback tone replacing sound to the called party as the sound source of the supplementary service of the called party through the above procedure. That is, the service providing system of the present
10 invention prepares the setting of the sound source of the specific supplementary service of the called party to correspond to the service request shortcut key of the calling terminal subscriber. The called party can access the service providing system through the CP ARS to more
15 conveniently set the sound source of the specific supplementary service of the called party to the sound source gifted from the calling party. Further, if the called party is a non-subscriber to the service, the called party can conveniently subscribe to the service depending on the
20 guidance of the accessed CP ARS. In the meantime, if communication service providers to which the calling party and the called party subscribe are different, there should be interworking therebetween. This case is described in detail below.

25 FIG. 10 is a diagram showing a service of allowing a calling party to set the sound source of his or her supplementary service to the sound source of the ringback tone replacing sound of a called party having subscribed to another communication network using a DTMF shortcut key
30 during the placing of a call using a mobile phone according to a first embodiment of the present invention. For ease of understanding of this embodiment, numerals (1) to (11) are expressed in FIG. 10.

35 Referring to FIG. 10, if the calling party places a call to a called party, who has subscribed to a ringback tone replacement service, the calling party listens to the

ringback tone replacing sound of the called party depending on a ringback tone replacement service scenario. At this time, if the calling party is impressed thereby the ringback tone replacing sound of the called party and desires to
5 change the ringback tone replacing sound to his or her own service sound source, the calling party presses a DTMF shortcut key for the service sound source contracted between mobile communication service providers on a calling terminal, for example, "1#" used to change a ringback tone replacing
10 sound (1). Then, the service IP server in a communication service provider network (a first communication service provider network), to which the called party subscribes, detects the corresponding shortcut key (2). The service IP server transmits information on a calling party phone number
15 (calling party MIN), a called party phone number (called party MIN), a ringback tone replacing sound code, and a DTMF shortcut key, which the service IP server collects for a current service, to a first service providing system in the first communication service provider network (3).

20 Next, the first service providing system, having received the collected information from the service IP server, analyzes the information (DTMF key analysis) and transmits the analyzed results to the ringback tone replacement MCP (a first MCP) of the called party (4). The
25 first MCP extracts the name of a singer and the title of a song of the corresponding ringback tone replacing sound code, and transmits the extracted information to the first service providing system. Thereafter, the first service providing system transmits the collected information (for example,
30 calling party/called party information including calling party MIN/called party MIN) and the singer name and song title corresponding to the ringback tone replacing sound of the called party to a second service providing system in a communication service provider network (a second
35 communication service provider network) to which the calling party subscribes (5).

Next, the second service providing system transmits information indicating whether the calling party subscribes to the corresponding service and sound source information to the second MCP while interworking with a corresponding service MCP (for example, the ringback tone replacement MCP of the calling party: a second MCP), thus requesting a sound source code corresponding to the name of a singer and the title of a song for the ringback sound replacing sound of the called party from the second MCP (6). The second service providing system transmits sound source information, including the sound source code corresponding to the singer name and the song title, to the CP server in the second communication service provider network, and receives a new sound source code to be used for the supplementary service of the calling party from the CP server (7). Thereafter, the second service providing system requests the second MCP to change the service sound source using the calling party information and the received new sound source code (8). If the calling party is a non-subscriber to the service, the service providing system allows the calling party to automatically subscribe to the ringback tone replacement service. Further, the second MCP requests the SCP server to change the sound source of the calling terminal subscriber (9). Further, the second service providing system notifies the calling terminal of the sound source change results using SMS after transmitting billing information to the IDR server for billing processing (10). If the calling party does not subscribe to the corresponding service yet, the second service providing system allows the calling party to automatically subscribe to the service, and then notifies the calling terminal of subscription contents together with sound source change contents using SMS. Then, the calling party accesses the CP ARS after a telephone conversation to listen to the sound source and confirm the change of the sound source.

FIG. 11 is a diagram showing a service of allowing a calling party to gift his or her preset title song or ringback tone replacing sound to a called party, having subscribed to another communication network, as the supplementary service sound source of the called party through the use of a DTMF shortcut key during the placing of a call using a mobile phone according to a first embodiment of the present invention. For ease of understanding of this embodiment, numerals (1) to (13) are expressed in FIG. 11.

10

Referring to FIG. 11, if the calling party places a call to a called party having subscribed to a ringback tone replacement service, the calling party receives the ringback tone replacing sound of the called party depending on a ringback tone replacement service scenario. In the case where the calling party desires to gift a specific sound source, such as a title song set through the Web/ME (WAP) or ARS by the calling party, or a ringback tone replacing sound to the called party as a supplementary service sound source, the calling party presses a shortcut key for a service sound source on a calling terminal, for example, "1*" to change a ringback tone replacing sound (1). Then, a first service IP server in a communication service provider network (a first communication service provider network), to which the called party subscribes, detects the corresponding shortcut key (2). The first service IP server transmits information on a calling party phone number (calling party MIN), a called party phone number (called party MIN), and a ringback tone replacing sound code, which the first service IP server collects for a current service, to a first service providing system in the first communication service provider network (3).

Next, the first service providing system transmits the data received from the first service IP server to a second service providing system in a communication service provider network (a second communication service provider network) to

which the calling party subscribes (4). The second service providing system requests and receives the information of the title song of the calling party from a second CP server in the second communication service provider network (5). If
5 the title song of the calling party is registered, the second service providing system transmits the sound source information of the calling party to the first service providing system (7).

Next, the first service providing system requests the
10 title song information of the calling party and the registration of a gift from the first CP server in the first communication service provider network, and receives the sound source code of a corresponding sound source (8). Further, the first service providing system notifies the
15 called party of a message indicating the setting request for the sound source or the receipt of the gift of the sound source using SMS (9). Thereafter, the first service providing system transmits information, indicating that the gift of the sound source has been given, to the second
20 service providing system (10). The called party having received the SMS message accesses the CP ARS in the first communication service provider network to subscribe to the service and listen to and set the sound source (11).

In the meantime, after the procedure (5), if the title
25 song of the calling party is not registered, the second service providing system transmits calling party information to the calling party's MCP in the second communication service provider network, and then receives the name of a singer and the title of a song corresponding to the ringback
30 tone replacing sound of the calling party (6). Further, the second service providing system transmits the sound source information, including the name of the singer and the title of the song, to the CP server in the second communication service provider network and then receives a sound source
35 code to be used for the supplementary service. Thereafter, the second service providing system requests the calling

party's MCP to change the sound source using the calling party information and the received sound source code. Next, procedures (7) to (11) are performed in the same manner as those of the above-embodiment.

5 Further, if the supplementary service of the called party requested by the calling party at the above procedure (8) is a ringback tone replacement service, the first CP server requests the called party's MCP, that is, the ringback tone replacement MCP of the called party side in this case,
10 to set/change the sound source of the ringback tone replacement sound of the called party (12). Then, the called party's MCP requests the first SCP server in the first communication service provider network to set/change the sound source of the ringback tone replacing sound of the
15 called party.

FIG. 12 is a signal flowchart showing a subscription procedure for a sound source change service according to a first embodiment of the present invention.

Referring to FIG. 12, if a calling terminal subscriber
20 requests a subscription to the communication supplementary service of the present invention (sound source change service) at step 1201, information indicating whether the calling terminal subscriber subscribes to the service may be stored in a subscriber database (DB). Thereafter, the
25 subscriber DB transmits service subscription information, including at least calling terminal identifier provided from the calling terminal subscriber when subscribing to the sound source change service, to a Home Location Register (HLR) at
30 step 1203. The HLR sets the sound source change service in the profile of a corresponding calling terminal subscriber on the basis of the received service subscription information at
step 1205. Further, the subscriber DB transmits the subscriber information of the calling terminal subscriber, who has applied for the sound source change service of the
35 present invention, to the service providing apparatus at step 1207. The service providing apparatus sets a sound source

change service code using the received subscriber information at step 1209. The sound source change service code corresponds to at least one piece of subscriber information set by the user.

5 FIG. 13 is view showing a method of utilizing the sound source change service according to a first embodiment of the present invention.

Referring to FIG. 13, a calling terminal subscriber sets DTMF shortcut keys for the sound source change service on the
10 calling terminal thereof. That is, the calling terminal subscriber sets the shortcut keys so as to use them for a service of changing the sound source of at least one supplementary service of the calling terminal subscriber to the ringback tone replacing sound of the called party
15 (hereinafter referred to as a "first sound source change service). For example, shortcut keys for the first sound source change service includes a shortcut key "1+#" used to change the sound source of a ringback tone replacement service to the sound source of the ringback tone replacing
20 sound of the called party, a shortcut key "2+#" used to change the sound source of a ringer to the sound source of the ringback tone replacing sound of the called party, a shortcut key "3+#" used to change the sound source of background music to the sound source of the ringback tone
25 replacing sound of the called party, a shortcut key "4+#" used to change the sound source of a music mail to the sound source of the ringback tone replacing sound of the called party, a shortcut key "5+#", used to change the sound source of MOD to the sound source of the ringback tone replacing
30 sound of the called party, and a shortcut key "6+#" used to change the sound source of VOD to the sound source of the ringback tone replacing sound of the called party.

Further, the calling terminal subscriber sets shortcut keys used to set the sound source change service or to gift a
35 sound source on or to the called terminal of an opposite party. That is, the calling terminal subscriber sets the

shortcut keys to use them for a service of gifting the title song or ringback tone replacing sound of the calling terminal subscriber to the called party as at least one supplementary service sound source of the called party (hereinafter referred to as a "second sound source change service"). For example, the shortcut keys for the second sound source change service include a shortcut key "1+*" used to set the sound source of the ringback tone replacing sound of the called party to the sound source of the title song or ringback tone replacing sound of the calling party, a shortcut key "2+*" used to set the sound source of the ringer of the called party to the sound source of the title song or ringback tone replacing sound of the calling party, a shortcut key "3+*" used to set the sound source of the background music of the called party to the sound source of the title song or ringback tone replacing sound of the calling party, a shortcut key "4+*" used to set the sound source of the music mail of the called party to the sound source of the title song or ringback tone replacing sound of the calling party, a shortcut key "5+*" used to set the sound source of MOD of the called party to the sound source of the title song or ringback tone replacing sound of the calling party, and a shortcut key "6+*" used to set the sound source of VOD of the called party to the sound source of the title song or ringback tone replacing sound of the calling party.

As described above, the present invention defines the DTMF shortcut keys on the calling terminal so as to use the sound source change services. In the meantime, such a shortcut key may be added or changed depending on the definition of the services. The above-described supplementary services include at least one supplementary service, to which the calling or called terminal subscriber subscribes through at least one specific communication service provider. The setting information for the supplementary services may be stored in the database of a corresponding contents provider or master contents provider,

or a database system, such as SCP. For example, the supplementary service setting information is set with respect to the calling or called terminal subscriber, as shown in Table 2.

5 Table 2

Service name	Service code	Sound source code	Sound source title	Sound source singer name
Ringback tone replacing sound	A1	A 0001	Mountain birds	AA
Ringer	A2	A 0002	Sea	AB
Background music	A3	A 0003	Sky	AC
Music mail	A4	A 0004	River	AD
Morning call	A5	A 0005	Sound	AE
MOD	A6	A 0006	Song	AF
VOD	A7	A 0007	Movie	AG

As shown in Table 2, if the calling or called terminal subscriber subscribes to the ringback tone replacement, ringer, background music, Karaoke, music mail, morning call,
10 MOD and VOD services, the setting information related to the subscribed services is stored in the service providing apparatus or the contents provider server. The ringer, Karaoke and music mail services may be used without separate subscriptions to services. Such a supplementary service can
15 be very conveniently set or gifted by allowing the calling terminal subscriber to only press the shortcut keys on the calling terminal through the sound source change services of the present invention.

FIG. 14 is a view showing a title song according to a
20 first embodiment of the present invention.

Referring to FIG. 14, a calling terminal subscriber may set his or her title song through a title song management means, such as an Internet personal field 1401 used to manage the sound sources of sound source change services, and
25 utilize the sound source change services of the present invention through the use of the title song management means.

For example, the calling terminal subscriber can gift his or her title song to the called party as the supplementary service sound source of the called party while registering and managing the title song through the Web/WAP (ME) or the
5 ARS system using the title song management means provided from a service providing system. In the meantime, the title song may be designated according to service types in such a way that, if there is a single title song, it is set to a representative title song, while if there are a plurality of
10 title songs, the title songs can be set with respect to respective services. For example, if the title songs are two or more, the calling terminal subscriber can set the title songs by allocating priorities to the title songs or classifying the title songs according to time bands or
15 prefixes with respect to sound source change services. In the present embodiment, a first title song 1403 and a second title song 1405 are registered, and a priority is allocated to the first title song 1403. Further, if a plurality of title songs are registered, a priority can be set and changed
20 by each subscriber having subscribed to the service.

As described above, the calling terminal subscriber can select/listen to/manage his or her title songs using the wired Internet, the wireless Internet, the Automatic Response System (ARS), etc. Further, the calling terminal subscriber
25 can conveniently gift his or her sound source to the called party using the title song management system. Moreover, in the present invention, even a calling terminal subscriber, who is a non-subscriber to the sound source change services of the present invention, can use the services at the same
30 time to automatically subscribe to the sound source change services. In this case, it is preferable to perform a separate confirmation procedure, such as the notification of an SMS message to the non-subscriber.

35 Second embodiment:

FIG. 15 is a view schematically showing the construction of a communication network to which a service according to a second embodiment of the present invention is applied.

Referring to FIG. 15, the communication network according to the second embodiment of the present invention includes at least an MSC 1503 and a HLR as components constituting the communication network. Further, in order to provide specific supplementary services, such as a ringback tone replacement service and a background music service, the communication network includes a SCP 1511 that manages the subscribers to the ringback tone replacement/the background music services, and the codes of ringback tone replacing sounds and background music, and an Intelligent Peripheral (IP) 1509 that plays a ringback tone replacing sound to a calling party. Further, the communication network includes a plurality of MCPs 1531, 1533, 1535 and 1537 that register the sound sources of the respective supplementary services and manage the files thereof. Further, the communication network performs basic functions while interworking with the IP 1509, a service IP server 1500 which is an intelligent peripheral used to provide the additional communication service according to the second embodiment of the present invention (hereinafter referred to as a "push service"), the MCPs 1531 to 1537 used to provide respective supplementary services, and a service providing MCP system 1660 which is additional equipment used to provide the service of the present invention. In the present specification, the sound source push service includes at least a service of allowing a calling party to compulsorily set the supplementary service sound source of a called party to the supplementary service sound source of the calling party.

In detail, the communication network of the present invention includes an MSC 1503 managing at least one mobile communication terminal 1501, a Service Switching Point (SSP) 1505, the intelligent peripheral 1509 coupled to both the MSC 1503 and the SSP 1505 through a Mobile Switching Center

(MSC)/Personal Communication Exchange (PCX) network 1507, the service IP server 1500, and a Service Control Point (SCP) 1511 coupled to both the IP 1509 and the service IP server 1500. The SCP 1511 is coupled to a WISE (CS) 1515, which is
5 a kind of subscriber management server, through a WISE network 1513, which is a kind of subscriber management network, to a Network Management System (NMS) 1519 through a NMS network 1517, to a SMSC 1523 through a SMSC network 1521, and to an Internet Detail Record (IDR) system 1527 through an
10 IDR network 1525.

Further, the communication network includes the plurality of MCPs 1531, 1533, 1535 and 1537 coupled to the SCP 1511. The MCPs 1531 to 1537 are coupled to ARSs 1532, 1534, 1536 and 1538 related to respective services,
15 respectively. The ARSs 1532 to 1538 are coupled to a mobile communication terminal 1543 and a wired telephone 1545 through a mobile communication network or a public switched telephone network (MSC/PSTN) 1541. Further, the MCPs 1531 to 1537 and the ARSs 1532 to 1538 are coupled to at least one
20 Internet user terminal 1549 through the Internet 1547.

Further, the communication network includes a sound source push service providing system 1600 (hereinafter referred to as a "service providing system") that provides a service of allowing a calling party to push his or her
25 service sound source or ringback tone replacing sound as the supplementary service sound source of a called party using a DTMF shortcut key during the placing of a call according to the present invention. The service providing system 1600 is coupled to the service IP server 1500, the SCP 1511 and the
30 MCPs 1531 to 1537. The service providing system 1600 includes a Gateway (G/W) as a basic device. For example, the service providing system 1600 includes a first gateway 1600A and a second gateway 1600S as shown in FIG. 15. In this case, the first and second gateways 1600A and 1600S are
35 operated as active-active servers or active-standby servers.

Further, the service providing system 1600 may include a Redundant Array of Inexpensive Disks (RAID) 1651 coupled to the first and second service providing G/Ws 1600A and 1600S, as shown in FIG. 15. The RAID 1651 represents a device of
5 repeatedly storing the same important data in various devices. If the RAID 1651 is used, data input/output operations are balanced and overlapped, thus improving an entire system performance.

Further, the service providing system 1600 may include
10 an Operation, Administration and Maintenance Server (OA&M server: OMS) 1653 connected to both the first and second gateways 1600A and 1600S. The OMS 1653 has a function of operating and administering the system and executing billing processing and statistical processing at a remote place. The
15 OMS 1653 provides graphic user environments for convenience of operators. The OMS 1653 is comprised of a server that operates/administers the service providing system 200, and subscribers. The OMS 1653 functions as OA&M that performs configuration management, statistics management, operation
20 management and fault management for the service providing system 1600 and the RAID 1651. For this function, the OMS 1653 includes an interworking function with a CP server 1661 and a CP ARS 1663, which will be described later, a Web-based OA&M function, a Man Machine Communication (MMC) and Common
25 Line Interface (CLI) processing function, a system configuration management function, a mapping table code management and statistics inquiry function, a system status and fault management function, and an interworking function with the NMS.

Further, the communication network according to the
30 second embodiment of the present invention includes the contents provider (CP) server 1661 and the CP ARS 1663 connected to the SCP 1511, the MCPs 1531 to 1537, and the service providing system 1600. The CP server 1661 and the CP
35 ARS 1663, adapted to provide the service of the present invention, can be used as a service providing MCP system 1660

to provide the present service. Therefore, the CP server 1661 and the CP ARS 1663 are included in the service providing system 1600 in wider sense. The service providing MCP system 1660 includes a Web server 1665 and a WAP/ME
5 server 1667 connected to the Internet. The CP ARS 1663 may be connected to at least one telephone terminal 1553 through the mobile communication network/public switched telephone network 1551.

When a calling party pushes his or her service sound
10 source as the service sound source of the called party using a DTMF signal, the CP server 1661 functions to change the service sound source of a called party or the code thereof to correspond to the service sound source of the calling party, provided from the service providing system 1600, using
15 subscriber information and corresponding sound source information while interworking with the service providing system 1600. Further, the CP server 1661 includes a connection protocol processing unit with the service providing system 1600, a sound source managing unit for the
20 sound source push service, a subscriber managing unit for the sound source push service, a code managing unit for sound sources in the service providing system, a code managing unit in the service providing system for service sound sources provided from other service providers, an update functioning
25 unit of the service providing system for sound source codes, a database managing unit that manages a sound source code DB, a sound source push service subscriber information DB, an external CP/MCP information DB and an external CP/MCP sound source code DB, a backup functioning unit, a statistics
30 managing unit that manages protocol message processing statistics, sound source code change statistics according to service providers and system load factor statistics, and a fault management functioning unit that manages the connection failures of the service providing system and system failures.

35 The CP ARS 1663 allows the called terminal subscriber to listen to the service sound source of the called party

subscriber, confirm the setting of the service sound source, or use services, such as gifts for friends, when the called terminal subscriber accesses the service providing system through the sound source push service. For this operation, 5 the CP ARS 1663 includes an interworking function with the service providing system 1600, an interworking function with a MSC based on ITU-T No. 7 signaling and a PSTN exchange based on R2/PRI signaling, a first connection protocol processing function that processes a connection protocol with 10 the CP server 1661, a second connection protocol processing function that processes a connection protocol with at least one MCP providing conventional supplementary services, such as a ringback tone replacement service, a ringer service, a background music service, a Karaoke service, a music mail service, a morning call service, a MOD/VOD service, and a 15 third connection protocol processing function that processes a connection protocol with other external MCPs.

Further, the CP ARS 1663 includes a sound source download and management function for the sound source push 20 service of the present invention, supplementary service functions including the pushing of a selected sound source to a subscriber having subscribed to another service provider, the copy of the sound source of a subscriber having subscribed to another service provider and other 25 supplementary services interworking between network service providers, a statistic function including the statistics of selected sound sources, call processing statistics and system load factor statistics, and a fault management function for system failure management and TCP/IP interworking fault 30 processing. Further, the CP ARS 1663 may process ITU-T No. 7 signaling user part SS7 ISUP and Interactive Voice Response (IVR) functions in the CP ARS server.

In the meantime, the above-described service IP server 1500 is predicted to be placed in the MSC 1503 or the service 35 providing system 1600 with the later technical development of electronic communication equipment. Therefore, the present

invention includes an example in which the service IP server 1500 is an independent device, or in which it is an IP functioning unit placed in the MSC 1503 or the service providing system 1600.

5 FIG. 16 is a block diagram showing a service providing apparatus according to a second embodiment of the present invention.

Referring to FIG. 16, the service providing apparatus according to the second embodiment of the present invention is a service device that allows a calling terminal subscriber to push his or her supplementary service sound source as the supplementary service sound source of a called party using a DTMF shortcut key during the placing of a call. The service providing apparatus 1600A basically includes an external data receiving unit that receives a user signal from at least one external intelligent peripheral (IP), a data processing unit that processes the received data, a database processing unit, a Short Message Service Center (SMSC) interworking processing unit, an Internet Detain record (IDR) interworking processing unit, a Network Management System (NMS) interworking processing unit, a service providing MCP system interworking unit, an external MCP interworking unit and an external data transmitting unit that transmits processed results to another server. The service providing apparatus 1600A of the present invention performs basic functions while interworking with the IP, at least one MCP that provides each supplementary service, the service providing MCP system, which is the additional equipment of the present invention, the CP ARS, which is the ARS of the present invention, and the Web/WAP (ME) for the processing of access to the wired/wireless Internet.

In detail, for parts for transmission/reception of external data, the service providing apparatus 1600A includes an IP interface 1601 coupled to at least one IP 1509, an MCP interface 1603 coupled to the MCPs 1531, 1533 and 1535, a CP server interface 1605 coupled to the CP server 1661, a SMSC

interface 1607 coupled to the SMSC 1523, an IDR interface 1609 coupled to the IDR 1527, a WAP/ME push server interface 1611 coupled to a WAP/ME push server 1555, a Web interface 1613 coupled to a WAP/ME gateway 1557, and a Simple Network Management Protocol (SNMP) agent 1615 connected to the NMS 1519. The above-described SMSC interface 1607 is an interface for short message service notification (SMS notification) according to new subscription. For this operation, the SMSC interface 1607 may use a Short Message Peer-to-Peer (SMPP) protocol. The IDR interface 1609 is an interface interworking with the IDR 1527 for billing for services. The IDR interface 1609 complies with standards defined by respective communication network service providers.

Further, the service providing apparatus 1600A includes a task manager 1617 managing all tasks in the system, a database 1627 connected to the task manager 1617, a Common Gateway Interface (CGI) 1629 connected to the task manager 1617, and a high availability module 1631 increasing the availability of the system. The task manager 1617 includes a request processing task 1619 adapted to request the setting or change of sound sources from the SCP 1511 through the CP server 1661 or the MCPs 1531, 1533 and 1535, a code conversion task 1621 converting the different sound source codes of the respective MCPs into the sound source codes of required supplementary services, a log task 1623 recording a log for tasks performed by the task manager 1617, and a statistics task 1625 processing the statistics of the tasks performed by the task manager 1617.

Through the above-construction, the present invention can provide the following advantages to service users. First, a calling terminal subscriber having subscribed to the present service can compulsorily set at least one supplementary service sound source of a called party to at least one supplementary service sound source of the calling party in real time using a DTMF shortcut key while listening

to the ringback tone replacing sound set by the called party at the time of attempting each call. Second, a calling terminal user, who does not subscribe to the service, can immediately subscribe to the service and push his or her sound source as the sound source of the called party in real time by pressing a specific DTMF shortcut key while listening to the ringback tone replacing sound at the time of attempting each call. At this time, the present service provider preferably ensures the confirmation of the subscription of the calling terminal user to the service using SMS or the like. Third, a calling terminal subscriber pushes at least one of supplementary service sound sources, such as a title song, a ringback tone replacing sound, a ringer sound source, a background music sound source, a music mail sound source, etc., which are preset by the calling terminal subscriber, as at least one supplementary service sound source of the called party using a DTMF shortcut key at the time of attempting each call. Accordingly, the called party can immediately use the sound source of the calling terminal subscriber as his or her supplementary service sound source.

Further, the present invention can provide the following advantages to communication service providers. First, a mobile communication service provider can yield additional profits due to the inducement of new subscription to supplementary services and the increased number of subscribers. Second, the mobile communication service provider, the MCP and the CP provide environments in which a subscriber can frequently change his or her supplementary service sound source, and then increase additional profits due to the change/reuse of the sound sources. Third, the inducement of the new subscription of subscribers, who do not know a method and procedure of subscribing to the service and are incapable of subscribing to the service, can be increased.

FIG. 17 is a signal flowchart showing the subscription procedure of the sound source push service according to a second embodiment of the present invention.

Referring to FIG. 17, if a calling terminal user requests a subscription to the supplementary service of the present invention (sound source push service) at step 1701, whether the calling terminal user subscribes to the service is stored in the subscriber database DB. Thereafter, the subscriber DB transmits service subscription information including at least calling terminal identifier, provided from the calling terminal user when subscribing to the sound source push service, to a Home Location Register (HLR) at step 1703. The HLR sets the sound source push service on the profile of the corresponding calling terminal subscriber on the basis of the received service subscription information at step 1705. Further, the subscriber DB transmits the subscriber information of the calling terminal subscriber, having applied for the sound source push service of the present invention, to the service providing apparatus at step 1707. Further, the service providing apparatus sets a sound source push service code using the received subscriber information at step 1709. The sound source push service code corresponds to at least one piece of subscriber information set by the user. As described above, the calling terminal user can subscribe to the present service through the wired/wireless Internet, the ARS, an agency/customer center, etc., and then push his or her service sound source as the service sound source of a called party.

FIG. 18 is a signal flowchart of a process of setting a service sound source in the sound source push service according to a second embodiment of the present invention. In this embodiment, a procedure of automatically subscribing to the present service is described.

Referring to FIG. 18, while listening to the ringback tone replacing sound of a called party after calling the called party at step 1801, a calling party presses a DTMF

shortcut key on a calling terminal so as to push his or her set supplementary service sound source as the sound source of a supplementary service preset by the called party. At this time, the DTMF shortcut key signal of the calling terminal is transmitted to a service IP server through a MSC in a communication network at step 1803. The service IP server recognizes the received DTMF signal as an intelligent network service call, and detects the DTMF shortcut key signal at step 1805. Thereafter, the service IP server transmits collected information, including a calling terminal identifier corresponding to a calling terminal, a called terminal identifier corresponding to a called terminal, sound source information for the ringback tone replacing sound, and the DTMF shortcut key information, to the service providing system at step 1807.

The service providing system requests from the CP server information, indicating whether the supplementary service sound source selected through the push service by the calling party exists, and the supplementary service sound source at step 1809. In this case, the CP server includes the service providing MCP system that provides the service according to the second embodiment of the present invention. The CP server searches the subscriber database for information indicating whether the calling and called parties subscribe to the present service through the use of data including the subscriber information of the calling terminal identifier and the called terminal identifier, received from the service providing system, at step 1811. If the calling or called party does not subscribe to the present service, the CP server requests the WISE (Customer care System: CS) of a communication service provider to allow the calling or called party to subscribe to the service at step 1813. Further, the CP server responds to the request from the service providing system at step 1815.

As described above, in the present invention, the service providing system automatically performs a service

subscription procedure even though the calling or called party does not subscribe to the present service yet. Through the above procedure, the calling party can push his or her at least one supplementary service sound source or ringback tone replacing sound source, or a basic sound source provided from the present service provider, as at least one supplementary service sound source of the called party through the wired/wireless Internet of the Web/WAP (ME) and the ARS, or compulsorily set at least one supplementary service sound source of the called party to at least one service sound source of the calling party.

FIG. 19 is a view showing the definition of shortcut keys for the sound source push service according to a second embodiment of the present invention.

Referring to FIG. 19, the calling terminal subscriber uses shortcut keys on a calling terminal so as to push the sound source of his or her supplementary services, such as a title song, ringback tone replacing sound, ringer, background music, music mail, MOD and VOD, as at least one supplementary service sound source of the called party. For example, if sound sources set by the calling party correspond to service types, that is, if the calling party respectively sets the service sound sources, such as the ringback tone replacing sound source, ringer sound source, and background music sound source, the shortcut keys for the sound source push service may be used in such a way that a shortcut key "1+*" is used to set the ringback tone replacing sound source of the called party to the ringback tone replacing sound source of the calling party, a shortcut key "2+*" is used to set the ringer sound source of the called party to the ringer sound source of the calling party, a shortcut key "3+*" is used to set the background music sound source of the called party to the background music sound source of the calling party, a shortcut key "4+*" is used to set the music mail sound source of the called party to the music mail sound source of the calling party, a shortcut key "5+*" is used to set the MOD

sound source of the called party to the MOD sound source of the calling party, and a shortcut key "6+*" is used to set the VOD sound source of the called party to the VOD sound source of the calling party.

5 Further, if the service sound source (title song) set by the calling party is composed of a single sound source or if the calling party uses his or her ringback tone replacing sound as the title song (service sound source) without setting the service sound source, shortcut keys for the sound
10 source push service may be used in such a way that a shortcut key "1+*" is used to set the ringback tone replacing sound source of the called party to the service sound source of the calling party, a shortcut key "2+*" is used to set the ringer sound source of the called party to the service sound source
15 of the calling party, a shortcut key "3+*" is used to set the background music sound source of the called party to the service sound source of the calling party, a shortcut key "4+*" is used to set the music mail sound source of the called party to the service sound source of the calling party, a shortcut key "5+*" is used to set the MOD sound
20 source of the called party to the service sound source of the calling party, and a shortcut key "6+*" is used to set the VOD sound source of the called party to the service sound source of the calling party.

25 The definition and example of the above-described shortcut keys are summarized and shown in Table 3. The definition of the shortcut keys for the sound source push service, or the definition of the service may be changed with the operations of the service. Further, the definition may
30 be extended depending on the addition of services. Further, the calling terminal subscriber can freely change and set the shortcut keys for the sound source push service within an allowable range defined by a service operator.

Table 3

DTMF shortcut key	Service item
1+*	Ringback tone replacing sound source push

2+*	Ringer sound source push
3+*	Background music sound source push
4+*	Music mail sound source push
5+*	MOD sound source push
6+*	VOD sound source push

As shown in Table 3, in the sound source push service of the present invention, the calling party can immediately set/change the sound source of the specific supplementary service of a called party, selected by the calling party, to the supplementary service sound source of the calling party by pressing a specific DTMF shortcut key on the calling terminal during the placing of a call. For example, if the calling party requests the sound source push service by pressing the shortcut key "1+*" on the calling terminal during the placing of a call, the service sound source set by the calling party using the sound source push service is pushed as the supplementary service sound source of the called party. This method may be more efficiently used in the case where the called subscriber does not know how to use a method of subscribing to the supplementary service and changing a service sound source.

FIG. 20 is a view showing the subscription to the sound source push service and the setting of service sound sources, and the list of sound sources pushed to a called party through the wired Internet in the sound source push service according to a second embodiment of the present invention. FIG. 21 is a view showing the subscription to the sound source push service and the setting of service sound sources, and the list of sound sources pushed to a called party through the wireless Internet in the sound source push service according to a second embodiment of the present invention.

Referring to FIG. 20, a subscriber having subscribed to the present service can designate and manage at least one sound source as his or her supplementary service sound source. For example, the subscriber can designate a service

sound source provided from the first MCP as his or her service sound source (title song). If the subscriber designates and uses a plurality of service sound sources according to respective services, supplementary service sound sources, such as a ringback tone replacing sound (ringback tone) source provided from the first MCP, a ringer sound source provided from the second MCP, a background music sound source provided from the third MCP, a morning call sound source provided from the fourth MCP, a music mail sound source provided from the fifth MCP, and a MOD/VOD sound source provided from the sixth MCP, are stored in a storage space of the subscriber coupled to the Internet. Further, the subscriber can manage the supplementary service sound sources stored in his or her storage space in the form of a homepage 2001 through the use of the wired/wireless Internet, ARS, etc. At this time, the subscriber can perform pre-listening for the service sound source designated by the subscriber through the wired Internet by clicking a corresponding sound source. Further, in the sound source push service according to the second embodiment of the present invention, dates and opposite parties' phone numbers for transmitted supplementary service sound sources can be recorded and stored at the homepage 2001 provided from the communication service provider, as shown in FIG. 20. In this way, the service sound sources designated by the subscriber are used to be pushed as the supplementary service sound sources of the called party in real time using the DTMF shortcut key during the placing of a call or the listening of a ringback tone replacing sound.

Referring to FIG. 21, as described above, the subscriber having subscribed to the present service can store and manage at least one supplementary service sound source of a ringback tone replacing sound source, a ringer sound source, a background music sound source, a morning call sound source, a music mail sound source and a MOD/VOD sound source provided from at least one MCP, as his or her supplementary service

sound source, in his or her storage space accessible by a mobile communication terminal. In this case, the storage space includes a predetermined space within a storage device provided from the service provider to the subscriber.

5 Further, the user can subscribe to the present service, set his or her at least one service sound source, manage the list of service sound sources pushed by the subscriber to the called party, and utilize services, such as the way of using the present service, on a menu screen 2101. In this way, at

10 least one service sound source designated (set) by the subscriber is used to be pushed as the supplementary service sound source of the called party in real time using the DTMF shortcut key during the placing of a call or the listening of a ringback tone replacing sound.

15 FIG. 22 is a signal flowchart showing the sound source push service according to a second embodiment of the present invention. FIG. 23 is a diagram showing the sound source push service according to a second embodiment of the present invention. For reference, numerals are expressed in FIG. 23

20 for ease of understanding of the present invention.

Referring to FIGS. 22 and 23, if a calling party places a call to a called party having subscribed to a ringback tone replacement service, the called party receives a ringback tone replacing sound depending on a ringback tone replacement

25 service scenario at step 2201. At this time, the calling party presses a DTMF shortcut key for a service sound source on a calling terminal in the case where the calling party desires to push at least one of his or her preset supplementary service sound sources as at least one

30 supplementary service sound source of the called party at step 2203. For example, service sound source shortcut keys includes a shortcut key "1+*" used to push a ringback tone replacing sound, a shortcut key "2+*" used to push a background music sound source, a shortcut key "3+*" used to

35 push a ringer sound source, a shortcut key "4+*" used to push a music mail sound source, a shortcut key "5+*" used to push

a MOD sound source, and a shortcut key "6+*" used to push a VOD sound source.

5 If the shortcut key for the service sound source is input from the calling terminal, the service IP server receives the service sound source shortcut key from the MSC at step 2205. Further, the service IP server detects a specific DTMF signal used as the service sound source shortcut key at step 2207. Thereafter, the service IP server transmits information on a calling party phone number
10 (calling party MIN), a called party phone number (called party MIN), a ringback tone replacing sound code and a DTMF shortcut key, which the service IP server collects for a current ringback tone replacement service, to the service providing system at step 2209. In this case, the service
15 providing system includes a gateway G/W as a service providing apparatus according to the second embodiment of the present invention.

The service providing system requests the title song information and sound source push service information of the
20 calling party from the CP server interworking with the service providing system to provide the present service at step 2211. In response to the request, the CP server searches a database at step 2213. Thereafter, if the title song exists in the database, the CP server transmits a
25 response signal, including the sound source information of the title song, to the service providing system at step 2215.

If the title song of the calling party does not exist in the database at step 2213, the CP server transmits a response signal, indicating that the title song is not registered in
30 the database, to the service providing system at step 2215. The service providing system, having confirmed that the title song of the calling party is not registered, transmits calling party information to a first MCP that provides a supplementary service selected using a DTMF shortcut key by
35 the calling party (hereinafter referred to as a "first supplementary service"), and then receives the name of a

singer and the title of a song corresponding to the sound source of the first supplementary service from the first MCP at step 2219. Thereafter, the service providing system requests from the CP server a sound source code corresponding to the name of the singer and the title of the song, to be used for the supplementary service of the called party (hereinafter referred to as a "second supplementary service"), which is selected using the DTMF shortcut key, at step 2221. At this time, a service registration request signal for allowing the called party, who is an object to the sound source push service, to automatically subscribe to the service is transmitted to the CP server together with the sound source code request signal (refer to FIG. 18). In response to the request from the service providing system, the CP server transmits the sound source code to the service providing system at step 2223. In this case, the sound source code is extracted from a mapping table formed to allow sound source codes, singer names and song titles for various supplementary services, provided from a plurality of MCPs, to refer to each other.

Next, the service providing system transmits a sound source setting/change request signal to a second MCP that provides a second supplementary service at step 2225. The sound source change request signal includes the sound source information of the title song of the calling party, or the sound source code of the first supplementary service and called party information, such as a called terminal identifier. At this time, if the second supplementary service is a ringback tone replacement service or background music service, the second MCP transmits the sound source change request signal to the SCP at step 2227. Thereafter, the service providing system notifies the called terminal that the first supplementary service sound source is pushed as a second supplementary service sound source using SMS of the SMSC at steps 2229 and 2231. Through the above process, the calling party conveniently pushes his or her

supplementary service sound source as the supplementary service sound source of the called party and then sets the supplementary service sound source of the called party using a DTMF shortcut key during the placing of a call. Meanwhile,
5 in this embodiment, the called party accesses the CP ARS connected to the CP server to listen to a sound source, confirm sound source information and change the sound source, and to newly subscribe to the present service and change subscription information. If the called party changes a
10 sound source, the sound source change information thereof is transmitted to a corresponding MCP.

FIG. 24 is a view schematically showing a procedure of providing the sound source push service according to a second embodiment of the present invention. In FIG. 24, numerals
15 are expressed for ease of understanding of the present invention.

Referring to FIG. 24, the calling party subscribes to the sound source push service at the CP server of the present invention-in this case, the CP server includes the service
20 providing MCP system-through the wired/wireless Internet, such as Web or WAP (ME), or ARS, and sets the sound source of his or her sound source push service to at least one title song (1). If the calling party does not set the title song, the ringback tone replacing sound of the calling party or a
25 basic sound source provided from a service provider can be used as the sound source of the present service. Next, the calling party presses a DTMF shortcut key on a calling terminal so as to push the title song in the sound source push service, set by the calling party, or a specific
30 supplementary service sound source (hereinafter referred to as a "first service sound source") as at least one supplementary service sound source of the called party (hereinafter referred to as a "second service sound source") in real time using a DTMF shortcut key while listening to the
35 ringback tone replacing sound at the time of placing a call (2). The supplementary service sound source of the calling

or called party includes a ringback tone replacing sound source, a ringer sound source, a background music sound source, a music mail sound source, a morning call sound source and a MOD/VOD sound source.

5 Next, the IP server (service IP server), providing the sound source push service according to the second embodiment of the present invention, receives a DTMF shortcut key from a MSC. Further, the service IP server detects an intelligent network service call from the DTMF shortcut key received from
10 the MSC (DTMF detection)(3). Thereafter, the service IP server transmits collected information, including the phone number information of calling and called terminals, the ringback tone replacing sound source information of the called party and the DTMF shortcut key information, to the
15 service providing system (4). In detail, the collected information includes the subscriber information (calling number and called number), the DTMF shortcut key information and the ringback tone replacing sound source code.

 Next, the service providing system requests the sound
20 source information of the first service sound source from the CP server using the data received from the IP server and receives a response signal to the request (5). Further, the service providing system transmits a sound source change request signal to a MCP having the second service sound
25 source (6). Thereafter, the service providing system notifies the called party of the sound source information pushed by the calling party in the form of an SMS message through the SMSC (7). At this time, the SMS message includes the details of the sound source push service used by the
30 calling party and a callback number to the CP ARS, or a callback URL to the Web/WAP (ME) server.

 Next, the service providing system transmits a completion message, indicating that the notification message for the results of the sound source push service has been
35 transmitted to the called terminal, to the CP server (8). The CP server performs an automatic subscription procedure

for the present service with respect to the called party through the WISE (CS) (9). Such a subscription procedure is performed in the case where the called party does not subscribe to the present service. Further, the CP server
5 transmits the details of the use of the sound source push service to the Internet Detain record (IDR) system so as to bill the calling party for the sound source push service (10).

In the meantime, the called party accesses a
10 corresponding service MCP system using a callback number to the CP ARS or Web/WAP (ME) callback URL included in the SMS message (11). At this time, if the supplementary service of the called party is a ringer download service, the called party accesses a ringer MCP using the callback URL. Further,
15 if the supplementary service of the called party is one of the ringback tone replacement service, the background music service, the music mail service and the MOD/VOD service, the called party may access the CP ARS, and the MCP system providing the corresponding service. Further, the CP server
20 requests the SCP to allow the called party to subscribe to the corresponding service and set a corresponding sound source if the called party is a non-subscriber to the service (12).

Next, an interworking procedure between service
25 providers of the sound source push service according to the second embodiment of the present invention is described. That is, if communication network service providers to which the calling party and the called party subscribe are different, the sound source push service of the present
30 invention is performed by interworking between the communication network service providers. FIG. 25 is a view showing a procedure of allowing a calling party to push the sound source of at least one supplementary service (first supplementary service), preset by the calling party, as the
35 sound source of at least one supplementary service (second supplementary service) of a called party having subscribed to

another communication network using a DTMF shortcut key during the placing of a call in the sound source push service according to a second embodiment of the present invention. In FIG. 25, numerals are expressed for ease of understanding of the present invention.

Referring to FIG. 25, if a calling party places a call to a called party having subscribed to a ringback tone replacement service, the called party receives a ringback tone replacing sound depending on a ringback tone replacement service scenario. At this time, the calling party presses a service sound source shortcut key (DTMF shortcut key) on a calling terminal so as to push his or her set title song, a specific supplementary service sound source, or a basic sound source provided from the present service provider, as the supplementary service sound source of the called party (1). A first service IP server in a first communication service provider network (B service provider network), to which the called party has subscribed, detects the service sound source shortcut key (DTMF detection) (2). Further, the first service IP server transmits information on a calling party phone number (calling party MIN), a called party phone number (called party MIN), a ringback tone replacing sound code, and a DTMF shortcut key, which the first service IP server collects for a current service, to a first service providing system in the first communication service provider network (3).

Next, the first service providing system transmits data received from the first service IP server to a second service providing system in a second communication service provider network (A service provider network) to which the calling party has subscribed (4). The second service providing system requests and receives the title song information of the calling party from the second CP server in the second communication service provider network (5). At the procedure (5), if the title song of the calling party is not registered, the second service providing system transmits

calling party information to the second MCP providing the second supplementary service, and receives the name of a singer and the title of a song corresponding to the sound source of the second supplementary service (6). Further, the
5 second service providing system requests and receives a sound source code corresponding to the singer name and song title from the second CP server. At this time, the second CP server interworks with the first CP server, and extracts the sound source code using a mapping table formed to allow sound
10 source codes, singer names and song titles for various supplementary services, provided from respective MCPs, to refer to each other.

Next, if the title song of the calling party is registered, the second service providing system transmits the
15 sound source information of the title song of the calling party to the first service providing system (7). The first service providing system requests the title song information of the calling party and the registration of the sound source push service from the first CP server in the first
20 communication service provider network, and receives the sound source code corresponding to the title song (8). The first service providing system notifies the called party of the details of the use of the sound source push service using SMS (9). Further, the first service providing system
25 transmits a completion message, indicating that the sound source push service has been completed, to the second service providing system (10).

Thereafter, the called party accesses the ARS connected to the first CP server using the callback number or URL
30 included in the SMS message, and then subscribes to the service and listen to and change the sound source (11). At this time, the subscription of the called party to the service and sound source setting request information thereof is transmitted from the ARS to the MCP, or transmitted to the
35 SCP if necessary (12 and 13).

The present invention is not limited to the above embodiments, but various modifications are possible by those skilled in the art, without departing from the scope and spirit of the invention.

CLAIMS

1. A method of providing a sound source change service, which changes a sound source of at least one supplementary
5 service of a calling party using a sound source of a ringback tone replacing sound of a called party during placing of a call, in a service providing system connected to a Mobile Switching Center (MSC) managing at least one calling terminal and at least one called terminal through a mobile
10 communication network, a service IP server and a Contents Provider (CP) server, comprising:
detecting a DTMF shortcut key signal received from the calling terminal through the service IP server during the placing of a call using the calling terminal;
15 receiving collected information from the service IP server in response to the DTMF shortcut key signal;
processing the collected information in a predetermined form;
transmitting a ringback tone replacing sound code
20 included in the collected information to the CP server on the basis of the processed information, the CP server extracting a sound source code of the supplementary service corresponding to the ringback tone replacing sound code using a mapping table formed to allow a plurality of sound source
25 codes, provided from at least a first Master Contents Provider (MCP) and a second MCP that provides the supplementary service to the calling party, and names of singers and titles of songs corresponding to the plurality of sound source codes to refer to each other;
30 receiving the sound source code from the CP server; and
transmitting a sound source change request signal including calling party information, included in the collected information, and the sound source code to the
second MCP.

35

2. A method of providing a sound source change service, which changes a sound source of at least one supplementary service of a calling party using a sound source of a ringback tone replacing sound of a called party during placing of a call, in a service providing system connected to a Mobile Switching Center (MSC) managing at least one calling terminal and at least one called terminal through a mobile communication network, a service IP server and a Contents Provider (CP) server, comprising:

detecting a DTMF shortcut key signal received from the calling terminal through the service IP server during the placing of a call using the calling terminal;

receiving collected information from the service IP server in response to the DTMF shortcut key signal;

processing DTMF shortcut key information, included in the collected information;

transmitting a ringback tone replacing sound code included in the collected information to a first Master Contents Provider (MCP) that provides the ringback tone replacing sound of the called party on the basis of the processed information;

receiving sound source information corresponding to the ringback tone replacing sound code from the first MCP;

transmitting the sound source information to the CP server, the CP server extracting a sound source code of the supplementary service corresponding to the sound source information using a mapping table;

receiving the sound source code from the CP server; and

transmitting a sound source change request signal including calling party information, included in the collected information, and the sound source code, to a second MCP that provides the supplementary service.

3. The sound source change service providing method according to claim 1 or 2, wherein the service IP server is placed in the MSC.

4. The sound source change service providing method according to claim 1 or 2, wherein the service IP server is placed in the service providing system.

5

5. The sound source change service providing method according to claim 1 or 2, wherein the collected information includes subscriber information, including a calling terminal identifier and a called terminal identifier corresponding to the called terminal, a sound source code including MCP identification (ID) and serial number corresponding to the first MCP, and the DTMF shortcut key information.

6. The sound source change service providing method according to claim 1 or 2, wherein the collected information is stored in a database of the service providing system, read in a First-In First-Out (FIFO) manner, and then sequentially transmitted to the CP server or the first MCP.

7. The sound source change service providing method according to claim 1 or 2, wherein the CP server is a service providing Master Contents Provider (MCP) system including at least one CP and an Automatic Response System (ARS).

8. The sound source change service providing method according to claim 1 or 2, further comprising the second MCP transmitting a sound source change request signal to a Service Control Point (SCP) when the supplementary service sound source is a ringback tone replacing sound source or a ringback tone sound source.

9. The sound source change service providing method according to claim 1 or 2, further comprising notifying the calling terminal of change results for the supplementary service sound source using a short message through a Short Message Service Center (SMSC).

10. The sound source change service providing method according to claim 9, further comprising the calling terminal accessing an ARS server or a Web/Wireless Application Protocol (WAP)/Mobile Explorer (ME) server using a callback number to the ARS server or a callback URL to the Web/WAP (ME) server, included in the short message.

11. A method of providing a sound source change service, which changes a sound source of at least one supplementary service of a calling party using a sound source of a ringback tone replacing sound of a called party during placing of a call, in a plurality of service providing systems each connected to at least one Mobile Switching Center (MSC) managing at least one calling terminal and at least one called terminal through a mobile communication network, at least one service IP server and at least one Contents Provider (CP) server, the service providing systems interworking with each other, comprising:

detecting a DTMF shortcut key signal received from the calling terminal through a first service IP server in a first communication service provider network to which a called terminal subscriber subscribes during the placing of a call using the calling terminal;

a first service providing system in the first communication service provider network receiving collected information from the first service IP server in response to the DTMF shortcut key signal;

processing the collected information in a predetermined form;

transmitting a ringback tone replacing sound code, included in the collected information, to a first MCP that provides the ringback tone replacing sound to the called party, on the basis of the processed information;

receiving first sound source information corresponding to the ringback tone replacing sound code from the first MCP;

the first service providing system transmitting the first sound source information to a second service providing system in a second communication service provider network to which a calling terminal subscriber subscribes;

5 transmitting the first sound source information to a CP server in the second communication service provider network, the CP server extracting a sound source code of the supplementary service, corresponding to the first sound source information, using a mapping table formed to allow a
10 plurality of pieces of sound source code information for the supplementary service of the calling party, and name information of a plurality of singers and title information of a plurality of songs corresponding to the sound source code information to refer to each other;
15 receiving the sound source code from the CP server; and
 transmitting a sound source change request signal including calling party information, included in the collected information, and the sound source code to a second MCP that provides the supplementary service in the second
20 communication service provider network.

12. The sound source change service providing method according to claim 11, further comprising:

 the second service providing system transmitting the
25 calling party information and the first sound source information to a third MCP in the second communication service provider network interworking with the first MCP;

 receiving second sound source information, which corresponds to the first sound source information and is
30 usable in the second communication service provider network, from the third MCP; and

 transmitting the second sound source information to the CP server so as to obtain the sound source code corresponding to the second sound source information.

35

13. A method of providing a sound source change service, which changes a sound source of at least one supplementary service of a called party using a sound source of a ringback tone replacing sound of a calling party during placing of a call, in a service providing system connected to a Mobile Switching Center (MSC) managing at least one calling terminal and at least one called terminal through a mobile communication network, a service IP server, a Contents Provider (CP) server, and an Automatic Response System (ARS) server, comprising:

5 detecting a DTMF shortcut key signal received from the calling terminal through the service IP server during the placing of a call using the calling terminal;

10 receiving collected information from the service IP server in response to the DTMF shortcut key signal;

15 processing the collected information in a predetermined form;

20 transmitting calling party information included in the collected information to a first MCP that provides the ringback tone replacing sound to the calling party on the basis of the processed information;

25 receiving sound source information of the ringback tone replacing sound corresponding to the calling party information from the first MCP;

30 transmitting the sound source information to the CP server, the CP server extracting a sound source code of the supplementary service corresponding to the sound source information using a mapping table formed to allow a plurality of sound source codes, provided from at least the first MCP and a second MCP that provides supplementary services to the called party, and names of a plurality of singers and titles of a plurality of songs corresponding to the sound source codes to refer to each other;

 receiving the sound source code from the CP server;

transmitting called party information, included in the collected information, and the sound source code to the second MCP; and

5 transmitting a short message to the called terminal through a Short Message Service Center (SMSC), the short message including information used to request setting of the sound source of the supplementary service, and a callback number to the ARS server or a callback URL to a Web/WAP (ME) server,

10 wherein the second MCP sets a sound source of the supplementary service to the sound source code in response to a sound source change request signal from the called terminal, while interworking with the ARS server or the Web/WAP (ME) server.

15

14. A method of providing a sound source change service, which changes a sound source of at least one supplementary service of a called party using a sound source of a title song of a calling party during placing of a call, in a service providing system connected to a Mobile Switching Center (MSC) managing at least one calling terminal and at least one called terminal through a mobile communication network, a service IP server and a Contents Provider (CP) server, and an Automatic Response System (ARS) server, comprising:

25

detecting a DTMF shortcut key signal received from the calling terminal through the service IP server during the placing of a call using the calling terminal;

30 receiving collected information from the service IP server in response to the DTMF shortcut key signal;

processing the collected information in a predetermined form;

35 transmitting a sound source request signal for the title song to the CP server on the basis of the processed information;

receiving the sound source code from the CP server;

transmitting called party information, included in the collected information, and the sound source code to a MCP that provides the supplementary service to the called party; and

5 transmitting a short message to the called terminal through a Short Message Service Center (SMSC), the short message including information used to request setting of the sound source of the supplementary service, and a callback number to the ARS server or a callback URL to a Web/WAP (ME) server,

10 wherein the MCP sets a sound source of the supplementary service to the sound source code in response to a sound source change request signal from the called terminal, while interworking with the ARS server or the Web/WAP (ME) server.

15 15. The sound source change service providing method according to claim 13 or 14, further comprising transmitting a service subscription request signal for the called party to a subscriber management server.

20 16. The sound source change service providing method according to claim 13 or 14, further comprising the ARS server transmitting a sound source change request signal to a Service Control Point (SCP) through the CP server or the first MCP when the supplementary service sound source is a ringback tone replacing sound source or a ringback tone sound source.

25 17. The sound source change service providing method according to claim 14, wherein the supplementary service includes at least one of a ringback tone replacement service, a ringer service, a background music service, a Karaoke service, a music mail service, a morning call service, a Music-On-Demand (MOD) service and a Video-On-Demand (VOD) service.

18. A method of providing a sound source change service, which changes a sound source of at least one supplementary service of a called party using a specific sound source of a calling party during placing of a call, in a plurality of service providing systems each connected to a Mobile Switching Center (MSC) managing at least one calling terminal and at least one called terminal through a mobile communication network, a service IP server, a Contents Provider (CP) server, and an Automatic Response System (ARS) server, comprising:

- detecting a DTMF shortcut key signal received from the calling terminal through a first service IP server in a first communication service provider network to which a calling terminal subscriber subscribes during the placing of a call using the calling terminal;
- a first service providing system in the first communication service provider network receiving collected information from the first service IP server in response to the DTMF shortcut key signal;
- processing the collected information in a predetermined form;
- transmitting calling party information to a first CP server in the first communication service provider network that provides the specific sound source on the basis of the processed information;
- receiving sound source information of the specific sound source corresponding to the calling party information from the first CP server;
- the first service providing system transmitting the sound source information to a second service providing system in a second communication service provider network to which a called terminal subscriber subscribes;
- transmitting the sound source information to a second CP server in the second communication service provider network, the second CP server extracting a sound source code of the supplementary service, corresponding to the sound source

information, using a mapping table formed to allow a plurality of pieces of sound source code information for the supplementary service, and name information of a plurality of singers and title information of a plurality of songs corresponding to the sound source code information to refer to each other;

receiving the sound source code from the second CP server;

transmitting a sound source change request signal including the called party information, included in the collected information, and the sound source code to a second MCP that provides the supplementary service in the second communication service provider network; and

transmitting a short message to the called terminal through a Short Message Service Center (SMSC), the short message including information used to request setting of the sound source of the supplementary service, and a callback number to the ARS server or a callback URL to a Web/WAP (ME) server,

wherein the second MCP sets a sound source of the supplementary service to the sound source code in response to a sound source change request signal from the called terminal, while interworking with the ARS server or the Web/WAP (ME) server.

19. The sound source change service providing method according to claim 18, wherein the second CP server includes the second MCP.

20. A service providing apparatus for providing a sound source change service, which is coupled to a Mobile Switching Center (MSC) managing at least one calling terminal and at least one called terminal through a mobile communication network, a service IP server and a contents provider (CP) server and adapted to provide a service of changing a sound source of at least one supplementary service of a calling

party using a sound source of a ringback tone replacing sound of a called party during placing of a call, comprising:

an IP interface coupled to at least one service IP server;

5 a CP server interface coupled to the CP server;

a Short Message Service Center (SMSC) interface coupled to a SMSC;

an Internet Detail Record (IDR) interface coupled to an IDR;

10 a WAP/ME push server interface coupled to a WAP/ME push server;

a Web interface coupled to a WAP/ME gateway;

a Simple Network Management Protocol (SNMP) agent coupled to a Network Management System (NMS);

15 a task manager adapted to manage tasks in the service providing apparatus;

a database coupled to the task manager;

a Common Gateway Interface (CGI) coupled to the database; and

20 a high availability module adapted to increase availability of the service providing apparatus.

21. The sound source change service providing apparatus according to claim 20, further comprising a Master Contents Provider (MCP) server interface coupled to at least one MCP that provides at least one supplementary service.

22. A service providing apparatus for providing a sound source change service, which is coupled to a Mobile Switching Center (MSC) managing at least one calling terminal and at least one called terminal through a mobile communication network, a service IP server and a contents provider (CP) server and adapted to provide the sound source change service, which comprises a first service of changing a sound source of at least one supplementary service of a calling party using a sound source of a ringback tone replacing sound

30

35

of a called party during placing of a call and a second service of changing a sound source of at least one supplementary service of the called party using a specific sound source of the calling party during the placing of a call, comprising:

a DTMF signal detecting unit detecting a DTMF shortcut key signal received from the calling terminal through the service IP server during the placing of a call using the calling terminal;

a collected information processing unit processing collected information, received from the service IP server, in a predetermined form;

a data transmitting/receiving unit receiving the collected information from the service IP server in response to the DTMF shortcut key signal, transmitting a sound source information request signal adapted to request sound source information for the first supplementary service to a first MCP that provides the first supplementary service, receiving the sound source information from the first MCP, transmitting the sound source information to the CP server, receiving a sound source code from the CP server, and transmitting a sound source change request signal to a second MCP that provides the second supplementary service; and

a control unit storing the processed information in a database, reading the processed information in a First-In First-Out (FIFO) manner, sequentially transmitting the read information to the first MCP, and controlling the DTMF signal detecting unit, the collected information processing unit and the data transmitting/receiving unit.

23. A service providing system, which is connected to a Mobile Switching Center (MSC) managing at least one calling terminal and at least one called terminal through a mobile communication network, a service IP server and a contents provider (CP) server and adapted to provide a sound source change service of changing a sound source of at least one

supplementary service of a calling party using a sound source of a ringback tone replacing sound of a called party during placing of a call, comprising:

a memory; and

5 a processor coupled to the memory,

the memory storing a program for controlling the processor; and

the processor operative with the program to detect a DTMF shortcut key signal received from the calling terminal
10 through the service IP server during the placing of a call using the calling terminal, receive collected information from the service IP server in response to the DTMF shortcut key signal, process the collected information in a predetermined form, transmit, on the basis of the processed
15 information, a ringback tone replacing sound code included in the collected information to the CP server, which extracts a sound source code of the supplementary service corresponding to the ringback tone replacing sound code using a mapping table formed to allow a plurality of sound source codes,
20 provided from at least a first MCP providing the ringback tone replacing sound to the called party and a second MCP providing the supplementary service to the calling party, and names of a plurality of singers and titles of a plurality of songs corresponding to the sound source codes to refer to
25 each other, receive the sound source code from the CP server and transmit a sound source change request signal including calling party information, included in the collected information, and the sound source code to the second MCP.

30 24. A service providing system, which is connected to a Mobile Switching Center (MSC) managing at least one calling terminal and at least one called terminal through a mobile communication network, a service IP server and a contents provider (CP) server and adapted to provide a sound source
35 change service of changing a sound source of at least one supplementary service of a calling party using a sound source

of a ringback tone replacing sound of a called party during placing of a call, comprising:

a memory; and

a processor coupled to the memory,

5 the memory storing a program for controlling the processor; and

the processor operative with the program to detect a DTMF shortcut key signal received from the calling terminal through the service IP server during the placing of a call
10 using the calling terminal, receive collected information from the service IP server in response to the DTMF shortcut key signal, process DTMF shortcut key information included in the collected information, transmit a ringback tone replacing sound code included in the collected information to a first
15 MCP that provides the ringback tone replacing sound to the called party on the basis of the processed information, receive sound source information corresponding to the ringback tone replacing sound code from the first MCP, transmit the sound source information to the CP server, which
20 extracts a sound source code of the supplementary service corresponding to the sound source information using a mapping table formed to allow sound source code information of at least one supplementary service and a name of a singer and a title of a song corresponding to the sound source code
25 information to refer to each other, receive the sound source code from the CP server, and transmit a sound source change request signal including calling party information, included in the collected information, and the sound source code to the second MCP.

30

25. A service providing system, which is connected to at least one Mobile Switching Center (MSC) managing at least one calling terminal and at least one called terminal through a mobile communication network, a service IP server and a
35 contents provider (CP) server and adapted to provide a sound source change service of changing a sound source of at least

one supplementary service of a calling party using a sound source of a ringback tone replacing sound of a called party during placing of a call, comprising:

a memory; and

5 a processor coupled to the memory,
the memory storing a program for controlling the processor; and

the processor operative with the program to detect a DTMF shortcut key signal received from the calling terminal
10 through a first service IP server in a first communication service provider network to which a called terminal subscriber subscribes during the placing of a call using the calling terminal, allow a first service providing system in the first communication service provider network to receive
15 collected information from the first service IP server in response to the DTMF shortcut key signal, process the collected information in a predetermined form, transmit a ringback tone replacing sound code included in the collected information to a first MCP that provides the ringback tone
20 replacing sound to the called party on the basis of the processed information, receive sound source information corresponding to the ringback tone replacing sound code from the first MCP, allow the first service providing system to transmit the sound source information to a second service
25 providing system in a second communication service provider network to which the calling terminal subscriber subscribes, allow the second service providing system to transmit the sound source information to a CP server, which extracts a sound source code of the supplementary service corresponding
30 to the sound source information using a mapping table formed to allow a plurality of pieces of sound source code information for the supplementary service of the calling party, and name information of a plurality of singers and title information of a plurality of songs corresponding to
35 the sound source code information to refer to each other, in the second communication service provider network, receive

the sound source code from the CP server, and transmit a sound source change request signal including calling party information, included in the collected information, and the sound source code to a second MCP that provides the supplementary service in the second communication service provider network.

26. A service providing system, which is connected to at least one Mobile Switching Center (MSC) managing at least one calling terminal and at least one called terminal through a mobile communication network, a service IP server, a contents provider (CP) server and an Automatic Response System (ARS) server, and adapted to provide a sound source change service of changing a sound source of at least one supplementary service of a called party using a specific sound source of a calling party during placing of a call, comprising:

- a memory; and
- a processor coupled to the memory,
- the memory storing a program for controlling the processor; and

- the processor operative with the program to detect a DTMF shortcut key signal received from the calling terminal through the service IP server during the placing of a call using the calling terminal, receive collected information from the service IP server in response to the DTMF shortcut key signal, process the collected information in a predetermined form, transmit a sound source code request signal for the specific sound source to the CP server on the basis of the processed information, receive a sound source code from the CP server, transmit called party information, included in the collected information, and the sound source code to a MCP that provides the supplementary service to the called party, transmit a short message, including information used to request setting of the sound source of the supplementary service and a callback number to the ARS server or a callback URL to a Web/WAP (ME) server, to the called

terminal through a Short Message Service Center (SMSC), and
allow the MCP to set the sound source of the supplementary
service to the sound source code in response to a sound
source change request signal from the called terminal while
5 interworking with the ARS server or the Web/WAP (ME) server.

27. A service providing system, which is connected to a
Mobile Switching Center (MSC) managing at least one calling
terminal and at least one called terminal through a mobile
10 communication network, a service IP server, a contents
provider (CP) server and an Automatic Response System (ARS)
server, and adapted to provide a sound source change service
of changing a sound source of at least one supplementary
service of a called party using a specific sound source of a
15 calling party during placing of a call, comprising:

- a memory; and
- a processor coupled to the memory,
 - the memory storing a program for controlling the
processor; and
 - 20 the processor operative with the program to detect a
DTMF shortcut key signal received from the calling terminal
through the service IP server during the placing of a call
using the calling terminal, receive collected information from
the service IP server in response to the DTMF shortcut key
25 signal, process the collected information in a predetermined
form, transmit calling party information included in the
collected information to a first MCP that provides the
specific sound source on the basis of the processed
information, receive sound source information of the ringback
30 tone replacing sound corresponding to the calling party
information from the first MCP, transmit the sound source
information to the CP server, which extracts a sound source
code of the supplementary service corresponding to the sound
source information using a mapping table formed to allow a
35 plurality of sound source codes, provided from at least the
first MCP and a second MCP that provides the supplementary

service to the called party, and names of a plurality of singers and titles of a plurality of songs corresponding to the sound source codes to refer to each other, receive the sound source code from the CP server, transmitting called party information, included in the collected information, and the sound source code to the second MCP, transmitting a short message, including information used to request setting of the sound source of the supplementary service and a callback number to the ARS server or a callback URL to a Web/WAP (ME) server, to the called terminal through a Short Message Service Center (SMSC), and allow the second MCP to set the sound source of the supplementary service to the sound source code in response to a sound source change request signal from the called terminal while interworking with the ARS server or the Web/WAP (ME) server.

28. A service providing system, which is connected to at least one Mobile Switching Center (MSC) managing at least one calling terminal and at least one called terminal through a mobile communication network, a service IP server, a contents provider (CP) server and an Automatic Response System (ARS) server, and adapted to provide a sound source change service of changing a sound source of at least one supplementary service of a called party using a specific sound source of a calling party during placing of a call, comprising:

- a memory; and
- a processor coupled to the memory,
- the memory storing a program for controlling the processor; and
- the processor operative with the program to detect a DTMF shortcut key signal received from the calling terminal through a first service IP server in a first communication service provider network to which a called terminal subscriber subscribes during the placing of a call using the calling terminal, allow a first service providing system in the first communication service provider network to receive

collected information from the first service IP server in response to the DTMF shortcut key signal, process the collected information in a predetermined form, transmit calling party information to a first CP server in the first communication service provider network that provides the specific sound source on the basis of the processed information, receive sound source information of the specific sound source corresponding to the calling party information from the first CP server, allow the first service providing system to transmit the sound source information to a second service providing system in a second communication service provider network to which the called terminal subscriber subscribes, allow the second service providing system to transmit the sound source information to a second CP server, which extracts a sound source code of the supplementary service corresponding to the sound source information using a mapping table formed to allow a plurality of pieces of sound source code information for the supplementary service, and name information of a plurality of singers and title information of a plurality of songs corresponding to the sound source code information to refer to each other, in the second communication service provider network, receive the sound source code from the second CP server, transmit a sound source change request signal including called party information, included in the collected information, and the sound source code to a second MCP that provides the supplementary service in the second communication service provider network, transmit a short message, including information used to request setting of the sound source of the supplementary service and a callback number to the ARS server or a callback URL to a Web/WAP (ME) server, to the called terminal through a Short Message Service Center (SMSC), and allow the second MCP to set the sound source of the supplementary service to the sound source code in response to a sound source change request signal from the

called terminal while interworking with the ARS server or the Web/WAP (ME) server.

29. A method of providing a sound source push service,
5 which pushes a sound source of at least one first
supplementary service, set to correspond to at least one
calling terminal, as a sound source of at least one second
supplementary service, set to correspond to at least one
called terminal, during placing of a call, in a service
10 providing system coupled to a Mobile Switching Center (MSC)
managing the calling terminal and the called terminal through
a mobile communication network, a service IP server and a
contents provider (CP) server, comprising:

detecting a DTMF shortcut key signal received from the
15 calling terminal through the service IP server during the
placing of a call by the calling terminal;

receiving collected information from the service IP
server in response to the DTMF shortcut key signal;

processing the collected information in a predetermined
20 form;

transmitting a sound source information request signal,
adapted to request sound source information for the first
supplementary service, to a first MCP that provides the first
supplementary service on the basis of the processed
25 information, the sound source information request signal
including a calling terminal identifier corresponding to the
calling terminal;

receiving the sound source information from the first
MCP;

30 transmitting the sound source information to the CP
server, the CP server extracting a sound source code
corresponding to the sound source information using a mapping
table;

receiving the sound source code from the CP server;

35 transmitting a sound source change request signal
including called party information, included in the collected

information, and the sound source code to a second MCP that provides the second supplementary service.

5 30. The sound source push service providing method according to claim 29, wherein the service IP server is placed in the MSC.

10 31. The sound source push service providing method according to claim 29, wherein the service IP server is placed in the service providing system.

15 32. The sound source push service providing method according to claim 29, wherein the CP server, the first MCP and the second MCP are included in a single contents provider.

20 33. The sound source push service providing method according to claim 29, wherein the first and second MCPs are integrated into a single MCP.

25 34. The sound source push service providing method according to claim 29, wherein the collected information includes subscriber information, including calling party information corresponding to the calling terminal and called party information corresponding to the called terminal, the sound source code including identifiers and serial numbers of contents providers (CP/MCP) that provide the supplementary service, and the DTMF shortcut key information.

30 35. The sound source push service providing method according to claim 29, wherein the processed information is stored in a database of the service providing system, read in a First-In First-Out (FIFO) manner, and then sequentially transmitted to the first MCP.

35

36. The sound source push service providing method according to claim 29, wherein the sound source information includes names of singers and titles of songs.

5 37. The sound source push service providing method according to claim 29, wherein the mapping table includes a database formed to allow a plurality of sound source codes for supplementary services, provided from the first and second MCPs, and names of singers and titles of songs
10 corresponding to the plurality of sound source codes to refer to each other.

 38. The sound source push service providing method according to claim 29, further comprising the second MCP
15 transmitting a sound source change request signal to a Service Control Point (SCP) when the second supplementary service is a ringback tone replacement service or a ringback tone service.

20 39. The sound source push service providing method according to claim 29, further comprising notifying the called terminal of sound source change results for the second supplementary service.

25 40. The sound source push service providing method according to claim 39, wherein the notification of the sound source change results for the second supplementary service is performed using a Short Message Service (SMS) through a Short Message Service Center (SMSC).

30 41. The sound source push service providing method according to claim 40, wherein the short message transmitted to the called terminal includes a callback number to an ARS server or a callback URL to a Web/WAP (ME) server.

35

42. A method of providing a sound source push service, which pushes a sound source of at least one first supplementary service, set to correspond to at least one calling terminal, as a sound source of at least one second supplementary service, set to correspond to at least one called terminal, during placing of a call, in a plurality of service providing systems each connected to a Mobile Switching Center (MSC) managing the calling terminal and the called terminal through a mobile communication network, a service IP server and a contents provider (CP) server, comprising:

detecting a DTMF shortcut key signal received from the calling terminal through a first service IP server in a first communication service provider network to which a calling terminal subscribes during the placing of a call using the calling terminal;

a first service providing system in the first communication service provider network receiving collected information from the first service IP server in response to the DTMF shortcut key signal;

processing the collected information in a predetermined form;

transmitting a first sound source information request signal, adapted to request first sound source information for the first supplementary service, to a first MCP that provides the first supplementary service, on the basis of the processed information, the first sound source information request signal including a calling terminal identifier corresponding to the calling terminal;

receiving the first sound source information from the first MCP;

the first service providing system transmitting the first sound source information to a second service providing system in a second communication service provider network to which the called terminal subscribes;

the second service providing system transmitting the first sound source information to a CP server in the second communication service provider network, the CP server extracting a sound source code corresponding to the first sound source information using a mapping table;
5 receiving the sound source code from the CP server; and transmitting a sound source change request signal including called party information, included in the collected information, and the sound source code to a second MCP that provides the second supplementary service in the second communication service provider network.
10

43. A service providing apparatus, which is connected to a Mobile Switching Center (MSC) managing at least one calling terminal and at least one called terminal through a mobile communication network, a service IP server and a contents provider (CP) server, and adapted to provide a sound source push service of pushing a sound source of at least one first supplementary service, set to correspond to the calling terminal, as a sound source of at least one second supplementary service, set to correspond to the called terminal, during placing of a call, comprising:
15
20

a data transmitting/receiving unit including an IP interface connected to at least one service IP server, a CP server interface connected to the CP server, a Short Message Service Center (SMSC) interface connected to a SMSC, an Internet Detail Record (IDR) interface connected to an IDR, a WAP/ME push server interface connected to a WAP/ME push server, and a Web interface connected to a WAP/ME gateway, the data transmitting/receiving unit receiving and transmitting data through at least one of the interfaces;
25
30

a control unit including a task manager that processes data received through the data transmitting/receiving unit;

a database processing unit including a database connected to the task manager and a Common Gateway Interface (CGI) connected to the database; and
35

a network interworking unit including a SMSC interworking unit, an IDR interworking unit, a Network Management System (NMS) interworking unit, a CP server interworking unit, a MCP interworking unit, and a Simple
5 Network Management Protocol (SNMP) agent connected to the NMS.

44. The sound source push service providing apparatus according to claim 43, further comprising a MCP server
10 interface connected to at least one MCP including the first and second MCPs.

45. A service providing apparatus, which is connected to a Mobile Switching Center (MSC) managing at least one calling
15 terminal and at least one called terminal through a mobile communication network, a service IP server and a contents provider (CP) server, and adapted to provide a sound source push service of pushing a sound source of at least one first supplementary service, set to correspond to the calling
20 terminal, as a sound source of at least one second supplementary service, set to correspond to the called terminal, during placing of a call, comprising:

a DTMF signal detecting unit detecting a DTMF shortcut key signal received from the calling terminal through the
25 service IP server during the placing of a call using the calling terminal;

a collected information processing unit processing collected information received from the service IP server in a predetermined form;

30 a data transmitting/receiving unit receiving the collected information from the service IP server in response to the DTMF shortcut key signal, transmitting a sound source information request signal adapted to request sound source information for the first supplementary service to a first
35 MCP that provides the first supplementary service on the basis of information processed by the collected information

processing unit, receiving the sound source information from the first MCP, transmitting the sound source information to the CP server, receiving a sound source code from the CP server, and transmitting a sound source change request signal
5 to a second MCP that provides the second supplementary service; and

a control unit storing the processed information in a database, reading the processed information in a First-In First-Out (FIFO) manner, sequentially transmitting the read
10 information to the first MCP, and controlling the DTMF signal detecting unit, the collected information processing unit and the data transmitting/receiving unit.

46. A service providing system, which is connected to a
15 Mobile Switching Center (MSC) managing at least one calling terminal and at least one called terminal through a mobile communication network, a service IP server and a contents provider (CP) server, and adapted to provide a sound source push service of pushing a sound source of at least one first
20 supplementary service, set to correspond to the calling terminal, as a sound source of at least one second supplementary service, set to correspond to the called terminal, during placing of a call, comprising:

a memory; and
25 a processor coupled to the memory,
the memory storing a program for controlling the processor; and

the processor operative with the program to detect a DTMF shortcut key signal received from the calling terminal
30 through the service IP server during the placing of a call using the calling terminal, receive collected information from the service IP server in response to the DTMF shortcut key signal, process the collected information in a predetermined form, transmit a sound source information
35 request signal, adapted to request sound source information for the first supplementary service and provided with a

calling terminal identifier corresponding to the calling terminal, to a first MCP that provides the first supplementary service, on the basis of the processed information, receive the sound source information from the first MCP, transmit the sound source information to the CP server, which extracts a sound source code corresponding to the sound source information using a mapping table, receive the sound source code from the CP server, and transmit a sound source change request signal including called party information, included in the collected information, and the sound source code to a second MCP that provides the second supplementary service.

47. A service providing system, which is connected to a Mobile Switching Center (MSC) managing at least one calling terminal and at least one called terminal through a mobile communication network, a service IP server and a contents provider (CP) server, and adapted to provide a sound source push service of pushing a sound source of at least one first supplementary service, set to correspond to the calling terminal, as a sound source of at least one second supplementary service, set to correspond to the called terminal, during placing of a call, performing the steps of:
a memory; and
a processor coupled to the memory,
the memory storing a program for controlling the processor; and

the processor operative with the program to detect a DTMF shortcut key signal received from the calling terminal through a first service IP server in a first communication service provider network to which a calling terminal subscribes during the placing of a call using the calling terminal, allow a first service providing system in the first communication service provider network to receive collected information from the first service IP server in response to the DTMF shortcut key signal, process the collected

information in a predetermined form, transmit a first sound
source information request signal, adapted to request first
sound source information for the first supplementary service,
to a first MCP that provides the first supplementary service,
5 on the basis of the processed information, the first sound
source information request signal including a calling
terminal identifier corresponding to the calling terminal,
receive the first sound source information from the first
MCP, the first service providing system transmitting the
10 first sound source information to a second service providing
system in a second communication service provider network to
which the called terminal subscribes, allow the second
service providing system to transmit the first sound source
information to a CP server in the second communication
15 service provider network, allow the CP server to extract a
sound source code corresponding to the first sound source
information using a mapping table, receive the sound source
code from the CP server, and transmit a sound source change
request signal including called party information, included
20 in the collected information, and the sound source code to a
second MCP that provides the second supplementary service in
the second communication service provider network.