

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

200001075-1

1005
Reference
Copy



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04B 7/00		A2	(11) International Publication Number: WO 99/16183
			(43) International Publication Date: 1 April 1999 (01.04.99)
(21) International Application Number: PCT/US98/19467		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 18 September 1998 (18.09.98)			
(30) Priority Data: 08/933,888 19 September 1997 (19.09.97) US			
(71) Applicant: QUALCOMM INCORPORATED [US/US]; 6455 Lusk Boulevard, San Diego, CA 92121 (US).			
(72) Inventors: WHEATLEY, Charles, E., III; 2208 Caminito Del Barco, Del Mar, CA 92014 (US). TIEDEMANN, Edward, G., Jr.; 4350 Bromfield Avenue, San Diego, CA 92122 (US).			
(74) Agents: MILLER, Russell, B. et al.; Qualcomm Incorporated, 6455 Lusk Boulevard, San Diego, CA 92121 (US).			

Published

Without international search report and to be republished upon receipt of that report.

(54) Title: MOBILE STATION ASSISTED TIMING SYNCHRONIZATION IN A CDMA COMMUNICATION SYSTEM

(57) Abstract

In the present invention, the slave base station (64) attains synchronization with the reference base station (62) through messages transmitted from and received by a mobile station (60) in the soft handoff region between the reference base station (62) and the slave base station (64). First, the round trip delay between the mobile station (60) and the reference base station (62) is measured by the reference base station (62). Once the mobile station (60) acquires the signal from the slave base station (64), it measures and reports the difference between the amount of time it takes a signal to travel from the reference base station (62) to it and the amount of time it takes a signal to travel from the slave base station (64) to it. The last measurement necessary is a measurement by the slave base station (64) of the time difference between the time it received the reverse link signal from the mobile (60) and station the time it transmitted a signal to the mobile station. A series of computations described in detail herein are performed upon the measured time values to determine the time difference between the slave base station (64) and an adjustment of the slave base station (64) timing is performed in accordance therewith.

