CROSSOVER JOINT FOR CONNECTING ECCENTRIC FLOW PATHS TO CONCENTRIC FLOW PATHS

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the benefit of U.S. Provisional Application 61/424,427, filed December 17, 2010 and U.S. Provisional Application 61/499,865, filed June 22, 2011.

BACKGROUND OF THE INVENTION

[0002] This section is intended to introduce various aspects of the art, which may be associated with exemplary embodiments of the present disclosure. This discussion is believed to assist in providing a framework to facilitate a better understanding of particular aspects of the present disclosure. Accordingly, it should be understood that this section should be read in this light, and not necessarily as admissions of prior art.

Field of the Invention

[0003] The present disclosure relates to the field of well completions. More specifically, the present invention relates to the completion of wellbores using sand screens and gravel packs. The application also relates to a downhole tool that may be used to connect eccentric flow paths to concentric flow paths for the installation of a gravel pack.

Discussion of Technology

[0004] In the drilling of oil and gas wells, a wellbore is formed using a drill bit that is urged downwardly at a lower end of a drill string. After drilling to a predetermined depth, the drill string and bit are removed and the wellbore is lined with a string of casing. An annular area is thus formed between the string of casing and the formation. A cementing operation is typically conducted in order to fill or “squeeze” the annular area with cement. The combination of cement and casing strengthens the wellbore and facilitates the isolation of the formation behind the casing.

[0005] It is common to place several strings of casing having progressively smaller outer diameters into the wellbore. The process of drilling and then cementing progressively smaller strings of casing is repeated several times until the well has reached total depth. The final string of casing, referred to as a production casing, is cemented in place and perforated. In some instances, the final string of casing is a liner, that is, a string of casing that is not tied back to the surface.

[0006] As part of the completion process, a wellhead is installed at the surface. The wellhead controls the flow of production fluids to the surface, or the injection of fluids into the

wellbore. Fluid gathering and processing equipment such as pipes, valves and separators are also provided. Production operations may then commence.

[0007] In some instances, a wellbore is completed in a formation that is loose or "unconsolidated." This means that as production fluids are produced into the wellbore, formation particles, e.g., sand and fines, may also invade the wellbore. Such particles are detrimental to production equipment. More specifically, formation particles can be erosive to downhole pumps as well as to pipes, valves, and fluid separation equipment at the surface.

[0008] The problem of unconsolidated formations can occur in connection with the completion of a cased wellbore. In that instance, formation particles may invade the perforations created through production casing and a surrounding cement sheath. However, the problem of unconsolidated formations is much more pronounced when a wellbore is formed as an "open hole" completion.

[0009] In an open-hole completion, a production casing is not extended through the producing zones and perforated; rather, the producing zones are left uncased, or "open." A production string or "tubing" is then positioned inside the wellbore extending down below the last string of casing and across a subsurface formation.

[0010] There are certain advantages to open-hole completions versus cased-hole completions. First, because open-hole completions have no perforation tunnels, formation fluids can converge on the wellbore radially 360 degrees. This has the benefit of eliminating the additional pressure drop associated with converging radial flow and then linear flow through particle-filled perforation tunnels. The reduced pressure drop associated with an open-hole completion virtually guarantees that it will be more productive than an unstimulated, cased hole in the same formation. Second, open-hole techniques are oftentimes less expensive than cased hole completions.

[0011] A common problem in open-hole completions is the immediate exposure of the wellbore to the surrounding formation. If the formation is unconsolidated or heavily sandy, the flow of production fluids into the wellbore may carry with it formation particles, e.g., sand and fines. Such particles can be erosive to production equipment downhole and to pipes, valves and separation equipment at the surface.

[0012] To control the invasion of sand and other particles, sand control devices may be employed. Sand control devices are usually installed downhole across formations to retain solid materials larger than a certain diameter while allowing fluids to be produced. A sand control device typically includes an elongated tubular body, known as a base pipe, having

numerous slotted openings. The base pipe is then typically wrapped with a filtration medium such as a screen or wire mesh.

[0013] To augment sand control devices, particularly in open-hole completions, it is common to install a gravel pack. Gravel packing a well involves placing gravel or other particulate matter around the sand control device after the sand control device is hung or otherwise placed in the wellbore. To install a gravel pack, a particulate material is delivered downhole by means of a carrier fluid. The carrier fluid with the gravel together forms a gravel slurry. The slurry dries in place, leaving a circumferential packing of gravel. The gravel not only aids in particle filtration but also helps maintain wellbore integrity. The use of gravel packs also eliminates the need for cementing, perforating, and post-perforation clean-up operations.

[0014] In an open-hole gravel pack completion, the gravel is positioned between a sand screen that surrounds a perforated base pipe and a surrounding wall of the wellbore. During production, formation fluids flow from the subterranean formation, through the gravel, through the screen, and into the inner base pipe. The base pipe thus serves as a part of the production string.

[0015] A problem historically encountered with gravel-packing is that an inadvertent loss of carrier fluid from the slurry during the delivery process can result in premature sand or gravel bridges being formed at various locations along open-hole intervals. For example, in an inclined production interval or an interval having an enlarged or irregular borehole, a poor distribution of gravel may occur due to a premature loss of carrier fluid from the gravel slurry into the formation. Premature sand bridging can block the flow of gravel slurry, causing voids to form along the completion interval. Thus, a complete gravel-pack from bottom to top is not achieved, leaving the wellbore exposed to sand and fines infiltration.

[0016] The problem of sand bridging has been addressed through the use of Alternate Path® Technology, or "APT." The Alternate Path® fluid bypass technology employs shunt tubes (or shunts) that allow the gravel slurry to bypass selected areas along a wellbore. Such fluid bypass technology is described, for example, in U.S. Pat. No. 5,588,487 entitled "Tool for Blocking Axial Flow in Gravel-Packed Well Annulus," and PCT Publication No. WO 2008/060479 entitled "Wellbore Method and Apparatus for Completion, Production, and Injection," each of which is incorporated herein by reference in its entirety. Additional references which discuss fluid bypass technology include U.S. Pat. No. 4,945,991; U.S. Pat. No. 5,113,935; U.S. Pat. No. 7,661,476; and M.D. Barry, *et al.*, "Open-hole Gravel Packing with Zonal Isolation," SPE Paper No. 110,460 (November 2007).

[0017] It is known to use rectangular shunt tubes that are eccentrically attached to the outside of a sand screen. Schlumberger's OptiPac™ fluid bypass gravel pack system is an example of a sand screen having external shunt tubes and one or more external transport tubes. See also G. Hurst, *et al.*, S. Tocalino, "*Alternate Path Completions: A Critical Review and Lessons Learned From Case Histories With Recommended Practices for Deepwater Applications*," SPE Paper No. 86,532 (2004). The eccentric layout reduces the overall diametrical size of the tool compared to if the equivalent shunt tubes were attached concentrically.

[0018] Recent technological advances have led to the development of two new downhole tools useful for the installation of a gravel pack. The first is an Alternate Path® sand screen having concentric internal shunt tubes. Embodiments of such a sand screen are shown and described in M.T. Hecker, *et al.*, "*Extending Openhole Gravel-Packing Capability: Initial Field Installation of Internal Shunt Alternate Path Technology*," SPE Paper No. 135,102 (2010); and in U.S. Patent Publ. No. 2008/0142227 filed in 2008 and entitled "*Wellbore Method and Apparatus for Completion, Production and Injection*." The second is a concentric, internal-shunt open-hole packer. Embodiments of such a packer are shown and described in co-pending U. S. Provisional Patent Application No. 61/424,427 filed 17 December 2010. That application is entitled "*Packer for Alternate Path Gravel Packing, and Method for Completing a Wellbore*." The combination of these tools enables a true zonal isolation in gravel pack completions.

[0019] It is desirable to be able to connect a first wellbore tool (such as the OptiPac™ sand screen) that presents eccentric flow paths, with a second wellbore tool (such as an internal-shunt screen or internal shunt open-hole packer) that provides concentric flow paths. Alternatively, it is desirable to connect a first wellbore tool (such as an Alternate Path® sand screen having concentric internal shunt tubes) with a blank pipe or packer having eccentric flow paths and shunt tubes. Alternatively still, it desirable to connect to joints of sand screen, wherein one joint has a concentric primary flow path, and another has an eccentric primary flow path.

[0020] Various connectors have been disclosed either between concentric flow paths or between eccentric flow paths. Such connectors are at least mentioned in, for example, U.S. Pat. No. 7,497,267; US7,886,819; US5,390,966, US5,868,200, US6,409,219, US6,520,254, US6,752,207, US6,789,621, US6,789,624, US6,814,139, US6,923,262, US7,048,061, US2008/0142227, US7,661,476, US7,828,056). They provide fluid communication between eccentric primary flow paths, between concentric primary flow paths, between eccentric secondary flow paths, or between concentric secondary flow paths. However, a crossover

tool connecting concentric flow paths to eccentric flow paths (or vice versa) between two screen joints or between a screen joint and a packer has not yet been developed.

[0021] Therefore, a need exists for an improved sand control system utilizing a crossover joint for connecting an eccentric sand screen with a concentric packer, or vice versa. A need further exists for a crossover tool that fluidly connects a first wellbore tool having a primary flow path and at least one secondary flow path, with a second wellbore tool also having a primary flow path and at least one secondary flow path, wherein a radial center of the primary flow path in the first wellbore tool is offset from a radial center of the primary flow path in the second wellbore tool.

SUMMARY OF THE INVENTION

[0022] A sand control system is first provided herein. The sand control system includes a first wellbore tool having a primary flow path and at least one secondary flow path. The sand control system also includes a second wellbore tool, with the second wellbore tool also having a primary flow path and at least one secondary flow path. A radial center of the primary flow path in the first wellbore tool is offset from a radial center of the primary flow path in the second wellbore tool.

[0023] The sand control system also has a crossover joint. The crossover joint connects the first wellbore tool to the second wellbore tool. The crossover joint comprises a primary flow path fluidly connecting the primary flow path of the first wellbore tool to the primary flow path of the second wellbore tool. The crossover joint also has at least one secondary flow path fluidly connecting the at least one secondary flow path of the first wellbore tool to the at least one secondary flow path of the second wellbore tool.

[0024] In one preferred embodiment of the sand control system, the first wellbore tool is a sand screen. The sand screen comprises an elongated base pipe, a filtering medium circumferentially around the base pipe, and at least one shunt tube along the base pipe. The shunt tube serves as an alternate flow channel. In this respect, the shunt tube is configured to allow gravel slurry to at least partially bypass the first wellbore tool when any premature sand bridge occurs in the surrounding annular region between the sand screen and the wellbore during a gravel-packing operation in the wellbore. In this instance, the base pipe serves as the primary flow path of the sand screen, and the at least one shunt tube serves as the at least one secondary flow path of the sand screen.

[0025] In the sand screen, the elongated base pipe is preferably eccentric to the sand screen. Each of the at least one shunt tube then may have a round profile, a square profile, or a rectangular profile.

[0026] In another preferred embodiment of the sand control system, the second wellbore tool is a packer. The packer comprises an elongated inner mandrel, a sealing element external to the inner mandrel, and an annulus serving as an alternate flow channel. The annulus is configured to allow gravel slurry to at least partially bypass the second wellbore tool during a gravel-packing operation in a wellbore after the packer has been set in the wellbore. In this instance, the inner mandrel serves as the primary flow path of the packer, and the annulus serves as the at least one secondary flow path of the packer.

[0027] In the packer, the inner mandrel is preferably concentric to the packer. Further, the annulus resides between the inner mandrel and a surrounding piston housing. The packer further has one or more flow ports providing fluid communication between the annulus and a pressure-bearing surface of the piston housing.

[0028] A crossover joint for connecting a first wellbore tool to a second wellbore tool is also provided herein. The crossover joint is configured in accordance with the crossover joint described above. The crossover joint may be used as part of a sand control system. However, the crossover joint may be used to connect any two tubular tools having primary flow paths and secondary flow paths, wherein a radial center of the primary flow path in the first wellbore tool is offset from a radial center of the primary flow path in the second wellbore tool.

[0029] In one embodiment, the primary flow path of the first wellbore tool is eccentric to the first wellbore tool, while the primary flow path of the second wellbore tool is concentric to the second wellbore tool. The first wellbore tool is preferably a sand screen, while the second wellbore tool is preferably a mechanically-set packer.

[0030] A base pipe serves as the primary flow path of the sand screen, while an elongated inner mandrel serves as the primary flow path of the packer. The secondary flow path for the sand screen is made up of shunt tubes which serve as alternate flow channels. The secondary flow path for the packer may be shunt tubes or may be an annulus formed between the inner mandrel and a surrounding moveable piston housing. The alternate flow channels allow a gravel slurry to bypass the sand screen joint, the crossover joint, and the packer, even after the packer has been set in the wellbore.

[0031] The at least one secondary flow path of the crossover joint changes direction along a longitudinal axis of the crossover joint at least once. In one aspect, an inner diameter of the primary flow path of the crossover joint is greater than an inner diameter of (i) the primary flow path of the first wellbore tool, (ii) the primary flow path of the second wellbore tool, or (iii) both.

[0032] The crossover joint may optionally include an outer protective shroud.

[0033] A method for completing a wellbore in a subsurface formation is also provided herein. In one aspect, the method comprises providing a first wellbore tool. The first wellbore tool has a primary flow path and at least one secondary flow path. The method also includes providing a second wellbore tool. The second wellbore tool also has a primary flow path and at least one secondary flow path. A radial center of the primary flow path of the first wellbore tool is offset from a radial center of the primary flow path for the second wellbore tool.

[0034] The method also includes providing a crossover joint. The crossover joint also comprises a primary flow path and a secondary flow path. The method then includes fluidly connecting the crossover joint to the first wellbore tool at a first end, and fluidly connecting the crossover joint to the second wellbore tool at a second end. In this manner, the primary flow path of the first wellbore tool is in fluid communication with the primary flow path of the second wellbore tool. Further, the at least one secondary flow path of the first wellbore tool is in fluid communication with the at least one secondary flow path of the second wellbore tool.

[0035] The method further includes running the crossover joint and connected first and second wellbore tools into a wellbore to a selected subsurface location. Fluid is then injected into an annular region between the crossover joint and the surrounding wellbore. The method then includes further injecting the fluid from the annulus and through the secondary flow paths of the first wellbore tool, the crossover joint, and the secondary flow paths of the second wellbore tool.

[0036] The crossover joint may be used to connect any two tubular tools having primary flow paths and secondary flow paths, wherein a radial center of the primary flow path in the first wellbore tool is offset from a radial center of the primary flow path in the second wellbore tool. However, it is preferred that the crossover joint be used as part of a sand control system. In this instance, the first wellbore tool is preferably a sand screen, while the second wellbore tool is preferably a settable packer.

[0037] In one embodiment, the primary flow path of the first wellbore tool (such as a sand screen) is eccentric to the first wellbore tool, while the primary flow path of the second wellbore tool (such as a packer) is concentric to the second wellbore tool.

[0038] A base pipe serves as the primary flow path of the sand screen, while an elongated inner mandrel serves as the primary flow path of the packer. The secondary flow path for the sand screen is made up of shunt tubes which serve as alternate flow channels. The secondary flow path for the packer may be shunt tubes or may be an annular area formed between the inner mandrel and a surrounding moveable piston housing. In any instance, the alternate flow channels allow a gravel slurry to bypass the sand screen joint, the crossover joint, and the packer, even after the packer has been set in the wellbore.

[0039] In one aspect, the method further comprises setting the packer in the wellbore. In this instance, the step of further injecting the fluid through the secondary flow paths is done after the packer has been set.

[0040] In another aspect, the method further comprises running a setting tool into the inner mandrel of the packer, and then pulling the setting tool to mechanically shift a release sleeve from a retained position along the inner mandrel of the packer. This serves to release the piston housing for axial movement. The method then includes communicating hydrostatic pressure to the piston housing through one or more flow ports, thereby axially moving the released piston housing and actuating the sealing element against the surrounding wellbore.

BRIEF DESCRIPTION OF THE DRAWINGS

[0041] So that the manner in which the present inventions can be better understood, certain illustrations, charts and/or flow charts are appended hereto. It is to be noted, however, that the drawings illustrate only selected embodiments of the inventions and are therefore not to be considered limiting of scope, for the inventions may admit to other equally effective embodiments and applications.

[0042] Figure 1 is a cross-sectional view of an illustrative wellbore. The wellbore has been drilled through three different subsurface intervals, each interval being under formation pressure and containing fluids.

[0043] Figure 2 is an enlarged cross-sectional view of an open-hole completion of the wellbore of Figure 1. The open-hole completion at the depth of the three subsurface intervals is more clearly seen.

[0044] Figure 3A is a cross-sectional side view of a packer assembly, in one embodiment. Here, a base pipe is shown, with surrounding packer elements. Two mechanically set packers are shown schematically, along with an intermediate swellable packer element.

[0045] Figure 3B is a cross-sectional view of the packer assembly of Figure 3A, taken across lines 3B-3B of Figure 3A. Shunt tubes are seen within the swellable packer element.

[0046] Figure 3C is a cross-sectional view of the packer assembly of Figure 3A, in an alternate embodiment. In lieu of shunt tubes, transport tubes are seen manifolded around the base pipe.

[0047] Figure 4A is a cross-sectional side view of the packer assembly of Figure 3A. Here, sand control devices, or sand screens, have been placed at opposing ends of the packer assembly. The sand control devices utilize external shunt tubes.

[0048] Figure 4B provides a cross-sectional view of the packer assembly of Figure 4A, taken across line 4B-4B of Figure 4A. Shunt tubes are seen outside of the sand screen to provide an alternative flowpath for a particulate slurry.

[0049] Figure 5A is another cross-sectional side view of the packer assembly of Figure 3A. Here, sand control devices, or sand screens, have again been placed at opposing ends of the packer assembly. However, the sand control devices utilize internal shunt tubes.

[0050] Figure 5B provides a cross-sectional view of the packer assembly of Figure 5A, taken across line 5B-5B of Figure 5A. Shunt tubes are seen within the sand screen to provide an alternative flowpath for a particulate slurry.

[0051] Figure 6A is a cross-sectional side view of one of the mechanically-set packers of Figure 3A. The mechanically-set packer is in its run-in position.

[0052] Figure 6B is a cross-sectional side view of the mechanically-set packer of Figure 6A. Here, the mechanically-set packer element is in its set position.

[0053] Figure 6C is a cross-sectional view of the mechanically-set packer of Figure 6A. The view is taken across line 6C-6C of Figure 6A.

[0054] Figure 6D is a cross-sectional view of the packer of Figure 6A. The view is taken across line 6D-6D of Figure 6B.

[0055] Figure 6E is a cross-sectional view of the packer of Figure 6A. The view is taken across line 6E-6E of Figure 6A.

[0056] Figure 6F is a cross-sectional view of the mechanically-set packer of Figure 6A. The view is taken across line 6F-6F of Figure 6B.

[0057] Figure 7A is an enlarged view of the release key of Figure 6A. The release key is in its run-in position along the inner mandrel. The shear pin has not yet been sheared.

[0058] Figure 7B is an enlarged view of the release key of Figure 6B. The shear pin has been sheared, and the release key has dropped away from the inner mandrel.

[0059] Figure 7C is a perspective view of a setting tool as may be used to latch onto a release sleeve, and thereby shear a shear pin within the release key.

[0060] Figures 8A through 8C demonstrate various eccentric designs for a wellbore tool. Here, the wellbore tools are sand screens or blank pipes. Each of the illustrative sand screens or blank pipes comprises a base pipe, with one or more eccentric alternate flow channels there around providing secondary flow paths.

[0061] Figures 9A through 9C demonstrate various concentric designs for a wellbore tool. Here, the wellbore tools are packers. Each of the illustrative packers comprises a base pipe, with concentric alternate flow channels there around providing secondary flow paths.

[0062] Figure 10A provides a side, cross-sectional view of a crossover joint for connecting inner base pipes of two tubular bodies, and for providing fluid communication between eccentric and concentric secondary flow paths. The crossover joint operates to fluidly connect a first wellbore tool to a second wellbore tool.

[0063] Figure 10B is a first transverse cross-sectional view, taken across line B-B of Figure 10A. The cut is taken at a first end of the crossover joint.

[0064] Figure 10C is a second transverse cross-sectional view, taken across line C-C of Figure 10A. The cut is taken at a second opposite end of the crossover joint.

[0065] Figure 11A is a Cartesian graph charting axis offset (first *y*-axis) against symmetric length of a crossover joint (*x*-axis) for a 16-foot crossover joint. Figure 11A also charts curvature (second *y*-axis) against symmetric length of a crossover joint (*x*-axis) for the 16-foot crossover joint.

[0066] Figure 11B is a Cartesian graph charting axis offset (first *y*-axis) against symmetric length of a crossover joint (*x*-axis) for an 8-foot crossover joint. Figure 11B also charts curvature (second *y*-axis) against symmetric length of a crossover joint (*x*-axis) for the 8-foot crossover joint.

[0067] Figure 11C is a Cartesian graph charting axis offset (*y*-axis) against symmetric length of a crossover joint (*x*-axis) for an 8-foot crossover joint. Here, the graph compares a crossover joint having a curved profile with a crossover joint having straight segments.

[0068] Figure 12 is a flow chart showing steps for a method for completing a wellbore in a subsurface formation, in one embodiment.

[0069] Figure 13 is another flow chart. Figure 13 shows steps for a method of setting a packer in a wellbore, in one embodiment.

DETAILED DESCRIPTION OF CERTAIN EMBODIMENTS

Definitions

[0070] As used herein, the term “hydrocarbon” refers to an organic compound that includes primarily, if not exclusively, the elements hydrogen and carbon. Hydrocarbons generally fall into two classes: aliphatic, or straight chain hydrocarbons, and cyclic, or closed ring hydrocarbons, including cyclic terpenes. Examples of hydrocarbon-containing materials include any form of natural gas, oil, coal, and bitumen that can be used as a fuel or upgraded into a fuel.

[0071] As used herein, the term “hydrocarbon fluids” refers to a hydrocarbon or mixtures of hydrocarbons that are gases or liquids. For example, hydrocarbon fluids may include a hydrocarbon or mixtures of hydrocarbons that are gases or liquids at formation conditions, at processing conditions or at ambient conditions (15° C and 1 atm pressure). Hydrocarbon fluids may include, for example, oil, natural gas, coal bed methane, shale oil, pyrolysis oil, pyrolysis gas, a pyrolysis product of coal, and other hydrocarbons that are in a gaseous or liquid state.

[0072] As used herein, the term “fluid” refers to gases, liquids, and combinations of gases and liquids, as well as to combinations of gases and solids, and combinations of liquids and solids.

[0073] As used herein, the term “subsurface” refers to geologic strata occurring below the earth's surface.

[0074] The term "subsurface interval" refers to a formation or a portion of a formation wherein formation fluids may reside. The fluids may be, for example, hydrocarbon liquids, hydrocarbon gases, aqueous fluids, or combinations thereof.

[0075] As used herein, the term "wellbore" refers to a hole in the subsurface made by drilling or insertion of a conduit into the subsurface. A wellbore may have a substantially circular cross section, or other cross-sectional shape. As used herein, the term "well", when referring to an opening in the formation, may be used interchangeably with the term "wellbore."

[0076] The term "tubular member" refers to any pipe, such as a joint of casing, a portion of a liner, or a pup joint.

[0077] The term "sand control device" means any elongated tubular body that permits an inflow of fluid into an inner bore or a base pipe while filtering out predetermined sizes of sand, fines and granular debris from a surrounding formation. A sand screen is an example of a sand control device.

[0078] The term "alternate flow channels" means any collection of manifolds and/or shunt tubes that provide fluid communication through or around a packer to allow a gravel slurry to by-pass the packer elements or any premature sand bridge in the annular region, and to continue gravel packing further downstream. The term "alternate flow channels" can also mean any collection of manifolds and/or shunt tubes that provide fluid communication through or around a sand screen or a blank pipe (with or without outer protective shroud) to allow a gravel slurry to by-pass any premature sand bridge in the annular region and continue gravel packing below, or above and below, the downhole tool.

Description of Specific Embodiments

[0079] The inventions are described herein in connection with certain specific embodiments. However, to the extent that the following detailed description is specific to a particular embodiment or a particular use, such is intended to be illustrative only and is not to be construed as limiting the scope of the inventions.

[0080] Certain aspects of the inventions are also described in connection with various figures. In certain of the figures, the top of the drawing page is intended to be toward the surface, and the bottom of the drawing page toward the well bottom. While wells commonly are completed in substantially vertical orientation, it is understood that wells may also be inclined and or even horizontally completed. When the descriptive terms "up and down" or

"upper" and "lower" or similar terms are used in reference to a drawing or in the claims, they are intended to indicate relative location on the drawing page or with respect to claim terms, and not necessarily orientation in the ground, as the present inventions have utility no matter how the wellbore is orientated.

[0081] **Figure 1** is a cross-sectional view of an illustrative wellbore **100**. The wellbore **100** defines a bore **105** that extends from a surface **101**, and into the earth's subsurface **110**. The wellbore **100** is completed to have an open-hole portion **120** at a lower end of the wellbore **100**. The wellbore **100** has been formed for the purpose of producing hydrocarbons for commercial sale. A string of production tubing **130** is provided in the bore **105** to transport production fluids from the open-hole portion **120** up to the surface **101**.

[0082] The wellbore **100** includes a well tree, shown schematically at **124**. The well tree **124** includes a shut-in valve **126**. The shut-in valve **126** controls the flow of production fluids from the wellbore **100**. In addition, a subsurface safety valve **132** is provided to block the flow of fluids from the production tubing **130** in the event of a rupture or catastrophic event above the subsurface safety valve **132**. The wellbore **100** may optionally have a pump (not shown) within or just above the open-hole portion **120** to artificially lift production fluids from the open-hole portion **120** up to the well tree **124**.

[0083] The wellbore **100** has been completed by setting a series of pipes into the subsurface **110**. These pipes include a first string of casing **102**, sometimes known as surface casing or a conductor. These pipes also include at least a second **104** and a third **106** string of casing. These casing strings **104**, **106** are intermediate casing strings that provide support for walls of the wellbore **100**. Intermediate casing strings **104**, **106** may be hung from the surface, or they may be hung from a next higher casing string using an expandable liner or liner hanger. It is understood that a pipe string that does not extend back to the surface (such as casing string **106**) is normally referred to as a "liner."

[0084] In the illustrative wellbore arrangement of **Figure 1**, intermediate casing string **104** is hung from the surface **101**, while casing string **106** is hung from a lower end of casing string **104**. Additional intermediate casing strings (not shown) may be employed. The present inventions are not limited to the type of casing arrangement used.

[0085] Each string of casing **102**, **104**, **106** is set in place through cement **108**. The cement **108** isolates the various formations of the subsurface **110** from the wellbore **100** and each other. The cement **108** extends from the surface **101** to a depth "**L**" at a lower end of the casing string **106**. It is understood that some intermediate casing strings may not be fully cemented.

[0086] An annular region **204** is formed between the production tubing **130** and the casing string **106**. A production packer **206** seals the annular region **204** near the lower end "**L**" of the casing string **106**.

[0087] In many wellbores, a final casing string known as production casing is cemented into place at a depth where subsurface production intervals reside. However, the illustrative wellbore **100** is completed as an open-hole wellbore. Accordingly, the wellbore **100** does not include a final casing string along the open-hole portion **120**.

[0088] In the illustrative wellbore **100**, the open-hole portion **120** traverses three different subsurface intervals. These are indicated as upper interval **112**, intermediate interval **114**, and lower interval **116**. Upper interval **112** and lower interval **116** may, for example, contain valuable oil deposits sought to be produced, while intermediate interval **114** may contain primarily water or other aqueous fluid within its pore volume. This may be due to the presence of native water zones, high permeability streaks or natural fractures in the aquifer, or fingering from injection wells. In this instance, there is a probability that water will invade the wellbore **100**.

[0089] Alternatively, upper **112** and intermediate **114** intervals may contain hydrocarbon fluids sought to be produced, processed and sold, while lower interval **116** may contain some oil along with ever-increasing amounts of water. This may be due to coning, which is a rise of near-well hydrocarbon-water contact. In this instance, there is again the possibility that water will invade the wellbore **100**.

[0090] Alternatively still, upper **112** and lower **116** intervals may be producing hydrocarbon fluids from a sand or other permeable rock matrix, while intermediate interval **114** may represent a non-permeable shale or otherwise be substantially impermeable to fluids.

[0091] In any of these events, it is desirable for the operator to isolate selected intervals. In the first instance, the operator will want to isolate the intermediate interval **114** from the production string **130** and from the upper **112** and lower **116** intervals so that primarily hydrocarbon fluids may be produced through the wellbore **100** and to the surface **101**. In the second instance, the operator will eventually want to isolate the lower interval **116** from the production string **130** and the upper **112** and intermediate **114** intervals so that primarily hydrocarbon fluids may be produced through the wellbore **100** and to the surface **101**. In the third instance, the operator will want to isolate the upper interval **112** from the lower interval **116**, but need not isolate the intermediate interval **114**. Solutions to these needs in the

context of an open-hole completion are provided herein, and are demonstrated more fully in connection with the proceeding drawings.

[0092] In connection with the production of hydrocarbon fluids from a wellbore having an open-hole completion, it is not only desirable to isolate selected intervals, but also to limit the influx of sand particles and other fines. In order to prevent the migration of formation particles into the production string **130** during operation, sand control devices **200** have been run into the wellbore **100**. These are described more fully below in connection with **Figure 2**.

[0093] Referring now to **Figure 2**, the sand control devices **200** contain an elongated tubular body referred to as a base pipe **205**. The base pipe **205** typically is made up of a plurality of pipe joints. The base pipe **205** (or each pipe joint making up the base pipe **205**) typically has small perforations or slots to permit the inflow of production fluids.

[0094] The sand control devices **200** also contain a filter medium **207** wound or otherwise placed radially around the base pipes **205**. The filter medium **207** may be a wire mesh screen or wire wrap fitted around the base pipe **205**. Alternatively, the filtering medium of the sand screen comprises a membrane screen, an expandable screen, a sintered metal screen, a porous media made of shape memory polymer, a porous media packed with fibrous material, or a pre-packed solid particle bed. The filter medium **207** prevents the inflow of sand or other particles above a pre-determined size into the base pipe **205** and the production tubing **130**.

[0095] In addition to the sand control devices **200**, the wellbore **100** includes one or more packer assemblies **210**. In the illustrative arrangement of **Figures 1** and **2**, the wellbore **100** has an upper packer assembly **210'** and a lower packer assembly **210''**. However, additional packer assemblies **210** or just one packer assembly **210** may be used. The packer assemblies **210'**, **210''** are uniquely configured to seal an annular region (seen at **202** of **Figure 2**) between the various sand control devices **200** and a surrounding wall **201** of the open-hole portion **120** of the wellbore **100**.

[0096] The packer assemblies **210'**, **210''** allow the operator to isolate selected intervals along the open-hole portion of the wellbore **100** in order to control the migration of formation fluids. For example, in connection with the production of condensable hydrocarbons, water may sometimes invade an interval. This may be due to the presence of native water zones, coning (rise of near-well hydrocarbon-water contact), high permeability streaks, natural fractures, or fingering from injection wells. Depending on the mechanism or cause of the water production, the water may be produced at different locations and times during a well's

lifetime. Similarly, a gas cap above an oil reservoir may expand and break through, causing gas production with oil. The gas breakthrough reduces gas cap drive and suppresses oil production. Annular zonal isolation may also be desired for production allocation, production/injection fluid profile control, selective stimulation, or water or gas control.

[0097] **Figure 2** is an enlarged cross-sectional view of the open-hole portion **120** of the wellbore **100** of **Figure 1**. The open-hole portion **120** and the three intervals **112**, **114**, **116** are more clearly seen. The upper **210'** and lower **210''** packer assemblies are also more clearly visible proximate upper and lower boundaries of the intermediate interval **114**, respectively. Finally, the sand control devices **200** along each of the intervals **112**, **114**, **116** are shown.

[0098] Concerning the packer assemblies themselves, each packer assembly **210'**, **210''** may have at least two packers. The two packers are preferably set through a combination of mechanical manipulation and hydraulic forces. The packer assemblies **210** represent an upper packer **212** and a lower packer **214**. Each packer **212**, **214** has an expandable portion or element fabricated from an elastomeric or a thermoplastic material capable of providing at least a temporary fluid seal against the surrounding wellbore wall **201**.

[0099] The elements for the upper **212** and lower **214** packers should be able to withstand the pressures and loads associated with a gravel packing process. Typically, such pressures are from about 2,000 psi to 3,000 psi. The elements of the packers **212**, **214** should also withstand pressure load due to differential wellbore and/or reservoir pressures caused by natural faults, depletion, production, or injection. Production operations may involve selective production or production allocation to meet regulatory requirements. Injection operations may involve selective fluid injection for strategic reservoir pressure maintenance. Injection operations may also involve selective stimulation in acid fracturing, matrix acidizing, or formation damage removal.

[0100] The sealing surface or elements for the mechanically set packers **212**, **214** need only be on the order of inches to affect a suitable hydraulic seal. In one aspect, the elements are each about 6 inches (15.2 cm) to about 24 inches (61.0 cm) in length.

[0101] The elements for the packers **212**, **214** are preferably cup-type elements. Cup--type elements are known for use in cased-hole completions. However, they generally are not known for use in open-hole completions as they are not engineered to expand into engagement with an open-hole diameter. Moreover, such expandable cup-type elements

may not maintain the required pressure differential encountered over the life of production operations, resulting in decreased functionality.

[0102] It is preferred for the packers **212**, **214** to be able to expand to at least an 11-inch (about 28 cm) outer diameter surface, with no more than a 1.1 ovality ratio. The elements of the packers **212**, **214** should preferably be able to handle washouts in an 8-1/2 inch (about 21.6 cm) or 9-7/8 inch (about 25.1 cm) open-hole section **120**. The preferred cup-type nature of the expandable portions of the packer elements **212**, **214** will assist in maintaining at least a temporary seal against the wall **201** of the intermediate interval **114** (or other interval) as pressure increases during the gravel packing operation.

[0103] In one embodiment, the cup-type elements need not be liquid tight, nor must they be rated to handle multiple pressure and temperature cycles. The cup-type elements need only be designed for one-time use, to wit, during the gravel packing process of an open-hole wellbore completion. This is because an intermediate swellable packer element **216** is also preferably provided for long term sealing.

[0104] The upper **212** and lower **214** packers are set prior to a gravel pack installation process. As described more fully below, the packer **212**, **214** may be set by mechanically shearing a shear pin and sliding a release sleeve. This, in turn, releases a release key, which then allows hydrostatic pressure to act downwardly against a piston housing. The piston housing travels downward along an inner mandrel (not shown), and then acts upon both a centralizer and/or packer elements along the inner mandrel. The centralizer and the packer elements expand against the wellbore wall **201**. The expandable portions of the upper **212** and lower **214** packers are expanded into contact with the surrounding wall **201** so as to straddle the annular region **202** at a selected depth along the open-hole completion **120**.

[0105] As a “back-up” to the cup-type packer elements within the upper **212** and lower **214** packer elements, the packer assemblies **210’**, **210’’** also each include an intermediate packer element **216**. The intermediate packer element **216** defines a swelling elastomeric material fabricated from synthetic rubber compounds. Suitable examples of swellable materials may be found in Easy Well Solutions’ CONSTRICTOR™ or SWELLPACKER™, and Swellfix’s E-ZIP™. The swellable packer **216** may include a swellable polymer or swellable polymer material, which is known by those skilled in the art and which may be set by one of a conditioned drilling fluid, a completion fluid, a production fluid, an injection fluid, a stimulation fluid, or any combination thereof.

[0106] The swellable packer element **216** is preferably bonded to the outer surface of the mandrel **215**. The swellable packer element **216** is allowed to expand over time when contacted by hydrocarbon fluids, formation water, or any chemical described above which may be used as an actuating fluid. As the packer element **216** expands, it forms a fluid seal with the surrounding zone, e.g., interval **114**. In one aspect, a sealing surface of the swellable packet element **216** is from about 5 feet (1.5 meters) to 50 feet (15.2 meters) in length; and more preferably, about 3 feet (0.9 meters) to 40 feet (12.2 meters) in length.

[0107] The swellable packer element **216** must be able to expand to the wellbore wall **201** and provide the required pressure integrity at that expansion ratio. Since swellable packers are typically set in a shale section that may not produce hydrocarbon fluids, it is preferable to have a swelling elastomer or other material that can swell in the presence of formation water or an aqueous-based fluid. Examples of materials that will swell in the presence of an aqueous-based fluid are bentonite clay and a nitrile-based polymer with incorporated water absorbing particles.

[0108] Alternatively, the swellable packer element **216** may be fabricated from a combination of materials that swell in the presence of water and oil, respectively. Stated another way, the swellable packer element **216** may include two types of swelling elastomers -- one for water and one for oil. In this situation, the water-swellable element will swell when exposed to the water-based gravel pack fluid or in contact with formation water, and the oil-based element will expand when exposed to hydrocarbon production. An example of an elastomeric material that will swell in the presence of a hydrocarbon liquid is oleophilic polymer that absorbs hydrocarbons into its matrix. The swelling occurs from the absorption of the hydrocarbons which also lubricates and decreases the mechanical strength of the polymer chain as it expands. Ethylene propylene diene monomer (M-class) rubber, or EPDM, is one example of such a material.

[0109] The swellable packer **216** may be fabricated from other expandable material. An example is a shape-memory polymer. U.S. Pat. No. 7,243,732 and U.S. Pat. No. 7,392,852 disclose the use of such a material for zonal isolation.

[0110] The mechanically set packer elements **212**, **214** are preferably set in a water-based gravel pack fluid that would be diverted around the swellable packer element **216**, such as through shunt tubes (not shown in **Figure 2**). If only a hydrocarbon swelling elastomer is used, expansion of the element may not occur until after the failure of either of the mechanically set packer elements **212**, **214**.

[0111] The upper **212** and lower **214** packers are generally mirror images of each other, except for the release sleeves that shear the respective shear pins or other engagement mechanisms. Unilateral movement of a shifting tool (shown in and discussed in connection with **Figures 7A** and **7B**) will allow the packers **212**, **214** to be activated in sequence or simultaneously. The lower packer **214** is activated first, followed by the upper packer **212** as the shifting tool is pulled upward through an inner mandrel (shown in and discussed in connection with **Figures 6A** and **6B**). A short spacing is preferably provided between the upper **212** and lower **214** packers.

[0112] The packer assemblies **210'**, **210''** help control and manage fluids produced from different zones. In this respect, the packer assemblies **210'**, **210''** allow the operator to seal off an interval from either production or injection, depending on well function. Installation of the packer assemblies **210'**, **210''** in the initial completion allows an operator to shut-off the production from one or more zones during the well lifetime to limit the production of water or, in some instances, an undesirable non-condensable fluid such as hydrogen sulfide.

[0113] Packers historically have not been installed when an open-hole gravel pack is utilized because of the difficulty in forming a complete gravel pack above and below the packer. For example, see patent applications entitled "Wellbore Method and Apparatus for Completion, Production and Injection." The applications published on August 16, 2007, as WO 2007/092082 and WO 2007/092083, respectively. The applications disclose apparatus' and methods for gravel-packing an open-hole wellbore. PCT Publication Nos. WO 2007/092082 and WO 2007/092083 are each incorporated herein by reference in their entireties.

[0114] Certain technical challenges have remained with respect to the methods disclosed in the incorporated PCT publications, particularly in connection with the packer. The applications state that the packer may be a hydraulically actuated inflatable element. Such an inflatable element may be fabricated from an elastomeric material or a thermoplastic material. However, designing a packer element from such materials requires the packer element to meet a particularly high performance level. In this respect, the packer element needs to be able to maintain zonal isolation for a period of years in the presence of high pressures and/or high temperatures and/or acidic fluids. As an alternative, the applications state that the packer may be a swelling rubber element that expands in the presence of hydrocarbons, water, or other stimulus. However, known swelling elastomers typically require about 30 days or longer to fully expand into sealed fluid engagement with the surrounding rock formation. Therefore, improved packers and zonal isolation apparatus' are offered herein.

[0115] **Figure 3A** presents an illustrative packer assembly **300** providing an alternate flowpath for a gravel slurry. The packer assembly **300** is seen in cross-sectional side view. The packer assembly **300** includes various components that may be utilized to seal an annulus along the open-hole portion **120**.

[0116] The packer assembly **300** first includes a main body section **302**. The main body section **302** is preferably fabricated from steel or from steel alloys. The main body section **302** is configured to be a specific length **316**, such as about 40 feet (12.2 meters). The main body section **302** comprises individual pipe joints that will have a length that is between about 10 feet (3.0 meters) and 50 feet (15.2 meters). The pipe joints are typically threadedly connected end-to-end to form the main body section **302** according to length **316**.

[0117] The packer assembly **300** also includes opposing mechanically-set packers **304**. The mechanically-set packers **304** are shown schematically, and are generally in accordance with mechanically-set packer elements **212** and **214** of **Figure 2**. The packers **304** preferably include cup-type elastomeric elements that are less than 1 foot (0.3 meters) in length. As described further below, the packers **304** have alternate flow channels that uniquely allow the packers **304** to be set before a gravel slurry is circulated into the wellbore.

[0118] The packer assembly **300** also optionally includes a swellable packer **308**. The swellable packer **308** is in accordance with swellable packer element **216** of **Figure 2**. The swellable packer **308** is preferably about 3 feet (0.9 meters) to 40 feet (12.2 meters) in length. Together, the mechanically-set packers **304** and the intermediate swellable packer **308** surround the main body section **302**. Alternatively, a short spacing may be provided between the mechanically-set packers **304** in lieu of the swellable packer **308**.

[0119] The packer assembly **300** also includes a plurality of shunt tubes. The shunt tubes are seen in phantom at **318**. The shunt tubes **318** may also be referred to as transport tubes or jumper tubes. The shunt tubes **318** are blank sections of pipe having a length that extends along the length **316** of the mechanically-set packers **304** and the swellable packer **308**. The shunt tubes **318** on the packer assembly **300** are configured to couple to and form a seal with shunt tubes on connected sand screens as discussed further below.

[0120] The shunt tubes **318** provide an alternate flowpath through the mechanically-set packers **304** and the intermediate swellable packer **308** (or spacing). This enables the shunt tubes **318** to transport a carrier fluid along with gravel to different intervals **112**, **114** and **116** of the open-hole portion **120** of the wellbore **100**.

[0121] The packer assembly **300** also includes connection members. These may represent traditional threaded couplings. First, a neck section **306** is provided at a first end of the packer assembly **300**. The neck section **306** has external threads for connecting with a threaded coupling box of a sand screen or other pipe. Then, a notched or externally threaded section **310** is provided at an opposing second end. The threaded section **310** serves as a coupling box for receiving an external threaded end of a sand screen or other tubular member.

[0122] The neck section **306** and the threaded section **310** may be made of steel or steel alloys. The neck section **306** and the threaded section **310** are each configured to be a specific length **314**, such as 4 inches (10.2 cm) to 4 feet (1.2 meters) (or other suitable distance). The neck section **306** and the threaded section **310** also have specific inner and outer diameters. The neck section **306** has external threads **307**, while the threaded section **310** has internal threads **311**. These threads **307** and **311** may be utilized to form a seal between the packer assembly **300** and sand control devices or other pipe segments.

[0123] A cross-sectional view of the packer assembly **300** is shown in **Figure 3B**. **Figure 3B** is taken along the line **3B-3B** of **Figure 3A**. In **Figure 3B**, the swellable packer **308** is seen circumferentially disposed around the base pipe **302**. Various shunt tubes **318** are placed radially and equidistantly around the base pipe **302**. A central bore **305** is shown within the base pipe **302**. The central bore **305** receives production fluids during production operations and conveys them to the production tubing **130**.

[0124] **Figure 4A** presents a cross-sectional side view of a zonal isolation apparatus **400**, in one embodiment. The zonal isolation apparatus **400** includes the packer assembly **300** from **Figure 3A**. In addition, sand control devices **200** have been connected at opposing ends to the neck section **306** and the notched section **310**, respectively. Shunt tubes **318** from the packer assembly **300** are seen connected to shunt tubes **218** on the sand control devices **200**. The selective shunt tubes **218** on the sand control devices **200** include ports or nozzles or orifices **209**, such shunt tubes called packing tubes, to allow flow of gravel slurry between a wellbore annulus and the packing tubes. The shunt tubes **218** on the sand control devices **200** may optionally include valves at **209** to control the flow of gravel slurry such as to packing tubes (not shown).

[0125] **Figure 4B** provides a cross-sectional side view of the zonal isolation apparatus **400**. **Figure 4B** is taken along the line **4B-4B** of **Figure 4A**. This is cut through one of the sand screens **200**. In **Figure 4B**, the slotted or perforated base pipe **205** is seen. This is in

accordance with base pipe **205** of **Figures 1** and **2**. The central bore **105** is shown within the base pipe **205** for receiving production fluids during production operations.

[0126] An outer mesh **220** is disposed immediately around the base pipe **205**. The outer mesh **220** preferably comprises a wire mesh or wires helically wrapped around the base pipe **205**, and serves as a screen. In addition, shunt tubes **218** are placed radially and equidistantly around the outer mesh **205**. This means that the sand control devices **200** provide an external embodiment for the shunt tubes **218** (or alternate flow channels).

[0127] The configuration of the shunt tubes **218** is preferably concentric. This is seen in the cross-sectional view of **Figure 3B**. However, the shunt tubes **218** may be eccentrically designed. For example, Figure 2B in U.S. Pat. No. 7,661,476 presents a "Prior Art" arrangement for a sand control device wherein packing tubes 208a and transport tubes 208b are placed external to the base pipe 202 and surrounding filter medium 204.

[0128] A concentric flow channel sand screen comprises a central bore that receives production fluids, and a filtering medium concentrically disposed around the central bore. Further, two or more shunt tubes are placed radially around the central bore. An eccentric flow channel screen also comprises a central bore that receives production fluids, but with a filtering medium disposed eccentrically around the central bore. Two or more shunt tubes are placed adjacent the central bore, typically outside of both the central bore and the filtering medium. An outer shroud may be placed around the shunt tubes representing packing tubes and transport tubes.

[0129] In the arrangement of **Figures 4A** and **4B**, the shunt tubes **218** are external to the filter medium, or outer mesh **220**. However, the configuration of the sand control device **200** may be modified. In this respect, the shunt tubes **218** may be moved internal to the filter medium **220**.

[0130] **Figure 5A** presents a cross-sectional side view of a zonal isolation apparatus **500**, in an alternate embodiment. In this embodiment, sand control devices **200** are again connected at opposing ends to the neck section **306** and the notched section **310**, respectively, of the packer assembly **300**. In addition, shunt tubes **318** on the packer assembly **300** are seen connected to shunt tubes **218** on the sand control assembly **200**. However, in **Figure 5A**, the sand control assembly **200** utilizes internal shunt tubes **218**, meaning that the shunt tubes **218** are disposed between the base pipe **205** and the surrounding filter medium **220**.

[0131] **Figure 5B** provides a cross-sectional side view of the zonal isolation apparatus **500**. **Figure 5B** is taken along the line **B-B** of **Figure 5A**. This is cut through one of the sand screens **200**. In **Figure 5B**, the slotted or perforated base pipe **205** is again seen. This is in accordance with base pipe **205** of **Figures 1** and **2**. The central bore **105** is shown within the base pipe **205** for receiving production fluids during production operations.

[0132] Shunt tubes **218** are placed radially and equidistantly around the base pipe **205**. The shunt tubes **218** reside immediately around the base pipe **205**, and within a surrounding filter medium **220**. This means that the sand control devices **200** of **Figures 5A** and **5B** provide an internal embodiment for the shunt tubes **218**.

[0133] An annular region **225** is created between the base pipe **205** and the surrounding outer mesh or filter medium **220**. The annular region **225** accommodates the inflow of production fluids in a wellbore. The outer wire wrap **220** is supported by a plurality of radially extending support ribs **222**. The ribs **222** extend through the annular region **225**.

[0134] **Figures 4A** and **5A** present arrangements for connecting sand control joints to a packer assembly. Shunt tubes **318** (or alternate flow channels) within the packers fluidly connect to shunt tubes **218** along the sand screens **200**. However, the zonal isolation apparatus arrangements **400**, **500** of **Figures 4A-4B** and **5A-5B** are merely illustrative. In an alternative arrangement, a manifolding system may be used for providing fluid communication between the shunt tubes **218** and the shunt tubes **318**.

[0135] **Figure 3C** is a cross-sectional view of the packer assembly **300** of **Figure 3A**, in an alternate embodiment. In this arrangement, the shunt tubes **218** are manifolded around the base pipe **302**. A support ring **315** is provided around the shunt tubes **318**. Walls **222** separate the shunt tubes **318** within the swellable packer element **308**. It is again understood that the present apparatus and methods are not confined by the particular design and arrangement of shunt tubes **318** so long as slurry bypass is provided for the packer assembly **210**. However, it is preferred that a concentric arrangement be employed.

[0136] It should also be noted that the coupling mechanism for the sand control devices **200** with the packer assembly **300** may include a sealing mechanism (not shown). The sealing mechanism prevents leaking of the slurry that is in the alternate flowpath formed by the shunt tubes. Examples of such sealing mechanisms are described in U.S. Patent No. 6,464,261; Intl. Pat. Application Publ. No. WO 2004/094769; Intl. Pat. Application Publ. No. WO 2005/031105; U.S. Pat. Publ. No. 2004/0140089; U.S. Pat. Publ. No. 2005/0028977; U.S. Pat. Publ. No. 2005/0061501; and U.S. Pat. Publ. No. 2005/0082060.

[0137] As noted, the packer assembly **300** includes a pair of mechanically-set packers **304**. When using the packer assembly **300**, the packers **304** are beneficially set before the slurry is injected and the gravel pack is formed. This requires a unique packer arrangement wherein shunt tubes are provided for an alternate flow channel.

[0138] The packers **304** of **Figure 3A** are shown schematically. However, **Figures 6A** and **6B** provide more detailed views of a mechanically-set packer **600** that may be used in the packer assembly of **Figure 3A**, in one embodiment. The views of **Figures 6A** and **6B** provide cross-sectional side views. In **Figure 6A**, the packer **600** is in its run-in position, while in **Figure 6B** the packer **600** is in its set position.

[0139] Other embodiments of sand control devices **200** may be used with the apparatuses and methods herein. For example, the sand control devices may include stand-alone screens (SAS), pre-packed screens, or membrane screens. The joints may be any combination of screen, blank pipe, or zonal isolation apparatus.

[0140] The packer **600** first includes an inner mandrel **610**. The inner mandrel **610** defines an elongated tubular body forming a central bore **605**. The central bore **605** provides a primary flow path of production fluids through the packer **600**. After installation and commencement of production, the central bore **605** transports production fluids to the bore **105** of the sand screens **200** (seen in **Figures 4A** and **4B**) and the production tubing **130** (seen in **Figures 1** and **2**).

[0141] The packer **600** also includes a first end **602**. Threads **604** are placed along the inner mandrel **610** at the first end **602**. The illustrative threads **604** are external threads. A box connector **614** having internal threads at both ends is connected or threaded on threads **604** at the first end **602**. The first end **602** of inner mandrel **610** with the box connector **614** is called the box end. The second end (not shown) of the inner mandrel **610** has external threads and is called the pin end. The pin end (not shown) of the inner mandrel **610** allows the packer **600** to be connected to the box end of a sand screen or other tubular body such as a stand-alone screen, a sensing module, a production tubing, or a blank pipe.

[0142] The box connector **614** at the box end **602** allows the packer **600** to be connected to the pin end of a sand screen or other tubular body such as a stand-alone screen, a sensing module, a production tubing, or a blank pipe.

[0143] The inner mandrel **610** extends along the length of the packer **600**. The inner mandrel **610** may be composed of multiple connected segments, or joints. The inner mandrel **610** has a slightly smaller inner diameter near the first end **602**. This is due to a

setting shoulder **606** machined into the inner mandrel. As will be explained more fully below, the setting shoulder **606** catches a release sleeve **710** in response to mechanical force applied by a setting tool.

[0144] The packer **600** also includes a piston mandrel **620**. The piston mandrel **620** extends generally from the first end **602** of the packer **600**. The piston mandrel **620** may be composed of multiple connected segments, or joints. The piston mandrel **620** defines an elongated tubular body that resides circumferentially around and substantially concentric to the inner mandrel **610**. An annulus **625** is formed between the inner mandrel **610** and the surrounding piston mandrel **620**. The annulus **625** beneficially provides a secondary flow path or alternate flow channels for fluids.

[0145] In the arrangement of **Figures 6A** and **6B**, the alternate flow channels defined by the annulus **625** are external to the inner mandrel **610**. However, the packer could be reconfigured such that the alternate flow channels are within the bore **605** of the inner mandrel **610**. In either instance, the alternate flow channels are "along" the inner mandrel **610**.

[0146] The annulus **625** is in fluid communication with the secondary flow path of another downhole tool (not shown in **Figures 6A** and **6B**). Such a separate tool may be, for example, the sand screens **200** of **Figures 4A** and **5A**, or a blank pipe, a swellable zonal isolation packer such as packer **308** of **Figure 3A**, or other tubular body. The tubular body may or may not have alternate flow channels.

[0147] The packer **600** also includes a coupling **630**. The coupling **630** is connected and sealed (e.g., via elastomeric "o" rings) to the piston mandrel **620** at the first end **602**. The coupling **630** is then threaded and pinned to the box connector **614**, which is threadedly connected to the inner mandrel **610** to prevent relative rotational movement between the inner mandrel **610** and the coupling **630**. A first torque bolt is shown at **632** for pinning the coupling to the box connector **614**.

[0148] In one aspect, a NACA (National Advisory Committee for Aeronautics) key **634** is also employed. The NACA key **634** is placed internal to the coupling **630**, and external to a threaded box connector **614**. A first torque bolt is provided at **632**, connecting the coupling **630** to the NACA key **634** and then to the box connector **614**. A second torque bolt is provided at **636** connecting the coupling **630** to the NACA key **634**. NACA-shaped keys can (a) fasten the coupling **630** to the inner mandrel **610** via box connector **614**, (b) prevent the coupling **630** from rotating around the inner mandrel **610**, and (c) streamline the flow of slurry along the annulus **612** to reduce friction.

[0149] Within the packer **600**, the annulus **625** around the inner mandrel **610** is isolated from the main bore **605**. In addition, the annulus **625** is isolated from a surrounding wellbore annulus (not shown). The annulus **625** enables the transfer of gravel slurry from alternative flow channels (such as shunt tubes **218**) through the packer **600**. Thus, the annulus **625** becomes the alternative flow channel(s) for the packer **600**.

[0150] In operation, an annular space **612** resides at the first end **602** of the packer **600**. The annular space **612** is disposed between the box connector **614** and the coupling **630**. The annular space **612** receives slurry from alternate flow channels of a connected tubular body, and delivers the slurry to the annulus **625**. The tubular body may be, for example, an adjacent sand screen, a blank pipe, or a zonal isolation device.

[0151] The packer **600** also includes a load shoulder **626**. The load shoulder **626** is placed near the end of the piston mandrel **620** where the coupling **630** is connected and sealed. A solid section at the end of the piston mandrel **620** has an inner diameter and an outer diameter. The load shoulder **626** is placed along the outer diameter. The inner diameter has threads and is threadedly connected to the inner mandrel **610**. At least one alternate flow channel is formed between the inner and outer diameters to connect flow between the annular space **612** and the annulus **625**.

[0152] The load shoulder **626** provides a load-bearing point. During rig operations, a load collar or harness (not shown) is placed around the load shoulder **626** to allow the packer **600** to be picked up and supported with conventional elevators. The load shoulder **626** is then temporarily used to support the weight of the packer **600** (and any connected completion devices such as sand screen joints already run into the well) when placed in the rotary floor of a rig. The load may then be transferred from the load shoulder **626** to a pipe thread connector such as box connector **614**, then to the inner mandrel **610** or base pipe **205**, which is pipe threaded to the box connector **614**.

[0153] The packer **600** also includes a piston housing **640**. The piston housing **640** resides around and is substantially concentric to the piston mandrel **620**. The packer **600** is configured to cause the piston housing **640** to move axially along and relative to the piston mandrel **620**. Specifically, the piston housing **640** is driven by the downhole hydrostatic pressure. The piston housing **640** may be composed of multiple connected segments, or joints.

[0154] The piston housing **640** is held in place along the piston mandrel **620** during run-in. The piston housing **640** is secured using a release sleeve **710** and release key **715**. The release sleeve **710** and release key **715** prevent relative translational movement between

the piston housing **640** and the piston mandrel **620**. The release key **715** penetrates through both the piston mandrel **620** and the inner mandrel **610**.

[0155] **Figures 7A** and **7B** provide enlarged views of the release sleeve **710** and the release key **715** for the packer **600**. The release sleeve **710** and the release key **715** are held in place by a shear pin **720**. In **Figure 7A**, the shear pin **720** has not been sheared, and the release sleeve **710** and the release key **715** are held in place along the inner mandrel **610**. However, in **Figure 7B** the shear pin **720** has been sheared, and the release sleeve **710** has been translated along an inner surface **608** of the inner mandrel **610**.

[0156] In each of **Figures 7A** and **7B**, the inner mandrel **610** and the surrounding piston mandrel **620** are seen. In addition, the piston housing **640** is seen outside of the piston mandrel **620**. The three tubular bodies representing the inner mandrel **610**, the piston mandrel **620**, and the piston housing **640** are secured together against relative translational or rotational movement by four release keys **715**. Only one of the release keys **715** is seen in **Figure 7A**; however, four separate keys **715** are radially visible in the cross-sectional view of **Figure 6E**, described below.

[0157] The release key **715** resides within a keyhole **615**. The keyhole **615** extends through the inner mandrel **610** and the piston mandrel **620**. The release key **715** includes a shoulder **734**. The shoulder **734** resides within a shoulder recess **624** in the piston mandrel **620**. The shoulder recess **624** is large enough to permit the shoulder **734** to move radially inwardly. However, such play is restricted in **Figure 7A** by the presence of the release sleeve **710**.

[0158] It is noted that the annulus **625** between the inner mandrel **610** and the piston mandrel **620** is not seen in **Figure 7A** or **7B**. This is because the annulus **625** does not extend through this cross-section, or is very small. Instead, the annulus **625** employs separate radially-spaced channels that preserve the support for the release keys **715**, as seen best in **Figure 6E**. Stated another way, the large channels making up the annulus **625** are located away from the material of the inner mandrel **610** that surrounds the keyholes **615**.

[0159] At each release key location, a keyhole **615** is machined through the inner mandrel **610**. The keyholes **615** are drilled to accommodate the respective release keys **715**. If there are four release keys **715**, there will be four discrete bumps spaced circumferentially to significantly reduce the annulus **625**. The remaining area of the annulus **625** between adjacent bumps allows flow in the alternate flow channel **625** to by-pass the release key **715**.

[0160] Bumps may be machined as part of the body of the inner mandrel **610**. More specifically, material making up the inner mandrel **610** may be machined to form the bumps. Alternatively, bumps may be machined as a separate, short release mandrel (not shown), which is then threaded to the inner mandrel **610**. Alternatively still, the bumps may be a separate spacer secured between the inner mandrel **610** and the piston mandrel **620** by welding or other means.

[0161] It is also noted here that in **Figure 6A**, the piston mandrel **620** is shown as an integral body. However, the portion of the piston mandrel **620** where the keyholes **615** are located may be a separate, short release housing. This separate housing is then connected to the main piston mandrel **620**.

[0162] Each release key **715** has an opening **732**. Similarly, the release sleeve **710** has an opening **722**. The opening **732** in the release key **715** and the opening **722** in the release sleeve **710** are sized and configured to receive a shear pin. The shear pin is seen at **720**. In **Figure 7A**, the shear pin **720** is held within the openings **732**, **722** by the release sleeve **710**. However, in **Figure 7B** the shear pin **720** has been sheared, and only a small portion of the pin **720** remains visible.

[0163] An outer edge of the release key **715** has a ruggled surface, or teeth. The teeth for the release key **715** are shown at **736**. The teeth **736** of the release key **715** are angled and configured to mate with a reciprocal ruggled surface within the piston housing **640**. The mating ruggled surface (or teeth) for the piston housing **640** are shown at **646**. The teeth **646** reside on an inner face of the piston housing **640**. When engaged, the teeth **736**, **646** prevent movement of the piston housing **640** relative to the piston mandrel **620** or the inner mandrel **610**. Preferably, the mating ruggled surface or teeth **646** reside on the inner face of a separate, short outer release sleeve, which is then threaded to the piston housing **640**.

[0164] Returning now to **Figures 6A** and **6B**, the packer **600** includes a centralizing member **650**. The centralizing member **650** is actuated by the movement of the piston housing **640**. The centralizing member **650** may be, for example, as described in WO/2009/071874, entitled "Improved Centraliser." This application was filed on behalf of Petrowell Ltd., and has an international filing date of November 28, 2008. The international application is incorporated herein in its entirety.

[0165] The packer **600** further includes a sealing element **655**. As the centralizing member **650** is actuated and centralizes the packer **600** within the surrounding wellbore, the piston housing **640** continues to actuate the sealing element **655** as described in WO/2007/107773, entitled "Improved Packer" having an international filing date of

March 22, 2007. The international application is incorporated herein in its entirety by reference.

[0166] In **Figure 6A**, the centralizing member **650** and sealing element **655** are in their run-in position. In **Figure 6B**, the centralizing member **650** and connected sealing element **655** have been actuated. This means the piston housing **640** has moved along the piston mandrel **620**, causing both the centralizing member **650** and the sealing element **655** to engage the surrounding wellbore wall.

[0167] An anchor system as described in WO 2010/084353 may be used to prevent the piston housing **640** from going backward. This prevents contraction of the cup-type element **655**.

[0168] As noted, movement of the piston housing **640** takes place in response to hydrostatic pressure from wellbore fluids, including the gravel slurry. In the run-in position of the packer **600** (shown in **Figure 6A**), the piston housing **640** is held in place by the release sleeve **710** and associated piston key **715**. This position is shown in **Figure 7A**. In order to set the packer **600** (in accordance with **Figure 6B**), the release sleeve **710** must be moved out of the way of the release key **715** so that the teeth **736** of the release key **715** are no longer engaged with the teeth **646** of the piston housing **640**. This position is shown in **Figure 7B**.

[0169] To move the release the release sleeve **710**, a setting tool is used. An illustrative setting tool is shown at **750** in **Figure 7C**. The setting tool **750** defines a short cylindrical body **755**. Preferably, the setting tool **750** is run into the wellbore with a washpipe string (not shown). Movement of the washpipe string along the wellbore can be controlled at the surface.

[0170] An upper end **752** of the setting tool **750** is made up of several radial collet fingers **760**. The collet fingers **760** collapse when subjected to sufficient inward force. In operation, the collet fingers **760** latch into a profile **724** formed along the release sleeve **710**. The collet fingers **760** include raised surfaces **762** that mate with or latch into the profile **724** of the release key **710**. Upon latching, the setting tool **750** is pulled or raised within the wellbore. The setting tool **750** then pulls the release sleeve **710** with sufficient force to cause the shear pins **720** to shear. Once the shear pins **720** are sheared, the release sleeve **710** is free to translate upward along the inner surface **608** of the inner mandrel **610**.

[0171] As noted, the setting tool **750** may be run into the wellbore with a washpipe. The setting tool **750** may simply be a profiled portion of the washpipe body. Preferably, however,

the setting tool **750** is a separate tubular body **755** that is threadedly connected to the washpipe. In **Figure 7C**, a connection tool is provided at **770**. The connection tool **770** includes external threads **775** for connecting to a drill string or other run-in tubular. The connection tool **770** extends into the body **755** of the setting tool **750**. The connection tool **770** may extend all the way through the body **755** to connect to the washpipe or other device, or it may connect to internal threads (not seen) within the body **755** of the setting tool **750**.

[0172] Returning to **Figures 7A** and **7B**, the travel of the release sleeve **710** is limited. In this respect, a first or top end **726** of the release sleeve **710** stops against the shoulder **606** along the inner surface **608** of the inner mandrel **610**. The length of the release sleeve **710** is short enough to allow the release sleeve **710** to clear the opening **732** in the release key **715**. When fully shifted, the release key **715** moves radially inward, pushed by the ruggled profile in the piston housing **640** when hydrostatic pressure is present.

[0173] Shearing of the pin **720** and movement of the release sleeve **710** also allows the release key **715** to disengage from the piston housing **640**. The shoulder recess **624** is dimensioned to allow the shoulder **734** of the release key **715** to drop or to disengage from the teeth **646** of the piston housing **640** once the release sleeve **710** is cleared. Hydrostatic pressure then acts upon the piston housing **640** to translate it downward relative to the piston mandrel **620**.

[0174] After the shear pins **720** have been sheared, the piston housing **640** is free to slide along an outer surface of the piston mandrel **620**. To accomplish this, hydrostatic pressure from the annulus **625** acts upon a shoulder **642** in the piston housing **640**. This is seen best in **Figure 6B**. The shoulder **642** serves as a pressure-bearing surface. A fluid port **628** is provided through the piston mandrel **620** to allow fluid to access the shoulder **642**. Beneficially, the fluid port **628** allows a pressure higher than hydrostatic pressure to be applied during gravel packing operations. The pressure is applied to the piston housing **640** to ensure that the packer elements **655** engage against the surrounding wellbore.

[0175] The packer **600** also includes a metering device. As the piston housing **640** translates along the piston mandrel **620**, a metering orifice **664** regulates the rate the piston housing translates along the piston mandrel therefore slowing the movement of the piston housing and regulating the setting speed for the packer **600**.

[0176] To further understand features of the illustrative mechanically-set packer **600**, several additional cross-sectional views are provided. These are seen at **Figures 6C**, **6D**, **6E**, and **6F**.

[0177] First, **Figure 6C** is a cross-sectional view of the mechanically-set packer of **Figure 6A**. The view is taken across line **6C-6C** of **Figure 6A**. Line **6C-6C** is taken through one of the torque bolts **636**. The torque bolt **636** connects the coupling **630** to the NACA key **634**.

[0178] **Figure 6D** is a cross-sectional view of the mechanically-set packer of **Figure 6A**. The view is taken across line **6D-6D** of **Figure 6B**. Line **6D-6D** is taken through another of the torque bolts **632**. The torque bolt **632** connects the coupling **630** to the box connector **614**, which is threaded to the inner mandrel **610**.

[0179] **Figure 6E** is a cross-sectional view of the mechanically-set packer **600** of **Figure 6A**. The view is taken across line **6E-6E** of **Figure 6A**. Line **6E-E** is taken through the release key **715**. It can be seen that the release key **715** passes through the piston mandrel **620** and into the inner mandrel **610**. It is also seen that the alternate flow channel **625** resides between the release keys **715**.

[0180] **Figure 6F** is a cross-sectional view of the mechanically-set packer **600** of **Figure 6A**. The view is taken across line **6F-6F** of **Figure 6B**. Line **6F-6F** is taken through the fluid ports **628** within the piston mandrel **620**. As the fluid moves through the fluid ports **628** and pushes the shoulder **642** of the piston housing **640** away from the ports **628**, an annular gap **672** is created and elongated between the piston mandrel **620** and the piston housing **640**.

[0181] Coupling sand control devices **200** with a packer assembly **300** requires alignment of the shunt tubes **318** in the packer assembly **300** with the shunt tubes **218** along the sand control devices **200**. In this respect, the flow path of the shunt tubes **218** in the sand control devices should be un-interrupted when engaging a packer. **Figure 4A** (described above) shows sand control devices **200** connected to an intermediate packer assembly **300**, with the shunt tubes **218**, **318** in alignment. However, making this connection typically requires a special sub or jumper with a union-type connection, a timed connection to align the multiple tubes, or a cylindrical cover plate over the connecting tubes. These connections are expensive, time-consuming, and/or difficult to handle on the rig floor.

[0182] U.S. Patent No. 7,661,476, entitled "Gravel Packing Methods," discloses a production string (referred to as a joint assembly) that employs one or more sand screen joints. The sand screen joints are placed between a "load sleeve assembly" and a "torque sleeve assembly." The load sleeve assembly defines an elongated body comprising an outer wall (serving as an outer diameter) and an inner wall (providing an inner diameter). The inner wall forms a bore through the load sleeve assembly. Similarly, the torque sleeve assembly defines an elongated body comprising an outer wall (serving as an outer diameter)

and an inner wall (providing an inner diameter). The inner wall also forms a bore through the torque sleeve assembly.

[0183] The load sleeve assembly includes at least one transport conduit and at least one packing conduit. The at least one transport conduit and the at least one packing conduit are disposed exterior to the inner diameter and interior to the outer diameter. Similarly, torque sleeve assembly includes at least one conduit. The at least one conduit is also disposed exterior to the inner diameter and interior to the outer diameter.

[0184] The load sleeve assembly and the torque sleeve assembly may be used for connecting a production string to a joint of a sand screen. The production string includes a "main body portion" that is placed in fluid communication with the base pipe of the sand screen through the load sleeve assembly and the torque sleeve assembly. The load sleeve assembly and the torque sleeve assembly are made up or coupled with the base pipe in such a manner that the transport and packing conduits are in fluid communication, thereby providing alternate flow channels for gravel slurry.

[0185] A coupling assembly may also be used for connecting the load sleeve assembly to a joint of sand screen. The coupling assembly has a manifold region, wherein the manifold region is configured to be in fluid flow communication with the at least one transport conduit and at least one packing conduit of the load sleeve assembly during at least a portion of gravel packing operations. Benefits of the load sleeve assembly, the torque sleeve assembly, and a coupling assembly is that they enable a series of sand screen joints to be connected and run into the wellbore in a faster and less expensive way.

[0186] The load sleeve and the torque sleeve of U.S. Patent No. 7,661,476 assume that the sand screen and the packer being joined have a matching radial center. This means that the wellbore tools being run into the wellbore each have concentric flow paths, or they each have eccentric flow paths, and the flow paths match. However, it is desirable to be able to fluidly connect wellbore tools having different radial center lines. Further, it is desirable to be able to fluidly connect a first wellbore tool having a primary flow path that is concentric relative to that first tool, with a second wellbore tool having a primary flow path that is eccentric relative to that second tool. Accordingly, a crossover joint is provided herein.

[0187] **Figures 8A** through **8C** demonstrate various eccentric designs for a wellbore tool. Here, the illustrative wellbore tools are sand control devices. The sand control devices may be sand screens or blank pipes. Each of the wellbore tools **800A**, **800B**, **800C** comprises a base pipe **810** that defines a bore **805** therein. The bore **805** represents a primary flow path. In addition, each of the wellbore tools **800A** and **800C** comprises a filter

medium **820** around the base pipe **810**. Finally, each of the wellbore tools **800A**, **800B**, **800C** includes an alternate flow channel for a gravel slurry. The alternate flow channels in the illustrative sand screens **800A, 800C** are rectangular or round shunt tubes; the alternate flow channel in the illustrative blank pipe **800B** is an eccentric annulus between base pipe **810** and an outer housing **850**.

[0188] In **Figure 8A**, a first sand control device **800A** is shown. The sand control device **800A** includes the base pipe **810**. The filter medium **820** is concentrically disposed around the base pipe **810**. An outer protective shroud **840** is then eccentrically placed around the base pipe **810** and filter medium **820**. The shroud **840** is perforated, meaning it permits the ingress of gravel slurry and wellbore fluids.

[0189] An annular area **835** is formed between the filter medium **820** and the surrounding shroud **840**. Within the annular area **835** is a plurality of alternate flow channels. In the arrangement of **Figure 8A**, these represent transport tubes **830A** and packing tubes **832A**. The use of transport tubes and packing tubes as alternate flow channels for gravel slurry in general is known in the art. The transport tubes **830A** and packing tubes **832A** reside around the filter medium **820**.

[0190] In **Figure 8B**, a blank pipe **800B** is shown. The blank pipe **800B** again includes the base pipe **810**. In this arrangement, an outer housing **850** is eccentrically disposed around the base pipe **810**. An eccentric an annular area **835** is formed between the base pipe **810** and surrounding housing **850** serves as the alternate flow channel **830B**. The shunted blank pipe **800B** is installed above the top joint of a screen or across an isolated section between packers, as is known in the art.

[0191] In **Figure 8C**, a second sand control device **800C** is shown. The sand control device **800C** again includes the base pipe **810**. In this arrangement, the filter medium **820** is concentrically disposed around the base pipe **810**. An outer protective shroud **840** is then eccentrically placed around the base pipe **810** and filter medium **820**. The shroud **840** is perforated, meaning it permits the ingress of gravel slurry and wellbore fluids. An annular area **835** is again formed between the filter medium **820** and surrounding shroud **840**.

[0192] In **Figure 8C**, shunt tubes **830C** are provided in the annular area **835**. The shunt tubes **830C** serve as the alternate flow channels.

[0193] In each of **Figures 8A**, **8B** and **8C**, the respective alternate flow channels **830A**, **830B**, **830C** represent secondary flow paths. These secondary flow paths are eccentric to a radial center of the wellbore tools **800A**, **800B**, **800C**. In one embodiment, an eccentric

screen arrangement offers lower friction in the secondary flow paths when compared to shunt tubes in a concentric screen. It is believed that the use of eccentric screens at the toe of a horizontal completion will reduce the overall friction or extend the maximum gravel packing length of the completion.

[0194] **Figures 9A** through **9C** demonstrate various concentric designs for a wellbore tool. Here, the illustrative wellbore tools are packers. Each of the packers **900A**, **900B**, **900C** comprises a base pipe **910** that defines a bore **905** therein. The bore **905** represents a primary flow path. In addition, each of the packers **900A**, **900B**, **900C** comprises an outer housing **920** around the base pipe **910**.

[0195] In **Figure 9A**, a first packer **900A** is shown. The packer **900A** includes the base pipe **910**. The housing **920** is concentrically disposed around the base pipe **910**. An annular area **935** is formed between the base pipe **910** and the surrounding housing **920**. The annular area **935** optionally contains ribs **937** for supporting and spacing the housing **920** around the base pipe **910**.

[0196] The annular area **935** also contains a plurality of alternate flow channels. In the arrangement of **Figure 9A**, these represent transport tubes **930A** and packing tubes **932A**. The use of transport tubes and packing tubes as alternate flow channels for gravel slurry in general is known in the art.

[0197] In **Figure 9B**, a second packer **900B** is shown. The packer **900B** again includes the base pipe **910**. The housing **920** is concentrically disposed around the base pipe **910**. An annular area **935** is formed between the base pipe **910** and the surrounding housing **920**. In this arrangement, no transport tubes or packing tubes are employed; instead, the annular area **935** itself serves as an alternate flow channel **930B**.

[0198] In **Figure 9C**, a third packer **900C** is shown. The packer **900C** again includes the base pipe **910** and the surrounding housing **920**. In this arrangement, shunt tubes **930C** are eccentrically disposed adjacent the base pipe **910**. The shunt tubes **830C** reside in the annular area **935** and serve as the alternate flow channels.

[0199] In each of **Figures 9A**, **9B** and **9C**, the respective alternate flow channels **930A**, **930B**, **930C** represent secondary flow paths.

[0200] The **Figure 8** series described above uses sand control devices and blank pipe as the illustrative eccentric wellbore tools, while the **Figure 9** series uses packers as the illustrative concentric wellbore tools. However, it is understood that either of these series could show a blank pipe having a primary flow path and at least one secondary flow path.

Further, it is understood that the packers may have an eccentric design, and the sand control devices may have a concentric design. In any of these instances, what is needed is a crossover joint that places the primary flow paths in fluid communication and the secondary flow paths in fluid communication.

[0201] **Figures 10**A through **10C** provide cross-sectional views of a crossover joint **1000**. The crossover joint **1000** operates to fluidly connect a first wellbore tool to a second wellbore tool. In **Figure 10A**, a side view of the crossover joint **1000** is shown. It can be seen that the crossover joint **1000** defines an elongated tubular body. The crossover joint **1000** has a wall **1010**. The wall **1010** defines a bore **1005** therein. The bore **1005** serves as a curved primary flow path.

[0202] The wall **1010** has a first end **1012**, and a second opposite end **1014**. The bore **1005** runs the length of the crossover joint **1000** from the first end **1012** to the second end **1014**. The crossover joint **1000** also has at least one secondary flow path **1020**. The secondary flow path **1020** runs through the body **1010** of the crossover joint **1000**, and also runs from the first end **1012** to the second end **1014**.

[0203] **Figure 10B** provides a first transverse cross-sectional view of the crossover joint **1000**. This view is taken across line **B-B** of **Figure 10A**. Line **B-B** is placed at the first end **1012** of the crossover joint **1000**, which is a pin end. It can be seen from the view of **Figure 10B** that the bore **1005** of the crossover joint **1000** is eccentric relative to the joint **1000** at the first end **1012**. An extending connection member **1030** may be provided for fluidly connecting the secondary flow path **1020** to alternate flow channels in a sand screen or other adjacent wellbore tool.

[0204] **Figure 10C** provides a second transverse cross-sectional view of the crossover joint **1000**. This view is taken across line **C-C** of **Figure 10A**. Line **C-C** is cut through the second end **1014** of the crossover joint **1000**, which is a box end in **Figure 10A**, although it could be a pin end as well. It can be seen from the view of **Figure 10C** that the bore **1005** of the crossover joint **1000** is concentric relative to the joint **1000** at the second end **1014**.

[0205] In the arrangement of **Figures 10A** and **10B**, the first end **1012** of the crossover joint **1000** is designed to threadedly connect to or to provide fluid communication with a wellbore tool that is eccentric. Such a wellbore tool may have the profile of, for example, the sand control device **800A** of **Figure 8A**. Thus, the first end **1012** has an eccentric secondary flow path **1020** that aligns with pass-through rectangular ports (such as eccentric shunt tubes **830A**, **832A** of **Figure 8A**) in the sand screen.

[0206] Reciprocally, in the arrangement of **Figures 10A** and **10C**, the second end **1014** of the crossover joint **1000** is designed to threadedly connect to or to provide fluid communication with a wellbore tool that is concentric. Such a wellbore tool may have the profile of, for example, the packer **900C** of **Figure 9C**. Thus, the second end **1014** provides a concentric primary flow path **1005** that is connected to a packer, and a secondary flow path **1020** that connects to circular ports (such as shunt tubes **930C** of **Figure 9C)** in the packer.

[0207] It is noted that the eccentric wellbore tool may connect to the first end **1012** of the crossover joint **1000** either directly through a threaded connection, or indirectly through the use of a manifolding joint. Similarly, the concentric wellbore tool may connect to the second end **1014** of the crossover joint **1000** either directly through a threaded connection, or indirectly through the use of a coupling and a torque sleeve or a load sleeve. Examples of a coupling and a torque sleeve or a load sleeve are provided in U.S. Patent No. 7,661,476 and U.S. Patent No. 7,938,184.

[0208] It is further noted that either the eccentric wellbore tool or the concentric wellbore tool may be a sand screen, a packer, or a blank pipe. What is required is that each wellbore tool have a primary flow path and at least one secondary flow path, wherein a radial center of the primary flow path in the first wellbore tool is offset from a radial center of the primary flow path in the second wellbore tool.

[0209] The crossover joint **1000** itself also has a primary flow path **1005** and secondary flow path **1020**. The secondary flow path **1020** is also curved. Preferably, the secondary flow path **1020** comprises a plurality of shunt tubes or a shunt annulus for carrying a gravel slurry. However, the secondary flow path **1020** may be of any profile.

[0210] In the arrangement of **Figure 10B**, the secondary flow path **1030** is designed to fluidly communicate at the first end **1012** with the polygonal packing tubes **830A** and transport tubes **832A** of **Figure 8A**. Similarly, in the arrangement of **Figure 10C**, the secondary flow path **1020** is designed to fluidly communicate at the second end **1014** with the shunt tubes **930C** of **Figure 9C**. However, other fluid communication profiles may be employed at either the first end **1012** or the second end **1014**.

[0211] As seen in the arrangement of **Figure 10A**, the crossover joint **1000** may contain at least one inflection point along its length, providing for an “S” contour. The “S” contour compensates for the axis offset from the eccentric flow paths to the concentric flow paths. A continuous profile or contour with minimal curvature (or “dog leg”) can ease downhole tool pass-through, reduce torque and drag, minimize erosion by particle flow, and minimize flow

friction. A typical mathematical description of an "S" contour is a sigmoid function. Examples of sigmoid functions include, without limitation, hyperbolic tangent functions, inverse tangent functions, logistic functions, Rosin-Rammler functions, and error functions. Although the transit in the crossover joint **1000** can be as simple as a series of straight segments (without inflection point), a discontinuous profile at the turning point may pose a high local curvature.

[0212] **Figure 11A** is a Cartesian graph **1100A** charting axis offset (first *y*-axis) against symmetric length of an illustrative crossover joint (*x*-axis). This is for a 16-foot crossover joint. The crossover joint illustrated in the graph **1100A** of **Figure 11A** has a profile for a 0.54-inch axis-offset between concentric and eccentric wellbore tools. Axis offset is indicative of curvature. Thus, line **1110A** demonstrates a crossover profile and shows how the center of the bore of a crossover joint moves relative to a longitudinal center line of the tool. As can be seen, a curved or "S" profile is offered.

[0213] **Figure 11A** also charts curvature (second *y*-axis) against symmetric length (*x*-axis) for the 16-foot crossover joint. Curvature is indicative of how sharply the bore of the crossover joint turns at any given location along the center of the bore. Stated mathematically, curvature is related to derivatives of the profile as it reflects rate of change of direction along the profile **1110A**. This rate of change of direction is shown at line **1120A**. It is noted that at the 0-inches mark along the *x*-axis, the bore has an inflection point.

[0214] The curvature **1120A**, or profile, is based on a hyperbolic tangent function. The curvature **1120A** is represented by a common unit in the oil field -- degree per 100 feet. The example in **Figure 11A** indicates a maximum of 9°/100 ft curvature along the 192-inch (16 feet) crossover length. The curvature **1120A** is zero at the middle of the crossover, or the inflection point.

[0215] The crossover length can be reduced by half, to 96 inches. This is shown in **Figure 11B**.

[0216] **Figure 11B** is a Cartesian graph **1100B** charting axis offset (first *y*-axis) against symmetric length of another illustrative crossover joint (*x*-axis). This is for an 8-foot crossover joint. Line **1110B** demonstrates a crossover profile for the 96-inch joint, showing how the center of the bore of the crossover joint moves relative to a longitudinal center line of the tool. As can be seen, a curved profile is again offered.

[0217] **Figure 11B** also charts curvature (second *y*-axis) against symmetric length of a crossover joint (*x*-axis) for the 8-foot crossover joint. Line **1120B** demonstrates curvature of the bore of the crossover joint. Here, the maximum curvature is quadrupled to 36°/100 ft.

[0218] As noted above, a series of straight segments may be used in lieu of a curved profile. When a simplified geometry like straight segments is used, the crossover length may be further reduced, but the curvature at the turning (discontinuous) point(s) becomes high. Thus, the crossover design must be balanced between the length and the curvature.

[0219] **Figure 11C** is a Cartesian graph **1100C** charting axis offset (*y*-axis) against symmetric length of a crossover joint (*x*-axis). This is also for an 8-foot crossover joint. Here, the graph **1100C** compares how the center of the bore of a crossover joint moves relative to a longitudinal center line of the tool for two different bore profiles. Line **1110B** is the same line as **1110B** from **Figure 11B**. This, again, was for a curved profile. Line **1115** is provided to show a profile having straight segments.

[0220] The axis-offset and curvature of a crossover joint **1000** are important considerations. The primary flow path of the crossover joint **1000** should be able to accommodate movement of a tool such as the setting tool **750** of **Figure 7C** through the bore **1005**. It can be seen that the curvature range shown at line **1120A** in **Figure 11A** has a smaller range than the curvature range shown at line **1120B** in **Figure 11B**. This is to be expected as the crossover joint of **Figure 11A** has twice the length of the crossover joint of **Figure 11B**, thereby reducing the "rate of change of direction" for the curvature.

[0221] Another way to mitigate the curvature impact on the primary flow path is to increase the internal diameter of the crossover joint. The increased diameter eases the run of other downhole tools through the curved crossover joint.

[0222] When using a crossover joint, other design options may be considered. For example, when the secondary flow paths serve as alternate flow channels for gravel packing, a high differential pressure can occur between the secondary flow paths and the primary flow path. Additionally, a high differential pressure may occur between the secondary flow paths and the annulus between the crossover joint and the surrounding wellbore, that is, the wellbore annulus. For example, a 6,500 psi differential pressure is expected near the heel of when gravel packing a 5,000-foot horizontal completion interval. In order to maintain the mechanical integrity (that is, to stay within the burst, bending, and collapse ratings) of the secondary flow paths, a certain surrounding wall thickness is required. This, in turn, limits the inside diameter of the crossover joint.

[0223] Other considerations include minimizing length, providing an overall outer diameter that is less than or equal to the diameters of the adjacent wellbore tools, maximizing inner diameter of the primary flow path, and providing an overall mechanical integrity that is equal to or greater than that of the adjacent tools.

[0224] **Figure 12** is a flow chart showing steps for a method **1200** for completing a wellbore in a subsurface formation, in one embodiment. The method **1200** is applicable for the installation of wellbore tools having flow paths that do not align.

[0225] In one aspect, the method **1200** first comprises providing a first wellbore tool. This is shown at Box **1210**. The first wellbore tool has a primary flow path and at least one secondary flow path. The first wellbore tool may be a sand screen, a packer, or a blank pipe.

[0226] The method **1200** also includes providing a second wellbore tool. This is indicated at Box **1220**. The second wellbore tool also has a primary flow path and at least one secondary flow path. The second wellbore tool may be a sand screen, a packer, or a blank pipe. However, a radial center of the primary flow path of the first wellbore tool is offset from a radial center of the primary flow path for the second wellbore tool.

[0227] The method **1200** also includes providing a crossover joint. This is shown at Box **1230**. The crossover joint also comprises a primary flow path and at least one secondary flow path. The method **1200** then includes fluidly connecting the crossover joint to the first wellbore tool at a first end, and fluidly connecting the crossover joint to the second wellbore tool at a second end. These steps are provided at Boxes **1240** and **1250**, respectively. In this manner, the primary flow path of the first wellbore tool is in fluid communication with the primary flow path of the second wellbore tool. Further, the at least one secondary flow path of the first wellbore tool is in fluid communication with the at least one secondary flow path of the second wellbore tool.

[0228] The method **1200** further includes running the crossover joint and connected first and second wellbore tools into a wellbore. This is seen at Box **1260**. The crossover joint is run to a selected subsurface location within the wellbore. Fluid is then injected into the wellbore. This is shown at Box **1270**.

[0229] The method **1200** then includes further injecting the fluid from the wellbore and through the secondary flow paths of the first wellbore tool, the crossover joint, and the secondary flow paths for the second wellbore tool. This is provided at Box **1280**.

[0230] The crossover joint may be used to connect any two tubular tools having primary flow paths and secondary flow paths, wherein a radial center of the primary flow path in the first wellbore tool is offset from a radial center of the primary flow path in the second wellbore tool. However, it is preferred that the crossover joint be used as part of a sand control system. In this instance, the first wellbore tool is preferably a sand screen, while the second wellbore tool is preferably a mechanically-set packer, such as packer **600** of **Figures 6A** and **6B**.

[0231] In one embodiment, the primary flow path of the first wellbore tool (such as a sand screen) is eccentric to the first wellbore tool, while the primary flow path of the second wellbore tool (such as a packer) is concentric to the second wellbore tool. In this instance, a base pipe serves as the primary flow path of the sand screen, while an elongated inner mandrel serves as the primary flow path of the packer. The secondary flow path for the sand screen is made up of shunt tubes which serve as alternate flow channels. The secondary flow path for the packer may be shunt tubes or may be an annular area formed between the inner mandrel and a surrounding moveable piston housing. In any instance, the alternate flow channels allow a gravel slurry to bypass the sand screen joint, the crossover joint, and the packer, even after the packer has been set in the wellbore.

[0232] In one aspect, the method **1200** further comprises setting the packer in the wellbore. In this instance, the step of further injecting the fluid through the secondary flow paths is done after the packer has been set.

[0233] **Figure 13** is a flow chart that shows steps for a method **1300** of setting a packer in a wellbore, in one embodiment. The packer is designed in accordance with the packer **600** of **Figures 6A** and **6B**. The method **1300** first includes running a setting tool into the inner mandrel of the packer. This is shown in Box **1310**.

[0234] The setting tool is advanced beyond the depth of the packer. The method **1300** then includes pulling the setting to back up the wellbore. This is seen at Box **1320**. The setting tool has a collet fingers or other raised surfaces that catch on a release sleeve. As the setting tool is pulled up the wellbore, the collet fingers latch into a release sleeve. Pulling the setting tool mechanically shifts the release sleeve from a retained position along the inner mandrel of the packer. This, in turn, releases a piston housing in the packer for axial movement.

[0235] The method **1300** then includes communicating hydrostatic pressure to the piston housing. This is provided at Box **1330**. Communication of hydrostatic pressure is conducted through one or more flow ports. The flow ports are exposed to wellbore fluids when the

release sleeve is translated. The piston housing has a pressure-bearing surface that is acted on by the hydrostatic pressure. This causes axial movement of the released piston housing, and in turn actuates the sealing element against the surrounding wellbore.

[0236] The preferred embodiment for using a crossover joint offers the following tool sequence:

eccentric screen → crossover tool → concentric packer

[0237] A variation of this sequence is as follows:

eccentric screen → crossover tool → concentric packer → crossover tool → eccentric screen

[0238] However, the order of tool connections is not confined to using an eccentric sand screen and a concentric packer. If a concentric packer is not available, the operator may choose to use the following tool sequence:

concentric screen → crossover tool → eccentric packer → crossover tool → concentric screen

Thus, the crossover joint allows a change in the orientation of the base pipes and the eccentric shunt tubes along a series of sand screens. In this case, two crossover joints are needed. The first crossover joint preferably has a concentric box end and an eccentric pin end. The second crossover joint preferably has an eccentric box end and a concentric pin end.

A certain type of packer may actually be desirable in some circumstances. If, for example, a particular type of packer allows a higher hydrostatic pressure or higher pressure ratings in shunt flow paths, then that packer may be selected.

[0239] Another tool sequence for use with a crossover joint is:

concentric screen → crossover tool → eccentric screen

[0240] The use of concentric screens may be beneficial when gravel packing long intervals. Concentric sand screens can be more robust for gravel packing long intervals. For example, known concentric screens are capable of gravel packing 5,000 feet, compared to 3,000 feet with the commercial eccentric screens. The new crossover tool allows the operator to use the less-expensive eccentric screens on the toe or lower-pressure side of the interval during gravel-packing operations, and to use the concentric screens on the heel or

higher-pressure side of the interval during the gravel-packing operations. This reduces the overall cost of completion while still achieving the gravel packing goal.

[0241] It may be difficult to acquire more complex concentric sand screens in quantities needed for extended horizontal completions. Therefore, the crossover joint allows a horizontal completion to continue without delay by combining concentric screens with the more readily available eccentric screens. Thus, the use of crossover joints provides flexibility in maintaining and managing the inventory of sand screens.

[0242] The crossover joint also provides the operator flexibility in using the best screens for a particular interval, or the best performing packer for zonal isolation. The operator is not constrained by matching the flow paths of screens with packers, and may take advantage of the best wellbore tools available for the job.

[0243] The crossover joint also allows the operator to be creative with the use of blank pipes. For example, the crossover joint permits the use of concentric round shunt tubes on blank pipe joints above the eccentric screens in multi-zone frac pack applications. The concentric round shunt tubes allow for higher fluid injection pressures. The crossover joint enables fluid connectivity between and eccentric sand screen joint and the concentric blank pipe.

[0244] As can be seen, a wellbore apparatus is provided herein. The wellbore apparatus may generally be claimed as in the following sub-paragraphs:

1. A wellbore apparatus comprising:

a first wellbore tool having a primary flow path and at least one secondary flow path;

a second wellbore tool also having a primary flow path and at least one secondary flow path, wherein a radial center of the primary flow path in the first wellbore tool is offset from a radial center of the primary flow path in the second wellbore tool; and

a crossover joint for connecting the first wellbore tool to the second wellbore tool, the crossover joint comprising:

a primary flow path fluidly connecting the primary flow path of the first wellbore tool to the primary flow path of the second wellbore tool; and

at least one secondary flow path fluidly connecting the at least one secondary flow path of the first wellbore tool to the at least one secondary flow path of the second wellbore tool.

2. The wellbore apparatus of sub-paragraph 1 wherein:

the primary flow path in the crossover joint is eccentric to the crossover joint at a first end; and

the primary flow path in the crossover joint is concentric to the crossover joint at a second opposite end.

3. The wellbore apparatus of sub-paragraph 2, wherein the primary flow path in the crossover joint has a profile of a sigmoid function.

4. The wellbore apparatus of sub-paragraph 2, wherein the primary flow path in the crossover joint comprises at least two linear segments.

5. The wellbore apparatus of sub-paragraph 1 or sub-paragraph 2, wherein:

the wellbore apparatus is a sand control device;

the first wellbore tool is a sand screen that comprises an elongated base pipe, a filtering medium circumferentially around the base pipe, and at least one shunt tube along the base pipe serving as an alternate flow channel, the at least one shunt tube being configured to allow gravel slurry to at least partially bypass the first wellbore tool during a gravel-packing operation in a wellbore;

the base pipe serves as the primary flow path of the sand screen; and

the at least one shunt tube serves as the at least one secondary flow path of the sand screen.

6. The wellbore apparatus of sub-paragraph 5, wherein:

the at least one shunt tube is internal to the filtering medium, or is external to the filtering medium.

7. The wellbore apparatus of sub-paragraph 6, wherein:

each of the at least one shunt tube has a round profile, a square profile, or a rectangular profile; and

the elongated base pipe is eccentric to the sand screen.

8. The wellbore apparatus of sub-paragraph 7, wherein the first wellbore tool further comprises a perforated outer protective shroud around the at least one shunt tube.

9. The wellbore apparatus of sub-paragraph 1 or sub-paragraph 2, wherein:

the second wellbore tool is a packer, the packer comprising an elongated inner mandrel, a sealing element external to the inner mandrel, and an annular region serving as an alternate flow channel, the annular region being configured to allow gravel slurry to at least partially bypass the second wellbore tool during a gravel-packing operation in a wellbore after the packer has been set in the wellbore;

the inner mandrel serves as the primary flow path of the packer; and

the annular region serves as the at least one secondary flow path of the packer.

10. The wellbore apparatus of sub-paragraph 9, wherein the inner mandrel is concentric to the packer.

11. The wellbore apparatus of sub-paragraph 9, wherein the primary flow path has a profile of a sigmoid function.

12. The wellbore apparatus of sub-paragraph 1 or sub-paragraph 2, wherein:

the first wellbore tool is a blank pipe that comprises an elongated base pipe and at least one shunt tube along the base pipe serving as an alternate flow channel, the at least one shunt tube being configured to allow gravel slurry to at least partially bypass the first wellbore tool during a gravel-packing operation in a wellbore;

the base pipe serves as the primary flow path of the blank pipe; and

the at least one shunt tube serves as the at least one secondary flow path of the blank pipe.

13. The wellbore apparatus of sub-paragraph 5, wherein:

the second wellbore tool is a packer, the packer comprising an elongated inner mandrel, a sealing element external to the inner mandrel, and an annular region serving as an alternate flow channel, the annular region being configured to allow gravel slurry to at least partially bypass the second wellbore tool during a gravel-packing operation in a wellbore after the packer has been set in the wellbore;

the inner mandrel serves as the primary flow path of the packer; and

the annular region serves as the at least one secondary flow path of the packer.

14. The wellbore apparatus of sub-paragraph 13, wherein:

the elongated base pipe of the sand screen is eccentric to the sand screen; and

the inner mandrel of the packer is concentric to the packer.

15. The wellbore apparatus of sub-paragraph 5, wherein:

the second wellbore tool is also a sand screen that comprises an elongated base pipe, a filtering medium circumferentially around the base pipe, and at least one shunt tube along the base pipe serving as an alternate flow channel, the at least one shunt tube being configured to allow gravel slurry to at least partially bypass the second wellbore tool during a gravel-packing operation in a wellbore;

the elongated base pipe of the sand screen representing the first wellbore tool is concentric to the sand screen; and

the elongated base pipe of the sand screen representing the second wellbore tool is eccentric to the sand screen.

[0245] While it will be apparent that the inventions herein described are well calculated to achieve the benefits and advantages set forth above, it will be appreciated that the inventions are susceptible to modification, variation and change without departing from the spirit thereof. Improved methods for completing an open-hole wellbore are provided, which use a crossover tool for fluidly connecting an eccentric flow path to a concentric flow path.

CLAIMS

What is claimed is:

1. A crossover joint for connecting a first wellbore tool to a second wellbore tool, the first wellbore tool having a primary flow path and at least one secondary flow path, and the second wellbore tool having a primary flow path and at least one secondary flow path, wherein a radial center of the primary flow path in the first wellbore tool is offset from a radial center of the primary flow path in the second wellbore tool, the crossover joint comprising:

a primary flow path configured to fluidly connect the primary flow path of the first wellbore tool to the primary flow path of the second wellbore tool; and

at least one secondary flow path configured to fluidly connect the at least one secondary flow path of the first wellbore tool to the at least one secondary flow path of the second wellbore tool.

2. The crossover joint of claim 1, wherein:

the primary flow path in the crossover joint is eccentric to the crossover joint at a first end; and

the primary flow path in the crossover joint is concentric to the crossover joint at a second end.

3. The crossover joint of claim 2, wherein the primary flow path in the crossover joint has a profile of a sigmoid function.

4. The crossover joint of claim 2, wherein the primary flow path in the crossover joint changes direction along a longitudinal axis of the crossover joint at least once.

5. The crossover joint of claim 4, wherein the primary flow path in the crossover joint comprises at least two linear segments.

6. The crossover joint of claim 4, wherein the at least one secondary flow path of the crossover joint changes direction along a longitudinal axis of the crossover joint at least once.

7. A wellbore apparatus comprising:

a first wellbore tool having a primary flow path and at least one secondary flow path;

a second wellbore tool also having a primary flow path and at least one secondary flow path, wherein a radial center of the primary flow path in the first wellbore tool is offset from a radial center of the primary flow path in the second wellbore tool; and

a crossover joint for connecting the first wellbore tool to the second wellbore tool, the crossover joint comprising:

a primary flow path fluidly connecting the primary flow path of the first wellbore tool to the primary flow path of the second wellbore tool; and

at least one secondary flow path fluidly connecting the at least one secondary flow path of the first wellbore tool to the at least one secondary flow path of the second wellbore tool.

8. The wellbore apparatus of claim 7, wherein:

the primary flow path in the crossover joint is eccentric to the crossover joint at a first end; and

the primary flow path in the crossover joint is concentric to the crossover joint at a second end.

9. The wellbore apparatus of claim 8, wherein the primary flow path in the crossover joint has a profile of a sigmoid function.

10. The wellbore apparatus of claim 8, wherein the primary flow path in the crossover joint changes direction along a longitudinal axis of the crossover joint at least once.

11. The wellbore apparatus of claim 10, wherein the primary flow path in the crossover joint comprises at least two linear segments.

12. The wellbore apparatus of claim 10, wherein the at least one secondary flow path of the crossover joint changes direction along a longitudinal axis of the crossover joint at least once.

13. The wellbore apparatus of claim 8, wherein the primary flow path of the first wellbore tool is eccentric to the first wellbore tool.

14. The wellbore apparatus of claim 8, wherein the primary flow path of the second wellbore tool is concentric to the second wellbore tool.

15. The wellbore apparatus of claim 8, wherein the at least one secondary flow path of the first wellbore tool is eccentric to the first wellbore tool.

16. The wellbore apparatus of claim 7, wherein:

the wellbore apparatus is a sand control device;

the first wellbore tool is a sand screen that comprises an elongated base pipe, a filtering medium circumferentially around the base pipe, and at least one shunt tube along the base pipe serving as an alternate flow channel, the at least one shunt tube being configured to allow gravel slurry to at least partially bypass the first wellbore tool during a gravel-packing operation in a wellbore;

the base pipe serves as the primary flow path of the sand screen; and

the at least one shunt tube serves as the at least one secondary flow path of the sand screen.

17. The wellbore apparatus of claim 16, wherein:

the at least one shunt tube is internal to the filtering medium.

18. The wellbore apparatus of claim 16, wherein:

the at least one shunt tube is external to the filtering medium.

19. The wellbore apparatus of claim 18, wherein:

each of the at least one shunt tube has a round profile, a square profile, or a rectangular profile; and

the elongated base pipe is eccentric to the sand screen.

20. The wellbore apparatus of claim 19, wherein the first wellbore tool further comprises a perforated outer protective shroud around the at least one shunt tube.

21. The wellbore apparatus of claim 7, wherein:

the second wellbore tool is a packer, the packer comprising an elongated inner mandrel, a sealing element external to the inner mandrel, and an annular region serving as an alternate flow channel, the annular region being configured to allow gravel slurry to at least partially bypass the second wellbore tool during a gravel-packing operation in a wellbore after the packer has been set in the wellbore;

the inner mandrel serves as the primary flow path of the packer; and

the annular region serves as the at least one secondary flow path of the packer.

22. The wellbore apparatus of claim 21, wherein the inner mandrel is concentric to the packer.

23. The wellbore apparatus of claim 22, wherein the second end of the crossover joint is connected to the packer by means of:

a load sleeve external to the primary flow path at or near a first end, with at least one bored channel through and fluidly connected to the at least one secondary flow path; or

a torque sleeve external to the primary flow path at near a second opposite end with at least one bored channel through and fluidly connected to the at least one secondary flow path.

24. The wellbore apparatus of claim 21, wherein the annular region is eccentric to the packer.

25. The wellbore apparatus of claim 8, wherein the primary flow path has a profile of a sigmoid function.

26. The wellbore apparatus of claim 8, wherein an inner diameter of the primary flow path of the crossover joint is greater than an inner diameter of (i) the primary flow path of the first wellbore tool, (ii) the primary flow path of the second wellbore tool, or (iii) both.

27. The wellbore apparatus of claim 7, wherein:

the first wellbore tool is a blank pipe that comprises an elongated base pipe and at least one shunt tube along the base pipe serving as an alternate flow channel, the at least one shunt tube being configured to allow gravel slurry to at least partially bypass the first wellbore tool during a gravel-packing operation in a wellbore;

the base pipe serves as the primary flow path of the blank pipe; and

the at least one shunt tube serves as the at least one secondary flow path of the blank pipe.

28. The wellbore apparatus of claim 21, wherein the packer further comprises:

a release sleeve along an inner surface of the inner mandrel, the packer being configured so that shifting the release sleeve shears at least one shear pin along the inner mandrel;

a movable piston housing retained around the inner mandrel, with the annular region being formed between the inner mandrel and the surrounding piston housing; and

one or more flow ports providing fluid communication between the annular region and a pressure-bearing surface of the piston housing after the release sleeve has been shifted.

29. The wellbore apparatus of claim 21, wherein the sealing element of the packer is an elastomeric cup-type element.

30. The wellbore apparatus of claim 16, wherein:

the second wellbore tool is a packer, the packer comprising an elongated inner mandrel, a sealing element external to the inner mandrel, and an annular region serving as an alternate flow channel, the annular region being configured to allow gravel slurry to at least partially bypass the second wellbore tool during a gravel-packing operation in a wellbore after the packer has been set in the wellbore;

the inner mandrel serves as the primary flow path of the packer; and

the annular region serves as the at least one secondary flow path of the packer.

31. The wellbore apparatus of claim 30, wherein:

the elongated base pipe of the sand screen is eccentric to the sand screen; and

the inner mandrel of the packer is concentric to the packer.

32. The wellbore apparatus of claim 30, wherein:

the elongated base pipe of the sand screen is concentric to the sand screen; and

the inner mandrel of the packer is eccentric to the packer.

33. The wellbore apparatus of claim 16, wherein:

the second wellbore tool is also a sand screen that comprises an elongated base pipe, a filtering medium circumferentially around the base pipe, and at least one shunt tube along the base pipe serving as an alternate flow channel, the at least one shunt tube being configured to allow gravel slurry to at least partially bypass the second wellbore tool during a gravel-packing operation in a wellbore;

the elongated base pipe of the sand screen representing the first wellbore tool is concentric to the sand screen; and

the elongated base pipe of the sand screen representing the second wellbore tool is eccentric to the sand screen.

34. A method for completing a wellbore in a subsurface formation, the method comprising:

providing a first wellbore tool, the first wellbore tool having a primary flow path and at least one secondary flow path;

providing a second wellbore tool also comprising a primary flow path and at least one secondary flow path, wherein a radial center of the primary flow path in the first wellbore tool is offset from a radial center of the primary flow path in the second wellbore tool; and

providing a crossover joint, the crossover joint also comprising a primary flow path and at least one secondary flow path;

fluidly connecting the crossover joint to the first wellbore tool at a first end, and fluidly connecting the crossover joint to the second wellbore tool at a second end, such that the primary flow path of the first wellbore tool is in fluid communication with the primary flow path of the second wellbore tool, and the at least one secondary flow path of the first wellbore tool is in fluid communication with the at least one secondary flow path of the second wellbore tool;

running the crossover joint and connected first and second wellbore tools into a wellbore to a selected subsurface location, and thereby forming an annulus in the wellbore between the crossover joint and the surrounding wellbore;

injecting a fluid into the wellbore; and

further injecting the fluid from the wellbore and into the secondary flow paths of the first wellbore tool, the crossover joint, and the secondary flow paths of the second wellbore tool.

35. The method of claim 34, wherein:

the fluid is a gravel slurry for forming a gravel pack;

the first wellbore tool is a sand screen that comprises an elongated base pipe, a filtering medium circumferentially around the base pipe, and at least one shunt tube along the base pipe serving as an alternate flow channel, the at least one shunt tube being configured to allow gravel slurry to at least partially bypass the first wellbore tool during a gravel-packing operation in a wellbore;

the base pipe serves as the primary flow path of the sand screen; and

the at least one shunt tube serves as the at least one secondary flow path of the sand screen.

36. The method of claim 35, wherein the base pipe of the sand screen is eccentric to the sand screen.

37. The method of claim 35, wherein the primary flow path of the second wellbore tool is concentric to the second wellbore tool.

38. The method of claim 35, wherein:

the at least one secondary flow path of the sand screen is eccentric to the sand screen.

39. The method of claim 35, wherein the at least one shunt tube is internal to the filtering medium.

40. The method of claim 35, wherein the at least one shunt tube is external to the filtering medium.

41. The method of claim 35, wherein:

each of the at least one shunt tube has a round profile, a square profile, or a rectangular profile; and

the elongated base pipe is eccentric to the sand screen.

42. The method of claim 35, wherein:

the second wellbore tool is a packer, the packer comprising an elongated inner mandrel, a sealing element external to the inner mandrel, and an annular region serving as an alternate flow channel, the annular region being configured to allow gravel slurry to at least partially bypass the second wellbore tool during a gravel-packing operation in a wellbore after the packer has been set in the wellbore;

the inner mandrel serves as the primary flow path of the packer; and

the annular region serves as the at least one secondary flow path of the packer.

43. The method of claim 42, further comprising:

setting the packer in the wellbore; and

wherein further injecting the fluid through the secondary flow paths is done after the packer has been set.

44. The method of claim 43, wherein the inner mandrel is concentric to the packer.

45. The method of claim 44, wherein:

injecting a fluid into the wellbore comprises injecting a gravel slurry as part of a gravel-packing operation; and

further injecting the fluid through the secondary flow paths comprises injecting the gravel slurry through the alternate flow channels to allow the gravel slurry to at least partially

bypass the sealing element so that the wellbore is gravel-packed below the packer after the packer has been set in the wellbore.

46. The method of claim 42, wherein the annular region is eccentric to the packer.

47. The method of claim 43, wherein setting the packer comprises:

running a setting tool into the inner mandrel of the packer;

pulling the setting tool to mechanically shift a release sleeve from a retained position along the inner mandrel of the packer, thereby releasing the piston housing for axial movement; and

communicating hydrostatic pressure to the piston housing through the one or more flow ports, thereby axially moving the released piston housing and actuating the sealing element against the surrounding wellbore.

48. The method of claim 47, wherein the packer further comprises:

a release sleeve along an inner surface of the inner mandrel, the packer being configured so that shifting the release sleeve shears at least one shear pin along the inner mandrel;

a movable piston housing retained around the inner mandrel, with the annular region being formed between the inner mandrel and the surrounding piston housing; and

one or more flow ports providing fluid communication between the annular region and a pressure-bearing surface of the piston housing after the release sleeve has been shifted.

49. The method of claim 48, wherein:

running the setting tool comprises running a washpipe into a bore within the inner mandrel of the packer, the washpipe having the setting tool thereon; and

releasing the movable piston housing from its retained position comprises pulling the washpipe with the setting tool along the inner mandrel, thereby shifting the release sleeve and shearing the at least one shear pin, and thereby releasing the piston housing for axial movement along the inner mandrel.

50. The method of claim 35, wherein during the injecting step, the at least one secondary flow path in the crossover joint has a fluid pressure that is higher than a fluid pressure in the primary flow path of the crossover joint.

51. The method of claim 34, wherein during the injecting step, the at least one secondary flow path in the crossover joint has a fluid pressure that is higher than a fluid pressure in the wellbore annulus.

52. The method of claim 34, wherein the at least one secondary flow path in the first wellbore tool is connected to the at least one secondary flow path in the crossover joint by means of a manifold.

53. The method of claim 34, wherein the wellbore is completed to have an open hole portion along the selected subsurface location.