

SHIELDED HEADER

Field of the Invention

5 The present invention relates to electrical connectors, and more particularly to modular connectors for connecting daughter printed wiring boards to mother printed wiring boards.

Background of the Invention

10 In the manufacture of computers and other electronic apparatus, daughter printed wiring boards (PWBs) are commonly connected to mother PWBs by means of modular electrical connectors, typically comprising a receptacle and a header. A daughter card (or PWB) electrically and mechanically connects to a receptacle, which in turn electrically and mechanically
15 connects to a mother card (or backplane).

Modular electrical connectors of the type mentioned above are used, for example, to connect a large number of signal wires to a PWB. Consequently, a connector is provided with a number of columns of contact holes with contact pins disposed
20 therein. An exemplary connector is an 8 x 12 connector which has 12 columns of 8 contact holes with contact pins disposed therein.

As miniaturization becomes more prevalent, the number of signal wires to be connected to a connector increases, but the
25 dimensions of the connector itself must not increase and preferably should even decrease. This results in an increasing number of signal and ground connections in the limited space of the connector. In high-frequency

applications, this results in the risk of cross talk in the signal connections.

Accordingly, to combat the risk of cross talk due to mutual EMI of the signal connections, electrical connectors are equipped with shielding to attempt to shield each signal from EMI from neighboring and nearby signals. This shielding can be a conventional mechanical shield or an electrical shield in the form of a ground line. With today's electrical connectors, however, the current state of shielding still leaves great risk for cross talk. It is, therefore, desirable to provide an electrical connector that has enhanced shielding capabilities, yet does not significantly reduce signal density.

Stripline configurations, i.e., arrangements in which conductors in parallel in a dielectric are interposed between ground planes, are known in the art. A need exists for a way to use such configurations to reduce cross.

Summary of the Invention

A header for interconnecting electrical components is provided. The header comprises at least one column of conductors interposed between ground planes, wherein the column of conductors comprises at least a first, second and third conductor. The first conductor is a ground line, the second and third conductors are signal lines, and the first conductor is electrically connected to one of the ground planes, wherein the second conductor is positioned in the column in interposed relation between said first and third conductor.

In alternate embodiments, the header for interconnecting electrical components comprises a plurality of rows and columns of signal lines, wherein at least one column comprises at least one ground line situated between two signal lines so that the ground line is coplanar with the signal lines.

A ground plane for providing at least one ground line throughout a header for interconnecting electrical components

12 JUL 2004

also is provided. The ground plane comprises at least one substantially vertically-oriented metal shield section for separating signal lines of adjacent columns and at least one substantially horizontally-oriented ground shield, through which a ground line that carries a ground current passes.

Brief Description of the Drawings

Figure 1 is a top view of a preferred embodiment of a header of the present invention.

Figure 2 is a schematic of a conventional column of eight signal lines from an 8 x 12 header.

Figure 3 is a schematic of a column of signal lines of the present invention for an 8 x 12 header.

Figure 4 is a cross-sectional side view of the header of Figure 1.

Figure 5 is an inverted rear view of the header of Figure 1.

Figures 6 and 7 are the two side isometric views of the ground plane of the present invention.

Detailed Description of the Preferred Embodiments

A header for connecting a receptacle to a mother printed wiring board (PWB) and having an improved shielding design is provided. A top view of a preferred embodiment of a header of the present invention is shown in Figure 1. This preferred header is an 8 x 12 header, having twelve columns of eight contact holes, in which are disposed contact pins, each of which can carry a signal. It will be understood that the terminology 8 x 12 is used even though the drawings show 9 rows of contacts since only 8 rows of contacts on the header mate with contacts on the receptacle while one row of contacts on the header is grounded to a metallic shield on the receptacle. Alternatively, the 8 rows may be any number of rows of preferably at least 5 rows. Also, the 12 columns may alternatively be any number of columns which is a multiple of 3.

12 JUL 2004

A schematic of a conventional column of signal lines from an 8 x 12 header is shown in Figure 2. The conventional column of Figure 2 has signal lines 14, and a vertically-oriented shield 16 separating the columns of signals from each other. This conventional design provides limited protection against cross talk between signal connections.

A schematic of a column of signal lines of the present invention is shown in Figure 3. From ground line 12, there are two signal lines generally A and B (generally at 14), followed by a ground line C, two more signal lines D and E, followed by a ground line F, and then two more signal lines G and H. In addition, there are substantially vertically-oriented-metal shields 18 adjacent the signal lines 14 and substantially horizontally-oriented metal shields surrounding the ground lines 12, C and F. This new design provides enhanced protection against cross talk between signal connections. Preferably, these differential pairs of signal lines 14 are used with high speed signals and are offset 180 degrees. As is known in the art, when differential pair signals are offset by 180 degrees, noise in one signal tends to be cancelled by the noise in the other signal. A further explanation of differential pairs is found at pages 267-268 and 319-320 of "High-Speed Digital Design," by Howard W. Johnson et al. (Prentice Hall, 1993), the contents of which are incorporated herein by reference.

Still referring to Figure 3, parallel shield sections 22 and 42 are positioned to opposed sides of the ground and signal line conductors. A tab 21 is also used to contact the shield 22 to ground spring 40 which is also in contact with shield section 42. It will be appreciated that the ground shield sections 22 and 42 will affect the electromagnetic field around each signal line 14 so as to reduce cross talk between adjacent signal lines 14. It will also be seen that the ground lines as at lines 12, C, F and 28 are electrically connected to the shield 22 which will have the effect of further affecting the electromagnetic fields surrounding the

12 JUL 2004

signal lines 14 so as to still further enhance cross talk reduction. The tab 44 further enhances grounding and cross talk reduction by allowing ground current from shield section 22 to be further distributed to ground spring 40 and thus other shield sections such as shield section 42.

Figure 4 shows a cross-sectional side view of the header of Figure 1. Shown in Figure 4, there is a column comprised of a ground line 12, which mates with a grounding shield (not shown) on the receptacle, signal lines A, B, D, E, G and H (generally at 14), and ground lines C and F, which mate with contacts on the receptacle. Figure 4 also shows the metal shield 20, which comprises shields sections 22 situated between the columns of signal contact pins 10 at the location of the signal lines 14. Slots 24 also are present between the metal shield sections 22 where the ground lines 12, C and F are located. Figure 4 also shows the plastic housing 30, comprising the three walls 32, 34 and 36. Figure 5 shows an inverted rear view of the header of Figure 1.

The metal shield 20 of the present invention, referred to as a ground plane 20, is shown in Figures 6 and 7 in the two side isometric views. Figures 6 and 7 depict the metal shield sections 22, the slots 24 between the shield sections 22, and ground shields 28, through which the signal contact pins 10 (or signal lines 10) that carry the ground lines 12, C and F pass. Preferably, a ground plane 20 is one member. For example, the ground plane 20 alternatively may be described as a metal shield plate having slots 24 and ground shields 28 perpendicularly attached to the plate just above the location of the slots 24.

The metal shield sections 22 are substantially rectangularly-shaped and are substantially vertically-oriented. The ground shields 28 are substantially rectangularly-shaped and are substantially horizontally-oriented. Preferably, the ground shields 28 are oriented at approximately 90 degrees to the metal shield sections 22. Each ground shield 28 has four rectangularly-shaped corner

12 JUL 2004

tabs 29 that are bent (or curved) upward so that the ground planes 20 can be situated around the signal contact pins 10 without causing damage to the pins 10. Preferably, the ground shields 28 attach to the pins 10.

5 The header of the present invention is also equipped with springs 40 which are situated on housing wall 32, as depicted in Figures 1, 4 and 5. These springs 40 have a mechanical function and a grounding function. The springs 40 mechanically receive the connecting receptacle, to which the
10 daughter card connects. The springs 40 also provide an electrical link to the grounding signals 12 of each ground plane 20 by abutting each ground plane 20. As shown in Figure 6 and 7, each ground plane 20 has a connecting tab 21 which, by way of each tab's distal end 41, electrically connects each
15 ground plane 20 to the series of springs 40. In the embodiment of Figure 1, this 8 x 12 header preferably has 6 springs, as shown in Figures 1 and 5.

 The header design of the present invention reduces cross talk between signal lines 14 by providing a 2:1 signal line 14
20 to ground line 12, C and F ratio. The header of the present invention also has a conventional footprint that allows it to be used as a header for conventional connectors. The slotted design of the ground shields also allows for more plastic to be present than otherwise be present without the slots 24, as
25 depicted in Figure 1. This strengthens the existing electrical insulation provided by the plastic, thereby further reducing the risk of cross talk. It will also be appreciated that the header of the present invention, by making use of ground planes, allows for the use of fewer ground connections
30 to the printed circuit board. Because fewer pins need to be used for grounding, more pins can be used as signal pins, thereby allowing for more signal density.

 It is to be understood that even though numerous
35 characteristics and advantages of the present invention have been set forth in the foregoing description, together with details of the structure and function of the invention, the

disclosure is illustrative only. Accordingly, changes may be made in detail, especially in matters of shape, size and arrangement of parts within the principles of the invention to the full extent indicated by the broad general meaning of the
5 terms in which the appended claims are expressed.

12 JUL 2004

Claims:

1. A header for interconnecting electrical components
5 comprising at least one column of conductors interposed between
ground planes, wherein said column of conductors comprises at
least a first, second and third conductor, wherein the first
conductor is a ground line, the second and third conductors are
signal lines, the first conductor is electrically connected to one
10 of said ground planes, and the second conductor is positioned in
said column in interposed relation between said first and third
conductor, wherein the column includes a fourth and fifth
conductor which are signal lines and said fourth conductor is
positioned adjacent the first conductor in opposed relation to the
15 second conductor and said fifth conductor is positioned in outward
adjacent relation to the fourth conductor.

2. The header of claim 1, wherein the second and third
conductors are differential pairs, the fourth and fifth conductors
20 are differential pairs and the first conductor is interposed
between said differential pairs.

3. A ground plane for providing at least one ground line
throughout a header for interconnecting electrical components, the
25 header having rows and columns of parallel lines, the ground plane
comprising:

at least one metal shield section for separating lines of
adjacent columns, said at least one metal shield section being
substantially coplanar with the lines; and
30 at least one ground shield, through which a ground line that
carries a ground current passes, said at least one ground shield
being substantially transverse to the lines and wherein the at
least one ground shield engages said ground line.

35 4. The ground plane of claim 3 comprising:
a plurality of metal shield sections;

12 JUL 2004

a plurality of open slots situated between the shield sections; and

a plurality of ground shields, the ground shields being situated substantially between the shield sections.

5

5. The ground plane of claim 4, wherein:

each shield section is substantially rectangularly-shaped; and

each ground shield is substantially rectangularly-shaped.

10

6. The ground plane of claim 4 further comprising a connecting tab extending from an end of the ground plane and having a distal end for electrically connecting the ground plane to a series of springs.

15

7. The ground plane of claim 4, wherein:

each ground shield has shield tabs that project upward so that the ground planes can be situated around the ground lines without causing damage to the lines.

20

8. The ground plane of claim 7, wherein there are four tabs that are rectangular-shaped, each shield tab being situated at approximately each corner of the ground shield.

25

9. A header for interconnecting electrical components, the header comprising:

a plurality of rows and columns of signal lines, wherein at least one column comprises at least one ground line situated between two signal lines in the at least one column so that the at least one ground line is coplanar with the signal lines; and

30

at least one ground plane for providing grounding throughout the header situated between adjacent columns of signal lines, wherein the at least one ground plane engages the at least one ground line.

35

10. The header of claim 9, wherein there are at least two

12 JUL 2004

ground lines in the at least one column and there are two signal lines situated between the ground lines.

11. The header of claim 9 having a number of rows which is
5 at least 5 and a number of columns which is a multiple of 3, the header having signal lines and ground lines, wherein in each column, is a repeating pattern of two signal lines followed by a ground line.

10 12. The header of claim 11, wherein the signal lines are parallel and the header comprises 12 ground planes for providing grounding throughout the header, each ground plane situated adjacent a column of signal lines and comprising:

metal shield sections for separating lines of adjacent
15 columns, said at least one metal shield section being substantially coplanar with the signal lines; and

ground shields, through which each ground line passes, said at least one ground shield being substantially transverse to the signal lines.

20

13. The header of claim 9, wherein the signal lines are parallel and the at least one ground plane comprises:

at least one metal shield section for separating lines of adjacent columns, said at least one metal shield section being
25 substantially coplanar with the signal lines; and

at least one ground shield, through which a ground line passes, said at least one ground shield being substantially transverse to the signal lines.

30 14. The header of claim 13 further comprising at least one housing wall, in which is situated at least one spring for mechanically connecting the header to an electrical connector and for providing an electrical link to the at least one ground line of each ground plane whereby the at least one spring abuts the at
35 least one ground plane.

15. The header of claim 14, wherein the at least one ground

12 JUL 2004

- 11 -

plane further comprises a connecting tab having a distal end so that the at least one spring abuts the distal end of the connecting tab.

5