



159159

Display unit with sound generation system

Field of the invention

The present invention relates generally to a display unit, such as a display unit provided in an automobile or in an item of consumer electronics such as a TV set, a computer or a mobile phone etc. In particular, it relates to a display unit
5 having a sound generation system. Such a unit is referred to herein as an audio-visual reproduction apparatus.

Background of the invention

A conventional audio-visual reproduction apparatus comprises a screen on
10 which images can be generated and cone-type electromagnetic speakers disposed on both lateral sides or above-and-below the screen. Unfortunately, such an arrangement results in non-collocation between the visual information on the screen and the generated sound.

15 It would be desirable to make the user feel as if the sound is being generated from the display screen, and some efforts have been made to try to achieve this. For example, US 5,400,414 discloses an electromechanical transducer made of a piezo-polymer film. This film is transparent and is applied to a television screen, glass pane of a framed picture, or the like. Although such
20 an arrangement achieves audio-visual integration, the generated sound can be heard both by a target user and by others. This is because the sound generation system is omni-directional. One way to overcome this problem would be to use earphones or headphones. However, it is not always comfortable to wear an earphone or a headphone for a long time. In addition,
25 it is not safe for certain persons, e.g., car drivers while driving, to wear an earphone or headphone.

000000



300000?

Summary of the invention

The present invention aims to provide a new and useful audio-visual reproduction apparatus.

5

The invention is motivated by the observation that, in contrast to the sound generation systems employed in conventional display units, another known type of sound generation system is a so-called "parametric speaker". A parametric speaker employs an ultrasonic transducer array (that is, an array
10 composed of a plurality of transducer elements). The array is capable, under the control of an applied electronic signal, of transmitting into air a narrow ultrasonic sound beam. The ultrasonic sound beam is AM modulated using an audio signal, by using the audio signal to modulate the electronic signals which drive the ultrasonic transducer array. The AM modulated ultrasonic
15 beam is spontaneously demodulated as the beam propagates through the air because of non-linear acoustic effects, so as to generate an audible sound corresponding to the input audio signal. Parametric speakers use this phenomenon to produce a sound spotlight that is audible only by people at the location of the sound spotlight.

20

In general terms, the present invention proposes an audio-visual reproduction apparatus which comprises a visual display screen, and an ultrasonic transducer array for generating an ultrasonic beam and comprising two or more elements located around the periphery of the display screen. At least a
25 portion of transducer array is empty or transparent, through which the display screen is visible. When a parametric control signal (an ultrasonic signal modulated by an audio-frequency signal) is applied to the transducer array, a directed ultrasonic beam is generated. Non-linear effects in the air

demodulate the audio-frequency signal to generate, in effect, an audio beam propagating perpendicular to the screen.

Such an integration of audio and vision may make the user feel as if the sound is being generated from the display screen when he or she is watching it, and also may project the sound towards a target user and seldom, or never, disturb unrelated persons.

The ultrasonic transducer array may be made up of independent transducer elements, or may comprise two or more sub-arrays of transducer elements (e.g. closely adjacent one another).

Identical parametric signals may be applied to the individual sub-arrays, e.g. via a common amplifier. Alternatively, different parametric signals may be applied to different sub-arrays, e.g. via individual respective amplifiers. The gain for each amplifier may be selected to be the same. Alternatively, the respective gains may be selected, for example, to steer the sound beam from one angle to another one.

One possibility is for there to be two sub-arrays, the two sub-arrays being arranged to receive control signals derived respectively from left and right stereo channels.

The transducer elements may be formed separately, and mounted in relation to the display screen (e.g. onto a casing of the display screen). Alternatively, the transducer elements may be integrated, e.g. embedded, in a casing of the display screen.

In a further possibility, the apparatus may comprise a body (e.g. on which the screen is mounted) and one or more other sections which are movable relative to the body (e.g. foldable, such as on hinges, and/or receivable into

openings in the body). Some or all of the transducer elements may be provided on the movable section(s) of the apparatus. For example, the movable sections of the apparatus may be flaps which can have a compact configuration and an extended ("popped-out") configuration. Alternatively or
5 additionally, the flaps may be movable between multiple configurations.

A first advantage of providing the movable sections of the apparatus is that the movable sections may be movable between a "popped-out" configuration in which the transducer elements on the movable sections of the apparatus
10 are located to provide relatively high quality sound reproduction to a user, and a more compact configuration in which the apparatus may be transported more conveniently.

A second advantage of providing the movable sections of the apparatus is
15 that the movable sections may be adjustable (e.g. when they are in the popped-out configuration), through a range of positions in which they generate sound to a user (e.g. positions in which they generally face a user who is looking at the screen), to a position in which the sound generation is optimised.

20 Preferably, there may be a plurality of movable sections (e.g. at respective sides of the screen). In this case they may be arranged symmetrically to either side of the body. Optionally, in this case they may be arranged to be movable only symmetrically.

25 Alternatively or additionally, there may be one or more movable sections arranged on a longitudinal axis of symmetry of the body.

The transducer elements of the array may take various forms. One possibility
30 is for each said transducer element to be a respective piezoelectric unimorph

or bimorph element having a cone-shaped impedance layer. Alternatively, the transducer array may comprise a membrane with control circuitry being attached to the membrane to permit it to be driven by a parametric control signal. For example, the membrane may be driven by piezoelectric material
5 located on the membrane and arranged to receive a parametric control signal. Alternatively, the membrane may be driven by electrostatic forces between first conductive material located on the membrane and second conductive material located off the membrane, the first and second conductive materials being arranged to receive a voltage difference determined by the parametric
10 control signal.

Certain embodiments of the invention are television receivers, the display screen of the apparatus being the screen of the television receiver.

15 In alternative embodiments of the invention, the audio-visual reproduction apparatus is provided in a vehicle, such as a car, bus or even airplane. The audio-vision reproduction apparatus may be arranged on the rear of a seat in the automobile. Alternatively, such an apparatus may be arranged beside the driver, serving as a personal navigation system. One possibility is for the role
20 of the display screen in the audio-visual reproduction apparatus to be played by a mirror of the vehicle, such as the rear mirror, and for the transducer array to be arranged to generate audible sound to be heard by the driver only.

Further embodiments of the invention are the display units of computers, such
25 as laptop or desktop computers. The display unit may comprise the display screen and a rectangular transparent panel forming a protective cover resiliently mounted on the display unit along the periphery of the display unit by means of a resilient suspension. The ultrasonic transducer elements may then be mounted on, or integrated into, the periphery of the protective cover.

In a further possibility, the apparatus may be any other portable item of consumer electronics, e.g., a mobile radio telephone or cell phone. Due to the relatively small size of many portable items of consumer electronics, this possibility is particularly suitable for combination with the concept described above, of providing some or all of the transducer elements on sections of the apparatus which are movable relative to a body of the apparatus, such as flaps which can moved between a compact configuration and a popped-out configuration.

Brief Description of The Figures

Preferred features of the invention will now be described, for the sake of illustration only, with reference to the following figures in which:

Fig. 1 shows a first embodiment of the invention which is a television receiver with a picture screen encircled by a ring of adjacent, spaced apart PZT unimorph or bimorph ultrasonic transducer elements;

Fig. 2 schematically indicates sound generation in the embodiment of Fig. 1;

Fig. 3 shows a second embodiment of the invention which is a television receiver having a picture screen and eight sub-arrays of transducer elements distributed around four edges of the screen;

Fig. 4 shows schematically how a parametric signal is applied to the individual sub-arrays of the embodiment of Fig. 3;

Fig. 5 shows experimental results of sound pressure level (SPL) versus position generated by the embodiment of Fig. 3;

Fig. 6 shows schematically the process for producing the experimental results of Fig. 5;

Fig. 7 illustrates schematically an embodiment of the invention which is a display unit located in an automobile.

Fig. 8 shows an embodiment of the invention which is a laptop/desktop computer;

Fig. 9 illustrates the generation of sound by a further embodiment of the invention;

5 Fig. 10, which is composed of Figs. 10(a) and 10(b), illustrate membrane-type ultrasonic transducer arrays suitable for use in embodiments of the invention;

Fig. 11 shows a further embodiment of the invention which is a mobile radio telephone or cell phone;

10 Fig. 12 shows a further embodiment of the invention which is a mobile telephone having a parametric speaker attached to the edges of a display screen;

Fig. 13, which is composed of Figs. 13(a) and 13(b), shows a mobile telephone which is a further embodiment of the invention;

15 Fig. 14, which is composed of Figs. 14(a) and 14(b), shows a mobile telephone which is a further embodiment of the invention;

Fig. 15, which is composed of Figs. 15(a) and 15(b), shows a mobile telephone which is a further embodiment of the invention;

20 Fig. 16, which is composed of Figs. 16(a) and 16(b), shows a mobile telephone which is a further embodiment of the invention; and

Fig. 17, which is composed of Figs. 17(a) and 17(b), shows a mobile telephone which is a further embodiment of the invention.

25 Detailed Description of the embodiments

Referring firstly to FIG. 1, a first embodiment of the invention is shown which is a television receiver 1 with a display screen 11 and control elements 12 (for

- example, buttons or other devices for inputting control signals). Around the display screen 11 are distributed PZT unimorph or bimorph ultrasonic transducer elements 13 adjacent to each other in at least one ring. The elements 13 can be considered as collectively forming an array of elements spanning a two-dimensional region (which may, for example, be defined exactly as the minimal two-dimensional convex hull containing all the elements 13). A portion of the array is empty and the display screen is visible through the empty portion.
- 10 The elements 13 may be integrated with the television receiver (e.g. permanently embedded in a housing of the television receiver). Alternatively, they may be attached removably to the housing around the edges of the screen. When a parametric signal is applied to the transducer array via an amplifier, the elements 13 generate directional primary (ultrasonic) waves in the air. Nonlinear interaction between the airborne ultrasonic waves results in directional secondary (audible) waves.

In spite of the central empty portion of the array, our experiments have shown that the demodulated sound pressure level (SPL) in the central is still stronger than in conventional display devices. By adjusting the dimensions of the array, or the density of its elements 13, the demodulated SPL in the main beam and display space can be made uniform. This is illustrated schematically in FIG. 2, which shows the sound field generated by the embodiment of Fig. 1. The curves 14 represent the regenerated audio waves (i.e. the demodulated ultrasonic waves), and at the location A they are close to being uniform. The main audible sound field is constrained within the range between the lines "a" and "b", meaning that a highly-directional sound beam is achievable. These results indicate that such an audio-vision reproduction apparatus may achieve the functions of (i) making the user feel as if the sound is being generated from the display screen when he/she is watching it, and (ii) projecting the

sound towards a target user and seldom (or never) disturbing unrelated persons.

Whereas in Fig. 1, the PZT unimorph/bimorph transducer elements are arranged adjacent to each other to form an array with an empty central portion, as shown in FIG. 1, an alternative second embodiment is shown in Fig. 3. Here, there are a total of 8 sub-arrays 15 (although the number of sub-arrays is limited to this number and there may be any number of sub-arrays, particularly any number greater than two). Each sub-array may contain ultrasonic transducer elements closely adjacent to each other, e.g. in the form of a honey-comb structure. The sub-arrays 15 are attached to four edges of a television receiver. The spacing of neighbouring elements within each sub-array is smaller than the spacing of the sub-arrays from each other.

Optionally, all the sub-arrays of the second embodiment may be fed the same parametric signal (that is, an ultrasonic signal modulated by an audio signal). In this case, the parametric signal may be transmitted by a common amplifier to each sub-array. Alternatively, as shown in Fig. 4, a parametric signal may be transmitted to a unit 17 which divides the signal into 8 different channels, each of which is transmitted to a respective individual variable amplifier G1,..G8, and then to a respective one of the sub-arrays. The unit 17 controls the gains of the variable amplifiers G1,..G8. The gain of each amplifier G1,..G8 may be selected to be the same. Alternatively, it may be selected to be different for each amplifier G1,..G8 (the gains may be limited to real values, or optionally the amplifiers G1,..G8 may be capable of providing a complex gain value). Adjustment of the gain value of each of the amplifiers G1,..G8 may, for example, be performed according to techniques known in the field of parametric speakers, to result in the sound beam being steered from one angle to another one.

Experimental SPL results for a system resembling the second embodiment of Fig. 3 (in the case that all gains $G_1, \dots, G_8$ are equal) are shown in Fig. 5. However, whereas in the embodiment of Fig. 3 there are eight sub-arrays substantially equally spaced out in a ring around the screen, and each of the

5 sub-arrays consists of a single central transducer surrounded by six transducer elements in a ring, in the version used to generate the data of Fig. 5 there were six sub-arrays substantially equally spaced out in a ring around the screen, and each of the sub-arrays is composed of 4 concentric rings of transducer elements. Specifically, there was a first ring (i.e. ring of lowest

10 radius) including 5 elements, a second ring of 11 elements, a third ring of 17 elements, and a fourth ring of 24 elements.

These results were obtained, as indicated schematically in Fig. 6 by moving a measurement microphone moving along a line 19 in a plane parallel to the

15 audio-vision reproduction apparatus and spaced from it by 1.5m. The position shown in Fig. 5 as "0cm" corresponds to the microphone being positioned directly forward (in the propagation direction of the sound) from the centre of the screen.

20 As shown in Fig. 5, the ultrasonic SPL at the central position is smaller than that at other positions (especially the positions at about +20cm and -20cm). However, the demodulated SPL is not weaker accordingly. In other words, such an arrangement achieves improved conversion efficiency from ultrasonic energy into the audio-frequency energy near the centre of the sound beam. In

25 the main sound beam, the demodulated SPL tends to be uniform.

Note that in some embodiments it may be worth increasing the width of the empty portion of the array. This will have the effect of broadening the region within which the peak of the demodulated audio signal has a high SPL, and

30 thereby produce a highly-directional sound beam covering more listeners.

FIG. 7 shows one application of an audio-visual reproduction apparatus 1 which is an embodiment of the invention. An audio-visual reproduction apparatus 1 is provided on the rear of each seat 21 in a vehicle 2, which may be a car or bus, or even an airplane. An individual in the vehicle may watch a TV program or listen to music generated only by the apparatus to his or her front. As a result, he or she may select TV or radio programs according to what he or she wants, and his or her neighbours in the vehicle are not disturbed since the sound is transmitted to the individual as a directed beam. In contrast to conventional ways of restricting generated sound to a single individual (e.g. earphones or headphones), in this application the user does not have to wear any potentially uncomfortable device. Moreover, unlike the use of earphones or headphones, there may be collocation in the application of Fig. 7 between the visual information on the screen and the corresponding audio sound. In other words, the user feels as if the sound is being generated from the display screen.

While in Fig. 7 each audio-visual reproduction apparatus 1 is shown positioned on the rear of a respective seat, the invention is not limited in this respect. For example an audio-visual reproduction apparatus 1 may be positioned proximate the driver of the vehicle, e.g. serving as a personal navigation system in which the screen of the apparatus 1 is used to display direction information (e.g. a map) and the sound generation system is used to generate direction instructions.

In another possibility, role of the display screen of the apparatus 1 may be played by a mirror of the vehicle (rather than being an image generated based on electronic signals). In this case, the parametric speaker may be formed (and optionally integrated with) the mirror in the automobile, and may face the driver so that an audible sound may be heard by the driver only.

FIG. 8 is a schematic exploded view of a further embodiment of the invention which is a display unit of a laptop or desktop computer 3. The display unit of the computer 3 comprises a visual display screen 31, and in front of it a
5 rectangular transparent panel 33 forming a protective cover. The transparent protective cover 33 may be resiliently mounted onto the display unit along the periphery of the cover 33 by means of a resilient suspension 32, e.g., of foam rubber. The resilient suspensions functions to connect the protective cover 33 onto the display unit of the computer, and further isolates the display unit from
10 any unwanted vibration. The ultrasonic transducer elements 34 of the embodiment are mounted on the surrounding periphery of the protective cover, and together define a two-dimensional transducer array including a central empty portion through which the display screen 31 is visible.

15 The embodiment of Fig. 8 may function as a personal multimedia system. In this case, directional sound is emitted towards a user by inputting a parametric signal to the transducer array. The user might feel as if the sound is being generated from the display screen 31 when he or she is watching it since the audio and visual messages are integrated together. Note that this is
20 in contrast to conventional computers in which the audio devices are arranged beside the computer display.

In a variant of the embodiment of Fig. 8, shown in Fig. 9, the transducer array comprises two sub-arrays 35 on the surrounding periphery of protective cover
25 33. The audio source signals from two channels may be pre-processed and modulated to form parametric signals, and then amplified as respective inputs of the two ultrasonic transducer sub-arrays 35. A stereo audio effect may be achieved by this configuration. One sub-array may function as a left-channel ultrasonic speaker, and the other as a right-channel ultrasonic speaker.

Various transducer elements or arrays may be adopted for use as the ultrasonic transducer elements of embodiments of the present invention.

One possibility is for the transducer array to be formed of commercially-
5 available PZT ultrasonic transmitters comprising a piezoelectric unimorph/bimorph element and a cone-shaped impedance layer. The parametric speaker device in the present invention may be made up of these independent ultrasonic elements, particularly if they are connected in parallel electrically.

10

Alternatively, membrane-type elements may be adopted as the transducer elements. A suitable membrane-type transducer is described in Singapore patent application No. 200300490-0 (the disclosure of which is incorporated herein by reference). Fig. 10(a) shows another suitable monolithic transducer
15 array 4 comprising membrane-type elements. The membrane in the transducer 4 comprises at least two layers: a backing layer 42 selected from a wide range of materials such as metal, plastics and silicon; and an active layer 41 which is a functional material such as a piezoelectric ceramic material. Under the membrane are back cavities 43. Vibration of the
20 monolithic piezoelectric membrane at its resonant point will result in emission of an ultrasonic wave into the air.

Fig. 10(b) shows an alternative suitable transducer array 5 comprising a capacitive membrane. The capacitive ultrasonic transducer array has a
25 general structure resembling Fig. 10(a) in which a membrane 51 is stretched across a frame having multiple back-cavities, but in contrast to the transducer of Fig. 10(a) the transducer of Fig. 10(b) comprises two parallel plates. The membrane 51 in the FIG. 10(b) may function as a positive capacitive plate when it is conductive. Alternatively a conductive layer may be deposited onto
30 the membrane 51 when it is non-conductive. Opposite the membrane 51 is a

ground plate 52. It is preferable to adopt a small clearance between the two plates.

A separate membrane-type transducer (e.g. as in Figs. 10(a) and 10(b)) may
5 be employed as each of the transducer elements 13 of Fig. 1. Alternatively, a
single membrane may extend between multiple transducer elements 13
having a geometry which means that different regions of the membrane
constitute independent membrane elements. Similarly, a separate membrane-
type transducer may be employed for each respective transducer of each sub-
10 array 15 of Fig. 3, or alternatively separate membranes may extend across all
the transducers of each respective sub-array.

While in some embodiments of the invention the ultrasonic transducer
elements are separate from the protective cover of the screen, the
15 membrane-type ultrasonic transducer arrays of Figs. 10(a) and 10(b) may be
integrated with a protective cover of the embodiment. The protective cover
may serve as a substrate which can be patterned to form for example the
back-cavities of the transducer. After that, functional materials such as sheets
of ceramic-based piezoelectric materials (e.g. PZT, lead zirconate titanate)
20 and/or polymer-based piezoelectric materials (e.g. PVDF, polyvinylidene
fluoride) may be bonded onto the substrate to form an ultrasonic transducer
array in the periphery of the protective cover.

Such a tiny and thin parametric speaker might also be integrated with a
25 portable consumer electronic device to form a personal audio-visual
apparatus, capable of (i) making the user feel as if the sound is being
generated from the display screen when he or she is watching it, and (ii)
projecting the sound towards a target user and seldom (or never) disturbing
unrelated persons.

For example, Fig. 11 shows an embodiment of the invention which is a mobile radio telephone or cell phone 6 comprising a casing 61 containing, in conventional fashion, a transparent protective layer 62 mounted on the casing through which visual information generated on a screen behind the layer can be observed. A parametric speaker 63 (e.g. of a membrane type as described above in relation to Fig. 10) may be incorporated (e.g. hidden) in the protective layer 62. Various patterns, such as a shallow-hole array, may be fabricated in the protective layer 62 directly, and a sheet of functional material is then bonded onto the patterned substrate to form an ultrasonic transducer array which functions as a parametric speaker when an amplified parametric signal is input to the array.

Alternatively, the parametric speaker may be formed by mounting independent ultrasonic transducer elements or sub-arrays 67 on a mobile telephone adjacent to each other at the edges of a display screen 66, as shown in Fig. 12. The telephone may include a small camera 64 and buttons 65 to operate the telephone. The telephone may be arranged to be foldable. In this case, the personal audio-vision reproduction apparatus may be hidden in the main module when it is not in a working state.

Fig. 13(a) and (b) show plan views of a further embodiment of the invention in two respective configurations. The embodiment is a mobile telephone (or other item of consumer electronics) including a body 70 having a screen 71. The body 70 is provided with two "pop-up" flaps 72, 73, proximate, and on respective sides of, the screen 71. Fig. 13(a) shows a first configuration of the telephone in which the flaps 72, 73 are in a "popped-up" configuration in which their surfaces jut out from the body 70 to either side of the screen 72. The respective front surfaces of the flaps 72, 73 may be substantially parallel to and flush with the front surface of the phone (i.e. the surface containing the screen 71 and the keys). Fig. 13(b) shows a second, more compact,

configuration of the telephone in which the flaps 72, 73 do not jut out from the body 70. In the configuration of Fig. 13(b) the flaps 72, 73 are received in slots on the respective sides of the body 70. In alternative embodiments, they may fold back to the sides of the body 70. The telephone body 70 carries a first set
5 of transducer elements 74,75 arranged in respective rows of transducer elements above and below the screen 71. The flaps 72, 73 carry respective further rows of transducer elements 76, 77.

Optionally, when the flaps are in the "popped-up" configuration of Fig. 13(a),
10 the angle which the flaps 71, 72 make with the front surface of the telephone may be adjustable. For example, neither the common plane of the elements 76, nor the common plane of the elements 77, needs to be parallel to that of the elements 74, 75. Rather, the angles which the flaps 72, 73 make with the body 70 may be selected to optimize sound response. Optionally, the
15 telephone may be arranged so that flaps 72, 73 bend symmetrically about the long axis of the body 70, i.e. to preserve a mirror plane of symmetry which is perpendicular to, and which bisects, the front face of the mobile phone.

Figs. 14(a) and (b) are plan views of a further embodiment of the invention.
20 Elements corresponding to those of Fig. 13 are given reference numerals 10 higher. As in the embodiment of Fig. 13, the flaps 82, 83 move between a pop-out configuration (Fig. 14(a)) and a compact configuration (Fig. 14(b)). In contrast to the embodiment of Fig. 13, the flaps 82, 83 are shorter, so that they do not extend along the body 80 of the mobile telephone as far as the
25 rows of transducer elements 84, 85.

Figs. 15(a) and (b) are plan views of a further embodiment of the invention. Elements corresponding to those of Fig. 13 are given reference numerals 20 higher. As in the embodiment of Fig. 13, the flaps 92, 93 move between a
30 pop-out configuration (Fig. 15(a)) and a compact configuration (Fig. 15(b)). In

contrast to the embodiment of Fig. 13, in the embodiment of Fig. 15 there are no transducer elements provided on the body 90 itself.

Figs. 16(a) and (b) are plan views of a further embodiment of the invention.

- 5 The embodiment has a body 100. Unlike the embodiment of Fig. 13, there is only a single flap 102, which carries an array of transducers 106 and which is movable between a pop-out configuration (Fig. 16(a)) and a compact configuration (Fig. 16(b)).

- 10 Figs. 17(a) and (b) are plan views of a further embodiment of the invention. Elements corresponding to those of Fig. 16 are given reference numerals 10 higher. As in the embodiment of Fig. 16, there is only a single flap 112, but it is provided at the opposite end of the body 110, near the screen 111.

- 15 Several exemplary embodiments of the invention have been described above, but, as will be clear to a skilled reader, many variations are possible within the scope of the invention without departing from the inventive concepts disclosed herein

Claims

1. An audio-visual reproduction apparatus comprising:

a visual display screen, and

an array of ultrasonic transducer elements for generating an ultrasonic
5 beam, the array of transducer elements comprising two or more said
transducer elements located around the periphery of the display screen.
2. An apparatus according to claim 1 in which the transducer elements
are arranged as two or more sub-arrays of closely adjacent transducer
elements.
- 10 3. An apparatus according to claim 2 comprising a respective amplifier for
each of the sub-arrays of transducer elements, and a controller for
independently controlling the respective gains of the amplifiers.
4. An apparatus according to claim 2 or claim 3 in which there are two
15 sub-arrays, the two sub-arrays being arranged to receive control signals
derived respectively from left and right stereo channels.
5. An apparatus according to any preceding claim further comprising a
casing for the display screen, the transducer elements being integrated in the
20 casing of the display screen.
6. An apparatus according to any preceding claim comprising a body and
one or more other sections which are movable relative to the body, some or
all of the transducer elements being provided on the movable section(s) of the
25 apparatus.

7. An apparatus according to claim 6 in which the movable sections are foldable relative to the body.

8. An apparatus according to claim 6 or claim 7 in which the movable
5 sections are receivable into one or more openings in the body.

9. An apparatus according to any of claims 6 to 8 in which there are a plurality of said movable sections arranged symmetrically to either side of the body.

10

10. An apparatus according to any of claims 6 to 9 in which there is at least one said movable section arranged on a longitudinal axis of symmetry of the body.

11. An apparatus according to any preceding claim in which each said transducer element comprises a respective piezoelectric unimorph or
15 bimorph element and a cone-shaped impedance layer.

12. An apparatus according to any of claims 1 to 10 in which the transducer array comprises a membrane driven by piezoelectric material arranged to receive a parametric control signal.

20

13. An apparatus according to any of claims 1 to 10 in which the transducer array comprises a membrane driven by electrostatic forces between first conductive material located on the membrane and second conductive material located off the membrane, the first and second conductive
25 materials being arranged to have a voltage difference determined by a parametric control signal.

14. An apparatus according to any preceding claim which is a television receiver, the display screen of the apparatus being the screen of the television
30 receiver.

15. An apparatus according to any preceding claim which is located in a vehicle.
- 5 16. An apparatus according to claim 15 which is located on the rear of a seat of the vehicle.
17. An apparatus according to claim 15 in which the display screen is located for viewing by a driver of the vehicle.
- 10 18. An apparatus according to claim 17 which is a navigation system, the display screen being arranged to display navigation information and the transducer array being arranged to transmit audio navigation instructions.
- 15 19. An apparatus according to claim 17 in which the display screen is a guidance mirror of the vehicle.
20. An apparatus according to any of claims 1 to 13 or 11 to 19 which is the display unit of a computer.
- 20 21. An apparatus according to claim 20 in which the display unit comprises a transparent protective panel resiliently mounted extending across the front of the display screen, the ultrasonic transducer elements being located on the surrounding periphery of the protective panel.
- 25 22. An apparatus according to any of claims 1 to 13 which is a mobile radio telephone or a cell phone.
23. A portable item of consumer electronics having:
a body including a screen;

at least one section movable relative to the body and comprising one or more ultrasonic transducer elements for generating an ultrasonic beam.

24. An item according to claim 23 in which the or each movable section is
5 movable between a first configuration in which its ultrasonic transducer element(s) are arranged to generate an ultrasonic beam propagating towards a user viewing the screen, and a second more compact configuration.

25. An item according to claim 23 or claim 24 in which the angle of the or
10 each movable section is adjustable within a range of positions in which its ultrasonic transducer element(s) generate an ultrasonic beam propagating towards a user viewing the screen.

26. An item according to any of claims 23 to 25 in which there are a
15 plurality of movable sections, including a plurality of movable sections arranged on respective sides of a longitudinal axis of the body.

27. An item according to any of claims 23 to 26 in which there are a
20 plurality of movable sections, including a plurality of movable sections arranged on respective sides of the screen.

28. An item according to any of claims 23 to 27 in which the movable
sections include at least one section is arranged on a longitudinal axis of the
body.
25

29. An item according to any of claims 23 to 28 which is a mobile
telephone.